

BI / read / 15

BI 1
BI 2
BI 3
BI 4
BI 5
BI 6
BI 7
BI 8
BI 9
BI 10
BI 11
BI 12
BI 13
BI 14
BI 15
BI 16
BI 17
BI 18
BI 19
BI 20
BI 21
BI 22
BI 23
BI 24
BI 25

query	BI / read / 15			
title	Social normals			
pattern	<pre>graph TD Country[Country name = \$country] City1[City] City2[City] City3[City] person1[person1: Person] friend1[friend1: Person] person2[person2: Person id] friend2[friend2: Person] Country -- isPartOf --> City1 Country -- isPartOf --> City2 Country -- isPartOf --> City3 City1 -- isLocatedIn --> person1 City2 -- isLocatedIn --> friend1 City3 -- isLocatedIn --> person2 City3 -- isLocatedIn --> friend2 person1 -- knows --> friend1 person2 -- knows --> friend2 subgraph Calculation direction TB C1[person1: Person] -- count --> C1C[count] C2[friend1: Person] -- count --> C2C[count] C1C -- avg --> C3[floor] C2C -- avg --> C3 C3 -- floor --> SN[socialNormal = floor(avg(count))]</pre>			
desc.	<p>Given a Country <code>country</code>, determine the “social normal”, i.e. the floor of average number of friends that Persons of country have in <code>country</code>.</p> <p>Then, find all Persons in <code>country</code>, whose number of friends in <code>country</code> equals the social normal value.</p>			
params	1	country	String	
result	1	person.id	64-bit Integer	R
	2	count	32-bit Integer	A
sort	1	person.id	↑	
limit	100			
CPs	1.2, 2.3, 3.2, 3.3, 5.3, 6.1, 8.2, 8.4			