BI / read / 21

BI 1	au orv	BI / read / 21
BI 2	query title	
BI 3	uue	Zombies in a country
BI 4 BI 5 BI 6 BI 7 BI 8 BI 9 BI 10 BI 11 BI 12 BI 13 BI 14 BI 15 BI 16 BI 17 BI 18 BI 19 BI 20 BI 21 BI 22 BI 23 BI 24 BI 25	pattern	Country name = \$country
	desc.	Find zombies within the given country, and return their zombie scores. A zombie is a Person created before the given endDate, which has created an average of [0, 1) Messages per month, during the time range between profile's creationDate and the given endDate. The number of months spans the time range from the creationDate of the profile to the endDate with partial months on both end counting as one month (e.g. a creationDate of Jan 31 and an endDate of Mar 1 result in 3 months). For each zombie, calculate the following: • zombieLikeCount: the number of likes received from other zombies. • totalLikeCount: the total number of likes received. • zombieScore: zombieLikeCount / totalLikeCount. If the value of totalLikeCount is 0, the zombieScore of the zombie should be 0.0. For both zombieLikeCount and totalLikeCount, only consider likes received from profiles that were created before the given endDate.
	params	1 country String 2 endDate Date
	result	1 zombie.id 64-bit Integer R 2 zombieLikeCount 32-bit Integer A 3 totalLikeCount 32-bit Integer A 4 zombieScore 64-bit Float A zombieLikeCount / totalLikeCount
	sort	1 zombieScore ↓ 2 zombie.id ↑
	limit	100
	CPs	1.2, 2.1, 2.3, 2.4, 3.2, 3.3, 5.1, 5.3, 8.2, 8.4, 8.5
l		, , , , , , , , , , , , , , , , , , , ,