

AI-Assisted Bézier Curve Designer

A Web-Based Geometric Modeling Application

OUSMANE DAOU

MSc Computer Science
Geometric Modeling Course
University of Debrecen, Faculty of Informatics
Supervisor: Kunkli Roland Imre

November 9, 2025

Table of Contents

- 1 Introduction
- 2 Mathematical Foundations
- 3 Curve Fitting Algorithm
- 4 Implementation
- 5 Features
- 6 AI Integration
- 7 Results
- 8 Conclusion

What is it?

A comprehensive web-based application for interactive Bézier curve design with AI-assisted curve fitting capabilities.

Key Features:

- Real-time curve rendering
- AI-powered curve fitting
- Interactive control points
- Snap-to-grid
- Measurements display

Technologies:

- React + TypeScript
- WebGL (Three.js)
- Python + FastAPI
- TensorFlow

Problem:

- Creating precise Bézier curves requires expertise
- Manual control point manipulation is time-consuming
- Freehand drawings lack mathematical precision

Solution:

- Automatic curve fitting from freehand drawings
- AI-assisted optimization
- Intuitive interactive interface
- Real-time visual feedback


Bézier Curves: Definition

Definition

A cubic Bézier curve $\mathbf{B}(t)$ with control points $\mathbf{P}_0, \mathbf{P}_1, \mathbf{P}_2, \mathbf{P}_3$:

$$\mathbf{B}(t) = (1 - t)^3 \mathbf{P}_0 + 3(1 - t)^2 t \mathbf{P}_1 + 3(1 - t) t^2 \mathbf{P}_2 + t^3 \mathbf{P}_3$$

where $t \in [0, 1]$



Theorem (Properties of Bézier Curves)

① Endpoint Interpolation:

$$\mathbf{B}(0) = \mathbf{P}_0, \quad \mathbf{B}(1) = \mathbf{P}_3$$

② Tangency at Endpoints:

$$\mathbf{B}'(0) = 3(\mathbf{P}_1 - \mathbf{P}_0), \quad \mathbf{B}'(1) = 3(\mathbf{P}_3 - \mathbf{P}_2)$$

③ Convex Hull Property: *Curve lies within convex hull of control points*

④ Affine Invariance: *Transformations apply to control points*

Bernstein Basis Polynomials

Bézier curves use Bernstein polynomials as basis functions:

$$B_i^n(t) = \binom{n}{i} t^i (1-t)^{n-i}$$

For cubic Bézier curves ($n = 3$):

$$B_0^3(t) = (1-t)^3$$

$$B_1^3(t) = 3t(1-t)^2$$

$$B_2^3(t) = 3t^2(1-t)$$

$$B_3^3(t) = t^3$$

Properties:

- $\sum_{i=0}^n B_i^n(t) = 1$ (Partition of unity)
- $B_i^n(t) \geq 0$ for $t \in [0, 1]$ (Non-negativity)

Curve Fitting Problem

Given: Set of data points $\{\mathbf{Q}_j\}_{j=0}^m$ from freehand drawing

Find: Control points $\mathbf{P}_0, \mathbf{P}_1, \mathbf{P}_2, \mathbf{P}_3$ that minimize:

$$E = \sum_{j=0}^m \|\mathbf{B}(t_j) - \mathbf{Q}_j\|^2$$

Challenges:

- Parameterization: assign t_j to each point
- Endpoint selection
- Multi-segment fitting for complex shapes

Chord Length Parameterization:

$$t_j = t_{j-1} + \frac{\|\mathbf{Q}_j - \mathbf{Q}_{j-1}\|}{\sum_{k=1}^m \|\mathbf{Q}_k - \mathbf{Q}_{k-1}\|}$$

Centripetal Parameterization:

$$t_j = t_{j-1} + \frac{\|\mathbf{Q}_j - \mathbf{Q}_{j-1}\|^{1/2}}{\sum_{k=1}^m \|\mathbf{Q}_k - \mathbf{Q}_{k-1}\|^{1/2}}$$

Why Different Methods?

Centripetal parameterization often produces better results for curves with varying curvature.

Least Squares Optimization

Fix endpoints: $\mathbf{P}_0 = \mathbf{Q}_0$, $\mathbf{P}_3 = \mathbf{Q}_m$

Solve for $\mathbf{P}_1, \mathbf{P}_2$ using normal equations:

$$\begin{bmatrix} \sum B_1^3(t_j)^2 & \sum B_1^3(t_j)B_2^3(t_j) \\ \sum B_1^3(t_j)B_2^3(t_j) & \sum B_2^3(t_j)^2 \end{bmatrix} \begin{bmatrix} \mathbf{P}_1 \\ \mathbf{P}_2 \end{bmatrix} = \begin{bmatrix} \mathbf{R}_1 \\ \mathbf{R}_2 \end{bmatrix}$$


Result: Optimal control points that minimize squared error

Complexity: $O(m)$ for m data points

Algorithm 1 Adaptive Bézier Curve Fitting

- 1: **Input:** Points $\{\mathbf{Q}_j\}$, error threshold ϵ
 - 2: Compute chord length parameterization
 - 3: Set endpoints: $\mathbf{P}_0 = \mathbf{Q}_0$, $\mathbf{P}_3 = \mathbf{Q}_m$
 - 4: Estimate tangents from neighboring points
 - 5: Solve least squares for $\mathbf{P}_1, \mathbf{P}_2$
 - 6: Compute max fitting error $e_{\max}$
 - 7: **if** $e_{\max} > \epsilon$ **and** sufficient points **then**
 - 8: Find split point at maximum error
 - 9: Recursively fit left and right segments
 - 10: **else**
 - 11: Return single Bézier curve
 - 12: **end if**
-

System Architecture



Communication:

- **POST /api/fit-curve:** Curve fitting
- **POST /api/ai-suggest:** AI recommendations

WebGL Rendering Pipeline

- ➊ **Curve Sampling:** Convert Bézier to line segments (sample at n points where n is proportional to arc length)
- ➋ **Buffer Creation:** Store vertices in GPU memory
- ➌ **Geometry Setup:** BufferGeometry with position attributes
- ➍ **Material Application:** LineBasicMaterial with color/width
- ➎ **Scene Update:** Render at 60 FPS in animation loop

Performance: Hardware-accelerated rendering supports 500+ curves at 60 FPS

Key Implementation: Bézier Evaluation

```
function evaluateBezier(  
  curve: CubicBezier,  
  t: number  
): Point2D {  
  const mt = 1 - t;  
  const mt2 = mt * mt;  
  const mt3 = mt2 * mt;  
  const t2 = t * t;  
  const t3 = t2 * t;  
  
  return {  
    x: mt3 * curve.p0.x +  
      3 * mt2 * t * curve.p1.x +  
      3 * mt * t2 * curve.p2.x +  
      t3 * curve.p3.x,  
    y: mt3 * curve.p0.y +  
      3 * mt2 * t * curve.p1.y +  
      3 * mt * t2 * curve.p2.y +  
      t3 * curve.p3.y
```

Drawing Tools:

- Freehand drawing mode
- Select mode (V key)
- Control point editing
- Snap to grid (M key)
- Grid display toggle

Editing:

- Undo/Redo (Ctrl+Z/Y)
- Duplicate (Ctrl+D)
- Delete strokes
- Clear canvas

Measurements:

- Curve arc length
- Control point distances
- Toggle display (R key)

Visualization:

- Control points/polygon
- Color customization
- Line width adjustment
- Dark/Light theme

Snap to Grid

Quantizes coordinates to grid alignment:

$$\text{snap}(\mathbf{P}) = \left\lfloor \frac{\mathbf{P}}{g} + 0.5 \right\rfloor \cdot g$$

where $g = 50$ pixels (grid size)

Benefits:

- Precise technical drawings
- Aligned geometric shapes
- Easier control point manipulation

Implementation:

- Applied to drawing points
- Applied to control point dragging
- Toggle on/off with M key

Measurements Display

Arc Length Calculation:

$$L = \int_0^1 \|\mathbf{B}'(t)\| dt \approx \sum_{k=1}^n \|\mathbf{B}'(t_k)\| \Delta t$$

Using 50 sample points for accurate approximation

Distance Between Points:

$$d(\mathbf{P}_i, \mathbf{P}_j) = \sqrt{(x_j - x_i)^2 + (y_j - y_i)^2}$$

Display:

- Total curve length (bottom-left corner)
- Control point distances (on control polygon)
- Updates in real-time during editing

Selection Algorithm

Goal: Select curve by clicking near it

Method: Point-to-curve distance test

- 1 Sample $n = 20$ points on each Bézier curve
- 2 For each sample point $\mathbf{B}(i/n)$:

if $\|\mathbf{C} - \mathbf{B}(i/n)\| < \delta$ then select curve

- 3 Use threshold $\delta = 15$ pixels

Why This Works:

- 20 samples provide good coverage
- Threshold allows comfortable clicking
- Fast computation: $O(n \cdot k)$ for k curves

Neural Network Components:

- **Input:** Point sequence $\{\mathbf{Q}_j\}_{j=0}^m$
- **Encoder:** 1D Conv + LSTM + Attention
- **Latent Space:** 128-dimensional embedding
- **Decoder:** Predict optimal control points

Loss Function:

$$\mathcal{L} = \mathcal{L}_{\text{fitting}} + \lambda_1 \mathcal{L}_{\text{smoothness}} + \lambda_2 \mathcal{L}_{\text{simplicity}}$$

where:

$$\mathcal{L}_{\text{fitting}} = \sum_j \|\mathbf{B}(t_j) - \mathbf{Q}_j\|^2$$

$$\mathcal{L}_{\text{smoothness}} = \int_0^1 \|\mathbf{B}''(t)\|^2 dt$$

$$\mathcal{L}_{\text{simplicity}} = N_{\text{curves}}$$

AI Training Process

Dataset:

- 10,000+ hand-drawn curves
- Various shapes: lines, circles, spirals, letters
- Ground truth: expert-designed Bézier approximations

Training:

- Optimizer: Adam with learning rate 10^{-3}
- Batch size: 32
- Epochs: 100
- Validation split: 20%

Results:

- Average fitting error: 1.8 pixels
- 15% fewer curves than traditional method
- Smoother results preferred by users

Performance Metrics

Metric	Value
Frame Rate (idle)	60 FPS
Frame Rate (active drawing)	55-60 FPS
Curve Fitting (100 points)	15-25 ms
Selection Response	≤ 5 ms
Max Strokes @ 60 FPS	≤ 500
Memory Usage	50 MB

Browser Compatibility:

- Chrome, Firefox, Safari, Edge
- Requires WebGL 2.0 support

Fitting Accuracy

Root Mean Square Error (RMSE):

$$\text{RMSE} = \sqrt{\frac{1}{m+1} \sum_{j=0}^m \|\mathbf{B}(t_j) - \mathbf{Q}_j\|^2}$$

Typical Results:

- Smooth curves: 0.5-2.0 pixels
- Complex shapes: 2.0-5.0 pixels
- Sharp corners: 3.0-8.0 pixels

Comparison:

- Traditional method: 2.5 pixels average
- AI-assisted: 1.8 pixels average
- **28% improvement!**

Participants: 10 users (5 with CAD experience, 5 beginners)

Results:

- **90%** found interface intuitive
- **5 minutes** average learning time
- **85%** preferred AI fitting over manual adjustment
- **95%** found snap-to-grid useful
- **80%** used keyboard shortcuts after learning

Feedback:

- + Fast and responsive
- + Intuitive interactions
- + AI suggestions very helpful
- Need more export formats
- Want collaboration features

Key Achievements

- ① **Mathematical Rigor:** Proper implementation of Bézier curve theory
- ② **Efficient Algorithms:** Fast curve fitting with adaptive segmentation
- ③ **High Performance:** Real-time rendering at 60 FPS
- ④ **AI Integration:** Machine learning improves fitting quality
- ⑤ **User Experience:** Intuitive interface with modern interactions
- ⑥ **Comprehensive Features:** Drawing, editing, measurements, export

Advanced Geometry:

- C^1 and C^2 continuity between segments
- Rational Bézier curves (NURBS)
- 3D curve support
- Bézier surface patches

AI Enhancements:

- Shape recognition (circles, rectangles, etc.)
- Style transfer for artistic curves
- Predictive drawing assistance
- Automatic symmetry detection

Collaboration:

- Real-time multi-user editing
- Cloud storage and sync
- Version control

Conclusion

Summary

Successfully developed a comprehensive web-based Bézier curve design application that combines:

- Classical geometric modeling theory
- Modern web technologies
- Artificial intelligence

Impact

- Makes precise curve design accessible to non-experts
- Demonstrates AI's potential in geometric modeling
- Provides foundation for future research

Thank You!

References

-  Farin, G. (2002). *Curves and Surfaces for CAGD*. Morgan Kaufmann.
-  Piegl, L., & Tiller, W. (1997). *The NURBS Book*. Springer.
-  Schneider, P. J. (1990). An Algorithm for Automatically Fitting Digitized Curves. *Graphics Gems*.
-  Hoschek, J., & Lasser, D. (1993). *Fundamentals of Computer Aided Geometric Design*. CRC Press.