
SPECIFICATION OF THE STOKR SMART CONTRACTS

SICOS

CONTENTS

1	Abstract	6
2	Ownable Contracts	7
2.1	Purpose	7
2.2	Functionality	7
2.2.1	Ownership Transfer	7
3	Whitelist Contract	8
3.1	Purpose	8
3.2	Roles	8
3.2.1	Whitelist Owner	8
3.2.2	Whitelist Admins	8
3.2.3	Whitelisted Investors	9
3.3	Functionality	9
3.3.1	Ownership	9
3.3.2	Admin Management	9
3.3.3	Investor Management	10
4	Crowdsale Contract	11
4.1	Purpose	11
4.2	Roles	11
4.2.1	Crowdsale Owner	11
4.2.2	Investors	11
4.2.3	Rate Source	12
4.2.4	Token	12
4.2.5	Company Wallet	13
4.2.6	Reserve Account	13
4.3	Functionality	13
4.3.1	Ownership	13
4.3.2	Public vs. Private Sale	14
4.3.3	Purchase With Ether	15
4.3.4	Softcap / Sale Goal	16
4.3.5	Finalization	17
4.3.6	Refunding	17

4.4	Lifecycle	18
4.4.1	Before Start of Public Sale Phase	18
4.4.2	Public Sale Phase	18
4.4.3	Between End of Public Sale Phase and Finalization	19
4.4.4	After Finalization	19
5	Token Contract	20
5.1	Purpose	20
5.2	Roles	20
5.2.1	Token Owner	20
5.2.2	Token Minter	20
5.2.3	Whitelist	21
5.2.4	Profit Depositor	21
5.2.5	Profit Distributor	22
5.2.6	Key Recoverer	22
5.2.7	Token Holders	22
5.2.8	Third Party Trustees	23
5.3	Functionality	24
5.3.1	Ownership	24
5.3.2	Role Management	24
5.3.3	Whitelist Checks	25
5.3.4	Minting and Fixing Total Supply	25
5.3.5	Profit Sharing	26
5.3.6	Token Transfers	28
5.3.7	Key Recovery	29
5.3.8	Destruction	30
5.4	Lifecycle	30
5.4.1	Minting Phase	30
5.4.2	Trading Phase	30
6	Project Manager	31
6.1	Purpose	31
6.2	Roles	31
6.2.1	Project Manager Owner	31
6.2.2	Rate Admin	31
6.2.3	Whitelist	32

- 6.2.4 Token Factory 32
 - 6.2.5 Crowdsale Factory 33
- 6.3 Functionality 33
 - 6.3.1 Role Management 33
 - 6.3.2 Project Creation 34
 - 6.3.3 Rate Source 34

1 ABSTRACT

STOKR is as crowd-investing platform based on smart contracts on the [Ethereum](#) blockchain. On *STOKR* many projects will be deployed with the same smart contract structure (see [project manager](#)). There will be a shared [whitelist](#) for all projects on *STOKR*. Each project has its own [ERC20 Token](#) and its [Crowdsale](#) contract instance. The token contract is able to distribute profits generated by the projects to the token holders.

2 OWNABLE CONTRACTS

2.1 PURPOSE

All of the following contracts are ownable, that is they have an *owner* address—either another contract instance or an externally owned account—assigned which has special permissions on the contract. An owner is initially (i.e. upon deployment) the contract deployer, but may [transfer the ownership](#) to another address.

2.2 FUNCTIONALITY

This functionality is shared by all following contracts.

2.2.1 OWNERSHIP TRANSFER

Transfer the contract instance's ownership to a new address.

Function

```
transferOwnerShip(address)
```

Restrictions

only by current owner

Emitted events

```
OwnershipTransferred(address, address)
```

3 WHITELIST CONTRACT

3.1 PURPOSE

Provide a central list of investors' [Ethereum](#) addresses, who are allowed to buy or sell tokens.

3.2 ROLES

3.2.1 WHITELIST OWNER

Initially

the [Whitelist](#) contract deployer

Number

one at a time

Assignment

- by deploying the contract
- by gaining ownership from previous owner

Permissions

- [transfer ownership](#) to another account
- [assign/unassign whitelist admins](#)

3.2.2 WHITELIST ADMINS

Authority which manages the whitelist.

Initially

none

Number

zero or more

Assignment

by getting [added](#) or [removed](#) by the [whitelist owner](#)

Permissions

add or remove [investors](#) to/from the [whitelist](#)

3.2.3 WHITELISTED INVESTORS

Addresses of investors, who have completed and passed the KYC process.

Initially

none

Number

zero or more

Assignment

by getting added or removed from the whitelist by a whitelist admin

Permissions

none

3.3 FUNCTIONALITY

3.3.1 OWNERSHIP

see Ownable

3.3.2 ADMIN MANAGEMENT

ADDING ADMINS

A single whitelist admin can be added.

Function

`addAdmin(address)`

Restrictions

only by `whitelist owner`

Emitted events

`AdminAdded(address)`

REMOVING ADMINS

A single whitelist admin can be removed.

Function

`removeAdmin(address)`

Restrictions

only by `whitelist owner`

Emitted events

AdminRemoved(address)

3.3.3 INVESTOR MANAGEMENT

WHITELISTING INVESTORS

Several investors at once can be added to the whitelist.

Function

addToWhitelist(address[])

Restrictions

only by a [whitelist admin](#)

Emitted events

InvestorAdded(address, address)

UNWHITELISTING INVESTORS

Several investors at once can be removed from the whitelist.

Function

removeFromWhitelist(address[])

Restrictions

only by a [whitelist admin](#)

Emitted events

InvestorRemoved(address, address)

4 CROWDSALE CONTRACT

4.1 PURPOSE

Enable token purchase by investors and check if the sale has to be considered a success or a failure. Refund investors upon sale failure.

4.2 ROLES

4.2.1 CROWDSALE OWNER

Authority who administers the crowdsale.

Initially

the [Crowdsale](#) contract deployer

Number

one at a time

Assignment

- by deploying the contract
- by gaining ownership from previous owner

Permissions

- [transfer ownership](#) to another account
- distribute tokens to [investors](#) who paid in fiat currency (e.g. EUR) off-chain
- [finalize](#) the sale, but only
 1. once
 2. after the [public sale](#) has [closed](#)
- [distribute refunds](#) to [investors](#) who [paid in Ether](#), but only
 1. after [finalization](#)
 2. if the [sale goal](#) was missed

4.2.2 INVESTORS

Addresses who purchase tokens either via public or private sale.

Initially

all accounts that are whitelisted in the corresponding [whitelist](#)

Number

zero or more

Assignment

by being added or removed to/from the corresponding [whitelist](#)

Permissions

- [purchase tokens](#) with Ether in public sale, but only
 1. while the sale is [open](#)
 2. if there are enough tokens available for [public sale](#)
 3. if the amount of newly purchased tokens is at least a [predefined minimum](#)
- [claim refunds](#), thus withdraw invested Ether, but only
 1. after [finalization](#)
 2. if the [sale goal](#) was missed

4.2.3 RATE SOURCE

External contract which delivers the actual price of an Ether in Euro cents.

Initially

given to constructor

Number

one

Assignment

only once upon contract deployment

Permissions

none

4.2.4 TOKEN

Reference to the [token](#) instance which is sold by this crowdsale.

Initially

given to constructor

Number

one

Assignment

only once upon contract deployment

Permissions

none

4.2.5 COMPANY WALLET

Address which will receive all Ether that were paid by [investors](#) to [buy tokens](#) during [public sale](#) if the [goal](#) was reached. This is meant to be a multisig wallet.

Initially

given to constructor

Number

one

Assignment

only once upon contract deployment

Permissions

none

4.2.6 RESERVE ACCOUNT

Address which will receive some additional amount of tokens (depending on the total amount of sold tokens) upon [finalization](#) of a [successful sale](#). This is meant to be some vesting contract address.

Initially

given to constructor

Number

one

Assignment

only once upon contract deployment

Permissions

none

4.3 FUNCTIONALITY

4.3.1 OWNERSHIPsee [Ownable](#)

4.3.2 PUBLIC VS. PRIVATE SALE

The crowdsale is divided into two distinct sales—a public and a private sale—each being limited by its own *cap*. The cap is the maximum total amount of tokens that can be bought in the respective sale.

Both caps are given to the constructor upon deployment (parameters `tokenCapOfPublicSale` and `tokenCapOfPrivateSale`) in token units (quantity of 10^{-18} tokens).

[Whitelisted investors](#) can purchase tokens in public or private sale off-chain by paying in fiat currency (e.g. Euro). To make those investors receive their tokens, the crowdsale instance's [owner](#) has to [distribute](#) them manually.

Additionally, as long as the public crowdsale is [open](#), investors can [purchase](#) tokens directly by sending Ether to the crowdsale instance.

TOKEN DISTRIBUTION

[Whitelisted investors](#) can purchase tokens in public or private sale off-chain by paying in fiat currency (e.g. Euro). To make these investors receive their tokens, the crowdsale instance's [owner](#) has to distribute them manually via one of the two token distribution methods.

Note From the crowdsale smart contract's point of view the only distinction between public or private sale is, which pool of available tokens the newly minted tokens will be taken from.

Token distribution via public sale:

Function

```
distributeTokensViaPublicSale(address[], uint[])
```

Restrictions

- only by [owner](#)
- only if crowdsale wasn't [finalized](#) yet
- only if sum of token amounts to distribute doesn't exceed the amount of remaining tokens for public sale

Emitted events

- `TokenDistribution(address, uint)`
- `Minted(address, uint)`
- `Transfer(0x0, address, uint)`

Token Distribution via private sale:

Function

`distributeTokensViaPrivateSale(address[], uint[])`

Restrictions

- only by `owner`
- only if crowdsale wasn't `finalized` yet
- only if sum of token amounts to distribute doesn't exceed the amount of remaining tokens for private sale

Emitted events

- `TokenDistribution(address, uint)`
- `Minted(address, uint)`
- `Transfer(0x0, address, uint)`

4.3.3 PURCHASE WITH ETHER

As long as the public crowdsale is `open`, investors can `purchase` tokens directly by sending Ether to the crowdsale instance.

PURCHASE MINIMUM

When paying with Ether, the amount of tokens bought within a transaction has to be at least some predefined lower limit which is given to constructor upon deployment (parameter `tokenPurchaseMinimum`) in token units (quantity of 10^{-18} tokens).

Companies may decide to not define a lower threshold by setting `tokenPurchaseMinimum` to zero.

TOKEN PRICE

The price of a token denominated in EUR-cents has to be given to the constructor upon deployment (parameter `tokenPrice`).

The token price does not depend on the current Ether price. Therefore an external contract—an instance of `RateSource`—is called upon every token purchase with Ether to get the current Ether rate and adjust accordingly.

The amount of bought tokens is calculated as follows:

Let be

- *value* the sent Ether [in wei, i.e. 10^{-18} Ether],
- *price* the token price [in €-cent per token],
- *rate* the current Ether rate [in €-cent per Ether],

- *amount* the purchased token amount [in token units, i.e. 10^{-18} tokens],

then

amount := *value* × *price* ÷ *rate*

Whitelisted investors may purchase tokens via the public sale by sending Ether to the crowdsale instance.

Functions

- payable buyTokens()
- payable fallback function

Restrictions

- only by whitelisted investors
- only while the public sale is open that is from opening time till closing time
- only if amount of bought tokens in a single transaction is at least a predefined minimum purchase amount
- only if amount of bought tokens doesn't exceed the amount of remaining tokens for public sale

Emitted events

- TokenPurchase(address, uint, uint)
- Minted(address, uint)
- Transfer(0x0, address, uint)

4.3.4 SOFTCAP / SALE GOAL

Upon crowdsale deployment a predefined softcap (parameter **tokenGoal**) can be given to the constructor, which determines a goal, i.e. the minimum amount of sold token in both—public and private—sales, that has to be reached for the crowdsale to become a success.

If the goal was reached, the sale is considered successful, otherwise it is considered a failure.

During sale period, as long as the goal wasn't reached, invested Ether are accumulated in the crowdsale contract. After the goal was reached, all invested Ether are transferred to the company wallet address

Companies may decide to not define a goal by setting **tokenGoal** to zero.

4.3.5 FINALIZATION

After the crowdsale has ended, it has to be finalized manually by the crowdsale [owner](#). Depending on whether the [sale goal](#) was reached, this will either * if the goal was reached: #. mint additional tokens, i.e. a predefined percentage of total amount of sold tokens, for the benefit of the [reserve account](#) #. [finish minting](#) of the token, thus fixing its total supply * if the goal was missed: #. destroy the [token](#) instance #. enable the [refunding](#) of investors who (paid by sending Ether directly)[#crowdsale-func-purchase] to the crowdsale instance.

Function

```
finalize()
```

Restrictions

- only by crowdsale [owner](#)
- only after the public sale has closed
- only once

Emitted events

Depending on the success of sale:

1. if goal was reached
 - `Minted(address, uint)`
 - `Transfer(0x0, address, uint)`
 - `Finalization()`
2. if goal was missed
 - `Finalization()`

4.3.6 REFUNDING

If the [sale goal](#) was not reached, the crowdsale is considered a failure and [investors](#) who [purchased](#) tokens by sending Ether directly to the crowdsale instance can claim a refund.

DISTRIBUTE REFUNDS

The [owner](#) may distribute the refunds to investors, so that the latter don't need to withdraw them by themselves.

Function

```
distributeRefunds(address[])
```

Restrictions

- only by the `owner`
- only if the crowdsale was `finalized`
- only if the `sale goal` was missed

Emitted events

`InvestorRefund(address, uint)`

CLAIMING REFUNDS

Investors may get their invested Ether back by claiming them by themselves.

Function

`claimRefund()`

Restrictions

- only if the crowdsale was `finalized`
- only if the `sale goal` was missed

Emitted events

`InvestorRefund(address, uint)`

4.4 LIFECYCLE

4.4.1 BEFORE START OF PUBLIC SALE PHASE

Start time

at deployment

End time

at `openingTime`

4.4.2 PUBLIC SALE PHASE

The public sale is open for `investors` who want to `buy token with Ether` from opening time till closing time given as Ethereum block timestamps (UNIX epoch) to constructor upon deployment (parameters `openingTime` and `closingTime`)

Start time

at `openingTime`

End time

at `closingTime`

4.4.3 BETWEEN END OF PUBLIC SALE PHASE AND FINALIZATION

After the public sale has closed, the crowdsale **owner** is expected to manually **finalize** the crowdsale. Before doing so, he/she must **distribute** tokens to **investors** who have purchased them off-chain.

Start time

at `closingTime`

End time

upon call of `finalize()`

4.4.4 AFTER FINALIZATION

After **finalization** no tokens can be minted anymore, i.e. the **total token supply** is **fixed**. Depending on whether the **sale was successful** or not, **token holder** either may trade their tokens and withdraw their profit shares, or **claim refunds**.

Start time

upon call of `finalize()`

End time

never

5 TOKEN CONTRACT

5.1 PURPOSE ---

The Token contract is an [ERC20](#) compliant profit sharing token.

5.2 ROLES ---

5.2.1 TOKEN OWNER

Role administering authority.

Initially

the [Token](#) contract deployer

Number

one at a time

Assignment

- by deploying the contract
- by gaining ownership from previous owner

Permissions

- [transfer ownership](#) to another account
- assign [minter](#), but only once
- assign [profit depositor](#)
- assign [profit distributor](#)
- assign [key recoverer](#)

5.2.2 TOKEN MINTER

Authority who is allowed to [mint](#) some amount of tokens for the benefit of whitelisted investors and to finish minting, thus fixing the token's total supply.

Initially

none

Number

zero or one

Assignment

only once by the [token owner](#)

Note, this is expected to be a [Crowdsale](#) instance

Permissions

- [mint tokens](#) for the benefit of some investor, but only
 1. while minting was not finished
 2. the investor is whitelisted
- finish minting, but only once
- destroy the token contract

5.2.3 WHITELIST

A [Whitelist](#) contract instance which restricts the addresses who are able to send or receive tokens.

Initially

given to constructor

Number

one at a time

Assignment

by the [token owner](#)

Permissions

none

5.2.4 PROFIT DEPOSITOR

Authority who is able to [deposit company profits](#) (in Ether) into the token contract instance.

Initially

given to constructor

Number

one at a time

Assignment

by the [token owner](#)

Permissions

deposit profits, i.e. store some Ether amount into the Token instance

5.2.5 PROFIT DISTRIBUTOR

Authority who is able to [distribute profit shares](#) (in Ether) to token holders on their behalf, thus the latter don't need to withdraw their profit shares by themselves.

Initially

none

Number

one at a time

Assignment

by the [Token owner](#)

Permissions

distribute profit shares to [token holders](#), i.e. transfer some fraction of the Ether amount deposited in the token to investors according to their amount of tokens they hold

5.2.6 KEY RECOVERER

Authority who may [assign a new address](#) to a token holder's account.

Initially

given to constructor

Number

one at a time

Assignment

by the [Token owner](#)

Permissions

transfer investor account data from one address to another, but only if the new (destination) address was not already assigned to an investor's account

5.2.7 TOKEN HOLDERS

Addresses who hold some amount of tokens, thus have an account within the token contract instance.

Initially

none

Number

zero or more

Assignment

by first being [whitelisted](#) and then by purchasing tokens in the public or private [crowdsale](#) or receiving tokens transferred from another token holder

Permissions

- withdraw some fraction from profit deposited in the token, but only
 1. up to the amount of share he/she is owed
 2. if the [minting](#) was finished, i.e. the total supply of the [token](#) doesn't change anymore
- transfer some tokens to another [whitelisted investor](#)
- approve some third party trustee to transfer some amount of tokens from the token holder's account to another [whitelisted investor](#)

Note A token holder may not always be also a [whitelisted investor](#), because he/she may get removed from the [whitelist](#) after the receipt of tokens or because the token instance's [whitelist](#) was exchanged.

5.2.8 THIRD PARTY TRUSTEES

Addresses who are allowed by a token holder to transfer some limited amount of tokens on the token holder's behalf.

Initially

none

Number

zero or more

Assignment

by getting approved by a [token holder](#)

Permissions

transfer up to some allowed amount of tokens from the [token holder's](#) account to some other [whitelisted investor](#)

5.3 FUNCTIONALITY

5.3.1 OWNERSHIP

see Ownable

5.3.2 ROLE MANAGEMENT

The token instance's [owner](#) can set the addresses of the following authorities (roles):

1. [Minter](#), that is the related [crowdsale](#) contract instance

Function

`setMinter(address)`

Restrictions

- only by [owner](#)
- only once

Emitted events

none

2. [Profit depositor](#)

Function

`setProfitDepositor(address)`

Restrictions

only by [owner](#)

Emitted events

`ProfitDistributorChange(address)`

3. [Profit distributor](#)

Function

`setProfitDistributor(address)`

Restrictions

only by [owner](#)

Emitted events

`ProfitDepositorChange(address)`

4. [Key recoverer](#)

Function

`setKeyRecoverer(address)`

Restrictions

only by `owner`

Emitted events

`KeyRecovererChange(address, address)`

5.3.3 WHITELIST CHECKS

Prior to being able to send or receive any amount of tokens, both—the token sender and the token recipient—have to be `whitelisted investors` in the `Whitelist` instance that is assigned to the `token contract`.

This holds true for all function related to `token minting` and `token transfers`.

5.3.4 MINTING AND FIXING TOTAL SUPPLY

MINTING TOKENS

The token's total supply is initially not fixed. That means, the `minter` can create new tokens out of thin air and book them to any `whitelisted investor`.

Function

`mint(address, uint)`

Restrictions

- only by `minter`
- if total supply wasn't fixed
- token recipient must be `whitelisted`

Emitted events

- `Minted(address, uint)`
- `Transfer(0x0, address, uint)`

FIXING TOTAL SUPPLY

As long as the total token supply is not fixed, token holders won't be able to withdraw their Ether share of profits deposited in the token contract instance. The minter will eventually finish the minting, thus fixing the total supply of the token. This will happen upon `crowdsale` finalization.

Function

`finishMinting()`

Restrictions

- only by `minter`
- if total supply wasn't fixed yet

Emitted events

`MintFinished()`

Note Fixing the token's total supply is *irreversible*.

5.3.5 PROFIT SHARING**PROFIT DEPOSIT**

Profits are distributed to `token holder` by depositing Ether in the token contract, that is, the token's `profit depositor` authority sends Ether to the token contract instance.

Functions

- payable `depositProfits()`
- payable fallback function

Restrictions

only by `profit depositor` (`#token-role-depositor`)

Emitted events

`ProfitDeposit(address, uint)`

PROFIT SHARE

Profits, i.e. the Ether currently stored in the token contract, are distributed to `token holders` according to their share of the token's total supply.

The token contract ensures that regardless of whether a token holder withdraws his/her profit share immediately after new profits were deposited or waits for several profit deposits to have happened, even if tokens were transferred in the meantime, the profit share will he/she can claim always reflects his/her token share.

Profit Share Calculation

The profit share of an investor is related to his/her token share:

Let be

- $balance_{Inv}$ the amount of tokens held by the investor,
- $profitShareOwing_{Inv}$ the owing profits share [in Ether],
- $totalSupply$ the total supply of tokens,

- $\Delta totalProfits$ the profits which were deposited into the token, instance since the investor's last profit share withdrawal [in Ether],

then

$$balance_{Inv} \div totalSupply = profitShare_{Inv} \div \Delta totalProfits$$

Note A prerequisite to correct profit share calculation is a non-changing token's total supply. This means, profit shares won't get calculated and aren't withdrawable as long as the total supply wasn't fixed, that is, while the [crowdsale](#) is still ongoing.

Determining Owing Profit Shares

The currently owed profit share of an investor can be determined:

Function

`profitShareOwing(address)`

Restrictions

none, but until after the token's total was fixed (the [crowdsale](#) was finalized) this function won't calculate the correct value but return 0

Updating Individual Profit Shares

Whenever a profit share withdrawal or a token transfer takes place, the profit shares of the involved token holding parties have to be updated first. Profit share updating means, the owed profit share of a token holder up to this moment are calculated and saved.

Function

`updateProfitShare(address)`

Restrictions

only after the token's total was fixed

Emitted events

`ProfitShareUpdate(address, uint)`

Profit Share Withdrawal

There are three possible ways for [token holders](#) to get their owed profit share withdrawn from the token.

1. Withdraw by themselves and receive the profit share (Ether) on their Ethereum address

Function

`withdrawProfitShare()`

Restrictions

only after the token's total supply was fixed

Emitted events

`ProfitShareWithdrawal(address, address, uint)`

2. Withdraw by themselves but send the profit share (Ether) to another Ethereum address

Function

`withdrawProfitShareTo(address)`

Restrictions

only after the token's total supply was fixed

Emitted events

`ProfitShareWithdrawal(address, address, uint)`

3. Bulk Withdrawal by the [profit distributor](#) authority which sends the Ether to the [token holders'](#) Ethereum addresses

Function

`withdrawProfitShares(address[])`

Restrictions

- only by [profit distributor](#)
- only after the token's total supply was fixed

Emitted events

`ProfitShareWithdrawal(address, address, uint)`

5.3.6 TOKEN TRANSFERS

Token transfers are possible via the [ERC20](#) functions:

1. A [token holder](#) can send tokens to another [whitelisted investor](#)

Function

`transfer(address, uint)`

Restrictions

- only if the sender is a [whitelisted investor](#)
- only if the recipients is a [whitelisted investor](#)
- only if the total supply is fixed

Emitted events

`Transfer(address, address, uint)`

2. A [token holder](#) can approve a [third party trustee](#) to transfer up to some amount of tokens from the token holders account to any [whitelisted investor](#)

Function

```
approve(address, uint)
```

Restrictions

- only if the sender is a [whitelisted investor](#)
- only if the total supply is fixed

Emitted events

```
Approval(address, address, uint)
```

3. A [third party trustee](#) can transfer up to some allowed limit of an [token holder's](#) account to another [whitelisted investor](#)

Function

```
transferFrom(address, address, uint)
```

Restrictions

- only by a [trustee](#) approved by the [token holder](#)
- only if the token amount is below the allowed amount
- only if the [token holder](#) is a [whitelisted investor](#)
- only if the recipient is a [whitelisted investor](#)

Emitted events

```
Transfer(address, address, uint)
```

5.3.7 KEY RECOVERY

In case a [token holders](#) wants to change his/her Ethereum address, e.g. if he/she lost his/her private key or his account was compromised, the [key recoverer](#) authority can attach the account related data to the token holder's new address.

Function

```
recoverKey(address, address)
```

Restrictions

- only by [key recoverer](#)
- only if the new address isn't already assigned to some account data within this token instance

Emitted events

```
KeyRecovery(address, address)
```

5.3.8 DESTRUCTION

If the token sale wasn't successful, that is the total amount of tokens sold in both (public and private) sales of the [crowdsale](#) hasn't reached the predefined goal, the token contract instance gets destroyed, i.e. removed from the Ethereum ledger.

Any profits deposited in the token instance will be transferred to the [token owner](#) upon destruction.

Function

`destruct()`

Restrictions

only by [minter](#), i.e. the related [crowdsale](#) instance

Emitted events

none

5.4 LIFECYCLE ---

5.4.1 MINTING PHASE

As long as the token's [crowdsale](#) was not finalized tokens can be [minted](#), i.e. created out of thin air by the [minter](#) authority, which is supposed to be the [crowdsale](#) instance itself.

Start time

at deployment

End time

- upon call of `finishMinting()`
- upon token [destruction](#)

5.4.2 TRADING PHASE

After the [minting](#) was finished, the token's total supply is [fixed](#), thus [Token holder](#) can withdraw their [profit share](#) and are allowed to trade ([transfer](#)) their tokens with others.

Start time

upon call of `finishMinting()`

End time

never

6 PROJECT MANAGER

6.1 PURPOSE

Keep a central list of and create new *project*, where a project is a data structure containing:

1. the name of the project,
2. the associated [whitelist](#) contract instance,
3. the associated [token](#) contract instance,
4. the associated [crowdsale](#) contract instance.

Additionally, the project manager acts as the rate source for the managed crowdsale contracts.

6.2 ROLES

6.2.1 PROJECT MANAGER OWNER

Initially

the [Project Manager](#) contract deployer

Number

one at a time

Assignment

- by deploying the contract
- by gaining ownership from previous owner

Permissions

- [transfer ownership](#) to another account
- assign [minter](#), but only once
- assign [profit depositor](#)
- assign [profit distributor](#)
- assign [key recoverer](#)

6.2.2 RATE ADMIN

Authority who adjusts the ether rate to the current Ether price in Euro cents.

Initially

none

Number

zero or one

Assignment

only by [project manager owner](#)

Permissions

update current Ether rate

6.2.3 WHITELIST

Current [whitelist](#) which will be initially used in newly created projects.

Initially

none

Number

zero or one

Assignment

only by [project manager owner](#)

Permissions

update current Ether rate

6.2.4 TOKEN FACTORY

A helper contract to deploy new [token](#) contracts.

Initially

none

Number

zero or one

Assignment

only by [project manager owner](#)

Permissions

update current Ether rate

6.2.5 CROWDSALE FACTORY

A helper contract to deploy new crowdsale contracts.

Initially

none

Number

zero or one

Assignment

only by project manager owner

Permissions

update current Ether rate

6.3 FUNCTIONALITY

6.3.1 ROLE MANAGEMENT

The project manager instance's owner can set the addresses of the following roles:

1. Current whitelist

Function

setWhitelist(address)

Restrictions

only by owner

Emitted events

none

2. Token factory

Function

setTokenFactory(address)

Restrictions

only by owner

Emitted events

none

3. Crowdsale factory

Function

setCrowdsaleFactory(address)

Restrictionsonly by `owner`**Emitted events**

none

4. `Rate admin`**Function**`setRateAdmin(address)`**Restrictions**only by `owner`**Emitted events**`RateAdminChange(address, address)`

6.3.2 PROJECT CREATION

Creating a project involves several steps:

1. deploy a `token` instance which is assigned to the `current whitelist`,
2. deploy a `crowdsale` instance which is assigned to the token and the project manager as its `rate source`
3. set the crowdsale to be the `minter` of its token
4. save the project (the three contracts) along with the project name in the `projects` list

The project manager allows to easily set up a new project. It utilizes two helper factory contracts.

Function`createNewProject(...)`**Restrictions**only by `project manager owner`**Emitted events**

none

6.3.3 RATE SOURCE

As the `token price` denominated in EUR-cents should be constant, the Ether rate has to be adjusted regularly to the current Ether price (in EUR-cents).

Tokens which were deployed by the project manager will have this contract set as their rate source.

READING CURRENT RATE

Function

`etherRate()`

Restrictions

none

UPDATING CURRENT RATE

Function

`setEtherRate(uint)`

Restrictions

only by [rate admin](#)

Emitted events

`RateChange(uint, uint)`