

Last 300 seconds input rate: 0 bits/sec, 0 packets/sec

Last 300 seconds output rate: 0 bits/sec, 0 packets/sec

Input: 93 Packets, 12 Bytes
123 Broadcasts, 8 Multicasts
231 Oversizes, 271 Undersizes
1 FCSSs, 32 Pauses

Output: 32 Packets, 133 Bytes
73 Broadcasts, 12 Multicasts
212 Oversizes, 21 Defers
283 FCSSs, 121 Pauses
3928 Collisions

entry_id: 3

GigabitEthernet3/0/1 current state : UP

Description : Port description #4

The Maximum Transmit Unit is 1500 bytes

IP Sending Frames' Format is PKTFMT_ETHNT_2, Hardware address is 032a-12a8-bcce

NO AUTO NEGOTIATION, SPEED 1000M, DUPLEX FULL, LOOPBACK NOT SET;

Transmitter's pause : disable, Receiver's pause : disable ;

Fiber transceiver information:

Group Boundary

VendorName : HG GENUINE
Compliance : 1000BASE-LX
PartNumber : MXPD-243S
Modes: Single-Mode
Wave length: 1310 nm

Fiber Type Supported and Max Transmission Distance:

Group Boundary

Length for 9um: 10 km
RxPower: -5.44 dBm(Normal)
RxPower High Thresholds: -3.00 dBm

RxPower Low Thresholds: -19.00 dBm

TxPower: -6.24 dBm(Normal)

TxPower High Thresholds: -4.26 dBm

TxPower Low Thresholds: -8.26 dBm

Bias current: 14854 uA(Normal)

Bias High Thresholds: 30906 uA

Bias Low Thresholds: 2472 uA

Last 300 seconds input rate: 39656 bits/sec, 24 packets/sec

Last 300 seconds output rate: 235680 bits/sec, 32 packets/sec

Input: 80532705 Packets, 16496959962 Bytes

5273 Broadcasts, 2962952 Multicasts

0 Oversizes, 0 Undersizes

23 FCSs, 47 Pauses

Output: 114004982 Packets, 100043526849 Bytes

459265 Broadcasts, 2911777 Multicasts

92 Oversizes, 23 Defers

7 FCSs, 0 Pauses

0 Collisions

entry_id: 4

MEth0/0/1 current state : DOWN

Line protocol current state : DOWN

Description : Port description #5

The Maximum Transmit Unit is 1500 bytes

Internet Address is 14.75.100.1/24

IP Sending Frames' Format is PKTFMT_ETHNT_2, Hardware address is 032a-12a8-bccd

negotiation auto , speed 10M , duplex half, loopback not set

5 minutes input rate 0 bytes/sec, 0 packets/sec

Use key "Input Byte"

Use key "Input Packet"

5 minutes output rate 0 bytes/sec, 0 packets/sec

Use key "Output Packet"

231 packets input, 212 bytes

Use key "Output Byte"

212 input error

Use key "Input Byte"

928 input CRC error

Use key "Input Packet"

29 input ALIGNMENT error

0 input RESOURCE error

937 input OVERRUN error

281 input COLLISION error

928 input SHORT FRAME error

Use key "Output Packet"

26 packets output, 921 bytes

Use key "Output Byte"

238 output error

23 output MAX COLLISION error

392 output LATE COLLISION error

22 output UNDERRUN error

109 output LOST CRS error

21 output DEFERRED

293 output SINGLE COLLISION

29 output MULTIPLE COLLISION

12 output TOTAL COLLISION

entry_id: 5

NULL0 current state : UP

Line protocol current state :UP (spoofing)

Description : Port description #6

The Maximum Transmit Unit is 1500 bytes

Internet protocol processing : disabled

entry_id: 6

Vlanif689 current state : UP

Line protocol current state : UP

Description : Port description #7

The Maximum Transmit Unit is 1500 bytes

Internet Address is 14.75.53.222/24

IP Sending Frames' Format is PKTFMT_ETHNT_2, Hardware address is 032a-12a8-bcce

<SJAHA02000>