



DOC.IV-7  
EDITION: 2025-Q3

VERTICALLY INTEGRATED SYSTEMS

# PRODUCT CATALOG

FIBER OPTICS & PHOTONICS

# 2025

**SCOPE:** Optoelectronic  
Components & Solutions

**APPLICATIONS:** Optical  
Communication, Consumer &  
Automotive

**KEY TECH:** VCSELs, PIN  
Photodiodes, SiGe BICMOS



# 01. WELCOME TO VI SYSTEMS

---

VI SYSTEMS (VIS) DEVELOPS AND MANUFACTURES CUTTING-EDGE OPTOELECTRONIC COMPONENTS FOR COMMUNICATION, CONSUMER, AND AUTOMOTIVE APPLICATIONS. LOCATED IN THE HEART OF BERLIN, WE ARE A FABLESS COMPANY SPECIALIZING IN ULTRA-FAST SOLUTIONS FOR OPTICAL INTERCONNECTS AND SENSORS.

OUR PORTFOLIO INCLUDES VERTICAL CAVITY SURFACE-EMITTING LASERS (VCSELS) AND PIN PHOTODIODES DELIVERING SPEEDS UP TO 224 GBPS PER CHANNEL, ALONGSIDE DRIVER AND AMPLIFIER ICS OPERATING UP TO 56 GBPS. OUR LATEST GENERATION COMPONENTS ENABLE ENERGY-EFFICIENT 400 GBPS PAM-4 TRANSMISSION USING SHORT WAVE DIVISION MULTIPLEXING (SWDM).



## 02. TABLE OF CONTENTS

---

WELCOME TO VI SYSTEMS . . . . .	02
TECHNOLOGY & SERVICES . . . . .	03
WAFER MAPPING & HIGH-FREQUENCY TESTING . . . . .	04
OPTICAL & MECHANICAL INSPECTION . . . . .	06
MODELLING & SIMULATION . . . . .	06
VCSEL TRANSMITTER MODULES . . . . .	07
OPTICAL RECEIVERS & PHOTODETECTORS . . . . .	08
INTEGRATED CIRCUITS (ICS) . . . . .	09
ULTRA HIGH-SPEED VCSEL CHIPS . . . . .	10
ULTRA HIGH-SPEED VCSEL CHIPS (MA-SM / QSM) . . . . .	11
HIGH-SPEED VCSEL CHIPS . . . . .	12
HIGH-SPEED PHOTODIODES (PDS) . . . . .	13
CONTACT INFORMATION . . . . .	14

## 03. TECHNOLOGY & SERVICES

### INTEGRATED OPTICAL SOLUTIONS

VIS CUSTOMIZES STATE-OF-THE-ART SIGE BICMOS INTEGRATED CIRCUITS TO MATCH ULTRAHIGH-SPEED VCSEL TRANSMITTER AND PIN RECEIVER COMPONENTS.

BOTH KEY ELEMENTS ARE ASSEMBLED IN A PROPRIETARY HIGH-FREQUENCY DESIGN DELIVERING OUTSTANDING PERFORMANCE OVER A WIDE TEMPERATURE RANGE.

#### KEY ADVANTAGES:

- HIGH SPEED PERFORMANCE
- LOW POWER CONSUMPTION
- SMALL FOOTPRINT DESIGN
- HIGH RELIABILITY
- LOW COST MANUFACTURING

OUR UNIQUE SELLING POINT IS THE COMBINATION OF MICRO-ASSEMBLY INTEGRATION OF ADVANCED ELECTRO-OPTIC COMPONENTS, DEVELOPMENT OF HIGH-SPEED ICS AND MODULATION APPROACHES.

VIS OPERATES A FABLESS MODEL ENSURING RELIABILITY AND SCALABILITY.

INTEGRATED VCSEL  
DRIVER WITH VCSEL  
CHIP PHOTO

CONCEPTUAL GRAPHIC:  
ICS + OPTICAL  
COMPONENTS  
INTEGRATION

## 04. WAFER MAPPING & HIGH-FREQUENCY TESTING

### WAFER MAPPING SERVICES

VIS'S SEMI-AUTOMATIC PROBER STATION PERFORMS HIGH-SPEED ELECTRICAL AND OPTICAL TESTING EARLY IN THE MANUFACTURING PROCESS, REDUCING COSTS BY ELIMINATING OUT-OF-SPEC WAFERS.

FULL WAFER CHARACTERISATION: 100% CHARACTERISATION OF 2"–8" WAFERS USING AN ALIGNMENT CAMERA WITH PATTERN RECOGNITION; AUTOMATIC ALIGNMENT TO CHIPS; TEMPERATURE RANGE 25 °C–150 °C.

#### MEASURED PARAMETERS:

- L/I/V CURVES
- THRESHOLD CURRENT
- SLOPE EFFICIENCY
- OPTICAL SPECTRUM
- PHOTODIODE SENSITIVITY
- REVERSE BIAS AND DARK CURRENT

EMISSION ANALYSIS: NEARFIELD AND FARFIELD ANALYSIS FOR EMITTING DIAMETER, MODE CHARACTERISTICS, POLARIZATION AND ANGULAR POWER DISTRIBUTION.

SEMI-AUTOMATIC WAFER PROBER AND  
ALIGNMENT CAMERA PHOTO

### HIGH-FREQUENCY TEST & CHARACTERISATION

THE HIGH-FREQUENCY LAB ANALYSES ELECTRO-OPTICAL PERFORMANCE USING A SINE-WAVE GENERATOR UP TO 38 GHz WITH A 70 GHz SAMPLING OSCILLOSCOPE.

#### LABORATORY CAPABILITIES:

- 32 GHz DETECTOR COVERS 700–1600 NM
- EYE-DIAGRAM AND MODULATION TESTS UP TO 128 GBIT/S
- PRBS7/PRBS31 PATTERN GENERATION
- PHOTODETECTOR MODULES UP TO 112 GBIT/S AT 850 NM

HIGH-FREQUENCY TEST LABORATORY  
SETUP PHOTO

## 06. OPTICAL & MECHANICAL INSPECTION, MODELLING & SIMULATION

### OPTICAL & MECHANICAL INSPECTION

THE LABORATORY'S OPTICAL MICROSCOPES UP TO 1000× MAGNIFICATION AND THICKNESS ANALYSIS TECHNOLOGY RESOLVING 0.1 MM (HORIZONTAL) AND 0.5 MM (VERTICAL).

MICROPROBER STATION: ON-WAFER CHARACTERISATION OVER A WIDE TEMPERATURE RANGE; STATIC TESTS MEASURE FORWARD/REVERSE VOLTAGE, CURRENT AND DIFFERENTIAL RESISTANCE.

#### OPTICAL PARAMETERS:

- POWER
- SPECTRUM
- SENSITIVITY
- EFFICIENCY
- THRESHOLD CURRENT
- SLOPE EFFICIENCY
- AMPLIFICATION

ADVANCED STUDIES: COMPLEX ANALYSES USE FIB, SEM AND TEM WITH EXTERNAL PARTNERS.

### MODELLING & SIMULATION

THERMAL MODELLING OF SEMICONDUCTOR PACKAGES USES MODERN FEA/CFD TOOLS INTEGRATED WITH MECHANICAL CAD.

VCSEL SIMULATION: MODELLING OF VCSEL OPTICAL MODES (FUNDAMENTAL AND EXCITED MODES) AND THERMAL DISTRIBUTIONS, WHICH INFORM DESIGN IMPROVEMENTS.


STEREO MICROSCOPE WITH  
TEMPERATURE CHUCK

HIGH-RESOLUTION OPTICAL  
MICROSCOPE

TEM ANALYSIS PHOTO

THERMAL  
DISTRIBUTION  
GRAPHIC


## 06. VCSEL TRANSMITTER MODULES



### V25-850M

DATA RATE	28 GBPS (NRZ)
WAVELENGTH	850 NM
FIBER TYPE	50/125 MM

DATASHEET 



### V50-850M


DATA RATE	56 GBPS (PAM-4)
WAVELENGTH	850 NM
FIBER TYPE	50/125 MM


DATASHEET 



### VM100-850M

DATA RATE	112 GBPS (PAM-4)
WAVELENGTH	850 NM
FIBER TYPE	50/125 MM

DATASHEET 



### T56-850


DATA RATE	56 GBPS (NRZ)
WAVELENGTH	850 NM
FIBER TYPE	50/125 MM

DATASHEET 




### V25-1550M

WAVELENGTH	1550 NM
DATA RATE	25 GBPS (NRZ)
FIBER TYPE	9/125 MM

DATASHEET 

## 07. OPTICAL RECEIVERS & PHOTODETECTORS



### R56-850

INPUT 700-870 NM  
WAVELENGTH  
DATA RATE (NRZ) 56 GBPS  
FIBER TYPE 50/125 MM


DATASHEET 



### D30-850M


3 DB BANDWIDTH > 30 GHZ  
WAVELENGTH 840-1650 NM  
FIBER TYPE 50/125 MM

DATASHEET 



### D60M FC


INPUT 400-1650 NM  
WAVELENGTH  
3 DB BANDWIDTH > 60 GHZ  
FIBER TYPE MMF/SMF

DATASHEET 



## 08. INTEGRATED CIRCUITS (ICS)


### HIGH SPEED VCSEL DRIVERS



#### A56-230C

DATA RATE	UP TO 100 GBPS
SUPPLY VOLTAGE	3.3 V
POWER DISSIPATION	200 MW


DATASHEET 



#### A56-105C

DATA RATE	UP TO 56 GBPS
SUPPLY VOLTAGE	3.3 V
POWER DISSIPATION	105 MW

DATASHEET 



#### T56-250C

DATA RATE	UP TO 56 GBPS (NRZ)
DIFFERENTIAL GAIN	3.0 KΩ
POWER	150 MW

DATASHEET 

# 09. ULTRA HIGH-SPEED VCSEL CHIPS

SERIES: VM100

	<div><b>VM100 850</b></div> <table><tr><td>CHIP TYPE</td><td>MULTI-MODE</td></tr><tr><td>WAVELENGTH</td><td>840-860 NM</td></tr><tr><td>CONTACT</td><td>GSG</td></tr></table>	CHIP TYPE	MULTI-MODE	WAVELENGTH	840-860 NM	CONTACT	GSG	DATASHEET 
CHIP TYPE	MULTI-MODE							
WAVELENGTH	840-860 NM							
CONTACT	GSG							
	<div><b>VM100 880</b></div> <table><tr><td>CHIP TYPE</td><td>MULTI-MODE</td></tr><tr><td>WAVELENGTH</td><td>870-890 NM</td></tr><tr><td>CONTACT</td><td>GSG</td></tr></table>	CHIP TYPE	MULTI-MODE	WAVELENGTH	870-890 NM	CONTACT	GSG	DATASHEET 
CHIP TYPE	MULTI-MODE							
WAVELENGTH	870-890 NM							
CONTACT	GSG							
	<div><b>VM100 910</b></div> <table><tr><td>CHIP TYPE</td><td>MULTI-MODE</td></tr><tr><td>WAVELENGTH</td><td>900-920 NM</td></tr><tr><td>CONTACT</td><td>GSG</td></tr></table>	CHIP TYPE	MULTI-MODE	WAVELENGTH	900-920 NM	CONTACT	GSG	DATASHEET 
CHIP TYPE	MULTI-MODE							
WAVELENGTH	900-920 NM							
CONTACT	GSG							
	<div><b>VM100 940</b></div> <table><tr><td>CHIP TYPE</td><td>MULTI-MODE</td></tr><tr><td>WAVELENGTH</td><td>930-950 NM</td></tr><tr><td>CONTACT</td><td>GSG</td></tr></table>	CHIP TYPE	MULTI-MODE	WAVELENGTH	930-950 NM	CONTACT	GSG	DATASHEET 
CHIP TYPE	MULTI-MODE							
WAVELENGTH	930-950 NM							
CONTACT	GSG							

# 10. ULTRA HIGH-SPEED VCSEL CHIPS

SERIES: VM100 (MA-SM / QSM)

	<b>VM100 850 MA-SM</b> CHIP TYPE           MA-SM WAVELENGTH       840-860 NM CONTACT            GSG	DATASHEET 
	<b>VM100 880 MA-SM</b> CHIP TYPE           MA-SM WAVELENGTH       870-890 NM CONTACT            GSG	DATASHEET 
	<b>VM100 910 MA-SM</b> CHIP TYPE           MA-SM WAVELENGTH       900-920 NM CONTACT            GSG	DATASHEET 
	<b>VM100 940 MA-SM</b> CHIP TYPE           MA-SM WAVELENGTH       930-950 NM CONTACT            GSG	DATASHEET 
	<b>VM100 850 QSM</b> CHIP TYPE           QSM WAVELENGTH       840-860 NM CONTACT            GSG	DATASHEET 
	<b>VM100 910 QSM</b> CHIP TYPE           QSM WAVELENGTH       900-920 NM CONTACT            GSG	DATASHEET 

# 11. HIGH-SPEED VCSEL CHIPS


SERIES: V50 / VM50 / V25



## V50 850

CHIP TYPE	MULTI-MODE
WAVELENGTH	840-860 NM
CONTACT	SG / GS

DATASHEET 



## VM50 940

CHIP TYPE	MULTI-MODE
WAVELENGTH	930-950 NM
CONTACT	GSG


DATASHEET 



## V25 940 HP MA

FEATURE	HIGH POWER (LIFI)
WAVELENGTH	930-950 NM
CONTACT	SG / GS

DATASHEET 



## VM50 850

CHIP TYPE	MULTI-MODE
WAVELENGTH	840-860 NM
CONTACT	GSG

DATASHEET 



## V25 850 HT

FEATURE	HIGH TEMP (125°C)
WAVELENGTH	840-860 NM
CONTACT	SG / GS

DATASHEET 

## 12. HIGH-SPEED PHOTODIODES (PDS)

### SWDM-OPTIMIZED



#### D40 SWDM

CONTACT TYPE	GSG
DIAMETER	20 MM
BANDWIDTH	~40 GHZ

DATASHEET 



#### D35 SWDM

CONTACT TYPE	GSG
DIAMETER	25 MM
BANDWIDTH	~35 GHZ


DATASHEET 



#### D30 SWDM


CONTACT TYPE	GSG
DIAMETER	~23 MM
BANDWIDTH	~30 GHZ

DATASHEET 



#### D70 SWDM


CONTACT TYPE	GSG
DIAMETER	~25 MM
BANDWIDTH	~70 GHZ

DATASHEET 



#### D400G

CONTACT TYPE	GSG
DIAMETER	~16 MM
BANDWIDTH	~60 GHZ (25Ω)

DATASHEET 

## 13. CONTACT INFORMATION

---

FOR ADDITIONAL INFORMATION OR TO RECEIVE A QUOTATION, PLEASE CONTACT OUR SALES DEPARTMENT.

### ADDRESS

VI SYSTEMS GMBH

HARDENBERGSTRASSE 7 [!\[\]\(35dc653d59570f8f891c312eeece91a2\_img.jpg\)](#)

10623 BERLIN, GERMANY

### TELEPHONE

+49 30 3083143 30 [!\[\]\(aab88c0d099e5d18d6533a97b13ec28d\_img.jpg\)](#)

### EMAIL

SALES@V-I-SYSTEMS.COM [!\[\]\(5abce1a84a655b073239ab33e1199487\_img.jpg\)](#)

### WEB

WWW.V-I-SYSTEMS.COM [!\[\]\(097cdd6c9c875b64d9b8c9a2409491c4\_img.jpg\)](#)