

DOC.IV-7 EDITION: 2025-Q3

PRODUCT CATALOG

FIBER OTICS & PHOTONICS



SCOPE: Optoelectronic Components & Solutions

APPLICATIONS: Optical Communication, Consumer & Automotive

KEY TECH: VCSELs, PIN Photodiodes, SiGe BICMOS

TRANSMITTERS

01. WELCOME TO VI SYSTEMS

VI SYSTEMS (VIS) DEVELOPS AND MANUFACTURES CUTTING-EDGE OPTOELECTRONIC COMPONENTS FOR COMMUNICATION, CONSUMER, AND AUTOMOTIVE APPLICATIONS. LOCATED IN THE HEART OF BERLIN, WE ARE A FABLESS COMPANY SPECIALIZING IN ULTRA-FAST SOLUTIONS FOR OPTICAL INTERCONNECTS AND SENSORS.

OUR PORTFOLIO INCLUDES VERTICAL CAVITY SURFACE-EMITTING LASERS (VCSELS) AND PIN PHOTODIODES DELIVERING SPEEDS UP TO 224 GBPS PER CHANNEL, ALONGSIDE DRIVER AND AMPLIFIER ICS OPERATING UP TO 56 GBPS. OUR LATEST GENERATION COMPONENTS ENABLE ENERGY-EFFICIENT 400 GBPS PAM-4 TRANSMISSION USING SHORT WAVE DIVISION MULTIPLEXING (SWDM).

02 / 09 | < PREV



02. TABLE OF CONTENTS

- **02 WELCOME TO VI SYSTEMS**
- **04 TECHNOLOGY & SERVICES**
- **05 VCSEL TRANSMITTER MODULES**
- **06 OPTICAL RECEIVERS & PHOTODETECTORS**
- 07 INTEGRATED CIRCUITS (ICS)
- **08 VCSEL & PHOTODIODE CHIPS**
- **09 CONTACT INFORMATION**

< PREV

03 / 09



03. TECHNOLOGY & SERVICES

INTEGRATED OPTICAL SOLUTIONS

WE PAIR STATE-OF-THE-ART SIGE BICMOS INTEGRATED CIRCUITS WITH OUR ULTRAHIGH-SPEED VCSEL AND PIN COMPONENTS TO DELIVER OUTSTANDING PERFORMANCE.

WAFER MAPPING SERVICES

COMPREHENSIVE ELECTRICAL AND OPTICAL TESTING ON 2" TO 8" WAFERS AT TEMPERATURES UP TO 150°C.

HIGH-FREQUENCY TEST & CHARACTERIZATION

ELECTRO-OPTICAL PERFORMANCE MEASUREMENT WITH DATA MODULATION ANALYSIS UP TO 128 GBIT/S.

< PREV

04 / 09



04. VCSEL TRANSMITTER MODULES

V25-850M		Щ
DATA RATE	28 GBPS (NRZ)	DATASHEET
WAVELENGTH	850 NM	DAT
FIBER TYPE	50/125 MM	P
V50-850M		
DATA RATE	56 GBPS (PAM-4)	DATASHEET
WAVELENGTH	850 NM	DAT
FIBER TYPE	50/125 MM	P
VM100-850I	M	h.

VM100-850N	1	
DATA RATE	112 GBPS (PAM-4)	ASHE
WAVELENGTH	850 NM	DAT
FIBER TYPE	50/125 MM	P

T56-850	
DATA RATE	56 GBPS (NRZ)
WAVELENGTH	850 NM
FIBER TYPE	50/125 MM

DATASHEET

ICS

CHIPS



05. OPTICAL RECEIVERS & PHOTODETECTORS

R50-850		H
DATA RATE	56 GBPS (NRZ)	DATASHEET
WAVELENGTH	700-870 NM	DAT
FIBER TYPE	50/125 MM	P
D30-850M		
DATA RATE	112 GBPS (PAM-4)	DATASHEE
WAVELENGTH	840-1650 NM	DAT
FIBER TYPE	50/125 MM	P



06. INTEGRATED CIRCUITS (ICS)

HIGH SPEED VCSEL DRIVERS

A56-230C

DATA RATE UP TO 56 GBPS

SUPPLY VOLTAGE 3.3 V

POWER 230 MW DISSIPATION

P

A56-105C

DATA RATE UP TO 56 GBPS

SUPPLY VOLTAGE 3.3 V

POWER 105 MW DISSIPATION

P



07. VCSEL & PHOTODIODE CHIPS

HIGH SPEED VCSEL CHIPS

V25-850C

DATA RATE 28 GBPS (NRZ)

WAVELENGTH 850 NM

PEAK OUTPUT 4 MW **POWER**

P

V50-850C

56 GBPS (NRZ) DATA RATE

WAVELENGTH 850 NM

PEAK OUTPUT 4 MW **POWER**

P

08. CONTACT INFORMATION

FOR ADDITIONAL INFORMATION OR TO RECEIVE A QUOTATION, PLEASE CONTACT OUR SALES DEPARTMENT.

ADDRESSVI TELEPHONE+49 30 3083143 30 SYSTEMS GMBH, HARDENBERGSTRASSE 7, 10623 BERLIN, GERMANY

EMAILSALES@V-I- **WEB**WWW.V-I-SYSTEMS.COM SYSTEMS.COM

09 / 09