



DOC.IV-7  
EDITION: 2025-Q3

VERTICALLY INTEGRATED SYSTEMS

# PRODUCT CATALOG

FIBER OPTICS & PHOTONICS

# 2025

**SCOPE:** Optoelectronic  
Components & Solutions

**APPLICATIONS:** Optical  
Communication, Consumer &  
Automotive

**KEY TECH:** VCSELs, PIN  
Photodiodes, SiGe BICMOS



# 01. WELCOME TO VI SYSTEMS

---

VI SYSTEMS (VIS) DEVELOPS AND MANUFACTURES CUTTING-EDGE OPTOELECTRONIC COMPONENTS FOR COMMUNICATION, CONSUMER, AND AUTOMOTIVE APPLICATIONS. LOCATED IN THE HEART OF BERLIN, WE ARE A FABLESS COMPANY SPECIALIZING IN ULTRA-FAST SOLUTIONS FOR OPTICAL INTERCONNECTS AND SENSORS.

OUR PORTFOLIO INCLUDES VERTICAL CAVITY SURFACE-EMITTING LASERS (VCSELS) AND PIN PHOTODIODES DELIVERING SPEEDS UP TO 224 GBPS PER CHANNEL, ALONGSIDE DRIVER AND AMPLIFIER ICS OPERATING UP TO 56 GBPS. OUR LATEST GENERATION COMPONENTS ENABLE ENERGY-EFFICIENT 400 GBPS PAM-4 TRANSMISSION USING SHORT WAVE DIVISION MULTIPLEXING (SWDM).



## 02. TABLE OF CONTENTS

---

02 WELCOME TO VI SYSTEMS

04 TECHNOLOGY & SERVICES

05 VCSEL TRANSMITTER MODULES

06 OPTICAL RECEIVERS & PHOTODETECTORS

07 INTEGRATED CIRCUITS (ICS)

08 ULTRA HIGH-SPEED VCSEL CHIPS

09 HIGH-SPEED VCSEL CHIPS

10 HIGH-SPEED PHOTODIODES (PDS)

11 CONTACT INFORMATION



## 03. TECHNOLOGY & SERVICES

### INTEGRATED OPTICAL SOLUTIONS

WE PAIR STATE-OF-THE-ART SIGE BICMOS INTEGRATED CIRCUITS WITH OUR ULTRAHIGH-SPEED VCSEL AND PIN COMPONENTS TO DELIVER OUTSTANDING PERFORMANCE.

### WAFER MAPPING SERVICES

COMPREHENSIVE ELECTRICAL AND OPTICAL TESTING ON 2" TO 8" WAFERS AT TEMPERATURES UP TO 150°C.

### HIGH-FREQUENCY TEST & CHARACTERIZATION

ELECTRO-OPTICAL PERFORMANCE MEASUREMENT WITH DATA MODULATION ANALYSIS UP TO 128 GBIT/S.

## 04. VCSEL TRANSMITTER MODULES


### V25-850M

DATA RATE	28 GBPS (NRZ)
WAVELENGTH	850 NM
FIBER TYPE	50/125 MM

DATASHEET 


### V50-850M

DATA RATE	56 GBPS (PAM-4)
WAVELENGTH	850 NM
FIBER TYPE	50/125 MM

DATASHEET 


### VM100-850M

DATA RATE	112 GBPS (PAM-4)
WAVELENGTH	850 NM
FIBER TYPE	50/125 MM

DATASHEET 


### T56-850

DATA RATE	56 GBPS (NRZ)
WAVELENGTH	850 NM
FIBER TYPE	50/125 MM

DATASHEET 

### V25-1550M


WAVELENGTH	1550 NM
DATA RATE	25 GBPS (NRZ)
FIBER TYPE	9/125 MM

DATASHEET 

## 05. OPTICAL RECEIVERS & PHOTODETECTORS


### R56-850

INPUT 700-870 NM  
WAVELENGTH  
DATA RATE (NRZ) 56 GBPS  
FIBER TYPE 50/125 MM

DATASHEET 

### D30-850M

3 DB BANDWIDTH > 30 GHZ  
WAVELENGTH 840-1650 NM  
FIBER TYPE 50/125 MM

DATASHEET 

### D60M FC

INPUT 400-1650 NM  
WAVELENGTH  
3 DB BANDWIDTH > 60 GHZ  
FIBER TYPE MMF/SMF

DATASHEET 



# 06. INTEGRATED CIRCUITS (ICS)

## HIGH SPEED VCSEL DRIVERS

### A56-230C

DATA RATE	UP TO 100 GBPS
SUPPLY VOLTAGE	3.3 V
POWER DISSIPATION	200 MW

DATASHEET



### A56-105C

DATA RATE	UP TO 56 GBPS
SUPPLY VOLTAGE	3.3 V
POWER DISSIPATION	105 MW

DATASHEET



### T56-250C

DATA RATE	UP TO 56 GBPS (NRZ)
DIFFERENTIAL GAIN	3.0 KΩ
POWER DISSIPATION	150 MW

DATASHEET




## 08. ULTRA HIGH-SPEED VCSEL CHIPS

SERIES: VM100 (MM / MA-SM / QSM)


### VM100 850

CHIP TYPE	MULTI-MODE
WAVELENGTH	840-860 NM
CONTACT	GSG

DATASHEET 

### VM100 880

CHIP TYPE	MULTI-MODE
WAVELENGTH	870-890 NM
CONTACT	GSG

DATASHEET 


### VM100 910

CHIP TYPE	MULTI-MODE
WAVELENGTH	900-920 NM
CONTACT	GSG

DATASHEET 


### VM100 940

CHIP TYPE	MULTI-MODE
WAVELENGTH	930-950 NM
CONTACT	GSG

DATASHEET 


### VM100 850 MA-SM

CHIP TYPE	MA-SM
WAVELENGTH	840-860 NM
CONTACT	GSG

DATASHEET 

### VM100 850 QSM

CHIP TYPE	QSM
WAVELENGTH	840-860 NM
CONTACT	GSG

DATASHEET 





VERTICALLY INTEGRATED SYSTEMS

DOC.IV-7  
PRODUCT-GROUP: CHIPS

TRANSMITTERS

RECEIVERS

ICS


CHIPS

## 09. HIGH-SPEED VCSEL CHIPS

SERIES: V50 / VM50 / V25


### V50 850

CHIP TYPE	MULTI-MODE
WAVELENGTH	840-860 NM
CONTACT	SG / GS

DATASHEET 


### VM50 940

CHIP TYPE	MULTI-MODE
WAVELENGTH	930-950 NM
CONTACT	GSG

DATASHEET 


### V25 940 HP MA

FEATURE	HIGH POWER (LIFI)
WAVELENGTH	930-950 NM
CONTACT	SG / GS

DATASHEET 


### VM50 850

CHIP TYPE	MULTI-MODE
WAVELENGTH	840-860 NM
CONTACT	GSG

DATASHEET 

### V25 850 HT

FEATURE	HIGH TEMP (125°C)
WAVELENGTH	840-860 NM
CONTACT	SG / GS

DATASHEET 

# 10. HIGH-SPEED PHOTODIODES (PDS)

## SWDM-OPTIMIZED


### D40 SWDM

CONTACT TYPE	GSG
DIAMETER	20 MM
BANDWIDTH	~40 GHZ

DATASHEET 


### D35 SWDM

CONTACT TYPE	GSG
DIAMETER	25 MM
BANDWIDTH	~35 GHZ

DATASHEET 

### D30 SWDM

CONTACT TYPE	GSG
DIAMETER	~23 MM
BANDWIDTH	~30 GHZ

DATASHEET 


### D70 SWDM

CONTACT TYPE	GSG
DIAMETER	~25 MM
BANDWIDTH	~70 GHZ

DATASHEET 

### D400G

CONTACT TYPE	GSG
DIAMETER	~16 MM
BANDWIDTH	~60 GHZ (25Ω)

DATASHEET 



## 11. CONTACT INFORMATION

---

FOR ADDITIONAL INFORMATION OR TO RECEIVE A QUOTATION, PLEASE CONTACT OUR SALES DEPARTMENT.

**ADDRESS** VI  
SYSTEMS GMBH,  
HARDENBERGSTRASSE  
7, 10623 BERLIN,  
GERMANY

**TELEPHONE** +49 30 3083143 30

**EMAIL** SALES@V-I-  
SYSTEMS.COM

**WEB** WWW.V-I-SYSTEMS.COM