
# Mimic the Diffusion



#### Feature 1.

- High-noised distribution => Low-noised distribution (gradually update)
- High- $\beta$  VAE => Low- $\beta$  VAE
- This means "high distortion => low distortion"
- It may not be perfect, but the meaning is similar




Figure 2: Aggregated posteriors for arbitrarily chosen latent channels. Each row shares a model and channels, and distributions are placed in order of decreasing  $\beta$ . The posteriors of our model (b) are *aligned* relative to their counterparts (a).

#### Feature 2.

- Iterative refinement with "very small step"
- $\beta$ -Selectable VAE has the power to perform it
- It can represent continuous  $\beta$  intervals,
- With the same model capacity





Figure 3: Reconstruction and regularization errors of ELBO for various  $\beta$ s. For ELBO, i.e. the learning objective, a single  $\beta$ -Selectable VAE is capable of approximate many  $\beta$ -VAEs. This graph can be interpreted as a rate-distortion curve.

# Mimic the Diffusion



### Feature 3.

- "Randomness"
- Recursively re-input to VAE
- I think the latent variables on the posteriors with very close beta values,
- Would maintain its meaning on the other side well
- There will be a small loss of information, i.e. acceptable randomness
- This is a logical leap though

# Feature 4.

- Iterative "refinement" with very small step
- I think that the optimization of ELBO for the latent z can take over the role
- **BUT!!**
- Consider a few steps later:
- $x_t \pmod{x_0} \to z_t \to x_t' \pmod{x_t = x_{t+1}}$
- ELBO means how similar  $x_t$  and  $x_t'$  are... not likelihood!
- It loses the meaning as a refinement

# Reflection

- This is a huge problem that is *easy to spot*
- I accepted it as the right method
- Because some experimental results came out good (e.g. MNIST)
- Of course, one need to experiment with various variables, but
- There is a complacent attitude because that were good in one or two...

# Features (all)

- Iterative "refinement" with "very small step"
- With "gradually noised distribution" and "Randomness"
- If there is a good way to refine a sample, it could be done again