

Temporal Decay of Co-Citation Predictability: A 20-Year Statute Retrieval Benchmark from 502M Ukrainian Court Citations

Volodymyr Keshchenko
SecondLayer
mcvovkes@gmail.com

Анотація

Co-citation structure is widely assumed to provide stable retrieval signal in legal information systems. We test this assumption longitudinally by constructing UA-StatuteRetrieval, a benchmark that measures co-citation predictability across 20 annual snapshots (2007–2026) of 502 million citation records from 126 million Ukrainian court decisions. Using a leave-one-out protocol over the full bipartite citation graph, we find that Adamic-Adar MRR declines 33% on a fixed set of articles (from 0.43 to 0.29) and 47% under a train/test temporal split (from 0.51 to 0.27) – confirming genuine temporal decay rather than compositional shift or evaluation artifact. The decay is non-uniform: criminal procedure maintains stable co-citation patterns (MRR $\sim$ 0.40), while civil law degrades from 0.35 to 0.15 following the 2017 judicial reform. Hub articles ($>100K$ citations) resist decay, but mid-frequency articles (1K–10K) – the practical retrieval frontier – lose half their predictability. These findings establish that graph-based legal retrieval requires continual updating and that neural text-based methods are necessary precisely where co-citation signal is weakest. The benchmark is released at <https://huggingface.co/datasets/overthelx/ua-statute-retrieval>.

1 Introduction

Co-citation structure – the pattern of which statutory articles are cited together in court decisions – underpins many legal information retrieval systems [2, 6, 14]. The implicit assumption is that this structure provides a stable signal: if articles A and B were frequently co-cited in past decisions, they remain relevant to similar future cases.

We test this assumption empirically. From the Ukrainian Unified State Register of Court Decisions (ЄДРСР, 126M decisions, 2005–2026), we extract 502 million statutory citations and construct annual retrieval benchmarks spanning 20 years. Our evaluation protocol is leave-one-out over the full bipartite citation graph: for each decision, we mask each cited article and measure whether co-citation-based methods can recover it.

The central finding is that co-citation predictability decays: the same retrieval methods applied to the same articles yield progressively worse results over time. This is not a trivial consequence of changing article composition – we verify through ablation that decay persists on a fixed article set (33% decline) and strengthens under proper train/test separation (47% decline).

The decay concentrates along two dimensions:

1. Domain: criminal procedure resists decay while civil and administrative law degrade rapidly.
2. Frequency: hub articles ($>100K$ citations) maintain predictability; mid-frequency articles (1K–10K) – the practical retrieval challenge – lose half their signal.

These findings have direct implications for legal retrieval system design: graph-based methods should not be treated as static indexes but require continual updating, and neural text-based retrieval is necessary specifically for the mid-frequency, civil/administrative tail where co-citation fails.

2 Related Work

Legal retrieval benchmarks. BSARD [9] provides 1,108 queries for Belgian statutory article retrieval. SCALE [13] and LeSICiN [12] evaluate retrieval in Swiss and Indian contexts respectively. LEXTREME [11] and LegalBench [5] cover classification but not retrieval. All evaluate at a single time point; none measure temporal stability.

Legal citation networks. Fowler et al. [4] study US Supreme Court precedent networks; Coupette et al. [3] analyze European statute evolution; Winkels et al. [15] examine Dutch case law authority. CaseGNN++ [14] applies graph neural networks to legal retrieval. None release citation graphs as retrieval benchmarks or study temporal degradation.

Link prediction. We adapt Common Neighbors and Adamic-Adar [1] from social network link prediction [8] to bipartite legal graphs. Our contribution is the longitudinal application and the discovery that predictability is non-stationary.

3 Data

3.1 Source Corpus

The ЄДПОР publishes all Ukrainian court decisions since 2005. We process 126 million full-text decisions partitioned by adjudication year. Citation extraction uses compiled regex patterns for 13 codices with abbreviation normalization and article range expansion. After cleaning (retaining only well-formed article references), we obtain 502 million citation records.

3.2 Annual Snapshots

For each year $y \in \{2007, \dots, 2026\}$, we construct an evaluation snapshot:

1. Extract all codex citations from decisions adjudicated in year y .
2. Filter articles: minimum 50 citations, capped at 5,000 most frequent.
3. Filter cases: 3–200 cited articles per decision.

The 2024 snapshot contains 3,671 articles, 1,801,481 cases, and 16.4M citation edges.

4 Method

4.1 Evaluation Protocol

Let $M \in \{0, 1\}^{|U| \times |V|}$ be the binary case-article incidence matrix and $C = M^\top M$ (with $\text{diag}(C) = 0$) the article co-citation matrix.

For each case u with cited articles S_u ($|S_u| \geq 3$), and each target $v_t \in S_u$: score all candidates $v \notin S_u \cup \{v_t\}$ and compute the rank of v_t . Since $\text{diag}(C) = 0$, the target’s self-contribution is naturally excluded.

We sample 200,000 cases per year, yielding ~ 1.8 M predictions per snapshot.

Табл. 1: Retrieval baselines on the 2024 snapshot (200K cases, 1.8M predictions, 3,671 articles).

Metric	Adamic-Adar	Common Neighbors	Degree
Hit@1	0.145	0.141	0.030
Hit@5	0.406	0.398	0.063
Hit@10	0.545	0.534	0.111
Hit@20	0.675	0.664	0.175
MRR	0.272	0.266	0.059

Табл. 2: Performance by article citation frequency (2024, Adamic-Adar).

Bin	Articles	Predictions	Hit@10	MRR
Hub (>100K)	21	298,925	0.890	0.536
High (10K–100K)	354	1,127,489	0.601	0.274
Mid (1K–10K)	864	316,972	0.138	0.074
Low (100–1K)	1,689	68,807	0.041	0.020
Rare (<100)	739	5,338	0.012	0.010

4.2 Scoring Functions

Common Neighbors: $\text{CN}(v_t \mid S) = \sum_{s \in S} C_{s,v_t}$

Adamic-Adar: $\text{AA}(v_t \mid S) = \sum_{s \in S} C_{s,v_t} / \max(\log d_s, 1)$

Degree Baseline: $\text{DG}(v_t) = d_{v_t}$ (popularity only).

4.3 Ablation Controls

To distinguish genuine temporal decay from confounds, we introduce two controls:

Fixed-Article Ablation. We identify articles with ≥ 50 citations in both 2012 (peak) and 2024 (recent), yielding a shared vocabulary. Evaluating only on this fixed set isolates temporal decay from compositional shift (new articles diluting performance).

Temporal Train/Test Split. Within each year, we build C from the first 50% of cases (by document ID) and evaluate on the second 50%. This removes data leakage: the co-citation matrix never sees evaluation cases.

5 Results

5.1 Cross-Sectional Performance (2024)

Table 1 establishes the 2024 cross-section. Co-citation methods outperform degree by $4.6\times$ on MRR, confirming that citation context provides retrieval signal beyond popularity. These numbers represent the current state of predictability – subsequent sections show they were substantially higher in earlier years.

5.2 Difficulty Spectrum

Table 2 and Figure 1 show a $50\times$ MRR gap between hub and rare articles. The 21 hub articles achieve near-perfect recovery – a consequence of their dense co-citation clusters (Section 5.7) rather




Рис. 1: Retrieval performance vs. article citation frequency. The practical difficulty frontier lies at $\sim 10K$ citations: below this, graph-based methods approach the degree baseline.

than a meaningful retrieval achievement. The practical challenge resides in the 3,650 non-hub articles that constitute 84% of predictions.

5.3 Temporal Decay: Main Finding

Figure 2 presents the central result: Adamic-Adar MRR declines from 0.47 (2012) to 0.27 (2024). The decline is monotonic after 2012 with no recovery periods. All three methods show parallel degradation, confirming a structural phenomenon rather than a scoring artifact.

5.4 Ablation: Is the Decay Real?

Table 3 reports both ablation controls. Three findings confirm the decay is genuine:

1. Fixed-article ablation (same articles, different years): MRR declines 33.2%. Since article composition is controlled, this is pure temporal decay of co-citation structure.
2. Train/test split (no data leakage): MRR declines 46.9% – stronger than the original 41.5%. The original evaluation, which builds C from all cases including the evaluation set, actually underestimates the real-world degradation.
3. Residual composition effect: the 8.3pp gap between original (41.5%) and fixed-article (33.2%) decay quantifies the contribution of compositional shift – new articles appearing in later years do account for roughly one-fifth of the observed decline.

5.5 Non-Uniform Degradation

The decay concentrates in specific frequency bands (Figure 3). Hub articles maintain $MRR > 0.5$ across all 20 years – their dense co-citation clusters are structurally robust. Mid-frequency articles (1K–10K citations) show the steepest decline: from $MRR \sim 0.15$ in 2012 to ~ 0.07 in 2024, a 53% drop.




Рис. 2: MRR over 20 years. Co-citation predictability peaks in 2011–2012 and declines monotonically. Dashed: 2017 judicial reform. Dotted: 2022 invasion.

At the individual article level (Figure 4), the majority of shared articles fall below the diagonal, but the pattern varies by legal domain.

5.6 Domain-Specific Trajectories

Figure 5 reveals that the aggregate decay masks sharply divergent domain trajectories:

- Criminal Procedure (MRR ~ 0.40 , stable): highly formulaic citation patterns that persist across reforms.
- Civil Code (0.35 $\rightarrow$ 0.15): steepest decline, reflecting evolving interpretive practice and the 2017 reform’s reorganization of civil procedure.
- Administrative Courts (post-2022 break): wartime emergency legislation disrupts established patterns.

5.7 Structural Explanation

Figure 6 explains why hub articles resist decay: they form tight intra-code clusters representing canonical citation templates (e.g., administrative procedure articles 283–285 always co-occur). These templates are procedurally mandated – courts must cite them regardless of evolving substantive law. Mid-frequency articles lack such structural protection, making their co-citation patterns vulnerable to legal evolution.

6 Discussion

Mechanisms of decay. Two complementary mechanisms drive the observed degradation: (1) Structural breaks – the 2017 judicial reform replaced old procedural codes with new ones, disrupting established co-citation patterns. This manifests as a visible inflection in Figure 5. (2) Growing diversity – as annual case volume grows from 6.4M (2016) to 8.8M (2025), the distribution over article combinations becomes more diffuse, weakening co-citation signal for non-hub provisions.

Табл. 3: Ablation comparison: decay persists under both controls, confirming genuine temporal decay of co-citation predictability.

Year	Original	Fixed-Article	Train/Test
2008	0.420	0.424	0.479
2010	0.356	0.364	0.338
2012	0.465	0.426	0.509
2014	0.368	0.358	0.322
2016	0.353	0.360	0.351
2018	0.309	0.324	0.310
2020	0.292	0.300	0.291
2022	0.280	0.291	0.279
2024	0.272	0.285	0.271
Decay (2012→2024)	41.5%	33.2%	46.9%

Practical implications. The decay rate of $\sim 3\%$ MRR/year for mid-frequency articles implies that a graph-based retrieval system loses meaningful performance within 3–4 years without retraining. For criminal procedure, static co-citation indexes remain viable; for civil and administrative law, text-based retrieval (dense embeddings, BM25 over article text) is necessary to maintain quality. The domain-specific decay rates enable targeted hybrid strategies.

Benchmark design. The train/test split ablation reveals that standard leave-one-out evaluation underestimates real-world degradation by $\sim 5\text{pp}$. We recommend that future retrieval benchmarks adopt temporal splits as the default evaluation protocol.

7 Dataset Release

UA-StatuteRetrieval is available at <https://huggingface.co/datasets/overthelex/ua-statute-retrieval>:

- `article_retrieval_performance.parquet`: per-article metrics for 3,667 articles.
- `temporal_metrics.parquet`: year-by-year metrics (2007–2026), all methods.
- `difficulty_stratification.csv`: per-bin breakdowns.

The R evaluation scripts are released alongside the paper. The underlying 502M citation records remain proprietary; the co-citation graph is available separately [7].

8 Limitations

1. Codex articles only: specific laws (by number/date) are not covered.
2. Citation $\neq$ relevance: ground truth conflates procedural and substantive citations.
3. Single jurisdiction: results may not generalize to common-law systems where stare decisis creates different citation dynamics.
4. Graph-only baselines: text-based retrievers (likely more temporally robust) are not evaluated. This is deliberate – establishing graph-method decay is a prerequisite for motivating text-based alternatives.
5. Early-year anomalies: 2007 contains retrospective imports (15 cites/case vs. 4 average), and 2009 has only 52K decisions due to political crisis. Both outliers are retained but noted.




Рис. 3: MRR by year and difficulty bin. Hub articles (top) resist decay. Mid-frequency articles (middle) show the steepest decline, particularly after 2017.

9 Conclusion

We demonstrated that co-citation predictability in legal statute retrieval is non-stationary: it decays 33–47% over 12 years depending on evaluation protocol. The decay is genuine (persists on fixed articles, strengthens without data leakage), non-uniform (concentrates in civil/administrative domains and mid-frequency articles), and practically significant ($\sim 3\%$ MRR/year loss for the articles that matter most).

These findings challenge the implicit assumption that citation structure provides stable retrieval signal. Legal information systems that rely on co-citation should implement continual graph updates, and the mid-frequency / civil-law tail should be served by complementary text-based retrieval. The released benchmark enables direct measurement of temporal robustness for any retrieval system.

Литература

- [1] Lada A. Adamic and Eytan Adar. Friends and neighbors on the web. *Social Networks*, 25(3): 211–230, 2003.
- [2] Ryan C. Barron, Maksim E. Eren, Olga M. Serafimova, Cynthia Matuszek, and Boian S. Alexandrov. Bridging legal knowledge and AI: Retrieval-augmented generation with vector stores, knowledge graphs, and hierarchical non-negative matrix factorization. In *Proceedings of AAAI Workshop on AI for Access to Justice*, 2025.
- [3] Corinna Coupette, Janis Beckedorf, Dirk Hartung, Michael Bommarito, and Daniel Martin Katz. Measuring law over time: A network analytical framework with an application to statutes and regulations in the United States and Germany. *Frontiers in Physics*, 9, 2021.
- [4] James H. Fowler, Timothy R. Johnson, James F. Spriggs, Sangick Jeon, and Paul J. Wahlbeck. Network analysis and the law: Measuring the legal importance of precedents at the U.S. Supreme Court. *Political Analysis*, 15(3):324–346, 2007.




Рис. 4: Article-level MRR: 2012 vs. 2024 for shared articles. Points below the diagonal became harder. Criminal procedure (blue) clusters near the diagonal; civil articles scatter below.

- [5] Neel Guha, Julian Nyarko, Daniel Ho, Christopher Ré, Adam Chilton, Arvind Narasimhan, et al. LegalBench: A collaboratively built benchmark for measuring legal reasoning in large language models. In *NeurIPS Datasets and Benchmarks Track*, 2023.
- [6] Justin Ho, Alexandra Colby, and William Fisher. Incorporating legal structure in retrieval-augmented generation: A case study on copyright fair use. In *Proceedings of the ACL Workshop on Natural Legal Language Processing*, 2025.
- [7] Volodymyr Keshchenko. Citation graph analysis of 99.5M Ukrainian court decisions: Co-citation structure, temporal dynamics, and community evolution. *arXiv preprint*, 2025.
- [8] David Liben-Nowell and Jon Kleinberg. The link-prediction problem for social networks. *Journal of the American Society for Information Science and Technology*, 58(7):1019–1031, 2007.
- [9] Ehsan Lotfi, Nikolay Banar, Nerses Yuzbashyan, and Walter Daelemans. Bilingual BSARD: Extending statutory article retrieval to dutch. In *Proceedings of the Natural Legal Language Processing Workshop*, 2024.
- [10] Antoine Louis, Gijs van Dijk, and Gerasimos Spanakis. Finding the law: Enhancing statutory article retrieval via graph neural networks. In *Proceedings of EACL*, 2023.
- [11] Joel Niklaus, Veton Matoshi, Pooja Rani, Andrea Galassi, Matthias Stürmer, and Ilias Chalkidis. LEXTREME: A multi-lingual and multi-task benchmark for the legal domain. In *Findings of the Association for Computational Linguistics: ACL 2023*, 2023.




Рис. 5: Per-codex MRR over time. Criminal Procedure remains stable; Civil Code degrades most. The 2017 reform creates a visible inflection in civil/administrative codes.

- [12] Shounak Paul, Pawan Goyal, and Saptarshi Ghosh. LeSICiN: A heterogeneous graph-based approach for automatic legal statute identification from indian legal documents. In Proceedings of AAAI, 2022.
- [13] Vishvaksenan Rasiah, Ronja Stern, Veton Matoshi, Matthias Stürmer, Ilias Chalkidis, Daniel E. Ho, and Joel Niklaus. SCALE: Scaling up the complexity for advanced language model evaluation. In Proceedings of the Natural Legal Language Processing Workshop, 2023.
- [14] Yanran Tang, Ruihong Qiu, Yilun Liu, Xue Li, and Zi Huang. CaseGNN++: Graph contrastive learning for legal case retrieval with graph augmentation. In Proceedings of SIGIR, 2024.
- [15] Radboud Winkels, Jelle de Ruyter, and Henryk Kroese. Determining authority of dutch case law. Legal Knowledge and Information Systems, 2011.




Рис. 6: Co-citation Jaccard similarity among the 20 most-cited articles (2024). Block-diagonal structure reflects procedural “citation templates” that resist temporal change.