

**Overture Technical Report Series
No. TR-005**

December 2020

Guidelines for using VDM Combinatorial Testing Features

by

Nick Battle
Peter Gorm Larsen





Document history

Month	Year	Version	Version of Overture.exe	Comment
December	2010	0.1	3.0.2	Initial version

Contents

1	Introduction	1
1.1	What is Combinatorial Testing?	1
1.2	The Structure of this Document	2
2	Working with Traces	3
2.1	Basic Trace Constructs	3
2.2	Using Variables	8
2.3	Tests with Errors	14
2.4	Trace Reduction	16
2.5	How Does Trace Expansion Work?	18
2.6	Language Considerations	20
2.6.1	Traces in VDM-SL	20
2.6.2	Traces in VDM++ and VDM-RT	22
2.6.3	Expansion and Execution Considerations	22
3	Combinatorial Testing Patterns	25
3.1	Traces and Test Operations	25
3.2	Common Patterns	26
3.2.1	Sets for “let” bindings	26
3.2.2	Bracketing operations with headers and trailers	27
3.2.3	Graph searching by traces	27
3.2.4	Building data in stages	27
3.2.5	Oracle functions	27
3.2.6	Using positive and negative sense checks	27
3.3	Avoiding Test Explosions	27
4	Combinatorial Testing Examples	29
4.1	The LUHN Check Digit Model	29
4.2	The Basket Service Model	29
A	Combinatorial Testing Syntax	31
B	Overture Screenshots	33



C	Example Model Listings	35
C.1	The LUHN Check Digit Model	35
C.2	The Basket Service Model	35



Chapter 1

Introduction

This manual is a complete guide the combinatorial testing of VDM models. It assumes the reader has no prior knowledge of combinatorial testing, but a working knowledge of VDM, in particular, the VDM++ and VDM-SL dialects.

1.1 What is Combinatorial Testing?

Creating a comprehensive set of tests for VDM specifications can be a time consuming process. To try to make the generation of test cases simpler, Overture provides a VDM language extension (for all dialects) called Combinatorial Testing [Nie&11, Larsen&10].

In general, specifications are tested to verify that certain properties or behaviours are met, as specified by constraints in the specification and validation conjectures in the tests.

The simplest way to test a specification is to write ad-hoc tests, starting from a known system state and proceeding with a sequence of operation calls that should move to a new state or produce some particular result or error response. The problem with this kind of testing is that it can be very laborious to produce the number of tests needed to cover the complete system behaviour. It is also expensive to maintain a large test suite as the specification evolves.

The most complete way to test a specification is to produce a formal mathematical proof that it will never violate its constraints, and always meet its validation conjectures if presented with a legal sequence of operation calls. This provides the highest level of confidence in the correctness of a specification, but it can be unrealistic to produce a complete formal proof for complex specifications, even with tool support [Paulson97, Bicarregui&94].

Model checking provides an approach to formal testing that is considerably better than ad-hoc testing but not as complete as formal proof [Clarke&99]. This approach uses a formal specification of the system properties desired, often written in a temporal calculus, and the model checker symbolically executes the specification searching for execution paths that violate the constraints. Since the execution is symbolic, extremely large state spaces can be searched (billions of cases is not uncommon), and failed cases can produce a “counter example” that demonstrates the failure. This is a very powerful technique, but in practice, realistic specifications often produce a state space explosion that is too great for model checkers.



Combinatorial testing is an approach that is far more powerful than ad-hoc testing, but not as complete as model checking. Tests are produced automatically from “**traces**” that are relatively simple to define. The approach allows specifications to be tested with perhaps millions of test cases, but cannot guarantee to catch every corner case in the way that a model checker can. Therefore the technique is useful for specifications that are too complex for model checking or formal proof.

A combinatorial trace is a pattern that describes the construction of argument values and the sequences of operation calls that will exercise the specification. A specification may contain several traces, each designed to test a particular aspect. Traces are automatically expanded into a (potentially large) number of tests, each of which is a particular sequence of operation calls and argument values. The execution of tests is performed automatically, starting each in a known state; a test is considered to pass if it does not violate the specification’s constraints, or the test’s validation conjectures. Individual failed tests can be executed in isolation to find out why they failed, which is similar to a model checker’s counter example.

1.2 The Structure of this Document

The document is intended to be read sequentially, but readers who are familiar with the basics of VDM traces can skip Chapter 2 and go straight to the patterns in Chapter 3.

- Chapter 2, Working with Traces introduces the concept of a combinatorial test and explains how to work with traces in VDM.
- Chapter 3, Combinatorial Testing Patterns looks at common ways of using traces that are useful in many different situations.
- Chapter 4, Combinatorial Testing Examples uses two more significant specifications to demonstrate typical usage of traces in real life.
- Appendix A, Combinatorial Testing Syntax defines the formal grammar of traces.
- Appendix B, Overture Screenshots includes screen shots of the Combinatorial Testing perspective in Overture.
- Appendix C, Example Model Listings contains the full listings of the models explored in Chapter 4.

Chapter 2

Working with Traces

2.1 Basic Trace Constructs

Combinatorial tests are embedded within a VDM specification using a section called “**traces**”. Typically, one or more traces are added to a separate class or module that is intended for testing rather than the main specification, though you can add traces to any class you wish. In this chapter, we will use the example classes below:

```
class Counter
instance variables
    total:int := 0;

operations
    public inc: () ==> int
    inc() == ( total := total + 1; return total; )

    public dec: () ==> int
    dec() == ( total := total - 1; return total; )

end Counter

class Tester
instance variables
    obj:Counter := new Counter();

traces
    T1: obj.inc();

end Tester
```

Notice that there are two classes, Counter and Tester. The Counter class defines a



simple operation that increments and decrements a total state value that is initially zero. The `Tester` class creates an instance of `Counter` and defines a single trace called `T1`. Trace names are simple identifiers, optionally separated by slashes (e.g. `item456/interface/all`). This example is the simplest trace possible and indicates that the trace should expand to a single test that just calls `obj.inc()`.

This trace can either be executed in Overture in the Combinatorial Testing perspective (see Appendix B), or it can be executed from the command line using the `runtrace` command. The command line output is illustrated here for simplicity:

```
> runtrace Tester'T1
Generated 1 tests in 0.004 secs.
Test 1 = obj.inc()
Result = [1, PASSED]
Executed in 0.007 secs.
All tests passed
```

The first line of output indicates that one test has been generated from the trace. With more complex examples, this generation could expand to thousands or millions of tests, and consequently it may take a few seconds.

The next line of the output describes the test that was generated. Note that this is called “Test 1”, and consists of a single call to `obj.inc()`.

The line below the test gives the result of executing that test. There is a single return value from the call to `obj.inc()`, 1, which is listed along with the word “PASSED” that indicates that there were no constraint violations in the test execution.

Lastly the time taken to execute all of the tests is given, and an indication of whether any tests failed.

The reason that this trace only expands to a single test is that the trace, when considered as a pattern, only matches a single operation call. But if we change the trace to the following:

```
traces
T1: obj.inc() | obj.dec();
```

The trace is now saying that it would match either a call to `obj.inc()` or a call to `obj.dec()`. Therefore the test expansion produces the following:

```
> runtrace Tester'T1
Generated 2 tests
Test 1 = obj.inc()
Result = [1, PASSED]
Test 2 = obj.dec()
Result = [-1, PASSED]
Executed in 0.033 secs.
```



```
All tests passed
```

This time two tests are generated. The first calls `obj.inc()`, the second `obj.dec()`. Notice that the decrement test is completely separate from the increment test. It produces `-1` as its result, because the `Counter` object is re-created for each test. It does not decrement the counter back to zero after the first test incremented it.

If we want to test an increment followed by a decrement, that would be expressed using a semi-colon separator:

traces

```
T1: obj.inc(); obj.dec();
```

This produces the output:

```
Generated 1 tests
Test 1 = obj.inc(); obj.dec()
Result = [1, 0, PASSED]
Executed in 0.027 secs.
All tests passed
```

This generates a single test again, but you can see that the test involves two calls and that they return 1 and 0, respectively. So this time the second call is operating on the same object instance as the first.

If the increment and decrement operations are independent, it makes sense to test calls to them in either order, which would be expressed as:

traces

```
T1: || ( obj.inc(), obj.dec() );
```

Notice that the separator has changed to a comma. That produces the output:

```
Generated 2 tests
Test 1 = obj.inc(); obj.dec()
Result = [1, 0, PASSED]
Test 2 = obj.dec(); obj.inc()
Result = [-1, 0, PASSED]
Executed in 0.029 secs.
All tests passed
```

So now both orderings of the two calls are produced. This is because there are two orderings that match the pattern `|| (..., ...)`. This particular trace construct naturally expands to an arbitrary number of calls and produces a test for every permutation of the calls in brackets.



But what if some tests are a pair of calls and some are not? If we want to make a call optional, the ? operator can be added to any operation call (i.e. not just within || operators) to indicate that this will match tests where the call is made and where it is not. For example:

traces

```
T1: || ( obj.inc(), obj.dec()? );
```

This means that the decrement call is optional and so although it is included in the orderings of the pair, it should also be absent in some cases. This example produces the following:

```
Generated 4 tests
Test 1 = obj.inc(); skip
Result = [1, (), PASSED]
Test 2 = obj.inc(); obj.dec()
Result = [1, 0, PASSED]
Test 3 = skip; obj.inc()
Result = [(), 1, PASSED]
Test 4 = obj.dec(); obj.inc()
Result = [-1, 0, PASSED]
Executed in 0.043 secs.
All tests passed
```

You see that the decrement call is sometimes present and sometimes replaced by **skip**, which indicates the absence of an optional call. Notice also that the || operator and the ? operator work together to combine their effects in this example, though ? can be used for any operation call.

Along the same lines as ?, it is possible to add * and + operators to any call, which indicate that it should be called zero or more times, and one or more times. The maximum number of times is a tool preset value that defaults to 5, though it can be changed. So for example:

traces

```
T1: obj.inc()*;
T2: obj.dec()+;
```

```
> runtrace Tester`T1
Generated 6 tests
Test 1 = skip
Result = [(), PASSED]
Test 2 = obj.inc()
Result = [1, PASSED]
Test 3 = obj.inc(); obj.inc()
Result = [1, 2, PASSED]
Test 4 = obj.inc(); obj.inc(); obj.inc()
```



```
Result = [1, 2, 3, PASSED]
Test 5 = obj.inc(); obj.inc(); obj.inc(); obj.inc()
Result = [1, 2, 3, 4, PASSED]
Test 6 = obj.inc(); obj.inc(); obj.inc(); obj.inc(); obj.inc()
Result = [1, 2, 3, 4, 5, PASSED]
Executed in 0.046 secs.
All tests passed

> runtrace Tester`T2
Generated 5 tests
Test 1 = obj.dec()
Result = [-1, PASSED]
Test 2 = obj.dec(); obj.dec()
Result = [-1, -2, PASSED]
Test 3 = obj.dec(); obj.dec(); obj.dec()
Result = [-1, -2, -3, PASSED]
Test 4 = obj.dec(); obj.dec(); obj.dec(); obj.dec()
Result = [-1, -2, -3, -4, PASSED]
Test 5 = obj.dec(); obj.dec(); obj.dec(); obj.dec(); obj.dec()
Result = [-1, -2, -3, -4, -5, PASSED]
Executed in 0.042 secs.
All tests passed
```

The important difference between these two is that T1 includes an extra **skip** case, whereas T2 does not.

Lastly, it is possible to indicate a specific number of repetitions of a call or a range of repetitions. For example:

traces

```
T1: obj.inc(){3};
T2: obj.dec(){2, 4};
```

```
> runtrace Tester`T1
Generated 1 tests
Test 1 = obj.inc(); obj.inc(); obj.inc()
Result = [1, 2, 3, PASSED]
Executed in 0.026 secs.
All tests passed

> runtrace Tester`T2
Generated 3 tests
Test 1 = obj.dec(); obj.dec()
Result = [-1, -2, PASSED]
```



```
Test 2 = obj.dec(); obj.dec(); obj.dec()
Result = [-1, -2, -3, PASSED]
Test 3 = obj.dec(); obj.dec(); obj.dec(); obj.dec()
Result = [-1, -2, -3, -4, PASSED]
Executed in 0.01 secs.
All tests passed
```

The T1 trace now produces a single test with precisely three repetitions, while the T2 trace gives three tests with 2, 3 and 4 repetitions respectively.

If you combine a `||` operator with a repetition, the result is to repeat all of the possibilities of the permutation with the given number of repetitions. For example:

traces

```
T1: || ( obj.inc(), obj.dec() ) {2};
```

```
> runtrace Tester`T1
Generated 4 tests
Test 1 = obj.inc(); obj.dec(); obj.inc(); obj.dec()
Result = [1, 0, 1, 0, PASSED]
Test 2 = obj.dec(); obj.inc(); obj.inc(); obj.dec()
Result = [-1, 0, 1, 0, PASSED]
Test 3 = obj.inc(); obj.dec(); obj.dec(); obj.inc()
Result = [1, 0, -1, 0, PASSED]
Test 4 = obj.dec(); obj.inc(); obj.dec(); obj.inc()
Result = [-1, 0, -1, 0, PASSED]
Executed in 0.038 secs.
All tests passed
```

Here, the `||` operator produces `(inc, dec)` and `(dec, inc)`; then the repetition doubles this, but it doubles every combination of the two rather than simply repeating each one twice.

2.2 Using Variables

So far, the trace examples have called operations that do not include any arguments. Arguments can be passed as literals, but traces also provide the means to define variables that can change value as tests are generated from a trace.

If we overload the example increment and decrement operations with versions that take an integer parameter, by which to change the counter, we can write traces like this:

```
...
public inc: int ==> int
```



CHAPTER 2. WORKING WITH TRACES

```
inc(i) == ( total := total + i; return total; );
```

```
public dec: int ==> int  
dec(i) == ( total := total - i; return total; )
```

traces

```
T1:  
    let a in set {1, ..., 10} be st a mod 2 = 0 in  
        obj.inc(a);
```

```
> runtrace Tester'T1  
Generated 5 tests  
Test 1 = obj.inc(2)  
Result = [2, PASSED]  
Test 2 = obj.inc(4)  
Result = [4, PASSED]  
Test 3 = obj.inc(6)  
Result = [6, PASSED]  
Test 4 = obj.inc(8)  
Result = [8, PASSED]  
Test 5 = obj.inc(10)  
Result = [10, PASSED]  
Executed in 0.04 secs.  
All tests passed
```

In a standard VDM specification, the **let...be st** expression would choose an arbitrary element from the set that meets the **st** clause. But in a trace context, this looseness is used as a pattern that expands to a test covering each possible set value that would match. Notice that the tests list the actual value of the argument passed, rather than the symbolic name, “a”.

A trace can include multiple **let** clauses, but if these are nested, then the trace expands to the *combination* of the variables. For example:

traces

```
T1:  
    let a in set {1, 2, 3} in  
        let b in set {4, 5, 6} in  
            ( obj.inc(a); obj.dec(b) );
```

```
> runtrace Tester'T1  
Generated 9 tests  
Test 1 = obj.inc(1); obj.dec(4)
```



```
Result = [1, -3, PASSED]
Test 2 = obj.inc(1); obj.dec(5)
Result = [1, -4, PASSED]
Test 3 = obj.inc(1); obj.dec(6)
Result = [1, -5, PASSED]
Test 4 = obj.inc(2); obj.dec(4)
Result = [2, -2, PASSED]
Test 5 = obj.inc(2); obj.dec(5)
Result = [2, -3, PASSED]
Test 6 = obj.inc(2); obj.dec(6)
Result = [2, -4, PASSED]
Test 7 = obj.inc(3); obj.dec(4)
Result = [3, -1, PASSED]
Test 8 = obj.inc(3); obj.dec(5)
Result = [3, -2, PASSED]
Test 9 = obj.inc(3); obj.dec(6)
Result = [3, -3, PASSED]
Executed in 0.066 secs.
All tests passed
```

This example produces a test for every combination of “a” and “b” values, which is therefore nine tests. The round brackets are needed around the pair of operation calls because a call binds tightly to the **let**. Without the brackets, you get the following scope error, referring to the “a” in the second call to `obj.dec(a)`:

```
traces
  T1:
    let a in set {6, 7, 10} in
      obj.inc(a); obj.dec(a)
```

```
Error 3182: Name 'Tester'a' is not in scope in 'Tester' (example.vpp) at line 28:29
Type checked 2 classes in 0.12 secs. Found 1 type error
```

Note also that the variables defined are in scope throughout the clauses below, so the “a” variable could be used to define the set of “b” values:

```
traces
  T1:
    let a in set {1, 2, 3} in
      let b in set {a, ..., a + 2} in
        ( obj.inc(a); obj.dec(b) );
```



```
> runtrace Tester`T1
Generated 9 tests
Test 1 = obj.inc(1); obj.dec(1)
Result = [1, 0, PASSED]
Test 2 = obj.inc(1); obj.dec(2)
Result = [1, -1, PASSED]
Test 3 = obj.inc(1); obj.dec(3)
Result = [1, -2, PASSED]
Test 4 = obj.inc(2); obj.dec(2)
Result = [2, 0, PASSED]
Test 5 = obj.inc(2); obj.dec(3)
Result = [2, -1, PASSED]
Test 6 = obj.inc(2); obj.dec(4)
Result = [2, -2, PASSED]
Test 7 = obj.inc(3); obj.dec(3)
Result = [3, 0, PASSED]
Test 8 = obj.inc(3); obj.dec(4)
Result = [3, -1, PASSED]
Test 9 = obj.inc(3); obj.dec(5)
Result = [3, -2, PASSED]
Executed in 0.059 secs.
All tests passed
```

If two variables should take values from the same set of values, it is possible to use a multiple bind in a trace, but not a bind list. For example:

```
traces
  T1:
    let a, b in set {1, 2, 3} in
      ( obj.inc(a); obj.dec(b) );
```

```
> runtrace Tester`T1
Generated 9 tests
Test 1 = obj.inc(1); obj.dec(1)
Result = [1, 0, PASSED]
Test 2 = obj.inc(2); obj.dec(1)
Result = [2, 1, PASSED]
Test 3 = obj.inc(3); obj.dec(1)
Result = [3, 2, PASSED]
Test 4 = obj.inc(1); obj.dec(2)
Result = [1, -1, PASSED]
Test 5 = obj.inc(2); obj.dec(2)
```




```
Result = [2, 0, PASSED]
Test 6 = obj.inc(3); obj.dec(2)
Result = [3, 1, PASSED]
Test 7 = obj.inc(1); obj.dec(3)
Result = [1, -2, PASSED]
Test 8 = obj.inc(2); obj.dec(3)
Result = [2, -1, PASSED]
Test 9 = obj.inc(3); obj.dec(3)
Result = [3, 0, PASSED]
Executed in 0.061 secs.
All tests passed
```

As well as defining a variable value from a set, variables can be used to simplify calculations that would otherwise have to be made in the arguments to operation calls. These simpler **let** definitions do not increase the number of tests generated from the trace, they just introduce new names in the scope that follows. Multiple variable definitions can be declared in one **let** expression. For example:

traces

```
T1:
    let a in set {1, 2, 3} in
        let b = a + 1, c = a - 1 in
            ( obj.inc(b); obj.dec(c) );
```

```
> runtrace Tester'T1
Generated 3 tests
Test 1 = obj.inc(2); obj.dec(0)
Result = [2, 2, PASSED]
Test 2 = obj.inc(3); obj.dec(1)
Result = [3, 2, PASSED]
Test 3 = obj.inc(4); obj.dec(2)
Result = [4, 2, PASSED]
Executed in 0.054 secs.
All tests passed
```

If repetitions are added to a clause within a **let** body, they bind tightly to the operation call rather than the entire **let** clause. If you want to repeat the entire **let**, you have to bracket the whole clause and add a repetition to that. For example:

traces

```
T1:
    let a in set {1, 2, 3} in
```



```
obj.inc(a){1, 2}
T2:
  ( let a in set {1, 2, 3} in
    obj.inc(a) ){1, 2}
```

```
> runtrace Tester`T1
Generated 6 tests
Test 1 = obj.inc(1)
Result = [1, PASSED]
Test 2 = obj.inc(1); obj.inc(1)
Result = [1, 2, PASSED]
Test 3 = obj.inc(2)
Result = [2, PASSED]
Test 4 = obj.inc(2); obj.inc(2)
Result = [2, 4, PASSED]
Test 5 = obj.inc(3)
Result = [3, PASSED]
Test 6 = obj.inc(3); obj.inc(3)
Result = [3, 6, PASSED]
Executed in 0.044 secs.
All tests passed

> runtrace Tester`T2
Generated 12 tests
Test 1 = obj.inc(1)
Result = [1, PASSED]
Test 2 = obj.inc(2)
Result = [2, PASSED]
Test 3 = obj.inc(3)
Result = [3, PASSED]
Test 4 = obj.inc(1); obj.inc(1)
Result = [1, 2, PASSED]
Test 5 = obj.inc(2); obj.inc(1)
Result = [2, 3, PASSED]
Test 6 = obj.inc(3); obj.inc(1)
Result = [3, 4, PASSED]
Test 7 = obj.inc(1); obj.inc(2)
Result = [1, 3, PASSED]
Test 8 = obj.inc(2); obj.inc(2)
Result = [2, 4, PASSED]
Test 9 = obj.inc(3); obj.inc(2)
Result = [3, 5, PASSED]
Test 10 = obj.inc(1); obj.inc(3)
```



```
Result = [1, 4, PASSED]
Test 11 = obj.inc(2); obj.inc(3)
Result = [2, 5, PASSED]
Test 12 = obj.inc(3); obj.inc(3)
Result = [3, 6, PASSED]
Executed in 0.03 secs.
All tests passed
```

The difference may seem subtle, but the effect is significant. T1 behaves like a simple “{1, 2}” repetition for each of the **let** values, whereas T2 produces either one or two cases from the *entire set* created by the **let** clause.

Although the example above uses a **let** <set bind> expression, it is also possible to use a **let** <seq bind> or **let** <type bind>. In a trace context, the ordering that a sequence bind carries does not affect the generation of tests; if the example had **let** a **in seq** [1, 2, 3], the same tests would be generated, and since tests are independent their order is not meaningful. So sequence binds are not particularly useful in traces. However type binds (of finite types) are a shorthand for “all values of this type”, which can be useful in some circumstances. This is covered later in Chapter 3.

2.3 Tests with Errors

The examples so far have only includes tests that **PASSED**. This means that they completed the sequence of operation calls without violating any pre-conditions, post-conditions, state invariants, type invariants, recursive measures or dynamic type checks.

If a sequence of operations causes a post-condition failure, then it is certain that there is a problem with the specification - it should not be possible to provoke a post-condition failure with a set of legal calls (ie. ones which pass the pre-conditions and type invariants). On the other hand, if a sequence of operations violates a pre-condition, or a type or class invariant, then it is *possible* that the specification has a problem, but it is also possible that the test itself is at fault (passing illegal values).

The combinatorial testing environment indicates the exit status of the test in the verdict returned in the last item of the results (all **PASSED** above). So if pre/post/invariant conditions are violated during a test, this may be set to **FAILED** or **INDETERMINATE**¹. If a test fails, then any subsequent test which starts *with the same sequence of calls* as the failed sequence will also fail. These tests are filtered out of the remaining test sequence automatically, and not executed.

For example, if we introduce a pre- and postcondition into our example, we see this behaviour:

```
...
public inc: int ==> int
inc(i) == ( total := total + i; return total; )
```

¹The tools sometimes call this **INCONCLUSIVE**



```

pre i < 10
post total < 20;

traces
  T1:
    let a in set {6, 7, 10} in
      obj.inc(a){1, 5}

```

```

> runtrace Tester'T1
Generated 15 tests
Test 1 = obj.inc(6)
Result = [6, PASSED]
Test 2 = obj.inc(6); obj.inc(6)
Result = [6, 12, PASSED]
Test 3 = obj.inc(6); obj.inc(6); obj.inc(6)
Result = [6, 12, 18, PASSED]
Test 4 = obj.inc(6); obj.inc(6); obj.inc(6); obj.inc(6)
Result = [6, 12, 18, Error 4072: Postcondition failure: post_inc in 'Counter' at line 15:16, FAILED]
Test 5 = obj.inc(6); obj.inc(6); obj.inc(6); obj.inc(6); obj.inc(6)
Test 5 FILTERED by test 4
Test 6 = obj.inc(7)
Result = [7, PASSED]
Test 7 = obj.inc(7); obj.inc(7)
Result = [7, 14, PASSED]
Test 8 = obj.inc(7); obj.inc(7); obj.inc(7); obj.inc(7)
Result = [7, 14, Error 4072: Postcondition failure: post_inc in 'Counter' at line 15:16, FAILED]
Test 9 = obj.inc(7); obj.inc(7); obj.inc(7); obj.inc(7)
Test 9 FILTERED by test 8
Test 10 = obj.inc(7); obj.inc(7); obj.inc(7); obj.inc(7); obj.inc(7)
Test 10 FILTERED by test 8
Test 11 = obj.inc(10)
Result = [Error 4071: Precondition failure: pre_inc in 'Counter' at line 14:11, INCONCLUSIVE]
Test 12 = obj.inc(10); obj.inc(10)
Test 12 FILTERED by test 11
Test 13 = obj.inc(10); obj.inc(10); obj.inc(10); obj.inc(10)
Test 13 FILTERED by test 11
Test 14 = obj.inc(10); obj.inc(10); obj.inc(10); obj.inc(10)
Test 14 FILTERED by test 11
Test 15 = obj.inc(10); obj.inc(10); obj.inc(10); obj.inc(10); obj.inc(10)
Test 15 FILTERED by test 11
Executed in 0.075 secs.
Some tests failed or indeterminate

```

The `inc` operation now has a pre-condition that the argument must be less than 10 and a postcondition that the resulting total must be less than 20. The trace makes 1 to 5 calls to the `inc` operation with arguments 6, 7 and 10, respectively.

The first three tests are fine, but Test 4 fails because the fourth call to `inc(6)` pushes the total over the limit. This is therefore a post-condition `FAILED` test, and the error message is listed along with the results of the earlier operation calls. Test 5 then tries to do the same, but adds a further call. This must fail in the same place as Test 4, because Test 4 is the “stem” of Test 5. Therefore this test is “`FILTERED` by Test 4”. Similarly, Test 8 fails and Tests 9 and 10 are filtered by this failure.

Test 11 fails on the first call to `inc(10)`, since the argument must be less than 10. This



produces an `INDETERMINATE` error because we are not sure whether this is a problem with the trace or the specification being tested. Lastly, Tests 12 to 15 are filtered by Test 11, since they would behave the same way.

At the end of the run, the `runtrace` command indicates that some tests failed or were indeterminate, just to remind you.

2.4 Trace Reduction

A trace may expand to many millions of tests and these may take many hours to execute. This can make large traces difficult to work with, both while the trace is being developed and subsequently when traces are used to check that a change to a specification is sound.

Therefore the trace system provides the means to reduce the number of tests that are generated. This limited number can then be checked more quickly, which naturally does not provide the confidence of a full execution, but is convenient to work with when a sample of tests is sufficient.

Trace reduction can be achieved in four different ways:

- *RANDOM* reduction. This is the simplest kind of reduction, and is used to randomly select tests from the full set. For example, a 1% *RANDOM* reduction of a trace that expands to a million tests would select 10,000 tests from the set. The pseudorandom selection is seeded, so that a consistent subset of the tests can be selected.
- *SHAPES_NOVARS* reduction. The “shape” of a test means the sequence of operation names (regardless of arguments passed), and the idea of shaped reduction is to preserve *at least one test* of every shape in the full set. So for example, a test that calls `[opA(1), opB(2), opC(3)]` would be considered the same shape as a test that calls `[opA(111), opB(222), opC(333)]`, but different to a test that calls `[opX(1), opY(2)]`. So a shaped reduction of 1% of one million tests would try to select 10,000 tests, but it also guarantees to include at least one test of every shape within the million, even if that means the reduction is (say) 1.5%.
- *SHAPES_VARVALUES* reduction. The simple interpretation of a shape above only looks at the names of the operations called. This second kind of shaped reduction looks at the variable names used in the `let` bindings and constants as well as the names of the operations. So with this kind of reduction, `[opA(a), opA(b)]` is different to `[opA(x), opA(y)]`, even if the values of “a” and “x” can sometimes be the same. Typically, different variable names are used in different parts of a complex trace and so this reduction method is trying to select all of the different parts of a trace, even if the sequence of operation names produced is the same as another part of the trace.
- *SHAPES_VARVALUES* reduction. The third type of shaped reduction is even more specific about what constitutes a shape, taking into account the *value* of the variables used as well as their names. So `[opA(a)]` will be considered a different shape to another `[opA(a)]` elsewhere, as long as “a” is bound to a different value.



The following simple trace, using the `Counter` example from previous chapters, illustrates RANDOM reduction:

```
traces
  T1:
      let a in set {1, ..., 1000} in
      let b in set {1, ..., 1000} in
          ( obj.inc(a); obj.dec(b) );
```

```
> filter
Usage: filter %age | RANDOM | SHAPES_NOVARS | SHAPES_VARVALUES | SHAPES_VARVALUES
Trace filter currently 100.0% NONE (seed 0)

> filter random
Trace filter currently 100.0% RANDOM (seed 0)

> filter 1
Trace filter currently 1.0% RANDOM (seed 0)

> seedtrace 1234
Seed now set to 1234

> runtrace Tester`T1
Generated 1000000 tests, reduced to 10000, in 1.571 secs.
Test 66 = obj.inc(1); obj.dec(66)
Result = [1, -65, PASSED]
Test 155 = obj.inc(1); obj.dec(155)
Result = [1, -154, PASSED]
Test 323 = obj.inc(1); obj.dec(323)
Result = [1, -322, PASSED]
Test 419 = obj.inc(1); obj.dec(419)
Result = [1, -418, PASSED]
...
Test 999815 = obj.inc(1000); obj.dec(815)
Result = [1000, 185, PASSED]
Test 999894 = obj.inc(1000); obj.dec(894)
Result = [1000, 106, PASSED]
Test 999992 = obj.inc(1000); obj.dec(992)
Result = [1000, 8, PASSED]
Executed in 4.932 secs.
```

The “filter” and “seedtrace” commands are used to set the filtering required, then the trace is executed as normal. But we see that the million tests have been reduced to 10,000 (taking a few seconds). Then instead of trying every combination of “a” and “b”, the filtering selects them at random, starting with $a = 1$, $b = 65$ and ending with $a = 1000$, $b = 992$.

The next example illustrates shaped reduction. The trace joins together two `let` bindings, repeating each call once and twice. This would normally produce 36 tests.

```
traces
  T1:
      let a in set {1, 2, 3} in obj.inc(a){1,2};
      let b in set {1, 2, 3} in obj.dec(b){1,2}
```



```
> filter 1
Trace filter currently 1.0% RANDOM (seed 0)

> filter shapes_novars
Trace filter currently 1.0% SHAPES_NOVARS (seed 0)

> rt Tester`T1
Generated 36 tests, reduced by SHAPES_NOVARS, in 0.001 secs.
Test 1 = obj.inc(1); obj.dec(1)
Result = [1, 0, PASSED]
Test 2 = obj.inc(1); obj.inc(1); obj.dec(1)
Result = [1, 2, 1, PASSED]
Test 7 = obj.inc(1); obj.dec(1); obj.dec(1)
Result = [1, 0, -1, PASSED]
Test 8 = obj.inc(1); obj.inc(1); obj.dec(1); obj.dec(1)
Result = [1, 2, 1, 0, PASSED]
Executed in 0.006 secs.
All tests passed
>
```

Here, we try to reduce this to 1%, but using the SHAPES_NOVARS option. A reduction of 1% of 36 tests ought to produce a single test (reduction will never produce zero tests), but in fact the shaped reduction produces four. You can see that there is one case of each “shape”: one inc and one dec; two incs and one dec, and so on. So the idea is that the shaped reduction has given a representative sample of all of the possible shapes, disregarding variable names or values.

Reducing this trace using SHAPES_VARVALUES produces the same number of shapes, since the two calls always use the same variable names. But reduction using SHAPES_VARVALUES regards all of the tests as different shapes, because the variable/value/operation combinations are different in all of the tests.

In practice, the most useful reductions are RANDOM and SHAPES_NOVARS. Random reductions give a simple way to cut down a large number of tests. Shaped reduction is choosing one example of every “path” that the trace is taking the specification through, which is often closely related to the different use cases that the system has.

2.5 How Does Trace Expansion Work?

The sections above have given an overview of all the trace operators, and there are some examples of combinations of operators. But to see how traces are expanded in general, we need to look at traces from a different point of view. The syntax of traces is deliberately made similar to the syntax



of VDM-SL, but to understand how operators combine to produce multiple tests, it helps to look at operators as though they followed a separate “expansion” grammar. In the description that follows, a `set` is a set of tests:

- `set = object.opname(args)`. The simplest form of a trace is a set that comprises a single call to an operation or function with arguments. The arguments can be symbolic, and bound to various values by the `let` operator described below.
- `set = set1; set2; ...; setn`. A set of tests may be formed from an ordered sequence of sets. This expands to all possible selections of one test from each of the sets. In its simplest form, this could be a sequence of operation calls which therefore just expands to one test. But a combination of sets of tests results in a set of the product of the sizes of those sets.
- `set = set1 ?`. A set of tests may be formed from another set with a `?` operator. This produces the same set, but includes a “skip” step.
- `set = set1 {n[, n]}`. A set of tests may be formed from another set with a `{n}` or `{n1, n2}` operator. This produces a set with every member of the original set repeated `n` times, or between `n1` and `n2` times (inclusive).
- `set = set1 *|+`. A set of tests may be formed from another set with a `*` or `+` operator. This produces another set with every member of the original set repeated from 0 to `N` times (with `*`) or 1 to `N` times (with `+`). The value of `N` is tool dependent, but defaults to 5.
- `set = set1 | set2 | ... | setn`. A set of tests may be formed by combining a number of other test sets with a `|` operator. This produces a set with the union of the other sets.
- `set = || (set1, set2, ..., setn)`. A set may be formed from the permutations of a number of other sets. This produces a set with each permutation of each selection of one test from each set.
- `set = let <multiple bind> [be st <cond>] in set1`. A set of tests may be formed from a `multiple bind`, which expands to the substitution of all the possible the bound values in the original set.
- `set = let <name> = <exp> [, <name2> = <exp2>, ...] in set1`. A set of tests may be evaluated in a scope that defines `name/value` pairs. This does not increase the number of tests in the set, but just binds free variables.

For example, if (for brevity) we say that a test with a single call to `obj.opA()` is written as “[A]”, and similarly “[B]” and “[C]” for other operation calls, and “[−]” for a skip, then we can say the following trace operators produce these sets of tests:



```

A? = { [A], [-] }
A;B = { [AB] }
A;B? = { [AB], [A] }
A* = { [-], [A], [AA], [AAA], [AAAA], [AAAAA], ... }
A+ = { [A], [AA], [AAA], [AAAA], [AAAAA], ... }
A{3} = { [AAA] }
A{1,3} = { [A], [AA], [AAA] }
A | B = { [A], [B] }
A | B? = { [A], [B], [-] }
|| (A, B, C) = { [ABC], [ACB], [BAC], [BCA], [CAB], [CBA] }
|| (A, (B;C)) = { [ABC], [BCA] }
|| (A, B+) = { [AB], [BA], [ABB], [BBA], [ABBB], [BBBA], ... }
let a in set {1,2,3} in A(a) = { [A(1)], [A(2)], [A(3)] }
let b : bool * bool in B(b) = {
    [B(mk_(true, true))], [B(mk_(true, false))],
    [B(mk_(false, true))], [B(mk_(false, false))]
}
let z = 1 in B(z) = { [B(1)] }

```

Note that the repeat limits in a trace (like $\{1,3\}$) must be numeric literals. But values in a multiple bind set or sequence can be variables, either bound earlier in the trace or other fields within scope of the trace inside the object or module where it is defined. Similarly, the values in the right hand side of let definitions can be variables within the trace or the object/module scope.

2.6 Language Considerations

Combinatorial tests are available for both VDM-SL and VDM++/VDM-RT. The process of trace expansion and execution is very similar in all cases, but there are some differences that are described below.

2.6.1 Traces in VDM-SL

Traces are added in a “traces” section within a VDM-SL specification. This can either be within one or more modules or within a flat specification. The name of the traces in a module are implicitly exported, so they are referred to as `<module name> `<trace name>`. You can omit the module name if it is the default module.

The VDM-SL specification that is equivalent to the example used above is like this:

```

module Counter
exports all
definitions

```



```

state S of
    total:int
init s == s = mk_S(0)
end

operations
    inc: int ==> int
    inc(i) == ( total := total + i; return total; )

    dec: int ==> int
    dec(i) == ( total := total - i; return total; )
end Counter

module Tester
imports from Counter all
definitions

traces
    T1: Counter'inc(1)*;

end Tester

```

And in the VDM-SL command line, that would be executed as follows. Note that `Tester` is not the default module, so the trace name is qualified:

```

> modules
Counter (default)
Tester
> runtrace Tester'T1
Generated 6 tests in 0.002 secs.
Test 1 = skip
Result = [()], PASSED]
Test 2 = inc(1)
Result = [1, PASSED]
Test 3 = inc(1); inc(1)
Result = [1, 2, PASSED]
Test 4 = inc(1); inc(1); inc(1)
Result = [1, 2, 3, PASSED]
Test 5 = inc(1); inc(1); inc(1); inc(1)
Result = [1, 2, 3, 4, PASSED]
Test 6 = inc(1); inc(1); inc(1); inc(1); inc(1)
Result = [1, 2, 3, 4, 5, PASSED]
Executed in 0.019 secs.
All tests passed
>

```

This trace is very similar to the VDM++ example. The `Counter` module has a single state that is equivalent to the VDM++ “total” instance variable. Note that this is reset to zero automatically before each test is executed. This is because each test re-initializes the specification, and the module state has an “`init`” clause that sets the total to zero.



Notice also that the operation calls are not applied to a Counter object, unlike VDM++.

2.6.2 Traces in VDM++ and VDM-RT

Traces are added in a “traces” section within a VDM++ or VDM-RT specification, inside one or more classes. In effect, the name of the trace is a public static symbol, so it is referred to as `<classname>`<tracename>`, as we have seen in the examples above. You can omit the class name if that is the default class.

Although a VDM++ trace is effectively a static scope, and can call static operations directly (similar to a VDM-SL trace), every test execution occurs in a *new instance* of the containing class - in our examples, in a new Tester instance. This means that objects created within the Tester’s construction will be freshly initialized and ready for use in each test run. In the example, the Counter object `obj` is created for each test, because the instance variable is initialized at construction.

2.6.3 Expansion and Execution Considerations

The process of running a combinatorial test has two phases: expanding the trace to a number of test definitions; and subsequently executing those definitions. The trace expansion typically does not take very long, since it is only constructing a tree of iterators that are capable of generating the tests one after another. The subsequent execution of those tests can obviously take a long time, depending on how many there are.

We have seen (above) how the specification is initialized before test execution, and the state of the module or class is available to the trace, but care must be taken if operations or functions within the environment are used as part of a trace. This is because some expressions are evaluated during trace expansion and some during test execution. For example:

```
...
functions
  private static range: int * int -> set of int
  range(a, b) == {a, ..., b};

values
  Z = 100;

traces
  T1: let x in set range(3, 5) in
      let y in set range(x, x+2) in
        obj.inc(Z + x + y);
```

In this case, the `range` function is used to create a set for the multi-binds, and this is executed during *expansion*, once for “x” and three times for “y”. Similarly, the right hand side of simple let



definitions are executed during trace expansion. But the addition of $z + x + y$ in the argument to `inc` is called during *execution* (once for each test).

Trace generation starts inside a fresh object instance of the class (or initialized module) that contains the trace. So if operations are called during trace *expansion*, these can modify state and so affect subsequent operation calls elsewhere in the expansion. This can become very confusing, and it is not a recommended trace design strategy! On the other hand, calling functions as part of the trace expansion can make traces easier to understand and can provide the means to build complex sets that would be difficult to construct directly within the trace statements.

When a test is listed in the trace output, the arguments that are passed to operation calls are shown as literals, if possible. As seen in the examples here, a call to `obj.inc(1)` is shown, rather than `obj.inc(a)`. This is possible whenever arguments can be easily evaluated. For example the $z + x + y$ case above would produce `Test 1 = obj.inc(106)`, which is $100 + 3 + 3$. But if the argument is a more complex expression involving operation applies or new object creation, these cannot be evaluated and so the argument expression is listed “as is”. For example, if the trace above is changed to call `obj.inc(max(x, y))`, the test would be listed with “x” and “y” rather than their current values:

```
> runtrace Tester'T1
Generated 9 tests in 0.006 secs.
Test 1 = inc(max(x, y))
Result = [3, PASSED]
Test 2 = inc(max(x, y))
Result = [3, PASSED]
...
```



Chapter 3

Combinatorial Testing Patterns

3.1 Traces and Test Operations

After expanding a trace to all of the operation call sequences that match, a test is ultimately just a sequence of operation or function calls. But these calls do not have to be the primary operations that drive the specification. In some cases, it makes sense for traces to expand to a set of tests that call *test operations* that maintain their own state and exercise the main specification, checking the responses and the main state. Checks like this, that do not directly form part of the constraints of the specification, are usually called *validation conjectures*. The task of the testing operations is therefore to check that, whatever the call sequence made by the trace, the validation conjectures for the specification are maintained.

For example, a specification may describe how a sequence of parts are produced as calls are made to `newPart()`, `adjustPart()`, `completePart()`. The process of creation of individual parts may well involve preconditions, postconditions, type invariants and so on. But there may also be a requirement that (say) over time, the total number of parts of type A and type B never differ by more than a tolerance. This is a validation conjecture: it is not directly stated in the constraints of the specification, but it is a behaviour that must be manifest by the system over time. Therefore the trace(s) for such a system can call the main operations via test operations, like `testNewPart()` and so on, and the `testCompletePart()` operation can check the history of parts created to validate that the tolerance is always respected, regardless of the sequence of operations that the trace tries. Note that these test operations can maintain their own state that is private and separate from that of the main specification.

In such cases, it makes sense to add all of the test operations to a separate class or module, to make it clear that they are not part of the main specification. This is illustrated in the Basket Service example in Chapter 4.



3.2 Common Patterns

Experience has shown that the testing of many specifications with traces requires several common “patterns” to create data selections or sequences of operations. These are presented in this chapter.

3.2.1 Sets for “let” bindings

The set of values that is used by a `let multiple-bind` is usually shown as an enumeration of literals in examples. But the set value can use any VDM expression that yields a set. The following cases are generally useful:

- Set comprehensions can be used to select values from a larger set that meet the membership predicate. This is similar to the use of the `be st` clause, but the filter acts on the members of the set rather than the values that are bound:

```
let pair in set {mk_(a, b) | a, b in set VALUES & a > b} in ...
```

- The `power` operator can be used to produce all possible subsets from another set, though you often have to eliminate the empty set, which is produced by the operator:

```
let options in set power ALL_OPTIONS \ {{}} in ...
```

- If you are using finite types (i.e. types that have a finite number of values), then you can use a type multiple bind to conveniently choose all of the possible values of that type:

```
let product : Product in ...
```

- Often elements have to be chosen from a set such that they are different to previous selections from the same set. This can sometimes be done in a single `let` bind by using a `be st` clause that states that the values are different. But a common usage is to make a selection from a set that has had the first choice(s) eliminated:

```
let a, b in set S be st a <> b in ...  
let c in set S \ {a, b} in ...  
let d in set S be st d not in set {a, b, c} in ...
```

- A common requirement is to select names items from a set, such that the items form every possible permutation of that set. This can be done by using the looseness of a set bind, which expands to such a permutation. Note the use of the set pattern and the set-of-set $\{S\}$ in the bind values:

```
let {a, b, c, d, e} in set {S} be st ... in ...
```



3.2.2 Bracketing operations with headers and trailers

3.2.3 Graph searching by traces

3.2.4 Building data in stages

3.2.5 Oracle functions

3.2.6 Using positive and negative sense checks

3.3 Avoiding Test Explosions



Chapter 4

Combinatorial Testing Examples

4.1 The LUHN Check Digit Model

4.2 The Basket Service Model



Appendix A

Combinatorial Testing Syntax

traces definitions = **'traces'**, [named trace, { **';**', named trace }] ;

named trace = identifier, { **'/'**, identifier }, **':'**, trace definition list ;

trace definition list = trace definition term, { **';**', trace definition term } ;

trace definition term = trace definition, { **'|'**, trace definition } ;

trace definition = trace binding definition
| trace repeat definition ;

trace binding definition = trace let def binding
| trace let best binding ;

trace let def binding = **'let'**, local definition, { **'/'**, local definition },
'in', trace definition ;

trace let best binding = **'let'**, multiple bind, [**'be'**, **'st'**, expression],
'in', trace definition ;

trace repeat definition = trace core definition, [trace repeat pattern] ;

trace repeat pattern = **'*'**
| **'+'**
| **'?'**
| **'{'**, numeric literal, [**'/'**, numeric literal, **'}'**] ;

trace core definition = trace apply expression
| trace concurrent expression
| trace bracketed expression ;

trace apply expression = call statement ;



trace bracketed expression = ‘(’, trace definition list, ‘)’ ;

Appendix B

Overture Screenshots



Appendix C

Example Model Listings

The VDM models listed in this appendix are described in detail in Chapter 4

C.1 The LUHN Check Digit Model

C.2 The Basket Service Model



References

- [Bicarregui&94] Juan Bicarregui and John Fitzgerald and Peter Lindsay and Richard Moore and Brian Ritchie. *Proof in VDM: A Practitioner's Guide*. FACIT, Springer-Verlag, 1994. 245 pages. ISBN 3-540-19813-X.
- This book is a tutorial on the process of formal reasoning in VDM. It discusses how to go about building proofs and provides the most complete set of proof rules for VDM-SL to date.
- [Clarke&99] E. Clarke and O. Grumberg and D. Peled. *Model Checking*. The MIT Press, 1999.
- [Larsen&10] Peter Gorm Larsen and Kenneth Lausdahl and Nick Battle. Combinatorial Testing for VDM. In *Proceedings of the 2010 8th IEEE International Conference on Software Engineering and Formal Methods*, pages 278–285, IEEE Computer Society, Washington, DC, USA, September 2010. ISBN 978-0-7695-4153-2.
- [Nie&11] Nie, Changhai and Leung, Hareton. A Survey of Combinatorial Testing. *ACM Comput. Surv.*, 43(2):11:1–11:29, February 2011.
- [Paulson97] Lawrence C. Paulson. Generic Automatic Proof Tools. In Robert Veroff, editor, *Automated Reasoning and its Applications: Essays in Honor of Larry Wos*, pages 23–47, MIT Press, Cambridge, MA, USA, 1997.