

**Overture Technical Report Series
No. TR-005**

December 2020

Guidelines for using VDM Combinatorial Testing Features

by

Nick Battle
Peter Gorm Larsen





Document history

| Month | Year | Version | Version of Overture.exe | Comment |
|----------|------|---------|-------------------------|-----------------|
| December | 2010 | 0.1 | 3.0.2 | Initial version |

Contents

| | | |
|----------|--|-----------|
| 1 | Introduction | 1 |
| 1.1 | What is Combinatorial Testing? | 1 |
| 2 | Working with Traces | 3 |
| 2.1 | Basic Trace Constructs | 3 |
| 2.2 | Using Variables | 8 |
| 2.3 | Tests with Errors | 14 |
| 2.4 | How Does Trace Expansion Work? | 15 |
| 2.5 | Language Considerations | 17 |
| 2.5.1 | Traces in VDM-SL | 17 |
| 2.5.2 | Traces in VDM++ and VDM-RT | 19 |
| 2.5.3 | Expansion and Execution Considerations | 19 |
| 3 | Combinatorial Testing Patterns | 21 |
| 4 | Combinatorial Testing Examples | 23 |
| A | Combinatorial Testing Syntax | 25 |
| B | Overture Screenshots | 27 |



Chapter 1

Introduction

This manual is a complete guide the combinatorial testing of VDM models. It assumes the reader has no prior knowledge of combinatorial testing, but a working knowledge of VDM, in particular, the VDM++ and VDM-SL dialects.

1.1 What is Combinatorial Testing?

Creating a comprehensive set of tests for VDM specifications can be a time consuming process. To try to make the generation of test cases simpler, Overture provides a VDM language extension (for all dialects) called Combinatorial Testing.

In general, specifications are tested to verify that certain properties or behaviours are met, as specified by constraints in the specification and validation conjectures in the tests.

The simplest way to test a specification is to write ad-hoc tests, starting from a known system state and proceeding with a sequence of operation calls that should move to a new state or produce some particular result or error response. The problem with this kind of testing is that it can be very laborious to produce the number of tests needed to cover the complete system behaviour. It is also expensive to maintain a large test suite as the specification evolves.

The most complete way to test a specification is to produce a formal mathematical proof that it will never violate its constraints, and always meet its validation conjectures if presented with a legal sequence of operation calls. This provides the highest level of confidence in the correctness of a specification, but it can be unrealistic to produce a complete formal proof for complex specifications, even with tool support.

Model checking provides an approach to formal testing that is considerably better than ad-hoc testing but not as complete as formal proof. This approach uses a formal specification of the system properties desired, often written in a temporal calculus, and the model checker symbolically executes the specification searching for execution paths that violate the constraints. Since the execution is symbolic, extremely large state spaces can be searched (billions of cases is not uncommon), and failed cases can produce a “counter example” that demonstrates the failure. This is a very powerful technique, but in practice, realistic specifications often produce a state space explosion that is too great for model checkers.



Combinatorial testing is an approach that is far more powerful than ad-hoc testing, but not as complete as model checking. Tests are produced automatically from “traces” that are relatively simple to define. The approach allows specifications to be tested with perhaps millions of test cases, but cannot guarantee to catch every corner case in the way that a model checker can. Therefore the technique is useful for specifications that are too complex for model checking or formal proof.

A combinatorial trace is a pattern that describes the construction of argument values and the sequences of operation calls that will exercise the specification. A specification may contain several traces, each designed to test a particular aspect. Traces are automatically expanded into a (potentially large) number of tests, each of which is a particular sequence of operation calls and argument values. The execution of tests is performed automatically, starting each in a known state; a test is considered to pass if it does not violate the specification’s constraints, or the test’s validation conjectures. Individual failed tests can be executed in isolation to find out why they failed, which is similar to a model checker’s counter example.

Chapter 2

Working with Traces

2.1 Basic Trace Constructs

Combinatorial tests are embedded within a VDM specification using a section called “traces”. Typically, one or more traces are added to a separate class or module that is intended for testing rather than the main specification, though you can add traces to any class you wish. In this chapter, we will use the example classes below:

```
class Counter
instance variables
    total:int := 0;

operations
    public inc: () ==> int
    inc() == ( total := total + 1; return total; )

    public dec: () ==> int
    dec() == ( total := total - 1; return total; )

end Counter

class Tester
instance variables
    obj:Counter := new Counter();

traces
    T1: obj.inc();

end Tester
```

Notice that there are two classes, Counter and Tester. The Counter defines a simple class



that increments and decrements a total state value that is initially zero. The `Tester` class creates an instance of `Counter` and defines a single trace called `T1`. Trace names are simple identifiers, optionally separated by slashes (eg. `item456/interface/all`). This example is the simplest trace possible and indicates that the trace should expand to a single test that just calls `obj.inc()`.

This trace can either be executed in Overture in the Combinatorial Testing perspective (see Appendix B), or it can be executed from the command line using the `runtrace` command. The command line output is illustrated here for simplicity:

```
> runtrace Tester`T1
Generated 1 tests in 0.004 secs.
Test 1 = obj.inc()
Result = [1, PASSED]
Executed in 0.007 secs.
All tests passed
```

The first line of output indicates that one test has been generated from the trace. With more complex examples, this generation could expand to thousands or millions of tests, and consequently it may take a few seconds.

The next line of the output describes the test that was generated. Note that this is called “Test 1”, and consists of a single call to `obj.inc()`.

The line below the test gives the result of executing that test. There is a single return value from the call to `obj.inc()`, 1, which is listed along with the word “PASSED” that indicates that there were no constraint violations in the test execution.

Lastly the time taken to execute all of the tests is given, and an indication of whether any tests failed.

The reason that this trace only expands to a single test is that the trace, when considered as a pattern, only matches a single operation call. But if we change the trace to the following:

```
traces
T1: obj.inc() | obj.dec();
```

The trace is now saying that it would match either a call to `obj.inc()` or a call to `obj.dec()`. Therefore the test expansion produces the following:

```
> runtrace Tester`T1
Generated 2 tests
Test 1 = obj.inc()
Result = [1, PASSED]
Test 2 = obj.dec()
Result = [-1, PASSED]
Executed in 0.033 secs.
All tests passed
```




This time two tests are generated. The first calls `obj.inc()`, the second `obj.dec()`. Notice that the decrement test is completely separate from the increment test. It produces -1 as its result, because the Counter object is re-created for each test. It does not decrement the counter back to zero after the first test incremented it.

If we want to test an increment followed by a decrement, that would be expressed using a semi-colon separator:

traces

```
T1: obj.inc(); obj.dec();
```

This produces the output:

```
Generated 1 tests
Test 1 = obj.inc(); obj.dec()
Result = [1, 0, PASSED]
Executed in 0.027 secs.
All tests passed
```

This generates a single test again, but you can see that the test involves two calls and that they return 1 and 0, respectively. So this time the second call is operating on the same object instance as the first.

If the increment and decrement operations are independent, it makes sense to test calls to them in either order, which would be expressed as:

traces

```
T1: || ( obj.inc(), obj.dec() );
```

Notice that the separator has changed to a comma. That produces the output:

```
Generated 2 tests
Test 1 = obj.inc(); obj.dec()
Result = [1, 0, PASSED]
Test 2 = obj.dec(); obj.inc()
Result = [-1, 0, PASSED]
Executed in 0.029 secs.
All tests passed
```

So now both orderings of the two calls are produced. This is because there are two orderings that match the pattern `|| (..., ...)`. This particular trace construct naturally expands to an arbitrary number of calls and produces a test for every permutation of the calls in brackets.

But what if some tests are a pair of calls and some are not? If we want to make a call optional, the `?` operator can be added to any operation call (ie. not just within `||` operators) to indicate that this will match tests where the call is made and where it is not. For example:



traces

```
T1: || ( obj.inc(), obj.dec()? );
```

This means that the decrement call is optional and so although it is included in the orderings of the pair, it should also be absent in some cases. This example produces the following:

```
Generated 4 tests
Test 1 = obj.inc(); skip
Result = [1, (), PASSED]
Test 2 = obj.inc(); obj.dec()
Result = [1, 0, PASSED]
Test 3 = skip; obj.inc()
Result = [(), 1, PASSED]
Test 4 = obj.dec(); obj.inc()
Result = [-1, 0, PASSED]
Executed in 0.043 secs.
All tests passed
```

You see that the decrement call is sometimes present and sometimes replaced by `skip`, which indicates the absence of an optional call. Notice also that the `||` operator and the `?` operator work together to combine their effects in this example, though `?` can be used for any operation call.

Along the same lines as `?`, it is possible to add `*` and `+` operators to any call, which indicate that it should be called zero or more times, and one or more times. The maximum number of times is a tool preset value that defaults to 5, though it can be changed. So for example:

traces

```
T1: obj.inc()*;
T2: obj.dec()+;
```

```
> runtrace Tester`T1
Generated 6 tests
Test 1 = skip
Result = [(), PASSED]
Test 2 = obj.inc()
Result = [1, PASSED]
Test 3 = obj.inc(); obj.inc()
Result = [1, 2, PASSED]
Test 4 = obj.inc(); obj.inc(); obj.inc()
Result = [1, 2, 3, PASSED]
Test 5 = obj.inc(); obj.inc(); obj.inc(); obj.inc()
Result = [1, 2, 3, 4, PASSED]
Test 6 = obj.inc(); obj.inc(); obj.inc(); obj.inc(); obj.inc()
```



CHAPTER 2. WORKING WITH TRACES

```
Result = [1, 2, 3, 4, 5, PASSED]
Executed in 0.046 secs.
All tests passed
```

```
> runtrace Tester`T2
Generated 5 tests
Test 1 = obj.dec()
Result = [-1, PASSED]
Test 2 = obj.dec(); obj.dec()
Result = [-1, -2, PASSED]
Test 3 = obj.dec(); obj.dec(); obj.dec()
Result = [-1, -2, -3, PASSED]
Test 4 = obj.dec(); obj.dec(); obj.dec(); obj.dec()
Result = [-1, -2, -3, -4, PASSED]
Test 5 = obj.dec(); obj.dec(); obj.dec(); obj.dec(); obj.dec()
Result = [-1, -2, -3, -4, -5, PASSED]
Executed in 0.042 secs.
All tests passed
```

The important difference between these two is that T1 includes an extra skip case, whereas T2 does not.

Lastly, it is possible to indicate a specific number of repetitions of a call or a range of repetitions. For example:

traces

```
T1: obj.inc(){3};
T2: obj.dec(){2, 4};
```

```
> runtrace Tester`T1
Generated 1 tests
Test 1 = obj.inc(); obj.inc(); obj.inc()
Result = [1, 2, 3, PASSED]
Executed in 0.026 secs.
All tests passed

> runtrace Tester`T2
Generated 3 tests
Test 1 = obj.dec(); obj.dec()
Result = [-1, -2, PASSED]
Test 2 = obj.dec(); obj.dec(); obj.dec()
Result = [-1, -2, -3, PASSED]
Test 3 = obj.dec(); obj.dec(); obj.dec(); obj.dec()
Result = [-1, -2, -3, -4, PASSED]
Executed in 0.01 secs.
```



All tests passed

The T1 trace now produces a single test with precisely three repetitions, while the T2 trace gives three tests with 2, 3 and 4 repetitions respectively.

If you combine a `||` operator with a repetition, the result is to repeat all of the possibilities of the permutation with the given number of repetitions. For example:

traces

```
T1: || ( obj.inc(), obj.dec() ) {2};
```

```
> runtrace Tester`T1
Generated 4 tests
Test 1 = obj.inc(); obj.dec(); obj.inc(); obj.dec()
Result = [1, 0, 1, 0, PASSED]
Test 2 = obj.dec(); obj.inc(); obj.inc(); obj.dec()
Result = [-1, 0, 1, 0, PASSED]
Test 3 = obj.inc(); obj.dec(); obj.dec(); obj.inc()
Result = [1, 0, -1, 0, PASSED]
Test 4 = obj.dec(); obj.inc(); obj.dec(); obj.inc()
Result = [-1, 0, -1, 0, PASSED]
Executed in 0.038 secs.
All tests passed
```

Here, the `||` operator produces (inc, dec) and (dec, inc); then the repetition doubles this, but it doubles every combination of the two rather than simply repeating each one twice.

2.2 Using Variables

So far, the trace examples have called operations that do not include any arguments. Arguments can be passed as literals, but traces also provide the means to define variables that can change value as tests are generated from a trace.

If we overload the example increment and decrement operations with versions that take an integer parameter, by which to change the counter, we can write traces like this:

```
...
public inc: int ==> int
inc(i) == ( total := total + i; return total; );

public dec: int ==> int
dec(i) == ( total := total - i; return total; )
```

traces



```
T1:
    let a in set {1, ..., 10} be st a mod 2 = 0 in
        obj.inc(a);
```

```
> runtrace Tester`T1
Generated 5 tests
Test 1 = obj.inc(2)
Result = [2, PASSED]
Test 2 = obj.inc(4)
Result = [4, PASSED]
Test 3 = obj.inc(6)
Result = [6, PASSED]
Test 4 = obj.inc(8)
Result = [8, PASSED]
Test 5 = obj.inc(10)
Result = [10, PASSED]
Executed in 0.04 secs.
All tests passed
```

In a standard VDM specification, the `let...be st` expression would choose an arbitrary element from the set that meets the `st` clause. But in a trace context, this looseness is used as a pattern that expands to a test covering each possible set value that would match. Notice that the tests list the actual value of the argument passed, rather than the symbolic name, “a”.

A trace can include multiple `let` clauses, but if these are nested, then the trace expands to the *combination* of the variables. For example:

```
traces
T1:
    let a in set {1, 2, 3} in
        let b in set {4, 5, 6} in
            ( obj.inc(a); obj.dec(b) );
```

```
> runtrace Tester`T1
Generated 9 tests
Test 1 = obj.inc(1); obj.dec(4)
Result = [1, -3, PASSED]
Test 2 = obj.inc(1); obj.dec(5)
Result = [1, -4, PASSED]
Test 3 = obj.inc(1); obj.dec(6)
Result = [1, -5, PASSED]
Test 4 = obj.inc(2); obj.dec(4)
Result = [2, -2, PASSED]
```



```
Test 5 = obj.inc(2); obj.dec(5)
Result = [2, -3, PASSED]
Test 6 = obj.inc(2); obj.dec(6)
Result = [2, -4, PASSED]
Test 7 = obj.inc(3); obj.dec(4)
Result = [3, -1, PASSED]
Test 8 = obj.inc(3); obj.dec(5)
Result = [3, -2, PASSED]
Test 9 = obj.inc(3); obj.dec(6)
Result = [3, -3, PASSED]
Executed in 0.066 secs.
All tests passed
```

This example produces a test for every combination of “a” and “b” values, which is therefore nine tests. The round brackets are needed around the pair of operation calls because a call binds tightly to the `let`. Without the brackets, you get the following scope error, referring to the “a” in the second call to `obj.dec(a)`:

```
traces
T1:
    let a in set {6, 7, 10} in
        obj.inc(a); obj.dec(a)
```

```
Error 3182: Name 'Tester'a' is not in scope in 'Tester' (example.vpp) at line 28:29
Type checked 2 classes in 0.12 secs. Found 1 type error
```

Note also that the variables defined are in scope throughout the clauses below, so the “a” variable could be used to define the set of “b” values:

```
traces
T1:
    let a in set {1, 2, 3} in
        let b in set {a, ..., a + 2} in
            ( obj.inc(a); obj.dec(b) );
```

```
> runtrace Tester`T1
Generated 9 tests
Test 1 = obj.inc(1); obj.dec(1)
Result = [1, 0, PASSED]
Test 2 = obj.inc(1); obj.dec(2)
Result = [1, -1, PASSED]
Test 3 = obj.inc(1); obj.dec(3)
```



CHAPTER 2. WORKING WITH TRACES

```
Result = [1, -2, PASSED]
Test 4 = obj.inc(2); obj.dec(2)
Result = [2, 0, PASSED]
Test 5 = obj.inc(2); obj.dec(3)
Result = [2, -1, PASSED]
Test 6 = obj.inc(2); obj.dec(4)
Result = [2, -2, PASSED]
Test 7 = obj.inc(3); obj.dec(3)
Result = [3, 0, PASSED]
Test 8 = obj.inc(3); obj.dec(4)
Result = [3, -1, PASSED]
Test 9 = obj.inc(3); obj.dec(5)
Result = [3, -2, PASSED]
Executed in 0.059 secs.
All tests passed
```

If two variables should take values from the same set of values, it is possible to use a multiple bind in a trace, but not a bind list. For example:

```
traces
  T1:
      let a, b in set {1, 2, 3} in
        ( obj.inc(a); obj.dec(b) );
```

```
> runtrace Tester`T1
Generated 9 tests
Test 1 = obj.inc(1); obj.dec(1)
Result = [1, 0, PASSED]
Test 2 = obj.inc(2); obj.dec(1)
Result = [2, 1, PASSED]
Test 3 = obj.inc(3); obj.dec(1)
Result = [3, 2, PASSED]
Test 4 = obj.inc(1); obj.dec(2)
Result = [1, -1, PASSED]
Test 5 = obj.inc(2); obj.dec(2)
Result = [2, 0, PASSED]
Test 6 = obj.inc(3); obj.dec(2)
Result = [3, 1, PASSED]
Test 7 = obj.inc(1); obj.dec(3)
Result = [1, -2, PASSED]
Test 8 = obj.inc(2); obj.dec(3)
Result = [2, -1, PASSED]
Test 9 = obj.inc(3); obj.dec(3)
Result = [3, 0, PASSED]
```



Executed in 0.061 secs.
All tests passed

As well as defining a variable value from a set, variables can be used to simplify calculations that would otherwise have to be made in the arguments to operation calls. These simpler `let` definitions do not increase the number of tests generated from the trace, they just introduce new names in the scope that follows. Multiple variable definitions can be declared in one `let` expression. For example:

```
traces
T1:
    let a in set {1, 2, 3} in
        let b = a + 1, c = a - 1 in
            ( obj.inc(b); obj.dec(c) );
```

```
> runtrace Tester`T1
Generated 3 tests
Test 1 = obj.inc(2); obj.dec(0)
Result = [2, 2, PASSED]
Test 2 = obj.inc(3); obj.dec(1)
Result = [3, 2, PASSED]
Test 3 = obj.inc(4); obj.dec(2)
Result = [4, 2, PASSED]
Executed in 0.054 secs.
All tests passed
```

If repetitions are added to a clause within a `let` body, they bind tightly to the operation call rather than the entire `let` clause. If you want to repeat the entire `let`, you have to bracket the whole clause and add a repetition to that. For example:

```
traces
T1:
    let a in set {1, 2, 3} in
        obj.inc(a){1, 2}
T2:
    ( let a in set {1, 2, 3} in
        obj.inc(a) ) {1, 2}
```

```
> runtrace Tester`T1
Generated 6 tests
Test 1 = obj.inc(1)
Result = [1, PASSED]
```




CHAPTER 2. WORKING WITH TRACES

```
Test 2 = obj.inc(1); obj.inc(1)
Result = [1, 2, PASSED]
Test 3 = obj.inc(2)
Result = [2, PASSED]
Test 4 = obj.inc(2); obj.inc(2)
Result = [2, 4, PASSED]
Test 5 = obj.inc(3)
Result = [3, PASSED]
Test 6 = obj.inc(3); obj.inc(3)
Result = [3, 6, PASSED]
Executed in 0.044 secs.
All tests passed
```

```
> runtrace Tester`T2
Generated 12 tests
Test 1 = obj.inc(1)
Result = [1, PASSED]
Test 2 = obj.inc(2)
Result = [2, PASSED]
Test 3 = obj.inc(3)
Result = [3, PASSED]
Test 4 = obj.inc(1); obj.inc(1)
Result = [1, 2, PASSED]
Test 5 = obj.inc(2); obj.inc(1)
Result = [2, 3, PASSED]
Test 6 = obj.inc(3); obj.inc(1)
Result = [3, 4, PASSED]
Test 7 = obj.inc(1); obj.inc(2)
Result = [1, 3, PASSED]
Test 8 = obj.inc(2); obj.inc(2)
Result = [2, 4, PASSED]
Test 9 = obj.inc(3); obj.inc(2)
Result = [3, 5, PASSED]
Test 10 = obj.inc(1); obj.inc(3)
Result = [1, 4, PASSED]
Test 11 = obj.inc(2); obj.inc(3)
Result = [2, 5, PASSED]
Test 12 = obj.inc(3); obj.inc(3)
Result = [3, 6, PASSED]
Executed in 0.03 secs.
All tests passed
```

The difference may seem subtle, but the effect is significant. T1 behaves like a simple “{1, 2}” repetition for each of the `let` values, whereas T2 produces either one or two cases from the *entire* set created by the `let` clause.



Although the example above uses a `let <set bind>` expression, it is also possible to use a `let <seq bind>` or `let <type bind>`. In a trace context, the ordering that a sequence bind carries does not affect the generation of tests; if the example had `let a in seq [1, 2, 3]`, the same tests would be generated, and since tests are independent their order is not meaningful. So sequence binds are not particularly useful in traces. However type binds (of finite types) are a shorthand for “all values of this type”, which can be useful in some circumstances. This is covered later in Chapter 3.

2.3 Tests with Errors

The examples so far have only includes tests that PASSED. This means that they completed the sequence of operation calls without violating any preconditions, postconditions, state invariants, type invariants, recursive measures or dynamic type checks.

If a sequence of operations causes a postcondition failure, then it is certain that there is a problem with the specification it should not be possible to provoke a post condition failure with a set of legal calls (ie. ones which pass the preconditions and type invariants). On the other hand, if a sequence of operations violates a precondition, or a type or class invariant, then it is *possible* that the specification has a problem, but it is also possible that the test itself is at fault (passing illegal values).

The combinatorial testing environment indicates the exit status of the test in the verdict returned in the last item of the results (all PASSED above). So if pre/post/invariant conditions are violated during a test, this may be set to FAILED or INDETERMINATE¹. If a test fails, then any subsequent test which starts *with the same sequence of calls* as the failed sequence will also fail. These tests are filtered out of the remaining test sequence automatically, and not executed.

For example, if we introduce a pre- and postcondition into our example, we see this behaviour:

```
...
public inc: int ==> int
inc(i) == ( total := total + i; return total; )
pre i < 10
post total < 20;

traces
T1:
    let a in set {6, 7, 10} in
        obj.inc(a){1, 5}
```

```
> runtrace Tester'T1
Generated 15 tests
Test 1 = obj.inc(6)
Result = [6, PASSED]
```

¹The tools sometimes call this INCONCLUSIVE



```

Test 2 = obj.inc(6); obj.inc(6)
Result = [6, 12, PASSED]
Test 3 = obj.inc(6); obj.inc(6); obj.inc(6)
Result = [6, 12, 18, PASSED]
Test 4 = obj.inc(6); obj.inc(6); obj.inc(6); obj.inc(6)
Result = [6, 12, 18, Error 4072: Postcondition failure: post_inc in 'Counter' at line 15:16, FAILED]
Test 5 = obj.inc(6); obj.inc(6); obj.inc(6); obj.inc(6); obj.inc(6)
Test 5 FILTERED by test 4
Test 6 = obj.inc(7)
Result = [7, PASSED]
Test 7 = obj.inc(7); obj.inc(7)
Result = [7, 14, PASSED]
Test 8 = obj.inc(7); obj.inc(7); obj.inc(7)
Result = [7, 14, Error 4072: Postcondition failure: post_inc in 'Counter' at line 15:16, FAILED]
Test 9 = obj.inc(7); obj.inc(7); obj.inc(7); obj.inc(7)
Test 9 FILTERED by test 8
Test 10 = obj.inc(7); obj.inc(7); obj.inc(7); obj.inc(7); obj.inc(7)
Test 10 FILTERED by test 8
Test 11 = obj.inc(10)
Result = [Error 4071: Precondition failure: pre_inc in 'Counter' at line 14:11, INCONCLUSIVE]
Test 12 = obj.inc(10); obj.inc(10)
Test 12 FILTERED by test 11
Test 13 = obj.inc(10); obj.inc(10); obj.inc(10)
Test 13 FILTERED by test 11
Test 14 = obj.inc(10); obj.inc(10); obj.inc(10); obj.inc(10)
Test 14 FILTERED by test 11
Test 15 = obj.inc(10); obj.inc(10); obj.inc(10); obj.inc(10); obj.inc(10)
Test 15 FILTERED by test 11
Executed in 0.075 secs.
Some tests failed or indeterminate

```

The `inc` operation now has a precondition that the argument must be less than 10 and a postcondition that the resulting total must be less than 20. The trace makes 1 to 5 calls to the `inc` operation with arguments 6, 7 and 10, respectively.

The first three tests are fine, but Test 4 fails because the fourth call to `inc(6)` pushes the total over the limit. This is therefore a postcondition FAILED test, and the error message is listed along with the results of the earlier operation calls. Test 5 then tries to do the same, but adds a further call. This must fail in the same place as Test 4, because Test 4 is the “stem” of Test 5. Therefore this test is “FILTERED by Test 4”. Similarly, Test 8 fails and Tests 9 and 10 are filtered by this failure.

Test 11 fails on the first call to `inc(10)`, since the argument must be less than 10. This produces an INDETERMINATE error because we are not sure whether this is a problem with the trace or the specification being tested. Lastly, Tests 12 to 15 are filtered by Test 11, since they would behave the same way.

At the end of the run, the `runtrace` command indicates that some tests failed or were indeterminate, just to remind you.

2.4 How Does Trace Expansion Work?

The sections above have given an overview of all the trace operators, and there are some examples of combinations of operators. But to see how traces are expanded in general, we need to look at traces from a different point of view. The syntax of traces is deliberately made similar to the syntax



of VDM-SL, but to understand how operators combine to produce multiple tests, it helps to look at operators as though they followed a separate “expansion” grammar. In the description that follows, a `set` is a set of tests:

- `set = object.opname(args)`. The simplest form of a trace is a set that comprises a single call to an operation or function with arguments. The arguments can be symbolic, and bound to various values by the `let` operator described below.
- `set = set1; set2; ...; setn`. A set of tests may be formed from an ordered sequence of sets. This expands to all possible selections of one test from each of the sets. In its simplest form, this could be a sequence of operation calls which therefore just expands to one test. But a combination of sets of tests results in a set of the product of the sizes of those sets.
- `set = set1 ?`. A set of tests may be formed from another set with a `?` operator. This produces the same set, but includes a “skip” step.
- `set = set1 {n[, n]}`. A set of tests may be formed from another set with a `{n}` or `{n1, n2}` operator. This produces a set with every member of the original set repeated `n` times, or between `n1` and `n2` times (inclusive).
- `set = set1 *|+`. A set of tests may be formed from another set with a `*` or `+` operator. This produces another set with every member of the original set repeated from 0 to `N` times (with `*`) or 1 to `N` times (with `+`). The value of `N` is tool dependent, but defaults to 5.
- `set = set1 | set2 | ... | setn`. A set of tests may be formed by combining a number of other test sets with a `|` operator. This produces a set with the union of the other sets.
- `set = || (set1, set2, ..., setn)`. A set may be formed from the permutations of a number of other sets. This produces a set with each permutation of each selection of one test from each set.
- `set = let <multiple bind> [be st <cond>] in set1`. A set of tests may be formed from a `multiple bind`, which expands to the substitution of all the possible the bound values in the original set.
- `set = let <name> = <exp> [, <name2> = <exp2>, ...] in set1`. A set of tests may be evaluated in a scope that defines name/value pairs. This does not increase the number of tests in the set, but just binds free variables.

For example, if (for brevity) we say that a test with a single call to `obj.opA()` is written as “[A]”, and similarly “[B]” and “[C]” for other operation calls, and “[−]” for a skip, then we can say the following trace operators produce these sets of tests:



```

A? = { [A], [-] }
A;B = { [AB] }
A;B? = { [AB], [A] }
A* = { [-], [A], [AA], [AAA], [AAAA], [AAAAA], ... }
A+ = { [A], [AA], [AAA], [AAAA], [AAAAA], ... }
A{3} = { [AAA] }
A{1,3} = { [A], [AA], [AAA] }
A | B = { [A], [B] }
A | B? = { [A], [B], [-] }
|| (A, B, C) = { [ABC], [ACB], [BAC], [BCA], [CAB], [CBA] }
|| (A, (B;C)) = { [ABC], [BCA] }
|| (A, B+) = { [AB], [BA], [ABB], [BBA], [ABBB], [BBBA], ... }
let a in set {1,2,3} in A(a) = { [A(1)], [A(2)], [A(3)] }
let b : bool * bool in B(b) = {
    [B(true, true)], [B(true, false)],
    [B(false, true)], [B(false, false)]
}
let z = 1 in B(z) = { [B(1)] }

```

Note that the repeat limits in a trace (like $\{1,3\}$) must be numeric literals. But values in a multiple bind set or sequence can be variables, either bound earlier in the trace or other fields within scope of the trace inside the object or module where it is defined. Similarly, the values in the right hand side of let definitions can be variables within the trace or the object/module scope. These variables are evaluated *during the trace expansion*, whereas the substituted values operation arguments are evaluated *during test execution*.

2.5 Language Considerations

Combinatorial tests are available for both VDM-SL and VDM++/VDM-RT. The process of trace expansion and execution is very similar in all cases, but there are some differences that are described below.

2.5.1 Traces in VDM-SL

Traces are added in a “traces” section within a VDM-SL specification. This can either be within one or more modules or within a flat specification. The name of the traces in a module are implicitly exported, so they are referred to as `<modulename>`<tracename>`. You can omit the module name if it is the default module.

The equivalent VDM-SL specification that is equivalent to the example used above is like this:

```

module Counter
exports all
definitions

```



```
state S of
  total:int
init s == s = mk_S(0)
end

operations
  inc: int ==> int
  inc(i) == ( total := total + i; return total; )

  dec: int ==> int
  dec(i) == ( total := total - i; return total; )
end Counter

module Tester
imports from Counter all
definitions

traces
  T1: Counter`inc(1)*;

end Tester
```

And in the VDM-SL command line, that would be executed as follows. Note that Tester is not the default module, so the trace name is qualified:

```
> modules
Counter (default)
Tester
> runtrace Tester`T1
Generated 6 tests in 0.002 secs.
Test 1 = skip
Result = [(), PASSED]
Test 2 = inc(1)
Result = [1, PASSED]
Test 3 = inc(1); inc(1)
Result = [1, 2, PASSED]
Test 4 = inc(1); inc(1); inc(1)
Result = [1, 2, 3, PASSED]
Test 5 = inc(1); inc(1); inc(1); inc(1)
Result = [1, 2, 3, 4, PASSED]
Test 6 = inc(1); inc(1); inc(1); inc(1); inc(1)
Result = [1, 2, 3, 4, 5, PASSED]
Executed in 0.019 secs.
All tests passed
>
```

So this model is very similar to the VDM++ example. The Counter module has a single state that is equivalent to the VDM++ “total” instance variable. Note that this is reset to zero automatically before each test is executed. This is because each test effectively re-initializes the specification, and the module state has an “init” clause that sets the total to zero.



Notice also that the operation calls are not applied to a Counter object, unlike VDM++.

2.5.2 Traces in VDM++ and VDM-RT

Traces are added in a “traces” section within a VDM++ or VDM-RT specification, inside one or more classes. In effect the name of the trace is a public static symbol, so it is referred to as `<classname>`<tracename>`, as we have seen in the examples above. You can omit the class name if that is the default class.

Although a VDM++ trace is effectively a static scope, and can call static operations directly (similar to a VDM-SL trace), every test execution occurs in a *new instance* of the containing class - in our examples, in a new Tester instance. This means that objects created within the Tester’s construction will be freshly initialized and ready for use in each test run. In the example, the Counter object is created for each test, because the “obj” instance variable is initialized at construction.

2.5.3 Expansion and Execution Considerations

The process of running a combinatorial test has two phases: expanding the trace to a number of test definitions; and subsequently executing those definitions. The trace expansion typically does not take very long, since it is only constructing a tree of iterators that are capable of generating the tests one after another. The subsequent execution of those tests can obviously take a long time, depending on how many there are.

We have seen (above) how the specification is initialized before test execution, and the state of the module or class is available to the trace, but care must be taken if operations or functions within the environment are used as part of a trace. This is because some expressions are evaluated during expansion and some during execution. For example:

```
...
functions
  private static range: int * int -> set of int
  range(a, b) == {a, ..., b};

values
  Z = 100;

traces
  T1: let x in set range(3, 5) in
      let y in set range(x, x+2) in
        obj.inc(Z + x + y);
```

In this case, the `range` function is used to create a set for the multi-binds, and this is executed during expansion - once for “x” and three times for “y”. But the addition of `Z + x + y` in the argument to `inc` is called during execution.



Chapter 3

Combinatorial Testing Patterns



Chapter 4

Combinatorial Testing Examples



Appendix A

Combinatorial Testing Syntax

traces definitions = **'traces'**, [named trace, { **';**', named trace }] ;

named trace = identifier, { **'/'**, identifier }, **':'**, trace definition list ;

trace definition list = trace definition term, { **';**', trace definition term } ;

trace definition term = trace definition, { **'|'**, trace definition } ;

trace definition = trace binding definition
| trace repeat definition ;

trace binding definition = trace let def binding
| trace let best binding ;

trace let def binding = **'let'**, local definition, { **'/'**, local definition },
'in', trace definition ;

trace let best binding = **'let'**, multiple bind, [**'be'**, **'st'**, expression],
'in', trace definition ;

trace repeat definition = trace core definition, [trace repeat pattern] ;

trace repeat pattern = **'*'**
| **'+'**
| **'?'**
| **'{'**, numeric literal, [**'/'**, numeric literal, **'}'**] ;

trace core definition = trace apply expression
| trace concurrent expression
| trace bracketed expression ;

trace apply expression = call statement ;

Appendix B

Overture Screenshots