LDMS USER GROUP MEETING

November 2, 2026

©2026 Open Grid Computing, Inc.

Agenda

- Dropping old distributions from build tests
- Issue #2402 – ldmsd command-permission
- Q&A

Dropping old distributions from build tests

Dropping old distributions from build tests

Current GitHub build tests:

- AlmaLinux 8, AlmaLinux 9, Ubuntu 22.04, Ubuntu 24.04
- CentOS 7 — end of life June 30, 2024
- openSUSE 15 — end of life April 30, 2026 (16.0 is current)

Proposed:

- CentOS 7: remove the build test
- openSUSE 15: remove the build test

Dropping old distributions from build tests – Input from the Floor

CentOS 7 — proposed: remove build test

- Any objection?
- No objection (Nov 2, 2026)

openSUSE Leap 15 — proposed: remove build test

- Any site still needs Leap 15 or SLES 15?
- If yes, what is the timeline until it is retired?
- No – We will keep this

Issue 2402 - ldmsd command-permission concerns

ldmsd command-permission concerns (Issue #2402)

- A GitHub issue flags six ldmsd commands as possibly too open to non-admin users
- Goal today: agree on what the concern actually is, and where the line should sit
- Background:
  - how a client connects and is identified
  - how ldmsd decides what that client may do
  - the concern and where it lands

Connecting to ldmsd

What ldmsd knows about a client depends on which authentication plugin is bound to the connection

- Authenticated once, at connect – before any config command is accepted
- Result to one verified uid/gid, trusted for every communication on that connection

For example,

- munge – uid/gid recovered from a signed credential, not client-asserted

Each command sets its own trust level

Trust levels of ldmsd configuration commands

- XUG – caller's uid/gid must match ldmsd's own
- XALL – any authenticated user pass, admin or not

The commands flagged on issue 2402 have XALL.

- For these commands, passing authentication is all it takes to run them.

Six Config Commands Flagged on Issue 2402

	See config, metric set topology, and ldmsd performance statistics	**Reset** ldmsd's performance statistics	**Change** daemon-wide behavior
plugn_status	Yes	No	No
plugn_sets	Yes	No	No
xprt_stats	Yes	xprt_stats [reset=true]	No
thread_stats	Yes	thread_stats [reset=true]	No
stats_reset	No	Yes	No
profiling	Yes	configurable	Yes

	See config, metric set topology, and ldmsd performance statistics	**Reset** ldmsd's performance statistics	**Change** daemon-wide behavior	**Path forward**
plugn_status	Yes	No	No	Keep at XALL
plugn_sets	Yes	No	No	Keep at XALL
xprt_stats	Yes	xprt_stats [reset=true]	No	Ignore 'reset' and log and suggest to use a new reset_xprt_stats command under XUG
thread_stats	Yes	thread_stats [reset=true]	No	Ignore 'reset' and log and suggest to use a new reset_xprt_stats command under XUG
stats_reset	No	Yes	No	XALL → XUG reset_stats_all – alias to stats_reset
profiling	Yes	configurable	Yes	XALL → XUG

Q & A

- V4.5.4 has been released





Thank you!

The Concern & Where It Lands

For these commands, passing authentication is all it takes to run them.

- Not escalation or breach – least -privilege over ldmsd's own performance statistics state

Path forward and open questions:

- **Change behavior** (profiling): Change from XALL to XUG
- **See** or **Query** → should leave them open as XALL
- **Reset** is the questionable one.
  - **stats_reset** could change from XALL to XUG
  - What about the optional reset for the stats and status commands?
    - Leave them alone?
    - Restrict the command to it to XUG?
    - Remove the optional reset and leave them at XALL?
    - Make it configurable to make all config commands to XUG?