

NAME

ovn-ctl – controls Open Virtual Network daemons.

SYNOPSIS

ovn-ctl [*options*] *command* [-- *extra_args*]

DESCRIPTION

This program is intended to be invoked internally by Open Virtual Network startup scripts. System administrators should not normally invoke it directly.

COMMANDS

start_northd

Starts ovn-northd.

start_controller

Starts ovn-controller.

start_controller_vtep

Starts ovn-controller-vtep.

start_ic

Starts ovn-ic.

start_ovsdb

Starts the OVN Northbound and Southbound database servers.

start_nb_ovsdb

Starts the OVN Northbound database server.

start_sb_ovsdb

Starts the OVN Southbound database server.

start_sb_relay_ovsdb

Starts the OVN Southbound database relay server.

start_ic_ovsdb

Starts the OVN interconnection Northbound and Southbound database servers.

start_ic_nb_ovsdb

Starts the OVN interconnection Northbound database server.

start_ic_sb_ovsdb

Starts the OVN interconnection Southbound database server.

start_ovnbr_ovsdb

Starts the OVN bridge controller database server.

start_ovnbr_controller

Starts the OVN bridge controller.

stop_northd

Stops ovn-northd.

stop_controller

Stops ovn-controller.

stop_controller_vtep

Stops ovn-controller-vtep.

stop_ic

Stops ovn-ic.

stop_ovsdb

Stops the OVN Northbound and Southbound database servers.

stop_nb_ovsdb

Stops the OVN Northbound database server.

stop_sb_ovsdb
Stops the OVN Southbound database server.

stop_sb_relay_ovsdb
Stops the OVN Southbound database relay server.

stop_ic_ovsdb
Stops the OVN interconnection Northbound and Southbound database servers.

stop_ic_nb_ovsdb
Stops the OVN interconnection Northbound database server.

stop_ic_sb_ovsdb
Stops the OVN interconnection Southbound database server.

stop_ovnbr_ovsdb
Stops the OVN bridge controller database server.

stop_ovnbr_controller
Stops the OVN bridge controller.

restart_northd
Restarts ovn-northd.

restart_controller
Restarts ovn-controller.

restart_controller_vtep
Restarts ovn-controller-vtep.

restart_ic
Restarts ovn-ic.

restart_ovsdb
Restarts the OVN Northbound and Southbound database servers.

restart_nb_ovsdb
Restarts the OVN Northbound database server.

restart_sb_ovsdb
Restarts the OVN Southbound database server.

restart_sb_relay_ovsdb
Restarts the OVN Southbound database relay server.

restart_ic_ovsdb
Restarts the OVN interconnection Northbound and Southbound database servers.

restart_ic_nb_ovsdb
Restarts the OVN interconnection Northbound database server.

restart_ic_sb_ovsdb
Restarts the OVN interconnection Southbound database server.

restart_ovnbr_ovsdb
Restarts the OVN bridge controller database server.

restart_ovnbr_controller
Restarts the OVN bridge controller.

promote_ovnnb
Promotes the OVN Northbound database server.

promote_ovnsb
Promotes the OVN Southbound database server.

demote_ovnnb

Demotes the OVN Northbound database server.

demote_ovnsb

Demotes the OVN Southbound database server.

status_ovnnb

Reports the status of the OVN Northbound database server.

status_ovnsb

Reports the status of the OVN Southbound database server.

status_northd

Reports whether northd is running.

status_ovsdb

Reports whether the OVN Northbound and Southbound database servers are running.

status_controller

Reports whether ovn-controller is running.

status_controller_vtep

Reports whether ovn-controller-vtep is running.

status_ic

Reports whether ovn-ic is running.

status_ic_ovsdb

Reports whether the OVN interconnection database servers are running.

status_ovnbr_ovsdb

Reports the status of the OVN bridge controller database server.

status_ovnbr_controller

Reports whether the OVN bridge controller is running.

promote_ic_nb

Promotes the OVN IC-NB database server.

promote_ic_sb

Promotes the OVN IC-SB database server.

demote_ic_nb

Attempts to demote the OVN IC-NB database server. The current implementation does not target the server, so the operation does not complete.

demote_ic_sb

Attempts to demote the OVN IC-SB database server. The current implementation does not target the server, so the operation does not complete.

status_ic_nb

Reports the status of the OVN IC-NB database server.

status_ic_sb

Reports the status of the OVN IC-SB database server.

run_ic_nb_ovsdb

Runs the OVN IC-NB database server in the foreground.

run_ic_sb_ovsdb

Runs the OVN IC-SB database server in the foreground.

run_nb_ovsdb

Runs the OVN Northbound database server in the foreground.

run_sb_ovsdb

Runs the OVN Southbound database server in the foreground.

run_sb_relay_ovsdb

Runs the OVN Southbound database relay server in the foreground and blocks until it exits.

run_ovnbr_ovsdb

Runs the OVN bridge controller database server in the foreground and blocks until it exits.

help Displays usage information.

OPTIONS

--ovn-northd-priority=NICE
--ovn-northd-wrapper=WRAPPER
--ovn-controller-priority=NICE
--ovn-controller-wrapper=WRAPPER
--ovn-ic-priority=NICE
--ovn-ic-wrapper=WRAPPER
--ovsdb-nb-wrapper=WRAPPER
--ovsdb-sb-wrapper=WRAPPER
--ovn-br-controller-priority=NICE
--ovn-br-controller-wrapper=WRAPPER
--ovn-user=USER:GROUP
-h | --help

FILE LOCATION OPTIONS

--db-sock=SOCKET
--db-nb-file=FILE
--db-sb-file=FILE
--db-nb-schema=FILE
--db-sb-schema=FILE
--db-sb-create-insecure-remote=yes|no
--db-nb-create-insecure-remote=yes|no
--db-ic-nb-file=FILE
--db-ic-sb-file=FILE
--db-ic-nb-schema=FILE
--db-ic-sb-schema=FILE
--db-ic-sb-create-insecure-remote=yes|no
--db-ic-nb-create-insecure-remote=yes|no
--db-nb-config-file=FILE
--db-sb-config-file=FILE
--db-ic-nb-config-file=FILE
--db-ic-sb-config-file=FILE
--db-sb-relay-config-file=FILE
--ovn-controller-ssl-key=KEY

--ovn-controller-ssl-cert=CERT
--ovn-controller-ssl-ca-cert=CERT
--ovn-controller-ssl-bootstrap-ca-cert=CERT
--db-ovnbr-sock=SOCKET
--db-ovnbr-file=FILE
--db-ovnbr-schema=FILE
--db-ovnbr-create-insecure-remote=yes|no
--db-ovnbr-config-file=FILE
--ovn-br-controller-ssl-key=KEY
--ovn-br-controller-ssl-cert=CERT
--ovn-br-controller-ssl-ca-cert=CERT
--ovn-br-controller-ssl-bootstrap-ca-cert=CERT

PROTOCOL, CIPHER AND CIPHERSUITE OPTIONS

--ovn-controller-ssl-protocols=PROTOCOLS
--ovn-ic-ssl-protocols=PROTOCOLS
--ovn-northd-ssl-protocols=PROTOCOLS
--ovn-nb-db-ssl-protocols=PROTOCOLS
--ovn-sb-db-ssl-protocols=PROTOCOLS
--ovn-ic-nb-db-ssl-protocols=PROTOCOLS
--ovn-ic-sb-db-ssl-protocols=PROTOCOLS
--ovn-controller-ssl-ciphers=CIPHERS
--ovn-ic-ssl-ciphers=CIPHERS
--ovn-northd-ssl-ciphers=CIPHERS
--ovn-nb-db-ssl-ciphers=CIPHERS
--ovn-sb-db-ssl-ciphers=CIPHERS
--ovn-ic-nb-db-ssl-ciphers=CIPHERS
--ovn-ic-sb-db-ssl-ciphers=CIPHERS
--ovn-controller-ssl-ciphersuites=CIPHERSUITES
--ovn-ic-ssl-ciphersuites=CIPHERSUITES
--ovn-northd-ssl-ciphersuites=CIPHERSUITES
--ovn-nb-db-ssl-ciphersuites=CIPHERSUITES
--ovn-sb-db-ssl-ciphersuites=CIPHERSUITES
--ovn-ic-nb-db-ssl-ciphersuites=CIPHERSUITES
--ovn-ic-sb-db-ssl-ciphersuites=CIPHERSUITES
--ovn-br-controller-ssl-protocols=PROTOCOLS
--ovn-br-db-ssl-protocols=PROTOCOLS
--ovn-br-controller-ssl-ciphers=CIPHERS
--ovn-br-db-ssl-ciphers=CIPHERS
--ovn-br-db-ssl-ciphersuites=CIPHERSUITES

--ovn-controller-ssl-server-name=NAME
--ovn-ic-ssl-server-name=NAME
--ovn-northd-ssl-server-name=NAME
--ovn-nb-db-ssl-server-name=NAME
--ovn-sb-db-ssl-server-name=NAME
--ovn-ic-nb-db-ssl-server-name=NAME
--ovn-ic-sb-db-ssl-server-name=NAME
--ovn-sb-relay-db-ssl-server-name=NAME

ADDRESS AND PORT OPTIONS

--db-nb-sync-from-addr=IP ADDRESS
--db-nb-sync-from-port=PORT NUMBER
--db-nb-sync-from-proto=PROTO
--db-sb-sync-from-addr=IP ADDRESS
--db-sb-sync-from-port=PORT NUMBER
--db-sb-sync-from-proto=PROTO
--db-ic-nb-sync-from-addr=IP ADDRESS
--db-ic-nb-sync-from-port=PORT NUMBER
--db-ic-nb-sync-from-proto=PROTO
--db-ic-sb-sync-from-addr=IP ADDRESS
--db-ic-sb-sync-from-port=PORT NUMBER
--db-ic-sb-sync-from-proto=PROTO
--ovn-northd-nb-db=PROTO:IP ADDRESS: PORT..
--ovn-northd-sb-db=PROTO:IP ADDRESS: PORT..
--ovn-ic-nb-db=PROTO:IP ADDRESS: PORT..
--ovn-ic-sb-db=PROTO:IP ADDRESS: PORT..

CLUSTERING OPTIONS

--db-nb-cluster-local-addr=IP ADDRESS
--db-nb-cluster-local-port=PORT NUMBER
--db-nb-cluster-local-proto=PROTO (tcp/ssl)
--db-nb-cluster-remote-addr=IP ADDRESS
--db-nb-cluster-remote-port=PORT NUMBER
--db-nb-cluster-remote-proto=PROTO (tcp/ssl)
--db-nb-election-timer=Timeout in milliseconds
--db-sb-cluster-local-addr=IP ADDRESS
--db-sb-cluster-local-port=PORT NUMBER
--db-sb-cluster-local-proto=PROTO (tcp/ssl)
--db-sb-cluster-remote-addr=IP ADDRESS
--db-sb-cluster-remote-port=PORT NUMBER
--db-sb-cluster-remote-proto=PROTO (tcp/ssl)
--db-sb-election-timer=Timeout in milliseconds

```
--db-ic-nb-cluster-local-addr=IP ADDRESS
--db-ic-nb-cluster-local-port=PORT NUMBER
--db-ic-nb-cluster-local-proto=PROTO (tcp/ssl)
--db-ic-nb-cluster-remote-addr=IP ADDRESS
--db-ic-nb-cluster-remote-port=PORT NUMBER
--db-ic-nb-cluster-remote-proto=PROTO (tcp/ssl)
--db-ic-sb-cluster-local-addr=IP ADDRESS
--db-ic-sb-cluster-local-port=PORT NUMBER
--db-ic-sb-cluster-local-proto=PROTO (tcp/ssl)
--db-ic-sb-cluster-remote-addr=IP ADDRESS
--db-ic-sb-cluster-remote-port=PORT NUMBER
--db-ic-sb-cluster-remote-proto=PROTO (tcp/ssl)
--db-cluster-schema-upgrade=yes|no
```

PROBE INTERVAL OPTIONS

```
--db-nb-probe-interval-to-active=Time in milliseconds
--db-sb-probe-interval-to-active=Time in milliseconds
```

EXTRA OPTIONS

Any options after '-' will be passed on to the binary run by *command* with the exception of *start_northd*, which can have options specified in *ovn-northd-db-params.conf*. Any *extra_args* passed to *start_northd* will be passed to the *ovsdb-servers* if **--ovn-manage-ovsdb=yes**

CONFIGURATION FILES

Following are the optional configuration files. If present, it should be located in the *etc* dir

ovnnb-active.conf

If present, this file should hold the url to connect to the active Northbound DB server

```
tcp:x.x.x.x:6641
```

ovnsb-active.conf

If present, this file should hold the url to connect to the active Southbound DB server

```
tcp:x.x.x.x:6642
```

ovn-northd-db-params.conf

If present, *start_northd* will not start the DB server even if **--ovn-manage-ovsdb=yes**. This file should hold the database url parameters to be passed to *ovn-northd*.

```
--ovnnb-db=tcp:x.x.x.x:6641 --ovnsb-db=tcp:x.x.x.x:6642
```

ic-nb-active.conf

If present, this file should hold the url to connect to the active Interconnection Northbound DB server

```
tcp:x.x.x.x:6645
```

ic-sb-active.conf

If present, this file should hold the url to connect to the active Interconnection Southbound DB server

```
tcp:x.x.x.x:6646
```

ovn-ic-db-params.conf

If present, this file should hold the database url parameters to be passed to *ovn-ic*.

```
--ic-nb-db=tcp:x.x.x.x:6645 --ic-sb-db=tcp:x.x.x.x:6646
```

RUNNING OVN DB SERVERS WITHOUT DETACHING

ovn-ctl run_nb_ovsdb

This command runs the OVN nb ovsdb-server without passing the **detach** option, making it to block until ovsdb-server exits. This command will be useful for starting the OVN nb ovsdb-server in a container.

ovn-ctl run_sb_ovsdb

This command runs the OVN sb ovsdb-server without passing the **detach** option, making it to block until ovsdb-server exits. This command will be useful for starting the OVN sb ovsdb-server in a container.

ovn-ctl run_ic_nb_ovsdb

This command runs the OVN IC-NB ovsdb-server without passing the **detach** option, making it to block until ovsdb-server exits. This command will be useful for starting the OVN IC-NB ovsdb-server in a container.

ovn-ctl run_ic_sb_ovsdb

This command runs the OVN IC-SB ovsdb-server without passing the **detach** option, making it to block until ovsdb-server exits. This command will be useful for starting the OVN IC-SB ovsdb-server in a container.

ovn-ctl run_ovnbr_ovsdb

This command runs the OVN bridge db ovsdb-server without passing the **detach** option, making it to block until ovsdb-server exits. This command will be useful for starting the OVN br db ovsdb-server in a container.

EXAMPLE USAGE

Run ovn-controller on a host already running OVS

```
# ovn-ctl start_controller
```

Run ovn-northd on a host already running OVS

```
# ovn-ctl start_northd
```

All-in-one OVS+OVN for testing

```
# ovs-ctl start --system-id="random"
```

```
# ovn-ctl start_northd
```

```
# ovn-ctl start_controller
```

Promote and demote ovsdb servers

```
# ovn-ctl promote_ovnnb
```

```
# ovn-ctl promote_ovnsb
```

```
# ovn-ctl --db-nb-sync-from-addr=x.x.x.x --db-nb-sync-from-port=6641 --db-nb-probe-interval-to-active=60000 demote_ovnnb
```

```
# ovn-ctl --db-sb-sync-from-addr=x.x.x.x --db-sb-sync-from-port=6642 --db-sb-probe-interval-to-active=60000 demote_ovnsb
```

Creating a clustered db on 3 nodes with IPs x.x.x.x, y.y.y.y and z.z.z.z

Starting OVN ovsdb servers and ovn-northd on the node with IP x.x.x.x

```
# ovn-ctl --db-nb-addr=x.x.x.x --db-nb-create-insecure-remote=yes --db-sb-addr=x.x.x.x --db-sb-create-insecure-remote=yes --db-nb-cluster-local-addr=x.x.x.x --db-sb-cluster-local-addr=x.x.x.x --ovn-northd-nb-db=tcp:x.x.x.x:6641,tcp:y.y.y.y:6641,tcp:z.z.z.z:6641 --ovn-northd-sb-db=tcp:x.x.x.x:6642,tcp:y.y.y.y:6642,tcp:z.z.z.z:6642 start_northd
```

Starting OVN ovsdb-servers and ovn-northd on the node with IP y.y.y.y and joining the cluster started at x.x.x.x

```
# ovn-ctl --db-nb-addr=y.y.y.y --db-nb-create-insecure-remote=yes --db-sb-addr=y.y.y.y --db-sb-create-insecure-remote=yes --db-nb-cluster-local-addr=y.y.y.y --db-sb-cluster-local-addr=y.y.y.y --db-nb-cluster-remote-addr=x.x.x.x --db-sb-cluster-remote-addr=x.x.x.x
```

```

--ovn-northd-nb-db=tcp:x.x.x.x:6641,tcp:y.y.y.y:6641,tcp:z.z.z.z:6641
--ovn-northd-sb-db=tcp:x.x.x.x:6642,tcp:y.y.y.y:6642,tcp:z.z.z.z:6642 start_northd

```

Starting OVN ovsdb-servers and ovn-northd on the node with IP z.z.z.z and joining the cluster started at x.x.x.x

```

# ovn-ctl --db-nb-addr=z.z.z.z --db-nb-create-insecure-remote=yes --db-nb-cluster-local-addr=z.z.z.z --db-sb-addr=z.z.z.z --db-sb-create-insecure-remote=yes --db-sb-cluster-local-addr=z.z.z.z --db-nb-cluster-remote-addr=x.x.x.x --db-sb-cluster-remote-addr=x.x.x.x
--ovn-northd-nb-db=tcp:x.x.x.x:6641,tcp:y.y.y.y:6641,tcp:z.z.z.z:6641
--ovn-northd-sb-db=tcp:x.x.x.x:6642,tcp:y.y.y.y:6642,tcp:z.z.z.z:6642 start_northd

```

Passing ssl keys when starting OVN dbs will supersede the default ssl values in db

Starting standalone ovn db server passing SSL/TLS certificates

```

# ovn-ctl --ovn-nb-db-ssl-key=/etc/ovn/ovnnb-privkey.pem
--ovn-nb-db-ssl-cert=/etc/ovn/ovnnb-cert.pem --ovn-nb-db-ssl-ca-cert=/etc/ovn/cacert.pem
--ovn-sb-db-ssl-key=/etc/ovn/ovnsb-privkey.pem --ovn-sb-db-ssl-cert=/etc/ovn/ovnsb-cert.pem
--ovn-sb-db-ssl-ca-cert=/etc/ovn/cacert.pem start_northd

```

Avoiding automatic clustered OVN database schema upgrade

If you desire more control over clustered DB schema upgrade, you can opt-out of automatic on-start upgrade attempts with **--no-db-cluster-schema-upgrade**.

Start OVN NB and SB clustered databases on host with IP x.x.x.x without schema upgrade

```

# ovn-ctl start_nb_ovsdb --db-nb-cluster-local-addr=x.x.x.x --no-db-cluster-schema-upgrade
# ovn-ctl start_sb_ovsdb --db-sb-cluster-local-addr=x.x.x.x --no-db-cluster-schema-upgrade

```

Trigger clustered DB schema upgrade manually

```

# ovsdb-client convert unix:/var/run/ovn/ovnnb_db.sock /usr/local/share/ovn/ovn-nb.ovsschema #
ovsdb-client convert unix:/var/run/ovn/ovnsb_db.sock /usr/local/share/ovn/ovn-sb.ovsschema

```

Run OVN bridge controller services on a host already running OVS

```

# ovn-ctl start_ovnbr_ovsdb
# ovn-ctl start_ovnbr_controller

```