NAME

ovn-ic – Open Virtual Network interconnection controller

SYNOPSIS

ovn-ic [*options*]

DESCRIPTION

ovn-ic, OVN interconnection controller, is a centralized daemon which communicates with global interconnection databases IC_NB/IC_SB to configure and exchange data with local NB/SB for interconnecting with other OVN deployments.

OPTIONS

--ovnnb-db=*database*

The OVSDB database containing the OVN Northbound Database. If the **OVN_NB_DB** environment variable is set, its value is used as the default. Otherwise, the default is **unix:/ovnnb_db.sock**.

--ovnsb-db=*database*

The OVSDB database containing the OVN Southbound Database. If the **OVN_SB_DB** environment variable is set, its value is used as the default. Otherwise, the default is **unix:/ovnsb_db.sock**.

--ic-nb-db=*database*

The OVSDB database containing the OVN Interconnection Northbound Database. If the **OVN_IC_NB_DB** environment variable is set, its value is used as the default. Otherwise, the default is **unix:/ovn_ic_nb_db.sock**.

--ic-sb-db=*database*

The OVSDB database containing the OVN Interconnection Southbound Database. If the **OVN_IC_SB_DB** environment variable is set, its value is used as the default. Otherwise, the default is **unix:/ovn_ic_sb_db.sock**.

--dump-inc-proc-graph [**=***node*]

Dump the incremental processing engine graph representation in DOT format to stdout at startup and then exit. If *node* is specified, only the subgraph rooted at that engine node is printed.

database in the above options must be an OVSDB active or passive connection method, as described in **ovsdb**(7).

Daemon Options

--pidfile[**=***pidfile*]

Causes a file (by default, *program***.pid**) to be created indicating the PID of the running process. If the *pidfile* argument is not specified, or if it does not begin with **/**, then it is created in .

If **--pidfile** is not specified, no pidfile is created.

--overwrite-pidfile

By default, when **--pidfile** is specified and the specified pidfile already exists and is locked by a running process, the daemon refuses to start. Specify **--overwrite-pidfile** to cause it to instead overwrite the pidfile.

When **--pidfile** is not specified, this option has no effect.

--detach

Runs this program as a background process. The process forks, and in the child it starts a new session, closes the standard file descriptors (which has the side effect of disabling logging to the console), and changes its current directory to the root (unless **--no-chdir** is specified). After the child completes its initialization, the parent exits.

--monitor

Creates an additional process to monitor this program. If it dies due to a signal that indicates a programming error (**SIGABRT**, **SIGALRM**, **SIGBUS**, **SIGFPE**, **SIGILL**, **SIGPIPE**, **SIGSEGV**, **SIGXCPU**, or **SIGXFSZ**) then the monitor process starts a new copy of it. If the daemon dies or

exits for another reason, the monitor process exits.

This option is normally used with **−−detach**, but it also functions without it.

−−no−chdir

By default, when **−−detach** is specified, the daemon changes its current working directory to the root directory after it detaches. Otherwise, invoking the daemon from a carelessly chosen directory would prevent the administrator from unmounting the file system that holds that directory.

Specifying **−−no−chdir** suppresses this behavior, preventing the daemon from changing its current working directory. This may be useful for collecting core files, since it is common behavior to write core dumps into the current working directory and the root directory is not a good directory to use.

This option has no effect when **−−detach** is not specified.

−−no−self−confinement

By default this daemon will try to self-confine itself to work with files under well-known directories determined at build time. It is better to stick with this default behavior and not to use this flag unless some other Access Control is used to confine daemon. Note that in contrast to other access control implementations that are typically enforced from kernel-space (e.g. DAC or MAC), self-confinement is imposed from the user-space daemon itself and hence should not be considered as a full confinement strategy, but instead should be viewed as an additional layer of security.

−−user=*user***:***group*

Causes this program to run as a different user specified in *user***:***group*, thus dropping most of the root privileges. Short forms *user* and **:***group* are also allowed, with current user or group assumed, respectively. Only daemons started by the root user accepts this argument.

On Linux, daemons will be granted **CAP_IPC_LOCK** and **CAP_NET_BIND_SERVICES** before dropping root privileges. Daemons that interact with a datapath, such as **ovs−vswitchd**, will be granted three additional capabilities, namely **CAP_NET_ADMIN**, **CAP_NET_BROADCAST** and **CAP_NET_RAW**. The capability change will apply even if the new user is root.

Logging Options

−v[*spec*]

−−verbose=[*spec*]

Sets logging levels. Without any *spec*, sets the log level for every module and destination to **dbg**. Otherwise, *spec* is a list of words separated by spaces or commas or colons, up to one from each category below:

- A valid module name, as displayed by the **vlog/list** command on **ovs−appctl**(8), limits the log level change to the specified module.
- **syslog**, **console**, or **file**, to limit the log level change to only to the system log, to the console, or to a file, respectively. (If **−−detach** is specified, the daemon closes its standard file descriptors, so logging to the console will have no effect.)
- **off**, **emer**, **err**, **warn**, **info**, or **dbg**, to control the log level. Messages of the given severity or higher will be logged, and messages of lower severity will be filtered out. **off** filters out all messages. See **ovs−appctl**(8) for a definition of each log level.

Case is not significant within *spec*.

Regardless of the log levels set for **file**, logging to a file will not take place unless **−−log−file** is also specified (see below).

For compatibility with older versions of OVS, **any** is accepted as a word but has no effect.

−v

−−verbose

Sets the maximum logging verbosity level, equivalent to **−−verbose=dbg**.

−vPATTERN:*destination***:***pattern*
−−verbose=PATTERN:*destination***:***pattern*
Sets the log pattern for *destination* to *pattern*. Refer to **ovs−appctl**(8) for a description of the valid syntax for *pattern*.

−vFACILITY:*facility*
−−verbose=FACILITY:*facility*
Sets the RFC5424 facility of the log message. *facility* can be one of **kern**, **user**, **mail**, **daemon**, **auth**, **syslog**, **lpr**, **news**, **uucp**, **clock**, **ftp**, **ntp**, **audit**, **alert**, **clock2**, **local0**, **local1**, **local2**, **local3**, **local4**, **local5**, **local6** or **local7**. If this option is not specified, **daemon** is used as the default for the local system syslog and **local0** is used while sending a message to the target provided via the **−−syslog−target** option.

−−log−file[**=***file*]
Enables logging to a file. If *file* is specified, then it is used as the exact name for the log file. The default log file name used if *file* is omitted is **/usr/local/var/log/ovn/***program***.log**.

−−syslog−target=*host***:***port*
Send syslog messages to UDP *port* on *host*, in addition to the system syslog. The *host* must be a numerical IP address, not a hostname.

−−syslog−method=*method*
Specify *method* as how syslog messages should be sent to syslog daemon. The following forms are supported:

- **libc**, to use the libc **syslog()** function. Downside of using this options is that libc adds fixed prefix to every message before it is actually sent to the syslog daemon over **/dev/log** UNIX domain socket.
- **unix:***file*, to use a UNIX domain socket directly. It is possible to specify arbitrary message format with this option. However, **rsyslogd 8.9** and older versions use hard coded parser function anyway that limits UNIX domain socket use. If you want to use arbitrary message format with older **rsyslogd** versions, then use UDP socket to localhost IP address instead.
- **udp:***ip***:***port*, to use a UDP socket. With this method it is possible to use arbitrary message format also with older **rsyslogd**. When sending syslog messages over UDP socket extra precaution needs to be taken into account, for example, syslog daemon needs to be configured to listen on the specified UDP port, accidental iptables rules could be interfering with local syslog traffic and there are some security considerations that apply to UDP sockets, but do not apply to UNIX domain sockets.
- **null**, to discard all messages logged to syslog.

The default is taken from the **OVS_SYSLOG_METHOD** environment variable; if it is unset, the default is **libc**.

PKI Options

PKI configuration is required in order to use SSL/TLS for the connections to the Northbound and Southbound databases.

−p *privkey.pem*
−−private−key=*privkey.pem*
Specifies a PEM file containing the private key used as identity for outgoing SSL/TLS connections.

−c *cert.pem*
−−certificate=*cert.pem*
Specifies a PEM file containing a certificate that certifies the private key specified on **−p** or **−−private−key** to be trustworthy. The certificate must be signed by the certificate authority (CA) that the peer in SSL/TLS connections will use to verify it.

−C *cacert.pem*
−−ca−cert=*cacert.pem*
Specifies a PEM file containing the CA certificate for verifying certificates presented to this program by SSL/TLS peers. (This may be the same certificate that SSL/TLS peers use to verify the certificate specified on **−c** or **−−certificate**, or it may be a different one, depending on the PKI design in use.)

−C none
−−ca−cert=none
Disables verification of certificates presented by SSL/TLS peers. This introduces a security risk, because it means that certificates cannot be verified to be those of known trusted hosts.

−−ssl−server−name=*servername*
Specifies the server name to use for TLS Server Name Indication (SNI). By default, the hostname from the connection string is used for SNI. This option allows overriding the SNI hostname, which is useful when connecting through proxies or service meshes where the connection endpoint differs from the intended server name.

Other Options
−−unixctl=*socket*
Sets the name of the control socket on which *program* listens for runtime management commands (see *RUNTIME MANAGEMENT COMMANDS,* below). If *socket* does not begin with **/**, it is interpreted as relative to . If **−−unixctl** is not used at all, the default socket is **/***program***.***pid***.ctl**, where *pid* is *program*'s process ID.

Specifying **none** for *socket* disables the control socket feature.

−h
−−help
Prints a brief help message to the console.

−V
−−version
Prints version information to the console.

RUNTIME MANAGEMENT COMMANDS

ovn−appctl can send commands to a running **ovn−ic** process. The currently supported commands are described below.

exit Causes **ovn−ic** to gracefully terminate.

pause Pauses the ovn-ic operation from processing any database changes. This will also instruct ovn-ic to drop any lock on SB DB.

resume
Resumes the ovn-ic operation to process database contents. This will also instruct ovn-northd to aspire for the lock on SB DB.

is−paused
Returns "true" if ovn-ic is currently paused, "false" otherwise.

status Prints this server's status. Status will be "active" if ovn-ic has acquired OVSDB lock on SB DB, "standby" if it has not or "paused" if this instance is paused.

inc−engine/show−stats
Display **ovn−ic** engine counters. For each engine node the following counters have been added:

- **recompute**
- **compute**
- **cancel**

inc−engine/show−stats *engine_node_name* [*counter_name*]
Display the **ovn−ic** engine counter(s) for the specified *engine_node_name*. *counter_name* is optional and can be one of **recompute**, **compute** or **cancel**.

inc−engine/clear−stats
Reset **ovn−ic** engine counters.

inc−engine/recompute
Triggers a full recompute of the incremental processing engine on the next iteration.

inc−engine/compute−log−timeout *msecs*
Sets the timeout in milliseconds for logging engine compute events.

inc−engine/list−stopwatches [*node*]
Lists the engine nodes and their change handler names. If *node* is specified, only the handlers for that engine node are listed.

inc−engine/enable−stopwatch [*node*]
Enables the per-node and per-handler stopwatches in the incremental processing engine. If *node* is specified, only that node's stopwatches are enabled; otherwise all nodes are affected. While enabled, every engine node recompute and change handler invocation is timed and the results can be viewed with the **stopwatch/show** command. Stopwatches are disabled by default because they add measurable CPU overhead.

inc−engine/disable−stopwatch [*node*]
Disables the per-node and per-handler stopwatches in the incremental processing engine. If *node* is specified, only that node's stopwatches are disabled; otherwise all nodes are affected. This is the default state.

ACTIVE-STANDBY FOR HIGH AVAILABILITY

You may run **ovn−ic** more than once in an OVN deployment. When connected to a standalone or clustered DB setup, OVN will automatically ensure that only one of them is active at a time. If multiple instances of **ovn−ic** are running and the active **ovn−ic** fails, one of the hot standby instances of **ovn−ic** will automatically take over.