

Hidden cord one-piece elongated toilet with skirted trapway, dual-flush

K-1381-HC

Features

- One-piece toilets integrate the tank and bowl into a seamless, easy-to-clean design
- Elongated bowl offers added room and comfort
- Dual flush offers a choice of 0.8 or 1.28 gpf (3.0 or 4.8 lpf)
- Left-hand Polished Chrome trip lever
- 2-1/8" (54 mm) glazed trapway
- Skirted trapway simplifies cleaning
- Hidden cord design conceals bidet seat cords (bidet seat sold separately)
- Coordinates with other products in the Veil collection
- Includes bidet water inlet hose



Standard 12" (305 mm) rough-in

Recommended Products/Accessories

K-28821 PureWash® E930 Elongated bidet toilet seat with remote control

K-8298-CR PureWash® E820 Elongated bidet toilet seat with remote control

K-27142-CR PureWash® E700 Elongated bidet toilet seat with remote control

K-26132-CSP PureWash® E545 Elongated bidet toilet seat 1023457 Wax Ring/Hardware Kit

1265114 Connector Hose





Codes/Standards

ASME A112.19.2/CSA B45.1 ASME A112.19.14 DOE - Energy Policy Act 1992 EPA WaterSense® California Energy Commission (CEC) IAPMO Certification

KOHLER® Toilets and Seats Limited Warranty

See website for detailed warranty information.

Available Colors/Finishes

Color tiles intended for reference only.


Color	Code	Description
	0	White
	7	Black Black™





Hidden cord one-piece elongated toilet with skirted trapway, dual-flush

K-1381-HC



Technical Information

All product dimensions are nominal. Toilet type: Floor-mount

Waste Outlet: Floor

Bowl shape: Compact elongated

Flush type: Class Five Trap passageway: 2" (51 mm)

Water surface size: 9" x 7-1/2" (229 mm x 191 mm)

Rim to water 5-3/8" (137 mm)

surface:

Rough-in: 12" (305 mm)

Template: Footprint, 1262234-7, not required,

included

Fixture Supply Requirements

Min static pressure: 20 psi (137.9 kPa) Max static pressure: 80 psi (551.6 kPa) Min flowing 15 psi (103.4 kPa)

pressure:

6-8-2024 20:05 - US

Min flow rate: 1 gpm (3.8 lpm)

Notes

Install this product according to the installation instructions.

