


REMOTE PROCEDURE CALL

51

51

RPC as a Programming Abstraction



Copyright Springer Verlag Berlin Heidelberg 2004

52

52

The basic RPC protocol

client



server



*registers with
name service*

53

53

The basic RPC protocol

client

*“binds” to
server*



server


*registers with
name service*



54

54


The basic RPC protocol



55

55


The basic RPC protocol



56

56


The basic RPC protocol



57


57

The basic RPC protocol




58


58




59




60



61



62



63

Data in messages

- Marshalling
- Byte ordering issues (big-endian versus little endian), strings (some CPUs require padding), alignment, etc
- As fast as possible
 - yet must also be very general

64

64

Fancy argument passing

- RPC transparent for simple calls
 - New forms of exceptions
- Complex structures, pointers, big arrays?
- Most limit size, types of RPC arguments.

65

65

RPC WITH LOST MESSAGES

66

66

RPC Semantics in the Presence of Failures

- The client is unable to locate the server
- The request message from the client to server is lost
- The reply message from the client is lost
- The server crashes after sending a request
- The client crashes after sending a request

67

67


Client is Unable to Locate Server

- Causes:
 - server down
 - server moved
 - different version of server, ...
- Fixes
 - Network failure exceptions
 - Transparency is lost

68

68

Messages Lost



69

69


Lost Request Message

- Easiest to deal with
- Just retransmit the message!
- If multiple message are lost then
 - “client is unable to locate server” error

70

70


Overcoming lost packets



71

71


Overcoming lost packets



72

72


Overcoming lost packets



73

73


Overcoming lost packets



74

74


Overcoming lost packets



75

75

Overcoming lost packets



76

76


Costs in fault-tolerant version?

- Acks are expensive.
 - Suppress the initial ack
- Retransmission is costly.
 - Tune the delay
- Big messages
 - ack a burst at a time

77

77

Big packets



78

78

Lost Reply Message

- Did server execute the procedure or not?
- Possible fixes
 - Retransmit the request
 - Only works if operation is idempotent
 - What if operation not idempotent?
 - Assign unique sequence numbers to every request
 - **Shared state between client and server...**

79


79

RPC WITH CRASHES

80

80


Server Crashes



81

81

Server Crashes



Client cannot distinguish these scenarios

82

82

Server Crashes

- Three possible semantics
 - At least once semantics
 - Client keeps trying until it gets a reply
 - At most once semantics
 - Client gives up on failure
 - Exactly once semantics
 - Can this be correctly implemented?

83

83

Impossibility of Exactly Once Semantics (1)

- Example: Print server
 - Client wants to print a document on the server
 - Three possible events at server:
 - Reply with completion message (R)
 - Print the text (P)
 - Crash (C)

84

84

Impossibility of Exactly Once Semantics (2)

- These events (R, P, C) can occur in six different orderings:

Reply	Reply	Crash	Print	Print	Crash
Print	Crash	(Reply)	Reply	Crash	(Print)
Crash	(Print)	(Print)	Crash	(Reply)	(Reply)

85

85

Impossibility of Exactly Once Semantics (3)

- Assume server crashes, later recovers, and notifies clients
- What should clients do?

Client reissue strategy	Server (strategy R → P)		
	RPC	RC(P)	C(RP)
Always	DUP	OK	OK
Never	OK	ZERO	ZERO
Only when ACK	DUP	OK	ZERO
Only when not ACK	OK	ZERO	OK

86

86

Impossibility of Exactly Once Semantics (4)

- Assume server crashes, later recovers, and notifies clients
- What should clients do?

Client reissue strategy	Server (strategy $P \rightarrow R$)		
	PRC	PC(R)	C(PR)
Always	DUP	DUP	OK
Never	OK	OK	ZERO
Only when ACK	DUP	OK	ZERO
Only when not ACK	OK	DUP	OK

87

Impossibility of Exactly Once Semantics (5)

- Can we fix this?
- Fundamental problem: distributed agreement
- Analogy: Coordinating attacks of allied armies
 - Allied armies on opposing hillsides
 - Messengers travel through valley occupied by enemy
 - Omission failures (not Byzantine!)


88

88

Impossibility of Exactly Once Semantics (6)



Shall we attack?



89

89

Client Crashes

- Let's the server computation **orphan**
- Orphans can
 - Waste CPU cycles
 - Lock files
 - Client reboots and it gets the old reply immediately

90

90

Client Crashes: Possible Solutions

- Extermination:
 - Client log, kill orphan on reboot
 - Disadvantage: log overhead
- Reincarnation:
 - Client broadcasts new “epoch” when reboots
 - New epoch: servers kill orphans
 - Disadvantage: network partition

91

91

Client Crashes: Possible Solutions

- Expiration:
 - Each RPC is given a lease T
 - Must renew lease before expiration
 - If client reboots after T sec, all orphans are gone
 - Problem: what is a good value of T ?

92

92