

# Distributed Transactions

Dominic Duggan


Stevens Institute of Technology

Based in part on materials by K. Birman

1

1


## Client, server, and databases



2

2

## Multiple Databases




3

3

## Transactional RPC


- Transaction Managers
- Transaction Processing Monitor (TPM)
- XA API



4

4


## Basic TRPC (making calls)



5

5


## Basic TRPC (making calls)



6


6

## Basic TRPC (making calls)



7

## Basic TRPC (making calls)




8

7

8


## Basic TRPC (making calls)



9

9


## Basic TRPC (committing calls)



10


10

## Basic TRPC (committing calls)



11

## Basic TRPC (committing calls)



12

## TWO PHASE COMMIT (2PC)

13

13

## Atomic Commitment

- Given a set of processes
- **Coordinator** (i.e. TPM) wants to initiate an action (commit)
- **Participants** may vote for or against the action
- Perform the action only if all vote in favor
- Otherwise abort
- Goal is *all-or-nothing* outcome

14

14


## Non-triviality

- Avoid solutions that do nothing
- What is a trivial solution?
- What is a validity condition?

15

15

## Commit protocol illustrated




16

16




## Commit protocol illustrated



17

17

## Commit protocol illustrated



*Note: garbage collection protocol not shown here*

18

18


## Two-phase Commit

- Phase 0: Flush caches on Web, app server
- Phase 1: Coordinator asks participants for vote
  - Data managers force updates to the log
  - Then say “ok to commit”
- Phase 2: If all are ok to commit, then coordinator tells participants to commit. Otherwise, abort.
- Data managers then make updates permanent or rollback to old values, and release locks

19

19

## Commit protocol illustrated



*Note: garbage collection protocol not shown here*

20

20

## Non-triviality

- Avoid solutions that do nothing
- Commit validity: if all vote for commit, protocol must commit
- ...but what if participant vote is lost?
- “Non-triviality” condition hard to capture

21

21

## Unilateral abort

- Any data manager can unilaterally abort a transaction until it has said “prepared”
- Implication: even a data manager where only reads were done must participate in 2PC protocol!

22

22

## **PROBLEMS WITH 2PC**

23

23

## **Non-blocking Commit**

- Goal: a protocol that allows all operational processes to terminate the protocol even if some subset crash

24

24


## Commit with unreliable failure detectors

- Assume processes fail by crashing
  - No Byzantine failures
- Coordinator detects failures (unreliably) using timeouts
- Challenge: terminate the protocol if the coordinator fails

25

25

## 2 phase commit



26

## **THREE PHASE COMMIT (3PC)**

27

27

### Three-phase commit

- Seeks to increase availability
- Makes an unrealistic assumption that failures are accurately detectable
- With this, can terminate the protocol even if a failure does occur

28

28


## Three-phase commit

- Coordinator starts protocol by sending **request**
- Participants vote to commit or to abort
- Coordinator collects votes, decides on outcome
- Coordinator can abort immediately
- To commit, coordinator first sends a “**prepare to commit**” message
- Participants acknowledge, commit occurs during a final round of “**commit**” messages

29


29

## Three-phase commit



30


## State diagram for non-faulty member



31

31

## State diagram for non-faulty member




32

32




## State diagram for non-faulty member



33

33


## State diagram for non-faulty member



34

34


## State diagram for non-faulty member



35

35


## State diagram for non-faulty member



36

36


## State diagram for non-faulty member



37

37

## State diagram for non-faulty member



38

38

## Observations about 3PC

- Key point: Extra buffer state
- What if none of surviving participants have heard from coordinator?
  - After voting phase
  - 2PC: Some crashed processes may have committed
  - 3PC: No crashed process has committed yet (Why?)

39

39

## Observations about 3PC

- If any process is in “prepare to commit” all voted for commit
- Protocol commits only when all surviving processes have acknowledged prepare to commit
- After coordinator fails, it is easy to run the protocol forward to commit state (or back to abort state)

40

40

## Problems with 3PC

- Assumes reliable failure detectors
- But even with realistic failure detectors (that can make mistakes), protocol still blocks!
  - “Network partitioning”
- Can prove that this problem is not avoidable

41

41


## Situation in practical systems?

- Most use protocols based on 2PC
- Need to extend garbage collection
  - protocol state information
- Some systems accept the risk of blocking
- Others reduce the consistency property to make progress

42

42

## Example: Primary with Backup



43