


# PAXOS

67

67


## RSM: Split-Brain



68

68

## Paxos: Consensus Box




- Collects proposed values
- Picks one proposed value
- Remembers it forever

69

69


## Paxos: Normal Execution



70


70

## Paxos: Normal Execution




71

## Paxos: Normal Execution




72

## Paxos: Split Brain



73

## Paxos: Split Brain



74

## Paxos: general approach

- One (or more) node decides to be the **leader**
- Leader proposes a value and solicits acceptance from others (**acceptors**)
- Leader announces result **or tries again**

75

75

## Paxos requirement

- Correctness (**safety**):
  - All nodes agree on the same value
  - The agreed value X has been proposed by some node
- Fault-tolerance:
  - If less than  $N/2$  nodes fail, the rest nodes should reach agreement *eventually w.h.p*
  - **Liveness** is not *guaranteed*

76

76

## Why is agreement hard?

- What if  $>1$  nodes become leaders simultaneously?
- What if there is a network partition?
- What if a leader crashes in the middle of solicitation?
- What if a leader crashes after deciding but before announcing results?
- What if the new leader proposes different values than already decided value?

77

77


## Paxos setup

- Each node runs as a *proposer*, *acceptor* and *learner*
- **Proposer** (leader) proposes a value and solicit acceptance from **acceptors**
- Leader announces the chosen value to **learners**

78

78

## Paxos setup




79

79

## Strawman 1: Single Acceptor

- Designate a single node X as acceptor (e.g. one with smallest id)
  - Each *proposer* sends its value to X
  - X decides on one of the values
  - X announces its decision to all *learners*
- **Problem?**
  - Failure of the single acceptor halts decision
  - Need multiple acceptors!




80

80

## Strawman 2: multiple acceptors

- Each proposer (leader) proposes to all acceptors
- Each acceptor accepts the first proposal it receives and rejects other proposals
- If the leader receives positive replies from a majority of acceptors, it chooses its own value
  - There is at most 1 majority, hence only a single value is chosen
- Leader sends chosen value to all learners



81

## Strawman 2: multiple acceptors

- Each proposer (leader) proposes to all acceptors
- Each acceptor accepts the first proposal it receives
  - Rejects other proposals
- If the leader receives positive replies from a majority of acceptors, it chooses its own value
  - There is at most 1 majority
- Leader sends chosen value to all learners
- **Problem:**
  - What if multiple leaders propose simultaneously so there is **no majority** accepting?

82

82



## Paxos solution

- Proposals (for a value e.g.  $k^{\text{th}}$  command) are ordered by proposal #
- Each acceptor must accept the first proposal that it receives
- Each acceptor may accept multiple proposals
  - If a proposal with value  $v$  is chosen, all higher proposals chosen have value  $v$

83

83

## Paxos solution

- Proposals (for a value e.g.  $k^{\text{th}}$  command) are ordered by proposal #
- Each acceptor must accept the first proposal that it receives
- Each acceptor may accept multiple proposals
  - If a proposal with value  $v$  is chosen, all higher proposals chosen have value  $v$
  - If a proposal with value  $v$  is chosen, all higher proposals accepted by any acceptor have value  $v$

84

84

## Paxos solution

- Proposals (for a value e.g.  $k^{\text{th}}$  command) are ordered by proposal #
- Each acceptor must accept the first proposal that it receives
- Each acceptor may accept multiple proposals
  - If a proposal with value  $v$  is chosen, all higher proposals chosen have value  $v$
  - If a proposal with value  $v$  is chosen, all higher proposals accepted by any acceptor have value  $v$
  - If a proposal with value  $v$  is chosen, all higher proposals issued by any proposer have value  $v$

85

85

## Paxos solution

- Proposals (for a value e.g.  $k^{\text{th}}$  command) are ordered by proposal #
  - Each acceptor must accept the first proposal that it receives
  - Each acceptor
    - If a proposal with value  $v$  is chosen, all higher proposals chosen have value  $v$
    - If a proposal with value  $v$  is chosen, all higher proposals accepted by any acceptor have value  $v$
    - If a proposal with value  $v$  is chosen, all higher proposals issued by any proposer have value  $v$
- Before proposing value  $v$  for proposal  $n$ , proposer will poll acceptors for
- Promise that they will not accept any future proposals  $< n$
  - What value if any that they accepted for highest numbered proposal  $< n$

86

86

## Paxos operation: node state

- Each node maintains:
  - $n_a, v_a$ : highest proposal # and its corresponding accepted value
    - initially null
  - $n_h$ : highest proposal # seen
  - $my_n$ : my proposal # in current Paxos

87

87

## Paxos operation: 3P protocol

- Phase 1 (Prepare)
  - A node decides to be leader (and propose)
  - Leader chooses  $my_n > n_h$
  - Leader sends  $\langle \text{prepare}, my_n \rangle$  to all nodes

88

88

## Paxos operation: 3P protocol

- Phase 1 (Prepare)
  - A node decides to be leader (and propose)
  - Leader chooses  $my_n > n_h$
  - Leader sends  $\langle \text{prepare}, my_n \rangle$  to all nodes
  - Upon receiving  $\langle \text{prepare}, n \rangle$ 
    - If  $n < n_h$   
reply  $\langle \text{prepare-reject} \rangle$
    - else  $/* n > n_h */$   
 $n_h = n$   
reply  $\langle \text{prepare-ok}, n_a, v_a \rangle$

89

89


## Paxos operation: 3P protocol

- Phase 1 (Prepare)
  - A node decides to be leader (and propose)
  - Leader chooses  $my_n > n_h$
  - Leader sends  $\langle \text{prepare}, my_n \rangle$  to all nodes
  - Upon receiving  $\langle \text{prepare}, n \rangle$ 
    - If  $n < n_h$   
reply  $\langle \text{prepare-reject} \rangle$
    - else  $/* n > n_h */$   
 $n_h = n$   
reply  $\langle \text{prepare-ok}, n_a, v_a \rangle$


This node will not accept  
any proposal lower than  $n$

90

90



91



92

## Paxos operation

- Phase 2 (Accept):
  - If leader gets prepare-ok from a majority
    - V = non-empty value corresponding to the highest  $n_a$  received
    - If V = null, then leader can pick any V
    - Send <accept,  $myn$ , V> to all nodes

93

93

## Paxos operation

- Phase 2 (Accept):
  - If leader gets prepare-ok from a majority
    - V = non-empty value corresponding to the highest  $n_a$  received
    - If V = null, then leader can pick any V
    - Send <accept,  $myn$ , V> to all nodes
  - If leader fails to get majority prepare-ok
    - Delay and restart Paxos

94

94


# Paxos operation

- Phase 2 (Accept):
  - If leader gets prepare-ok from a majority
    - V = non-empty value corresponding to the highest  $n_a$  received
    - If V = null, then leader can pick any V
    - Send <accept,  $myn$ , V> to all nodes
  - If leader fails to get majority prepare-ok
    - Delay and restart Paxos
  - Upon receiving <accept, n, V>
    - If  $n < n_h$ 
      - reply with <accept-reject>
    - else
      - $n_a = n$ ;  $v_a = V$ ;  $n_h = n$
      - reply with <accept-ok>

95

95

## Paxos operation: an example



96

96

## Paxos operation

- Phase 3 (Decide)
  - If leader gets accept-ok from a majority
    - Send <decide,  $v_a$ > to all nodes

97

97

## Paxos operation


- Phase 3 (Decide)
  - If leader gets accept-ok from a majority
    - Send <decide,  $v_a$ > to all nodes
  - If leader fails to get accept-ok from a majority
    - Delay and restart Paxos

98

98



## Paxos operation: an example



99

## Paxos properties

- When is the value V chosen?
  1. When leader receives a majority prepare-ok and proposes V
  2. When a majority of nodes accept V
  3. When the leader receives a majority accept-ok for value V

100

100

## Understanding Paxos

- What if more than one leader is active?
- Suppose two leaders use different proposal number, N0:10, N1:11
- Can both leaders see a majority of prepare-ok?

101

101

## Understanding Paxos

- What if leader fails while sending accept?
- What if a node fails after receiving accept?
  - If it doesn't restart ...
  - If it reboots ...
- What if a node fails after sending prepare-ok?
  - If it reboots ...

102

102