

Web Application Hacking Lesson XSRF part 2

Lesson Objectives

- Review lecture on the XSRF(below)
- Complete lab on Cross Site Request Forgery(below)

Cross Site Request Forgery Lecture:

Cross Site Request Forgery is very dangerous, and also quite common. OWASP describes Cross Site Request Forgery as:

Cross-Site Request Forgery (CSRF) is an attack that tricks the victim into loading a page that contains a malicious request. It is malicious in the sense that it inherits the identity and privileges of the victim to perform an undesired function on the victim's behalf, like change the victim's e-mail address, home address, or password, or purchase something. CSRF attacks generally target functions that cause a state change on the server but can also be used to access sensitive data.

For most sites, browsers will automatically include with such requests any credentials associated with the site, such as the user's session cookie, basic auth credentials, IP address, Windows domain credentials, etc. Therefore, if the user is currently authenticated to the site, the site will have no way to distinguish this from a legitimate user request.

In this way, the attacker can make the victim perform actions that they didn't intend to, such as logout, purchase item, change account information, retrieve account information, or any other function provided by the vulnerable website.

In other words, this is one reason why people tell you not to click on links (or open e-mails) from people you do not trust. Just by clicking a link they can steal your information or change your password without you knowing about it.

Lab for Cross Site Request Forgery Introduction

The Attack:

We are going to use Burp Suite to capture the HTTP request when we try to change a password, and from that we will create a "hidden" link to send to a victim (via e-mail, IM, etc.) that will change their password to whatever we want so we can access their account.

Lab Prep

Open the link to <https://hack.me>

Choose "Start a hackme"

Scroll down and select "DVWA 1.0.7"

BackTrack Linux Offensive Security Exploit-DB Aircrack-ng SomaFM

HACKME BETA

Name	Author	Last revision	Category	Tags
Web App Hack tutorial	hannu-balk	Mar 2, 2013	OWASP	XSS SQLI NEW!!
Joomla 1.5 - Core - Password Change	litsnarf	Jan 30, 2013	CMS	SQLI JOOMLA
Peruggia 1.2	ohpe	Jan 21, 2013	OWASP	XSS SQLI CSRF
Mutillidae 2.3.10	audiopocalypse	Dec 20, 2012	OWASP	XSS SQLI CSRF
DVWA 1.0.7				
FooRadio				
~ Reto SW #1				

[root@bt: ~/De

Accept the agreement
after selecting
“anonymous login”

On the left hand side
choose security and
select low. Click submit

After setting the security
level, click CSRF.

DVWA

DVWA Security

Script Security

Security Level is currently **high**.

You can set the security level to low, medium or high.

The security level changes the vulnerability level of DVWA.

high low medium high

Submit

PHPIDS

PHPIDS v.0.6 (PHP-Intrusion Detection System) is a security tool that can detect and prevent attacks.

You can enable PHPIDS across this site for the duration of your visit.

PHPIDS is currently **disabled**. [\[enable PHPIDS\]](#)

[\[Simulate attack\]](#) - [\[View IDS log\]](#)

Home
Instructions
Setup
Brute Force
Command Execution
CSRF
File Inclusion
SQL Injection
SQL Injection (Blind)
Upload
XSS reflected
XSS stored
DVWA Security
PHP Info

Lab 1– CSRF via GET requests

Launch ZAP 2.0

1. in the directory that holds the zap file, type: `java -jar zap.jar`
2. Open firefox and configure it to use the ZAP 2.0 Proxy http://www.youtube.com/watch?v=Xp_PBH7wjiw&list=PLEBitBW-Hlsv8cEIUntAO8st2UGhmrjUB&index=2
3. Refresh the site so that it ZAP 2.0 lists the site on the left hand panel
4. Go to the CSRF page in DVWA and Change your admin password by entering a password in the New password and Confirm new password fields and clicking the Change button.

track5r3 [Running] - Oracle VM VirtualBox

Applications Places System

3:59 PM michael

Tue Mar 5, 3:59 PM

Damn Vulnerable Web App (DVWA) v1.0.7 :: Vulnerability: Cross Site Request Forgery (CSRF) - Mozilla Firefox

File Edit View History Bookmarks Tools Help

Hackme DVWA 1.0.7 Damn Vulnerable Web App (...) Damn Vulnerable Web App (...)

s8484-101047-loj.sipontum.hack.me/vulnerabilities/csrf/

BackTrack Linux Offensive Security Exploit-DB Aircrack-ng SomaFM

DVWA

Vulnerability: Cross Site Request Forgery (CSRF)

Change your admin password:

Current password:
.....

New password:
....

Confirm new password:
....

Change

More info


http://www.owasp.org/index.php/Cross-Site_Request_Forgery
<http://www.cgisecurity.com/csrf-faq.html>
http://en.wikipedia.org/wiki/Cross-site_request_forgery

Home
Instructions
Setup
Brute Force
Command Execution
CSRF
File Inclusion
SQL Injection
SQL Injection (Blind)
Upload
XSS reflected
XSS stored
DVWA Security
PHP Info
About


hiderefer.com/?http://www.owasp.org/index.php/Cross-Site_Request_Forgery

[root@bt: ~/Desktop/S... Damn Vulnerable Web ... pinata - File Browser Tamper Data - Ongoin...


In ZAP, in the left pane, under sites expand the “vulnerabilities” pages. Highlight the GET request as shown



On the right hand panel, select the entire text that is under the “REQUEST” tab.




Right click the text and copy the text.




In the pinata directory open the CSRFBody.txt file with gedit (right click the file , open with) and paste this text in there.

From a shell, navigate to the pinata directory ,and run the python script pinata.py by typing python pinata.py

```
root@bt: ~
root@bt: ~/Desktop/Scripts/ZAP_2.0.0
root@bt: ~/Desktop/Scripts/pinata# ls
CSRFBody-GETExample.txt  CSRFBody.txt  CSRFBody.txt.  CSRFGet.html  markup.py  markup.pyc  pinata.py  pinataWithEncoding.py
root@bt:~/Desktop/Scripts/pinata# python pinata.py
```



Now, using FireFox , navigate and open the file CSRFGet.html file. Notice that there seems to be a broken image link on the left hand side



Now log out of the app, and test the if the password was changed .
Login with user name of admin and the password of pwnd.

Note that you are now logged in with a password that you changed via new HTML code.

Now imagine this on a bank website, where all you needed to do was get someone to click a link that would deposit X amount of money in Y account, or on Facebook where you could change peoples passwords and get into all the hidden stuff they locked you out of.

Proof of Lab

-
- **Proof of Lab Instructions:**
 1. Do a <PrtScn> of all input, and results
 2. Paste into a word document
 3. Post to Teambox and email to me
-

Questions:

1. What XSRF?
2. What are some ways that an attacker could use XSRF in an attack?
3. Google some ways and list 2 that one could implement as protection vs. XSRF