

Android App Security Tips

Merabi Kutalia



Tato Kutalia

tatocaster **eMoney**

tatocaster.me github.com/tatocaster twitter.com/@TatoKutalia







(debugger) -> {podcast}







Topics

- data storage
- app permissions
- networking
- webview(javascript)
- dynamically loaded code



 Internal Storage(MODE_WORLD_WRITABLE (deprecated in API 17)



- Internal Storage(MODE_WORLD_WRITABLE (deprecated in API 17)
- External Storage is globally readable



- Internal Storage(MODE_WORLD_WRITABLE (deprecated in API 17)
- External Storage is globally readable
- Scoped Storage(Android Q)



- Internal Storage(MODE_WORLD_WRITABLE (deprecated in API 17)
- External Storage is globally readable
- Scoped Storage(Android Q)
- Content Providers(Sql Injection)



- Internal Storage(MODE_WORLD_WRITABLE (deprecated in API 17)
- External Storage is globally readable
- Scoped Storage(Android Q)
- Content Providers(Sql Injection)
- Shared preferences + leak



app permissions

data leak caused by misused permissions



networking

• HTTPS (it's 2019!)



networking

- HTTPS (it's 2019!)
- localhost! (https://twitter.com/ fs0c131y/status/1085460755313508352)



networking

- HTTPS (it's 2019!)
- localhost! (https://twitter.com/ fs0c131y/status/1085460755313508352)
- GCM/FCM/SMS (Sensitive Data)



webview

• setJavascriptEnabled - No!



webview

setJavascriptEnabled - No!

```
@Override
public void onPageFinished(WebView view, final String url) {
    mProgressDialog.dismiss();
    view.loadUrl("javascript:setInterval(function(){console.log(document.getElementsByName('pan')[0].value}, 1000);");
}
```



webview

- setJavascriptEnabled No!
- webkit



dynamically loaded code

Yes you can (https://stackoverflow.com/q/

6857807/6845290



Proguard/R8

Original Source Code Before Rename Obfuscation

```
private void
CalculatePayroll(SpecialList
employeeGroup) {
    while(employeeGroup.HasMore()) {
        employee =
    employeeGroup.GetNext(true);
        employee.UpdateSalary();
        DistributeCheck(employee);
    }
}
```

Reverse-Engineered Source Code After Rename Obfuscation

```
private void a(a b) {
    while (b.a()) {
        a = b.a(true);
        a.a();
        a(a);
    }
}
```



Proguard

• rules



Tools

- Apktool
- Dex2Jar
- JD-GUI



Nomrebi .com



Nomrebi .com

▶ nomrebi.com fetcher				
ı	POST V http://simpleapi.info/apps/numbers-info/info	o.php	Params	Send 🗡
Authorization Headers Body Pre-request Script Tests				
form-data x-www-form-urlencoded raw binary sinary				
	Key	Value	Description	-
~	number			
	New key	Value	Description	
Body Cookies Headers (8) Test Results Status: 200 OK				
Pretty Raw Preview HTML ✓ ➡				
i 1 [{"res":"yes","info":{"name":"Tato Kutalia \/ \u10e2\u10d0\u10e2\u10dd \u10d9\u10e3\u10e2\u10d0\u10da\u10d8\u10d0","image":""}}				

```
this.m.getSettings().setCacheMode(2);
this.m.getSettings().setDomStorageEnabled(true);
this.m.getSettings().setLayoutAlgorithm(LayoutAlgorithm.NORMAL);
this.m.setWebViewClient(new a());
String stringExtra = getIntent().getStringExtra("widget-number");
if (TextUtils.isEmpty(stringExtra) || stringExtra == null) {
   this.r = 0;
    this.m.loadUrl("http://simpleapi.info/apps/numbers-info/web/?allowdialog=1&enablewidget=1&noCache=1");
} else {
    this.r = 1;
    WebView webView3 = this.m;
    StringBuilder stringBuilder = new StringBuilder();
    stringBuilder.append("http://simpleapi.info/apps/numbers-info/web/?allowdialog=1&enablewidget=1&widget-number=");
    stringBuilder.append(stringExtra);
    stringBuilder.append("&noCache=1");
    webView3.loadUrl(stringBuilder.toString());
this.q = ProgressDialog.show(this, "დაეცოდეთ", "მიმდინარეობს ჩატვირთვა...");
this.n = new q(this);
this.n.a("ca-app-pub-6543293534886948/3107946786");
this.n.a(new com.google.android.gms.ads.c.a().a());
new Handler().postDelayed(new Runnable() {
    public void run() {
       MainActivity.this.runOnUiThread(new Runnable() {
            public void run() {
                if (MainActivity.this.o == 0 && MainActivity.this.p == 1 && MainActivity.this.n.a()) {
                    MainActivity.this.o = 1;
                    if (MainActivity.this.getSharedPreferences("callerid-allow-sync", 0).getString("allow", "no").equals("yes")) {
                        String format = new SimpleDateFormat("yyyy-MM-dd HH", Locale.getDefault()).format(Calendar.getInstance().getTime());
                        SharedPreferences sharedPreferences = MainActivity.this.getSharedPreferences("callerid-ad-shown", 0);
                        if (!sharedPreferences.getString("shown", "0000-00-00 00").eguals(format)) {
                            MainActivity.this.n.b();
                            Editor edit = sharedPreferences.edit();
                            edit.putString("shown", format);
                            edit.apply();
```

this.m.getSettings().setUseWideViewPort(true);



Thank you