

P2P File Sharing

Example

- Alice runs P2P client application on her notebook computer
- Intermittently connects to Internet; gets new IP address for each connection
- Asks for "Hey Jude"
- Application displays other peers that have copy of Hey Jude.
- Alice chooses one of the peers, Bob.
- File is copied from Bob's PC to Alice's notebook: HTTP
- While Alice downloads, other users uploading from Alice.
- Alice's peer is both a Web client and a transient Web server.

All peers are servers = highly scalable!

P2P: Centralized Directory


original "Napster" design

1) when peer connects, it informs central server:

- IP address
- content

2) Alice queries for "Hey Jude"

3) Alice requests file from Bob



P2P: problems with centralized directory

- Single point of failure
- Performance bottleneck
- Copyright infringement

file transfer is
decentralized, but
locating content is
highly centralized


Query Flooding: Gnutella

- fully distributed
 - no central server
- public domain protocol
- many Gnutella clients implementing protocol


overlay network: graph

- edge between peer X and Y if there's a TCP connection
- all active peers and edges is overlay net
- Edge is not a physical link
- Given peer will typically be connected with < 10 overlay neighbors

Gnutella: protocol

- ❑ Query message sent over existing TCP connections
 - ❑ peers forward Query message
 - ❑ QueryHit sent over reverse path
- 

Scalability:
limited scope
flooding




Gnutella: Peer Joining

1. Joining peer X must find some other peer in Gnutella network: use list of candidate peers
2. X sequentially attempts to make TCP with peers on list until connection setup with Y
3. X sends Ping message to Y; Y forwards Ping message.
4. All peers receiving Ping message respond with Pong message
5. X receives many Pong messages. It can then setup additional TCP connections

Peer leaving: see homework problem 16 in Textbook!


P2P Case study: Skype

- inherently P2P: pairs of users communicate.
- proprietary application-layer protocol (inferred via reverse engineering)
- hierarchical overlay with SNs
- Index maps usernames to IP addresses; distributed over SNs



Peers as relays

- Problem when both Alice and Bob are behind "NATs".
 - NAT prevents an outside peer from initiating a call to insider peer
- Solution:
 - Using Alice's and Bob's SNs, Relay is chosen
 - Each peer initiates session with relay.
 - Peers can now communicate through NATs via relay



Distributed Hash Table (DHT)

- DHT = distributed P2P database
- Database has (key, value) pairs;
 - key: ss number; value: human name
 - key: content type; value: IP address
- Peers query DB with key
 - DB returns values that match the key
- Peers can also insert (key, value) peers


DHT Identifiers

- Assign integer identifier to each peer in range $[0, 2^n - 1]$.
 - Each identifier can be represented by n bits.
- Require each key to be an integer in **same range**.
- To get integer keys, hash original key.
 - eg, $\text{key} = h(\text{"Led Zeppelin IV"})$
 - This is why they call it a distributed "hash" table

How to assign keys to peers?

- Central issue:
 - Assigning (key, value) pairs to peers.
- Rule: assign key to the peer that has the **closest** ID.
- Convention in lecture: closest is the **immediate successor** of the key.
- Ex: $n=4$; peers: 1,3,4,5,8,10,12,14;
 - key = 13, then successor peer = 14
 - key = 15, then successor peer = 1


Circular DHT (1)



- Each peer *only* aware of immediate successor and predecessor.
- "Overlay network"


Circle DHT (2)

$O(N)$ messages
on avg to resolve
query, when there
are N peers




Define closest
as closest
successor

Circular DHT with Shortcuts



- Each peer keeps track of IP addresses of predecessor, successor, short cuts.
- Reduced from 6 to 2 messages.
- Possible to design shortcuts so $O(\log N)$ neighbors, $O(\log N)$ messages in query

Peer Churn



- To handle peer churn, require each peer to know the IP address of its two successors.
- Each peer periodically pings its two successors to see if they are still alive.

- Peer 5 abruptly leaves
- Peer 4 detects; makes 8 its immediate successor; asks 8 who its immediate successor is; makes 8's immediate successor its second successor.
- What if peer 13 wants to join?