Beyond Euclidean Space: Geometric Alignment for Structure-Aware Dense Retrieval

Abstract

Retrieving structured documents requires understanding both their content and how that content is organized. This study explores whether hyperbolic representations can help SANTA learn these relationships and improve dense retrieval. We focus on its Structured Data Alignment (SDA) component, which aligns structured data with natural-language text, and consider two hyperbolic representations: the Poincaré ball and the Lorentz hyperboloid. We plan to evaluate these variants on CodeSearchNet and Adv for code retrieval, alongside an S1000D XML retrieval dataset to be constructed for this study. Comparisons with the original SANTA model will use consistent encoder and training settings. The evaluation will examine retrieval effectiveness across the three datasets, hierarchical relationship preservation in S1000D XML, and computational cost. Our aim is to understand when geometric alignment helps retrieve structured technical documents and whether better retrieval is accompanied by better preservation of their structure.

Keywords— Dense retrieval; Hyperbolic representation learning; Geometric alignment; S1000D XML

1 Introduction

1.1 Research Background and Motivation

Structure-aware pretraining can improve dense retrieval over structured data by aligning structured content with natural-language text and learning structural semantics, as demonstrated by SANTA in code and product search [1]. From a geometric perspective, Poincaré embeddings provide a means of jointly representing hierarchy and similarity in hyperbolic space, offering a compact representation of data with latent hierarchical structure [2].

1.2 Research Gap and Objectives

Hyperbolic geometry provides a framework for representing hierarchical relationships through models such as the Poincaré ball and the Lorentz hyperboloid [3]. An important development in machine learning was the work of Nickel and Kiela [2], who demonstrated that Poincaré embeddings could capture hierarchy and similarity in low-dimensional representations, with favorable results on taxonomy reconstruction and link prediction. These findings suggest that representation geometry can support the learning of hierarchical structure. More recently, HypRAG applied Lorentz-based representations to dense retrieval for retrieval-augmented generation, using geometry-aware pooling to preserve hierarchical information when aggregating token representations into document embeddings [4]. Its evaluations on MTEB and RAGBench reported improvements over the evaluated Euclidean baselines in embedding quality and in context and answer relevance, providing evidence for the practical value of hyperbolic representations in retrieval settings. For structure-aware dense retrieval, this motivates examining how hyperbolic geometry can complement the alignment between structured data and natural-language descriptions. Specifically, this study aims to incorporate hyperbolic representations into the Structured Data Alignment (SDA) component of SANTA [1] and evaluate whether this geometric choice improves retrieval performance compared with its original formulation.

1.3 Contributions

This study aims to make two contributions:

1. We aim to incorporate hyperbolic representations into SANTA's SDA component and evaluate their effect on structure-aware dense retrieval.
2. We aim to construct an S1000D XML retrieval dataset and use it to evaluate the modified SANTA model against its original formulation.

2 Related Work

2.1 Dense Retrieval

Dense retrieval represents queries and documents as dense vectors and ranks documents through learned similarity functions. DPR [5] established a widely used dual-encoder formulation, learning query and passage representations from supervised question–passage pairs. Subsequent research improved both training and representation granularity: ANCE [6] mined challenging negatives from a dynamically updated corpus index, while ColBERT [7] retained token-level representations and computed fine-grained matching through late interaction. Retrieval-oriented pretraining also became an important direction. For example, coCondenser [8] introduced a corpus-level contrastive objective to prepare the passage embedding space before supervised training. Together, these approaches show that retrieval performance depends on the representation architecture, negative sampling, and pretraining objectives, providing essential controls when evaluating changes to representation geometry.

More recent research has expanded toward zero-shot retrieval and general-purpose embeddings built from large language models (LLMs). HyDE [9] generated hypothetical documents from queries and encoded them to retrieve real documents without task-specific relevance labels. Wang et al. [10] used LLM-generated synthetic data to train text embeddings through contrastive learning, evaluating generalization on BEIR and MTEB. The Qwen3 Embedding technical report [11] further combined foundation models, synthetic data, and multi-stage training for multilingual text embedding and retrieval. These developments broaden the available retrieval backbones and training resources, while motivating evaluation beyond a single domain. For structured content, SANTA [1] introduced Structured Data Alignment and Masked Entity Prediction, demonstrating their effectiveness in code and product search. Building on this direction, the present study examines whether hyperbolic alignment within SDA improves S1000D XML retrieval and preserves relevant hierarchical relationships, with encoder and training conditions controlled to distinguish geometric effects from other sources of improvement.

2.2 Hyperbolic Representation Learning

The use of hyperbolic geometry to represent relational structure predates modern neural embedding methods. Krioukov et al. [12] connected negative curvature with degree heterogeneity and clustering in complex networks, providing a basis for relating geometry to structural organization. In 2017, Nickel and Kiela [2] introduced Poincaré embeddings for learning hierarchy and similarity jointly. On the WordNet noun hierarchy, they compared Poincaré, Euclidean, and translational embeddings across dimensions using reconstruction and held-out link prediction, with mean rank and mean average precision showing strong low-dimensional performance. Their 2018 study [3] investigated Lorentz-based optimization on WordNet, EuroVoc, ACM, and MeSH, evaluating relation ranking and correlations between embedding norms and taxonomic depth. Its improvements concerned the learned embeddings and optimization procedure; the Poincaré and Lorentz models describe the same hyperbolic geometry at matching dimension and curvature. Also in 2018, Ganea et al. [13] extended hyperbolic learning to classifiers and neural layers. Comparisons on binary SNLI entailment and synthetic noisy-prefix recognition showed clearer advantages for more tree-like prefix relationships, while SNLI results were broadly comparable to Euclidean counterparts.

Subsequent applications examined how these geometric properties interact with task objectives and model components. Hyper-Know [14] combined Poincaré representations, knowledge-graph attention, and adaptive regularization for recommendation. On Amazon-book, Last-FM, and Yelp2018, held-out interaction ranking and component ablations assessed Recall@K and NDCG@K, reporting improvements over the evaluated baselines.

These results support the combined approach, rather than attributing all gains to geometry alone. Weber et al. [15] trained segmentation models on Cityscapes and tested them on five additional driving datasets, comparing hierarchical, flat Euclidean, and hyperbolic classifiers. Flat Euclidean models remained strong accuracy baselines, whereas hyperbolic representations showed particular benefits for parent-level calibration under domain shift. More directly related to retrieval, HypRAG [4] evaluated Lorentz-based text encoders on MTEB and RAGBench, comparing embedding quality and generated-answer grounding and relevance. Pooling ablations and analyses of radial separation between general and specific concepts examined how document aggregation retained hierarchical information. Together, these studies motivate evaluating the modified SANTA model on S1000D XML retrieval through controlled comparisons of geometry and alignment components, alongside direct checks of the structural relationships retained by its representations. Retrieval gains alone would not establish successful structural learning.

3 Preliminary

3.1 SANTA and Structured Data Alignment

SANTA learns representations of natural-language text and structured data in a shared embedding space [1]. Its Structured Data Alignment (SDA) objective uses paired structured and unstructured content as positive examples and contrastively distinguishes matched pairs from mismatched examples. Masked Entity Prediction provides complementary supervision by reconstructing masked entities in structured data. These existing objectives provide the background for examining the geometry of SDA; the proposed changes to its representations and alignment objective are described in Section 4.

3.2 Hyperbolic Geometry for Representation Learning

Hyperbolic space has constant negative sectional curvature and supports compact representations of hierarchical relationships [2, 3]. Let $c > 0$ denote the magnitude of curvature, so that the curvature is $-c$, and let d denote the intrinsic dimension. The Poincaré ball and Lorentz hyperboloid are two coordinate models of this same geometry. Their definitions below use a common curvature convention to support subsequent comparisons.

3.2.1 Poincaré Ball Model

The Poincaré ball is defined by

$$\mathbb{B}_c^d = \{\mathbf{x} \in \mathbb{R}^d : c\|\mathbf{x}\|_2^2 < 1\}, \qquad g_{\mathbf{x}} = (\lambda_{\mathbf{x}}^c)^2 I_d, \qquad \lambda_{\mathbf{x}}^c = \frac{2}{1 - c\|\mathbf{x}\|_2^2}. \tag{1}$$

Its geodesic distance is

$$d_{\mathbb{B}}^c(\mathbf{x}, \mathbf{y}) = \frac{1}{\sqrt{c}} \operatorname{arcosh}\left(1 + \frac{2c\|\mathbf{x} - \mathbf{y}\|_2^2}{(1 - c\|\mathbf{x}\|_2^2)(1 - c\|\mathbf{y}\|_2^2)}\right). \tag{2}$$

A tangent vector $\mathbf{v} \in T_{\mathbf{0}}\mathbb{B}_c^d \cong \mathbb{R}^d$ can be mapped into the ball using the exponential map [13]:

$$\exp_{\mathbf{0}}^{\mathbb{B},c}(\mathbf{v}) = \tanh(\sqrt{c}\|\mathbf{v}\|_2)\frac{\mathbf{v}}{\sqrt{c}\|\mathbf{v}\|_2}. \tag{3}$$

At $\mathbf{v} = \mathbf{0}$, the map is defined by continuity as $\mathbf{0}$. The conformal factor makes distances grow near the boundary, allowing radial position to encode hierarchical depth when supported by the learning objective.

3.2.2 Lorentz Hyperboloid Model

For $\mathbf{x} = (x_0, \mathbf{x}_s)$ and $\mathbf{y} = (y_0, \mathbf{y}_s)$ in $\mathbb{R}^{d+1}$, define the Lorentz inner product and upper hyperboloid by

$$\langle \mathbf{x}, \mathbf{y} \rangle_L = -x_0 y_0 + \mathbf{x}_s^\top \mathbf{y}_s, \qquad \mathbb{H}_c^d = \{\mathbf{x} : \langle \mathbf{x}, \mathbf{x} \rangle_L = -1/c,\ x_0 > 0\}. \tag{4}$$

The induced metric on its tangent spaces is positive definite, and the geodesic distance is [3]

$$d_{\mathbb{H}}^c(\mathbf{x}, \mathbf{y}) = \frac{1}{\sqrt{c}} \operatorname{arcosh}(-c\langle \mathbf{x}, \mathbf{y} \rangle_L). \tag{5}$$

At the origin $\mathbf{o} = (1/\sqrt{c}, \mathbf{0})$, a tangent vector has the form $\mathbf{v} = (0, \mathbf{h})$. Its exponential map is

$$\exp_{\mathbf{o}}^{\mathbb{H},c}(0, \mathbf{h}) = \left(\frac{\cosh(\sqrt{c}\|\mathbf{h}\|_2)}{\sqrt{c}}, \frac{\sinh(\sqrt{c}\|\mathbf{h}\|_2)}{\sqrt{c}\|\mathbf{h}\|_2}\mathbf{h}\right), \tag{6}$$

with value $\mathbf{o}$ at $\mathbf{h} = \mathbf{0}$. This construction produces a valid manifold point from a Euclidean encoder representation interpreted as a tangent vector.

3.2.3 Correspondence Between the Models

The distance-preserving coordinate transformation from the ball to the hyperboloid and its inverse are

$$\Phi_c(\mathbf{z}) = \left(\frac{1 + c\|\mathbf{z}\|_2^2}{\sqrt{c}(1 - c\|\mathbf{z}\|_2^2)}, \frac{2\mathbf{z}}{1 - c\|\mathbf{z}\|_2^2} \right), \qquad \Phi_c^{-1}(\mathbf{x}) = \frac{\mathbf{x}_s}{\sqrt{c}x_0 + 1}. \tag{7}$$

Consequently, $d^c_{\mathbb{H}}(\Phi_c(\mathbf{z}), \Phi_c(\mathbf{w})) = d^c_{\mathbb{B}}(\mathbf{z}, \mathbf{w})$. The origin metrics have different coordinate scales: matched tangent vectors satisfy $\mathbf{h} = 2\mathbf{v}$ in Eqs. 3 and 6. Comparisons should therefore control intrinsic dimension, curvature, and representation scale; differences between implementations may reflect optimization or numerical behavior rather than different underlying geometries. These definitions supply the distances and mappings needed to formulate hyperbolic SDA, while its scoring function and training objective belong to the proposed method.

4 Proposed Method

4.1 Architecture




Figure 1: Conceptual architecture of geometric alignment for structure-aware dense retrieval. The diagram summarizes candidate alignment geometries and evaluation settings; the mixed-geometry branch and hierarchy-aware objective represent optional extensions.

4.2 Structure-Aware Representations

4.3 Geometric Alignment

4.4 Learning Objectives and Optimization

4.5 Retrieval and Computational Complexity

5 Experimental Setup

5.1 Research Questions

5.2 Datasets and Data Preparation

5.3 Baseline Methods

5.4 Evaluation Metrics and Statistical Analysis

5.5 Implementation Details

6 Results and Analysis

6.1 Retrieval Effectiveness

6.2 Structural Alignment Analysis

6.3 Ablation Studies

6.4 Sensitivity and Robustness

6.5 Efficiency Analysis

6.6 Qualitative and Error Analysis

7 Discussion

7.1 Interpretation of Findings

7.2 Implications for Structure-Aware Retrieval

7.3 Limitations and Threats to Validity

8 Conclusion

References

[1] X. Li, Z. Liu, C. Xiong, S. Yu, Y. Gu, Z. Liu, and G. Yu, "Structure-aware language model pretraining improves dense retrieval on structured data," in *Findings of the Association for Computational Linguistics: ACL 2023*, 2023, pp. 11 560–11 574.

[2] M. Nickel and D. Kiela, "Poincaré embeddings for learning hierarchical representations," in *Advances in Neural Information Processing Systems*, vol. 30, 2017, pp. 6338–6347.

[3] ——, "Learning continuous hierarchies in the Lorentz model of hyperbolic geometry," in *Proceedings of the 35th International Conference on Machine Learning*, ser. Proceedings of Machine Learning Research, vol. 80. PMLR, 2018, pp. 3779–3788.

[4] H. Madhu, N. Bui, A. Maatouk, L. Tassiulas, S. Krishnaswamy, M. Yang, S. Ganguly, K. Srinivasan, and Z. Ying, "HypRAG: Hyperbolic dense retrieval for retrieval augmented generation," in *Proceedings of the 43rd International Conference on Machine Learning*, ser. Proceedings of Machine Learning Research, vol. 306. PMLR, 2026, pp. 85 524–85 547.

[5] V. Karpukhin, B. Oğuz, S. Min, P. Lewis, L. Wu, S. Edunov, D. Chen, and W.-t. Yih, "Dense passage retrieval for open-domain question answering," in *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, 2020, pp. 6769–6781.

[6] L. Xiong, C. Xiong, Y. Li, K.-F. Tang, J. Liu, P. Bennett, J. Ahmed, and A. Overwijk, "Approximate nearest neighbor negative contrastive learning for dense text retrieval," in *International Conference on Learning Representations*, 2021.

[7] O. Khattab and M. Zaharia, "ColBERT: Efficient and effective passage search via contextualized late interaction over BERT," in *Proceedings of the 43rd International ACM SIGIR Conference on Research and Development in Information Retrieval*, 2020, pp. 39–48.

[8] L. Gao and J. Callan, "Unsupervised corpus aware language model pre-training for dense passage retrieval," in *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, 2022, pp. 2843–2853.

[9] L. Gao, X. Ma, J. Lin, and J. Callan, "Precise zero-shot dense retrieval without relevance labels," in *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, 2023, pp. 1762–1777.

[10] L. Wang, N. Yang, X. Huang, L. Yang, R. Majumder, and F. Wei, "Improving text embeddings with large language models," in *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, 2024, pp. 11 897–11 916.

[11] Y. Zhang, M. Li, D. Long, X. Zhang, H. Lin, B. Yang, P. Xie, A. Yang, D. Liu, J. Lin, F. Huang, and J. Zhou, "Qwen3 Embedding: Advancing text embedding and reranking through foundation models," *arXiv preprint arXiv:2506.05176*, 2025.

[12] D. Krioukov, F. Papadopoulos, M. Kitsak, A. Vahdat, and M. Boguñá, "Hyperbolic geometry of complex networks," *Physical Review E*, vol. 82, no. 3, p. 036106, 2010.

[13] O.-E. Ganea, G. Bécigneul, and T. Hofmann, "Hyperbolic neural networks," in *Advances in Neural Information Processing Systems*, vol. 31, 2018.

[14] C. Ma, L. Ma, Y. Zhang, H. Wu, X. Liu, and M. Coates, "Knowledge-enhanced Top-K recommendation in Poincaré ball," in *Proceedings of the AAAI Conference on Artificial Intelligence*, vol. 35, no. 5, 2021, pp. 4285–4293.

[15] S. Weber, B. Zöngür, N. Araslanov, and D. Cremers, "Flattening the parent bias: Hierarchical semantic segmentation in the Poincaré ball," in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024, pp. 28 223–28 232.

A Supplementary Method and Experimental Details