

# CS 301 Assignment 3

Student ID: 200482797

Owen Monus

March 16th, 2024

1. (a) Represent the following decimal numbers in twos complement using 16 bits: +512, -29.  
 $512 \rightarrow 0000001000000000$   
 $-29 \rightarrow 1111111111100011$
- (b) Represent the following twos complement values in decimal:  
 $1101011 \rightarrow -21$   
 $0101101 \rightarrow 45$
2. (a) The  $r$ 's complement of an  $n$ -digit number  $N$  in base  $r$  is defined as  $r^n - N$  for  $N \neq 0$  and 0 for  $N = 0$ . Find the tens complement of the decimal number 13,250.

13,250's 10's complement is 86,750.

- (b) Calculate  $72,530 - 13,250$  using tens complement arithmetic. Assume that the rules are similar to those for twos complement arithmetic.

Take 10s comp of 13250, add that to 72530.

$$72530 + 86750 = 159,280$$

3. Use the Booth's algorithm to multiply 23 (multiplicand) by 29 (multiplier), where each number is represented using 6 bits.

```
// Booth's Algorithm with M = 23, N = 29
A = 0
B = 010111 // 23
C = 011101 // 29
C_-1 = 0
n = 6

while(n > 0) {
    if (LSB(C) == 0 && C_-1 == 1)
        A = A + B
    if (LSB(C) == 1 && C_-1 == 0)
        A = A - B

    n = n - 1
    A||C||C_-1 = (A||C||C_-1) >>> 1
}
```

Table 1: Booth's Algorithm:  $23 \times 29$

Operation	n	A	C	C <sub>-1</sub>	B
initial value	6 <sub>10</sub>	000000	011101	0	010111
$A = A - B$	6 <sub>10</sub>	101001	011101	0	010111
right shift	6 <sub>10</sub>	110100	101110	1	010111
$A = A + B$	5 <sub>10</sub>	001011	101110	1	010111
right shift	5 <sub>10</sub>	000101	110111	0	010111
$A = A - B$	4 <sub>10</sub>	101110	110111	0	010111
right shift	4 <sub>10</sub>	110111	011011	1	010111
right shift	3 <sub>10</sub>	111011	101101	1	010111
right shift	2 <sub>10</sub>	111101	110110	1	010111
$A = A + B$	1 <sub>10</sub>	010100	110110	1	010111
right shift	1 <sub>10</sub>	001010	011011	0	010111

Result = 0b001010011011 = 667<sub>10</sub>

```

4. // One instruction machine
LOAD E
MUL F
STORE T
LOAD D
SUB T
STORE X
LOAD B
MUL C
ADD A
DIV X
STORE X

// Two instruction machine
MOVE X,F
MUL X,E
MOVE T,D
SUB T,X

MOVE X,C
MUL X,B
ADD X,A
DIV X,T

// Three instruction machine
MUL T,E,F
SUB T,D,T
MUL X,B,C
ADD X,X,A
DIV X,X,T

```

5. Both an arithmetic left shift and a logical left shift correspond to a multiplication by 2 when there is no overflow. If overflow occurs, arithmetic and logical left shift operations produce different results, but the arithmetic left shift retains the sign of the number.

Table 2: Shifts for Decimal Numbers

$d$	2's	LLS	ALS	Condition
-16	10000	00000	10000	overflow
-15	10001	00001	10010	overflow
-14	10010	00100	10100	overflow
-13	10011	00011	10110	overflow
-12	10100	01000	11000	overflow
-11	10101	01010	11010	overflow
-10	10110	01100	11100	overflow
-9	10111	01110	11110	overflow
-8	11000	10000	10000	no overflow
-7	11001	10010	10010	no overflow
-6	11010	10100	10100	no overflow
-5	11011	10110	10110	no overflow
-4	11100	11000	11000	no overflow
-3	11101	11010	11010	no overflow
-2	11110	11100	11100	no overflow
-1	11111	11110	11110	no overflow
0	00000	00000	00000	no overflow
1	00001	00010	00010	no overflow
2	00010	00100	00100	no overflow
3	00011	00110	00110	no overflow
4	00100	01000	01000	no overflow
5	00101	01010	01010	no overflow
6	00110	01100	01100	no overflow
7	00111	01110	01110	no overflow
8	01000	10000	00000	overflow
9	01001	10010	00010	overflow
10	01010	10100	00100	overflow
11	01011	10110	00110	overflow
12	01100	11000	01000	overflow
13	01101	11010	01010	overflow
14	01110	11100	01100	overflow
15	01111	11110	01110	overflow

As shown in the table, when an operation results in overflow, the Arithmetic Left Shift and Logical Left Shift result in different results. The Arithmetic Left Shift retains the sign of the number, whereas the Logical Left Shift does not.