Abstract

Paxos [6] is a widely used and notoriously hard to understand[12] method for solving one type of distributed consensus problem. This note provides a quick explanation of Paxos, a novel proof of correctness that is intended to provide insight into why the algorithm is as simple as the author has claimed, an explanation of why it does and why it doesn't work, and has a brief discussion of alternatives.

Understanding Paxos and other distributed consensus algorithms

A Preprint

Victor Yodaiken *

February 15, 2022

1 Paxos

There was an old lady who swallowed a bird; How absurd to swallow a bird! — Bonne/Mills.

Despite being not "live", the Paxos algorithm [6, 7, 8, 9] is a brilliantly intricate distributed consensus algorithm and incorporates an interesting insight about the importance of correctly posing the problem. Additionally, the algorithm, or related algorithms, are apparently widely used in practice according to papers like *e.g.* [3, 1, 13] and indicators such as the 312 hits turned up when searching for "Paxos" and "consensus" in the USPTO database of issued patents. The basic algorithm is notoriously hard to understand[12], but is shown here to be really as simple as the author has claimed.

1.1 Consensus

Distributed consensus involves getting a collection of agents (devices or processes or equivalent) that communicate only by exchanging discrete data packets (messages) to agree on a value. Consensus can involve true unanimous consensus or a majority or some other "quorum" depending on the specific requirements. For example, a collection of database "replicas" might need to agree on when a transaction or series of transactions can be committed so that a distributed database stays consistent and fault tolerant. If networks provide reliable atomic broadcast the problem is easy (see, for example the Auragen fault tolerant message systems [2]), but most work in this area assumes packets can be delayed or lost or reordered but that no malicious, spurious, or corrupted packets are delivered.

1.2 The naive method

If there is a single "proposer" agent (to propose a value), distributed consensus can be simple. The proposer sends a proposal message to all the "acceptors" and keeps resending until it has received acknowledgments from a quorum. In most cases, there are not very many acceptors (often just 2 or 3), agents rarely fail, and message delivery is fairly reliable and fast, so this process can be efficient. If messages get through with high probability after a number of resends, the algorithm is highly probable to complete (to be "live"). The proposer can simply provide a new value at each round, possibly with a sequence number, to produce a sequence of agreed on values. There is a smart optimization method from Chang/Maxemchuck[4] that is not widely used for some reason but can radically reduce message counts.

^{*©}Victor Yodaiken, 2018-2021.

If the proposer fails a new unique proposer must be elected, but the election must ensure that the agents can come to consensus about which proposer has won. We have to solve the distributed consensus problem a second time to make the first solution work in the presence of failures². We'll return to this topic in section 3.

2 Paxos 1 and 2: fly, spider, bird, otter, kangaroo, jellyfish, etcetera.

The paper "Paxos made simple" [6] starts by providing a method with multiple competing proposers to build in resilience against proposer failures³. The competition is based on the clever observation that we don't really care which proposer wins or whether multiple proposers win, we only care that no more than a single consensus value wins. Proposers attempt two stages: in stage one they send acceptors a "pre-proposal" that only contains a proposer sequence number. In stage two proposers send a full proposal pair consisting of the same proposer sequence number and a proposed value. No two proposers ever share a sequence number and a proposer cannot use the same sequence number with two different values. A proposer starts stage 2 only when or if it has received acks for its pre-proposal from more than half of the acceptors and it wins only if it gets acks for its full proposal from more than half the acceptors. An acceptor's acknowledgments are in strict order, each is either before or after any other acknowledgment by the same acceptor and an acceptor can only acknowledge proposals and pre-proposals if it has not previously acknowledged a greater sequence number either in a pre-proposal or a full proposal 4. Acceptors must attach the highest numbered full proposal the acceptor has already acknowledged to any pre-proposal acknowledgment. When it goes to the second stage, the proposer must inherit (adopt) the highest numbered value from any proposals (if any) attached to the acks it was sent by acceptors. If no full proposal is sent back, the proposer can chose an arbitrary value. All of this guarantees that the lowest numbered winning proposal determines the value for any other winning proposals - in fact, it determines the value for any higher numbered proposals that are acknowledged even one time. We can prove this by

Suppose (n_1, v_1) is the lowest numbered winning proposal and list in order of sequence numbers all the greater or equal numbered proposals that have been acknowledged at least once $(n_1, v_1), \dots (n_k, v_k)$. This list includes but is not limited to all proposals that have won - we just need one acknowledgment to put the proposal on the list after the first pair. It doesn't even matter whether the proposer received the acknowledgment. If j = 1, $v_j = v_1$ by construction. Suppose j > 1 and for all $1 \le i < j$, the list element (n_i, v_i) has $v_i = v_1$ (induction hypothesis) and then consider the next list element (n_j, v_j) . For (n_j, v_j) to be on the list it must have been acknowledged by at least one acceptor and the preproposal n_j had to have been acknowledged by more than 1/2 of the acceptors, at least one acceptor a has to have acknowledged both n_j and (n_1, v_1) . Since $n_j > n_1$, it must be that a acknowledged (v_1, v_1) before it acknowledged n_j so a sent back either (n_1, v_1) or a higher numbered proposal to the proposer of n_j . It follows that the proposer of n_j had to inherit some proposal (n_i, v_i) with $n_i \ge n_1$. It must be that (n_i, v_i) is on the list since it had to have been acknowledged to be sent back with the acknowledgment of n_j . If acceptor a' sent (n_i, v_i) back to the proposer of n_j , a' must have acknowledged (n_i, v_i) before it acknowledged n_j so $n_i < n_j$. But if (n_i, v_i) is on the list with $n_1 \le n_i < n_j$ then $v_i = v_1$ by the induction hypothesis. QED

Although Paxos is safe it is not live: the proposers can block each other and prevent any proposal value at all from winning. The proof of safety above gives clues about how easy it is for one proposal to block another. Suppose proposer 1 with sequence number 1 succeeds in stage one and either fails or stalls indefinitely so that proposer 1 cannot get any acks for its proposal. The proposed solution in "Paxos made simple" is to allow proposers that cannot advance to increase their sequence number (the new number still needs to be unique), abandon the old proposal value, if any, and start over again. Basically, this doesn't change much - it is as if new proposers entered the competition and the one with the abandoned number stalled forever. Unfortunately, it turns out that it is still possible for proposers to keep blocking and restarting so that the algorithm spins forever, never reaching consensus:

It's easy to construct a scenario in which two proposers each keep issuing a sequence of proposals with increasing numbers, none of which are ever chosen. Proposer p completes phase 1 for a proposal number n 1. Another proposer q then completes phase 1 for a proposal number n 2 > n 1. Proposer p's phase 2 accept requests for a proposal numbered n 1 are ignored because the acceptors have all promised not to accept any new proposal numbered less than n 2. So, proposer p then

²Effectively, we have to swallow the bird to catch the spider.

³I cannot decipher the original Paxos paper[7]

⁴This is a critical point and it is ambiguous in the text of "Paxos made simple". At one point the requirement as written is implied, at another point it is implied that proposers can only send proposals to acceptors that have acknowledged the pre-proposal – which would have the same effect.

begins and completes phase 1 for a new proposal number n > 3 > n 2, causing the second phase 2 accept requests of proposer q to be ignored. And so on. [6]

Or see the simulation in [15].

The explication in [6] then shifts to a very different method, confusingly also called "Paxos" where there is exactly one proposer – a "distinguished" proposer.

In normal operation, a single server is elected to be the leader, which acts as the distinguished proposer (the only one that tries to issue proposals) in all instances of the consensus algorithm

How this proposer is to be chosen is not completely specified. The distinguished proposer can carry out the two stage process and is assured to win since there will be no other competitor (or it could simply use the procedure of section 1.2). Just to make this point as clearly as possible, the two stage competition doesn't accomplish any purpose if there is a single proposer, so reverting to a single proposer algorithm and letting some other algorithm solve the distributed consensus problem for choosing that single proposer means that the second version of Paxos is just an inefficient version of the simple algorithm in section 1.2.

3 Time

In the passage where multi-proposer version of Paxos is abandoned for the single proposer version, "Paxos made simple" has the following note:

The famous result of Fischer, Lynch, and Patterson [5] implies that a reliable algorithm for electing a proposer must use either randomness or real time— for example, by using timeouts.

This is striking because the original premise of the paper is that there are no timeouts: "Agents operate at arbitrary speed". Completely "asynchronous" models of networks were popular in academic computer science in the era in which "Paxos made simple" was written for reasons that are not clear, at least to me. The "theorem" of [5] is the tautological result that if it is impossible to distinguish between a failed agent and a slow to respond agent (e.g. if "Agents operate at arbitrary speed") then it is impossible to distinguish between a failed agent and a slow to respond agent, which the authors sensibly conclude means that no totally clock free distributed consensus algorithm can be made to work in the presence of dropped messages and agents that can fail. Consideration of this observation leads to the conclusion that the first version of Paxos could be made to be live in the presence of agent failures if proposers had to wait for a timeout before restarting with a new number. If a stalled proposer had to wait t time units before restarting with a new number and t was enough time so that it was highly probable a competing proposer could complete the protocol, then the algorithm would be live (probably).

The simple consensus algorithm of 1.2 could be improved to allow recovery from failure of the single proposer using clocks as proposed in numerous pre-Paxos systems such as those of Liskov[10, 11] (and clock technology has advanced a lot in 30 years [14]). The proposer could be required to send a "heartbeat" message every so often to remind the acceptors that it was still alive. The heartbeat could be combined with e.g. messages proposing new consensus values for efficiency. Acceptors could timeout if they had not heard from a proposer for too long and then wait some randomized time before proposing themselves as the new proposer. Acceptors could accept the new proposer with a time limited lease which extends when the candidate confirms it won by sending a heart beat. See [4] for a well worked out system including state recovery.

In practice, distributed algorithms, including those named Paxos (see [3, 1] for example) rely on timeouts and leases and other time related mechanisms. Raft [12] relies on timeouts as well.

References

- [1] William J Bolosky et al. "Paxos replicated state machines as the basis of a high-performance data store". In: *Symposium on Networked Systems Design and Implementation (NSDI)*. 2011, pp. 141–154.
- [2] Anita Borg, Jim Baumbach, and Sam Glazer. "A Message System Supporting Fault Tolerance". In: *Proceedings of the Ninth ACM Symposium on Operating System Principles, SOSP 1983, Bretton Woods, New Hampshire, USA, October 10-13, 1983.* Ed. by Jerome H. Saltzer, Roy Levin, and David D. Redell. ACM, 1983, pp. 90–99. doi: 10.1145/800217.806617. url: https://doi.org/10.1145/800217.806617.

- [3] Tushar D. Chandra, Robert Griesemer, and Joshua Redstone. "Paxos Made Live: An Engineering Perspective". In: *Proceedings of the Twenty-sixth Annual ACM Symposium on Principles of Distributed Computing*. PODC '07. Portland, Oregon, USA: ACM, 2007, pp. 398–407. isbn: 978-1-59593-616-5. doi: 10.1145/1281100.1281103. url: http://doi.acm.org/10.1145/1281100.1281103.
- [4] Jo-Mei Chang and N. F. Maxemchuk. "Reliable Broadcast Protocols". In: *ACM Trans. Comput. Syst.* 2.3 (Aug. 1984), pp. 251-273. issn: 0734-2071. doi: 10.1145/989.357400. url: http://doi.acm.org/10.1145/989.357400.
- [5] Michael J. Fischer, Nancy A. Lynch, and Michael S. Paterson. "Impossibility of Distributed Consensus with One Faulty Process". In: *J. ACM* 32.2 (Apr. 1985), pp. 374–382. issn: 0004-5411. doi: 10.1145/3149.214121. url: https://doi.org/10.1145/3149.214121.
- [6] Leslie Lamport. "Paxos Made Simple". In: ACM SIGACT News (Distributed Computing Column) 32, 4 (Whole Number 121, December 2001) (Dec. 2001), pp. 51-58. url: https://www.microsoft.com/en-us/research/publication/paxos-made-simple/.
- [7] Leslie Lamport. "The Part-Time Parliament." In: ACM Trans. Comput. Syst. 16.2 (1998), pp. 133-169. url: https://www.microsoft.com/en-us/research/publication/part-time-parliament/.
- [8] Leslie B. Lamport. Fault-tolerant system and method for implementing a distributed state machine. United States Patent. 1992.
- [9] Michael T. Massa Leslie B. Lamport. Fault-tolerant system and method for implementing a distributed state machine. United States Patent. 2007.
- [10] Barbara Liskov. "Practical Uses of Synchronized Clocks in Distributed Systems". In: *Proc. of the Tenth Annual Symposium on Principles of Distributed Computing*. Aug. 1991. url: http://delivery.acm.org/10.1145/120000/112601/p1-liskov.pdf.
- [11] Brian M. Oki and Barbara H. Liskov. "Viewstamped Replication: A New Primary Copy Method to Support Highly-Available Distributed Systems". In: *Proceedings of the Seventh Annual ACM Symposium on Principles of Distributed Computing*. PODC '88. Toronto, Ontario, Canada: Association for Computing Machinery, 1988, pp. 8–17. isbn: 0897912772. doi: 10.1145/62546.62549. url: https://doi.org/10.1145/62546.62549.
- [12] Diego Ongaro and John Ousterhout. "In Search of an Understandable Consensus Algorithm". In: *Proceedings of the 2014 USENIX Conference on USENIX Annual Technical Conference*. USENIX ATC'14. Philadelphia, PA: USENIX Association, 2014, pp. 305–320. isbn: 978-1-931971-10-2. url: http://dl.acm.org/citation.cfm?id=2643634.2643666.
- [13] Roberto De Prisco, Butler Lampson, "Revisiting and Nancy Lynch. althe paxos gorithm". In: 243.1 (2000),35-91. **Theoretical** Computer Science pp. issn: https://doi.org/10.1016/S0304-3975(00)00042-6. 0304-3975. doi: url: http://www.sciencedirect.com/science/article/pii/S0304397500000426.
- [14] Victor Yodaiken. "Fault Recovery for Time Sync Networks". In: *Proceeding of the 27th Annual Workshop on Synchronization and Timing Systems*. ATIS, June 2018.
- [15] Victor Yodaiken. Paxos Simulation. 2018. url: https://github.com/yaupon0/cc-utils/blob/main/paxos.lua.