

# Rubric Questions:

## 1. Problems Encountered in the Map

---

### Inconsistent abbreviations

Before I imported the data to MongoDB I took a quick look at the street names with the following code:

```
import re
import xml.etree.cElementTree as ET
import pprint
from collections import defaultdict
import codecs
import json
from pymongo import MongoClient

#filename = "sample.osm"
filename = "san-diego-tijuana_mexico.osm"

street_type_re = re.compile(r'\b\S+\.?$', re.IGNORECASE)
expected = ["Street", "Avenue", "Boulevard", "Drive", "Court", "Place", "Square", "Lane", "Road",
            "Trail", "Parkway", "Commons"]

def is_street_name(elem):
    return (elem.attrib['k'] == "addr:street")

def audit_street_type(street_types, street_name):
    m = street_type_re.search(street_name)
    if m:
        street_type = m.group()
        if street_type not in expected:
            street_types[street_type].add(street_name)

def check_street_names():
    street_types = defaultdict(set)
    for event, elem in ET.iterparse(filename, events = ("start",)):
        if elem.tag == "way":
            for tag in elem.iter("tag"):
                if is_street_name(tag):
                    audit_street_type(street_types, tag.attrib['v'])
    pprint.pprint(dict(street_types))

check_street_names()
```

The code groups the different street types. The output showed that for some street types there were several inconsistent abbreviations (e.g. “Av”, “Ave” and “Ave.” for Avenue). I don’t mind abbreviations in general, but I decided to remove the inconsistencies (e.g. replace “Av” and “Ave.” with “Ave”). The changes are done according to the following key-value pairs:

```
mapping = {
    r"St.\b": "St",
    r"\bBl\b" : "Bld",
    r"Bld.\b" : "Bld",
    r"Ave.\b": "Ave",
    r"Av\b" : "Ave",
    r"Rd.\b": "Rd",
    r"Py\b" : "Pkwy",
    r"Prky\b" : "Pkwy",
    r"Wy\b": "Way",
    r"\bstreet\b" : "Street"
}
```

A given street name can be updated using regular expressions as follows:

```
def update_name(name, mapping):
    for key in mapping:
        name = re.sub(key,mapping[key],name)
    return name
```

---

## Specifying the data model and updating the street names

The updates of the street names was performed during the data conversion process, i.e. transforming the OSM/XML-file into a JSON/Python dict format:

```
CREATED = [ "version", "changeset", "timestamp", "user", "uid"]
```

*#Convert data into dict format and save as a JSON file*

```
def shape_element(element):
    node = {}
    if element.tag == "node" or element.tag == "way" :

        node['created'] = {}
        la = None
        lo = None
        for at in element.attrib:
            if at == 'lat':
                la = float(element.attrib[at])
            elif at == 'lon':
                lo = float(element.attrib[at])
            elif at in CREATED:
                node['created'][at] = element.attrib[at]
```

```

else:
    node[at] = element.attrib[at]

if la!= None:  #i.e. latitude information is actually present
    node['pos'] = [la,lo]

node['address'] = {}
for tag in element.iter("tag"):
    k_split = tag.attrib['k'].split(":")
    if k_split[0] == 'addr':
        if len(k_split) > 2:
            continue
        else:
            if k_split[1] == "street":          #key == "addr:street"
                                                #if necessary update name according to 'mapping'
                node['address'][k_split[1]] = update_name(tag.attrib['v'],mapping)

            else:                               #different key (not a street name)
                node['address'][k_split[1]] = tag.attrib['v']
    else:
        node[tag.attrib['k']] = tag.attrib['v']

#check for empty fields and delete them
if node['address'] == {}:
    del node['address']
if node['created'] == {}:
    del node['created']

node['node_refs'] = []
for nd in element.iter("nd"):
    node['node_refs'].append(nd.attrib['ref'])
if node['node_refs'] == []:
    del node['node_refs']

node['type'] = element.tag #this possibly overrides already existing tags with key "type"
                           #the line has moved to the bottom as in a preliminary analysis
                           #556 such tags were found using the MongoDB query:
                           #db.data.find({"$and":[{"type":{"$ne":"way"}},{"type":
                           #{"$ne":"node"}}]}).count()

    return node
else:
    return None

def process_map(file_in):
    file_out = "{0}.json".format(file_in)
    data = []
    with codecs.open(file_out, "w") as fo:

```

```
for _, element in ET.iterparse(file_in):
    el = shape_element(element)
    if el:
        data.append(el)
        fo.write(json.dumps(el) + "\n")
return data
```

```
process_map(filename)
```

## 2. Data Overview

---

### Import to MongoDB

I "bulk" imported the created JSON file using the shell command 'mongoimport':

```
mongoimport -d sd -c data --file san-diego-tijuana_mexico.osm.json --drop
```

```
$.....imported 1594251 documents
```

---

### Size

Size of the OSM file: 548 MB

Size of the converted in imported JSON file: 517.4 MB

---

### Overview

```
from pymongo import MongoClient
```

```
def get_db(dbase):
    client = MongoClient('localhost:27017')
    db = client[dbase]
    return db
```

```
#Access database
```

```
db = get_db("sd")
```

```
#Number of files
```

```
db.data.find().count() #1594251
```

```
#Number of nodes
```

```
db.data.find({"type":"node"}).count() #1480433
```

```
#Number of ways
db.data.find({"type":"way"}).count() #113818

# Top 1 contributing user
result = db.data.aggregate([{"$group":{"_id":"$created.user", "count":{"$sum":1}}}, {"$sort":{"count":-1}}, {"$limit":1}])
print list(result) #[{u'count': 684272, u'_id': u'Adam Geitgey'}]

# Number of users appearing only once (having 1 post)
result2 = db.data.aggregate([{"$group":{"_id":"$created.user", "count":{"$sum":1}}}, {"$group":{"_id":"$count", "num_users":{"$sum":1}}}, {"$sort":{"_id":1}}, {"$limit":1}])
print list(result2) #[{u'num_users': 189, u'_id': 1}]
```

---

## Overview of restaurants

```
#Number of restaurants
db.data.find({"amenity":"restaurant"}).count() #643
db.data.find({"$and":{"amenity":"restaurant"}, {"type":"node"}}).count() #544
db.data.find({"$and":{"amenity":"restaurant"}, {"type":"way"}}).count() #99

#Number of restaurants with (partial) address information
db.data.find({"$and":{"amenity":"restaurant"}, {"address":{"$exists": True}}}).count() #160

#Number of restaurants with a given country code
db.data.find({"$and":{"amenity":"restaurant"}, {"is_in:country_code":{"$exists": True}}}).count()
#48
```

This tells us that many restaurants miss information about their location, which gives raise to the following idea.

## 3. Additional Ideas

As the dataset is dealing with a metropolitan area that covers two countries, for a lot of restaurants there would be no explicit tag from which could be inferred directly whether the restaurant would be located in Mexico or the U.S.. For only 48 restaurants such a tag (“is\_in:country\_code”) given.

As we are talking about OSM data, every element should contain information about it’s location (given as a tuple “pos” : [latitude, longitude]) which can be confirmed like

```
restaurants = db.data.find({"$and":{"amenity":"restaurant"}, {"pos":{"$exists": True}}})
restaurants.count()
```

which gives 544 (= total number of restaurant nodes).

Therefore, the idea is to update the “is\_in:country\_code” for all restaurants using the location information in the “pos” field. To do so, I approximate the border as a straight line.

#The border Mexico - USA through San Diego and Tijuana follows approximately this simple straight line where x represents latitude and y longitude:  
# $y = 0.0906502699248 * (x + 117.124002) + 32.533842$

```
def us_border(pos):  
    x,y = pos #unpack the position array  
    if (0.0906502699248 * (x + 117.124002) + 32.533842) < y:  
        return False #if y below the border line => on the Mexican side  
    else:  
        return True # above => U.S.
```

#update "is\_in:country\_code" by looping through all restaurants  
for r in restaurants:

```
    if us_border(r["pos"]):  
        r["is_in:country_code"] = "US"  
    else:  
        r["is_in:country_code"] = "MX"  
    db.data.save(r)
```

```
db.data.find_one({"$and":[{"amenity":"restaurant"}, {"address": {"$exists": True}}]})
```

Out[155]:

```
{u'is_in:country_code': u'US',  
 u'_id': ObjectId('554673422b65e207212b891f'),  
 u'address': {u'city': u'San Diego',  
  u'country': u'US',  
  u'housenumber': u'4110',  
  u'postcode': u'92105',  
  u'street': u'Home Ave'},  
 u'alt_name': u'Chiquitas',  
 u'amenity': u'restaurant',  
 u'contact:phone': u'619.264.2072',  
 u'created': {u'changeset': u'11503119',  
  u'timestamp': u'2012-05-04T23:16:26Z',  
  u'uid': u'674368',  
  u'user': u'Ron Larson',  
  u'version': u'8'},  
 u'cuisine': u'mexican',  
 u'drive_in': u'no',  
 u'id': u'356140998',  
 u'name': u'Chiquita's Mexican Food',  
 u'pos': [32.723789, -117.1070615],  
 u'smoking': u'no',  
 u'source': u'Personal knowledge and visit.',  
 u'takeaway': u'yes',  
 u'type': u'node'}
```

As we can see, the “is\_in:country\_code” field has been updated correctly. In this case, there already has been address information. However, I wanted to try something new and explore how to update MongoDB collections.

## **Python Code for Lesson 6 quizzes:**

See attachment.

## **Link to the Map:**

**File:** [https://s3.amazonaws.com/metro-extracts.mapzen.com/san-diego-tijuana\\_mexico.osm.bz2](https://s3.amazonaws.com/metro-extracts.mapzen.com/san-diego-tijuana_mexico.osm.bz2)

**Position:** <http://www.openstreetmap.org/#map=10/32.8254/-117.2791>

I chose San Diego because I will move there this summer.

## **Sample file:**

See attachment.

## **References:**

[https://wiki.openstreetmap.org/wiki/OSM\\_XML#Example\\_OSM\\_XML\\_file](https://wiki.openstreetmap.org/wiki/OSM_XML#Example_OSM_XML_file)

<http://docs.mongodb.org/manual/reference/>

<http://api.mongodb.org/python/current/examples/aggregation.html>