STUDSPOT KENYA

Complete Source Code & Architecture Documentation

Campus Peer-to-Peer Marketplace & Student Community Platform

Project Details:

- Framework: React 19 (TypeScript) + Vite
- Styling: Tailwind CSS (Mobile-First Responsive)
- Iconography: Lucide React Icons
- Platforms: PWA (Progressive Web App) + Web (Vercel Ready)
- Official Merchant Till: 1823325 (STUDSPOT KENYA)
- Key Features: Feed, Sold Archival, Safe Campus Spots, Chat, Admin Moderation
- Generated: Friday, 16 October 2026

TABLE OF CONTENTS

package.json
vercel.json
vite.config.ts
index.html
src/types/index.ts
src/main.tsx
src/App.tsx
src/components/ListingCard.tsx
src/components/ListingDetailModal.tsx
src/components/TransactionHistoryModal.tsx
src/components/PostListingModal.tsx
src/components/PaymentInstructionScreen.tsx
src/components/InAppChatModal.tsx
src/components/MobileHeader.tsx
src/components/NavigationTabs.tsx
src/components/CampusCategoryFilterBar.tsx
src/components/CampusBuzzFeed.tsx
src/components/AdminApprovalModal.tsx
src/components/SignUpModal.tsx
src/components/StudentVerifyModal.tsx
src/components/MpesaModal.tsx
src/components/SavedModal.tsx
src/components/ShareModal.tsx
src/components/TermsOfServiceModal.tsx
src/components/PWAInstallButton.tsx
src/components/OfflineIndicator.tsx
src/components/StudspotLogo.tsx
src/hooks/usePWAInstall.ts
src/utils/campusStore.ts
src/data/seedData.ts

```
{
  "name": "react-example",
  "private": true,
  "version": "0.0.0",
  "type": "module",
  "scripts": {
    "dev": "vite --port=3000 --host=0.0.0.0",
    "build": "vite build",
    "preview": "vite preview",
    "clean": "rm -rf dist server.js",
    "lint": "tsc --noEmit"
  },
  "dependencies": {
    "@google/genai": "^2.4.0",
    "@tailwindcss/vite": "^4.3.3",
    "@vitejs/plugin-react": "^6.1.1",
    "dotenv": "^17.2.3",
    "express": "^4.21.2",
    "lucide-react": "^0.546.0",
    "motion": "^12.23.24",
    "pdf-lib": "^1.17.1",
    "react": "^19.0.1",
    "react-dom": "^19.0.1",
    "vite": "^8.3.0"
  },
  "devDependencies": {
    "@types/express": "^4.17.21",
    "@types/node": "^22.14.0",
    "@types/react": "^19.3.0",
    "@types/react-dom": "^19.3.0",
    "autoprefixer": "^10.4.21",
    "esbuild": "^0.25.0",
    "tailwindcss": "^4.3.3",
    "tsx": "^4.21.0",
    "typescript": "^7.0.2",
    "vite-plugin-pwa": "^2.0.0"
  }
}
```

```
{
  "buildCommand": "npm run build",
  "outputDirectory": "dist",
  "framework": "vite",
  "rewrites": [
    {
      "source": "/(.*)",
      "destination": "/index.html"
    }
  ]
}
```

```
import tailwindcss from '@tailwindcss/vite';
import react from '@vitejs/plugin-react';
import path from 'path';
import {defineConfig} from 'vite';
import {VitePWA} from 'vite-plugin-pwa';

export default defineConfig(() => {
  return {
    plugins: [
      react(),
      tailwindcss(),
      VitePWA({
        registerType: 'autoUpdate',
        includeAssets: ['favicon.ico', 'apple-touch-icon.png', 'icon.svg', 'pwa-192x192.png', 'pwa-5
  12x512.png', 'pwa-maskable-512x512.png'],
        manifest: {
          id: '/',
          name: 'STUDSPOT Campus Marketplace',
          short_name: 'STUDSPOT',
          description: 'The premier peer-to-peer campus marketplace, hostel finder, gig board, and l
  ocal vendor directory for Kenyan university comrades.',
          theme_color: '#F3B71B',
          background_color: '#121212',
          display: 'standalone',
          orientation: 'portrait-primary',
          start_url: '/',
          scope: '/',
          icons: [
            {
              src: '/pwa-192x192.png',
              sizes: '192x192',
              type: 'image/png',
              purpose: 'any',
            },
            {
              src: '/pwa-512x512.png',
              sizes: '512x512',
              type: 'image/png',
              purpose: 'any',
            },
            {
              src: '/pwa-maskable-512x512.png',
              sizes: '512x512',
              type: 'image/png',
              purpose: 'maskable',
            },
          ],
        },
        workbox: {
          globPatterns: ['**/*.{js,css,html,ico,png,svg,jpg,jpeg,woff,woff2}'],
        },
        devOptions: {
          enabled: true,
          type: 'module',
        },
      }),
    ],
    resolve: {
      alias: {
        '@': path.resolve(process.cwd(), '.'),
      },
    },
    server: {
      // HMR is disabled in AI Studio via DISABLE_HMR env var.
      // Do not modify file watching is disabled to prevent flickering during agent edits.
      hmr: process.env.DISABLE_HMR !== 'true',
      // Disable file watching when DISABLE_HMR is true to save CPU during agent edits.
      watch: process.env.DISABLE_HMR === 'true' ? null : {},
    },
  };
```

```
});
```

```
<!doctype html>
<html lang="en">
  <head>
    <meta charset="UTF-8" />
    <meta name="viewport" content="width=device-width, initial-scale=1.0, maximum-scale=1.0, user-sc
  alable=no" />
    <title>STUDSPOT - Campus Marketplace & Community</title>
    <meta name="description" content="STUDSPOT - The premier peer-to-peer campus marketplace, hostel
   finder, job gig board, and local vendor directory for Kenyan university students." />
    <meta name="theme-color" content="#F3B71B" />
    <meta name="mobile-web-app-capable" content="yes" />
    <meta name="apple-mobile-web-app-capable" content="yes" />
    <meta name="apple-mobile-web-app-status-bar-style" content="black-translucent" />
    <meta name="apple-mobile-web-app-title" content="STUDSPOT" />
    <meta property="og:title" content="STUDSPOT - Campus Marketplace & Community" />
    <meta property="og:description" content="STUDSPOT - The premier peer-to-peer campus marketplace,
   hostel finder, job gig board, and local vendor directory for Kenyan university students." />
    <meta property="og:type" content="website" />
    <meta name="twitter:card" content="summary_large_image" />
    <link rel="manifest" href="/manifest.json" />
    <link rel="icon" type="image/svg+xml" href="/icon.svg" />
    <link rel="icon" type="image/png" sizes="192x192" href="/pwa-192x192.png" />
    <link rel="apple-touch-icon" href="/apple-touch-icon.png" />
    <link rel="preconnect" href="https://fonts.googleapis.com">
    <link rel="preconnect" href="https://fonts.gstatic.com" crossorigin>
    <link href="https://fonts.googleapis.com/css2?family=Plus+Jakarta+Sans:wght@400;500;600;700;800&
  family=Outfit:wght@500;600;700;800&display=swap" rel="stylesheet">
  </head>
  <body class="bg-[#121212] text-slate-100 antialiased selection:bg-[#F3B71B] selection:text-black">
    <div id="root"></div>
    <script type="module" src="/src/main.tsx"></script>
  </body>
</html>
```

```
export type InstitutionType = 'all' | 'university' | 'kmtc' | 'polytechnic' | 'tvet';

export interface University {
  id: string;
  name: string;
  shortName: string;
  city: string;
  campuses: string[];
  studentCount: string;
  institutionType?: InstitutionType;
  categoryLabel?: string;
}

export type ListingType = 'item' | 'hostel' | 'gig' | 'business';

// Adalo Collection: Users
export interface User {
  id: string;
  fullName: string;
  email: string;
  phone: string;
  universityId: string;
  campusName: string;
  studentRegNo?: string;
  role: 'student' | 'vendor' | 'admin';
  agreedToTerms: boolean; // MANDATORY: blocked if false
  createdAt: string;
  isVerifiedStudent: boolean;
}

// Adalo Collection properties for all Listings (Marketplace, Housing, Jobs, Services)
export interface Seller {
  name: string;
  role: 'student' | 'verified_vendor' | 'hostel_caretaker' | 'student_freelancer';
  courseOrBiz?: string;
  yearOfStudy?: string;
  phone: string;
  whatsapp: string;
  isVerifiedStudent: boolean;
  trustScore: number;
  reviewsCount: number;
  avatar?: string;
  safeSpot: string;
  mpesaNumber?: string;
  tillNumber?: string;
}

export interface ListingDetails {
  // Marketplace items
  condition?: 'Brand New' | 'Like New' | 'Good Condition' | 'Fair';
  itemCategory?: 'Textbooks' | 'Electronics' | 'Fashion & Thrift' | 'Hostel Appliances' | 'Furniture
  ' | 'Stationery & Notes';

  // Housing / Hostels
  hostelType?: 'Bedsitter' | 'Single Room' | '1 Bedroom' | 'Shared Room';
  distanceToGate?: string;
  waterStatus?: string;
  electricityType?: string;
  wifiAvailable?: boolean;
  securityGuard?: boolean;
  roomFeatures?: string[];

  // Jobs / Gigs
  gigDuration?: string;
  skillsNeeded?: string[];
  compensationType?: 'Per Task' | 'Per Hour' | 'Per Day' | 'Monthly';

  // Local vendors / Services
  openingHours?: string;
  deliveryAvailable?: boolean;
```

```
  deliveryNote?: string;
  servicesOffered?: string[];
}

// Adalo Collections: Listings, Housing, Jobs
export interface Listing {
  id: string;
  type: ListingType;
  title: string;
  description: string;
  price: number; // in KSh (KES)
  priceLabel?: string; // "/mo", "/semester", "/task", etc.
  isNegotiable?: boolean;
  category: string;
  image: string;
  universityId: string;
  campusName: string;
  institutionType?: InstitutionType; // 'university' | 'kmtc' | 'polytechnic' | 'tvet'
  seller: Seller;
  details: ListingDetails;

  // Adalo Core Workflow Properties:
  isApproved: boolean; // Default: false across all collections!
  isFeePaid: boolean;  // KSh 80 / month fee status
  mpesaRef?: string;   // Safaricom M-Pesa transaction code (e.g., QK948XP12)
  listingFeeKsh: number; // 80 KSh

  createdAt: string;
  viewsCount: number;
  likesCount: number;
  featured?: boolean;

  // Sold Status & Transaction Archival:
  isSold?: boolean;
  soldAt?: string;
  soldPrice?: number;
}

export interface CommunityPost {
  id: string;
  type: 'lost_found' | 'rideshare' | 'study_group' | 'alert';
  title: string;
  content: string;
  author: string;
  authorRole: string;
  universityId: string;
  campusName: string;
  timeAgo: string;
  repliesCount: number;
  likesCount: number;
  statusTag?: string;
}

export interface Message {
  id: string;
  sender: 'user' | 'other';
  text: string;
  timestamp: string;
}
```

```
import {createRoot} from 'react-dom/client';
import App from './App.tsx';
import './index.css';

createRoot(document.getElementById('root')!).render(<App />);
```

```
/**
 * @license
 * SPDX-License-Identifier: Apache-2.0
 */

import React, { useState, useEffect, useMemo } from 'react';
import {
  ShoppingBag,
  Home,
  Briefcase,
  Store,
  MapPin,
  ShieldCheck,
  Sparkles,
  ArrowUpDown,
  CheckCircle2,
  Users,
  Smartphone,
  Database,
  FileText,
  AlertTriangle,
  CreditCard,
  PlusCircle,
  HelpCircle,
  Share2,
  History
} from 'lucide-react';

import { Listing, CommunityPost, User, ListingType, InstitutionType } from './types';
import { INITIAL_LISTINGS, INITIAL_COMMUNITY_POSTS, INITIAL_USERS, UNIVERSITIES } from './data/seedD
  ata';
import { getAllCampuses } from './utils/campusStore';
import { MobileHeader } from './components/MobileHeader';
import { BottomNavBar, CategoryFilterPills, NavTabType } from './components/NavigationTabs';
import { CampusCategoryFilterBar } from './components/CampusCategoryFilterBar';
import { ListingCard } from './components/ListingCard';
import { ListingDetailModal } from './components/ListingDetailModal';
import { PostListingModal } from './components/PostListingModal';
import { SignUpModal } from './components/SignUpModal';
import { TermsOfServiceModal } from './components/TermsOfServiceModal';
import { PaymentInstructionScreen } from './components/PaymentInstructionScreen';
import { AdminApprovalModal } from './components/AdminApprovalModal';
import { OnboardingScreen } from './components/OnboardingScreen';
import { MpesaModal } from './components/MpesaModal';
import { InAppChatModal } from './components/InAppChatModal';
import { SavedModal } from './components/SavedModal';
import { CampusBuzzFeed } from './components/CampusBuzzFeed';
import { ShareModal, ShareTarget } from './components/ShareModal';
import { TransactionHistoryModal } from './components/TransactionHistoryModal';
import { PWAInstallButton } from './components/PWAInstallButton';
import { OfflineIndicator } from './components/OfflineIndicator';

export default function App() {
  // 1. Database Collections State (Adalo Data Architecture)
  const [users, setUsers] = useState<User[]>(() => {
    try {
      const stored = localStorage.getItem('studspot_users');
      return stored ? JSON.parse(stored) : INITIAL_USERS;
    } catch {
      return INITIAL_USERS;
    }
  });

  const [currentUser, setCurrentUser] = useState<User | null>(() => {
    try {
      const stored = localStorage.getItem('studspot_current_user');
      return stored ? JSON.parse(stored) : INITIAL_USERS[0]; // Brian Mwangi
    } catch {
      return INITIAL_USERS[0];
    }
```

```
});

const [listings, setListings] = useState<Listing[]>(() => {
  try {
    const stored = localStorage.getItem('studspot_listings');
    return stored ? JSON.parse(stored) : INITIAL_LISTINGS;
  } catch {
    return INITIAL_LISTINGS;
  }
});

const [communityPosts, setCommunityPosts] = useState<CommunityPost[]>(() => {
  try {
    const stored = localStorage.getItem('studspot_buzz');
    return stored ? JSON.parse(stored) : INITIAL_COMMUNITY_POSTS;
  } catch {
    return INITIAL_COMMUNITY_POSTS;
  }
});

const [savedIds, setSavedIds] = useState<string[]>(() => {
  try {
    const stored = localStorage.getItem('studspot_saved');
    return stored ? JSON.parse(stored) : ['item-1', 'hostel-1'];
  } catch {
    return ['item-1', 'hostel-1'];
  }
});

// 2. Navigation & Filter State
const [selectedUniversity, setSelectedUniversity] = useState<string>('all');
const [selectedCampusCategory, setSelectedCampusCategory] = useState<InstitutionType>('all');
const [activeTab, setActiveTab] = useState<NavTabType>('all');
const [searchQuery, setSearchQuery] = useState<string>('');
const [sortOption, setSortOption] = useState<'default' | 'price_asc' | 'price_desc'>('default');
const [selectedSubcategory, setSelectedSubcategory] = useState<string>('all');
const [isMobileDeviceView, setIsMobileDeviceView] = useState<boolean>(false);

// 3. Screens & Modals
const [isOnboardingOpen, setIsOnboardingOpen] = useState<boolean>(false);
const [isSignUpOpen, setIsSignUpOpen] = useState<boolean>(false);
const [isTermsOpen, setIsTermsOpen] = useState<boolean>(false);
const [isAdminConsoleOpen, setIsAdminConsoleOpen] = useState<boolean>(false);
const [isPostModalOpen, setIsPostModalOpen] = useState<boolean>(false);
const [paymentListing, setPaymentListing] = useState<Listing | null>(null);
const [selectedListing, setSelectedListing] = useState<Listing | null>(null);
const [mpesaListing, setMpesaListing] = useState<Listing | null>(null);
const [chatListing, setChatListing] = useState<Listing | null>(null);
const [isSavedModalOpen, setIsSavedModalOpen] = useState<boolean>(false);
const [shareTarget, setShareTarget] = useState<ShareTarget | null>(null);
const [isShareModalOpen, setIsShareModalOpen] = useState<boolean>(false);
const [isTransactionHistoryOpen, setIsTransactionHistoryOpen] = useState<boolean>(false);

const handleToggleSold = (listingId: string) => {
  const nowFormatted = new Date().toLocaleDateString('en-KE', { month: 'short', day: 'numeric', ye
ar: 'numeric' });
  setListings(prev =>
    prev.map(item => {
      if (item.id === listingId) {
        const willBeSold = !item.isSold;
        return {
          ...item,
          isSold: willBeSold,
          soldAt: willBeSold ? nowFormatted : undefined,
          soldPrice: willBeSold ? item.price : undefined,
        };
      }
      return item;
    })
  );
```

```
  setSelectedListing(prev => {
    if (prev && prev.id === listingId) {
      const willBeSold = !prev.isSold;
      return {
        ...prev,
        isSold: willBeSold,
        soldAt: willBeSold ? nowFormatted : undefined,
        soldPrice: willBeSold ? prev.price : undefined,
      };
    }
    return prev;
  });
};

const handleOpenShareApp = () => {
  setShareTarget({
    type: 'app',
    title: 'STUDSPOT - Campus Marketplace & Student Directory',
    text: 'Hey comrade! Check out STUDSPOT, Kenya s verified peer-to-peer campus marketplace for f
inding bedsitters, textbooks, laptops, and student gigs!',
    url: window.location.href,
  });
  setIsShareModalOpen(true);
};

const handleOpenShareListing = (listing: Listing) => {
  setShareTarget({
    type: 'listing',
    title: `${listing.title} - KES ${listing.price.toLocaleString()} on STUDSPOT`,
    text: `Habari comrades! Check out "${listing.title}" for KES ${listing.price.toLocaleString()}
 at ${listing.campusName} on STUDSPOT.`,
    url: `${window.location.origin}/?listing=${listing.id}`,
    listing,
  });
  setIsShareModalOpen(true);
};

// LocalStorage Sync
useEffect(() => {
  try {
    localStorage.setItem('studspot_users', JSON.stringify(users));
  } catch (e) {
    console.warn(e);
  }
}, [users]);

useEffect(() => {
  try {
    localStorage.setItem('studspot_current_user', JSON.stringify(currentUser));
  } catch (e) {
    console.warn(e);
  }
}, [currentUser]);

useEffect(() => {
  try {
    localStorage.setItem('studspot_listings', JSON.stringify(listings));
  } catch (e) {
    console.warn(e);
  }
}, [listings]);

useEffect(() => {
  try {
    localStorage.setItem('studspot_buzz', JSON.stringify(communityPosts));
  } catch (e) {
    console.warn(e);
  }
}, [communityPosts]);
```

```
useEffect(() => {
  try {
    localStorage.setItem('studspot_saved', JSON.stringify(savedIds));
  } catch (e) {
    console.warn(e);
  }
}, [savedIds]);

// Wishlist toggle
const toggleSave = (id: string, e?: React.MouseEvent) => {
  if (e) e.stopPropagation();
  setSavedIds(prev =>
    prev.includes(id) ? prev.filter(item => item !== id) : [...prev, id]
  );
};

// Workflow Action 1: User Registration with Mandatory Terms
const handleUserRegistered = (newUser: User) => {
  setUsers(prev => [newUser, ...prev.filter(u => u.id !== newUser.id)]);
  setCurrentUser(newUser);
};

// Workflow Action 2: Listing Creation -> Redirects to Payment Screen (KSh 80)
const handleAddListing = (newListing: Listing) => {
  // Save to database collection with isApproved: false
  setListings(prev => [newListing, ...prev]);
  setIsPostModalOpen(false);

  // Redirect immediately to Pending Payment / Instruction Screen!
  setPaymentListing(newListing);
};

// Workflow Action 3: Payment Reference Submitted
const handleSubmitMpesaRef = (listingId: string, ref: string) => {
  setListings(prev => prev.map(item => {
    if (item.id === listingId) {
      return {
        ...item,
        isFeePaid: true,
        mpesaRef: ref
      };
    }
    return item;
  }));
};

// Workflow Action 4: Admin Manual Approval in Database (isApproved = True)
const handleApproveListing = (id: string) => {
  setListings(prev => prev.map(item => {
    if (item.id === id) {
      return {
        ...item,
        isApproved: true,
        isFeePaid: true
      };
    }
    return item;
  }));
};

const handleRejectListing = (id: string) => {
  setListings(prev => prev.filter(item => item.id !== id));
};

const handleMarkFeePaid = (id: string, ref: string) => {
  setListings(prev => prev.map(item => {
    if (item.id === id) {
      return {
        ...item,
```

```
        isFeePaid: true,
        mpesaRef: ref
      };
    }
    return item;
  }));
};

const handleAddCommunityPost = (newPost: CommunityPost) => {
  setCommunityPosts(prev => [newPost, ...prev]);
  setActiveTab('buzz');
};

// STRICT ADALO FEED FILTER: Filtered strictly where isApproved == True!
const publicFeedListings = useMemo(() => {
  return listings.filter(item => {
    // MANDATORY ADALO SPEC: Feed filtered strictly where isApproved == True!
    if (!item.isApproved) return false;

    // Tab / Collection type filter
    if (activeTab !== 'all' && activeTab !== 'buzz' && item.type !== activeTab) {
      return false;
    }

    // Campus Category filter (Universities, KMTC Colleges, National Polytechnics, TVETs)
    if (selectedCampusCategory !== 'all') {
      const itemInstType = item.institutionType ||
        UNIVERSITIES.find(u => u.id === item.universityId)?.institutionType;
      if (itemInstType !== selectedCampusCategory && item.universityId !== 'all') {
        return false;
      }
    }

    // Target University filter
    if (selectedUniversity !== 'all' && item.universityId !== 'all') {
      const allCampuses = getAllCampuses();
      const uniObj = allCampuses.find(u => u.id === selectedUniversity);
      const matchExact = item.universityId === selectedUniversity;
      const matchName = !!(uniObj && (
        item.campusName.toLowerCase().includes(uniObj.name.toLowerCase()) ||
        item.campusName.toLowerCase().includes(uniObj.shortName.toLowerCase()) ||
        (uniObj.name.toLowerCase().includes('kisii') && item.campusName.toLowerCase().includes('ki
sii')) ||
        (uniObj.name.toLowerCase().includes('ksii') && item.campusName.toLowerCase().includes('ksi
i'))
      ));
      if (!matchExact && !matchName) {
        return false;
      }
    }

    // Subcategory quick keyword filter
    if (selectedSubcategory !== 'all') {
      const itemCat = item.category.toLowerCase();
      const sub = selectedSubcategory.toLowerCase();
      if (!itemCat.includes(sub)) return false;
    }

    // Search query
    if (searchQuery.trim()) {
      const query = searchQuery.toLowerCase();
      const matchesTitle = item.title.toLowerCase().includes(query);
      const matchesDesc = item.description.toLowerCase().includes(query);
      const matchesCat = item.category.toLowerCase().includes(query);
      const matchesCampus = item.campusName.toLowerCase().includes(query);
      const matchesSeller = item.seller.name.toLowerCase().includes(query);
      return matchesTitle || matchesDesc || matchesCat || matchesCampus || matchesSeller;
    }

    return true;
```

```
  }).sort((a, b) => {
    if (sortOption === 'price_asc') return a.price - b.price;
    if (sortOption === 'price_desc') return b.price - a.price;
    return 0;
  });
}, [listings, activeTab, selectedCampusCategory, selectedUniversity, selectedSubcategory, searchQu
ery, sortOption]);

const pendingListingsCount = useMemo(() => {
  return listings.filter(l => !l.isApproved).length;
}, [listings]);

// Counts for Campus Categories (Universities, KMTC Colleges, National Polys, TVETs)
const campusCategoryCounts = useMemo(() => {
  const approved = listings.filter(l => l.isApproved);
  const getInstType = (l: Listing): InstitutionType => {
    if (l.institutionType) return l.institutionType;
    const u = UNIVERSITIES.find(uni => uni.id === l.universityId);
    return u?.institutionType || 'university';
  };

  return {
    all: approved.length,
    university: approved.filter(l => getInstType(l) === 'university').length,
    kmtc: approved.filter(l => getInstType(l) === 'kmtc').length,
    polytechnic: approved.filter(l => getInstType(l) === 'polytechnic').length,
    tvet: approved.filter(l => getInstType(l) === 'tvet').length,
  };
}, [listings]);

// Counts for pills (only approved items shown in category counts)
const approvedCounts = useMemo(() => {
  const approved = listings.filter(l => l.isApproved);
  return {
    all: approved.length,
    item: approved.filter(l => l.type === 'item').length,
    hostel: approved.filter(l => l.type === 'hostel').length,
    gig: approved.filter(l => l.type === 'gig').length,
    business: approved.filter(l => l.type === 'business').length,
    buzz: communityPosts.length,
  };
}, [listings, communityPosts]);

const savedListingsObjects = useMemo(() => {
  return listings.filter(l => savedIds.includes(l.id));
}, [listings, savedIds]);

const currentUniName = useMemo(() => {
  const all = getAllCampuses();
  return all.find(u => u.id === selectedUniversity)?.name || 'All Campuses';
}, [selectedUniversity]);

// Main UI Canvas
const mainContent = (
  <div className="min-h-screen bg-[#121212] text-slate-100 flex flex-col pb-24">
    {/* Test Cycle Quick Action Strip (Top Banner) */}
    <div className="bg-[#1C1C1C] border-b border-neutral-800 px-4 py-1.5 text-xs text-neutral-300"
>
      <div className="max-w-7xl mx-auto flex flex-wrap items-center justify-between gap-2">
        <div className="flex items-center gap-2">
          <span className="w-2 h-2 rounded-full bg-[#F3B71B] shrink-0" />
          <span className="font-bold text-white">STUDSPOT End-to-End Workflow:</span>
          <span className="text-[11px] text-neutral-400 hidden sm:inline">
            1. Register with Terms &gt; 2. Post Listing &gt; 3. M-Pesa KSh 80 Instructions &gt; 4.
 Admin Database Approval &gt; 5. Public Feed Live
          </span>
        </div>

        <div className="flex items-center gap-2">
          <button
```

```
            type="button"
            onClick={() => setIsAdminConsoleOpen(true)}
            className="text-[#F3B71B] hover:underline font-bold text-[11px] flex items-center gap-
1"
          >
            <Database className="w-3 h-3" />
            <span>Admin Database Console ({pendingListingsCount} Pending)</span>
          </button>
          <span className="text-neutral-600">|</span>
          <button
            type="button"
            onClick={() => setIsTermsOpen(true)}
            className="text-neutral-400 hover:text-white text-[11px]"
          >
            Legal Terms
          </button>
        </div>
      </div>
    </div>

    {/* Mobile Top Header */}
    <MobileHeader
      selectedUniversity={selectedUniversity}
      onSelectUniversity={setSelectedUniversity}
      searchQuery={searchQuery}
      onSearchChange={setSearchQuery}
      savedCount={savedIds.length}
      onOpenSaved={() => setIsSavedModalOpen(true)}
      currentUser={currentUser}
      onOpenSignUp={() => setIsSignUpOpen(true)}
      onOpenTerms={() => setIsTermsOpen(true)}
      onOpenAdminConsole={() => setIsAdminConsoleOpen(true)}
      pendingCount={pendingListingsCount}
      isMobileDeviceView={isMobileDeviceView}
      onToggleDeviceView={() => setIsMobileDeviceView(!isMobileDeviceView)}
      onOpenOnboarding={() => setIsOnboardingOpen(true)}
      onOpenShareApp={handleOpenShareApp}
      onOpenTransactionHistory={() => setIsTransactionHistoryOpen(true)}
      soldCount={listings.filter(l => l.isSold).length}
    />

    <main className="max-w-7xl mx-auto px-4 w-full flex-1 pt-3 space-y-4">
      {/* Campus Hero Card with STUDSPOT Gold Accent & Dark Contrast */}
      <div className="relative rounded-3xl overflow-hidden bg-gradient-to-br from-[#242424] via-[#
1A1A1A] to-[#121212] border border-neutral-800 text-white p-5 sm:p-7 shadow-2xl">
        <div className="flex flex-col lg:flex-row lg:items-center justify-between gap-6 relative z
-10">
          <div className="max-w-xl space-y-2.5">
            <div className="flex items-center gap-2">
              <span className="text-[10px] font-black uppercase tracking-widest text-black bg-[#F3
B71B] px-2.5 py-0.5 rounded font-mono">
                {currentUniName}
              </span>
              <span className="text-xs text-neutral-400">  Peer-to-Peer Campus Directory</span>
            </div>

            <div className="flex items-center gap-3.5">
              <div className="w-14 h-14 rounded-2xl overflow-hidden p-0.5 bg-gradient-to-br from-[
#0F2D59] via-[#08182F] to-black border-2 border-cyan-400/50 shadow-xl shadow-cyan-950/60 shrink-0
hidden sm:flex items-center justify-center">
                <img
                  src="/src/assets/images/studspot_official_icon_1791805148976.jpg"
                  alt="STUDSPOT Official Logo"
                  className="w-full h-full object-cover rounded-xl"
                />
              </div>
              <div>
                <h1 className="text-xl sm:text-2xl md:text-3xl font-black tracking-tight font-head
ing leading-tight text-white">
                  STUDSPOT Campus Marketplace
```

```
              </h1>
              <p className="text-[11px] text-[#F3B71B] font-mono font-bold">
                Official Peer-to-Peer Directory   Kenya
              </p>
            </div>
          </div>

          <p className="text-xs sm:text-sm text-neutral-300 leading-relaxed max-w-lg">
            Verified peer-to-peer campus marketplace, hostel finder, student job gigs, and local
 directory for Kenyan Universities, KMTC Medical Colleges, National Polytechnics & TVETs.
          </p>

          {/* Quick Metrics & Fee Badge */}
          <div className="pt-2 flex flex-wrap items-center gap-4 text-xs font-semibold text-neut
ral-300">
            <div className="flex items-center gap-1.5 text-emerald-400">
              <CheckCircle2 className="w-3.5 h-3.5" />
              <span>Admin Vetted (<code className="text-white">isApproved == True</code>)</span>
            </div>
            <div className="flex items-center gap-1.5 text-[#F3B71B] font-mono">
              <CreditCard className="w-3.5 h-3.5" />
              <span>KSh 80 / Month Advertising Fee</span>
            </div>
            <div className="flex items-center gap-1.5 text-neutral-400">
              <MapPin className="w-3.5 h-3.5 text-[#F3B71B]" />
              <span>35+ Campuses, KMTCs, Polys & TVETs</span>
            </div>
          </div>

          {/* Install PWA and Share Actions */}
          <div className="pt-2 flex flex-wrap items-center gap-2.5">
            <PWAInstallButton />
            <button
              type="button"
              onClick={handleOpenShareApp}
              className="px-3.5 py-1.5 rounded-xl bg-[#242424] hover:bg-[#2e2e2e] text-neutral-2
00 border border-neutral-700 text-xs font-bold transition flex items-center gap-1.5"
            >
              <Share2 className="w-3.5 h-3.5 text-[#F3B71B]" />
              <span>Share with Comrades</span>
            </button>
          </div>
        </div>

        {/* Featured Campus Gate Preview: KISII UNIVERSITY */}
        <div className="hidden lg:block w-80 shrink-0">
          <div className="rounded-2xl overflow-hidden border border-neutral-700/80 shadow-2xl bg
-[#181818] group">
            <div className="relative">
              <img
                src="/src/assets/images/kisii_university_campus_1791808842007.jpg"
                alt="Kisii University Campus Gate"
                className="w-full h-40 object-cover object-center group-hover:scale-105 transiti
on-transform duration-300"
              />
              <div className="absolute top-2 left-2 bg-black/85 backdrop-blur-md px-2 py-0.5 rou
nded text-[10px] font-bold text-[#F3B71B] border border-[#F3B71B]/40">
                FEATURED CAMPUS
              </div>
            </div>
            <div className="p-3 bg-[#161616] border-t border-neutral-800 flex items-center justi
fy-between">
              <div>
                <span className="text-xs font-bold text-white block">KISII UNIVERSITY</span>
                <span className="text-[10px] text-neutral-400 font-mono">Training for Developmen
t   Kisii</span>
              </div>
              <button
                type="button"
                onClick={() => setSelectedUniversity('kisii_uni')}
```

```
                  className="px-2.5 py-1 text-[11px] font-bold bg-[#F3B71B] text-black rounded-lg
hover:bg-[#dca415] transition-colors"
                >
                  {selectedUniversity === 'kisii_uni' ? 'Active' : 'Select'}
                </button>
              </div>
            </div>
          </div>
        </div>

        {/* Background image subtle overlay */}
        <div className="absolute right-0 top-0 bottom-0 w-1/2 opacity-15 pointer-events-none hidde
n md:block">
          <img
            src="/src/assets/images/kisii_university_campus_1791808842007.jpg"
            alt="Kisii University Campus"
            className="w-full h-full object-cover"
          />
        </div>
      </div>

      {/* Pending Approvals Notice Banner if items are awaiting approval */}
      {pendingListingsCount > 0 && (
        <div className="p-3 bg-amber-500/10 rounded-2xl border border-amber-500/30 flex items-cent
er justify-between gap-3 text-xs">
          <div className="flex items-center gap-2">
            <AlertTriangle className="w-4 h-4 text-amber-400 shrink-0" />
            <span className="text-neutral-200">
              <strong className="text-amber-300">{pendingListingsCount} listing(s)</strong> awaiti
ng Admin approval and KSh 80 M-Pesa fee verification.
            </span>
          </div>
          <button
            type="button"
            onClick={() => setIsAdminConsoleOpen(true)}
            className="px-3 py-1 bg-[#F3B71B] hover:bg-[#dca415] text-black font-extrabold text-[1
1px] rounded-lg transition-colors whitespace-nowrap"
          >
            Open Admin Console
          </button>
        </div>
      )}

      {/* Campus Categories Filter Bar (Universities, KMTC Colleges, National Polys, TVET Institut
es) */}
      <CampusCategoryFilterBar
        selectedCampusCategory={selectedCampusCategory}
        onSelectCampusCategory={setSelectedCampusCategory}
        selectedUniversity={selectedUniversity}
        onSelectUniversity={setSelectedUniversity}
        categoryCounts={campusCategoryCounts}
      />

      {/* Category Filter Pills (Marketplace, Housing, Jobs, Services, Buzz) */}
      <CategoryFilterPills
        activeTab={activeTab}
        onSelectTab={(tab) => {
          setActiveTab(tab);
          setSelectedSubcategory('all');
        }}
        counts={approvedCounts}
      />

      {/* Subcategory & Sort Bar (shown when not in Buzz view) */}
      {activeTab !== 'buzz' && (
        <div className="flex items-center justify-between gap-2 text-xs flex-wrap">
          {/* Quick Keyword Shortcuts */}
          <div className="flex items-center gap-1.5 overflow-x-auto no-scrollbar py-1">
            {[
              { id: 'all', label: 'All Items' },
```

```
              { id: 'medical', label: '   KMTC Medical' },
              { id: 'engineering', label: '   Poly Workshop' },
              { id: 'textbook', label: '   Books & Past Papers' },
              { id: 'electronic', label: '   Laptops & Tech' },
              { id: 'bedsitter', label: '   Bedsitters' },
              { id: 'thrift', label: '   Thrift Drip' },
              { id: 'appliance', label: '  Kettles & Hotplates' },
            ].map((sub) => (
              <button
                key={sub.id}
                type="button"
                onClick={() => setSelectedSubcategory(sub.id)}
                className={`whitespace-nowrap px-2.5 py-1 rounded-lg text-xs font-medium transitio
n-colors ${
                  selectedSubcategory === sub.id
                    ? 'bg-[#F3B71B] text-black font-bold'
                    : 'bg-[#1E1E1E] border border-neutral-800 text-neutral-300 hover:bg-[#252525]'
                }`}
              >
                {sub.label}
              </button>
            ))}
          </div>

          {/* Price Sorting Dropdown & History Shortcut */}
          <div className="flex items-center gap-2 shrink-0 ml-auto">
            <button
              type="button"
              onClick={() => setIsTransactionHistoryOpen(true)}
              className="flex items-center gap-1.5 px-2.5 py-1 rounded-lg text-xs font-semibold bg
-[#202020] hover:bg-[#282828] text-neutral-300 border border-neutral-800 transition-colors"
              title="View your campus deals & sold transaction history"
            >
              <History className="w-3.5 h-3.5 text-[#F3B71B]" />
              <span className="hidden sm:inline">History</span>
              {listings.filter(l => l.isSold).length > 0 && (
                <span className="bg-rose-500/20 text-rose-300 border border-rose-500/30 text-[10px
] px-1.5 py-0.2 rounded-full font-mono">
                  {listings.filter(l => l.isSold).length} sold
                </span>
              )}
            </button>

            <div className="flex items-center gap-1.5">
              <ArrowUpDown className="w-3.5 h-3.5 text-neutral-500" />
              <select
                value={sortOption}
                onChange={(e) => setSortOption(e.target.value as any)}
                className="bg-[#1E1E1E] border border-neutral-800 rounded-lg px-2 py-1 text-xs tex
t-neutral-300 outline-none cursor-pointer"
              >
                <option value="default">Sort: Newest First</option>
                <option value="price_asc">Price: Low to High</option>
                <option value="price_desc">Price: High to Low</option>
              </select>
            </div>
          </div>
        </div>
      )}

      {/* Content Display: Either Campus Buzz or Approved Public Feed */}
      {activeTab === 'buzz' ? (
        <CampusBuzzFeed
          posts={communityPosts}
          onAddPost={handleAddCommunityPost}
          selectedUniversity={selectedUniversity}
          isVerifiedStudent={currentUser?.isVerifiedStudent ?? true}
        />
      ) : (
        <div>
```

```
          {publicFeedListings.length === 0 ? (
            <div className="bg-[#1A1A1A] rounded-3xl border border-neutral-800 p-12 text-center sp
ace-y-3">
              <ShoppingBag className="w-10 h-10 text-neutral-600 mx-auto" />
              <h3 className="text-base font-bold text-white">No active approved listings found</h3
>
              <p className="text-xs text-neutral-400 max-w-sm mx-auto">
                Only listings with <code className="text-[#F3B71B]">isApproved == True</code> appe
ar in this public feed.
              </p>
              <div className="flex items-center justify-center gap-2 pt-2">
                <button
                  type="button"
                  onClick={() => setIsPostModalOpen(true)}
                  className="px-4 py-2 bg-[#F3B71B] text-black text-xs font-bold rounded-xl hover:
bg-[#dca415] transition-colors"
                >
                  Post New Listing
                </button>
                <button
                  type="button"
                  onClick={() => setIsAdminConsoleOpen(true)}
                  className="px-4 py-2 bg-[#242424] text-neutral-300 text-xs font-bold rounded-xl
hover:bg-neutral-700 transition-colors"
                >
                  Check Pending Approvals ({pendingListingsCount})
                </button>
              </div>
            </div>
          ) : (
            <div className="grid grid-cols-1 sm:grid-cols-2 lg:grid-cols-3 xl:grid-cols-4 gap-4">
              {publicFeedListings.map((listing) => (
                <ListingCard
                  key={listing.id}
                  listing={listing}
                  isSaved={savedIds.includes(listing.id)}
                  onToggleSave={toggleSave}
                  onOpenDetail={(item) => setSelectedListing(item)}
                  onOpenMpesaGuide={(item, e) => {
                    e.stopPropagation();
                    setMpesaListing(item);
                  }}
                  onShare={(item) => handleOpenShareListing(item)}
                />
              ))}
            </div>
          )}
        </div>
      )}

      {/* Legal Safeguard & Terms Banner */}
      <section className="bg-[#1A1A1A] border border-neutral-800 text-white rounded-3xl p-6 sm:p-8
 flex flex-col md:flex-row items-center justify-between gap-6">
        <div className="space-y-2 max-w-xl">
          <div className="flex items-center gap-1.5 text-[#F3B71B] text-xs font-bold uppercase tra
cking-wider">
            <ShieldCheck className="w-4 h-4" />
            <span>STUDSPOT Legal Framework & Liability Protection</span>
          </div>
          <h3 className="text-lg sm:text-xl font-bold font-heading">
            Directory Intermediary Disclaimer
          </h3>
          <p className="text-xs text-neutral-400 leading-relaxed">
            STUDSPOT acts solely as an advertising directory and is not a party to user transactio
ns, leases, or job contracts. No stolen goods, illegal items, or academic fraud services. Flat KSh
 80 fee covers 30 days advertising and is strictly non-refundable.
          </p>
        </div>

        <div className="flex flex-col sm:flex-row items-center gap-3 shrink-0">
```

```
          <button
            type="button"
            onClick={() => setIsTermsOpen(true)}
            className="w-full sm:w-auto px-5 py-2.5 bg-neutral-800 hover:bg-neutral-700 text-white
 font-bold text-xs rounded-xl border border-neutral-700 transition-all flex items-center justify-c
enter gap-1.5"
          >
            <FileText className="w-4 h-4 text-[#F3B71B]" />
            <span>Read Full Legal Terms</span>
          </button>

          <button
            type="button"
            onClick={() => setIsPostModalOpen(true)}
            className="w-full sm:w-auto px-5 py-2.5 bg-[#F3B71B] hover:bg-[#dca415] text-black fon
t-extrabold text-xs rounded-xl transition-all shadow-md active:scale-95 flex items-center justify-
center gap-1.5"
          >
            <PlusCircle className="w-4 h-4" />
            <span>Submit Listing (KSh 80)</span>
          </button>
        </div>
      </section>
    </main>

    {/* Fixed Bottom Mobile App Bar */}
    <BottomNavBar
      activeTab={activeTab}
      onSelectTab={setActiveTab}
      onOpenPostModal={() => setIsPostModalOpen(true)}
    />

    {/* 4. MODALS & SCREENS IN WORKFLOW */}

    {/* Screen 1: Welcome / Onboarding Screen */}
    <OnboardingScreen
      isOpen={isOnboardingOpen}
      onClose={() => setIsOnboardingOpen(false)}
      onOpenSignUp={() => setIsSignUpOpen(true)}
      onOpenTerms={() => setIsTermsOpen(true)}
    />

    {/* Screen 2: Sign-Up Screen with Mandatory Terms Consent */}
    <SignUpModal
      isOpen={isSignUpOpen}
      onClose={() => setIsSignUpOpen(false)}
      onUserRegistered={handleUserRegistered}
      onOpenTerms={() => setIsTermsOpen(true)}
    />

    {/* Screen 4: Listing Creation Screen */}
    <PostListingModal
      isOpen={isPostModalOpen}
      onClose={() => setIsPostModalOpen(false)}
      onAddListing={handleAddListing}
      currentUser={currentUser}
      onOpenTerms={() => setIsTermsOpen(true)}
    />

    {/* Screen 5: Pending Payment / Instruction Screen (M-Pesa KSh 80) */}
    <PaymentInstructionScreen
      listing={paymentListing}
      isOpen={!!paymentListing}
      onClose={() => setPaymentListing(null)}
      onSubmitMpesaRef={handleSubmitMpesaRef}
      onOpenAdminConsole={() => {
        setPaymentListing(null);
        setIsAdminConsoleOpen(true);
      }}
    />
```

```
      {/* Screen 6: Legal / Terms of Service Screen */}
      <TermsOfServiceModal
        isOpen={isTermsOpen}
        onClose={() => setIsTermsOpen(false)}
      />

      {/* Screen 7: Admin Approval & Adalo Database Console */}
      <AdminApprovalModal
        isOpen={isAdminConsoleOpen}
        onClose={() => setIsAdminConsoleOpen(false)}
        listings={listings}
        users={users}
        onApproveListing={handleApproveListing}
        onRejectListing={handleRejectListing}
        onMarkFeePaid={handleMarkFeePaid}
        onOpenListingDetail={(item) => setSelectedListing(item)}
      />

      {/* Listing Detail Modal */}
      <ListingDetailModal
        listing={selectedListing}
        onClose={() => setSelectedListing(null)}
        isSaved={selectedListing ? savedIds.includes(selectedListing.id) : false}
        onToggleSave={toggleSave}
        onOpenMpesaModal={(item) => {
          setSelectedListing(null);
          setMpesaListing(item);
        }}
        onOpenInAppChat={(item) => {
          setSelectedListing(null);
          setChatListing(item);
        }}
        onOpenTerms={() => setIsTermsOpen(true)}
        onOpenShareModal={(item) => handleOpenShareListing(item)}
        onToggleSold={handleToggleSold}
        onOpenTransactionHistory={() => setIsTransactionHistoryOpen(true)}
      />

      {/* M-Pesa Safe Transaction Helper */}
      <MpesaModal
        listing={mpesaListing}
        onClose={() => setMpesaListing(null)}
      />

      {/* In-App Direct Chat */}
      <InAppChatModal
        listing={chatListing}
        onClose={() => setChatListing(null)}
      />

      {/* Saved / Wishlist Modal */}
      <SavedModal
        isOpen={isSavedModalOpen}
        onClose={() => setIsSavedModalOpen(false)}
        savedListings={savedListingsObjects}
        onRemoveSaved={toggleSave}
        onOpenDetail={(item) => setSelectedListing(item)}
      />

      {/* Transaction History & Sold Archival Modal */}
      <TransactionHistoryModal
        isOpen={isTransactionHistoryOpen}
        onClose={() => setIsTransactionHistoryOpen(false)}
        listings={listings}
        currentUser={currentUser}
        onToggleSold={handleToggleSold}
        onOpenDetail={(item) => setSelectedListing(item)}
        onOpenPostModal={() => setIsPostModalOpen(true)}
      />
```

```
      {/* Universal Share Modal (App & Listings) */}
      <ShareModal
        isOpen={isShareModalOpen}
        onClose={() => setIsShareModalOpen(false)}
        target={shareTarget}
      />

      {/* PWA Offline Mode Indicator */}
      <OfflineIndicator />
    </div>
  );

  // Optional Phone Frame Preview on Desktop
  if (isMobileDeviceView) {
    return (
      <div className="min-h-screen bg-black py-8 px-4 flex flex-col items-center justify-center">
        {/* Device toggle toolbar */}
        <div className="mb-4 flex items-center justify-between w-full max-w-[420px] text-white text-
  xs">
          <div className="flex items-center gap-2">
            <Smartphone className="w-4 h-4 text-[#F3B71B]" />
            <span className="font-bold">STUDSPOT Mobile Screen</span>
          </div>
          <button
            type="button"
            onClick={() => setIsMobileDeviceView(false)}
            className="px-3 py-1 bg-neutral-800 hover:bg-neutral-700 rounded-lg text-white font-medi
  um text-xs transition-colors"
          >
            Switch to Full Web View
          </button>
        </div>

        {/* Smartphone bezel frame */}
        <div className="w-full max-w-[420px] h-[860px] bg-[#121212] rounded-[52px] p-3 shadow-2xl bo
  rder-4 border-neutral-700 relative overflow-hidden flex flex-col">
          {/* Dynamic Island Notch */}
          <div className="absolute top-4 left-1/2 -translate-x-1/2 w-28 h-5 bg-black rounded-full z-
  50 flex items-center justify-center">
            <div className="w-2.5 h-2.5 bg-neutral-800 rounded-full mr-2" />
          </div>

          {/* Screen Content Container */}
          <div className="w-full h-full bg-[#121212] rounded-[44px] overflow-y-auto no-scrollbar rel
  ative pt-2">
            {mainContent}
          </div>
        </div>
      </div>
    );
  }

  return mainContent;
}
```

```
import React, { useState } from 'react';
import {
  Heart,
  MapPin,
  ShieldCheck,
  MessageCircle,
  ArrowUpRight,
  Wifi,
  Droplet,
  Clock,
  CheckCircle2,
  Share2
} from 'lucide-react';
import { Listing } from '../types';

interface ListingCardProps {
  listing: Listing;
  isSaved: boolean;
  onToggleSave: (id: string, e: React.MouseEvent) => void;
  onOpenDetail: (listing: Listing) => void;
  onOpenMpesaGuide: (listing: Listing, e: React.MouseEvent) => void;
  onShare?: (listing: Listing, e: React.MouseEvent) => void;
}

export const ListingCard: React.FC<ListingCardProps> = ({
  listing,
  isSaved,
  onToggleSave,
  onOpenDetail,
  onOpenMpesaGuide,
  onShare,
}) => {
  const [imgError, setImgError] = useState(false);

  const formatPrice = (price: number) => {
    return new Intl.NumberFormat('en-KE').format(price);
  };

  const getWhatsAppLink = (e: React.MouseEvent) => {
    e.stopPropagation();
    const cleanNumber = listing.seller.whatsapp.replace(/[^0-9]/g, '');
    const message = encodeURIComponent(
      `Habari ${listing.seller.name}! I saw your listing "${listing.title}" (KES ${formatPrice(listi
  ng.price)}) on STUDSPOT. Is it still available for meetup at ${listing.campusName}?`
    );
    window.open(`https://wa.me/${cleanNumber}?text=${message}`, '_blank', 'noopener,noreferrer');
  };

  const getCampusCategoryInfo = (uniId: string) => {
    if (uniId.startsWith('kmtc')) {
      return { label: 'KMTC', color: 'bg-emerald-500/15 text-emerald-400 border-emerald-500/30' };
    }
    if (uniId.includes('poly')) {
      return { label: 'POLY', color: 'bg-cyan-500/15 text-cyan-400 border-cyan-500/30' };
    }
    if (['ntti', 'kinyanjui_tech', 'rvtti', 'kist', 'thika_tvet', 'riat', 'kaiboi_tvet'].includes(un
  iId)) {
      return { label: 'TVET', color: 'bg-purple-500/15 text-purple-400 border-purple-500/30' };
    }
    return { label: 'UNI', color: 'bg-[#F3B71B]/15 text-[#F3B71B] border-[#F3B71B]/30' };
  };

  const campusCat = getCampusCategoryInfo(listing.universityId);

  return (
    <div
      onClick={() => onOpenDetail(listing)}
      className={`group bg-[#1E1E1E] rounded-2xl border transition-all duration-200 overflow-hidden
  flex flex-col cursor-pointer shadow-[0_4px_16px_rgba(0,0,0,0.3)] ${
        listing.isSold
```

```
        ? 'border-neutral-800/80 opacity-75 grayscale contrast-90 hover:grayscale-[30%] hover:opac
ity-95'
        : 'border-neutral-800 hover:border-[#F3B71B]/50 hover:shadow-[0_8px_24px_rgba(243,183,27,0
.1)]'
    }`}
  >
    {/* Image container */}
    <div className="relative aspect-[4/3] bg-neutral-900 overflow-hidden">
      {!imgError ? (
        <img
          src={listing.image}
          alt={listing.title}
          onError={() => setImgError(true)}
          referrerPolicy="no-referrer"
          className={`w-full h-full object-cover transition-transform duration-300 ${
            listing.isSold ? 'blur-[0.5px]' : 'group-hover:scale-[1.03]'
          }`}
        />
      ) : (
        <div className="w-full h-full flex flex-col items-center justify-center p-4 bg-[#252525] t
ext-neutral-400">
          <span className="text-2xl mb-1">
            {listing.type === 'item' && '  '}
            {listing.type === 'hostel' && '  '}
            {listing.type === 'gig' && '  '}
            {listing.type === 'business' && '  '}
          </span>
          <span className="text-xs font-semibold text-neutral-300 text-center line-clamp-1">{listi
ng.title}</span>
        </div>
      )}

      {/* Sold Overlay Banner */}
      {listing.isSold && (
        <div className="absolute inset-0 bg-neutral-950/65 backdrop-blur-[1px] z-10 flex flex-col
items-center justify-center p-3 pointer-events-none">
          <div className="bg-rose-950/90 border border-rose-500/80 text-rose-100 font-black text-x
s uppercase tracking-widest px-3 py-1.5 rounded-xl shadow-xl flex items-center gap-1.5 backdrop-bl
ur-md">
            <span className="w-2 h-2 rounded-full bg-rose-500 animate-pulse" />
            <span>SOLD</span>
          </div>
          <span className="text-[10px] text-neutral-300 font-medium mt-1 drop-shadow">
            Archived in History
          </span>
        </div>
      )}

      {/* Action buttons: Share & Favorite */}
      <div className="absolute top-2.5 right-2.5 flex items-center gap-1.5 z-10">
        <button
          type="button"
          onClick={(e) => {
            e.stopPropagation();
            onShare?.(listing, e);
          }}
          className="w-8 h-8 rounded-full bg-black/60 hover:bg-black/85 backdrop-blur-sm shadow-sm
 flex items-center justify-center text-neutral-300 hover:text-[#F3B71B] active:scale-90 transition
-all"
          aria-label="Share listing"
          title="Share with comrades"
        >
          <Share2 className="w-3.5 h-3.5" />
        </button>
        <button
          type="button"
          onClick={(e) => onToggleSave(listing.id, e)}
          className="w-8 h-8 rounded-full bg-black/60 hover:bg-black/85 backdrop-blur-sm shadow-sm
 flex items-center justify-center text-neutral-300 hover:text-rose-500 active:scale-90 transition-
all"
```

```
          aria-label={isSaved ? 'Remove from saved' : 'Save listing'}
        >
          <Heart className={`w-4 h-4 transition-colors ${isSaved ? 'fill-rose-500 text-rose-500' :
 'text-neutral-300'}`} />
        </button>
      </div>

      {/* Type indicator text */}
      <div className="absolute bottom-2.5 left-2.5 flex items-center gap-1.5">
        <span className="bg-black/85 backdrop-blur-sm text-white px-2 py-0.5 rounded-md text-[10px
] font-bold tracking-wide border border-neutral-800">
          {listing.type === 'item' && 'MARKETPLACE'}
          {listing.type === 'hostel' && 'HOUSING'}
          {listing.type === 'gig' && 'JOB / GIG'}
          {listing.type === 'business' && 'LOCAL SERVICE'}
        </span>
        <span className={`backdrop-blur-sm px-1.5 py-0.5 rounded-md text-[9px] font-bold tracking-
wide border font-mono ${campusCat.color}`}>
          {campusCat.label}
        </span>
      </div>
    </div>

    {/* Content */}
    <div className="p-3.5 flex-1 flex flex-col justify-between">
      <div>
        {/* Metadata row with zero-pill rule */}
        <div className="flex items-center gap-1.5 text-xs text-neutral-400 mb-1.5">
          <span className="font-semibold text-neutral-300 truncate max-w-[120px]">{listing.categor
y}</span>
          <span aria-hidden="true" className="text-neutral-600"> </span>
          <span className="truncate">{listing.campusName}</span>
        </div>

        {/* Title */}
        <h3 className="text-sm font-bold text-white line-clamp-2 leading-snug group-hover:text-[#F
3B71B] transition-colors">
          {listing.title}
        </h3>

        {/* Quick domain metadata */}
        {listing.type === 'hostel' && (
          <div className="mt-2 text-[11px] text-neutral-300 flex flex-wrap items-center gap-2">
            <span className="flex items-center gap-1">
              <Droplet className="w-3 h-3 text-cyan-400" />
              {listing.details.waterStatus || 'Water 24/7'}
            </span>
            <span aria-hidden="true" className="text-neutral-600"> </span>
            <span className="flex items-center gap-1">
              <Wifi className="w-3 h-3 text-emerald-400" />
              Wi-Fi
            </span>
          </div>
        )}

        {listing.type === 'gig' && (
          <div className="mt-2 text-[11px] text-neutral-300 flex items-center gap-1.5">
            <Clock className="w-3 h-3 text-[#F3B71B]" />
            <span>{listing.details.gigDuration || 'Flexible'}</span>
            <span aria-hidden="true" className="text-neutral-600"> </span>
            <span className="text-[#F3B71B] font-medium">{listing.details.compensationType || 'Per
 Task'}</span>
          </div>
        )}

        {listing.type === 'item' && listing.details.condition && (
          <div className="mt-2 text-[11px] text-neutral-400 flex items-center gap-1">
            <span>Condition:</span>
            <span className="font-medium text-neutral-200">{listing.details.condition}</span>
          </div>
```

```
        )}

        {listing.type === 'business' && listing.details.deliveryAvailable && (
          <div className="mt-2 text-[11px] text-emerald-400 flex items-center gap-1 font-medium">
            <CheckCircle2 className="w-3 h-3 text-emerald-400" />
            <span>Hostel Doorstep Delivery</span>
          </div>
        )}
      </div>

      {/* Bottom row: Price & Quick Action buttons */}
      <div className="mt-3 pt-3 border-t border-neutral-800 flex items-center justify-between gap-
2">
        <div>
          <div className="text-[10px] text-neutral-400 font-medium">
            {listing.isSold ? 'Sold Price (KES)' : 'Price (KES)'}
          </div>
          <div className="flex items-baseline gap-1.5">
            <span className={`text-base font-black font-mono tracking-tight ${
              listing.isSold ? 'text-neutral-400 line-through' : 'text-[#F3B71B]'
            }`}>
              KES {formatPrice(listing.price)}
            </span>
            {listing.isSold ? (
              <span className="text-[10px] font-bold text-rose-400 bg-rose-500/15 border border-ro
se-500/30 px-1.5 py-0.2 rounded font-mono">
                SOLD
              </span>
            ) : (
              listing.priceLabel && (
                <span className="text-[11px] text-neutral-400 font-medium">{listing.priceLabel}</s
pan>
              )
            )}
          </div>
        </div>

        <div className="flex items-center gap-1.5">
          <button
            type="button"
            onClick={getWhatsAppLink}
            className="min-h-[36px] min-w-[36px] px-2.5 py-1.5 rounded-xl bg-emerald-950/80 text-e
merald-400 border border-emerald-600/30 hover:bg-[#008938] hover:text-white transition-colors flex
 items-center gap-1 text-xs font-semibold"
            title="Chat with seller on WhatsApp"
          >
            <MessageCircle className="w-3.5 h-3.5" />
            <span className="hidden sm:inline">WhatsApp</span>
          </button>

          <button
            type="button"
            onClick={() => onOpenDetail(listing)}
            className="min-h-[36px] min-w-[36px] p-2 rounded-xl bg-neutral-800 text-neutral-200 ho
ver:bg-[#F3B71B] hover:text-black transition-colors flex items-center justify-center"
            title="View full details"
          >
            <ArrowUpRight className="w-3.5 h-3.5" />
          </button>
        </div>
      </div>

      {/* Seller Info micro-strip */}
      <div className="mt-2 flex items-center justify-between text-[11px] text-neutral-400">
        <div className="flex items-center gap-1 truncate">
          {listing.seller.isVerifiedStudent ? (
            <ShieldCheck className="w-3.5 h-3.5 text-emerald-400 shrink-0" />
          ) : (
            <span className="w-1.5 h-1.5 bg-neutral-600 rounded-full shrink-0" />
          )}
```

```
            <span className="truncate font-medium text-neutral-300">{listing.seller.name}</span>
          </div>
          <span className="text-neutral-500 text-[10px] shrink-0 font-mono">
            {listing.seller.trustScore}% trust
          </span>
        </div>
      </div>
    </div>
  );
};
```

```
import React, { useState } from 'react';
import {
  X,
  Heart,
  MapPin,
  ShieldCheck,
  MessageCircle,
  Phone,
  Share2,
  ShieldAlert,
  CreditCard,
  CheckCircle,
  Droplet,
  Wifi,
  Zap,
  Building2,
  Clock,
  Check,
  Copy,
  Send,
  Scale,
  CheckCircle2,
  RotateCcw,
  Tag,
  History
} from 'lucide-react';
import { Listing } from '../types';

interface ListingDetailModalProps {
  listing: Listing | null;
  onClose: () => void;
  isSaved: boolean;
  onToggleSave: (id: string, e: React.MouseEvent) => void;
  onOpenMpesaModal: (listing: Listing) => void;
  onOpenInAppChat: (listing: Listing) => void;
  onOpenTerms: () => void;
  onOpenShareModal?: (listing: Listing) => void;
  onToggleSold?: (listingId: string) => void;
  onOpenTransactionHistory?: () => void;
}

export const ListingDetailModal: React.FC<ListingDetailModalProps> = ({
  listing,
  onClose,
  isSaved,
  onToggleSave,
  onOpenMpesaModal,
  onOpenInAppChat,
  onOpenTerms,
  onOpenShareModal,
  onToggleSold,
  onOpenTransactionHistory,
}) => {
  const [copiedLink, setCopiedLink] = useState(false);
  const [copiedTill, setCopiedTill] = useState(false);
  const [imgError, setImgError] = useState(false);

  if (!listing) return null;

  const formatPrice = (price: number) => {
    return new Intl.NumberFormat('en-KE').format(price);
  };

  const handleShare = () => {
    if (onOpenShareModal) {
      onOpenShareModal(listing);
    } else {
      navigator.clipboard?.writeText(window.location.href);
      setCopiedLink(true);
      setTimeout(() => setCopiedLink(false), 2000);
```

```
  }
};

const handleCopyTill = (text: string) => {
  navigator.clipboard?.writeText(text);
  setCopiedTill(true);
  setTimeout(() => setCopiedTill(false), 2000);
};

const openWhatsApp = () => {
  const cleanNumber = listing.seller.whatsapp.replace(/[^0-9]/g, '');
  const message = encodeURIComponent(
    `Habari ${listing.seller.name}! I saw your listing "${listing.title}" (KES ${formatPrice(listi
ng.price)}) on STUDSPOT. Is it available for meetup at ${listing.campusName}?`
  );
  window.open(`https://wa.me/${cleanNumber}?text=${message}`, '_blank', 'noopener,noreferrer');
};

const callSeller = () => {
  window.location.href = `tel:${listing.seller.phone}`;
};

return (
  <div className="fixed inset-0 z-50 flex items-center justify-center p-0 sm:p-4 bg-black/85 backd
rop-blur-md animate-in fade-in duration-150 overflow-y-auto">
    <div
      className="w-full sm:max-w-2xl bg-[#1A1A1A] text-slate-100 sm:rounded-3xl shadow-2xl border
border-neutral-800 overflow-hidden flex flex-col max-h-[96vh] my-auto animate-in zoom-in-95 durati
on-150"
      onClick={(e) => e.stopPropagation()}
    >
      {/* Modal Top Header with Close and Share */}
      <div className="sticky top-0 z-20 bg-[#141414]/95 backdrop-blur-md px-4 py-3 border-b border
-neutral-800 flex items-center justify-between">
        <div className="flex items-center gap-2">
          <span className="text-xs font-bold uppercase tracking-wider text-[#F3B71B]">
            {listing.type === 'item' && 'Marketplace Listing'}
            {listing.type === 'hostel' && 'Student Housing & Hostels'}
            {listing.type === 'gig' && 'Jobs & Campus Gigs'}
            {listing.type === 'business' && 'Local Campus Service'}
          </span>
          {listing.isSold ? (
            <span className="text-[10px] bg-rose-500/15 text-rose-400 border border-rose-500/30 px
-2 py-0.5 rounded font-mono font-bold flex items-center gap-1">
              <span className="w-1.5 h-1.5 rounded-full bg-rose-500" />
              Marked as Sold
            </span>
          ) : listing.isApproved ? (
            <span className="text-[10px] bg-emerald-500/10 text-emerald-400 border border-emerald-
500/20 px-2 py-0.2 rounded font-mono font-bold">
               Admin Approved
            </span>
          ) : (
            <span className="text-[10px] bg-amber-500/10 text-amber-300 border border-amber-500/20
 px-2 py-0.2 rounded font-mono font-bold">
              Pending Approval
            </span>
          )}
        </div>

        <div className="flex items-center gap-1.5">
          <button
            type="button"
            onClick={handleShare}
            className="p-2 rounded-xl text-neutral-300 hover:bg-neutral-800 transition-colors flex
 items-center gap-1 text-xs font-medium"
            title="Share listing link"
          >
            {copiedLink ? <Check className="w-4 h-4 text-[#F3B71B]" /> : <Share2 className="w-4 h-
4" />}
```

```
            <span className="hidden sm:inline">{copiedLink ? 'Copied' : 'Share'}</span>
          </button>

          <button
            type="button"
            onClick={(e) => onToggleSave(listing.id, e)}
            className="p-2 rounded-xl text-neutral-300 hover:bg-neutral-800 transition-colors"
            aria-label="Save listing"
          >
            <Heart className={`w-4 h-4 ${isSaved ? 'fill-rose-500 text-rose-500' : 'text-neutral-3
00'}`} />
          </button>

          <button
            type="button"
            onClick={onClose}
            className="p-2 rounded-xl text-neutral-400 hover:text-white hover:bg-neutral-800 trans
ition-colors"
            aria-label="Close modal"
          >
            <X className="w-5 h-5" />
          </button>
        </div>
      </div>

      {/* Scrollable Modal Body */}
      <div className="overflow-y-auto flex-1 p-4 sm:p-6 space-y-5">
        {/* Sold Archival Notice Banner if item is marked as Sold */}
        {listing.isSold && (
          <div className="bg-rose-950/40 border border-rose-500/40 rounded-2xl p-3.5 flex items-st
art justify-between gap-3 animate-in fade-in">
            <div className="flex items-start gap-2.5">
              <CheckCircle2 className="w-5 h-5 text-rose-400 shrink-0 mt-0.5" />
              <div>
                <div className="text-xs font-bold text-rose-200">
                  This Listing Has Been Marked as SOLD
                </div>
                <p className="text-[11px] text-neutral-300 mt-0.5 leading-relaxed">
                  Deal concluded. This item is blurred/grayed out in the public campus feed but pr
eserved as part of the user's transaction history.
                  {listing.soldAt && <span className="font-mono text-rose-300"> ({listing.soldAt})
</span>}
                </p>
              </div>
            </div>
            {onOpenTransactionHistory && (
              <button
                type="button"
                onClick={() => {
                  onClose();
                  onOpenTransactionHistory();
                }}
                className="text-[11px] font-bold text-[#F3B71B] hover:text-[#ffd666] underline whi
tespace-nowrap shrink-0 flex items-center gap-1"
              >
                <History className="w-3.5 h-3.5" />
                <span>View History  </span>
              </button>
            )}
          </div>
        )}

        {/* Main Visual */}
        <div className="relative rounded-2xl overflow-hidden aspect-video bg-neutral-900 border bo
rder-neutral-800">
          {!imgError ? (
            <img
              src={listing.image}
              alt={listing.title}
              onError={() => setImgError(true)}
```

```
              referrerPolicy="no-referrer"
              className={`w-full h-full object-cover ${listing.isSold ? 'grayscale contrast-90 blu
r-[0.5px]' : ''}`}
            />
          ) : (
            <div className="w-full h-full flex flex-col items-center justify-center p-6 bg-[#24242
4] text-neutral-400">
              <span className="text-4xl mb-2">  </span>
              <span className="text-sm font-semibold text-white">{listing.title}</span>
            </div>
          )}

          {listing.isSold && (
            <div className="absolute inset-0 bg-neutral-950/50 backdrop-blur-[1px] flex items-cent
er justify-center pointer-events-none">
              <span className="bg-rose-950/90 border border-rose-500/80 text-rose-100 font-black t
ext-xs uppercase tracking-widest px-4 py-2 rounded-xl shadow-2xl flex items-center gap-1.5 backdro
p-blur-md">
                <span className="w-2 h-2 rounded-full bg-rose-500 animate-pulse" />
                <span>SOLD   ARCHIVED</span>
              </span>
            </div>
          )}

          <div className="absolute bottom-3 left-3 bg-black/80 backdrop-blur-md text-white text-xs
 font-semibold px-3 py-1 rounded-lg flex items-center gap-1.5 border border-neutral-700">
            <MapPin className="w-3.5 h-3.5 text-[#F3B71B]" />
            <span>{listing.campusName}</span>
          </div>
        </div>

        {/* Title & Price Header */}
        <div>
          <div className="flex items-center gap-2 text-xs text-neutral-400 mb-1.5">
            <span className="font-semibold text-[#F3B71B]">{listing.category}</span>
            <span aria-hidden="true" className="text-neutral-600"> </span>
            <span>Listed {listing.createdAt}</span>
            <span aria-hidden="true" className="text-neutral-600"> </span>
            <span>{listing.viewsCount} views</span>
          </div>

          <h1 className="text-xl sm:text-2xl font-black text-white leading-snug">
            {listing.title}
          </h1>

          <div className="mt-3 flex items-baseline gap-2 flex-wrap">
            <span className={`text-2xl sm:text-3xl font-black font-mono tracking-tight ${
              listing.isSold ? 'text-neutral-400 line-through' : 'text-[#F3B71B]'
            }`}>
              KES {formatPrice(listing.price)}
            </span>
            {listing.isSold ? (
              <span className="text-xs font-black text-rose-400 bg-rose-500/15 border border-rose-
500/30 px-2 py-0.5 rounded font-mono">
                SOLD
              </span>
            ) : (
              listing.priceLabel && (
                <span className="text-sm font-semibold text-neutral-400">{listing.priceLabel}</spa
n>
              )
            )}
            {listing.isNegotiable && !listing.isSold && (
              <span className="text-xs font-semibold text-neutral-300 bg-neutral-800 border border
-neutral-700 px-2 py-0.5 rounded-md ml-2">
                Negotiable
              </span>
            )}
          </div>
        </div>
```

```
        {/* Deal & Transaction Status Action Card */}
        <div className="bg-[#222222] rounded-2xl p-3.5 border border-neutral-700/80 flex flex-col
sm:flex-row sm:items-center justify-between gap-3">
          <div className="flex items-start gap-2.5 min-w-0">
            <Tag className="w-4 h-4 text-[#F3B71B] shrink-0 mt-0.5" />
            <div className="min-w-0">
              <div className="text-xs font-bold text-white flex items-center gap-2 flex-wrap">
                <span>Deal Status:</span>
                {listing.isSold ? (
                  <span className="text-rose-400 font-mono font-bold bg-rose-500/10 border border-
rose-500/20 px-1.5 py-0.2 rounded text-[11px]">
                    SOLD   Archived
                  </span>
                ) : (
                  <span className="text-emerald-400 font-mono font-bold bg-emerald-500/10 border b
order-emerald-500/20 px-1.5 py-0.2 rounded text-[11px]">
                    ACTIVE   Live in Feed
                  </span>
                )}
              </div>
              <p className="text-[11px] text-neutral-400 mt-0.5">
                {listing.isSold
                  ? 'Item is marked sold. It is grayed out in feeds and tracked in your transactio
n history.'
                  : 'Agreed a transaction with a fellow student? Mark as Sold to gray out in feed
and record history.'}
              </p>
            </div>
          </div>

          <div className="flex items-center gap-2 shrink-0 self-end sm:self-center">
            <button
              type="button"
              onClick={() => onToggleSold?.(listing.id)}
              className={`px-3 py-2 rounded-xl text-xs font-bold transition-all flex items-center
gap-1.5 shadow-sm active:scale-95 ${
                listing.isSold
                  ? 'bg-neutral-800 hover:bg-neutral-700 text-neutral-200 border border-neutral-60
0'
                  : 'bg-rose-600 hover:bg-rose-500 text-white border border-rose-500'
              }`}
            >
              {listing.isSold ? (
                <>
                  <RotateCcw className="w-3.5 h-3.5" />
                  <span>Relist (Mark Active)</span>
                </>
              ) : (
                <>
                  <CheckCircle2 className="w-3.5 h-3.5" />
                  <span>Mark as Sold</span>
                </>
              )}
            </button>

            {onOpenTransactionHistory && (
              <button
                type="button"
                onClick={() => {
                  onClose();
                  onOpenTransactionHistory();
                }}
                className="p-2 rounded-xl bg-neutral-800 hover:bg-neutral-700 text-neutral-300 hov
er:text-white border border-neutral-700"
                title="Open Transaction History"
              >
                <History className="w-4 h-4" />
              </button>
            )}
```

```
          </div>
        </div>

        {/* Description */}
        <div className="space-y-1.5">
          <h3 className="text-xs font-bold text-neutral-400 uppercase tracking-wider">About This L
isting</h3>
          <p className="text-sm text-neutral-300 leading-relaxed whitespace-pre-line">
            {listing.description}
          </p>
        </div>

        {/* Domain Specific Feature Panels */}
        {listing.type === 'hostel' && (
          <div className="bg-[#242424] rounded-2xl p-4 border border-neutral-800 space-y-3">
            <h3 className="text-xs font-bold text-white uppercase tracking-wider flex items-center
 gap-1.5">
              <Building2 className="w-4 h-4 text-[#F3B71B]" />
              <span>Hostel Specifications</span>
            </h3>
            <div className="grid grid-cols-2 gap-3 text-xs">
              <div className="p-2.5 bg-[#1A1A1A] rounded-xl border border-neutral-800">
                <div className="text-neutral-400 font-medium">Room Type</div>
                <div className="font-bold text-white mt-0.5">{listing.details.hostelType || 'Bedsi
tter'}</div>
              </div>
              <div className="p-2.5 bg-[#1A1A1A] rounded-xl border border-neutral-800">
                <div className="text-neutral-400 font-medium">Distance to Gate</div>
                <div className="font-bold text-white mt-0.5">{listing.details.distanceToGate || '5
 mins walk'}</div>
              </div>
              <div className="p-2.5 bg-[#1A1A1A] rounded-xl border border-neutral-800">
                <div className="text-neutral-400 font-medium flex items-center gap-1">
                  <Droplet className="w-3.5 h-3.5 text-cyan-400" /> Water Status
                </div>
                <div className="font-bold text-white mt-0.5">{listing.details.waterStatus || 'Bore
hole 24/7'}</div>
              </div>
              <div className="p-2.5 bg-[#1A1A1A] rounded-xl border border-neutral-800">
                <div className="text-neutral-400 font-medium flex items-center gap-1">
                  <Zap className="w-3.5 h-3.5 text-amber-400" /> Electricity
                </div>
                <div className="font-bold text-white mt-0.5">{listing.details.electricityType || '
Prepaid Token'}</div>
              </div>
            </div>

            {listing.details.roomFeatures && listing.details.roomFeatures.length > 0 && (
              <div>
                <div className="text-[11px] font-semibold text-neutral-400 mb-1.5">Amenities Inclu
ded</div>
                <div className="flex flex-wrap gap-1.5">
                  {listing.details.roomFeatures.map((feat, i) => (
                    <span key={i} className="text-xs bg-[#1A1A1A] border border-neutral-700 px-2.5
 py-1 rounded-lg text-neutral-300 flex items-center gap-1">
                      <CheckCircle className="w-3 h-3 text-[#F3B71B]" />
                      {feat}
                    </span>
                  ))}
                </div>
              </div>
            )}
          </div>
        )}

        {listing.type === 'gig' && (
          <div className="bg-[#242424] rounded-2xl p-4 border border-neutral-800 space-y-3">
            <h3 className="text-xs font-bold text-white uppercase tracking-wider flex items-center
 gap-1.5">
              <Clock className="w-4 h-4 text-[#F3B71B]" />
```

```
              <span>Gig Requirements & Duration</span>
            </h3>
            <div className="flex items-center justify-between text-xs p-3 bg-[#1A1A1A] rounded-xl
border border-neutral-800">
              <div>
                <span className="text-neutral-400">Duration: </span>
                <span className="font-bold text-white">{listing.details.gigDuration}</span>
              </div>
              <div>
                <span className="text-neutral-400">Compensation: </span>
                <span className="font-bold text-[#F3B71B]">{listing.details.compensationType}</spa
n>
              </div>
            </div>

            {listing.details.skillsNeeded && (
              <div>
                <div className="text-[11px] font-semibold text-neutral-400 mb-1.5">Skills Needed</
div>
                <div className="flex flex-wrap gap-1.5">
                  {listing.details.skillsNeeded.map((skill, i) => (
                    <span key={i} className="text-xs bg-[#1A1A1A] border border-neutral-700 px-2.5
 py-1 rounded-lg text-neutral-300 font-medium">
                      {skill}
                    </span>
                  ))}
                </div>
              </div>
            )}
          </div>
        )}

        {listing.type === 'business' && (
          <div className="bg-[#242424] rounded-2xl p-4 border border-neutral-800 space-y-2.5">
            <h3 className="text-xs font-bold text-white uppercase tracking-wider">Business Operati
ng Hours & Delivery</h3>
            <div className="text-xs text-neutral-300 space-y-1">
              <div><span className="text-neutral-400">Hours:</span> <span className="font-semibold
 text-white">{listing.details.openingHours}</span></div>
              {listing.details.deliveryNote && (
                <div><span className="text-neutral-400">Delivery:</span> <span className="font-sem
ibold text-[#F3B71B]">{listing.details.deliveryNote}</span></div>
              )}
            </div>
          </div>
        )}

        {/* Comrade Seller Card */}
        <div className="bg-[#242424] rounded-2xl p-4 border border-neutral-800">
          <div className="flex items-start justify-between gap-3">
            <div className="flex items-center gap-3">
              <div className="w-12 h-12 rounded-2xl bg-[#F3B71B] text-black font-extrabold text-lg
 flex items-center justify-center shrink-0 shadow-sm">
                {listing.seller.name.charAt(0)}
              </div>
              <div>
                <div className="flex items-center gap-1.5">
                  <span className="font-bold text-white text-sm">{listing.seller.name}</span>
                  {listing.seller.isVerifiedStudent && (
                    <span className="text-[11px] text-emerald-400 bg-emerald-500/10 border border-
emerald-500/20 font-bold px-1.5 py-0.2 rounded-md flex items-center gap-0.5">
                      <ShieldCheck className="w-3 h-3 text-emerald-400" />
                      Verified
                    </span>
                  )}
                </div>
                <p className="text-xs text-neutral-400 mt-0.5">
                  {listing.seller.courseOrBiz} {listing.seller.yearOfStudy ? `  ${listing.seller.y
earOfStudy}` : ''}
                </p>
```

```
              </div>
            </div>

            <div className="text-right shrink-0">
              <div className="text-xs font-mono font-bold text-[#F3B71B]">{listing.seller.trustSco
re}% Trust</div>
              <div className="text-[10px] text-neutral-400">{listing.seller.reviewsCount} reviews<
/div>
            </div>
          </div>

          {/* Recommended Safe Campus Meetup Spot */}
          <div className="mt-3.5 pt-3 border-t border-neutral-700 flex items-start gap-2 text-xs t
ext-neutral-300">
            <MapPin className="w-4 h-4 text-[#F3B71B] shrink-0 mt-0.5" />
            <div>
              <span className="font-semibold text-white">Recommended Campus Safe Spot: </span>
              <span>{listing.seller.safeSpot}</span>
              <p className="text-[11px] text-neutral-400 mt-0.5">
                Always inspect item in daylight at public campus spots before paying.
              </p>
            </div>
          </div>

          {/* M-Pesa / Till display if available */}
          {(listing.seller.tillNumber || listing.seller.mpesaNumber) && (
            <div className="mt-2.5 p-2 bg-[#1A1A1A] rounded-xl border border-neutral-700 flex item
s-center justify-between text-xs">
              <div className="flex items-center gap-1.5 text-neutral-200 font-mono font-medium">
                <CreditCard className="w-3.5 h-3.5 text-[#F3B71B] shrink-0" />
                <span>{listing.seller.tillNumber || `M-Pesa: ${listing.seller.mpesaNumber}`}</span
>
              </div>
              <button
                type="button"
                onClick={() => handleCopyTill(listing.seller.tillNumber || listing.seller.mpesaNum
ber || '')}
                className="text-[11px] font-bold text-[#F3B71B] hover:text-white flex items-center
 gap-1 px-2 py-0.5 rounded-md hover:bg-neutral-800"
              >
                {copiedTill ? <Check className="w-3 h-3" /> : <Copy className="w-3 h-3" />}
                <span>{copiedTill ? 'Copied' : 'Copy'}</span>
              </button>
            </div>
          )}
        </div>

        {/* Directory Intermediary Legal Disclaimer Banner */}
        <div className="bg-[#242424] rounded-2xl p-3.5 border border-neutral-700 flex items-start
gap-2.5 text-xs text-neutral-300">
          <Scale className="w-4 h-4 text-[#F3B71B] shrink-0 mt-0.5" />
          <div className="space-y-1">
            <span className="font-bold text-white">STUDSPOT Directory Disclaimer:</span>
            <p className="text-[11px] text-neutral-400 leading-normal">
              STUDSPOT acts solely as an advertising venue & directory and is not a party to user
transactions, leases, or job contracts. We assume no liability for defective goods or disputes.
            </p>
            <button
              type="button"
              onClick={onOpenTerms}
              className="text-[#F3B71B] font-bold underline text-[11px] block mt-0.5"
            >
              Read Terms & Conditions & Liability Waiver
            </button>
          </div>
        </div>
      </div>

      {/* Modal Bottom Actions Bar */}
      <div className="sticky bottom-0 z-20 bg-[#141414] border-t border-neutral-800 p-3 sm:p-4 fle
```

```
  x items-center gap-2">
          {/* WhatsApp Direct Connect */}
          <button
            type="button"
            onClick={openWhatsApp}
            className="flex-1 min-h-[46px] rounded-xl bg-[#008938] hover:bg-emerald-600 text-white f
  ont-bold text-xs sm:text-sm flex items-center justify-center gap-2 shadow-sm active:scale-[0.98] t
  ransition-all"
          >
            <MessageCircle className="w-4 h-4" />
            <span>Chat on WhatsApp</span>
          </button>

          {/* In-App Message */}
          <button
            type="button"
            onClick={() => onOpenInAppChat(listing)}
            className="min-h-[46px] px-3.5 rounded-xl bg-[#242424] hover:bg-neutral-700 text-white f
  ont-bold text-xs flex items-center justify-center gap-1.5 transition-colors"
            title="Send in-app message"
          >
            <Send className="w-4 h-4 text-[#F3B71B]" />
            <span className="hidden sm:inline">In-App Chat</span>
          </button>

          {/* Call direct */}
          <button
            type="button"
            onClick={callSeller}
            className="min-h-[46px] px-3.5 rounded-xl border border-neutral-700 bg-[#1A1A1A] hover:b
  g-neutral-800 text-neutral-200 font-bold text-xs flex items-center justify-center gap-1.5 transiti
  on-colors"
            title="Call seller"
          >
            <Phone className="w-4 h-4 text-neutral-400" />
            <span className="hidden sm:inline">Call</span>
          </button>
        </div>
      </div>
    </div>
  );
};
```

```
import React, { useState, useMemo } from 'react';
import {
  X,
  History,
  CheckCircle2,
  RotateCcw,
  ShoppingBag,
  ArrowUpRight,
  Receipt,
  Tag,
  ShieldCheck,
  CreditCard,
  PlusCircle,
  ExternalLink,
  Clock
} from 'lucide-react';
import { Listing, User } from '../types';

interface TransactionHistoryModalProps {
  isOpen: boolean;
  onClose: () => void;
  listings: Listing[];
  currentUser: User | null;
  onToggleSold: (listingId: string) => void;
  onOpenDetail: (listing: Listing) => void;
  onOpenPostModal: () => void;
}

type HistoryTab = 'all' | 'sold' | 'active' | 'mpesa';

export const TransactionHistoryModal: React.FC<TransactionHistoryModalProps> = ({
  isOpen,
  onClose,
  listings,
  currentUser,
  onToggleSold,
  onOpenDetail,
  onOpenPostModal,
}) => {
  const [activeTab, setActiveTab] = useState<HistoryTab>('all');

  const formatPrice = (price: number) => {
    return new Intl.NumberFormat('en-KE').format(price);
  };

  const userListings = useMemo(() => {
    return listings;
  }, [listings]);

  const soldListings = useMemo(() => {
    return userListings.filter(item => !!item.isSold);
  }, [userListings]);

  const activeListings = useMemo(() => {
    return userListings.filter(item => !item.isSold);
  }, [userListings]);

  const mpesaReceipts = useMemo(() => {
    return userListings.filter(item => item.isFeePaid || item.mpesaRef);
  }, [userListings]);

  const totalSoldValue = useMemo(() => {
    return soldListings.reduce((sum, item) => sum + item.price, 0);
  }, [soldListings]);

  const displayedListings = useMemo(() => {
    if (activeTab === 'sold') return soldListings;
    if (activeTab === 'active') return activeListings;
    return userListings;
  }, [activeTab, userListings, soldListings, activeListings]);
```

```
if (!isOpen) return null;

return (
  <div className="fixed inset-0 z-50 flex items-center justify-center p-3 sm:p-5 bg-black/85 backd
rop-blur-md animate-in fade-in duration-150 overflow-y-auto">
    <div
      className="w-full max-w-3xl bg-[#1A1A1A] text-slate-100 rounded-3xl shadow-2xl border border
-neutral-800 overflow-hidden flex flex-col max-h-[94vh] my-auto animate-in zoom-in-95 duration-150
"
      onClick={(e) => e.stopPropagation()}
    >
      {/* Header */}
      <div className="p-4 sm:p-5 border-b border-neutral-800 bg-[#141414] flex items-center justif
y-between">
        <div className="flex items-center gap-3">
          <div className="w-10 h-10 rounded-2xl bg-[#F3B71B]/15 border border-[#F3B71B]/30 flex it
ems-center justify-center text-[#F3B71B]">
            <History className="w-5 h-5" />
          </div>
          <div>
            <div className="flex items-center gap-2">
              <h2 className="text-base sm:text-lg font-bold text-white font-heading">
                Transaction History & Activity
              </h2>
              <span className="text-[10px] bg-neutral-800 text-neutral-300 border border-neutral-7
00 px-2 py-0.5 rounded-full font-mono">
                {currentUser?.fullName || 'Brian Mwangi'}
              </span>
            </div>
            <p className="text-xs text-neutral-400">
              Track campus deals, completed sales, grayed-out items & M-Pesa receipts
            </p>
          </div>
        </div>

        <button
          type="button"
          onClick={onClose}
          className="p-2 rounded-xl text-neutral-400 hover:text-white hover:bg-neutral-800 transit
ion-colors"
          aria-label="Close modal"
        >
          <X className="w-5 h-5" />
        </button>
      </div>

      {/* Top Summary Metrics Strip */}
      <div className="p-4 bg-[#141414]/60 border-b border-neutral-800/80 grid grid-cols-2 sm:grid-
cols-4 gap-3">
        <div className="bg-[#202020] p-3 rounded-2xl border border-neutral-800">
          <div className="text-[10px] text-neutral-400 uppercase tracking-wider font-semibold">
            Sold Deals
          </div>
          <div className="text-lg font-black text-rose-400 font-mono mt-0.5">
            {soldListings.length}
          </div>
          <div className="text-[10px] text-neutral-500 truncate mt-0.5">
            Archived in feed
          </div>
        </div>

        <div className="bg-[#202020] p-3 rounded-2xl border border-neutral-800">
          <div className="text-[10px] text-neutral-400 uppercase tracking-wider font-semibold">
            Closed Value
          </div>
          <div className="text-lg font-black text-[#F3B71B] font-mono mt-0.5 truncate">
            KES {formatPrice(totalSoldValue)}
          </div>
          <div className="text-[10px] text-neutral-500 truncate mt-0.5">
```

```
            Total volume sold
          </div>
        </div>

        <div className="bg-[#202020] p-3 rounded-2xl border border-neutral-800">
          <div className="text-[10px] text-neutral-400 uppercase tracking-wider font-semibold">
            Active Listings
          </div>
          <div className="text-lg font-black text-emerald-400 font-mono mt-0.5">
            {activeListings.length}
          </div>
          <div className="text-[10px] text-neutral-500 truncate mt-0.5">
            Live on campus
          </div>
        </div>

        <div className="bg-[#202020] p-3 rounded-2xl border border-neutral-800">
          <div className="text-[10px] text-neutral-400 uppercase tracking-wider font-semibold">
            M-Pesa Receipts
          </div>
          <div className="text-lg font-black text-cyan-400 font-mono mt-0.5">
            {mpesaReceipts.length}
          </div>
          <div className="text-[10px] text-neutral-500 truncate mt-0.5">
            KSh 80 fees verified
          </div>
        </div>
      </div>

      {/* Tab Filters */}
      <div className="px-4 pt-3 pb-2 border-b border-neutral-800 bg-[#171717] flex items-center ga
p-2 overflow-x-auto no-scrollbar">
        <button
          type="button"
          onClick={() => setActiveTab('all')}
          className={`px-3 py-1.5 rounded-xl text-xs font-bold transition-all whitespace-nowrap fl
ex items-center gap-1.5 ${
            activeTab === 'all'
              ? 'bg-[#F3B71B] text-black shadow-sm'
              : 'text-neutral-400 hover:text-white hover:bg-neutral-800'
          }`}
        >
          <span>All Listings</span>
          <span className="text-[10px] px-1.5 py-0.2 rounded-md font-mono bg-black/20">
            {userListings.length}
          </span>
        </button>

        <button
          type="button"
          onClick={() => setActiveTab('sold')}
          className={`px-3 py-1.5 rounded-xl text-xs font-bold transition-all whitespace-nowrap fl
ex items-center gap-1.5 ${
            activeTab === 'sold'
              ? 'bg-rose-500 text-white shadow-sm'
              : 'text-neutral-400 hover:text-white hover:bg-neutral-800'
          }`}
        >
          <span className="w-2 h-2 rounded-full bg-rose-400" />
          <span>Sold (Archived)</span>
          <span className="text-[10px] px-1.5 py-0.2 rounded-md font-mono bg-black/20">
            {soldListings.length}
          </span>
        </button>

        <button
          type="button"
          onClick={() => setActiveTab('active')}
          className={`px-3 py-1.5 rounded-xl text-xs font-bold transition-all whitespace-nowrap fl
ex items-center gap-1.5 ${
```

```
            activeTab === 'active'
              ? 'bg-emerald-500 text-white shadow-sm'
              : 'text-neutral-400 hover:text-white hover:bg-neutral-800'
          }`}
        >
          <span>Active Listings</span>
          <span className="text-[10px] px-1.5 py-0.2 rounded-md font-mono bg-black/20">
            {activeListings.length}
          </span>
        </button>

        <button
          type="button"
          onClick={() => setActiveTab('mpesa')}
          className={`px-3 py-1.5 rounded-xl text-xs font-bold transition-all whitespace-nowrap fl
ex items-center gap-1.5 ${
            activeTab === 'mpesa'
              ? 'bg-cyan-600 text-white shadow-sm'
              : 'text-neutral-400 hover:text-white hover:bg-neutral-800'
          }`}
        >
          <Receipt className="w-3.5 h-3.5" />
          <span>M-Pesa Receipts</span>
          <span className="text-[10px] px-1.5 py-0.2 rounded-md font-mono bg-black/20">
            {mpesaReceipts.length}
          </span>
        </button>
      </div>

      {/* Content Body */}
      <div className="overflow-y-auto flex-1 p-4 sm:p-5 space-y-3">
        {activeTab === 'mpesa' ? (
          /* M-Pesa Fee Records Table */
          <div className="space-y-2.5">
            {mpesaReceipts.length === 0 ? (
              <div className="text-center py-12 text-neutral-500 text-xs">
                <Receipt className="w-8 h-8 mx-auto mb-2 opacity-40" />
                <p>No M-Pesa fee receipts recorded yet.</p>
              </div>
            ) : (
              mpesaReceipts.map((item) => (
                <div
                  key={item.id}
                  className="p-3.5 bg-[#202020] rounded-2xl border border-neutral-800 flex flex-co
l sm:flex-row items-start sm:items-center justify-between gap-3 text-xs"
                >
                  <div className="flex items-center gap-3 min-w-0">
                    <div className="w-10 h-10 rounded-xl bg-emerald-950/60 border border-emerald-6
00/40 text-emerald-400 flex items-center justify-center shrink-0">
                      <CreditCard className="w-5 h-5" />
                    </div>
                    <div className="min-w-0">
                      <div className="flex items-center gap-2">
                        <span className="font-mono font-bold text-emerald-400">
                          {item.mpesaRef || 'QK-VERIFIED'}
                        </span>
                        <span className="text-[10px] bg-emerald-500/10 text-emerald-400 border bor
der-emerald-500/20 px-1.5 py-0.2 rounded font-mono">
                          Verified Safaricom
                        </span>
                      </div>
                      <div className="text-white font-medium truncate mt-0.5">
                        {item.title}
                      </div>
                      <div className="text-[11px] text-neutral-400 mt-0.5">
                        Campus: {item.campusName}   Fee: KES 80 Listing Tier
                      </div>
                    </div>
                  </div>
```

```
                <div className="flex items-center gap-2 self-end sm:self-center shrink-0">
                  <div className="text-right">
                    <div className="font-mono font-bold text-white">KES 80.00</div>
                    <div className="text-[10px] text-neutral-400 font-mono">Status: Paid</div>
                  </div>
                  <button
                    type="button"
                    onClick={() => {
                      onClose();
                      onOpenDetail(item);
                    }}
                    className="p-2 rounded-xl bg-neutral-800 text-neutral-300 hover:text-white h
over:bg-neutral-700"
                    title="View listing"
                  >
                    <ArrowUpRight className="w-4 h-4" />
                  </button>
                </div>
              </div>
            ))
          )}
        </div>
      ) : displayedListings.length === 0 ? (
        /* Empty state */
        <div className="text-center py-12 text-neutral-500 text-xs space-y-2">
          <ShoppingBag className="w-10 h-10 mx-auto text-neutral-600" />
          <p className="font-bold text-neutral-300 text-sm">No listings found in this category</
p>
          <p className="text-neutral-500 max-w-sm mx-auto">
            {activeTab === 'sold'
              ? 'No items marked as sold yet. When you conclude a transaction, click "Mark as So
ld" on any of your listings to gray it out on the feed and archive it here.'
              : 'Start by posting a textbook, hostel room, or student gig.'}
          </p>
          <div className="pt-2">
            <button
              type="button"
              onClick={() => {
                onClose();
                onOpenPostModal();
              }}
              className="px-4 py-2 bg-[#F3B71B] hover:bg-[#dca415] text-black font-bold rounded-
xl text-xs"
            >
              Post a New Listing
            </button>
          </div>
        </div>
      ) : (
        /* Listings List */
        displayedListings.map((item) => (
          <div
            key={item.id}
            className={`p-3 sm:p-4 rounded-2xl border transition-all flex flex-col sm:flex-row i
tems-start sm:items-center justify-between gap-3 ${
              item.isSold
                ? 'bg-[#1C1C1C] border-neutral-800/80 opacity-80'
                : 'bg-[#212121] border-neutral-800 hover:border-neutral-700'
            }`}
          >
            {/* Left side: Thumbnail + Details */}
            <div
              onClick={() => {
                onClose();
                onOpenDetail(item);
              }}
              className="flex items-center gap-3 flex-1 min-w-0 cursor-pointer"
            >
              <div className="relative w-16 h-16 rounded-xl overflow-hidden bg-neutral-900 shrin
k-0 border border-neutral-800">
```

```
                  <img
                    src={item.image}
                    alt={item.title}
                    referrerPolicy="no-referrer"
                    className={`w-full h-full object-cover ${item.isSold ? 'grayscale contrast-90
blur-[0.5px]' : ''}`}
                  />
                  {item.isSold && (
                    <div className="absolute inset-0 bg-black/60 flex items-center justify-center"
>
                      <span className="text-[9px] font-black text-rose-300 uppercase tracking-wide
st bg-rose-950/80 px-1 py-0.5 rounded border border-rose-500/50">
                        SOLD
                      </span>
                    </div>
                  )}
                </div>

                <div className="min-w-0">
                  <div className="flex items-center gap-2">
                    <span className="text-[10px] font-bold text-[#F3B71B] uppercase tracking-wider
">
                      {item.category}
                    </span>
                    <span className="text-neutral-600"> </span>
                    <span className="text-[11px] text-neutral-400 truncate">
                      {item.campusName}
                    </span>
                  </div>

                  <h4 className="text-xs sm:text-sm font-bold text-white truncate mt-0.5">
                    {item.title}
                  </h4>

                  <div className="flex items-center gap-2 mt-1">
                    <span className={`text-xs font-mono font-bold ${
                      item.isSold ? 'text-neutral-400 line-through' : 'text-[#F3B71B]'
                    }`}>
                      KES {formatPrice(item.price)} {item.priceLabel}
                    </span>

                    {item.isSold ? (
                      <span className="text-[10px] bg-rose-500/15 text-rose-400 border border-rose
-500/30 px-1.5 py-0.2 rounded font-mono font-bold flex items-center gap-1">
                        <CheckCircle2 className="w-2.5 h-2.5" />
                        Sold {item.soldAt ? `(${item.soldAt})` : ''}
                      </span>
                    ) : (
                      <span className="text-[10px] bg-emerald-500/15 text-emerald-400 border borde
r-emerald-500/20 px-1.5 py-0.2 rounded font-mono font-bold">
                        Active in Feed
                      </span>
                    )}
                  </div>
                </div>
              </div>

              {/* Right side: Action Controls */}
              <div className="flex items-center gap-2 self-end sm:self-center shrink-0 pt-2 sm:pt-
0 border-t sm:border-t-0 border-neutral-800 w-full sm:w-auto justify-between sm:justify-end">
                {/* Toggle Sold Button */}
                <button
                  type="button"
                  onClick={(e) => {
                    e.stopPropagation();
                    onToggleSold(item.id);
                  }}
                  className={`px-3 py-1.5 rounded-xl text-xs font-bold transition-all flex items-c
enter gap-1.5 shadow-sm active:scale-95 ${
                    item.isSold
```

```
                      ? 'bg-neutral-800 hover:bg-neutral-700 text-neutral-200 border border-neutra
  l-700'
                      : 'bg-rose-600 hover:bg-rose-500 text-white border border-rose-500'
                  }`}
                  title={item.isSold ? 'Mark this listing as active again' : 'Mark this listing as
   sold'}
                >
                  {item.isSold ? (
                    <>
                      <RotateCcw className="w-3.5 h-3.5" />
                      <span>Relist (Mark Active)</span>
                    </>
                  ) : (
                    <>
                      <CheckCircle2 className="w-3.5 h-3.5" />
                      <span>Mark as Sold</span>
                    </>
                  )}
                </button>

                {/* View Details */}
                <button
                  type="button"
                  onClick={() => {
                    onClose();
                    onOpenDetail(item);
                  }}
                  className="p-2 rounded-xl bg-neutral-800 hover:bg-neutral-700 text-neutral-300 h
  over:text-white transition-colors"
                  title="View full listing details"
                >
                  <ArrowUpRight className="w-4 h-4" />
                </button>
              </div>
            </div>
          ))
        )}
      </div>

      {/* Footer info note */}
      <div className="p-3.5 bg-[#141414] border-t border-neutral-800 flex items-center justify-bet
  ween text-[11px] text-neutral-400">
        <div className="flex items-center gap-1.5">
          <Tag className="w-3.5 h-3.5 text-[#F3B71B]" />
          <span>Marking items as 'Sold' blurs & grays them out in the public feed while preserving
   transaction records.</span>
        </div>
        <button
          type="button"
          onClick={onClose}
          className="px-3 py-1 rounded-lg bg-neutral-800 hover:bg-neutral-700 text-white font-medi
  um text-xs transition-colors shrink-0 ml-2"
        >
          Close
        </button>
      </div>
    </div>
  </div>
  );
};
```

```
import React, { useState } from 'react';
import {
  X,
  Upload,
  MapPin,
  Check,
  Sparkles,
  ShoppingBag,
  Home,
  Briefcase,
  Store,
  CreditCard,
  ShieldAlert,
  GraduationCap,
  PenTool
} from 'lucide-react';
import { Listing, ListingType, University, User, InstitutionType } from '../types';
import { UNIVERSITIES, SAFE_MEETUP_SPOTS } from '../data/seedData';
import { saveCustomCampus, getAllCampuses } from '../utils/campusStore';

interface PostListingModalProps {
  isOpen: boolean;
  onClose: () => void;
  onAddListing: (listing: Listing) => void;
  currentUser: User | null;
  onOpenTerms: () => void;
}

const STOCK_PHOTOS: Record<ListingType, { label: string; url: string }[]> = {
  item: [
    { label: 'Electronics & Laptops', url: '/src/assets/images/student_cyber_tech_1791796604735.jpg'
   },
    { label: 'Campus Thrift Drip', url: '/src/assets/images/campus_thrift_fashion_1791796594005.jpg'
   },
    { label: 'Textbooks & Books', url: '/src/assets/images/hero_campus_marketplace_1791796569675.jpg
  ' },
  ],
  hostel: [
    { label: 'Furnished Bedsitter', url: '/src/assets/images/hostel_student_room_1791796581832.jpg'
  },
    { label: 'Single Study Room', url: '/src/assets/images/hostel_student_room_1791796581832.jpg' },
  ],
  gig: [
    { label: 'Academic & Writing Work', url: '/src/assets/images/student_cyber_tech_1791796604735.jp
  g' },
    { label: 'Campus Promo & Brand', url: '/src/assets/images/hero_campus_marketplace_1791796569675.
  jpg' },
  ],
  business: [
    { label: 'Hostel Food & Delivery', url: '/src/assets/images/campus_thrift_fashion_1791796594005.
  jpg' },
    { label: 'Tech & Phone Repair', url: '/src/assets/images/student_cyber_tech_1791796604735.jpg' }
  ,
  ]
};

export const PostListingModal: React.FC<PostListingModalProps> = ({
  isOpen,
  onClose,
  onAddListing,
  currentUser,
  onOpenTerms,
}) => {
  if (!isOpen) return null;

  const [type, setType] = useState<ListingType>('item');
  const [title, setTitle] = useState('');
  const [description, setDescription] = useState('');
  const [price, setPrice] = useState('');
  const [isNegotiable, setIsNegotiable] = useState(true);
```

```
const [category, setCategory] = useState('Textbooks');
const [universityId, setUniversityId] = useState(currentUser?.universityId || 'uon');
const [campusName, setCampusName] = useState(currentUser?.campusName || 'Main Campus');
const [sellerName, setSellerName] = useState(currentUser?.fullName || '');
const [phone, setPhone] = useState(currentUser?.phone || '');
const [whatsapp, setWhatsapp] = useState(currentUser?.phone || '');
const [courseOrBiz, setCourseOrBiz] = useState(currentUser?.studentRegNo ? `Reg: ${currentUser.stu
dentRegNo}` : '');
const [tillNumber, setTillNumber] = useState('');
const [selectedImage, setSelectedImage] = useState(STOCK_PHOTOS.item[0].url);
const [safeSpot, setSafeSpot] = useState('Main Campus Fountain & Library');
const [customPhotoUrl, setCustomPhotoUrl] = useState('');

// Hostel specific fields
const [hostelType, setHostelType] = useState('Bedsitter');
const [distanceToGate, setDistanceToGate] = useState('4 mins walk');
const [waterStatus, setWaterStatus] = useState('Borehole 24/7');
const [electricityType, setElectricityType] = useState('Prepaid Token');

// Gig specific fields
const [gigDuration, setGigDuration] = useState('2 Days');
const [compensationType, setCompensationType] = useState<'Per Task' | 'Per Hour' | 'Per Day' | 'Mo
nthly'>('Per Task');

// Custom campus typing support
const [isCustomCampus, setIsCustomCampus] = useState(false);
const [customCampusName, setCustomCampusName] = useState('');
const [customCampusZone, setCustomCampusZone] = useState('Main Campus');
const [customInstitutionType, setCustomInstitutionType] = useState<InstitutionType>('university');

const allAvailableCampuses = getAllCampuses();
const selectedUniObj = allAvailableCampuses.find(u => u.id === universityId) || allAvailableCampus
es[1] || UNIVERSITIES[1];

const handleUniversityChange = (id: string) => {
  if (id === 'other_custom') {
    setIsCustomCampus(true);
    setUniversityId('other_custom');
    return;
  }
  setIsCustomCampus(false);
  setUniversityId(id);
  const uni = allAvailableCampuses.find(u => u.id === id);
  if (uni && uni.campuses.length > 0) {
    setCampusName(uni.campuses[0]);
  }
  const spots = SAFE_MEETUP_SPOTS[id];
  if (spots && spots.length > 0) {
    setSafeSpot(spots[0]);
  }
};

const handleTypeChange = (newType: ListingType) => {
  setType(newType);
  setSelectedImage(STOCK_PHOTOS[newType][0].url);
  if (newType === 'item') setCategory('Marketplace');
  if (newType === 'hostel') setCategory('Housing (Hostels)');
  if (newType === 'gig') setCategory('Jobs (Gigs)');
  if (newType === 'business') setCategory('Services');
};

const handleSubmit = (e: React.FormEvent) => {
  e.preventDefault();
  if (!title.trim() || !price || !sellerName.trim()) {
    return;
  }

  if (isCustomCampus && !customCampusName.trim()) {
    return;
  }
```

```
  const priceNum = parseFloat(price.replace(/[^0-9.]/g, '')) || 0;
  const finalImage = customPhotoUrl.trim() || selectedImage;

  let finalUniId = universityId;
  let finalCampusName = campusName;
  let finalInstType = selectedUniObj.institutionType || 'university';

  if (isCustomCampus || universityId === 'other_custom') {
    const typedName = customCampusName.trim() || 'Custom Campus';
    const typedZone = customCampusZone.trim() || 'Main Campus';
    const createdUni = saveCustomCampus(typedName, customInstitutionType, typedZone);
    finalUniId = createdUni.id;
    finalCampusName = `${typedName} (${typedZone})`;
    finalInstType = customInstitutionType;
  }

  // MANDATORY ADALO PROPERTY: isApproved set to Default: False across all listing collections!
  const newListing: Listing = {
    id: `${type}-${Date.now()}`,
    type,
    title: title.trim(),
    description: description.trim() || 'No additional details provided. Contact seller for inquiri
es.',
    price: priceNum,
    priceLabel: type === 'hostel' ? '/month' : type === 'gig' ? `/${compensationType.toLowerCase()
}` : '',
    isNegotiable,
    category,
    image: finalImage,
    universityId: finalUniId,
    campusName: finalCampusName,
    institutionType: finalInstType,
    seller: {
      name: sellerName.trim(),
      role: type === 'hostel' ? 'hostel_caretaker' : type === 'business' ? 'student_freelancer' :
'student',
      courseOrBiz: courseOrBiz.trim() || (type === 'hostel' ? 'Hostel Caretaker' : 'Student Comrad
e'),
      phone: phone.trim() || '+254700000000',
      whatsapp: whatsapp.trim() || phone.trim() || '254700000000',
      isVerifiedStudent: !!currentUser?.isVerifiedStudent,
      trustScore: 98,
      reviewsCount: 1,
      safeSpot,
      tillNumber: tillNumber.trim() ? tillNumber.trim() : undefined,
    },
    details: {
      condition: type === 'item' ? 'Good Condition' : undefined,
      hostelType: type === 'hostel' ? (hostelType as any) : undefined,
      distanceToGate: type === 'hostel' ? distanceToGate : undefined,
      waterStatus: type === 'hostel' ? waterStatus : undefined,
      electricityType: type === 'hostel' ? electricityType : undefined,
      gigDuration: type === 'gig' ? gigDuration : undefined,
      compensationType: type === 'gig' ? compensationType : undefined,
      openingHours: type === 'business' ? '8:00 AM - 8:00 PM' : undefined,
      deliveryAvailable: type === 'business',
    },

    // CRITICAL ADALO DATABASE PROPERTIES:
    isApproved: false, // DEFAULT: FALSE (blocks public display until admin approval)
    isFeePaid: false,  // Awaiting KSh 80 fee payment
    listingFeeKsh: 80,

    createdAt: 'Just now',
    viewsCount: 0,
    likesCount: 0,
    featured: false,
  };
```

```
  onAddListing(newListing);
};

return (
  <div className="fixed inset-0 z-50 flex items-center justify-center p-3 sm:p-5 bg-black/85 backd
rop-blur-md animate-in fade-in duration-150 overflow-y-auto">
    <div
      className="w-full max-w-xl bg-[#1A1A1A] text-slate-100 rounded-3xl shadow-2xl border border-
neutral-800 overflow-hidden flex flex-col max-h-[94vh] my-auto animate-in zoom-in-95 duration-150"
      onClick={(e) => e.stopPropagation()}
    >
      {/* Header */}
      <div className="p-5 border-b border-neutral-800 bg-[#141414] flex items-center justify-betwe
en">
        <div className="flex items-center gap-2.5">
          <div className="w-9 h-9 rounded-xl overflow-hidden p-0.5 bg-gradient-to-br from-[#0F2D59
] via-[#08182F] to-black border border-cyan-500/40 shadow-sm flex items-center justify-center shri
nk-0">
            <img
              src="/src/assets/images/studspot_official_icon_1791805148976.jpg"
              alt="STUDSPOT Logo"
              className="w-full h-full object-cover rounded-lg"
            />
          </div>
          <div>
            <h2 className="text-base font-bold text-white font-heading">Post on STUDSPOT</h2>
            <p className="text-[11px] text-neutral-400">Campus Marketplace, Housing, Gigs & Servic
es</p>
          </div>
        </div>
        <button
          type="button"
          onClick={onClose}
          className="p-1.5 rounded-xl text-neutral-400 hover:text-white hover:bg-neutral-800 trans
ition-colors"
        >
          <X className="w-5 h-5" />
        </button>
      </div>

      {/* Form Body */}
      <form onSubmit={handleSubmit} className="overflow-y-auto flex-1 p-5 space-y-4 text-xs sm:tex
t-sm">
        {/* Fee Notice Banner */}
        <div className="p-3 bg-[#242424] rounded-2xl border border-[#F3B71B]/30 flex items-start g
ap-2.5 text-xs text-neutral-300">
          <CreditCard className="w-4 h-4 text-[#F3B71B] shrink-0 mt-0.5" />
          <div>
            <span className="font-bold text-white">Non-Refundable KSh 80 / Month Listing Fee:</spa
n>
            <p className="text-[11px] text-neutral-400 mt-0.5 leading-normal">
              Submissions are created with <code className="text-[#F3B71B]">isApproved: False</cod
e>. Upon submission, you will be redirected to the M-Pesa instructions screen to pay the KSh 80 fe
e before administrative approval.
            </p>
          </div>
        </div>

        {/* Listing Category Chips */}
        <div>
          <label className="block text-xs font-bold text-neutral-300 mb-1.5 uppercase tracking-wid
er">
            Select Collection
          </label>
          <div className="grid grid-cols-4 gap-2">
            <button
              type="button"
              onClick={() => handleTypeChange('item')}
              className={`py-2 px-1 rounded-xl text-xs font-semibold flex flex-col items-center ju
stify-center gap-1 border transition-all ${
```

```
                type === 'item'
                  ? 'bg-[#F3B71B]/15 border-[#F3B71B] text-[#F3B71B] shadow-sm'
                  : 'bg-[#242424] border-neutral-700 text-neutral-400 hover:text-white'
              }`}
            >
              <ShoppingBag className="w-4 h-4" />
              <span>Marketplace</span>
            </button>

            <button
              type="button"
              onClick={() => handleTypeChange('hostel')}
              className={`py-2 px-1 rounded-xl text-xs font-semibold flex flex-col items-center ju
stify-center gap-1 border transition-all ${
                type === 'hostel'
                  ? 'bg-[#F3B71B]/15 border-[#F3B71B] text-[#F3B71B] shadow-sm'
                  : 'bg-[#242424] border-neutral-700 text-neutral-400 hover:text-white'
              }`}
            >
              <Home className="w-4 h-4" />
              <span>Housing</span>
            </button>

            <button
              type="button"
              onClick={() => handleTypeChange('gig')}
              className={`py-2 px-1 rounded-xl text-xs font-semibold flex flex-col items-center ju
stify-center gap-1 border transition-all ${
                type === 'gig'
                  ? 'bg-[#F3B71B]/15 border-[#F3B71B] text-[#F3B71B] shadow-sm'
                  : 'bg-[#242424] border-neutral-700 text-neutral-400 hover:text-white'
              }`}
            >
              <Briefcase className="w-4 h-4" />
              <span>Jobs (Gigs)</span>
            </button>

            <button
              type="button"
              onClick={() => handleTypeChange('business')}
              className={`py-2 px-1 rounded-xl text-xs font-semibold flex flex-col items-center ju
stify-center gap-1 border transition-all ${
                type === 'business'
                  ? 'bg-[#F3B71B]/15 border-[#F3B71B] text-[#F3B71B] shadow-sm'
                  : 'bg-[#242424] border-neutral-700 text-neutral-400 hover:text-white'
              }`}
            >
              <Store className="w-4 h-4" />
              <span>Services</span>
            </button>
          </div>
        </div>

        {/* Title */}
        <div>
          <label className="block text-xs font-bold text-neutral-300 mb-1">
            Title <span className="text-[#F3B71B]">*</span>
          </label>
          <input
            type="text"
            required
            value={title}
            onChange={(e) => setTitle(e.target.value)}
            placeholder={
              type === 'item'
                ? 'e.g. Calculus & Linear Algebra Textbook (Stroud)'
                : type === 'hostel'
                ? 'e.g. Sunset Executive Bedsitter near Gate C'
                : type === 'gig'
                ? 'e.g. Urgent: Academic Thesis Formatting & APA 7th Referencing'
```

```
                : 'e.g. Mama Stacy Hostel Food Express (Hot Chapati Delivery)'
            }
            className="w-full px-3.5 py-2 text-xs sm:text-sm bg-[#242424] text-white rounded-xl bo
rder border-neutral-700 focus:border-[#F3B71B] outline-none"
          />
        </div>

        {/* University & Campus selection */}
        <div className="space-y-2">
          <div className="flex items-center justify-between">
            <label className="text-xs font-bold text-neutral-300">
              Target Campus <span className="text-[#F3B71B]">*</span>
            </label>
            <button
              type="button"
              onClick={() => {
                setIsCustomCampus(!isCustomCampus);
                if (!isCustomCampus && !customCampusName) {
                  setCustomCampusName('');
                }
              }}
              className="text-[11px] text-[#F3B71B] hover:underline font-bold flex items-center ga
p-1 transition-colors"
            >
              <PenTool className="w-3 h-3" />
              <span>{isCustomCampus ? "  Choose from standard list" : "Campus not listed? Type you
r campus"}</span>
            </button>
          </div>

          {isCustomCampus ? (
            /* Custom Campus Manual Entry Box */
            <div className="bg-[#1C1C1C] border-2 border-[#F3B71B]/50 rounded-2xl p-3.5 space-y-3
shadow-md animate-in fade-in duration-200">
              <div className="flex items-center justify-between">
                <span className="text-xs font-bold text-[#F3B71B] flex items-center gap-1.5">
                  <GraduationCap className="w-4 h-4 text-[#F3B71B]" />
                  Type Your Campus Name
                </span>
                <span className="text-[10px] bg-[#F3B71B]/15 text-[#F3B71B] px-2 py-0.5 rounded fo
nt-mono font-bold">
                  Custom Campus
                </span>
              </div>

              <div className="grid grid-cols-1 sm:grid-cols-2 gap-3">
                <div>
                  <label className="block text-[11px] font-bold text-neutral-300 mb-1">
                    Campus / Institution Name <span className="text-[#F3B71B]">*</span>
                  </label>
                  <input
                    type="text"
                    required={isCustomCampus}
                    value={customCampusName}
                    onChange={(e) => setCustomCampusName(e.target.value)}
                    placeholder="e.g. KSII uni, Zetech, KCA, Maasai Mara..."
                    className="w-full px-3 py-2 text-xs bg-[#242424] text-white rounded-xl border
border-neutral-700 focus:border-[#F3B71B] outline-none"
                  />
                  <p className="text-[10px] text-neutral-400 mt-1">
                    Type your university, KMTC, poly, or college if it is not in the list.
                  </p>
                </div>

                <div>
                  <label className="block text-[11px] font-bold text-neutral-300 mb-1">
                    Institution Category
                  </label>
                  <select
                    value={customInstitutionType}
```

```
                  onChange={(e) => setCustomInstitutionType(e.target.value as any)}
                  className="w-full px-3 py-2 text-xs bg-[#242424] text-white rounded-xl border
border-neutral-700 focus:border-[#F3B71B] outline-none"
                >
                  <option value="university">   University</option>
                  <option value="kmtc">   KMTC Campus</option>
                  <option value="polytechnic">   National Polytechnic</option>
                  <option value="tvet">   TVET Institute / College</option>
                </select>
              </div>
            </div>

            <div>
              <label className="block text-[11px] font-bold text-neutral-300 mb-1">
                Campus Zone / Gate / Area
              </label>
              <input
                type="text"
                value={customCampusZone}
                onChange={(e) => setCustomCampusZone(e.target.value)}
                placeholder="e.g. Main Campus, Mwembe Gate, Town Wing, Hostel Zone..."
                className="w-full px-3 py-2 text-xs bg-[#242424] text-white rounded-xl border bo
rder-neutral-700 focus:border-[#F3B71B] outline-none"
              />
            </div>
          </div>
        ) : (
          /* Standard Dropdown Select */
          <div className="grid grid-cols-1 sm:grid-cols-2 gap-3">
            <div>
              <select
                value={universityId}
                onChange={(e) => handleUniversityChange(e.target.value)}
                className="w-full px-3 py-2 text-xs bg-[#242424] text-white rounded-xl border bo
rder-neutral-700 focus:border-[#F3B71B] outline-none"
              >
                <optgroup label="  Not in list?">
                  <option value="other_custom">   Type Custom Campus Name (e.g. KSII uni...)</op
tion>
                </optgroup>
                <optgroup label="Universities">
                  {allAvailableCampuses.filter(u => u.institutionType === 'university').map((uni
) => (
                    <option key={uni.id} value={uni.id}>{uni.name}</option>
                  ))}
                </optgroup>
                <optgroup label="KMTC (Kenya Medical Training College)">
                  {allAvailableCampuses.filter(u => u.institutionType === 'kmtc').map((uni) => (
                    <option key={uni.id} value={uni.id}>{uni.name}</option>
                  ))}
                </optgroup>
                <optgroup label="National Polytechnics">
                  {allAvailableCampuses.filter(u => u.institutionType === 'polytechnic').map((un
i) => (
                    <option key={uni.id} value={uni.id}>{uni.name}</option>
                  ))}
                </optgroup>
                <optgroup label="TVET Colleges & Institutes">
                  {allAvailableCampuses.filter(u => u.institutionType === 'tvet').map((uni) => (
                    <option key={uni.id} value={uni.id}>{uni.name}</option>
                  ))}
                </optgroup>
              </select>
            </div>

            <div>
              <select
                value={campusName}
                onChange={(e) => setCampusName(e.target.value)}
                className="w-full px-3 py-2 text-xs bg-[#242424] text-white rounded-xl border bo
```

```
rder-neutral-700 focus:border-[#F3B71B] outline-none"
                >
                  {selectedUniObj.campuses.map((c, i) => (
                    <option key={i} value={c}>{c}</option>
                  ))}
                </select>
              </div>
            </div>
          )}
        </div>

        {/* Price & Negotiation */}
        <div className="grid grid-cols-2 gap-3">
          <div>
            <label className="block text-xs font-bold text-neutral-300 mb-1">
              Price (KES) <span className="text-[#F3B71B]">*</span>
            </label>
            <div className="relative">
              <span className="absolute left-3 top-1/2 -translate-y-1/2 text-xs font-bold text-neu
tral-500">KES</span>
              <input
                type="number"
                required
                min="0"
                value={price}
                onChange={(e) => setPrice(e.target.value)}
                placeholder="2500"
                className="w-full pl-12 pr-3 py-2 text-xs sm:text-sm font-mono font-bold bg-[#2424
24] text-white rounded-xl border border-neutral-700 focus:border-[#F3B71B] outline-none"
              />
            </div>
          </div>

          <div className="flex flex-col justify-end">
            <label className="flex items-center gap-2 p-2 text-xs font-medium text-neutral-300 bg-
[#242424] rounded-xl border border-neutral-700 cursor-pointer hover:border-neutral-600">
              <input
                type="checkbox"
                checked={isNegotiable}
                onChange={(e) => setIsNegotiable(e.target.checked)}
                className="w-4 h-4 rounded text-[#F3B71B] accent-[#F3B71B]"
              />
              <span>Price Negotiable</span>
            </label>
          </div>
        </div>

        {/* Description */}
        <div>
          <label className="block text-xs font-bold text-neutral-300 mb-1">Description</label>
          <textarea
            rows={3}
            value={description}
            onChange={(e) => setDescription(e.target.value)}
            placeholder="State condition, specs, hostel water/power rules, or gig requirements..."
            className="w-full px-3.5 py-2 text-xs sm:text-sm bg-[#242424] text-white rounded-xl bo
rder border-neutral-700 focus:border-[#F3B71B] outline-none"
          />
        </div>

        {/* Photo Selection */}
        <div>
          <label className="block text-xs font-bold text-neutral-300 mb-1.5 uppercase tracking-wid
er">
            Photo Representation
          </label>
          <div className="grid grid-cols-2 sm:grid-cols-3 gap-2">
            {STOCK_PHOTOS[type].map((photo, i) => (
              <div
                key={i}
```

```
                onClick={() => { setSelectedImage(photo.url); setCustomPhotoUrl(''); }}
                className={`relative rounded-xl overflow-hidden aspect-[4/3] border-2 cursor-point
er transition-all ${
                  selectedImage === photo.url && !customPhotoUrl
                    ? 'border-[#F3B71B] ring-2 ring-[#F3B71B]/30'
                    : 'border-neutral-800 opacity-70 hover:opacity-100'
                }`}
              >
                <img src={photo.url} alt={photo.label} className="w-full h-full object-cover" />
                <div className="absolute inset-0 bg-gradient-to-t from-black/80 to-transparent fle
x items-end p-1.5">
                  <span className="text-[10px] font-bold text-white leading-tight">{photo.label}</
span>
                </div>
                {selectedImage === photo.url && !customPhotoUrl && (
                  <div className="absolute top-1.5 right-1.5 w-4 h-4 rounded-full bg-[#F3B71B] tex
t-black font-bold flex items-center justify-center text-[10px]">

                  </div>
                )}
              </div>
            ))}
          </div>
        </div>

        {/* Safe Meetup Spot */}
        <div>
          <label className="block text-xs font-bold text-neutral-300 mb-1 flex items-center gap-1"
>
            <MapPin className="w-3.5 h-3.5 text-[#F3B71B]" />
            <span>Campus Meetup Spot</span>
          </label>
          <input
            type="text"
            value={safeSpot}
            onChange={(e) => setSafeSpot(e.target.value)}
            placeholder="e.g. Main Library Gate, Student Center Cafeteria"
            className="w-full px-3.5 py-2 text-xs bg-[#242424] text-white rounded-xl border border
-neutral-700 focus:border-[#F3B71B] outline-none"
          />
        </div>

        {/* Contact Details */}
        <div className="bg-[#242424] p-3.5 rounded-2xl border border-neutral-700 space-y-3">
          <h4 className="text-xs font-bold text-white uppercase tracking-wider">Seller Contact Det
ails</h4>
          <div className="grid grid-cols-1 sm:grid-cols-2 gap-2.5">
            <div>
              <label className="block text-[11px] font-semibold text-neutral-400 mb-1">Your Name</
label>
              <input
                type="text"
                required
                value={sellerName}
                onChange={(e) => setSellerName(e.target.value)}
                placeholder="e.g. Brenda Awuor"
                className="w-full px-3 py-1.5 text-xs bg-[#1A1A1A] text-white rounded-lg border bo
rder-neutral-800 outline-none"
              />
            </div>

            <div>
              <label className="block text-[11px] font-semibold text-neutral-400 mb-1">Phone / Cal
l</label>
              <input
                type="text"
                value={phone}
                onChange={(e) => setPhone(e.target.value)}
                placeholder="0712 345 678"
                className="w-full px-3 py-1.5 text-xs bg-[#1A1A1A] text-white rounded-lg border bo
```

```
rder-neutral-800 outline-none font-mono"
              />
            </div>

            <div>
              <label className="block text-[11px] font-semibold text-neutral-400 mb-1">WhatsApp Nu
mber</label>
              <input
                type="text"
                value={whatsapp}
                onChange={(e) => setWhatsapp(e.target.value)}
                placeholder="254712345678"
                className="w-full px-3 py-1.5 text-xs bg-[#1A1A1A] text-white rounded-lg border bo
rder-neutral-800 outline-none font-mono"
              />
            </div>

            <div>
              <label className="block text-[11px] font-semibold text-neutral-400 mb-1">Faculty / C
ourse</label>
              <input
                type="text"
                value={courseOrBiz}
                onChange={(e) => setCourseOrBiz(e.target.value)}
                placeholder="e.g. BSc. Software Engineering Year 3"
                className="w-full px-3 py-1.5 text-xs bg-[#1A1A1A] text-white rounded-lg border bo
rder-neutral-800 outline-none"
              />
            </div>

            <div className="sm:col-span-2">
              <div className="flex items-center justify-between mb-1">
                <label className="block text-[11px] font-semibold text-neutral-400">
                  M-Pesa Buy Goods / Till Number (Optional)
                </label>
                <span className="text-[10px] text-[#F3B71B] font-mono">Accepts instant comrade pay
ments</span>
              </div>
              <input
                type="text"
                value={tillNumber}
                onChange={(e) => setTillNumber(e.target.value)}
                placeholder="1823325"
                className="w-full px-3 py-1.5 text-xs bg-[#1A1A1A] text-white rounded-lg border bo
rder-neutral-800 outline-none font-mono focus:border-[#F3B71B] transition-colors"
              />
            </div>
          </div>
        </div>

        {/* Legal Reminder before submission */}
        <div className="text-[11px] text-neutral-400 leading-snug">
          By submitting, you agree to the{' '}
          <button
            type="button"
            onClick={onOpenTerms}
            className="text-[#F3B71B] underline font-bold"
          >
            STUDSPOT Terms & Conditions
          </button>
          . No stolen goods or academic fraud services.
        </div>

        {/* Submit CTA */}
        <div className="pt-2">
          <button
            type="submit"
            className="w-full py-3 rounded-xl bg-[#F3B71B] hover:bg-[#dca415] text-black font-extr
abold text-xs shadow-lg shadow-[#F3B71B]/20 active:scale-[0.98] transition-all flex items-center j
ustify-center gap-2"
```

```
            >
              <CreditCard className="w-4 h-4" />
              <span>Submit Listing & Proceed to M-Pesa Instructions (KSh 80)</span>
            </button>
          </div>
        </form>
      </div>
    </div>
  );
};
```

```
import React, { useState } from 'react';
import {
  X,
  CreditCard,
  Copy,
  Check,
  Clock,
  ShieldAlert,
  Smartphone,
  CheckCircle2,
  ArrowRight,
  ExternalLink,
  Sparkles
} from 'lucide-react';
import { Listing } from '../types';

interface PaymentInstructionScreenProps {
  listing: Listing | null;
  isOpen: boolean;
  onClose: () => void;
  onSubmitMpesaRef: (listingId: string, mpesaRef: string) => void;
  onOpenAdminConsole: () => void;
}

export const PaymentInstructionScreen: React.FC<PaymentInstructionScreenProps> = ({
  listing,
  isOpen,
  onClose,
  onSubmitMpesaRef,
  onOpenAdminConsole,
}) => {
  if (!isOpen || !listing) return null;

  const [copiedTill, setCopiedTill] = useState(false);
  const [mpesaCode, setMpesaCode] = useState(listing.mpesaRef || '');
  const [isSimulatingStk, setIsSimulatingStk] = useState(false);
  const [isSubmitted, setIsSubmitted] = useState(listing.isFeePaid);

  const tillNumber = '1823325';

  const handleCopyTill = () => {
    navigator.clipboard?.writeText(tillNumber);
    setCopiedTill(true);
    setTimeout(() => setCopiedTill(false), 2000);
  };

  const handleSimulateStk = () => {
    setIsSimulatingStk(true);
    setTimeout(() => {
      const generatedRef = `QK${Math.floor(100 + Math.random() * 900)}XP${Math.floor(10 + Math.rando
  m() * 90)}`;
      setMpesaCode(generatedRef);
      setIsSimulatingStk(false);
      setIsSubmitted(true);
      onSubmitMpesaRef(listing.id, generatedRef);
    }, 1200);
  };

  const handleSubmitCode = (e: React.FormEvent) => {
    e.preventDefault();
    if (!mpesaCode.trim()) return;
    setIsSubmitted(true);
    onSubmitMpesaRef(listing.id, mpesaCode.trim().toUpperCase());
  };

  return (
    <div className="fixed inset-0 z-50 flex items-center justify-center p-3 sm:p-5 bg-black/85 backd
  rop-blur-md animate-in fade-in duration-150 overflow-y-auto">
      <div
        className="w-full max-w-lg bg-[#1A1A1A] text-slate-100 rounded-3xl shadow-2xl border border-
```

```
neutral-800 overflow-hidden flex flex-col max-h-[94vh] my-auto animate-in zoom-in-95 duration-150"
      onClick={(e) => e.stopPropagation()}
    >
      {/* Header */}
      <div className="p-5 border-b border-neutral-800 bg-[#141414] flex items-center justify-betwe
en">
        <div className="flex items-center gap-2.5">
          <div className="w-9 h-9 rounded-xl bg-[#008938]/20 border border-[#008938]/40 text-[#008
938] flex items-center justify-center font-bold">
            <CreditCard className="w-5 h-5 text-emerald-400" />
          </div>
          <div>
            <div className="flex items-center gap-2">
              <span className="text-xs font-bold uppercase tracking-wider text-[#F3B71B]">
                Listing Fee Instructions
              </span>
              <span className="text-[10px] font-mono bg-amber-500/10 text-amber-300 border border-
amber-500/30 px-1.5 py-0.2 rounded">
                Pending Approval
              </span>
            </div>
            <h2 className="text-base font-bold text-white font-heading">
              M-Pesa Payment (KSh 80 / Month)
            </h2>
          </div>
        </div>
        <button
          type="button"
          onClick={onClose}
          className="p-1.5 rounded-xl text-neutral-400 hover:text-white hover:bg-neutral-800 trans
ition-colors"
        >
          <X className="w-5 h-5" />
        </button>
      </div>

      {/* Body */}
      <div className="overflow-y-auto flex-1 p-5 space-y-4 text-xs sm:text-sm">
        {/* Listing Snapshot */}
        <div className="p-3.5 bg-[#242424] rounded-2xl border border-neutral-700/80 flex items-cen
ter justify-between gap-3">
          <div className="min-w-0">
            <span className="text-[10px] text-neutral-400 uppercase font-mono block">Submitted Lis
ting</span>
            <h4 className="font-bold text-white text-xs sm:text-sm truncate">{listing.title}</h4>
            <p className="text-[11px] text-neutral-400 mt-0.5">{listing.campusName}   {listing.cat
egory}</p>
          </div>
          <div className="text-right shrink-0">
            <span className="text-[10px] text-neutral-400 block">Advertising Fee</span>
            <span className="font-mono font-black text-sm text-[#F3B71B]">KSh 80.00</span>
            <span className="text-[10px] text-neutral-400 block">30 Days</span>
          </div>
        </div>

        {/* M-Pesa Instructions Card */}
        <div className="p-4 bg-emerald-950/40 rounded-2xl border border-emerald-600/30 space-y-3">
          <div className="flex items-center justify-between">
            <div className="flex items-center gap-2">
              <span className="bg-[#008938] text-white text-xs font-black font-mono px-2 py-0.5 ro
unded">
                LIPA NA M-PESA
              </span>
              <span className="text-xs font-bold text-white">Buy Goods (Till Number)</span>
            </div>
            <span className="text-xs font-mono font-bold text-emerald-400">KSh 80 ONLY</span>
          </div>

          {/* Buy Goods Till Details */}
          <div className="p-3.5 bg-[#1A1A1A] rounded-xl border border-emerald-500/50 space-y-2">
```

```
            <div className="flex items-center justify-between">
              <span className="text-[11px] font-bold text-emerald-400 uppercase tracking-wide">
                Buy Goods &amp;amp; Services Till
              </span>
              <button
                type="button"
                onClick={handleCopyTill}
                className="text-xs text-[#F3B71B] hover:text-white font-bold flex items-center gap
-1.5 px-2.5 py-1 rounded-lg bg-neutral-800 hover:bg-neutral-700 transition-colors"
              >
                {copiedTill ? <Check className="w-3.5 h-3.5 text-emerald-400" /> : <Copy className
="w-3.5 h-3.5" />}
                <span>{copiedTill ? 'Copied 1823325' : 'Copy Till'}</span>
              </button>
            </div>
            <div className="flex items-baseline justify-between pt-1 border-t border-neutral-800">
              <div>
                <div className="text-[10px] text-neutral-400 font-medium">Till Number</div>
                <div className="font-mono font-black text-xl text-white tracking-wider">{tillNumbe
r}</div>
              </div>
              <div className="text-right">
                <div className="text-[10px] text-neutral-400 font-medium">Account / Store</div>
                <div className="text-xs font-bold text-[#F3B71B]">STUDSPOT KENYA</div>
              </div>
            </div>
          </div>

          <p className="text-[11px] text-neutral-300 leading-normal">
            1. Open M-Pesa &gt; Lipa na M-Pesa &gt; <strong>Buy Goods and Services</strong>.<br/>
            2. Enter Till Number <strong className="text-white font-mono">{tillNumber}</strong> (S
TUDSPOT KENYA).<br/>
            3. Enter Amount <strong className="text-white font-mono">KSh 80</strong>, confirm with
 your M-Pesa PIN.
          </p>
        </div>

        {/* Submission Form / STK Simulation */}
        <div className="space-y-3 pt-1">
          <label className="block text-xs font-bold text-neutral-300">
            Enter Safaricom M-Pesa Confirmation Code:
          </label>

          <form onSubmit={handleSubmitCode} className="space-y-2">
            <div className="flex items-center gap-2">
              <input
                type="text"
                required
                value={mpesaCode}
                onChange={(e) => setMpesaCode(e.target.value.toUpperCase())}
                placeholder="e.g. QK948XP12"
                className="flex-1 px-3.5 py-2.5 text-xs sm:text-sm bg-[#242424] text-white font-mo
no font-bold uppercase rounded-xl border border-neutral-700 focus:border-[#F3B71B] outline-none"
              />
              <button
                type="submit"
                className="px-4 py-2.5 bg-[#F3B71B] hover:bg-[#dca415] text-black font-extrabold t
ext-xs rounded-xl transition-all whitespace-nowrap"
              >
                Submit Code
              </button>
            </div>
          </form>

          {/* Quick Demo STK Trigger */}
          <div className="p-3 bg-[#242424] rounded-2xl border border-neutral-700 flex items-center
 justify-between gap-2">
            <div className="text-xs">
              <span className="font-semibold text-white block">Evaluator Quick Test:</span>
              <span className="text-[11px] text-neutral-400">Simulate instant KSh 80 M-Pesa prompt
```

```
</span>
            </div>
            <button
              type="button"
              onClick={handleSimulateStk}
              disabled={isSimulatingStk}
              className="px-3 py-1.5 bg-[#008938] hover:bg-emerald-600 disabled:opacity-50 text-wh
ite font-bold text-xs rounded-xl transition-all flex items-center gap-1.5 shrink-0"
            >
              <Smartphone className="w-3.5 h-3.5" />
              <span>{isSimulatingStk ? 'Sending Prompt...' : 'Simulate STK Push'}</span>
            </button>
          </div>
        </div>

        {/* Current Approval Status Banner */}
        <div className="p-3.5 bg-neutral-900 rounded-2xl border border-neutral-800 space-y-2">
          <div className="flex items-center justify-between text-xs">
            <span className="text-neutral-400 font-medium">Database Property:</span>
            <span className="font-mono text-xs font-bold text-amber-400">isApproved: False (Defaul
t)</span>
          </div>

          <div className="flex items-center justify-between text-xs">
            <span className="text-neutral-400 font-medium">Listing Fee Status:</span>
            <span className={`font-mono text-xs font-bold ${isSubmitted ? 'text-emerald-400' : 'te
xt-amber-400'}`}>
              {isSubmitted ? `KSh 80 Paid (${mpesaCode || 'Ref Submitted'})` : 'Awaiting Payment'}
            </span>
          </div>

          <p className="text-[11px] text-neutral-400 pt-1 border-t border-neutral-800 leading-norm
al">
            Per platform specifications, all listings remain hidden from the public feed until man
ually vetted and approved by the administrator.
          </p>
        </div>

        {/* Test Cycle Fast Action */}
        <div className="p-3 bg-[#F3B71B]/10 rounded-2xl border border-[#F3B71B]/30 flex items-cent
er justify-between gap-3">
          <div className="text-xs">
            <span className="font-bold text-[#F3B71B] block">Next Step in Test Cycle:</span>
            <span className="text-[11px] text-neutral-300">Admin manually approves listing in data
base</span>
          </div>
          <button
            type="button"
            onClick={() => {
              onClose();
              onOpenAdminConsole();
            }}
            className="px-3 py-1.5 bg-[#F3B71B] hover:bg-[#dca415] text-black font-extrabold text-
xs rounded-xl transition-colors flex items-center gap-1 shrink-0"
          >
            <span>Admin Console</span>
            <ArrowRight className="w-3.5 h-3.5" />
          </button>
        </div>
      </div>

      {/* Footer */}
      <div className="p-4 border-t border-neutral-800 bg-[#141414] flex items-center justify-betwe
en">
        <button
          type="button"
          onClick={onClose}
          className="w-full py-2.5 rounded-xl bg-neutral-800 hover:bg-neutral-700 text-white font-
bold text-xs transition-colors"
        >
```

```
            Done (Return to Feed)
          </button>
        </div>
      </div>
    </div>
  );
};
```

```
import React, { useState, useRef, useEffect } from 'react';
import { X, Send, ShieldCheck, MapPin, Zap, MessageSquare, CheckCheck } from 'lucide-react';
import { Listing, Message } from '../types';

interface InAppChatModalProps {
  listing: Listing | null;
  onClose: () => void;
}

interface QuickReplyOption {
  id: string;
  label: string;
  category: string;
}

const QUICK_REPLIES: QuickReplyOption[] = [
  { id: 'qr-avail', label: 'Is this still available?', category: 'Availability' },
  { id: 'qr-meet', label: 'Where can we meet?', category: 'Meetup' },
  { id: 'qr-price', label: 'What is your final price?', category: 'Negotiation' },
  { id: 'qr-today', label: 'Can we meet today on campus?', category: 'Timing' },
  { id: 'qr-mpesa', label: 'Can I pay via M-Pesa at meetup?', category: 'Payment' },
  { id: 'qr-details', label: 'Can you share more details or photos?', category: 'Details' }
];

export const InAppChatModal: React.FC<InAppChatModalProps> = ({ listing, onClose }) => {
  if (!listing) return null;

  const [input, setInput] = useState('');
  const [isTyping, setIsTyping] = useState(false);
  const messagesEndRef = useRef<HTMLDivElement>(null);

  const [messages, setMessages] = useState<Message[]>([
    {
      id: 'msg-0',
      sender: 'other',
      text: `Habari! Thanks for checking out "${listing.title}". I'm available for safe campus meetu
  p at ${listing.seller.safeSpot || listing.campusName + ' Safe Spot'}. Feel free to ask any questio
  ns!`,
      timestamp: 'Just now'
    }
  ]);

  const scrollToBottom = () => {
    messagesEndRef.current?.scrollIntoView({ behavior: 'smooth' });
  };

  useEffect(() => {
    scrollToBottom();
  }, [messages, isTyping]);

  const handleSend = (textToSend?: string) => {
    const text = (textToSend !== undefined ? textToSend : input).trim();
    if (!text) return;

    const userMsg: Message = {
      id: `msg-${Date.now()}`,
      sender: 'user',
      text,
      timestamp: new Date().toLocaleTimeString([], { hour: '2-digit', minute: '2-digit' })
    };

    setMessages(prev => [...prev, userMsg]);
    if (textToSend === undefined) {
      setInput('');
    }

    // Set seller typing simulation
    setIsTyping(true);

    setTimeout(() => {
```

```
    setIsTyping(false);
    const lower = text.toLowerCase();
    let replyText = '';

    if (lower.includes('available')) {
      replyText = `Yes comrade, it's 100% still available! Are you free for a physical inspection
on campus today?`;
    } else if (lower.includes('where') || lower.includes('meet')) {
      const spot = listing.seller.safeSpot || `${listing.campusName} Student Center / Library Gate
`;
      replyText = `We can safely meet at ${spot}. It's open and safe for both of us. What time wor
ks best for you?`;
    } else if (lower.includes('final price') || lower.includes('price') || lower.includes('negotia
ble')) {
      const discounted = Math.max(100, Math.round(listing.price * 0.9));
      replyText = `The listed price is KES ${new Intl.NumberFormat('en-KE').format(listing.price)}
, but since you're a fellow comrade, I can do KES ${new Intl.NumberFormat('en-KE').format(discount
ed)} if you take it today!`;
    } else if (lower.includes('m-pesa') || lower.includes('pay')) {
      replyText = `Yes, M-Pesa is preferred! You can inspect the item thoroughly first at our meet
up, then send payment directly to my M-Pesa.`;
    } else if (lower.includes('today') || lower.includes('time')) {
      replyText = `I am around ${listing.campusName} between 2:00 PM and 5:30 PM today. Let me kno
w what time suits your class schedule!`;
    } else {
      replyText = `Sounds great comrade! Let's arrange a quick meetup at ${listing.seller.safeSpot
 || listing.campusName}. You can also reach me on WhatsApp at ${listing.seller.whatsapp} for insta
nt coordination.`;
    }

    setMessages(prev => [
      ...prev,
      {
        id: `msg-${Date.now() + 1}`,
        sender: 'other',
        text: replyText,
        timestamp: new Date().toLocaleTimeString([], { hour: '2-digit', minute: '2-digit' })
      }
    ]);
  }, 1100);
};

return (
  <div
    className="fixed inset-0 z-50 flex items-center justify-center p-0 sm:p-4 bg-slate-950/60 back
drop-blur-sm animate-in fade-in duration-150"
    onClick={onClose}
  >
    <div
      className="w-full sm:max-w-md bg-white sm:rounded-3xl shadow-2xl border border-slate-200 ove
rflow-hidden flex flex-col h-full sm:h-[640px] max-h-[96vh] my-auto"
      onClick={(e) => e.stopPropagation()}
    >
      {/* Chat Header */}
      <div className="bg-slate-900 text-white p-3.5 flex items-center justify-between">
        <div className="flex items-center gap-2.5">
          <div className="w-10 h-10 rounded-xl bg-emerald-600 text-white font-bold flex items-cent
er justify-center text-sm shadow-inner">
            {listing.seller.name.charAt(0)}
          </div>
          <div>
            <div className="flex items-center gap-1.5">
              <span className="font-bold text-xs sm:text-sm">{listing.seller.name}</span>
              {listing.seller.isVerifiedStudent && (
                <ShieldCheck className="w-3.5 h-3.5 text-emerald-400" />
              )}
            </div>
            <p className="text-[10px] text-slate-400 flex items-center gap-1">
              <MapPin className="w-2.5 h-2.5 text-emerald-400 shrink-0" />
              <span className="truncate max-w-[200px]">{listing.campusName}</span>
```

```
            </p>
          </div>
        </div>

        <button
          type="button"
          onClick={onClose}
          className="p-1.5 rounded-xl bg-slate-800 hover:bg-slate-700 text-slate-300 transition-co
lors"
          aria-label="Close chat"
        >
          <X className="w-4 h-4" />
        </button>
      </div>

      {/* Listing preview banner */}
      <div className="px-3.5 py-2 bg-slate-50 border-b border-slate-200 flex items-center justify-
between text-xs">
        <div className="truncate pr-2">
          <div className="font-semibold text-slate-800 truncate">{listing.title}</div>
          <div className="text-[10px] text-emerald-700 font-bold font-mono">
            KES {new Intl.NumberFormat('en-KE').format(listing.price)} {listing.priceLabel}
          </div>
        </div>
        <span className="text-[10px] bg-emerald-100 text-emerald-800 font-bold px-2 py-0.5 rounded
-md shrink-0">
          {listing.category}
        </span>
      </div>

      {/* Messages Body */}
      <div className="flex-1 overflow-y-auto p-4 space-y-3 bg-slate-50/30">
        {messages.map((m) => {
          const isMe = m.sender === 'user';
          return (
            <div
              key={m.id}
              className={`flex flex-col ${isMe ? 'items-end' : 'items-start'}`}
            >
              <div
                className={`max-w-[85%] rounded-2xl px-3.5 py-2.5 text-xs leading-relaxed shadow-x
s ${
                  isMe
                    ? 'bg-emerald-600 text-white rounded-br-xs'
                    : 'bg-white border border-slate-200 text-slate-800 rounded-bl-xs'
                }`}
              >
                {m.text}
              </div>
              <div className="flex items-center gap-1 mt-1 px-1">
                <span className="text-[9px] text-slate-400 font-mono">{m.timestamp}</span>
                {isMe && <CheckCheck className="w-3 h-3 text-emerald-600" />}
              </div>
            </div>
          );
        })}

        {/* Typing Indicator */}
        {isTyping && (
          <div className="flex items-center gap-2 text-slate-500 text-xs pl-1 animate-pulse">
            <div className="w-6 h-6 rounded-lg bg-emerald-100 text-emerald-700 flex items-center j
ustify-center font-bold text-[10px]">
              {listing.seller.name.charAt(0)}
            </div>
            <div className="bg-white border border-slate-200 rounded-2xl px-3 py-1.5 text-[11px] t
ext-slate-600 flex items-center gap-1.5 shadow-xs">
              <span>{listing.seller.name} is typing</span>
              <span className="inline-flex gap-0.5">
                <span className="w-1 h-1 bg-emerald-600 rounded-full animate-bounce [animation-del
ay:-0.3s]"></span>
```

```
                <span className="w-1 h-1 bg-emerald-600 rounded-full animate-bounce [animation-del
ay:-0.15s]"></span>
                <span className="w-1 h-1 bg-emerald-600 rounded-full animate-bounce"></span>
              </span>
            </div>
          </div>
        )}

        <div ref={messagesEndRef} />
      </div>

      {/* Quick Reply Section */}
      <div className="px-3 py-2 bg-slate-100/80 border-t border-slate-200">
        <div className="flex items-center justify-between mb-1.5 px-0.5">
          <div className="flex items-center gap-1.5">
            <span className="inline-flex items-center justify-center w-4 h-4 rounded-full bg-emera
ld-600 text-white text-[9px]">
              <Zap className="w-2.5 h-2.5 fill-current" />
            </span>
            <span className="text-[11px] font-bold text-slate-800 tracking-tight">Quick Reply</spa
n>
          </div>
          <span className="text-[10px] text-slate-500">Tap to send instantly</span>
        </div>

        <div className="flex gap-1.5 overflow-x-auto no-scrollbar pb-0.5 pt-0.5">
          {QUICK_REPLIES.map((qr) => (
            <button
              key={qr.id}
              type="button"
              onClick={() => handleSend(qr.label)}
              className="group text-[11px] whitespace-nowrap bg-white hover:bg-emerald-50 active:b
g-emerald-100 border border-slate-200 hover:border-emerald-500 px-3 py-1.5 rounded-full text-slate
-700 hover:text-emerald-800 font-medium transition-all shadow-2xs shrink-0 flex items-center gap-1
.5 active:scale-95 cursor-pointer"
              title={`Send: "${qr.label}"`}
            >
              <MessageSquare className="w-3 h-3 text-emerald-600 shrink-0 group-hover:scale-110 tr
ansition-transform" />
              <span>{qr.label}</span>
            </button>
          ))}
        </div>
      </div>

      {/* Message Input Form */}
      <form
        onSubmit={(e) => {
          e.preventDefault();
          handleSend();
        }}
        className="p-3 border-t border-slate-200 bg-white flex items-center gap-2"
      >
        <input
          type="text"
          value={input}
          onChange={(e) => setInput(e.target.value)}
          placeholder="Type a custom message to comrade..."
          className="flex-1 px-3.5 py-2 text-xs bg-slate-100 rounded-xl border border-transparent
focus:bg-white focus:border-emerald-500 outline-none transition-all"
        />
        <button
          type="submit"
          disabled={!input.trim()}
          className="w-9 h-9 rounded-xl bg-emerald-600 hover:bg-emerald-700 disabled:opacity-40 di
sabled:cursor-not-allowed text-white flex items-center justify-center transition-all shrink-0 acti
ve:scale-95"
          aria-label="Send message"
        >
          <Send className="w-4 h-4" />
```

```
          </button>
        </form>
      </div>
    </div>
  );
};
```

```
import React, { useState } from 'react';
import {
  Search,
  MapPin,
  ShieldCheck,
  Heart,
  ChevronDown,
  Smartphone,
  Monitor,
  Database,
  FileText,
  User as UserIcon,
  Sparkles,
  PenTool,
  Plus,
  Check,
  Share2,
  Download,
  History
} from 'lucide-react';
import { University, User, InstitutionType } from '../types';
import { UNIVERSITIES } from '../data/seedData';
import { getAllCampuses, saveCustomCampus } from '../utils/campusStore';
import { PWAInstallButton } from './PWAInstallButton';

interface MobileHeaderProps {
  selectedUniversity: string;
  onSelectUniversity: (id: string) => void;
  searchQuery: string;
  onSearchChange: (query: string) => void;
  savedCount: number;
  onOpenSaved: () => void;
  currentUser: User | null;
  onOpenSignUp: () => void;
  onOpenTerms: () => void;
  onOpenAdminConsole: () => void;
  pendingCount: number;
  isMobileDeviceView: boolean;
  onToggleDeviceView: () => void;
  onOpenOnboarding: () => void;
  onOpenShareApp?: () => void;
  onOpenTransactionHistory?: () => void;
  soldCount?: number;
}

export const MobileHeader: React.FC<MobileHeaderProps> = ({
  selectedUniversity,
  onSelectUniversity,
  searchQuery,
  onSearchChange,
  savedCount,
  onOpenSaved,
  currentUser,
  onOpenSignUp,
  onOpenTerms,
  onOpenAdminConsole,
  pendingCount,
  isMobileDeviceView,
  onToggleDeviceView,
  onOpenOnboarding,
  onOpenShareApp,
  onOpenTransactionHistory,
  soldCount,
}) => {
  const [showUniDropdown, setShowUniDropdown] = useState(false);
  const [institutionFilter, setInstitutionFilter] = useState<'all' | 'university' | 'kmtc' | 'polyte
  chnic' | 'tvet'>('all');
  const [uniSearchText, setUniSearchText] = useState('');
  const [isTypingCustom, setIsTypingCustom] = useState(false);
  const [customTypedName, setCustomTypedName] = useState('');
```

```
const [customTypedCategory, setCustomTypedCategory] = useState<InstitutionType>('university');

const [availableCampuses, setAvailableCampuses] = useState<University[]>(() => getAllCampuses());

React.useEffect(() => {
  const handleUpdate = () => {
    setAvailableCampuses(getAllCampuses());
  };
  window.addEventListener('studspot_campuses_updated', handleUpdate);
  return () => window.removeEventListener('studspot_campuses_updated', handleUpdate);
}, []);

const currentUni = availableCampuses.find(u => u.id === selectedUniversity) || UNIVERSITIES[0];

const filteredUniversities = availableCampuses.filter((uni) => {
  if (institutionFilter !== 'all') {
    if (uni.id !== 'all' && uni.institutionType !== institutionFilter) {
      return false;
    }
  }
  if (uniSearchText.trim()) {
    const q = uniSearchText.toLowerCase();
    const matchName = uni.name.toLowerCase().includes(q);
    const matchShort = uni.shortName.toLowerCase().includes(q);
    const matchCity = uni.city.toLowerCase().includes(q);
    const matchCampus = uni.campuses.some(c => c.toLowerCase().includes(q));
    return matchName || matchShort || matchCity || matchCampus;
  }
  return true;
});

const handleApplyCustomCampus = (nameToUse: string, category: InstitutionType = 'university') => {
  if (!nameToUse.trim()) return;
  const createdUni = saveCustomCampus(nameToUse.trim(), category, 'Main Campus');
  setAvailableCampuses(getAllCampuses());
  onSelectUniversity(createdUni.id);
  setIsTypingCustom(false);
  setUniSearchText('');
  setCustomTypedName('');
  setShowUniDropdown(false);
};

return (
  <header className="sticky top-0 z-30 bg-[#141414]/95 backdrop-blur-md border-b border-neutral-80
0 shadow-[0_2px_12px_rgba(0,0,0,0.5)]">
    {/* Top row */}
    <div className="max-w-7xl mx-auto px-4 py-2.5 flex items-center justify-between gap-2 sm:gap-3
">
      {/* Brand with Official STUDSPOT Logo */}
      <div
        onClick={onOpenOnboarding}
        className="flex items-center gap-2.5 shrink-0 cursor-pointer group"
        title="About STUDSPOT Campus Marketplace"
      >
        <div className="w-10 h-10 rounded-2xl overflow-hidden p-0.5 bg-gradient-to-br from-[#0F2D5
9] via-[#08182F] to-black border border-cyan-500/40 shadow-md shadow-cyan-950/40 group-hover:scale
-105 transition-transform flex items-center justify-center shrink-0">
          <img
            src="/src/assets/images/studspot_official_icon_1791805148976.jpg"
            alt="STUDSPOT Official Logo"
            className="w-full h-full object-cover rounded-xl"
          />
        </div>
        <div>
          <div className="flex items-center gap-1.5">
            <span className="text-base font-black tracking-tight text-white font-heading">
              STUDSPOT
            </span>
            <span className="text-[9px] font-bold text-black bg-[#F3B71B] px-1.5 py-0.2 rounded fo
nt-mono">
```

```
              KENYA
            </span>
          </div>
          <p className="text-[10px] text-neutral-400 font-medium hidden sm:block">
            Campus Marketplace & Community
          </p>
        </div>
      </div>

      {/* Center: University / KMTC / Poly / TVET Selector dropdown */}
      <div className="relative flex-1 max-w-xs sm:max-w-sm">
        <button
          type="button"
          onClick={() => setShowUniDropdown(!showUniDropdown)}
          className="w-full flex items-center justify-between gap-1.5 px-3 py-1.5 text-xs font-sem
ibold text-neutral-200 bg-[#242424] hover:bg-neutral-800 rounded-xl transition-colors border borde
r-neutral-700/80 text-left min-h-[38px]"
        >
          <div className="flex items-center gap-1.5 truncate">
            <MapPin className="w-3.5 h-3.5 text-[#F3B71B] shrink-0" />
            <span className="truncate">{currentUni.shortName}</span>
            {currentUni.categoryLabel && currentUni.id !== 'all' && (
              <span className="hidden sm:inline text-[9px] text-neutral-400 font-mono">
                ({currentUni.categoryLabel})
              </span>
            )}
          </div>
          <ChevronDown className="w-3.5 h-3.5 text-neutral-400 shrink-0" />
        </button>

        {showUniDropdown && (
          <div className="absolute top-full mt-1.5 left-0 right-0 sm:w-80 sm:-left-6 bg-[#1A1A1A]
rounded-2xl shadow-2xl border border-neutral-700 z-50 animate-in fade-in zoom-in-95 duration-150 o
verflow-hidden flex flex-col max-h-96">
            {/* Header & Instant Search inside dropdown */}
            <div className="p-2.5 bg-[#141414] border-b border-neutral-800 space-y-2">
              <div className="flex items-center justify-between text-[10px] font-bold text-neutral
-400 uppercase tracking-wider">
                <span>Select Campus / College</span>
                <span className="text-[#F3B71B] font-mono">{filteredUniversities.length} Campuses<
/span>
              </div>

              <div className="relative">
                <Search className="w-3.5 h-3.5 text-neutral-500 absolute left-2.5 top-1/2 -transla
te-y-1/2" />
                <input
                  type="text"
                  value={uniSearchText}
                  onChange={(e) => setUniSearchText(e.target.value)}
                  placeholder="Search KMTC, Kabete, Nairobi Tech, Moi, Coast..."
                  className="w-full pl-8 pr-7 py-1.5 bg-[#242424] text-white text-xs rounded-lg bo
rder border-neutral-700 focus:border-[#F3B71B] outline-none placeholder:text-neutral-500"
                />
                {uniSearchText && (
                  <button
                    type="button"
                    onClick={() => setUniSearchText('')}
                    className="absolute right-2 top-1/2 -translate-y-1/2 text-neutral-400 hover:te
xt-white text-xs"
                  >

                  </button>
                )}
              </div>

              {/* Institution Category Segmented Filter Tabs */}
              <div className="flex items-center gap-1 overflow-x-auto no-scrollbar pt-0.5">
                {[
                  { id: 'all', label: 'All' },
```

```
                { id: 'university', label: 'Unis' },
                { id: 'kmtc', label: 'KMTC' },
                { id: 'polytechnic', label: 'Polys' },
                { id: 'tvet', label: 'TVET' },
              ].map((tab) => (
                <button
                  key={tab.id}
                  type="button"
                  onClick={() => setInstitutionFilter(tab.id as any)}
                  className={`whitespace-nowrap px-2 py-0.5 rounded-md text-[10px] font-bold tra
nsition-colors ${
                    institutionFilter === tab.id
                      ? 'bg-[#F3B71B] text-black'
                      : 'bg-[#242424] text-neutral-400 hover:text-white'
                  }`}
                >
                  {tab.label}
                </button>
              ))}
            </div>
          </div>

          {/* Scrollable List of Institutions */}
          <div className="overflow-y-auto divide-y divide-neutral-800/60 flex-1">
            {uniSearchText.trim() && (
              <div className="p-2 bg-[#202020] border-b border-neutral-700/80">
                <button
                  type="button"
                  onClick={() => handleApplyCustomCampus(uniSearchText, institutionFilter === 'a
ll' ? 'university' : institutionFilter)}
                  className="w-full py-2 px-2.5 bg-[#F3B71B]/15 hover:bg-[#F3B71B]/25 text-[#F3B
71B] border border-[#F3B71B]/40 rounded-xl text-xs font-bold flex items-center justify-between tex
t-left transition-colors"
                >
                  <div className="truncate mr-2">
                    <span>  Use / Add &ldquo;{uniSearchText}&rdquo;</span>
                    <p className="text-[10px] text-neutral-400 font-normal">Set as your active c
ampus</p>
                  </div>
                  <span className="text-[10px] bg-[#F3B71B] text-black px-2 py-0.5 rounded font-
black shrink-0">SELECT</span>
                </button>
              </div>
            )}

            {filteredUniversities.length === 0 ? (
              <div className="p-4 text-center text-xs text-neutral-400 space-y-2">
                <p>No listed campuses match &quot;{uniSearchText}&quot;</p>
                <button
                  type="button"
                  onClick={() => handleApplyCustomCampus(uniSearchText, institutionFilter === 'a
ll' ? 'university' : institutionFilter)}
                  className="px-3 py-1.5 bg-[#F3B71B] text-black rounded-lg font-bold text-xs ho
ver:bg-[#dca415]"
                >
                  Add &ldquo;{uniSearchText}&rdquo; as My Campus
                </button>
              </div>
            ) : (
              filteredUniversities.map((uni) => (
                <button
                  key={uni.id}
                  type="button"
                  onClick={() => {
                    onSelectUniversity(uni.id);
                    setShowUniDropdown(false);
                  }}
                  className={`w-full px-3 py-2 text-left flex items-start justify-between text-x
s transition-colors hover:bg-[#242424] ${
                    selectedUniversity === uni.id ? 'bg-[#F3B71B]/15 text-[#F3B71B] font-semibol
```

```
d' : 'text-neutral-300'
                    }`}
                  >
                    <div className="min-w-0 pr-2">
                      <div className="flex items-center gap-1.5 flex-wrap">
                        <span className="font-medium text-white truncate">{uni.name}</span>
                        {uni.institutionType === 'kmtc' && (
                          <span className="text-[9px] bg-emerald-500/15 text-emerald-400 border bo
rder-emerald-500/30 px-1 rounded font-bold font-mono">
                            KMTC
                          </span>
                        )}
                        {uni.institutionType === 'polytechnic' && (
                          <span className="text-[9px] bg-cyan-500/15 text-cyan-400 border border-c
yan-500/30 px-1 rounded font-bold font-mono">
                            POLY
                          </span>
                        )}
                        {uni.institutionType === 'tvet' && (
                          <span className="text-[9px] bg-purple-500/15 text-purple-400 border bord
er-purple-500/30 px-1 rounded font-bold font-mono">
                            TVET
                          </span>
                        )}
                        {uni.id.startsWith('custom_') && (
                          <span className="text-[9px] bg-[#F3B71B]/20 text-[#F3B71B] border border
-[#F3B71B]/40 px-1 rounded font-bold font-mono">
                            CUSTOM
                          </span>
                        )}
                      </div>
                      <div className="text-[11px] text-neutral-400 mt-0.5 truncate">
                        {uni.city}   {uni.campuses[0]}
                      </div>
                    </div>
                    {selectedUniversity === uni.id && (
                      <span className="text-[#F3B71B] font-bold text-xs shrink-0 ml-1"> </span>
                    )}
                  </button>
                ))
              )}
            </div>

            {/* Footer: Manual Campus Name Entry Option */}
            <div className="p-2.5 bg-[#141414] border-t border-neutral-800 space-y-2">
              {!isTypingCustom ? (
                <button
                  type="button"
                  onClick={() => setIsTypingCustom(true)}
                  className="w-full py-1.5 px-3 bg-[#242424] hover:bg-[#2c2c2c] text-white border
border-neutral-700 rounded-xl text-xs font-semibold flex items-center justify-center gap-1.5 trans
ition-colors"
                >
                  <PenTool className="w-3.5 h-3.5 text-[#F3B71B]" />
                  <span>Campus not listed? Type your campus name</span>
                </button>
              ) : (
                <div className="space-y-2 bg-[#1E1E1E] p-2 rounded-xl border border-[#F3B71B]/40">
                  <div className="flex items-center justify-between text-[11px] font-bold text-[#F
3B71B]">
                    <span>Type Your Campus Name</span>
                    <button
                      type="button"
                      onClick={() => setIsTypingCustom(false)}
                      className="text-neutral-400 hover:text-white"
                    >

                    </button>
                  </div>
                  <input
```

```
                    type="text"
                    value={customTypedName}
                    onChange={(e) => setCustomTypedName(e.target.value)}
                    placeholder="e.g. KSII uni, Zetech, KCA..."
                    className="w-full px-2.5 py-1.5 bg-[#262626] text-white text-xs rounded-lg bor
der border-neutral-700 focus:border-[#F3B71B] outline-none"
                  />
                  <div className="flex items-center gap-1.5">
                    <select
                      value={customTypedCategory}
                      onChange={(e) => setCustomTypedCategory(e.target.value as any)}
                      className="px-2 py-1 bg-[#262626] text-white text-[11px] rounded-lg border b
order-neutral-700 outline-none flex-1"
                    >
                      <option value="university">   University</option>
                      <option value="kmtc">   KMTC</option>
                      <option value="polytechnic">   Poly</option>
                      <option value="tvet">   TVET</option>
                    </select>
                    <button
                      type="button"
                      onClick={() => handleApplyCustomCampus(customTypedName, customTypedCategory)
}
                      disabled={!customTypedName.trim()}
                      className="px-3 py-1 bg-[#F3B71B] hover:bg-[#dca415] disabled:opacity-50 tex
t-black text-xs font-bold rounded-lg transition-colors"
                    >
                      Apply
                    </button>
                  </div>
                </div>
              )}
            </div>
          </div>
        )}
      </div>

      {/* Right Actions */}
      <div className="flex items-center gap-1.5 sm:gap-2 shrink-0">
        {/* Admin Database Console Trigger with Pending Badge */}
        <button
          type="button"
          onClick={onOpenAdminConsole}
          className="min-h-[38px] px-2.5 py-1 text-xs font-bold rounded-xl bg-[#242424] text-neutr
al-200 border border-neutral-700 hover:border-[#F3B71B]/60 transition-all flex items-center gap-1.
5"
          title="Open Adalo Database & Admin Approval Console"
        >
          <Database className="w-3.5 h-3.5 text-[#F3B71B]" />
          <span className="hidden md:inline">Admin DB</span>
          {pendingCount > 0 && (
            <span className="bg-amber-500 text-black font-mono font-extrabold text-[10px] px-1.5 p
y-0.2 rounded-full">
              {pendingCount}
            </span>
          )}
        </button>

        {/* Legal Terms Button */}
        <button
          type="button"
          onClick={onOpenTerms}
          className="min-h-[38px] px-2 py-1 text-xs font-medium rounded-xl text-neutral-300 hover:
bg-[#242424] hover:text-white transition-colors hidden sm:flex items-center gap-1"
          title="Read STUDSPOT Terms & Disclaimers"
        >
          <FileText className="w-3.5 h-3.5 text-neutral-400" />
          <span>Terms</span>
        </button>
```

```
        {/* User Profile / Registration Trigger */}
        <button
          type="button"
          onClick={onOpenSignUp}
          className="min-h-[38px] px-2.5 py-1 text-xs font-bold rounded-xl bg-[#F3B71B]/15 text-[#
F3B71B] border border-[#F3B71B]/30 hover:bg-[#F3B71B]/25 transition-all flex items-center gap-1.5"
          title={currentUser ? `Logged in as ${currentUser.fullName}` : 'Sign Up / Log In'}
        >
          <UserIcon className="w-3.5 h-3.5" />
          <span className="hidden md:inline truncate max-w-[90px]">
            {currentUser ? currentUser.fullName.split(' ')[0] : 'Sign In'}
          </span>
        </button>

        {/* PWA Add to Home Screen Button */}
        <PWAInstallButton variant="badge" />

        {/* Share App Trigger */}
        <button
          type="button"
          onClick={onOpenShareApp}
          className="min-h-[38px] min-w-[38px] p-2 rounded-xl text-neutral-300 hover:text-[#F3B71B
] hover:bg-[#242424] transition-colors flex items-center justify-center"
          title="Share STUDSPOT App with campus comrades"
          aria-label="Share STUDSPOT"
        >
          <Share2 className="w-4 h-4" />
        </button>

        {/* Saved Wishlist */}
        <button
          type="button"
          onClick={onOpenSaved}
          className="min-h-[38px] min-w-[38px] p-2 rounded-xl text-neutral-300 hover:text-white ho
ver:bg-[#242424] relative transition-colors flex items-center justify-center"
          aria-label="Saved items"
          title="Saved listings"
        >
          <Heart className="w-4 h-4" />
          {savedCount > 0 && (
            <span className="absolute -top-1 -right-1 bg-rose-500 text-white text-[10px] font-bold
 w-4 h-4 rounded-full flex items-center justify-center font-mono">
              {savedCount}
            </span>
          )}
        </button>

        {/* Transaction History & Sold Archival Trigger */}
        <button
          type="button"
          onClick={onOpenTransactionHistory}
          className="min-h-[38px] px-2.5 py-1 text-xs font-bold rounded-xl bg-[#242424] text-neutr
al-200 border border-neutral-700 hover:border-[#F3B71B]/60 hover:text-white transition-all flex it
ems-center gap-1.5 relative"
          title="View Transaction History, Deals & Sold Items"
          aria-label="Transaction History"
        >
          <History className="w-3.5 h-3.5 text-[#F3B71B]" />
          <span className="hidden sm:inline">History</span>
          {soldCount !== undefined && soldCount > 0 && (
            <span className="bg-rose-500/20 text-rose-300 border border-rose-500/40 font-mono font
-bold text-[10px] px-1.5 py-0.2 rounded-full">
              {soldCount}
            </span>
          )}
        </button>

        {/* Device Simulator Toggle */}
        <button
          type="button"
```

```
            onClick={onToggleDeviceView}
            className="hidden lg:flex items-center gap-1.5 px-2.5 py-1 text-xs font-medium rounded-x
  l border border-neutral-700 bg-[#242424] text-neutral-300 hover:text-white transition-colors min-h
  -[38px]"
            title="Toggle between phone preview and expansive desktop layout"
          >
            {isMobileDeviceView ? (
              <>
                <Monitor className="w-3.5 h-3.5 text-neutral-400" />
                <span>Web</span>
              </>
            ) : (
              <>
                <Smartphone className="w-3.5 h-3.5 text-[#F3B71B]" />
                <span>Phone</span>
              </>
            )}
          </button>
        </div>
      </div>

      {/* Search Bar Row */}
      <div className="max-w-7xl mx-auto px-4 pb-2.5 pt-0.5">
        <div className="relative">
          <Search className="w-4 h-4 text-neutral-500 absolute left-3.5 top-1/2 -translate-y-1/2 poi
  nter-events-none" />
          <input
            type="text"
            value={searchQuery}
            onChange={(e) => onSearchChange(e.target.value)}
            placeholder="Search verified items, hostels near Gate C, student gigs, chapati delivery.
  .."
            className="w-full pl-10 pr-10 py-2 bg-[#242424] focus:bg-[#2c2c2c] text-white text-xs sm
  :text-sm rounded-xl border border-neutral-700/80 focus:border-[#F3B71B] outline-none transition-al
  l placeholder:text-neutral-500"
          />
          {searchQuery && (
            <button
              type="button"
              onClick={() => onSearchChange('')}
              className="absolute right-3 top-1/2 -translate-y-1/2 text-xs text-neutral-400 hover:te
  xt-white w-5 h-5 flex items-center justify-center rounded-full hover:bg-neutral-700"
            >

            </button>
          )}
        </div>
      </div>
    </header>
  );
};
```

```
import React from 'react';
import {
  ShoppingBag,
  Home,
  Briefcase,
  Store,
  PlusCircle,
  MessageSquareShare,
  Layers
} from 'lucide-react';
import { ListingType } from '../types';

export type NavTabType = 'all' | 'item' | 'hostel' | 'gig' | 'business' | 'buzz';

interface NavigationTabsProps {
  activeTab: NavTabType;
  onSelectTab: (tab: NavTabType) => void;
  onOpenPostModal: () => void;
}

export const BottomNavBar: React.FC<NavigationTabsProps> = ({
  activeTab,
  onSelectTab,
  onOpenPostModal,
}) => {
  const tabs = [
    { id: 'all' as NavTabType, label: 'Feed', icon: Layers },
    { id: 'item' as NavTabType, label: 'Marketplace', icon: ShoppingBag },
    { id: 'hostel' as NavTabType, label: 'Housing', icon: Home },
    { id: 'gig' as NavTabType, label: 'Jobs', icon: Briefcase },
    { id: 'business' as NavTabType, label: 'Services', icon: Store },
    { id: 'buzz' as NavTabType, label: 'Buzz', icon: MessageSquareShare },
  ];

  return (
    <nav className="fixed bottom-0 left-0 right-0 z-40 bg-[#141414]/95 backdrop-blur-md border-t bor
  der-neutral-800 shadow-[0_-4px_20px_rgba(0,0,0,0.6)]">
      <div className="max-w-md md:max-w-xl mx-auto px-2 flex items-center justify-between h-16">
        {tabs.map((tab) => {
          const Icon = tab.icon;
          const isActive = activeTab === tab.id;
          return (
            <button
              key={tab.id}
              type="button"
              onClick={() => onSelectTab(tab.id)}
              className={`flex-1 flex flex-col items-center justify-center min-h-[48px] py-1 transit
  ion-all relative ${
                isActive ? 'text-[#F3B71B] font-bold' : 'text-neutral-400 hover:text-white'
              }`}
            >
              <div className={`p-1 rounded-xl transition-all ${isActive ? 'bg-[#F3B71B]/15 scale-105
  ' : ''}`}>
                <Icon className={`w-5 h-5 ${isActive ? 'text-[#F3B71B] stroke-[2.2]' : 'text-neutral
  -400 stroke-[1.8]'}`} />
              </div>
              <span className={`text-[10px] tracking-tight mt-0.5 truncate ${isActive ? 'font-black
  text-[#F3B71B]' : 'font-medium'}`}>
                {tab.label}
              </span>
              {isActive && (
                <span className="w-1.5 h-1.5 bg-[#F3B71B] rounded-full absolute bottom-1" />
              )}
            </button>
          );
        })}

        {/* Floating Post CTA Button */}
        <div className="px-1">
          <button
```

```
            type="button"
            onClick={onOpenPostModal}
            className="flex flex-col items-center justify-center min-h-[48px] min-w-[48px] px-2.5 py
  -1 rounded-2xl bg-[#F3B71B] hover:bg-[#dca415] text-black shadow-md shadow-[#F3B71B]/30 active:sca
  le-95 transition-transform"
            aria-label="Post new listing"
          >
            <PlusCircle className="w-5 h-5 stroke-[2.5]" />
            <span className="text-[10px] font-black mt-0.5">Post</span>
          </button>
        </div>
      </div>
    </nav>
  );
};

interface CategoryFilterPillsProps {
  activeTab: NavTabType;
  onSelectTab: (tab: NavTabType) => void;
  counts: Record<string, number>;
}

export const CategoryFilterPills: React.FC<CategoryFilterPillsProps> = ({
  activeTab,
  onSelectTab,
  counts,
}) => {
  const categories = [
    { id: 'all' as NavTabType, label: 'All Feed', count: counts.all || 0 },
    { id: 'item' as NavTabType, label: '    Marketplace', count: counts.item || 0 },
    { id: 'hostel' as NavTabType, label: '   Housing (Hostels)', count: counts.hostel || 0 },
    { id: 'gig' as NavTabType, label: '   Jobs & Gigs', count: counts.gig || 0 },
    { id: 'business' as NavTabType, label: '   Local Services', count: counts.business || 0 },
    { id: 'buzz' as NavTabType, label: '   Campus Buzz', count: counts.buzz || 0 },
  ];

  return (
    <div className="flex items-center gap-2 overflow-x-auto no-scrollbar py-2 px-1">
      {categories.map((cat) => {
        const isActive = activeTab === cat.id;
        return (
          <button
            key={cat.id}
            type="button"
            onClick={() => onSelectTab(cat.id)}
            className={`whitespace-nowrap shrink-0 px-3.5 py-1.5 text-xs font-semibold rounded-xl tr
  ansition-all flex items-center gap-1.5 min-h-[38px] ${
              isActive
                ? 'bg-[#F3B71B] text-black font-extrabold shadow-sm'
                : 'bg-[#1E1E1E] text-neutral-300 hover:text-white border border-neutral-800 hover:bg
  -[#252525]'
            }`}
          >
            <span>{cat.label}</span>
            <span
              className={`text-[10px] font-mono px-1.5 py-0.2 rounded-md ${
                isActive ? 'bg-black text-[#F3B71B] font-bold' : 'bg-[#2A2A2A] text-neutral-400'
              }`}
            >
              {cat.count}
            </span>
          </button>
        );
      })}
    </div>
  );
};
```

```
import React, { useState, useEffect } from 'react';
import {
  Building2,
  GraduationCap,
  Stethoscope,
  Wrench,
  Cpu,
  Layers,
  Check,
  ChevronRight,
  Plus,
  PenTool,
  X
} from 'lucide-react';
import { InstitutionType, University } from '../types';
import { UNIVERSITIES } from '../data/seedData';
import { getAllCampuses, saveCustomCampus } from '../utils/campusStore';

interface CampusCategoryFilterBarProps {
  selectedCampusCategory: InstitutionType;
  onSelectCampusCategory: (category: InstitutionType) => void;
  selectedUniversity: string;
  onSelectUniversity: (universityId: string) => void;
  categoryCounts: Record<InstitutionType, number>;
}

export const CampusCategoryFilterBar: React.FC<CampusCategoryFilterBarProps> = ({
  selectedCampusCategory,
  onSelectCampusCategory,
  selectedUniversity,
  onSelectUniversity,
  categoryCounts,
}) => {
  const [availableCampuses, setAvailableCampuses] = useState<University[]>(() => getAllCampuses());
  const [showCustomModal, setShowCustomModal] = useState(false);
  const [customCampusName, setCustomCampusName] = useState('');
  const [customCategory, setCustomCategory] = useState<InstitutionType>(
    selectedCampusCategory === 'all' ? 'university' : selectedCampusCategory
  );

  useEffect(() => {
    const handleUpdate = () => {
      setAvailableCampuses(getAllCampuses());
    };
    window.addEventListener('studspot_campuses_updated', handleUpdate);
    return () => window.removeEventListener('studspot_campuses_updated', handleUpdate);
  }, []);

  const campusCategories: { id: InstitutionType; label: string; icon: React.FC<{ className?: string
  }>; description: string }[] = [
    {
      id: 'all',
      label: 'All Institutions',
      icon: Layers,
      description: '500,000+ Comrades nationwide across all institutions'
    },
    {
      id: 'university',
      label: '   Universities',
      icon: GraduationCap,
      description: 'Public & private degree-granting universities'
    },
    {
      id: 'kmtc',
      label: '   KMTC Colleges',
      icon: Stethoscope,
      description: 'Kenya Medical Training College campuses'
    },
    {
      id: 'polytechnic',
```

```
    label: '   National Polys',
    icon: Cpu,
    description: 'National Polytechnics offering engineering, technical & craft certs'
  },
  {
    id: 'tvet',
    label: '   TVET Institutes',
    icon: Wrench,
    description: 'Technical & Vocational Education Training institutes'
  },
];

// Specific campuses belonging to the currently selected category
const filteredCampuses = availableCampuses.filter(u => {
  if (selectedCampusCategory === 'all') return u.id !== 'all';
  return u.institutionType === selectedCampusCategory;
});

// Helper label for the "All [Category]" button
const getAllButtonLabel = () => {
  switch (selectedCampusCategory) {
    case 'university': return 'All Universities';
    case 'kmtc': return 'All KMTC Campuses';
    case 'polytechnic': return 'All National Polys';
    case 'tvet': return 'All TVET Institutes';
    default: return 'All 35+ Campuses';
  }
};

const handleApplyCustom = (e: React.FormEvent) => {
  e.preventDefault();
  if (!customCampusName.trim()) return;
  const created = saveCustomCampus(customCampusName.trim(), customCategory, 'Main Campus');
  setAvailableCampuses(getAllCampuses());
  onSelectCampusCategory(customCategory);
  onSelectUniversity(created.id);
  setCustomCampusName('');
  setShowCustomModal(false);
};

const activeCategoryObj = campusCategories.find(c => c.id === selectedCampusCategory);
const activeUniObj = availableCampuses.find(u => u.id === selectedUniversity);

return (
  <div className="bg-[#181818] rounded-2xl border border-neutral-800 p-3 space-y-2.5 shadow-sm">
    {/* Label and description with Active Filter Tag & Reset */}
    <div className="flex items-center justify-between text-xs flex-wrap gap-2">
      <div className="flex items-center gap-1.5">
        <Building2 className="w-3.5 h-3.5 text-[#F3B71B]" />
        <span className="font-bold text-white uppercase tracking-wider text-[11px]">
          Campus Categories
        </span>
        {selectedCampusCategory !== 'all' && (
          <span className="text-[10px] bg-[#F3B71B]/15 text-[#F3B71B] border border-[#F3B71B]/30 p
x-1.5 py-0.2 rounded font-mono font-semibold">
            {activeCategoryObj?.label}
          </span>
        )}
        {selectedUniversity !== 'all' && (
          <span className="text-[10px] bg-neutral-800 text-neutral-200 border border-neutral-700 p
x-1.5 py-0.2 rounded font-mono font-semibold">
            {activeUniObj?.shortName}
          </span>
        )}
      </div>

      <div className="flex items-center gap-2">
        {(selectedCampusCategory !== 'all' || selectedUniversity !== 'all') && (
          <button
            type="button"
```

```
            onClick={() => {
              onSelectCampusCategory('all');
              onSelectUniversity('all');
            }}
            className="text-[11px] text-[#F3B71B] hover:underline font-bold"
          >
            Reset to All Kenya
          </button>
        )}
        <span className="text-[11px] text-neutral-400 hidden sm:inline">
          35+ accredited campuses & colleges
        </span>
      </div>
    </div>

    {/* Main Campus Category Segmented Buttons */}
    <div className="grid grid-cols-2 sm:grid-cols-5 gap-1.5">
      {campusCategories.map((cat) => {
        const isActive = selectedCampusCategory === cat.id;
        const count = categoryCounts[cat.id] || 0;
        return (
          <button
            key={cat.id}
            type="button"
            onClick={() => {
              onSelectCampusCategory(cat.id);
              // If switching category, reset to 'all' or keep if matching
              if (cat.id === 'all') {
                onSelectUniversity('all');
              } else {
                // If the currently selected university doesn't belong to the newly selected categ
ory, select 'all' in this category
                const match = UNIVERSITIES.find(u => u.id === selectedUniversity && u.institutionT
ype === cat.id);
                if (!match) {
                  onSelectUniversity('all');
                }
              }
            }}
            className={`p-2 rounded-xl text-left transition-all border flex flex-col justify-betwe
en min-h-[46px] ${
              isActive
                ? 'bg-[#F3B71B] text-black border-[#F3B71B] font-bold shadow-sm'
                : 'bg-[#222222] text-neutral-300 border-neutral-800 hover:border-neutral-700 hover
:bg-[#282828]'
            }`}
          >
            <div className="flex items-center justify-between gap-1">
              <span className="text-xs truncate">{cat.label}</span>
              <span
                className={`text-[10px] font-mono px-1 py-0.2 rounded font-bold ${
                  isActive ? 'bg-black text-[#F3B71B]' : 'bg-[#181818] text-neutral-400'
                }`}
                title={`${count} active approved listings`}
              >
                {count}
              </span>
            </div>
          </button>
        );
      })}
    </div>

    {/* Sub-campus quick selector strip */}
    <div className="pt-2 border-t border-neutral-800/80">
      <div className="flex items-center gap-1.5 overflow-x-auto no-scrollbar py-0.5">
        <span className="text-[10px] uppercase font-bold text-neutral-400 tracking-wider shrink-0
mr-1">
          Campuses:
        </span>
```

```
        <button
          type="button"
          onClick={() => onSelectUniversity('all')}
          className={`whitespace-nowrap px-2.5 py-1 rounded-lg text-[11px] font-semibold transitio
n-all shrink-0 ${
            selectedUniversity === 'all'
              ? 'bg-[#F3B71B]/20 text-[#F3B71B] border border-[#F3B71B]/40 font-bold'
              : 'bg-[#242424] text-neutral-400 hover:text-white border border-neutral-800'
          }`}
        >
          {getAllButtonLabel()}
        </button>

        {filteredCampuses.map((uni) => {
          const isUniActive = selectedUniversity === uni.id;
          return (
            <button
              key={uni.id}
              type="button"
              onClick={() => onSelectUniversity(uni.id)}
              className={`whitespace-nowrap px-2.5 py-1 rounded-lg text-[11px] font-semibold trans
ition-all shrink-0 flex items-center gap-1 ${
                isUniActive
                  ? 'bg-[#F3B71B] text-black font-extrabold shadow-sm'
                  : 'bg-[#242424] text-neutral-300 hover:text-white border border-neutral-800 hove
r:bg-[#2c2c2c]'
              }`}
            >
              <span>{uni.shortName}</span>
              {isUniActive && <Check className="w-3 h-3 stroke-[3]" />}
            </button>
          );
        })}

        {/* Quick Add / Type Campus Pill */}
        <button
          type="button"
          onClick={() => setShowCustomModal(true)}
          className="whitespace-nowrap px-2.5 py-1 rounded-lg text-[11px] font-semibold transition
-all shrink-0 flex items-center gap-1 bg-[#222222] text-[#F3B71B] hover:bg-[#F3B71B]/15 border bor
der-[#F3B71B]/40"
          title="Type your campus if not listed (e.g. KSII uni)"
        >
          <Plus className="w-3 h-3" />
          <span>Type Campus...</span>
        </button>
      </div>
    </div>

    {/* Inline Quick Modal for Custom Campus */}
    {showCustomModal && (
      <div className="pt-2 border-t border-neutral-800 animate-in fade-in duration-150">
        <form onSubmit={handleApplyCustom} className="p-3 bg-[#1C1C1C] rounded-xl border border-[#
F3B71B]/50 space-y-2">
          <div className="flex items-center justify-between text-xs">
            <span className="font-bold text-[#F3B71B] flex items-center gap-1.5">
              <PenTool className="w-3.5 h-3.5" />
              Type Your Campus (e.g. KSII uni, Zetech, KCA...)
            </span>
            <button
              type="button"
              onClick={() => setShowCustomModal(false)}
              className="text-neutral-400 hover:text-white p-1"
            >
              <X className="w-3.5 h-3.5" />
            </button>
          </div>

          <div className="flex flex-col sm:flex-row items-stretch sm:items-center gap-2">
```

```
            <input
              type="text"
              autoFocus
              required
              value={customCampusName}
              onChange={(e) => setCustomCampusName(e.target.value)}
              placeholder="Enter campus name (e.g. KSII uni, Maasai Mara...)"
              className="flex-1 px-3 py-1.5 bg-[#262626] text-white text-xs rounded-lg border bord
  er-neutral-700 focus:border-[#F3B71B] outline-none"
            />

            <select
              value={customCategory}
              onChange={(e) => setCustomCategory(e.target.value as any)}
              className="px-2.5 py-1.5 bg-[#262626] text-white text-xs rounded-lg border border-ne
  utral-700 outline-none"
            >
              <option value="university">   University</option>
              <option value="kmtc">   KMTC</option>
              <option value="polytechnic">   Polytechnic</option>
              <option value="tvet">   TVET</option>
            </select>

            <button
              type="submit"
              disabled={!customCampusName.trim()}
              className="px-4 py-1.5 bg-[#F3B71B] hover:bg-[#dca415] disabled:opacity-50 text-blac
  k font-extrabold text-xs rounded-lg whitespace-nowrap transition-colors"
            >
              Filter Feed
            </button>
          </div>
        </form>
      </div>
    )}
  </div>
  );
};
```

```
import React, { useState } from 'react';
import {
  MessageSquareShare,
  MapPin,
  Clock,
  Plus,
  ThumbsUp,
  MessageCircle,
  AlertTriangle,
  BookOpen,
  Car,
  HelpCircle,
  X,
  Send
} from 'lucide-react';
import { CommunityPost } from '../types';

interface CampusBuzzFeedProps {
  posts: CommunityPost[];
  onAddPost: (post: CommunityPost) => void;
  selectedUniversity: string;
  isVerifiedStudent: boolean;
}

export const CampusBuzzFeed: React.FC<CampusBuzzFeedProps> = ({
  posts,
  onAddPost,
  selectedUniversity,
  isVerifiedStudent,
}) => {
  const [activeFilter, setActiveFilter] = useState<'all' | 'lost_found' | 'study_group' | 'rideshare
  ' | 'alert'>('all');
  const [showNewPostModal, setShowNewPostModal] = useState(false);
  const [likesMap, setLikesMap] = useState<Record<string, number>>({});

  // New post state
  const [postTitle, setPostTitle] = useState('');
  const [postContent, setPostContent] = useState('');
  const [postType, setPostType] = useState<'lost_found' | 'study_group' | 'rideshare' | 'alert'>('lo
  st_found');
  const [authorName, setAuthorName] = useState('');
  const [campusName, setCampusName] = useState('Main Campus');

  const filteredPosts = posts.filter(p => {
    if (activeFilter !== 'all' && p.type !== activeFilter) return false;
    if (selectedUniversity !== 'all' && p.universityId !== selectedUniversity) return false;
    return true;
  });

  const handleLike = (id: string) => {
    setLikesMap(prev => ({
      ...prev,
      [id]: (prev[id] || 0) + 1
    }));
  };

  const handleCreatePost = (e: React.FormEvent) => {
    e.preventDefault();
    if (!postTitle.trim() || !postContent.trim()) return;

    const newPost: CommunityPost = {
      id: `buzz-${Date.now()}`,
      type: postType,
      title: postTitle.trim(),
      content: postContent.trim(),
      author: authorName.trim() || 'Comrade Student',
      authorRole: isVerifiedStudent ? 'Verified Comrade' : 'Campus Member',
      universityId: selectedUniversity,
      campusName: campusName.trim() || 'Main Campus',
      timeAgo: 'Just now',
```

```
    repliesCount: 0,
    likesCount: 1,
    statusTag: postType === 'lost_found' ? 'LOST & FOUND' : postType === 'study_group' ? 'STUDY SQ
UAD' : postType === 'rideshare' ? 'CARPOOL' : 'CAMPUS ALERT',
  };

  onAddPost(newPost);
  setShowNewPostModal(false);
  setPostTitle('');
  setPostContent('');
};

return (
  <div className="space-y-4">
    {/* Header and Filter pills */}
    <div className="flex flex-col sm:flex-row sm:items-center justify-between gap-3">
      <div>
        <h2 className="text-lg font-bold text-white font-heading flex items-center gap-2">
          <MessageSquareShare className="w-5 h-5 text-[#F3B71B]" />
          <span>Campus Buzz & Noticeboard</span>
        </h2>
        <p className="text-xs text-neutral-400">
          Real-time student lost & found, study squads, carpools, and campus safety tips
        </p>
      </div>

      <button
        type="button"
        onClick={() => setShowNewPostModal(true)}
        className="self-start sm:self-auto px-3.5 py-2 rounded-xl bg-[#F3B71B] hover:bg-[#dca415]
text-black font-extrabold text-xs flex items-center gap-1.5 shadow-md shadow-[#F3B71B]/10 active:s
cale-95 transition-all"
      >
        <Plus className="w-4 h-4 stroke-[3]" />
        <span>Post to Campus Buzz</span>
      </button>
    </div>

    {/* Filter Tabs */}
    <div className="flex items-center gap-2 overflow-x-auto no-scrollbar pb-1">
      {[
        { id: 'all', label: 'All Buzz' },
        { id: 'lost_found', label: '   Lost & Found' },
        { id: 'study_group', label: '   Study Groups' },
        { id: 'rideshare', label: '   Carpool / Rideshare' },
        { id: 'alert', label: '   Safety Alerts' },
      ].map((f) => (
        <button
          key={f.id}
          type="button"
          onClick={() => setActiveFilter(f.id as any)}
          className={`whitespace-nowrap px-3 py-1.5 text-xs font-semibold rounded-xl transition-al
l ${
            activeFilter === f.id
              ? 'bg-[#F3B71B] text-black font-bold shadow-sm'
              : 'bg-[#1E1E1E] border border-neutral-800 text-neutral-300 hover:bg-[#252525]'
          }`}
        >
          {f.label}
        </button>
      ))}
    </div>

    {/* Posts Feed */}
    <div className="space-y-3">
      {filteredPosts.length === 0 ? (
        <div className="p-8 text-center bg-[#1A1A1A] rounded-2xl border border-neutral-800 text-ne
utral-400 text-xs">
          No community posts found for this campus filter. Be the first comrade to post!
        </div>
```

```
      ) : (
        filteredPosts.map((post) => {
          const addedLikes = likesMap[post.id] || 0;
          return (
            <div
              key={post.id}
              className="bg-[#1E1E1E] rounded-2xl border border-neutral-800 p-4 hover:border-[#F3B
71B]/50 transition-all shadow-[0_2px_8px_rgba(0,0,0,0.2)] space-y-2.5"
            >
              <div className="flex items-start justify-between gap-2">
                <div className="flex items-center gap-2">
                  <span className="text-xs font-bold text-[#F3B71B] bg-[#F3B71B]/15 border border-
[#F3B71B]/30 px-2 py-0.5 rounded-md font-mono">
                    {post.statusTag || post.type.toUpperCase()}
                  </span>
                  <span className="text-xs text-neutral-600"> </span>
                  <span className="text-xs text-neutral-400 flex items-center gap-1">
                    <MapPin className="w-3 h-3 text-[#F3B71B]" />
                    {post.campusName}
                  </span>
                </div>
                <span className="text-[11px] text-neutral-500 font-mono">{post.timeAgo}</span>
              </div>

              <h3 className="text-sm font-bold text-white leading-snug">{post.title}</h3>

              <p className="text-xs text-neutral-300 leading-relaxed whitespace-pre-line">
                {post.content}
              </p>

              <div className="pt-2 border-t border-neutral-800 flex items-center justify-between t
ext-xs text-neutral-400">
                <div className="flex items-center gap-1.5 font-medium text-neutral-300">
                  <span>By {post.author}</span>
                  <span className="text-neutral-600"> </span>
                  <span className="text-[11px] text-[#F3B71B] font-mono">{post.authorRole}</span>
                </div>

                <div className="flex items-center gap-3">
                  <button
                    type="button"
                    onClick={() => handleLike(post.id)}
                    className="flex items-center gap-1 hover:text-[#F3B71B] transition-colors"
                  >
                    <ThumbsUp className="w-3.5 h-3.5" />
                    <span>{post.likesCount + addedLikes}</span>
                  </button>
                  <span className="flex items-center gap-1">
                    <MessageCircle className="w-3.5 h-3.5" />
                    <span>{post.repliesCount} replies</span>
                  </span>
                </div>
              </div>
            </div>
          );
        })
      )}
    </div>

    {/* New Post Modal */}
    {showNewPostModal && (
      <div className="fixed inset-0 z-50 flex items-center justify-center p-4 bg-black/80 backdrop
-blur-sm animate-in fade-in duration-150">
        <div className="w-full max-w-md bg-[#1A1A1A] text-slate-100 rounded-3xl shadow-2xl border
border-neutral-800 overflow-hidden">
          <div className="px-5 py-3.5 border-b border-neutral-800 bg-[#141414] flex items-center j
ustify-between">
            <h3 className="font-bold text-sm text-white">Post to Campus Buzz</h3>
            <button
              type="button"
```

```
              onClick={() => setShowNewPostModal(false)}
              className="p-1 rounded-lg text-neutral-400 hover:text-white"
            >
              <X className="w-4 h-4" />
            </button>
          </div>

          <form onSubmit={handleCreatePost} className="p-5 space-y-3">
            <div>
              <label className="block text-xs font-bold text-neutral-300 mb-1">Post Type</label>
              <div className="grid grid-cols-2 gap-2 text-xs">
                <button
                  type="button"
                  onClick={() => setPostType('lost_found')}
                  className={`p-2 rounded-xl border text-left flex items-center gap-1.5 ${
                    postType === 'lost_found' ? 'bg-[#F3B71B]/20 border-[#F3B71B] font-bold text-[
#F3B71B]' : 'bg-[#242424] border-neutral-700 text-neutral-300'
                  }`}
                >
                  <HelpCircle className="w-3.5 h-3.5" />
                  <span>Lost & Found</span>
                </button>

                <button
                  type="button"
                  onClick={() => setPostType('study_group')}
                  className={`p-2 rounded-xl border text-left flex items-center gap-1.5 ${
                    postType === 'study_group' ? 'bg-[#F3B71B]/20 border-[#F3B71B] font-bold text-
[#F3B71B]' : 'bg-[#242424] border-neutral-700 text-neutral-300'
                  }`}
                >
                  <BookOpen className="w-3.5 h-3.5" />
                  <span>Study Squad</span>
                </button>

                <button
                  type="button"
                  onClick={() => setPostType('rideshare')}
                  className={`p-2 rounded-xl border text-left flex items-center gap-1.5 ${
                    postType === 'rideshare' ? 'bg-[#F3B71B]/20 border-[#F3B71B] font-bold text-[#
F3B71B]' : 'bg-[#242424] border-neutral-700 text-neutral-300'
                  }`}
                >
                  <Car className="w-3.5 h-3.5" />
                  <span>Carpool</span>
                </button>

                <button
                  type="button"
                  onClick={() => setPostType('alert')}
                  className={`p-2 rounded-xl border text-left flex items-center gap-1.5 ${
                    postType === 'alert' ? 'bg-[#F3B71B]/20 border-[#F3B71B] font-bold text-[#F3B7
1B]' : 'bg-[#242424] border-neutral-700 text-neutral-300'
                  }`}
                >
                  <AlertTriangle className="w-3.5 h-3.5" />
                  <span>Safety Alert</span>
                </button>
              </div>
            </div>

            <div>
              <label className="block text-xs font-bold text-neutral-300 mb-1">Title</label>
              <input
                type="text"
                required
                value={postTitle}
                onChange={(e) => setPostTitle(e.target.value)}
                placeholder="e.g. Lost Student ID card near Chiromo library"
                className="w-full px-3 py-2 text-xs bg-[#242424] text-white rounded-xl border bord
```

```
  er-neutral-700 outline-none focus:border-[#F3B71B]"
                />
              </div>

              <div>
                <label className="block text-xs font-bold text-neutral-300 mb-1">Details & Descripti
  on</label>
                <textarea
                  rows={3}
                  required
                  value={postContent}
                  onChange={(e) => setPostContent(e.target.value)}
                  placeholder="Explain what happened, details, contacts, or meetup spot..."
                  className="w-full px-3 py-2 text-xs bg-[#242424] text-white rounded-xl border bord
  er-neutral-700 outline-none focus:border-[#F3B71B]"
                />
              </div>

              <div className="grid grid-cols-2 gap-2">
                <div>
                  <label className="block text-xs font-bold text-neutral-300 mb-1">Your Name</label>
                  <input
                    type="text"
                    value={authorName}
                    onChange={(e) => setAuthorName(e.target.value)}
                    placeholder="e.g. Mercy Chemtai"
                    className="w-full px-3 py-1.5 text-xs bg-[#242424] text-white rounded-xl border
  border-neutral-700 outline-none focus:border-[#F3B71B]"
                  />
                </div>
                <div>
                  <label className="block text-xs font-bold text-neutral-300 mb-1">Campus</label>
                  <input
                    type="text"
                    value={campusName}
                    onChange={(e) => setCampusName(e.target.value)}
                    placeholder="e.g. Main Campus"
                    className="w-full px-3 py-1.5 text-xs bg-[#242424] text-white rounded-xl border
  border-neutral-700 outline-none focus:border-[#F3B71B]"
                  />
                </div>
              </div>

              <button
                type="submit"
                className="w-full py-2.5 rounded-xl bg-[#F3B71B] hover:bg-[#dca415] text-black font-
  extrabold text-xs shadow-md shadow-[#F3B71B]/20 active:scale-[0.98] transition-all flex items-cent
  er justify-center gap-2 mt-2"
              >
                <Send className="w-3.5 h-3.5" />
                <span>Post to Campus Buzz</span>
              </button>
            </form>
          </div>
        </div>
      )}
    </div>
  );
};
```

```
import React, { useState } from 'react';
import {
  X,
  CheckCircle,
  XCircle,
  Database,
  Users,
  Clock,
  CreditCard,
  ShieldCheck,
  AlertTriangle,
  ArrowRight,
  Eye,
  Trash2,
  Sparkles
} from 'lucide-react';
import { Listing, User } from '../types';

interface AdminApprovalModalProps {
  isOpen: boolean;
  onClose: () => void;
  listings: Listing[];
  users: User[];
  onApproveListing: (id: string) => void;
  onRejectListing: (id: string) => void;
  onMarkFeePaid: (id: string, mpesaRef: string) => void;
  onOpenListingDetail: (listing: Listing) => void;
}

export const AdminApprovalModal: React.FC<AdminApprovalModalProps> = ({
  isOpen,
  onClose,
  listings,
  users,
  onApproveListing,
  onRejectListing,
  onMarkFeePaid,
  onOpenListingDetail,
}) => {
  if (!isOpen) return null;

  const [activeTab, setActiveTab] = useState<'pending' | 'active' | 'users' | 'schema'>('pending');

  const pendingListings = listings.filter(l => !l.isApproved);
  const activeListings = listings.filter(l => l.isApproved);

  const formatPrice = (price: number) => {
    return new Intl.NumberFormat('en-KE').format(price);
  };

  return (
    <div className="fixed inset-0 z-50 flex items-center justify-center p-3 sm:p-5 bg-black/85 backd
  rop-blur-md animate-in fade-in duration-150 overflow-y-auto">
      <div
        className="w-full max-w-3xl bg-[#1A1A1A] text-slate-100 rounded-3xl shadow-2xl border border
  -neutral-800 overflow-hidden flex flex-col max-h-[92vh] my-auto animate-in zoom-in-95 duration-150
  "
        onClick={(e) => e.stopPropagation()}
      >
        {/* Top Header */}
        <div className="p-5 border-b border-neutral-800 bg-[#141414] flex items-center justify-betwe
  en">
          <div className="flex items-center gap-2.5">
            <div className="w-10 h-10 rounded-2xl overflow-hidden p-0.5 bg-gradient-to-br from-[#0F2
  D59] via-[#08182F] to-black border border-cyan-500/40 shadow-sm flex items-center justify-center s
  hrink-0">
              <img
                src="/src/assets/images/studspot_official_icon_1791805148976.jpg"
                alt="STUDSPOT Official Logo"
                className="w-full h-full object-cover rounded-xl"
```

```
            />
          </div>
          <div>
            <div className="flex items-center gap-2">
              <h2 className="text-base font-bold text-white font-heading">
                STUDSPOT Adalo Database & Admin Console
              </h2>
              <span className="text-[10px] bg-[#F3B71B]/20 text-[#F3B71B] font-mono px-2 py-0.5 ro
unded font-bold">
                Test Workflow
              </span>
            </div>
            <p className="text-[11px] text-neutral-400">
              Manage isApproved (Boolean) database properties, KSh 80 listing fees & user records
            </p>
          </div>
        </div>
        <button
          type="button"
          onClick={onClose}
          className="p-1.5 rounded-xl text-neutral-400 hover:text-white hover:bg-neutral-800 trans
ition-colors"
        >
          <X className="w-5 h-5" />
        </button>
      </div>

      {/* Console Nav Tabs */}
      <div className="px-5 pt-3 border-b border-neutral-800 bg-[#171717] flex items-center gap-2 o
verflow-x-auto no-scrollbar">
        <button
          type="button"
          onClick={() => setActiveTab('pending')}
          className={`px-3.5 py-2 text-xs font-bold rounded-t-xl transition-all border-b-2 flex it
ems-center gap-1.5 whitespace-nowrap ${
            activeTab === 'pending'
              ? 'border-[#F3B71B] text-[#F3B71B] bg-[#242424]'
              : 'border-transparent text-neutral-400 hover:text-white'
          }`}
        >
          <Clock className="w-3.5 h-3.5" />
          <span>Pending Approvals</span>
          <span className={`text-[10px] px-1.5 py-0.2 rounded-full font-mono ${
            pendingListings.length > 0 ? 'bg-amber-500 text-black font-bold' : 'bg-neutral-700 tex
t-neutral-300'
          }`}>
            {pendingListings.length}
          </span>
        </button>

        <button
          type="button"
          onClick={() => setActiveTab('active')}
          className={`px-3.5 py-2 text-xs font-bold rounded-t-xl transition-all border-b-2 flex it
ems-center gap-1.5 whitespace-nowrap ${
            activeTab === 'active'
              ? 'border-[#F3B71B] text-[#F3B71B] bg-[#242424]'
              : 'border-transparent text-neutral-400 hover:text-white'
          }`}
        >
          <CheckCircle className="w-3.5 h-3.5" />
          <span>Public Feed (isApproved: True)</span>
          <span className="text-[10px] px-1.5 py-0.2 rounded-full bg-neutral-700 text-neutral-300
font-mono">
            {activeListings.length}
          </span>
        </button>

        <button
          type="button"
```

```
          onClick={() => setActiveTab('users')}
          className={`px-3.5 py-2 text-xs font-bold rounded-t-xl transition-all border-b-2 flex it
ems-center gap-1.5 whitespace-nowrap ${
            activeTab === 'users'
              ? 'border-[#F3B71B] text-[#F3B71B] bg-[#242424]'
              : 'border-transparent text-neutral-400 hover:text-white'
          }`}
        >
          <Users className="w-3.5 h-3.5" />
          <span>Users Collection</span>
          <span className="text-[10px] px-1.5 py-0.2 rounded-full bg-neutral-700 text-neutral-300
font-mono">
            {users.length}
          </span>
        </button>

        <button
          type="button"
          onClick={() => setActiveTab('schema')}
          className={`px-3.5 py-2 text-xs font-bold rounded-t-xl transition-all border-b-2 flex it
ems-center gap-1.5 whitespace-nowrap ${
            activeTab === 'schema'
              ? 'border-[#F3B71B] text-[#F3B71B] bg-[#242424]'
              : 'border-transparent text-neutral-400 hover:text-white'
          }`}
        >
          <Database className="w-3.5 h-3.5" />
          <span>Adalo Collections Schema</span>
        </button>
      </div>

      {/* Tab Contents */}
      <div className="overflow-y-auto flex-1 p-5 space-y-4">
        {/* TAB 1: PENDING APPROVALS */}
        {activeTab === 'pending' && (
          <div className="space-y-3">
            <div className="p-3 bg-amber-500/10 rounded-2xl border border-amber-500/30 flex items-
start gap-2.5 text-xs text-amber-200">
              <AlertTriangle className="w-4 h-4 text-amber-400 shrink-0 mt-0.5" />
              <div>
                <span className="font-bold">Workflow Step: Admin Manual Approval in Database</span
>
                <p className="text-[11px] text-amber-300 mt-0.5">
                  Per the technical specification, all submitted listings default to <code classNa
me="bg-black/40 px-1 py-0.5 rounded text-[#F3B71B]">isApproved == False</code> and are hidden from
 the public feed until the administrator verifies the non-refundable KSh 80 M-Pesa fee and clicks
<strong>Approve</strong>.
                </p>
              </div>
            </div>

            {pendingListings.length === 0 ? (
              <div className="p-8 text-center bg-[#242424] rounded-2xl border border-neutral-800 t
ext-neutral-400 text-xs">
                <CheckCircle className="w-8 h-8 text-emerald-400 mx-auto mb-2" />
                <p className="font-bold text-white">All caught up! Zero pending approvals.</p>
                <p className="text-[11px] text-neutral-400 mt-1">
                  Try posting a new Marketplace item, Hostel, or Job from the app to test the pend
ing redirect and approval flow.
                </p>
              </div>
            ) : (
              pendingListings.map((item) => (
                <div
                  key={item.id}
                  className="p-4 bg-[#242424] rounded-2xl border border-neutral-700/80 space-y-3 h
over:border-neutral-600 transition-all"
                >
                  <div className="flex flex-col sm:flex-row sm:items-start justify-between gap-3">
                    <div className="flex items-start gap-3 min-w-0">
```

```
                    <img
                      src={item.image}
                      alt={item.title}
                      className="w-14 h-14 rounded-xl object-cover shrink-0 bg-neutral-800"
                    />
                    <div className="min-w-0">
                      <div className="flex items-center gap-2">
                        <span className="text-[10px] font-bold uppercase tracking-wider text-[#F
3B71B] bg-[#F3B71B]/10 px-2 py-0.2 rounded">
                          {item.category}
                        </span>
                        <span className="text-[11px] text-neutral-400 font-mono">
                          ID: {item.id}
                        </span>
                      </div>
                      <h4 className="font-bold text-sm text-white mt-1 leading-snug line-clamp-1
">
                        {item.title}
                      </h4>
                      <p className="text-xs text-neutral-400 mt-0.5">
                        By {item.seller.name}   {item.campusName}
                      </p>
                    </div>
                  </div>

                  <div className="text-left sm:text-right shrink-0">
                    <div className="text-sm font-black font-mono text-white">
                      KES {formatPrice(item.price)} {item.priceLabel}
                    </div>
                    <div className="text-[11px] font-mono mt-0.5">
                      {item.isFeePaid ? (
                        <span className="text-emerald-400 font-semibold flex items-center sm:jus
tify-end gap-1">
                          <CheckCircle className="w-3 h-3" />
                          Fee Paid ({item.mpesaRef || 'Ref Verified'})
                        </span>
                      ) : (
                        <span className="text-amber-400 font-semibold">Awaiting KSh 80 Payment</
span>
                      )}
                    </div>
                  </div>
                </div>

                {/* Database status row & action buttons */}
                <div className="pt-3 border-t border-neutral-800 flex flex-wrap items-center jus
tify-between gap-2 text-xs">
                  <div className="flex items-center gap-2">
                    <span className="text-neutral-400 text-[11px]">Database Status:</span>
                    <span className="font-mono text-[11px] font-bold text-rose-400 bg-rose-500/1
0 px-2 py-0.5 rounded border border-rose-500/20">
                      isApproved: False
                    </span>
                  </div>

                  <div className="flex items-center gap-2">
                    {!item.isFeePaid && (
                      <button
                        type="button"
                        onClick={() => onMarkFeePaid(item.id, 'QK-MANUAL-VERIFY')}
                        className="px-3 py-1.5 bg-neutral-800 hover:bg-neutral-700 text-neutral-
200 text-xs rounded-xl transition-colors font-medium"
                      >
                        Mark KSh 80 Paid
                      </button>
                    )}

                    <button
                      type="button"
                      onClick={() => onRejectListing(item.id)}
```

```
                      className="px-3 py-1.5 bg-rose-500/10 hover:bg-rose-500/20 text-rose-300 t
ext-xs rounded-xl transition-colors border border-rose-500/30 flex items-center gap-1"
                    >
                      <XCircle className="w-3.5 h-3.5" />
                      <span>Reject</span>
                    </button>

                    <button
                      type="button"
                      onClick={() => onApproveListing(item.id)}
                      className="px-4 py-1.5 bg-[#F3B71B] hover:bg-[#dca415] text-black font-ext
rabold text-xs rounded-xl transition-all shadow-md active:scale-95 flex items-center gap-1.5"
                    >
                      <CheckCircle className="w-4 h-4" />
                      <span>Approve & Activate Live</span>
                    </button>
                  </div>
                </div>
              </div>
            ))
          )}
        </div>
      )}

      {/* TAB 2: ACTIVE PUBLIC FEED */}
      {activeTab === 'active' && (
        <div className="space-y-2.5">
          <div className="text-xs text-neutral-400 flex items-center justify-between">
            <span>Listings currently visible on the Home Screen Feed (filtered where isApproved
== True):</span>
            <span className="font-mono text-[#F3B71B] font-bold">{activeListings.length} Active
Records</span>
          </div>

          {activeListings.map((item) => (
            <div
              key={item.id}
              className="p-3 bg-[#242424] rounded-2xl border border-neutral-800 flex items-cente
r justify-between gap-3 text-xs"
            >
              <div className="flex items-center gap-3 min-w-0">
                <img
                  src={item.image}
                  alt={item.title}
                  className="w-10 h-10 rounded-lg object-cover shrink-0"
                />
                <div className="min-w-0">
                  <h5 className="font-bold text-white truncate text-xs">{item.title}</h5>
                  <p className="text-[11px] text-neutral-400 mt-0.5">
                    {item.category}   KES {formatPrice(item.price)}   By {item.seller.name}
                  </p>
                </div>
              </div>

              <div className="flex items-center gap-2 shrink-0">
                <span className="font-mono text-[11px] text-emerald-400 bg-emerald-500/10 px-2 p
y-0.5 rounded border border-emerald-500/20 font-bold hidden sm:inline">
                  isApproved: True
                </span>
                <button
                  type="button"
                  onClick={() => onOpenListingDetail(item)}
                  className="p-1.5 rounded-lg bg-neutral-800 hover:bg-neutral-700 text-neutral-3
00"
                  title="View listing detail"
                >
                  <Eye className="w-3.5 h-3.5" />
                </button>
                <button
                  type="button"
```

```
                    onClick={() => onRejectListing(item.id)}
                    className="p-1.5 rounded-lg bg-rose-500/10 hover:bg-rose-500/20 text-rose-400"
                    title="Deactivate listing"
                  >
                    <Trash2 className="w-3.5 h-3.5" />
                  </button>
                </div>
              </div>
            ))}
          </div>
        )}

        {/* TAB 3: USERS COLLECTION */}
        {activeTab === 'users' && (
          <div className="space-y-3">
            <div className="text-xs text-neutral-400">
              Adalo Users Collection with mandatory terms consent records:
            </div>

            <div className="overflow-x-auto">
              <table className="w-full text-left text-xs text-neutral-300">
                <thead className="bg-[#141414] text-neutral-400 text-[10px] uppercase font-mono bo
rder-b border-neutral-800">
                  <tr>
                    <th className="p-2.5">User</th>
                    <th className="p-2.5">Email</th>
                    <th className="p-2.5">Campus</th>
                    <th className="p-2.5">Role</th>
                    <th className="p-2.5">Terms Consent</th>
                  </tr>
                </thead>
                <tbody className="divide-y divide-neutral-800 font-mono">
                  {users.map((u) => (
                    <tr key={u.id} className="hover:bg-neutral-800/40">
                      <td className="p-2.5 font-sans font-bold text-white">{u.fullName}</td>
                      <td className="p-2.5 text-neutral-400">{u.email}</td>
                      <td className="p-2.5 text-neutral-300">{u.campusName}</td>
                      <td className="p-2.5">
                        <span className={`px-1.5 py-0.5 rounded text-[10px] font-bold ${
                          u.role === 'admin' ? 'bg-[#F3B71B]/20 text-[#F3B71B]' : 'bg-neutral-800
text-neutral-300'
                        }`}>
                          {u.role.toUpperCase()}
                        </span>
                      </td>
                      <td className="p-2.5">
                        {u.agreedToTerms ? (
                          <span className="text-emerald-400 font-bold flex items-center gap-1 text
-[11px]">
                            <CheckCircle className="w-3.5 h-3.5" /> True
                          </span>
                        ) : (
                          <span className="text-rose-400 font-bold">False</span>
                        )}
                      </td>
                    </tr>
                  ))}
                </tbody>
              </table>
            </div>
          </div>
        )}

        {/* TAB 4: ADALO COLLECTIONS SCHEMA */}
        {activeTab === 'schema' && (
          <div className="space-y-3 text-xs">
            <div className="p-3 bg-[#242424] rounded-2xl border border-neutral-800 space-y-2">
              <h4 className="font-bold text-white text-sm">Adalo Database Architecture Map</h4>
              <p className="text-neutral-400 text-xs">
                All 4 required listing collections configured with the mandatory <code className="
```

```
text-[#F3B71B]">isApproved (Boolean, Default: False)</code> property:
              </p>
            </div>

            <div className="grid grid-cols-1 sm:grid-cols-2 gap-3">
              <div className="p-3 bg-[#242424] rounded-2xl border border-neutral-800 space-y-1.5">
                <span className="font-bold text-[#F3B71B] font-mono text-xs block">Collection: Use
rs</span>
                <ul className="text-[11px] text-neutral-400 space-y-0.5 font-mono">
                  <li>  id (Text)</li>
                  <li>  fullName (Text)</li>
                  <li>  email (Email)</li>
                  <li>  universityId (Text)</li>
                  <li>  agreedToTerms (Boolean, Mandatory)</li>
                  <li>  role (Text)</li>
                </ul>
              </div>

              <div className="p-3 bg-[#242424] rounded-2xl border border-neutral-800 space-y-1.5">
                <span className="font-bold text-[#F3B71B] font-mono text-xs block">Collection: Lis
tings (Marketplace)</span>
                <ul className="text-[11px] text-neutral-400 space-y-0.5 font-mono">
                  <li>  title (Text)</li>
                  <li>  price (Number, KES)</li>
                  <li>  category (Text)</li>
                  <li>  sellerId (Relationship &gt; User)</li>
                  <li className="text-[#F3B71B] font-bold">  isApproved (Boolean, Default: False)<
/li>
                  <li>  isFeePaid (Boolean)</li>
                  <li>  mpesaRef (Text)</li>
                </ul>
              </div>

              <div className="p-3 bg-[#242424] rounded-2xl border border-neutral-800 space-y-1.5">
                <span className="font-bold text-[#F3B71B] font-mono text-xs block">Collection: Hou
sing (Hostels)</span>
                <ul className="text-[11px] text-neutral-400 space-y-0.5 font-mono">
                  <li>  title (Text)</li>
                  <li>  monthlyRent (Number)</li>
                  <li>  hostelType (Text)</li>
                  <li>  distanceToGate (Text)</li>
                  <li className="text-[#F3B71B] font-bold">  isApproved (Boolean, Default: False)<
/li>
                  <li>  isFeePaid (Boolean)</li>
                </ul>
              </div>

              <div className="p-3 bg-[#242424] rounded-2xl border border-neutral-800 space-y-1.5">
                <span className="font-bold text-[#F3B71B] font-mono text-xs block">Collection: Job
s (Gigs)</span>
                <ul className="text-[11px] text-neutral-400 space-y-0.5 font-mono">
                  <li>  title (Text)</li>
                  <li>  compensation (Number)</li>
                  <li>  skillsNeeded (List)</li>
                  <li className="text-[#F3B71B] font-bold">  isApproved (Boolean, Default: False)<
/li>
                  <li>  isFeePaid (Boolean)</li>
                </ul>
              </div>
            </div>
          </div>
        )}
      </div>

      {/* Modal Footer */}
      <div className="p-4 border-t border-neutral-800 bg-[#141414] flex items-center justify-betwe
en">
        <div className="text-[11px] text-neutral-400">
          Adalo Engine Status: All collections synced with real-time UI
        </div>
```

```
          <button
            type="button"
            onClick={onClose}
            className="px-4 py-2 bg-neutral-800 hover:bg-neutral-700 text-white font-bold text-xs ro
  unded-xl transition-colors"
          >
            Close Admin Console
          </button>
        </div>
      </div>
    </div>
  );
};
```

```
import React, { useState } from 'react';
import { X, ShieldCheck, UserCheck, AlertCircle, Lock, Mail, Phone, School, CheckSquare, Square, Pen
  Tool, GraduationCap } from 'lucide-react';
import { User, InstitutionType } from '../types';
import { UNIVERSITIES } from '../data/seedData';
import { saveCustomCampus, getAllCampuses } from '../utils/campusStore';

interface SignUpModalProps {
  isOpen: boolean;
  onClose: () => void;
  onUserRegistered: (user: User) => void;
  onOpenTerms: () => void;
}

export const SignUpModal: React.FC<SignUpModalProps> = ({
  isOpen,
  onClose,
  onUserRegistered,
  onOpenTerms,
}) => {
  if (!isOpen) return null;

  const [mode, setMode] = useState<'signup' | 'login'>('signup');
  const [fullName, setFullName] = useState('');
  const [email, setEmail] = useState('');
  const [phone, setPhone] = useState('');
  const [universityId, setUniversityId] = useState('uon');
  const [campusName, setCampusName] = useState('Main Campus');
  const [studentRegNo, setStudentRegNo] = useState('');
  const [agreedToTerms, setAgreedToTerms] = useState(false);
  const [errorMsg, setErrorMsg] = useState('');

  // Custom campus typing support
  const [isCustomCampus, setIsCustomCampus] = useState(false);
  const [customCampusName, setCustomCampusName] = useState('');
  const [customCampusZone, setCustomCampusZone] = useState('Main Campus');
  const [customInstitutionType, setCustomInstitutionType] = useState<InstitutionType>('university');

  const allAvailableCampuses = getAllCampuses();
  const selectedUni = allAvailableCampuses.find(u => u.id === universityId) || allAvailableCampuses[
  1] || UNIVERSITIES[1];

  const handleUniversityChange = (id: string) => {
    if (id === 'other_custom') {
      setIsCustomCampus(true);
      setUniversityId('other_custom');
      return;
    }
    setIsCustomCampus(false);
    setUniversityId(id);
    const uni = allAvailableCampuses.find(u => u.id === id);
    if (uni && uni.campuses.length > 0) {
      setCampusName(uni.campuses[0]);
    }
  };

  const handleSubmit = (e: React.FormEvent) => {
    e.preventDefault();
    setErrorMsg('');

    if (mode === 'signup') {
      // MANDATORY TERMS CONSENT CHECK:
      if (!agreedToTerms) {
        setErrorMsg('You must check and agree to the STUDSPOT Terms & Conditions to register an acco
  unt.');
        return;
      }

      if (!fullName.trim() || !email.trim()) {
        setErrorMsg('Please fill in your name and email address.');
```

```
      return;
    }

    if (isCustomCampus && !customCampusName.trim()) {
      setErrorMsg('Please type your campus or college name.');
      return;
    }

    let finalUniId = universityId;
    let finalCampusName = campusName;

    if (isCustomCampus || universityId === 'other_custom') {
      const typedName = customCampusName.trim() || 'Custom Campus';
      const typedZone = customCampusZone.trim() || 'Main Campus';
      const createdUni = saveCustomCampus(typedName, customInstitutionType, typedZone);
      finalUniId = createdUni.id;
      finalCampusName = `${typedName} (${typedZone})`;
    }

    const newUser: User = {
      id: `usr-${Date.now()}`,
      fullName: fullName.trim(),
      email: email.trim(),
      phone: phone.trim() || '+254700000000',
      universityId: finalUniId,
      campusName: finalCampusName,
      studentRegNo: studentRegNo.trim() || undefined,
      role: 'student',
      agreedToTerms: true,
      createdAt: new Date().toISOString().split('T')[0],
      isVerifiedStudent: !!studentRegNo.trim(),
    };

    onUserRegistered(newUser);
    onClose();
  } else {
    // Login mode demo
    if (!email.trim()) {
      setErrorMsg('Please enter your registered email address.');
      return;
    }

    const existingUser: User = {
      id: `usr-demo-${Date.now()}`,
      fullName: email.split('@')[0] || 'Comrade Student',
      email: email.trim(),
      phone: '+254712345678',
      universityId: 'uon',
      campusName: 'Main Campus',
      role: email.includes('admin') ? 'admin' : 'student',
      agreedToTerms: true,
      createdAt: '2026-09-01',
      isVerifiedStudent: true,
    };

    onUserRegistered(existingUser);
    onClose();
  }
};

const handleQuickDemoUser = (role: 'student' | 'admin') => {
  const demoUser: User = {
    id: role === 'admin' ? 'usr-admin' : 'usr-demo-student',
    fullName: role === 'admin' ? 'STUDSPOT Platform Admin' : 'Faith Chebet (Comrade)',
    email: role === 'admin' ? 'admin@studspot.co.ke' : 'fchebet@students.uonbi.ac.ke',
    phone: '+254722998877',
    universityId: 'uon',
    campusName: 'Chiromo Campus',
    studentRegNo: role === 'student' ? 'F17/8241/2023' : undefined,
    role: role,
```

```
    agreedToTerms: true,
    createdAt: '2026-09-01',
    isVerifiedStudent: true,
  };
  onUserRegistered(demoUser);
  onClose();
};

return (
  <div className="fixed inset-0 z-50 flex items-center justify-center p-3 sm:p-5 bg-black/80 backd
rop-blur-md animate-in fade-in duration-150 overflow-y-auto">
    <div
      className="w-full max-w-md bg-[#1A1A1A] text-slate-100 rounded-3xl shadow-2xl border border-
neutral-800 overflow-hidden flex flex-col max-h-[94vh] my-auto animate-in zoom-in-95 duration-150"
      onClick={(e) => e.stopPropagation()}
    >
      {/* Header */}
      <div className="p-5 border-b border-neutral-800 bg-[#141414] flex items-center justify-betwe
en">
        <div className="flex items-center gap-2.5">
          <div className="w-9 h-9 rounded-xl overflow-hidden p-0.5 bg-gradient-to-br from-[#0F2D59
] via-[#08182F] to-black border border-cyan-500/40 shadow-sm flex items-center justify-center shri
nk-0">
            <img
              src="/src/assets/images/studspot_official_icon_1791805148976.jpg"
              alt="STUDSPOT Logo"
              className="w-full h-full object-cover rounded-lg"
            />
          </div>
          <div>
            <h2 className="text-base font-bold text-white font-heading">
              {mode === 'signup' ? 'Create STUDSPOT Account' : 'Welcome Back'}
            </h2>
            <p className="text-[11px] text-neutral-400">Campus Marketplace & Directory</p>
          </div>
        </div>
        <button
          type="button"
          onClick={onClose}
          className="p-1.5 rounded-xl text-neutral-400 hover:text-white hover:bg-neutral-800 trans
ition-colors"
        >
          <X className="w-5 h-5" />
        </button>
      </div>

      {/* Form Body */}
      <form onSubmit={handleSubmit} className="overflow-y-auto flex-1 p-5 space-y-4">
        {errorMsg && (
          <div className="p-3 rounded-xl bg-rose-500/10 border border-rose-500/30 text-rose-300 te
xt-xs flex items-start gap-2">
            <AlertCircle className="w-4 h-4 shrink-0 mt-0.5" />
            <span>{errorMsg}</span>
          </div>
        )}

        {mode === 'signup' ? (
          <>
            <div>
              <label className="block text-xs font-bold text-neutral-300 mb-1">Full Legal Name</la
bel>
              <input
                type="text"
                required
                value={fullName}
                onChange={(e) => setFullName(e.target.value)}
                placeholder="e.g. Brenda Awuor"
                className="w-full px-3.5 py-2 text-xs bg-[#242424] text-white rounded-xl border bo
rder-neutral-700 focus:border-[#F3B71B] outline-none"
              />
```

```
            </div>

            <div className="grid grid-cols-2 gap-2.5">
              <div>
                <label className="block text-xs font-bold text-neutral-300 mb-1">Student / Work Em
ail</label>
                <input
                  type="email"
                  required
                  value={email}
                  onChange={(e) => setEmail(e.target.value)}
                  placeholder="name@students.uonbi.ac.ke"
                  className="w-full px-3 py-2 text-xs bg-[#242424] text-white rounded-xl border bo
rder-neutral-700 focus:border-[#F3B71B] outline-none"
                />
              </div>
              <div>
                <label className="block text-xs font-bold text-neutral-300 mb-1">M-Pesa Phone</lab
el>
                <input
                  type="tel"
                  value={phone}
                  onChange={(e) => setPhone(e.target.value)}
                  placeholder="0712 345 678"
                  className="w-full px-3 py-2 text-xs bg-[#242424] text-white rounded-xl border bo
rder-neutral-700 focus:border-[#F3B71B] outline-none font-mono"
                />
              </div>
            </div>

            {/* Institution Selection or Custom Input */}
            <div className="space-y-2">
              <div className="flex items-center justify-between">
                <label className="text-xs font-bold text-neutral-300">
                  Campus / Institution <span className="text-[#F3B71B]">*</span>
                </label>
                <button
                  type="button"
                  onClick={() => {
                    setIsCustomCampus(!isCustomCampus);
                    if (!isCustomCampus && !customCampusName) {
                      setCustomCampusName('');
                    }
                  }}
                  className="text-[11px] text-[#F3B71B] hover:underline font-bold flex items-cente
r gap-1 transition-colors"
                >
                  <PenTool className="w-3 h-3" />
                  <span>{isCustomCampus ? "  Standard List" : "Can't find campus? Type it"}</span>
                </button>
              </div>

              {isCustomCampus ? (
                <div className="bg-[#1F1F1F] border border-[#F3B71B]/50 rounded-2xl p-3 space-y-2.
5 animate-in fade-in duration-150">
                  <div className="flex items-center justify-between text-[11px]">
                    <span className="font-bold text-[#F3B71B] flex items-center gap-1">
                      <GraduationCap className="w-3.5 h-3.5" />
                      Type Your Campus
                    </span>
                    <span className="text-[10px] text-neutral-400">e.g. KSII uni, Zetech...</span>
                  </div>

                  <div className="grid grid-cols-2 gap-2">
                    <div>
                      <input
                        type="text"
                        required={isCustomCampus}
                        value={customCampusName}
                        onChange={(e) => setCustomCampusName(e.target.value)}
```

```
                      placeholder="e.g. KSII uni / Kisii Uni"
                      className="w-full px-2.5 py-1.5 text-xs bg-[#282828] text-white rounded-lg
 border border-neutral-700 focus:border-[#F3B71B] outline-none"
                    />
                  </div>
                  <div>
                    <select
                      value={customInstitutionType}
                      onChange={(e) => setCustomInstitutionType(e.target.value as any)}
                      className="w-full px-2 py-1.5 text-xs bg-[#282828] text-white rounded-lg b
order border-neutral-700 focus:border-[#F3B71B] outline-none"
                    >
                      <option value="university">   University</option>
                      <option value="kmtc">   KMTC</option>
                      <option value="polytechnic">   Poly</option>
                      <option value="tvet">   TVET</option>
                    </select>
                  </div>
                </div>

                <div>
                  <input
                    type="text"
                    value={customCampusZone}
                    onChange={(e) => setCustomCampusZone(e.target.value)}
                    placeholder="Campus Wing/Gate (e.g. Main Campus, Town Campus)"
                    className="w-full px-2.5 py-1.5 text-xs bg-[#282828] text-white rounded-lg b
order border-neutral-700 focus:border-[#F3B71B] outline-none"
                  />
                </div>
              </div>
            ) : (
              <div className="grid grid-cols-2 gap-2.5">
                <div>
                  <select
                    value={universityId}
                    onChange={(e) => handleUniversityChange(e.target.value)}
                    className="w-full px-2.5 py-2 text-xs bg-[#242424] text-white rounded-xl bor
der border-neutral-700 focus:border-[#F3B71B] outline-none"
                  >
                    <optgroup label="  Not in list?">
                      <option value="other_custom">   Type Custom Campus...</option>
                    </optgroup>
                    <optgroup label="Universities">
                      {allAvailableCampuses.filter(u => u.institutionType === 'university').map(
(uni) => (
                        <option key={uni.id} value={uni.id}>{uni.shortName}</option>
                      ))}
                    </optgroup>
                    <optgroup label="KMTC Campuses">
                      {allAvailableCampuses.filter(u => u.institutionType === 'kmtc').map((uni)
=> (
                        <option key={uni.id} value={uni.id}>{uni.shortName}</option>
                      ))}
                    </optgroup>
                    <optgroup label="National Polytechnics">
                      {allAvailableCampuses.filter(u => u.institutionType === 'polytechnic').map
((uni) => (
                        <option key={uni.id} value={uni.id}>{uni.shortName}</option>
                      ))}
                    </optgroup>
                    <optgroup label="TVET Colleges">
                      {allAvailableCampuses.filter(u => u.institutionType === 'tvet').map((uni)
=> (
                        <option key={uni.id} value={uni.id}>{uni.shortName}</option>
                      ))}
                    </optgroup>
                  </select>
                </div>
                <div>
```

```
                  <select
                    value={campusName}
                    onChange={(e) => setCampusName(e.target.value)}
                    className="w-full px-2.5 py-2 text-xs bg-[#242424] text-white rounded-xl bor
der border-neutral-700 focus:border-[#F3B71B] outline-none truncate"
                  >
                    {selectedUni.campuses.map((c, i) => (
                      <option key={i} value={c}>{c}</option>
                    ))}
                  </select>
                </div>
              </div>
            )}
          </div>

          <div>
            <label className="block text-xs font-bold text-neutral-300 mb-1">
              Student Reg Number <span className="text-neutral-500 font-normal">(Optional for ve
rification)</span>
            </label>
            <input
              type="text"
              value={studentRegNo}
              onChange={(e) => setStudentRegNo(e.target.value)}
              placeholder="e.g. F17/8241/2023"
              className="w-full px-3.5 py-2 text-xs bg-[#242424] text-white rounded-xl border bo
rder-neutral-700 focus:border-[#F3B71B] outline-none font-mono"
            />
          </div>

          {/* MANDATORY TERMS & CONDITIONS CHECKBOX */}
          <div className="pt-2 border-t border-neutral-800">
            <label className="flex items-start gap-2.5 p-3 rounded-2xl bg-[#242424] border borde
r-neutral-700 cursor-pointer hover:border-[#F3B71B]/60 transition-colors">
              <input
                type="checkbox"
                checked={agreedToTerms}
                onChange={(e) => setAgreedToTerms(e.target.checked)}
                className="mt-0.5 w-4 h-4 rounded text-[#F3B71B] accent-[#F3B71B] focus:ring-0 c
ursor-pointer"
              />
              <div className="text-xs text-neutral-300 leading-snug">
                <span className="font-semibold text-white">
                  I agree to the STUDSPOT Terms & Conditions
                </span>{' '}
                including the Directory Intermediary Disclaimer, Limitation of Liability Waiver,
 and Non-Refundable KSh 80 listing fee.{' '}
                <button
                  type="button"
                  onClick={(e) => {
                    e.preventDefault();
                    onOpenTerms();
                  }}
                  className="text-[#F3B71B] underline font-bold hover:text-white"
                >
                  Read Terms & Disclaimers
                </button>
              </div>
            </label>
          </div>
        </>
      ) : (
        <>
          <div>
            <label className="block text-xs font-bold text-neutral-300 mb-1">Email Address</labe
l>
            <input
              type="email"
              required
              value={email}
```

```
                onChange={(e) => setEmail(e.target.value)}
                placeholder="name@students.uonbi.ac.ke"
                className="w-full px-3.5 py-2 text-xs bg-[#242424] text-white rounded-xl border bo
rder-neutral-700 focus:border-[#F3B71B] outline-none"
              />
            </div>
            <div>
              <label className="block text-xs font-bold text-neutral-300 mb-1">Password</label>
              <input
                type="password"
                placeholder="        "
                className="w-full px-3.5 py-2 text-xs bg-[#242424] text-white rounded-xl border bo
rder-neutral-700 focus:border-[#F3B71B] outline-none"
              />
            </div>
          </>
        )}

        {/* Submit Button */}
        <button
          type="submit"
          className="w-full py-3 rounded-xl bg-[#F3B71B] hover:bg-[#dca415] text-black font-extrab
old text-xs shadow-lg shadow-[#F3B71B]/20 active:scale-[0.98] transition-all flex items-center jus
tify-center gap-2 mt-3"
        >
          <UserCheck className="w-4 h-4" />
          <span>{mode === 'signup' ? 'Complete Registration' : 'Log In to STUDSPOT'}</span>
        </button>

        {/* Mode Switcher */}
        <div className="text-center pt-2">
          {mode === 'signup' ? (
            <p className="text-xs text-neutral-400">
              Already registered?{' '}
              <button
                type="button"
                onClick={() => setMode('login')}
                className="text-[#F3B71B] font-bold hover:underline"
              >
                Log In
              </button>
            </p>
          ) : (
            <p className="text-xs text-neutral-400">
              Don&apos;t have an account yet?{' '}
              <button
                type="button"
                onClick={() => setMode('signup')}
                className="text-[#F3B71B] font-bold hover:underline"
              >
                Sign Up
              </button>
            </p>
          )}
        </div>

        {/* Quick Demo Logins for easy evaluation */}
        <div className="pt-3 border-t border-neutral-800 text-center">
          <span className="text-[10px] uppercase tracking-wider text-neutral-500 font-bold block m
b-2">
            Quick Evaluator Sign-In
          </span>
          <div className="grid grid-cols-2 gap-2">
            <button
              type="button"
              onClick={() => handleQuickDemoUser('student')}
              className="py-1.5 px-2 bg-[#242424] hover:bg-neutral-700 text-neutral-300 text-xs ro
unded-lg transition-colors border border-neutral-700"
            >
                 Student Comrade
```

```
              </button>
              <button
                type="button"
                onClick={() => handleQuickDemoUser('admin')}
                className="py-1.5 px-2 bg-[#F3B71B]/10 hover:bg-[#F3B71B]/20 text-[#F3B71B] font-sem
  ibold text-xs rounded-lg transition-colors border border-[#F3B71B]/30"
              >
                  Platform Admin
              </button>
            </div>
          </div>
        </form>
      </div>
    </div>
  );
};
```

```
import React, { useState } from 'react';
import { X, ShieldCheck, CheckCircle2, Upload, School, AlertCircle } from 'lucide-react';
import { UNIVERSITIES } from '../data/seedData';
import { getAllCampuses } from '../utils/campusStore';

interface StudentVerifyModalProps {
  isOpen: boolean;
  onClose: () => void;
  isVerifiedStudent: boolean;
  onVerifySuccess: () => void;
}

export const StudentVerifyModal: React.FC<StudentVerifyModalProps> = ({
  isOpen,
  onClose,
  isVerifiedStudent,
  onVerifySuccess,
}) => {
  if (!isOpen) return null;

  const allCampuses = getAllCampuses();
  const [regNo, setRegNo] = useState('IN11/0024/2023');
  const [studentEmail, setStudentEmail] = useState('comrade@kisiiuniversity.ac.ke');
  const [universityId, setUniversityId] = useState('kisii_uni');
  const [isSubmitting, setIsSubmitting] = useState(false);
  const [success, setSuccess] = useState(false);

  const handleSubmit = (e: React.FormEvent) => {
    e.preventDefault();
    setIsSubmitting(true);
    setTimeout(() => {
      setIsSubmitting(false);
      setSuccess(true);
      onVerifySuccess();
      setTimeout(() => {
        onClose();
        setSuccess(false);
      }, 1400);
    }, 700);
  };

  return (
    <div className="fixed inset-0 z-50 flex items-center justify-center p-4 bg-slate-950/60 backdrop
  -blur-sm animate-in fade-in duration-150">
      <div
        className="w-full max-w-md bg-white rounded-3xl shadow-2xl border border-slate-200 overflow-
  hidden animate-in zoom-in-95 duration-150"
        onClick={(e) => e.stopPropagation()}
      >
        <div className="bg-emerald-800 text-white p-5 relative">
          <button
            type="button"
            onClick={onClose}
            className="absolute top-4 right-4 p-1.5 rounded-xl bg-white/10 hover:bg-white/20 text-wh
  ite transition-colors"
          >
            <X className="w-4 h-4" />
          </button>
          <div className="w-10 h-10 rounded-2xl bg-white/20 flex items-center justify-center mb-3">
            <ShieldCheck className="w-6 h-6 text-emerald-300" />
          </div>
          <h2 className="text-lg font-bold font-heading">Comrade ID Verification</h2>
          <p className="text-xs text-emerald-100/90 mt-0.5">
            Get the green verified badge to build 100% trust with buyers & sellers
          </p>
        </div>

        {success ? (
          <div className="p-6 text-center space-y-3">
            <div className="w-16 h-16 bg-emerald-100 text-emerald-600 rounded-full flex items-center
```

```
 justify-center mx-auto animate-bounce">
            <CheckCircle2 className="w-10 h-10" />
          </div>
          <h3 className="text-base font-bold text-slate-900">Student Verified!</h3>
          <p className="text-xs text-slate-500">
            Your comrade trust badge is now active across all your listings, bids, and hostel inqu
iries.
          </p>
        </div>
      ) : (
        <form onSubmit={handleSubmit} className="p-5 space-y-3.5">
          <div>
            <label className="block text-xs font-bold text-slate-700 mb-1">Select Institution / Co
llege</label>
            <select
              value={universityId}
              onChange={(e) => setUniversityId(e.target.value)}
              className="w-full px-3 py-2 text-xs bg-slate-50 rounded-xl border border-slate-200 f
ocus:bg-white focus:border-emerald-500 outline-none"
            >
              <optgroup label="Universities">
                {allCampuses.filter(u => u.institutionType === 'university').map((uni) => (
                  <option key={uni.id} value={uni.id}>{uni.name} ({uni.shortName})</option>
                ))}
              </optgroup>
              <optgroup label="KMTC (Kenya Medical Training College)">
                {allCampuses.filter(u => u.institutionType === 'kmtc').map((uni) => (
                  <option key={uni.id} value={uni.id}>{uni.name}</option>
                ))}
              </optgroup>
              <optgroup label="National Polytechnics">
                {allCampuses.filter(u => u.institutionType === 'polytechnic').map((uni) => (
                  <option key={uni.id} value={uni.id}>{uni.name}</option>
                ))}
              </optgroup>
              <optgroup label="TVET Colleges & Institutes">
                {allCampuses.filter(u => u.institutionType === 'tvet').map((uni) => (
                  <option key={uni.id} value={uni.id}>{uni.name}</option>
                ))}
              </optgroup>
            </select>
          </div>

          <div>
            <label className="block text-xs font-bold text-slate-700 mb-1">
              Student Registration / Admission No.
            </label>
            <input
              type="text"
              required
              value={regNo}
              onChange={(e) => setRegNo(e.target.value)}
              placeholder="e.g. F17/8241/2023 or C025-01-0942/2022"
              className="w-full px-3.5 py-2 text-xs bg-slate-50 font-mono rounded-xl border border
-slate-200 focus:bg-white focus:border-emerald-500 outline-none"
            />
          </div>

          <div>
            <label className="block text-xs font-bold text-slate-700 mb-1">
              Institutional Student Email (.ac.ke)
            </label>
            <input
              type="email"
              required
              value={studentEmail}
              onChange={(e) => setStudentEmail(e.target.value)}
              placeholder="name@students.uonbi.ac.ke"
              className="w-full px-3.5 py-2 text-xs bg-slate-50 rounded-xl border border-slate-200
 focus:bg-white focus:border-emerald-500 outline-none"
```

```
              />
            </div>

            <div className="p-3 bg-slate-50 rounded-xl border border-dashed border-slate-300 text-ce
  nter cursor-pointer hover:bg-slate-100/70 transition-colors">
              <Upload className="w-5 h-5 text-slate-400 mx-auto mb-1" />
              <div className="text-xs font-semibold text-slate-700">Upload or Snap Student ID Card</
  div>
              <p className="text-[10px] text-slate-400 mt-0.5">JPG or PNG (Exam card or student port
  al screenshot accepted)</p>
            </div>

            <div className="text-[11px] text-slate-500 flex items-start gap-1.5 pt-1">
              <AlertCircle className="w-3.5 h-3.5 text-emerald-600 shrink-0 mt-0.5" />
              <span>
                Verification keeps scam artists away from campus gates. Your registration details ar
  e kept strictly private.
              </span>
            </div>

            <button
              type="submit"
              disabled={isSubmitting}
              className="w-full py-2.5 rounded-xl bg-emerald-600 hover:bg-emerald-700 text-white fon
  t-bold text-xs shadow-md shadow-emerald-700/20 active:scale-[0.98] transition-all flex items-cente
  r justify-center gap-2"
            >
              {isSubmitting ? 'Verifying Student Portal...' : 'Confirm Student Verification'}
            </button>
          </form>
        )}
      </div>
    </div>
  );
};
```

```
import React, { useState } from 'react';
import {
  X,
  CreditCard,
  ShieldCheck,
  Check,
  Copy,
  Smartphone,
  AlertTriangle,
  ArrowRight
} from 'lucide-react';
import { Listing } from '../types';

interface MpesaModalProps {
  listing: Listing | null;
  onClose: () => void;
}

export const MpesaModal: React.FC<MpesaModalProps> = ({ listing, onClose }) => {
  if (!listing) return null;

  const [copiedTill, setCopiedTill] = useState(false);
  const [phoneNumber, setPhoneNumber] = useState('0712345678');
  const [stkState, setStkState] = useState<'idle' | 'sending' | 'prompted' | 'success'>('idle');

  const formatPrice = (price: number) => {
    return new Intl.NumberFormat('en-KE').format(price);
  };

  const copyToClipboard = (text: string) => {
    navigator.clipboard?.writeText(text);
    setCopiedTill(true);
    setTimeout(() => setCopiedTill(false), 2000);
  };

  const handleSimulateStk = (e: React.FormEvent) => {
    e.preventDefault();
    setStkState('sending');
    setTimeout(() => {
      setStkState('prompted');
      setTimeout(() => {
        setStkState('success');
      }, 2500);
    }, 1200);
  };

  const paymentTarget = listing.seller.tillNumber || `Send Money: ${listing.seller.mpesaNumber || li
  sting.seller.phone}`;

  return (
    <div className="fixed inset-0 z-50 flex items-center justify-center p-4 bg-slate-950/60 backdrop
  -blur-sm animate-in fade-in duration-150">
      <div
        className="w-full max-w-md bg-white rounded-3xl shadow-2xl border border-slate-200 overflow-
  hidden animate-in zoom-in-95 duration-150"
        onClick={(e) => e.stopPropagation()}
      >
        {/* Header */}
        <div className="bg-[#008938] text-white p-5 relative">
          <button
            type="button"
            onClick={onClose}
            className="absolute top-4 right-4 p-1.5 rounded-xl bg-white/10 hover:bg-white/20 text-wh
  ite transition-colors"
          >
            <X className="w-4 h-4" />
          </button>
          <div className="flex items-center gap-2 mb-1">
            <span className="font-mono font-black text-xl tracking-tight bg-white text-[#008938] px-
  2 py-0.5 rounded-md">
```

```
            M-PESA
          </span>
          <span className="text-xs font-semibold uppercase tracking-wider text-emerald-100">
            Safe Campus Trade
          </span>
        </div>
        <h2 className="text-base font-bold">Secure Campus Payment Guide</h2>
        <p className="text-xs text-emerald-100/90 mt-0.5">
          Pay safely for &quot;{listing.title.substring(0, 32)}...&quot;
        </p>
      </div>

      <div className="p-5 space-y-4">
        {/* Safety First Golden Rule */}
        <div className="p-3 bg-amber-50 rounded-2xl border border-amber-200/80 flex items-start ga
p-2.5 text-xs text-amber-900">
          <AlertTriangle className="w-4 h-4 text-amber-600 shrink-0 mt-0.5" />
          <div>
            <span className="font-bold">Rule #1 for University Comrades:</span>
            <p className="text-[11px] mt-0.5 leading-relaxed text-amber-800">
              Meet the seller in person at <span className="font-semibold underline">{listing.sell
er.safeSpot}</span>, test the item, and only confirm payment once physically satisfied!
            </p>
          </div>
        </div>

        {/* Amount Box */}
        <div className="p-3.5 bg-slate-50 rounded-2xl border border-slate-200 flex items-center ju
stify-between">
          <div>
            <div className="text-[11px] text-slate-400 font-medium">Item Amount</div>
            <div className="text-lg font-black text-slate-900 font-mono">
              KES {formatPrice(listing.price)} {listing.priceLabel}
            </div>
          </div>
          <div className="text-right">
            <div className="text-[11px] text-slate-400 font-medium">Payee</div>
            <div className="text-xs font-bold text-slate-800">{listing.seller.name}</div>
          </div>
        </div>

        {/* Payment Target / Till */}
        <div className="space-y-1.5">
          <div className="flex items-center justify-between text-xs">
            <span className="text-slate-500 font-medium">Recipient Details:</span>
            <button
              type="button"
              onClick={() => copyToClipboard(paymentTarget)}
              className="text-emerald-700 font-bold text-[11px] flex items-center gap-1 hover:text
-emerald-900"
            >
              {copiedTill ? <Check className="w-3 h-3" /> : <Copy className="w-3 h-3" />}
              <span>{copiedTill ? 'Copied to clipboard' : 'Copy details'}</span>
            </button>
          </div>
          <div className="p-3 bg-slate-900 text-white rounded-xl font-mono text-sm flex items-cent
er justify-between">
            <span>{paymentTarget}</span>
            <CreditCard className="w-4 h-4 text-emerald-400" />
          </div>
        </div>

        {/* Interactive STK Push Simulator */}
        <div className="pt-2 border-t border-slate-100">
          <div className="text-xs font-bold text-slate-800 mb-2 flex items-center gap-1.5">
            <Smartphone className="w-4 h-4 text-[#008938]" />
            <span>Simulate M-Pesa STK Push / Prompt</span>
          </div>

          {stkState === 'idle' && (
```

```
            <form onSubmit={handleSimulateStk} className="space-y-2">
              <input
                type="text"
                value={phoneNumber}
                onChange={(e) => setPhoneNumber(e.target.value)}
                placeholder="07XX XXX XXX"
                className="w-full px-3 py-2 text-xs bg-slate-50 font-mono rounded-xl border border
  -slate-200 outline-none"
              />
              <button
                type="submit"
                className="w-full py-2.5 rounded-xl bg-[#008938] hover:bg-[#00742f] text-white fon
  t-bold text-xs shadow-md shadow-emerald-700/20 active:scale-[0.98] transition-all flex items-cente
  r justify-center gap-2"
              >
                <span>Send M-Pesa STK Prompt to Phone</span>
                <ArrowRight className="w-3.5 h-3.5" />
              </button>
            </form>
          )}

          {stkState === 'sending' && (
            <div className="p-4 bg-emerald-50 rounded-2xl text-center space-y-1 text-xs text-emera
  ld-900 font-medium">
              <div className="animate-spin w-5 h-5 border-2 border-[#008938] border-t-transparent
  rounded-full mx-auto mb-2" />
              <p>Connecting to Safaricom Daraja Gateway...</p>
            </div>
          )}

          {stkState === 'prompted' && (
            <div className="p-4 bg-slate-900 text-white rounded-2xl space-y-2 text-center animate-
  pulse">
              <div className="text-[11px] text-emerald-400 font-mono font-bold">SIMULATED PHONE SC
  REEN</div>
              <div className="text-xs font-mono">
                Do you want to pay KES {formatPrice(listing.price)} to {listing.seller.name}?
              </div>
              <div className="text-[11px] text-slate-400">Enter M-Pesa PIN: ****</div>
            </div>
          )}

          {stkState === 'success' && (
            <div className="p-4 bg-emerald-50 rounded-2xl text-center space-y-2">
              <div className="text-emerald-700 font-bold text-xs flex items-center justify-center
  gap-1.5">
                <ShieldCheck className="w-4 h-4" />
                <span>Transaction Demo Confirmed!</span>
              </div>
              <p className="text-[11px] text-slate-600 font-mono">
                REF: QK948XP12 - KES {formatPrice(listing.price)} sent to {listing.seller.name}.
              </p>
              <button
                type="button"
                onClick={() => setStkState('idle')}
                className="text-[11px] font-bold text-emerald-800 underline mt-1"
              >
                Reset Demo
              </button>
            </div>
          )}
        </div>
      </div>
    </div>
  </div>
  );
};
```

```
import React from 'react';
import { X, Heart, Trash2, ArrowUpRight } from 'lucide-react';
import { Listing } from '../types';

interface SavedModalProps {
  isOpen: boolean;
  onClose: () => void;
  savedListings: Listing[];
  onRemoveSaved: (id: string) => void;
  onOpenDetail: (listing: Listing) => void;
}

export const SavedModal: React.FC<SavedModalProps> = ({
  isOpen,
  onClose,
  savedListings,
  onRemoveSaved,
  onOpenDetail,
}) => {
  if (!isOpen) return null;

  const formatPrice = (price: number) => {
    return new Intl.NumberFormat('en-KE').format(price);
  };

  return (
    <div className="fixed inset-0 z-50 flex items-center justify-center p-4 bg-slate-950/60 backdrop
  -blur-sm animate-in fade-in duration-150">
      <div
        className="w-full max-w-md bg-white rounded-3xl shadow-2xl border border-slate-200 overflow-
  hidden flex flex-col max-h-[85vh] animate-in zoom-in-95 duration-150"
        onClick={(e) => e.stopPropagation()}
      >
        <div className="px-5 py-4 border-b border-slate-100 flex items-center justify-between">
          <div className="flex items-center gap-2">
            <Heart className="w-5 h-5 text-rose-500 fill-rose-500" />
            <h3 className="font-bold text-sm text-slate-900">Saved Campus Listings</h3>
            <span className="text-xs bg-slate-100 px-2 py-0.5 rounded-full font-mono text-slate-600"
  >
              {savedListings.length}
            </span>
          </div>
          <button
            type="button"
            onClick={onClose}
            className="p-1.5 rounded-xl text-slate-400 hover:text-slate-700 hover:bg-slate-100"
          >
            <X className="w-4 h-4" />
          </button>
        </div>

        <div className="overflow-y-auto flex-1 p-4 space-y-2.5">
          {savedListings.length === 0 ? (
            <div className="p-8 text-center text-slate-400 text-xs">
              <Heart className="w-8 h-8 text-slate-200 mx-auto mb-2" />
              <p>No saved listings yet.</p>
              <p className="text-[11px] text-slate-400 mt-1">Tap the heart icon on any textbook, hos
  tel, or gig to bookmark it here.</p>
            </div>
          ) : (
            savedListings.map((listing) => (
              <div
                key={listing.id}
                className="flex items-center justify-between p-2.5 bg-slate-50 rounded-2xl border bo
  rder-slate-200/80 hover:bg-white transition-all gap-3"
              >
                <div
                  onClick={() => {
                    onClose();
                    onOpenDetail(listing);
```

```
                }}
                className="flex items-center gap-3 flex-1 min-w-0 cursor-pointer"
              >
                <img
                  src={listing.image}
                  alt={listing.title}
                  referrerPolicy="no-referrer"
                  className="w-14 h-14 rounded-xl object-cover shrink-0 bg-slate-200"
                />
                <div className="min-w-0">
                  <h4 className="text-xs font-bold text-slate-900 truncate">{listing.title}</h4>
                  <div className="text-[11px] text-slate-500 mt-0.5">{listing.campusName}</div>
                  <div className="text-xs font-black text-emerald-800 font-mono mt-0.5">
                    KES {formatPrice(listing.price)} {listing.priceLabel}
                  </div>
                </div>
              </div>

              <div className="flex items-center gap-1 shrink-0">
                <button
                  type="button"
                  onClick={() => {
                    onClose();
                    onOpenDetail(listing);
                  }}
                  className="p-2 rounded-xl bg-slate-100 hover:bg-slate-200 text-slate-700"
                  title="View details"
                >
                  <ArrowUpRight className="w-4 h-4" />
                </button>
                <button
                  type="button"
                  onClick={() => onRemoveSaved(listing.id)}
                  className="p-2 rounded-xl text-slate-400 hover:text-rose-600 hover:bg-rose-50 tr
  ansition-colors"
                  title="Remove from saved"
                >
                  <Trash2 className="w-4 h-4" />
                </button>
              </div>
            </div>
          ))
        )}
      </div>
    </div>
  </div>
  );
};
```

```
import React, { useState } from 'react';
import {
  X,
  Share2,
  Copy,
  Check,
  MessageCircle,
  Send,
  Twitter,
  Mail,
  QrCode,
  ExternalLink,
  Sparkles,
  Smartphone
} from 'lucide-react';
import { Listing } from '../types';

export interface ShareTarget {
  type: 'app' | 'listing';
  title: string;
  text: string;
  url: string;
  listing?: Listing;
}

interface ShareModalProps {
  isOpen: boolean;
  onClose: () => void;
  target: ShareTarget | null;
}

export const ShareModal: React.FC<ShareModalProps> = ({ isOpen, onClose, target }) => {
  const [copied, setCopied] = useState(false);
  const [showQR, setShowQR] = useState(false);

  if (!isOpen || !target) return null;

  const shareUrl = target.url || window.location.href;
  const shareTitle = target.title;
  const shareText = target.text;

  const handleCopyLink = async () => {
    try {
      await navigator.clipboard.writeText(shareUrl);
      setCopied(true);
      setTimeout(() => setCopied(false), 2500);
    } catch {
      // Fallback
      setCopied(true);
      setTimeout(() => setCopied(false), 2500);
    }
  };

  const handleNativeShare = async () => {
    if (navigator.share) {
      try {
        await navigator.share({
          title: shareTitle,
          text: shareText,
          url: shareUrl,
        });
        onClose();
      } catch (err) {
        // User cancelled or not supported
      }
    } else {
      handleCopyLink();
    }
  };
```

```
// WhatsApp share URL
const whatsAppMessage = encodeURIComponent(`${shareText}\n\n   Open on STUDSPOT: ${shareUrl}`);
const whatsAppUrl = `https://api.whatsapp.com/send?text=${whatsAppMessage}`;

// Twitter / X share URL
const twitterUrl = `https://twitter.com/intent/tweet?text=${encodeURIComponent(shareText)}&url=${e
ncodeURIComponent(shareUrl)}&hashtags=STUDSPOT,CampusMarketplace,KenyanComrades`;

// Telegram share URL
const telegramUrl = `https://t.me/share/url?url=${encodeURIComponent(shareUrl)}&text=${encodeURICo
mponent(shareText)}`;

// Email share URL
const emailUrl = `mailto:?subject=${encodeURIComponent(shareTitle)}&body=${encodeURIComponent(`${s
hareText}\n\nCheck it out here:\n${shareUrl}`)}`;

// SMS share URL
const smsUrl = `sms:?body=${encodeURIComponent(`${shareText} ${shareUrl}`)}`;

return (
  <div className="fixed inset-0 z-50 flex items-center justify-center p-4 bg-black/80 backdrop-blu
r-md animate-in fade-in">
    <div
      className="relative w-full max-w-md bg-[#181818] border border-neutral-700/80 rounded-3xl sh
adow-2xl overflow-hidden p-5 sm:p-6 text-white space-y-5 animate-in zoom-in-95"
      onClick={(e) => e.stopPropagation()}
    >
      {/* Header */}
      <div className="flex items-center justify-between">
        <div className="flex items-center gap-2.5">
          <div className="w-10 h-10 rounded-2xl bg-[#F3B71B]/15 border border-[#F3B71B]/40 flex it
ems-center justify-center text-[#F3B71B]">
            <Share2 className="w-5 h-5 stroke-[2.2]" />
          </div>
          <div>
            <h3 className="text-base font-extrabold text-white">
              {target.type === 'app' ? 'Share STUDSPOT' : 'Share with Comrades'}
            </h3>
            <p className="text-xs text-neutral-400">
              {target.type === 'app' ? 'Invite friends & campus groups' : 'Send this listing to Wh
atsApp or socials'}
            </p>
          </div>
        </div>
        <button
          onClick={onClose}
          className="p-1.5 text-neutral-400 hover:text-white rounded-full bg-neutral-800 hover:bg-
neutral-700 transition"
        >
          <X className="w-4 h-4" />
        </button>
      </div>

      {/* Preview box */}
      <div className="p-3 bg-[#222222] rounded-2xl border border-neutral-800 space-y-1.5">
        {target.listing ? (
          <div className="flex items-center gap-3">
            <img
              src={target.listing.image}
              alt={target.listing.title}
              className="w-12 h-12 rounded-xl object-cover border border-neutral-700 shrink-0"
            />
            <div className="min-w-0 flex-1">
              <span className="text-[10px] font-bold text-[#F3B71B] uppercase tracking-wide block
font-mono">
                {target.listing.campusName}
              </span>
              <p className="text-xs font-bold text-white truncate">{target.listing.title}</p>
              <p className="text-xs font-mono font-bold text-emerald-400">
                KES {target.listing.price.toLocaleString()}
```

```
              </p>
            </div>
          </div>
        ) : (
          <div className="flex items-center gap-3">
            <div className="w-12 h-12 rounded-xl overflow-hidden bg-black p-0.5 border border-cyan
-400/40 shrink-0">
              <img
                src="/src/assets/images/studspot_official_icon_1791805148976.jpg"
                alt="STUDSPOT"
                className="w-full h-full object-cover rounded-lg"
              />
            </div>
            <div className="min-w-0 flex-1">
              <p className="text-xs font-bold text-white">STUDSPOT Campus App</p>
              <p className="text-[11px] text-neutral-400">
                Peer-to-peer marketplace & student hostel directory across Kenya
              </p>
            </div>
          </div>
        )}
      </div>

      {/* Quick Native Share Button if supported */}
      {typeof navigator !== 'undefined' && 'share' in navigator && (
        <button
          type="button"
          onClick={handleNativeShare}
          className="w-full py-2.5 px-4 bg-gradient-to-r from-[#F3B71B] to-[#dca415] text-black fo
nt-extrabold text-xs sm:text-sm rounded-xl hover:opacity-95 transition shadow-lg shadow-[#F3B71B]/
20 flex items-center justify-center gap-2"
        >
          <Smartphone className="w-4 h-4 stroke-[2.5]" />
          <span>Open System Share Sheet (More Apps)</span>
        </button>
      )}

      {/* Social channels grid */}
      <div className="space-y-2">
        <label className="text-[11px] font-bold text-neutral-400 uppercase tracking-wider block">
          Direct Share to Campus Comrades
        </label>
        <div className="grid grid-cols-2 sm:grid-cols-4 gap-2">
          {/* WhatsApp */}
          <a
            href={whatsAppUrl}
            target="_blank"
            rel="noopener noreferrer"
            className="p-2.5 rounded-xl bg-emerald-950/80 hover:bg-emerald-900 border border-emera
ld-500/40 text-emerald-300 flex flex-col items-center justify-center gap-1 text-center transition
group"
          >
            <MessageCircle className="w-5 h-5 text-emerald-400 group-hover:scale-110 transition-tr
ansform" />
            <span className="text-[11px] font-bold">WhatsApp</span>
          </a>

          {/* X (Twitter) */}
          <a
            href={twitterUrl}
            target="_blank"
            rel="noopener noreferrer"
            className="p-2.5 rounded-xl bg-[#202020] hover:bg-neutral-800 border border-neutral-70
0 text-neutral-200 flex flex-col items-center justify-center gap-1 text-center transition group"
          >
            <Twitter className="w-5 h-5 text-sky-400 group-hover:scale-110 transition-transform" /
>
            <span className="text-[11px] font-bold">X (Twitter)</span>
          </a>
```

```
          {/* Telegram */}
          <a
            href={telegramUrl}
            target="_blank"
            rel="noopener noreferrer"
            className="p-2.5 rounded-xl bg-sky-950/60 hover:bg-sky-900/80 border border-sky-500/40
 text-sky-300 flex flex-col items-center justify-center gap-1 text-center transition group"
          >
            <Send className="w-5 h-5 text-sky-400 group-hover:scale-110 transition-transform" />
            <span className="text-[11px] font-bold">Telegram</span>
          </a>

          {/* SMS / Comrades */}
          <a
            href={smsUrl}
            className="p-2.5 rounded-xl bg-[#202020] hover:bg-neutral-800 border border-neutral-70
0 text-neutral-200 flex flex-col items-center justify-center gap-1 text-center transition group"
          >
            <Mail className="w-5 h-5 text-amber-400 group-hover:scale-110 transition-transform" />
            <span className="text-[11px] font-bold">SMS / Text</span>
          </a>
        </div>
      </div>

      {/* Copy Link Row */}
      <div className="space-y-1.5">
        <label className="text-[11px] font-bold text-neutral-400 uppercase tracking-wider block">
          Copy Direct Link
        </label>
        <div className="flex items-center gap-2">
          <input
            type="text"
            readOnly
            value={shareUrl}
            className="flex-1 bg-[#202020] text-neutral-300 text-xs px-3 py-2 rounded-xl border bo
rder-neutral-700 truncate outline-none select-all"
          />
          <button
            onClick={handleCopyLink}
            className={`px-3.5 py-2 rounded-xl text-xs font-bold transition flex items-center gap-
1.5 shrink-0 ${
              copied
                ? 'bg-emerald-500 text-black'
                : 'bg-[#F3B71B] hover:bg-[#dca415] text-black'
            }`}
          >
            {copied ? (
              <>
                <Check className="w-3.5 h-3.5 stroke-[3]" />
                <span>Copied!</span>
              </>
            ) : (
              <>
                <Copy className="w-3.5 h-3.5" />
                <span>Copy</span>
              </>
            )}
          </button>
        </div>
      </div>

      {/* Toggle QR Code View */}
      <div className="pt-1">
        <button
          onClick={() => setShowQR(!showQR)}
          className="w-full py-2 px-3 rounded-xl bg-[#202020] hover:bg-[#282828] border border-neu
tral-800 text-xs text-neutral-300 flex items-center justify-center gap-1.5 transition"
        >
          <QrCode className="w-4 h-4 text-[#F3B71B]" />
          <span>{showQR ? 'Hide Campus QR Code' : 'Show Campus QR Code to scan in person'}</span>
```

```
          </button>

          {showQR && (
            <div className="mt-3 p-4 bg-white rounded-2xl flex flex-col items-center justify-center
  text-center animate-in fade-in">
              {/* High Contrast Clean SVG QR Representation */}
              <div className="w-40 h-40 bg-white p-2 border-2 border-black rounded-xl flex items-cen
  ter justify-center">
                <svg viewBox="0 0 100 100" className="w-full h-full" fill="black">
                  {/* Position detection patterns */}
                  <rect x="5" y="5" width="28" height="28" rx="4" fill="none" stroke="black" strokeW
  idth="6" />
                  <rect x="12" y="12" width="14" height="14" fill="black" />
                  <rect x="67" y="5" width="28" height="28" rx="4" fill="none" stroke="black" stroke
  Width="6" />
                  <rect x="74" y="12" width="14" height="14" fill="black" />
                  <rect x="5" y="67" width="28" height="28" rx="4" fill="none" stroke="black" stroke
  Width="6" />
                  <rect x="12" y="74" width="14" height="14" fill="black" />
                  {/* QR Matrix Dots */}
                  <rect x="38" y="10" width="6" height="6" />
                  <rect x="48" y="18" width="6" height="6" />
                  <rect x="56" y="8" width="6" height="6" />
                  <rect x="38" y="26" width="6" height="6" />
                  <rect x="10" y="38" width="6" height="6" />
                  <rect x="22" y="44" width="6" height="6" />
                  <rect x="14" y="54" width="6" height="6" />
                  <rect x="40" y="40" width="20" height="20" rx="3" fill="#0F2D59" />
                  <circle cx="50" cy="50" r="5" fill="#F3B71B" />
                  <rect x="68" y="40" width="6" height="6" />
                  <rect x="80" y="48" width="6" height="6" />
                  <rect x="74" y="58" width="6" height="6" />
                  <rect x="42" y="68" width="6" height="6" />
                  <rect x="52" y="76" width="6" height="6" />
                  <rect x="40" y="86" width="6" height="6" />
                  <rect x="70" y="72" width="6" height="6" />
                  <rect x="82" y="82" width="6" height="6" />
                </svg>
              </div>
              <p className="mt-2 text-[11px] font-bold text-neutral-800 font-mono">
                Scan to open on smartphone camera
              </p>
            </div>
          )}
        </div>
      </div>
    </div>
  );
};
```

```
import React from 'react';
import { X, ShieldAlert, FileText, AlertTriangle, CheckCircle, Scale } from 'lucide-react';

interface TermsOfServiceModalProps {
  isOpen: boolean;
  onClose: () => void;
  onAccept?: () => void;
  showAcceptButton?: boolean;
}

export const TermsOfServiceModal: React.FC<TermsOfServiceModalProps> = ({
  isOpen,
  onClose,
  onAccept,
  showAcceptButton = false,
}) => {
  if (!isOpen) return null;

  return (
    <div className="fixed inset-0 z-50 flex items-center justify-center p-3 sm:p-5 bg-black/80 backd
  rop-blur-md animate-in fade-in duration-150 overflow-y-auto">
      <div
        className="w-full max-w-2xl bg-[#1A1A1A] text-slate-100 rounded-3xl shadow-2xl border border
  -neutral-800 overflow-hidden flex flex-col max-h-[92vh] my-auto animate-in zoom-in-95 duration-150
  "
        onClick={(e) => e.stopPropagation()}
      >
        {/* Header */}
        <div className="px-5 py-4 border-b border-neutral-800 bg-[#141414] flex items-center justify
  -between">
          <div className="flex items-center gap-2.5">
            <div className="w-8 h-8 rounded-xl bg-[#F3B71B]/20 text-[#F3B71B] flex items-center just
  ify-center font-bold">
              <Scale className="w-4 h-4" />
            </div>
            <div>
              <h2 className="text-base font-bold text-white font-heading">STUDSPOT Terms of Service
  & Legal Framework</h2>
              <p className="text-[11px] text-neutral-400">Platform Policies, Disclaimers & User Agre
  ement</p>
            </div>
          </div>
          <button
            type="button"
            onClick={onClose}
            className="p-1.5 rounded-xl text-neutral-400 hover:text-white hover:bg-neutral-800 trans
  ition-colors"
          >
            <X className="w-5 h-5" />
          </button>
        </div>

        {/* Legal Body */}
        <div className="overflow-y-auto flex-1 p-5 sm:p-6 space-y-6 text-xs sm:text-sm text-neutral-
  300 leading-relaxed">
          {/* Summary Box */}
          <div className="p-4 rounded-2xl bg-[#242424] border border-[#F3B71B]/30 flex items-start g
  ap-3">
            <ShieldAlert className="w-5 h-5 text-[#F3B71B] shrink-0 mt-0.5" />
            <div className="space-y-1 text-xs">
              <span className="font-bold text-white uppercase tracking-wider text-[11px]">
                Notice to University & College Students
              </span>
              <p className="text-neutral-300 leading-normal">
                By creating an account or posting on STUDSPOT, you agree to these legally binding te
  rms designed to protect the platform and fellow campus members.
              </p>
            </div>
          </div>
```

```
        {/* Clause 1: Directory Intermediary Disclaimer */}
        <section className="space-y-2">
          <div className="flex items-center gap-2 text-[#F3B71B] font-bold text-sm">
            <span className="w-6 h-6 rounded-lg bg-[#F3B71B]/20 flex items-center justify-center t
ext-xs">1</span>
            <h3>Directory Intermediary Disclaimer</h3>
          </div>
          <p className="pl-8 text-neutral-300">
            STUDSPOT operates solely as an online directory, communication medium, and advertising
 venue connecting university students, hostel caretakers, and campus businesses. <strong className
="text-white">STUDSPOT is not an auctioneer, retailer, broker, landlord, or employer.</strong> STU
DSPOT is not a party to any transactions, agreements, sales contracts, residential tenancy leases,
 or freelance gig arrangements formed between platform users. Users conduct trades, inspections, a
nd negotiations at their sole discretion.
          </p>
        </section>

        {/* Clause 2: Limitation of Liability Waiver */}
        <section className="space-y-2">
          <div className="flex items-center gap-2 text-[#F3B71B] font-bold text-sm">
            <span className="w-6 h-6 rounded-lg bg-[#F3B71B]/20 flex items-center justify-center t
ext-xs">2</span>
            <h3>Limitation of Liability Waiver</h3>
          </div>
          <p className="pl-8 text-neutral-300">
            To the fullest extent permitted under the laws of Kenya, STUDSPOT, its operators, dire
ctors, and affiliates <strong className="text-white">assume zero legal or financial liability</str
ong> for:
          </p>
          <ul className="pl-12 list-disc space-y-1 text-neutral-400">
            <li>Defective, malfunctioning, or counterfeit goods traded between users.</li>
            <li>Fraudulent listings, inaccurate hostel descriptions, or misrepresentation by third
 parties.</li>
            <li>Hostel deposit disputes, tenancy disagreements, eviction issues, or landlord misco
nduct.</li>
            <li>Lost funds, unauthorized M-Pesa reversals, or uncompleted gig payments.</li>
            <li>Physical injury, theft, or damages arising during in-person campus meetups.</li>
          </ul>
          <p className="pl-8 text-neutral-400 text-xs">
            Comrades are strictly advised to inspect items at designated daylight campus safe spot
s (such as University Library gates or Student Centers) prior to completing payment.
          </p>
        </section>

        {/* Clause 3: Prohibited Content & Listings */}
        <section className="space-y-2">
          <div className="flex items-center gap-2 text-rose-400 font-bold text-sm">
            <span className="w-6 h-6 rounded-lg bg-rose-500/20 text-rose-400 flex items-center jus
tify-center text-xs">3</span>
            <h3>Strictly Prohibited Content & Conduct</h3>
          </div>
          <p className="pl-8 text-neutral-300">
            STUDSPOT enforces a zero-tolerance policy against unlawful and harmful listings. The f
ollowing are strictly prohibited:
          </p>
          <ul className="pl-12 list-disc space-y-1 text-neutral-400">
            <li>Stolen goods, unverified electronic devices, or pirated copyright materials.</li>
            <li>Academic fraud services, including contract cheating, unauthorized exam paper diss
emination, or impersonation.</li>
            <li>Fake housing or hostel listings with fabricated pricing or non-existent units.</li
>
            <li>Controlled substances, illicit items, weapons, or counterfeit medications.</li>
          </ul>
          <p className="pl-8 text-rose-300 text-xs font-semibold">
            Any listing violating these standards will be immediately removed, the offending accou
nt banned, and listing fees forfeited without refund.
          </p>
        </section>

        {/* Clause 4: Non-Refundable KSh 80 Monthly Listing Fee */}
```

```
        <section className="space-y-2">
          <div className="flex items-center gap-2 text-[#F3B71B] font-bold text-sm">
            <span className="w-6 h-6 rounded-lg bg-[#F3B71B]/20 flex items-center justify-center t
  ext-xs">4</span>
            <h3>Non-Refundable KSh 80 / Month Advertising Fee</h3>
          </div>
          <p className="pl-8 text-neutral-300">
            To maintain listing quality and campus safety verification, STUDSPOT charges a flat li
  sting fee of <strong className="text-white">KSh 80 per listing for 30 consecutive calendar days</s
  trong> of active advertising space on the platform.
          </p>
          <p className="pl-8 text-neutral-400">
            This KSh 80 fee is strictly non-refundable once administrative review begins, regardle
  ss of whether the user sells the item ahead of schedule, changes their mind, or has their listing
  deleted due to prohibited content violations. All listings undergo administrative approval (<code
  className="text-[#F3B71B]">isApproved == True</code>) before publication.
          </p>
        </section>
      </div>

      {/* Modal Footer */}
      <div className="px-5 py-3.5 border-t border-neutral-800 bg-[#141414] flex items-center justi
  fy-between">
        <div className="text-[11px] text-neutral-400">
          Last Updated: 2026 Academic Year
        </div>
        <div className="flex items-center gap-2">
          <button
            type="button"
            onClick={onClose}
            className="px-4 py-2 rounded-xl text-xs font-medium text-neutral-300 hover:bg-neutral-
  800 transition-colors"
          >
            Close
          </button>
          {showAcceptButton && onAccept && (
            <button
              type="button"
              onClick={() => {
                onAccept();
                onClose();
              }}
              className="px-5 py-2 rounded-xl bg-[#F3B71B] hover:bg-[#dca415] text-black font-bold
   text-xs transition-colors flex items-center gap-1.5"
            >
              <CheckCircle className="w-4 h-4" />
              <span>I Understand & Accept</span>
            </button>
          )}
        </div>
      </div>
    </div>
  </div>
  );
};
```

```
import React, { useState } from 'react';
import {
  Download,
  Smartphone,
  Share,
  PlusSquare,
  X,
  CheckCircle2,
  Sparkles,
  ArrowRight,
  ShieldCheck,
  Globe
} from 'lucide-react';
import { usePWAInstall } from '../hooks/usePWAInstall';

interface PWAInstallModalProps {
  isOpen: boolean;
  onClose: () => void;
}

export const PWAInstallModal: React.FC<PWAInstallModalProps> = ({ isOpen, onClose }) => {
  const { isInstallable, isInstalled, isIOS, install } = usePWAInstall();
  const [justInstalled, setJustInstalled] = useState(false);

  if (!isOpen) return null;

  const handleInstallClick = async () => {
    if (isInstallable) {
      const success = await install();
      if (success) {
        setJustInstalled(true);
        setTimeout(() => {
          onClose();
        }, 2000);
      }
    }
  };

  return (
    <div className="fixed inset-0 z-50 flex items-center justify-center p-4 bg-black/80 backdrop-blu
  r-sm animate-in fade-in">
      <div className="relative w-full max-w-md bg-[#181818] border border-neutral-700/80 rounded-3xl
   shadow-2xl overflow-hidden p-6 text-white space-y-5">
        <button
          onClick={onClose}
          className="absolute top-4 right-4 p-2 text-neutral-400 hover:text-white rounded-full bg-ne
  utral-800/80 hover:bg-neutral-700 transition"
        >
          <X className="w-4 h-4" />
        </button>

        {/* Header with App Icon */}
        <div className="flex items-center gap-3.5 pt-1">
          <div className="w-14 h-14 rounded-2xl overflow-hidden p-0.5 bg-gradient-to-br from-[#0F2D5
  9] via-[#08182F] to-black border-2 border-cyan-400/50 shadow-xl shadow-cyan-950/60 shrink-0 flex i
  tems-center justify-center">
            <img
              src="/src/assets/images/studspot_official_icon_1791805148976.jpg"
              alt="STUDSPOT Icon"
              className="w-full h-full object-cover rounded-xl"
            />
          </div>
          <div>
            <div className="flex items-center gap-1.5">
              <h3 className="text-lg font-black tracking-tight text-white font-heading">
                STUDSPOT
              </h3>
              <span className="text-[9px] font-bold text-black bg-[#F3B71B] px-1.5 py-0.2 rounded fo
  nt-mono">
                PWA APP
```

```
            </span>
          </div>
          <p className="text-xs text-neutral-400 font-medium">
            Campus Marketplace & Community
          </p>
        </div>
      </div>

      {/* Benefits bullets */}
      <div className="bg-[#202020] rounded-2xl p-3.5 border border-neutral-800 space-y-2 text-xs">
        <div className="flex items-center gap-2 text-neutral-300">
          <CheckCircle2 className="w-4 h-4 text-emerald-400 shrink-0" />
          <span>Fast 1-tap launch from your phone home screen</span>
        </div>
        <div className="flex items-center gap-2 text-neutral-300">
          <CheckCircle2 className="w-4 h-4 text-[#F3B71B] shrink-0" />
          <span>Standalone full-screen experience with zero URL bars</span>
        </div>
        <div className="flex items-center gap-2 text-neutral-300">
          <CheckCircle2 className="w-4 h-4 text-cyan-400 shrink-0" />
          <span>Offline cached browsing & low data usage on campus Wi-Fi</span>
        </div>
      </div>

      {/* Actions / Instructions based on state */}
      {justInstalled ? (
        <div className="p-4 bg-emerald-500/10 border border-emerald-500/40 rounded-2xl text-center
 space-y-1">
          <p className="text-sm font-bold text-emerald-400">   Installed Successfully!</p>
          <p className="text-xs text-neutral-300">You can now open STUDSPOT directly from your hom
e screen.</p>
        </div>
      ) : isInstalled ? (
        <div className="p-4 bg-[#242424] border border-neutral-700 rounded-2xl text-center space-y
-1">
          <p className="text-sm font-bold text-[#F3B71B]">  Already Running in App Mode</p>
          <p className="text-xs text-neutral-400">STUDSPOT is active on your device.</p>
        </div>
      ) : isInstallable ? (
        <div className="space-y-3">
          <button
            onClick={handleInstallClick}
            className="w-full py-3 px-4 bg-gradient-to-r from-[#F3B71B] to-[#e5a80f] text-black fo
nt-extrabold text-sm rounded-xl hover:opacity-95 transition shadow-lg shadow-[#F3B71B]/20 flex ite
ms-center justify-center gap-2"
          >
            <Download className="w-4 h-4 stroke-[2.5]" />
            <span>Add to Home Screen (Install)</span>
          </button>
          <p className="text-[11px] text-center text-neutral-400">
            Instant install   No App Store or Google Play download required
          </p>
        </div>
      ) : isIOS ? (
        /* iOS Safari Specific Guide */
        <div className="p-4 bg-[#222222] border border-neutral-700 rounded-2xl space-y-2.5 text-xs
">
          <div className="flex items-center gap-2 text-[#F3B71B] font-bold">
            <Smartphone className="w-4 h-4" />
            <span>How to Install on iPhone / iPad (Safari):</span>
          </div>
          <ol className="space-y-2 text-neutral-300 pl-1">
            <li className="flex items-start gap-2">
              <span className="w-5 h-5 rounded-full bg-neutral-800 text-neutral-200 flex items-cen
ter justify-center font-bold text-[10px] shrink-0 mt-0.5">1</span>
              <span>Tap the <strong className="text-white">Share</strong> button <Share className=
"inline w-3.5 h-3.5 text-cyan-400 mx-0.5" /> in Safari's bottom toolbar.</span>
            </li>
            <li className="flex items-start gap-2">
              <span className="w-5 h-5 rounded-full bg-neutral-800 text-neutral-200 flex items-cen
```

```
  ter justify-center font-bold text-[10px] shrink-0 mt-0.5">2</span>
               <span>Scroll down and tap <strong className="text-white">Add to Home Screen</strong>
   <PlusSquare className="inline w-3.5 h-3.5 text-[#F3B71B] mx-0.5" />.</span>
             </li>
             <li className="flex items-start gap-2">
               <span className="w-5 h-5 rounded-full bg-neutral-800 text-neutral-200 flex items-cen
  ter justify-center font-bold text-[10px] shrink-0 mt-0.5">3</span>
               <span>Tap <strong className="text-white">Add</strong> in the top right corner. Done!
  </span>
             </li>
           </ol>
         </div>
       ) : (
         /* Chrome / Android manual guide fallback */
         <div className="p-4 bg-[#222222] border border-neutral-700 rounded-2xl space-y-2.5 text-xs
  ">
           <div className="flex items-center gap-2 text-[#F3B71B] font-bold">
             <Smartphone className="w-4 h-4" />
             <span>How to Install on Android / Chrome:</span>
           </div>
           <ol className="space-y-2 text-neutral-300 pl-1">
             <li className="flex items-start gap-2">
               <span className="w-5 h-5 rounded-full bg-neutral-800 text-neutral-200 flex items-cen
  ter justify-center font-bold text-[10px] shrink-0 mt-0.5">1</span>
               <span>Tap the <strong className="text-white">three dots menu ( )</strong> in Chrome
  at the top right.</span>
             </li>
             <li className="flex items-start gap-2">
               <span className="w-5 h-5 rounded-full bg-neutral-800 text-neutral-200 flex items-cen
  ter justify-center font-bold text-[10px] shrink-0 mt-0.5">2</span>
               <span>Select <strong className="text-white">Install app</strong> or <strong classNam
  e="text-white">Add to Home screen</strong>.</span>
             </li>
             <li className="flex items-start gap-2">
               <span className="w-5 h-5 rounded-full bg-neutral-800 text-neutral-200 flex items-cen
  ter justify-center font-bold text-[10px] shrink-0 mt-0.5">3</span>
               <span>Confirm install to add the STUDSPOT icon to your phone launcher.</span>
             </li>
           </ol>
         </div>
       )}

       <div className="pt-1 flex items-center justify-between text-[11px] text-neutral-400">
         <span className="flex items-center gap-1">
           <ShieldCheck className="w-3.5 h-3.5 text-emerald-400" />
           100% Free & Safe PWA
         </span>
         <button
           onClick={onClose}
           className="hover:underline text-neutral-300"
         >
           Close
         </button>
       </div>
     </div>
   </div>
  );
};

export const PWAInstallButton: React.FC<{ className?: string; variant?: 'button' | 'badge' | 'banner
  ' }> = ({
  className = '',
  variant = 'button',
}) => {
  const { isInstallable, isInstalled, install, isIOS } = usePWAInstall();
  const [showModal, setShowModal] = useState(false);

  // If already installed in standalone mode, return null or subtle badge
  if (isInstalled) {
    return null;
```

```
}

if (variant === 'badge') {
  return (
    <>
      <button
        onClick={() => {
          if (isInstallable) {
            install();
          } else {
            setShowModal(true);
          }
        }}
        className={`flex items-center gap-1.5 px-2.5 py-1 rounded-xl text-xs font-bold bg-[#F3B71B
]/15 hover:bg-[#F3B71B]/25 text-[#F3B71B] border border-[#F3B71B]/40 transition ${className}`}
        title="Add STUDSPOT to Home Screen"
      >
        <Download className="w-3.5 h-3.5" />
        <span className="hidden sm:inline">Add to Home Screen</span>
        <span className="sm:hidden">Install App</span>
      </button>
      <PWAInstallModal isOpen={showModal} onClose={() => setShowModal(false)} />
    </>
  );
}

if (variant === 'banner') {
  return (
    <>
      <div className="bg-gradient-to-r from-[#1E293B] via-[#0F172A] to-[#1E293B] border border-cya
n-500/30 rounded-2xl p-3 flex items-center justify-between gap-3 text-white shadow-lg">
        <div className="flex items-center gap-3">
          <div className="w-10 h-10 rounded-xl overflow-hidden bg-black p-0.5 border border-cyan-4
00/50 shrink-0">
            <img
              src="/src/assets/images/studspot_official_icon_1791805148976.jpg"
              alt="STUDSPOT"
              className="w-full h-full object-cover rounded-lg"
            />
          </div>
          <div>
            <p className="text-xs font-bold text-white flex items-center gap-1.5">
              Install STUDSPOT on your phone
              <span className="text-[9px] bg-[#F3B71B] text-black px-1.5 py-0.2 rounded font-black
 font-mono">PWA</span>
            </p>
            <p className="text-[11px] text-neutral-300">
              Faster loading, zero browser bars & instant comrade listings
            </p>
          </div>
        </div>
        <button
          onClick={() => {
            if (isInstallable) {
              install();
            } else {
              setShowModal(true);
            }
          }}
          className="px-3.5 py-1.5 bg-[#F3B71B] hover:bg-[#dca415] text-black font-extrabold text-
xs rounded-xl whitespace-nowrap transition shadow-sm flex items-center gap-1.5 shrink-0"
        >
          <Download className="w-3.5 h-3.5 stroke-[2.5]" />
          <span>Install</span>
        </button>
      </div>
      <PWAInstallModal isOpen={showModal} onClose={() => setShowModal(false)} />
    </>
  );
}
```

```
  return (
    <>
      <button
        onClick={() => {
          if (isInstallable) {
            install();
          } else {
            setShowModal(true);
          }
        }}
        className={`flex items-center gap-2 rounded-xl bg-[#F3B71B] hover:bg-[#dca415] px-3 py-1.5 t
  ext-xs font-black text-black shadow-sm transition ${className}`}
      >
        <Download className="w-4 h-4 stroke-[2.5]" />
        <span>Add to Home Screen</span>
      </button>
      <PWAInstallModal isOpen={showModal} onClose={() => setShowModal(false)} />
    </>
  );
};
```

```
import React, { useEffect, useState } from 'react';
import { WifiOff } from 'lucide-react';

export function useOnlineStatus() {
  const [isOnline, setIsOnline] = useState(
    typeof navigator !== 'undefined' ? navigator.onLine : true
  );

  useEffect(() => {
    const handleOnline = () => setIsOnline(true);
    const handleOffline = () => setIsOnline(false);

    window.addEventListener('online', handleOnline);
    window.addEventListener('offline', handleOffline);

    return () => {
      window.removeEventListener('online', handleOnline);
      window.removeEventListener('offline', handleOffline);
    };
  }, []);

  return isOnline;
}

export const OfflineIndicator: React.FC = () => {
  const isOnline = useOnlineStatus();

  if (isOnline) return null;

  return (
    <div className="fixed bottom-4 left-4 z-50 flex items-center gap-2 rounded-xl bg-amber-500/95 ba
  ckdrop-blur-md px-3.5 py-2 text-xs font-bold text-black shadow-2xl border border-amber-300 animate
  -in fade-in slide-in-from-bottom-2">
      <WifiOff className="w-4 h-4 text-black shrink-0" />
      <span>Offline Mode   Cached STUDSPOT data is being used.</span>
    </div>
  );
};
```

```
import React from 'react';

interface StudspotLogoProps {
  className?: string;
  size?: 'xs' | 'sm' | 'md' | 'lg' | 'xl';
  variant?: 'icon' | 'full' | 'app-icon' | 'badge';
  theme?: 'dark' | 'light' | 'auto';
  showTagline?: boolean;
}

export const StudspotLogo: React.FC<StudspotLogoProps> = ({
  className = '',
  size = 'md',
  variant = 'icon',
  theme = 'auto',
  showTagline = false,
}) => {
  // Dimension presets
  const sizeMap = {
    xs: { icon: 'w-6 h-6', text: 'text-xs', mark: 24 },
    sm: { icon: 'w-8 h-8', text: 'text-sm', mark: 32 },
    md: { icon: 'w-10 h-10', text: 'text-base', mark: 40 },
    lg: { icon: 'w-14 h-14', text: 'text-xl', mark: 56 },
    xl: { icon: 'w-20 h-20', text: 'text-2xl', mark: 80 },
  };

  const currentSize = sizeMap[size] || sizeMap.md;

  // The official logo image generated directly from the user's uploaded logo specification
  const logoImgSrc = '/src/assets/images/studspot_official_icon_1791805148976.jpg';

  // SVG Vector Mark Representation (crisp, scalable vector of the official logo)
  const SvgMark = (
    <div className={`relative ${currentSize.icon} shrink-0 rounded-2xl overflow-hidden shadow-sm bg-
  gradient-to-br from-[#0F2D59] to-[#08182F] p-0.5 border border-cyan-500/30 flex items-center justi
  fy-center`}>
      <img
        src={logoImgSrc}
        alt="STUDSPOT Logo"
        className="w-full h-full object-cover rounded-xl"
        loading="eager"
      />
    </div>
  );

  if (variant === 'icon') {
    return (
      <div className={`inline-flex items-center ${className}`}>
        {SvgMark}
      </div>
    );
  }

  if (variant === 'app-icon') {
    return (
      <div className={`inline-flex flex-col items-center gap-1.5 ${className}`}>
        <div className="relative rounded-2xl overflow-hidden shadow-2xl p-1 bg-gradient-to-b from-[#
  1E293B] to-[#0F172A] border border-neutral-700/80 hover:border-cyan-400/50 transition-all group">
          <img
            src={logoImgSrc}
            alt="STUDSPOT App Icon"
            className={`${currentSize.icon} object-cover rounded-xl group-hover:scale-105 transition
  -transform`}
          />
        </div>
        <span className="font-heading font-black tracking-tight text-white uppercase text-xs">
          STUDSPOT
        </span>
      </div>
    );
```

```
  }

  // Full variant: Logo mark + bold STUDSPOT typography
  return (
    <div className={`inline-flex items-center gap-2.5 ${className}`}>
      {SvgMark}
      <div className="flex flex-col leading-none">
        <div className="flex items-center gap-1.5">
          <span className={`font-heading font-black tracking-tight text-white ${currentSize.text}`}>
            STUDSPOT
          </span>
          <span className="text-[9px] font-bold text-black bg-[#F3B71B] px-1.5 py-0.2 rounded font-m
  ono">
            KENYA
          </span>
        </div>
        {showTagline ? (
          <span className="text-[10px] text-neutral-400 font-medium tracking-normal mt-0.5">
            Campus Marketplace & Community
          </span>
        ) : null}
      </div>
    </div>
  );
};
```

```
import { useEffect, useState } from 'react';

interface BeforeInstallPromptEvent extends Event {
  prompt: () => Promise<void>;
  userChoice: Promise<{ outcome: 'accepted' | 'dismissed'; platform: string }>;
}

export function usePWAInstall() {
  const [deferredPrompt, setDeferredPrompt] = useState<BeforeInstallPromptEvent | null>(null);
  const [isInstalled, setIsInstalled] = useState(false);
  const [isIOS, setIsIOS] = useState(false);

  useEffect(() => {
    // Detect standalone mode (already installed or launched from home screen)
    const isStandalone =
      window.matchMedia('(display-mode: standalone)').matches ||
      (window.navigator as unknown as { standalone?: boolean }).standalone === true;
    setIsInstalled(isStandalone);

    // Detect iOS devices (Safari does not fire beforeinstallprompt)
    const userAgent = window.navigator.userAgent.toLowerCase();
    const isIOSDevice = /iphone|ipad|ipod/.test(userAgent);
    setIsIOS(isIOSDevice);

    const handleBeforeInstallPrompt = (e: Event) => {
      e.preventDefault();
      setDeferredPrompt(e as BeforeInstallPromptEvent);
    };

    const handleAppInstalled = () => {
      setIsInstalled(true);
      setDeferredPrompt(null);
    };

    window.addEventListener('beforeinstallprompt', handleBeforeInstallPrompt);
    window.addEventListener('appinstalled', handleAppInstalled);

    return () => {
      window.removeEventListener('beforeinstallprompt', handleBeforeInstallPrompt);
      window.removeEventListener('appinstalled', handleAppInstalled);
    };
  }, []);

  const install = async () => {
    if (!deferredPrompt) return false;
    await deferredPrompt.prompt();
    const { outcome } = await deferredPrompt.userChoice;
    if (outcome === 'accepted') {
      setIsInstalled(true);
      setDeferredPrompt(null);
      return true;
    }
    return false;
  };

  return {
    isInstallable: !!deferredPrompt,
    isInstalled,
    isIOS,
    install,
    deferredPrompt,
  };
}
```

```
import { University, InstitutionType } from '../types';
import { UNIVERSITIES } from '../data/seedData';

const CUSTOM_CAMPUSES_KEY = 'studspot_custom_campuses';

// Load stored custom campuses from localStorage
export const getStoredCustomCampuses = (): University[] => {
  try {
    const raw = localStorage.getItem(CUSTOM_CAMPUSES_KEY);
    if (!raw) return [];
    const parsed = JSON.parse(raw);
    return Array.isArray(parsed) ? parsed : [];
  } catch (e) {
    console.warn('Failed to parse custom campuses from storage', e);
    return [];
  }
};

// Save a new custom campus
export const saveCustomCampus = (
  name: string,
  institutionType: InstitutionType = 'university',
  branch: string = 'Main Campus',
  city: string = 'Kenya'
): University => {
  const trimmedName = name.trim();
  if (!trimmedName) {
    throw new Error('Campus name cannot be empty');
  }

  const slug = trimmedName.toLowerCase().replace(/[^a-z0-9]/g, '_').substring(0, 30);
  const id = `custom_${slug}_${Date.now() % 10000}`;

  const categoryLabel =
    institutionType === 'kmtc' ? 'KMTC Campus' :
    institutionType === 'polytechnic' ? 'National Polytechnic' :
    institutionType === 'tvet' ? 'TVET Institute' : 'University';

  const newUni: University = {
    id,
    name: trimmedName,
    shortName: trimmedName.length > 20 ? trimmedName.substring(0, 18) + '...' : trimmedName,
    city: city || 'Kenya',
    campuses: [branch.trim() || 'Main Campus'],
    studentCount: 'Active Comrades',
    institutionType,
    categoryLabel: `${categoryLabel} (Custom)`
  };

  try {
    const existing = getStoredCustomCampuses();
    // Prevent duplicate exact names
    const filtered = existing.filter(u => u.name.toLowerCase() !== trimmedName.toLowerCase());
    const updated = [newUni, ...filtered];
    localStorage.setItem(CUSTOM_CAMPUSES_KEY, JSON.stringify(updated));
    // Dispatch window custom event so other components update synchronously
    if (typeof window !== 'undefined') {
      window.dispatchEvent(new CustomEvent('studspot_campuses_updated', { detail: newUni }));
    }
  } catch (e) {
    console.warn('Failed to persist custom campus', e);
  }

  return newUni;
};

// Get combined list of default seed universities and user-typed custom campuses
export const getAllCampuses = (): University[] => {
  const customList = getStoredCustomCampuses();
  // Filter out any default ones if conflict
```

```
  const existingIds = new Set(UNIVERSITIES.map(u => u.id));
  const uniqueCustom = customList.filter(u => !existingIds.has(u.id));
  return [...UNIVERSITIES, ...uniqueCustom];
};
```

```
import { University, Listing, CommunityPost, User } from '../types';

export const UNIVERSITIES: University[] = [
  {
    id: 'all',
    name: 'All Campuses (Kenya)',
    shortName: 'All Kenya',
    city: 'Nationwide',
    campuses: ['All Campuses'],
    studentCount: '500,000+',
    institutionType: 'all',
    categoryLabel: 'All Institutions'
  },
  // UNIVERSITIES
  {
    id: 'uon',
    name: 'University of Nairobi',
    shortName: 'UoN',
    city: 'Nairobi',
    campuses: ['Main Campus', 'Chiromo Campus', 'Parklands Campus', 'Lower Kabete', 'Upper Kabete',
  'Kikuyu Campus'],
    studentCount: '84,000+',
    institutionType: 'university',
    categoryLabel: 'University'
  },
  {
    id: 'ku',
    name: 'Kenyatta University',
    shortName: 'KU',
    city: 'Nairobi / Ruiru',
    campuses: ['Main Campus (Kahawa)', 'Parklands', 'City Campus', 'Ruiru Campus'],
    studentCount: '70,000+',
    institutionType: 'university',
    categoryLabel: 'University'
  },
  {
    id: 'jkuat',
    name: 'Jomo Kenyatta Univ. of Agriculture & Tech',
    shortName: 'JKUAT',
    city: 'Juja, Kiambu',
    campuses: ['Juja Main Campus', 'Nairobi CBD Campus', 'Karen Campus'],
    studentCount: '45,000+',
    institutionType: 'university',
    categoryLabel: 'University'
  },
  {
    id: 'strathmore',
    name: 'Strathmore University',
    shortName: 'Strathmore',
    city: 'Nairobi (Madaraka)',
    campuses: ['Madaraka Main Campus'],
    studentCount: '12,000+',
    institutionType: 'university',
    categoryLabel: 'University'
  },
  {
    id: 'usiu',
    name: 'United States International University - Africa',
    shortName: 'USIU-A',
    city: 'Nairobi (Roysambu)',
    campuses: ['Safari Park / Roysambu Campus'],
    studentCount: '10,000+',
    institutionType: 'university',
    categoryLabel: 'University'
  },
  {
    id: 'tuk',
    name: 'Technical University of Kenya',
    shortName: 'TUK',
    city: 'Nairobi CBD',
```

```
  campuses: ['Haile Selassie Main Campus'],
  studentCount: '25,000+',
  institutionType: 'university',
  categoryLabel: 'University'
},
{
  id: 'moi',
  name: 'Moi University',
  shortName: 'Moi Univ',
  city: 'Eldoret',
  campuses: ['Main Campus (Kesses)', 'Town Campus', 'Annex Law Campus'],
  studentCount: '38,000+',
  institutionType: 'university',
  categoryLabel: 'University'
},
{
  id: 'egerton',
  name: 'Egerton University',
  shortName: 'Egerton',
  city: 'Njoro, Nakuru',
  campuses: ['Njoro Main Campus', 'Nakuru Town Campus'],
  studentCount: '22,000+',
  institutionType: 'university',
  categoryLabel: 'University'
},
{
  id: 'daystar',
  name: 'Daystar University',
  shortName: 'Daystar',
  city: 'Machakos / Nairobi',
  campuses: ['Athi River Campus', 'Valley Road Nairobi'],
  studentCount: '8,000+',
  institutionType: 'university',
  categoryLabel: 'University'
},
{
  id: 'mku',
  name: 'Mount Kenya University',
  shortName: 'MKU',
  city: 'Thika / Nairobi',
  campuses: ['Thika Main Campus', 'Parklands Law Campus', 'Nairobi CBD'],
  studentCount: '52,000+',
  institutionType: 'university',
  categoryLabel: 'University'
},
{
  id: 'kisii_uni',
  name: 'Kisii University',
  shortName: 'KSII / Kisii Uni',
  city: 'Kisii',
  campuses: ['Main Campus (Kisii)', 'Eldoret Campus', 'Kericho Campus', 'Kisumu Campus', 'Nairobi
Campus'],
  studentCount: '32,000+',
  institutionType: 'university',
  categoryLabel: 'University'
},
{
  id: 'maseno',
  name: 'Maseno University',
  shortName: 'Maseno Uni',
  city: 'Maseno / Kisumu',
  campuses: ['Siriba Main Campus', 'College Campus', 'Kisumu City Campus'],
  studentCount: '24,000+',
  institutionType: 'university',
  categoryLabel: 'University'
},
{
  id: 'kca',
  name: 'KCA University',
  shortName: 'KCA Uni',
```

```
  city: 'Nairobi (Ruaraka)',
  campuses: ['Ruaraka Main Campus', 'Nairobi CBD', 'Western Campus'],
  studentCount: '20,000+',
  institutionType: 'university',
  categoryLabel: 'University'
},
{
  id: 'mmust',
  name: 'Masinde Muliro Univ. of Science & Technology',
  shortName: 'MMUST Kakamega',
  city: 'Kakamega',
  campuses: ['Main Campus (Kakamega)', 'Webuye Campus'],
  studentCount: '26,000+',
  institutionType: 'university',
  categoryLabel: 'University'
},
{
  id: 'chuka',
  name: 'Chuka University',
  shortName: 'Chuka Uni',
  city: 'Chuka, Tharaka Nithi',
  campuses: ['Main Campus', 'Embu Campus', 'Igembe Campus'],
  studentCount: '19,000+',
  institutionType: 'university',
  categoryLabel: 'University'
},
{
  id: 'other_custom',
  name: 'Other Campus (Type Your Own)',
  shortName: 'Other / Custom',
  city: 'Nationwide',
  campuses: ['Main Campus', 'Town Campus', 'Hostel Zone'],
  studentCount: 'Comrades',
  institutionType: 'all',
  categoryLabel: 'Custom Campus'
},

// KMTC (KENYA MEDICAL TRAINING COLLEGE) CAMPUSES
{
  id: 'kmtc_nairobi',
  name: 'KMTC Nairobi Campus (Mbagathi / KNH)',
  shortName: 'KMTC Nairobi',
  city: 'Nairobi',
  campuses: ['Mbagathi Way Main Gate', 'KNH Complex Gate', 'Karen Faculty'],
  studentCount: '8,500+',
  institutionType: 'kmtc',
  categoryLabel: 'KMTC Campus'
},
{
  id: 'kmtc_mombasa',
  name: 'KMTC Mombasa Campus',
  shortName: 'KMTC Mombasa',
  city: 'Mombasa',
  campuses: ['Coast General Hospital Gate', 'Port Reitz Satellite'],
  studentCount: '3,200+',
  institutionType: 'kmtc',
  categoryLabel: 'KMTC Campus'
},
{
  id: 'kmtc_kisumu',
  name: 'KMTC Kisumu Campus (JOOTRH)',
  shortName: 'KMTC Kisumu',
  city: 'Kisumu',
  campuses: ['JOOTRH Teaching Gate', 'Kondele Road Main Gate'],
  studentCount: '3,000+',
  institutionType: 'kmtc',
  categoryLabel: 'KMTC Campus'
},
{
  id: 'kmtc_nakuru',
```

```
    name: 'KMTC Nakuru Campus (PGH)',
    shortName: 'KMTC Nakuru',
    city: 'Nakuru',
    campuses: ['Provincial General Hospital (PGH)', 'Milimani Faculty'],
    studentCount: '2,800+',
    institutionType: 'kmtc',
    categoryLabel: 'KMTC Campus'
  },
  {
    id: 'kmtc_eldoret',
    name: 'KMTC Eldoret Campus (MTRH)',
    shortName: 'KMTC Eldoret',
    city: 'Eldoret',
    campuses: ['Moi Teaching & Referral (MTRH)', 'Nandi Road Gate'],
    studentCount: '2,900+',
    institutionType: 'kmtc',
    categoryLabel: 'KMTC Campus'
  },
  {
    id: 'kmtc_nyeri',
    name: 'KMTC Nyeri Campus',
    shortName: 'KMTC Nyeri',
    city: 'Nyeri',
    campuses: ['Nyeri PGH Gate', 'Mathari Complex'],
    studentCount: '2,100+',
    institutionType: 'kmtc',
    categoryLabel: 'KMTC Campus'
  },
  {
    id: 'kmtc_thika',
    name: 'KMTC Thika Campus',
    shortName: 'KMTC Thika',
    city: 'Thika',
    campuses: ['Thika Level 5 Gate', 'General Kago Road'],
    studentCount: '2,400+',
    institutionType: 'kmtc',
    categoryLabel: 'KMTC Campus'
  },
  {
    id: 'kmtc_machakos',
    name: 'KMTC Machakos Campus',
    shortName: 'KMTC Machakos',
    city: 'Machakos',
    campuses: ['Machakos Level 5 Hospital Gate'],
    studentCount: '2,000+',
    institutionType: 'kmtc',
    categoryLabel: 'KMTC Campus'
  },
  {
    id: 'kmtc_kakamega',
    name: 'KMTC Kakamega Campus',
    shortName: 'KMTC Kakamega',
    city: 'Kakamega',
    campuses: ['Kakamega General Hospital Gate'],
    studentCount: '2,200+',
    institutionType: 'kmtc',
    categoryLabel: 'KMTC Campus'
  },
  {
    id: 'kmtc_kisii',
    name: 'KMTC Kisii Campus',
    shortName: 'KMTC Kisii',
    city: 'Kisii',
    campuses: ['Kisii Teaching & Referral Gate'],
    studentCount: '2,300+',
    institutionType: 'kmtc',
    categoryLabel: 'KMTC Campus'
  },

  // NATIONAL POLYTECHNICS
```

```
{
  id: 'kabete_poly',
  name: 'The Kabete National Polytechnic',
  shortName: 'Kabete Poly',
  city: 'Nairobi (Waiyaki Way)',
  campuses: ['Waiyaki Way Main Gate', 'Uthiru Lower Gate', 'Administration Block'],
  studentCount: '18,000+',
  institutionType: 'polytechnic',
  categoryLabel: 'National Polytechnic'
},
{
  id: 'kcnp',
  name: 'Kenya Coast National Polytechnic',
  shortName: 'Coast Poly (KCNP)',
  city: 'Mombasa',
  campuses: ['Kisauni Main Gate', 'Mvita Center'],
  studentCount: '15,000+',
  institutionType: 'polytechnic',
  categoryLabel: 'National Polytechnic'
},
{
  id: 'kisumu_poly',
  name: 'The Kisumu National Polytechnic',
  shortName: 'Kisumu Poly',
  city: 'Kisumu',
  campuses: ['Nairobi Road Main Gate', 'Polytechnic Grounds'],
  studentCount: '16,000+',
  institutionType: 'polytechnic',
  categoryLabel: 'National Polytechnic'
},
{
  id: 'eldoret_poly',
  name: 'The Eldoret National Polytechnic',
  shortName: 'Eldoret Poly',
  city: 'Eldoret',
  campuses: ['Langas Main Gate', 'Engineering Workshops'],
  studentCount: '17,000+',
  institutionType: 'polytechnic',
  categoryLabel: 'National Polytechnic'
},
{
  id: 'nyeri_poly',
  name: 'The Nyeri National Polytechnic',
  shortName: 'Nyeri Poly',
  city: 'Nyeri',
  campuses: ['Outspan Road Main Gate'],
  studentCount: '12,000+',
  institutionType: 'polytechnic',
  categoryLabel: 'National Polytechnic'
},
{
  id: 'sigalagala_poly',
  name: 'The Sigalagala National Polytechnic',
  shortName: 'Sigalagala Poly',
  city: 'Kakamega',
  campuses: ['Sigalagala Main Gate', 'Town Wing'],
  studentCount: '14,000+',
  institutionType: 'polytechnic',
  categoryLabel: 'National Polytechnic'
},
{
  id: 'meru_poly',
  name: 'The Meru National Polytechnic',
  shortName: 'Meru Poly',
  city: 'Meru',
  campuses: ['Nchiru Main Gate'],
  studentCount: '13,000+',
  institutionType: 'polytechnic',
  categoryLabel: 'National Polytechnic'
},
```

```
{
  id: 'kitale_poly',
  name: 'The Kitale National Polytechnic',
  shortName: 'Kitale Poly',
  city: 'Kitale / Trans Nzoia',
  campuses: ['Kitale Town Main Gate'],
  studentCount: '11,000+',
  institutionType: 'polytechnic',
  categoryLabel: 'National Polytechnic'
},

// TVET COLLEGES & INSTITUTES
{
  id: 'ntti',
  name: 'Nairobi Technical Training Institute',
  shortName: 'Nairobi Tech (NTTI)',
  city: 'Nairobi (Ngara)',
  campuses: ['Ngara Ring Road Main Gate', 'Park Road Wing'],
  studentCount: '14,000+',
  institutionType: 'tvet',
  categoryLabel: 'TVET Institute'
},
{
  id: 'kinyanjui_tech',
  name: 'PC Kinyanjui Technical Training Institute',
  shortName: 'PC Kinyanjui TTI',
  city: 'Nairobi (Riruta)',
  campuses: ['Riruta Main Gate', 'Kabiria Wing'],
  studentCount: '10,000+',
  institutionType: 'tvet',
  categoryLabel: 'TVET Institute'
},
{
  id: 'rvtti',
  name: 'Rift Valley Technical Training Institute',
  shortName: 'RVTTI Eldoret',
  city: 'Eldoret',
  campuses: ['Kapsabet Road Main Gate', 'Town Center'],
  studentCount: '16,000+',
  institutionType: 'tvet',
  categoryLabel: 'TVET Institute'
},
{
  id: 'kist',
  name: 'Kiambu Institute of Science and Technology',
  shortName: 'KIST Kiambu',
  city: 'Kiambu',
  campuses: ['Kiambu Road Main Gate', 'Engineering Quad'],
  studentCount: '9,000+',
  institutionType: 'tvet',
  categoryLabel: 'TVET Institute'
},
{
  id: 'thika_tvet',
  name: 'Thika Technical Training Institute',
  shortName: 'Thika Tech TTI',
  city: 'Thika',
  campuses: ['Hospital Road Main Gate'],
  studentCount: '8,500+',
  institutionType: 'tvet',
  categoryLabel: 'TVET Institute'
},
{
  id: 'riat',
  name: 'Ramogi Institute of Advanced Technology',
  shortName: 'RIAT Kisumu',
  city: 'Kisumu',
  campuses: ['Riat Hills Main Gate'],
  studentCount: '9,500+',
  institutionType: 'tvet',
```

```
    categoryLabel: 'TVET Institute'
  },
  {
    id: 'kaiboi_tvet',
    name: 'Kaiboi Technical Training Institute',
    shortName: 'Kaiboi TTI',
    city: 'Nandi / Eldoret',
    campuses: ['Kaiboi Main Gate'],
    studentCount: '7,500+',
    institutionType: 'tvet',
    categoryLabel: 'TVET Institute'
  }
];

export const INITIAL_USERS: User[] = [
  {
    id: 'usr-1',
    fullName: 'Brian Mwangi',
    email: 'bmwangi@students.jkuat.ac.ke',
    phone: '+254712345678',
    universityId: 'jkuat',
    campusName: 'Juja Main Campus',
    studentRegNo: 'SCT211-0021/2022',
    role: 'student',
    agreedToTerms: true,
    createdAt: '2026-09-01',
    isVerifiedStudent: true
  },
  {
    id: 'usr-2',
    fullName: 'Stacy Wanjiku',
    email: 'swanjiku@strathmore.edu',
    phone: '+254798765432',
    universityId: 'strathmore',
    campusName: 'Madaraka Main Campus',
    studentRegNo: 'ST-09241/2023',
    role: 'student',
    agreedToTerms: true,
    createdAt: '2026-09-10',
    isVerifiedStudent: true
  },
  {
    id: 'usr-3',
    fullName: 'James Kamau',
    email: 'hostels@sunsetcourt.co.ke',
    phone: '+254721445566',
    universityId: 'jkuat',
    campusName: 'Juja Main Campus',
    role: 'vendor',
    agreedToTerms: true,
    createdAt: '2026-08-15',
    isVerifiedStudent: false
  },
  {
    id: 'usr-admin',
    fullName: 'STUDSPOT Admin Console',
    email: 'admin@studspot.co.ke',
    phone: '+254700112233',
    universityId: 'all',
    campusName: 'STUDSPOT HQ Nairobi',
    role: 'admin',
    agreedToTerms: true,
    createdAt: '2026-01-01',
    isVerifiedStudent: true
  }
];

export const INITIAL_LISTINGS: Listing[] = [
  // 1. MARKETPLACE ITEMS (Approved)
  {
```

```
  id: 'item-1',
  type: 'item',
  title: 'MacBook Pro M1 8GB/256GB (Battery 91%, Like New)',
  description: 'Clean unit with original 67W USB-C brick and Braided MagSafe cable. Perfect for Co
mputer Science, Software Engineering or Data Science students. No dents or display issues. Selling
 to upgrade.',
  price: 58000,
  priceLabel: '',
  isNegotiable: true,
  category: 'Electronics',
  image: '/src/assets/images/student_cyber_tech_1791796604735.jpg',
  universityId: 'jkuat',
  campusName: 'Juja Main Campus',
  seller: {
    name: 'Brian Mwangi',
    role: 'student',
    courseOrBiz: 'BSc. Computer Science',
    yearOfStudy: 'Year 4',
    phone: '+254712345678',
    whatsapp: '254712345678',
    isVerifiedStudent: true,
    trustScore: 99,
    reviewsCount: 18,
    safeSpot: 'JKUAT Library Gate A / Student Center',
    mpesaNumber: '0712 345 678'
  },
  details: {
    condition: 'Like New',
    itemCategory: 'Electronics'
  },
  isApproved: true,
  isFeePaid: true,
  mpesaRef: 'QK948XP12',
  listingFeeKsh: 80,
  createdAt: '2 hours ago',
  viewsCount: 342,
  likesCount: 29,
  featured: true
},
{
  id: 'item-2',
  type: 'item',
  title: 'Vintage Oversized Denim Jacket + NBO Streetwear Hoodie',
  description: 'Fresh curated thrift drop directly from Gikomba premium bale. Washed and ironed. F
its medium/large oversized. Great for chilly Nairobi campus mornings and casual lecture drip.',
  price: 1800,
  priceLabel: '',
  isNegotiable: false,
  category: 'Fashion & Thrift',
  image: '/src/assets/images/campus_thrift_fashion_1791796594005.jpg',
  universityId: 'strathmore',
  campusName: 'Madaraka Main Campus',
  seller: {
    name: 'Stacy Wanjiku',
    role: 'student',
    courseOrBiz: 'B.Com & Thrift Hustler',
    yearOfStudy: 'Year 3',
    phone: '+254798765432',
    whatsapp: '254798765432',
    isVerifiedStudent: true,
    trustScore: 96,
    reviewsCount: 34,
    safeSpot: 'Student Center Courtyard / Cafeteria',
    tillNumber: 'Till 892341'
  },
  details: {
    condition: 'Good Condition',
    itemCategory: 'Fashion & Thrift'
  },
  isApproved: true,
```

```
  isFeePaid: true,
  mpesaRef: 'QK812NY04',
  listingFeeKsh: 80,
  createdAt: '4 hours ago',
  viewsCount: 198,
  likesCount: 42,
  featured: true
},
{
  id: 'item-3',
  type: 'item',
  title: 'Engineering Mathematics 7th Ed (Stroud) + Chiromo Past CATs',
  description: 'Clean textbook with clear step-by-step calculus, differential equations and linear
 algebra examples. Includes printouts of 2023-2025 past continuous assessment tests and marking sc
hemes.',
  price: 1600,
  priceLabel: '',
  isNegotiable: true,
  category: 'Textbooks',
  image: '/src/assets/images/hero_campus_marketplace_1791796569675.jpg',
  universityId: 'uon',
  campusName: 'Chiromo Campus',
  seller: {
    name: 'Kevin Ochieng',
    role: 'student',
    courseOrBiz: 'BSc. Electrical Engineering',
    yearOfStudy: 'Year 4',
    phone: '+254722119933',
    whatsapp: '254722119933',
    isVerifiedStudent: true,
    trustScore: 98,
    reviewsCount: 12,
    safeSpot: 'Chiromo Physical Sciences Foyer',
    mpesaNumber: '0722 119 933'
  },
  details: {
    condition: 'Good Condition',
    itemCategory: 'Textbooks'
  },
  isApproved: true,
  isFeePaid: true,
  mpesaRef: 'QK772BZ88',
  listingFeeKsh: 80,
  createdAt: 'Yesterday',
  viewsCount: 220,
  likesCount: 19,
  isSold: true,
  soldAt: 'Yesterday',
  soldPrice: 1600
},
{
  id: 'item-4',
  type: 'item',
  title: 'Hostel Starter Bundle: Ramtons Kettle 1.7L + Hot Plate + Rice Cooker',
  description: 'Complete non-stick kitchen set for incoming first years or students moving off-cam
pus into bedsitters. All appliances in 100% working order, clean and energy saving.',
  price: 3800,
  priceLabel: '',
  isNegotiable: true,
  category: 'Hostel Appliances',
  image: '/src/assets/images/hostel_student_room_1791796581832.jpg',
  universityId: 'ku',
  campusName: 'Main Campus (Kahawa)',
  seller: {
    name: 'Naomi Cherotich',
    role: 'student',
    courseOrBiz: 'B.Ed Science (Graduating)',
    yearOfStudy: 'Alumni',
    phone: '+254705544332',
    whatsapp: '254705544332',
```

```
    isVerifiedStudent: true,
    trustScore: 100,
    reviewsCount: 15,
    safeSpot: 'KU Post Office / Nyayo Hostels Gate',
    mpesaNumber: '0705 544 332'
  },
  details: {
    condition: 'Like New',
    itemCategory: 'Hostel Appliances'
  },
  isApproved: true,
  isFeePaid: true,
  mpesaRef: 'QK651AK99',
  listingFeeKsh: 80,
  createdAt: '3 days ago',
  viewsCount: 512,
  likesCount: 67
},

// 2. HOUSING / HOSTELS (Approved)
{
  id: 'hostel-1',
  type: 'hostel',
  title: 'Sunset View Executive Bedsitter (4 Mins Walk to Gate C)',
  description: 'Modern ceramic tiled bedsitter with built-in wardrobe, dedicated kitchenette with
sink and storage shelves, private ceramic bathroom, large windows for natural light. Token prepaid
 power meter, 24/7 borehole water with pressure pump.',
  price: 8500,
  priceLabel: '/month',
  isNegotiable: false,
  category: 'Housing (Hostels)',
  image: '/src/assets/images/hostel_student_room_1791796581832.jpg',
  universityId: 'jkuat',
  campusName: 'Juja Main Campus',
  seller: {
    name: 'James Kamau (Caretaker)',
    role: 'hostel_caretaker',
    courseOrBiz: 'Sunset Court Management',
    phone: '+254721445566',
    whatsapp: '254721445566',
    isVerifiedStudent: false,
    trustScore: 97,
    reviewsCount: 29,
    safeSpot: 'Gate C Police Post / Sunset Gate',
    tillNumber: 'Paybill 247247'
  },
  details: {
    hostelType: 'Bedsitter',
    distanceToGate: '4 mins walk (Gate C)',
    waterStatus: '24/7 Borehole + City Water',
    electricityType: 'Prepaid Token Meter',
    wifiAvailable: true,
    securityGuard: true,
    roomFeatures: ['Kitchenette with sink', 'Prepaid token meter', 'CCTV & Night guard', 'High-spe
ed Wi-Fi included', 'Garbage collection included']
  },
  isApproved: true,
  isFeePaid: true,
  mpesaRef: 'QK543LK11',
  listingFeeKsh: 80,
  createdAt: '1 day ago',
  viewsCount: 684,
  likesCount: 88,
  featured: true
},
{
  id: 'hostel-2',
  type: 'hostel',
  title: 'Greenland Student Residency - Furnished Single Room',
  description: 'Secure, clean single room inside student residential complex. Includes single bed
```

```
with foam mattress, study desk, ergonomic chair, and bookshelf. Common modern washrooms cleaned tw
ice daily. Near Kahawa Sukari gate.',
  price: 5500,
  priceLabel: '/month',
  isNegotiable: false,
  category: 'Housing (Hostels)',
  image: '/src/assets/images/hostel_student_room_1791796581832.jpg',
  universityId: 'ku',
  campusName: 'Main Campus (Kahawa)',
  seller: {
    name: 'Grace Mutua',
    role: 'hostel_caretaker',
    courseOrBiz: 'Greenland Hostels Admin',
    phone: '+254733881122',
    whatsapp: '254733881122',
    isVerifiedStudent: false,
    trustScore: 95,
    reviewsCount: 41,
    safeSpot: 'Kahawa Sukari QuickMart Gate',
    tillNumber: 'Till 655431'
  },
  details: {
    hostelType: 'Single Room',
    distanceToGate: '7 mins walk to KU Footbridge',
    waterStatus: 'Constant Water Supply',
    electricityType: 'Included in rent',
    wifiAvailable: true,
    securityGuard: true,
    roomFeatures: ['Bed + Study desk provided', 'Hot shower installations', 'Biometric entry gate'
, 'Free high-speed fiber internet']
  },
  isApproved: true,
  isFeePaid: true,
  mpesaRef: 'QK421MN78',
  listingFeeKsh: 80,
  createdAt: '3 days ago',
  viewsCount: 430,
  likesCount: 52
},

// 3. JOBS & GIGS (Approved)
{
  id: 'gig-1',
  type: 'gig',
  title: 'Academic Thesis Formatting & APA 7th Referencing Assistant',
  description: 'Need an organized student to format 45 pages of postgraduate research proposal acc
ording to UoN guidelines: Table of contents, figure numbering, APA 7th in-text citations and refer
ence list clean-up. Turnaround: 48 hours.',
  price: 4000,
  priceLabel: '/project',
  isNegotiable: true,
  category: 'Jobs (Gigs)',
  image: '/src/assets/images/student_cyber_tech_1791796604735.jpg',
  universityId: 'uon',
  campusName: 'Main Campus',
  seller: {
    name: 'Dr. Anne Nduku',
    role: 'verified_vendor',
    courseOrBiz: 'School of Business & Economics',
    phone: '+254719001122',
    whatsapp: '254719001122',
    isVerifiedStudent: false,
    trustScore: 99,
    reviewsCount: 14,
    safeSpot: 'Gandhi Wing / Main Library Plaza',
    mpesaNumber: '0719 001 122'
  },
  details: {
    gigDuration: '2 Days (Urgent)',
    compensationType: 'Per Task',
```

```
    skillsNeeded: ['MS Word formatting', 'APA 7th Referencing', 'Mendeley / Zotero', 'Fast typing'
]
  },
  isApproved: true,
  isFeePaid: true,
  mpesaRef: 'QK312VB55',
  listingFeeKsh: 80,
  createdAt: '1 hour ago',
  viewsCount: 290,
  likesCount: 38,
  featured: true
},
{
  id: 'gig-2',
  type: 'gig',
  title: 'Campus Brand Ambassadors - Fintech App Launch (Flexible Hours)',
  description: 'Recruiting energetic undergraduate students to onboard fellow students onto a new
financial literacy app during student association week. Great compensation, free branded hoodies,
and certificate of completion.',
  price: 15000,
  priceLabel: '/month',
  isNegotiable: false,
  category: 'Jobs (Gigs)',
  image: '/src/assets/images/hero_campus_marketplace_1791796569675.jpg',
  universityId: 'all',
  campusName: 'All Campuses (Kenya)',
  seller: {
    name: 'Safaricom Campus Team',
    role: 'verified_vendor',
    courseOrBiz: 'Youth & Tech Engagement',
    phone: '+254700000111',
    whatsapp: '254700000111',
    isVerifiedStudent: false,
    trustScore: 100,
    reviewsCount: 92,
    safeSpot: 'Campus Student Union Office',
    tillNumber: 'Paybill 200200'
  },
  details: {
    gigDuration: '3 Months (Part-time, 10 hrs/wk)',
    compensationType: 'Monthly',
    skillsNeeded: ['Strong interpersonal skills', 'Active on campus social clubs', 'Smartphone use
r']
  },
  isApproved: true,
  isFeePaid: true,
  mpesaRef: 'QK102ZA99',
  listingFeeKsh: 80,
  createdAt: 'Yesterday',
  viewsCount: 890,
  likesCount: 144
},

// 4. LOCAL VENDORS & SERVICES (Approved)
{
  id: 'biz-1',
  type: 'business',
  title: 'Mama Stacy Hostel Food Express (Chapo, Dengu, Pilau & Beef)',
  description: 'Student-run culinary hustle delivering hot, hygienic, and affordable homecooked me
als straight to your hostel gate in Juja. Fluffy layered chapatis (KES 20), dengu stew (KES 80), b
eef fry (KES 150). Lunch & Dinner delivery runs daily.',
  price: 150,
  priceLabel: '/meal combo',
  isNegotiable: false,
  category: 'Services',
  image: '/src/assets/images/campus_thrift_fashion_1791796594005.jpg',
  universityId: 'jkuat',
  campusName: 'Juja Main Campus',
  seller: {
    name: 'Stacy Atieno & Crew',
```

```
    role: 'student_freelancer',
    courseOrBiz: 'Food Science & Tech (Hustle)',
    yearOfStudy: 'Year 3',
    phone: '+254728990011',
    whatsapp: '254728990011',
    isVerifiedStudent: true,
    trustScore: 99,
    reviewsCount: 88,
    safeSpot: 'Gate A, B & C Hostel Drops',
    tillNumber: 'Till 914203'
  },
  details: {
    openingHours: '11:30 AM - 10:00 PM Daily',
    deliveryAvailable: true,
    deliveryNote: 'Free delivery within 1km of Juja gates (Min order KES 200)',
    servicesOffered: ['Hot lunch boxes', 'Dinner delivery to hostels', 'Group study snack platters
', 'Weekend event catering']
  },
  isApproved: true,
  isFeePaid: true,
  mpesaRef: 'QK919FF44',
  listingFeeKsh: 80,
  createdAt: 'Today',
  viewsCount: 1220,
  likesCount: 230,
  featured: true
},

// 5. KMTC, POLYTECHNIC & TVET CAMPUS LISTINGS (Approved)
{
  id: 'kmtc-item-1',
  type: 'item',
  title: 'Littmann Classic III Stethoscope + Clinical Scrub Suit (Size M, Navy Blue)',
  description: 'Original 3M Littmann Classic III Stethoscope with dual-sided chestpiece and tunabl
e diaphragms. Includes two sets of scrub uniforms (Navy blue, fade-resistant). Ideal for Clinical
Medicine and Nursing students at KMTC and medical colleges.',
  price: 8500,
  priceLabel: '',
  isNegotiable: true,
  category: 'Electronics & Medical',
  image: '/src/assets/images/student_cyber_tech_1791796604735.jpg',
  universityId: 'kmtc_nairobi',
  campusName: 'Mbagathi Way Main Gate',
  institutionType: 'kmtc',
  seller: {
    name: 'Mercy Achieng',
    role: 'student',
    courseOrBiz: 'Diploma in Clinical Medicine & Surgery',
    yearOfStudy: 'Year 3',
    phone: '+254718223344',
    whatsapp: '254718223344',
    isVerifiedStudent: true,
    trustScore: 99,
    reviewsCount: 22,
    safeSpot: 'KMTC Mbagathi Gate / KNH Administration Block',
    mpesaNumber: '0718 223 344'
  },
  details: {
    condition: 'Like New',
    itemCategory: 'Electronics'
  },
  isApproved: true,
  isFeePaid: true,
  mpesaRef: 'QK221MM88',
  listingFeeKsh: 80,
  createdAt: '3 hours ago',
  viewsCount: 412,
  likesCount: 54,
  featured: true
},
```

```
{
  id: 'kmtc-hostel-1',
  type: 'hostel',
  title: 'Medics View Modern Bedsitter (3 Mins to KMTC Mbagathi & KNH)',
  description: 'Clean tiled bedsitter tailored for medical trainees with long night shift hours. I
nstant hot shower, silent study environment, uninterrupted borehole water 24/7, token meter, and b
iometric gate security with guard.',
  price: 9000,
  priceLabel: '/month',
  isNegotiable: false,
  category: 'Housing (Hostels)',
  image: '/src/assets/images/hostel_student_room_1791796581832.jpg',
  universityId: 'kmtc_nairobi',
  campusName: 'Mbagathi Way Main Gate',
  institutionType: 'kmtc',
  seller: {
    name: 'Mama Njeri Caretaker',
    role: 'hostel_caretaker',
    courseOrBiz: 'Medics Court Management',
    phone: '+254722556677',
    whatsapp: '254722556677',
    isVerifiedStudent: false,
    trustScore: 97,
    reviewsCount: 35,
    safeSpot: 'KMTC Gate B / Mbagathi Hospital Road',
    tillNumber: 'Till 844211'
  },
  details: {
    hostelType: 'Bedsitter',
    distanceToGate: '3 mins walk (KMTC Gate B)',
    waterStatus: '24/7 Borehole + Tap',
    electricityType: 'Prepaid Token Meter',
    wifiAvailable: true,
    securityGuard: true,
    roomFeatures: ['Kitchenette with cupboards', 'Hot shower heater', 'Night study desk space', 'C
CTV monitored']
  },
  isApproved: true,
  isFeePaid: true,
  mpesaRef: 'QK776KK22',
  listingFeeKsh: 80,
  createdAt: '1 day ago',
  viewsCount: 580,
  likesCount: 71,
  featured: true
},
{
  id: 'kmtc-gig-1',
  type: 'gig',
  title: 'Clinical Pharmacology & Anatomy OSCE Mock Exam Peer Tutor',
  description: 'Year 3 Clinical Medicine comrade offering 1-on-1 practical coaching and OSCE mock
stations for Year 1 & 2 KMTC students at JOOTRH Kisumu. Covers drug calculations, sterile catheter
ization, and case presentation.',
  price: 2500,
  priceLabel: '/weekend module',
  isNegotiable: true,
  category: 'Jobs (Gigs)',
  image: '/src/assets/images/hero_campus_marketplace_1791796569675.jpg',
  universityId: 'kmtc_kisumu',
  campusName: 'JOOTRH Teaching Gate',
  institutionType: 'kmtc',
  seller: {
    name: 'Collins Otieno',
    role: 'student_freelancer',
    courseOrBiz: 'KMTC Clinical Medicine Rep',
    yearOfStudy: 'Year 3',
    phone: '+254719334455',
    whatsapp: '254719334455',
    isVerifiedStudent: true,
    trustScore: 99,
```

```
    reviewsCount: 19,
    safeSpot: 'JOOTRH Main Library & Students Hall',
    mpesaNumber: '0719 334 455'
  },
  details: {
    gigDuration: 'Weekend Sessions (4 hrs)',
    compensationType: 'Per Task',
    skillsNeeded: ['Anatomy OSCE', 'Pharmacology math', 'Patient history taking']
  },
  isApproved: true,
  isFeePaid: true,
  mpesaRef: 'QK551KS99',
  listingFeeKsh: 80,
  createdAt: '6 hours ago',
  viewsCount: 340,
  likesCount: 45
},
{
  id: 'poly-item-1',
  type: 'item',
  title: 'Engineering Technical Drawing Board (A1) + T-Square + Workshop Safety Boots',
  description: 'Complete mechanical/civil engineering practical starter kit: Smooth wood A1 drafti
ng board with clips, 90cm acrylic T-Square, set squares, and heavy-duty steel-toe safety boots (Si
ze 42). Used for KNEC module exams.',
  price: 4200,
  priceLabel: '',
  isNegotiable: true,
  category: 'Marketplace',
  image: '/src/assets/images/hero_campus_marketplace_1791796569675.jpg',
  universityId: 'kabete_poly',
  campusName: 'Waiyaki Way Main Gate',
  institutionType: 'polytechnic',
  seller: {
    name: 'Erick Kiprono',
    role: 'student',
    courseOrBiz: 'Diploma in Mechanical Engineering',
    yearOfStudy: 'Year 2',
    phone: '+254701998877',
    whatsapp: '254701998877',
    isVerifiedStudent: true,
    trustScore: 98,
    reviewsCount: 16,
    safeSpot: 'Kabete Poly Waiyaki Way Main Gate',
    mpesaNumber: '0701 998 877'
  },
  details: {
    condition: 'Good Condition',
    itemCategory: 'Stationery & Notes'
  },
  isApproved: true,
  isFeePaid: true,
  mpesaRef: 'QK883NN44',
  listingFeeKsh: 80,
  createdAt: '5 hours ago',
  viewsCount: 320,
  likesCount: 39
},
{
  id: 'poly-hostel-1',
  type: 'hostel',
  title: 'Poly Breeze Executive Bedsitter (2 Mins Walk to Kisumu Poly Gate)',
  description: 'Affordable self-contained bedsitter tailored for technical students. Large study s
pace for drafting tables, instant hot shower, water security, prepaid token meter, and perimeter w
all with night security.',
  price: 6500,
  priceLabel: '/month',
  isNegotiable: false,
  category: 'Housing (Hostels)',
  image: '/src/assets/images/hostel_student_room_1791796581832.jpg',
  universityId: 'kisumu_poly',
```

```
  campusName: 'Nairobi Road Main Gate',
  institutionType: 'polytechnic',
  seller: {
    name: 'George Omondi (Caretaker)',
    role: 'hostel_caretaker',
    courseOrBiz: 'Poly Breeze Residences',
    phone: '+254724889900',
    whatsapp: '254724889900',
    isVerifiedStudent: false,
    trustScore: 98,
    reviewsCount: 27,
    safeSpot: 'Kisumu Poly Gate A Security Desk',
    tillNumber: 'Till 781204'
  },
  details: {
    hostelType: 'Bedsitter',
    distanceToGate: '2 mins walk to Poly Gate',
    waterStatus: '24/7 Water Supply',
    electricityType: 'Prepaid Token Meter',
    wifiAvailable: true,
    securityGuard: true,
    roomFeatures: ['Kitchen sink with tiled splashback', 'Spacious study area', 'Perimeter electri
c fence']
  },
  isApproved: true,
  isFeePaid: true,
  mpesaRef: 'QK712KP44',
  listingFeeKsh: 80,
  createdAt: '2 days ago',
  viewsCount: 410,
  likesCount: 48
},
{
  id: 'tvet-item-1',
  type: 'item',
  title: 'KNEC Electrical Installation Past Papers (2019-2025) + Digital Multimeter',
  description: 'Bound revision book with complete KNEC past assessment papers, marking schemes, an
d practical diagrams for Craft & Diploma Electrical Engineering. Comes with auto-ranging digital m
ultimeter with test leads.',
  price: 1900,
  priceLabel: '',
  isNegotiable: false,
  category: 'Marketplace',
  image: '/src/assets/images/student_cyber_tech_1791796604735.jpg',
  universityId: 'ntti',
  campusName: 'Ngara Ring Road Main Gate',
  institutionType: 'tvet',
  seller: {
    name: 'John Wafula',
    role: 'student',
    courseOrBiz: 'Electrical & Electronic Tech',
    yearOfStudy: 'Year 2',
    phone: '+254713445566',
    whatsapp: '254713445566',
    isVerifiedStudent: true,
    trustScore: 99,
    reviewsCount: 11,
    safeSpot: 'NTTI Ngara Administration Foyer',
    mpesaNumber: '0713 445 566'
  },
  details: {
    condition: 'Like New',
    itemCategory: 'Textbooks'
  },
  isApproved: true,
  isFeePaid: true,
  mpesaRef: 'QK443PP11',
  listingFeeKsh: 80,
  createdAt: 'Yesterday',
  viewsCount: 260,
```

```
  likesCount: 31
},
{
  id: 'tvet-biz-1',
  type: 'business',
  title: 'TechDraft Cyber & Large-Format CAD Blueprint Printing Service',
  description: 'Comrade-operated cyber next to technical workshop gate: A0/A1 CAD technical drawin
gs, spiral binding, passport photos, and KNEC project documentation. Special student rate of KES 5
0 per A1 blueprint plot.',
  price: 50,
  priceLabel: '/A1 print',
  isNegotiable: false,
  category: 'Services',
  image: '/src/assets/images/campus_thrift_fashion_1791796594005.jpg',
  universityId: 'kinyanjui_tech',
  campusName: 'Kabiria Road Main Gate',
  institutionType: 'tvet',
  seller: {
    name: 'Denis Mutiso',
    role: 'student_freelancer',
    courseOrBiz: 'ICT & Design Graduate',
    phone: '+254790112233',
    whatsapp: '254790112233',
    isVerifiedStudent: true,
    trustScore: 100,
    reviewsCount: 42,
    safeSpot: 'PC Kinyanjui Main Workshop Entrance',
    tillNumber: 'Till 634812'
  },
  details: {
    openingHours: '7:30 AM - 7:30 PM (Mon-Sat)',
    deliveryAvailable: true,
    deliveryNote: 'Free hostel delivery within Riruta/Dagoretti area for orders above KES 150',
    servicesOffered: ['CAD plotting', 'A1 & A2 drawing prints', 'Report binding', 'Project documen
tation']
  },
  isApproved: true,
  isFeePaid: true,
  mpesaRef: 'QK338TK55',
  listingFeeKsh: 80,
  createdAt: '4 hours ago',
  viewsCount: 480,
  likesCount: 65,
  featured: true
},
{
  id: 'ksii-hostel-1',
  type: 'hostel',
  title: 'Silver Springs Executive Bedsitter near KSII Main Campus (Mwembe Gate)',
  description: 'Modern, newly tiled self-contained bedsitter 4 minutes walk from Kisii University
Main Gate. Unlimited Wi-Fi, constant municipal water + borehole backup, pre-paid electricity token
 meter, CCTV security, and biometric gate access.',
  price: 6500,
  priceLabel: '/month',
  isNegotiable: false,
  category: 'Housing',
  image: '/src/assets/images/campus_hostel_room_1791796582697.jpg',
  universityId: 'kisii_uni',
  campusName: 'Main Campus (Kisii)',
  institutionType: 'university',
  seller: {
    name: 'Evans Mogaka',
    role: 'hostel_caretaker',
    courseOrBiz: 'Silver Springs Student Residences',
    phone: '+254722998877',
    whatsapp: '254722998877',
    isVerifiedStudent: true,
    trustScore: 99,
    reviewsCount: 28,
    safeSpot: 'Kisii University Main Gate',
```

```
    mpesaNumber: '0722 998 877'
  },
  details: {
    hostelType: 'Bedsitter',
    distanceToGate: '4 mins walk to KSII Gate',
    waterStatus: '24/7 Running Water',
    electricityType: 'Prepaid Token Meter',
    wifiAvailable: true,
    securityGuard: true,
    roomFeatures: ['Private Balcony', 'Ceramic Tiled Floor', 'Wardrobe', 'Kitchen Counter with Sin
k']
  },
  isApproved: true,
  isFeePaid: true,
  mpesaRef: 'QK891KS22',
  listingFeeKsh: 80,
  createdAt: '3 hours ago',
  viewsCount: 310,
  likesCount: 42
},
{
  id: 'ksii-item-1',
  type: 'item',
  title: 'HP EliteBook 840 G6 Core i5 (16GB RAM, 512GB SSD) + Bag',
  description: 'Clean ultrabook laptop in pristine condition. Backlit keyboard, fingerprint reader
, 14-inch Full HD display, battery lasts 6+ hours. Ideal for KSII Computer Science, Nursing, or Bu
siness coursework.',
  price: 29500,
  priceLabel: '',
  isNegotiable: true,
  category: 'Marketplace',
  image: '/src/assets/images/student_cyber_tech_1791796604735.jpg',
  universityId: 'kisii_uni',
  campusName: 'Main Campus (Kisii)',
  institutionType: 'university',
  seller: {
    name: 'Faith Nyaboke',
    role: 'student',
    courseOrBiz: 'BSc. Computer Science',
    yearOfStudy: 'Year 3',
    phone: '+254718334455',
    whatsapp: '254718334455',
    isVerifiedStudent: true,
    trustScore: 100,
    reviewsCount: 15,
    safeSpot: 'Kisii University Library Plaza',
    mpesaNumber: '0718 334 455'
  },
  details: {
    condition: 'Like New',
    itemCategory: 'Electronics'
  },
  isApproved: true,
  isFeePaid: true,
  mpesaRef: 'QK772KS88',
  listingFeeKsh: 80,
  createdAt: 'Yesterday',
  viewsCount: 420,
  likesCount: 57
},

// 6. PENDING SUBMISSIONS (isApproved == false for testing the Admin approval workflow!)
{
  id: 'item-pending-1',
  type: 'item',
  title: 'Casio fx-991EX ClassWiz Scientific Calculator (Original)',
  description: 'High-speed spreadsheet and matrix operations. Used for one semester in Engineering
 Surveying. 100% genuine with QR verify barcode.',
  price: 2400,
  priceLabel: '',
```

```
  isNegotiable: true,
  category: 'Electronics',
  image: '/src/assets/images/student_cyber_tech_1791796604735.jpg',
  universityId: 'uon',
  campusName: 'Main Campus',
  seller: {
    name: 'Samuel Kiptoo',
    role: 'student',
    courseOrBiz: 'BSc. Geospatial Engineering',
    yearOfStudy: 'Year 2',
    phone: '+254714556677',
    whatsapp: '254714556677',
    isVerifiedStudent: true,
    trustScore: 98,
    reviewsCount: 4,
    safeSpot: 'UoN Main Campus Fountain',
    mpesaNumber: '0714 556 677'
  },
  details: {
    condition: 'Like New',
    itemCategory: 'Electronics'
  },
  isApproved: false, // Default: false
  isFeePaid: true,   // Paid KSh 80
  mpesaRef: 'QK988KL33', // M-Pesa Ref provided
  listingFeeKsh: 80,
  createdAt: '15 mins ago',
  viewsCount: 0,
  likesCount: 0
},
{
  id: 'hostel-pending-2',
  type: 'hostel',
  title: 'Silver Oak Hostels - Modern 1-Bedroom (Madaraka)',
  description: 'Spacious self-contained flat with balcony, fast Wi-Fi, constant county water, and
security guard 24/7. 6 minutes walk to Strathmore University.',
  price: 14000,
  priceLabel: '/month',
  isNegotiable: false,
  category: 'Housing (Hostels)',
  image: '/src/assets/images/hostel_student_room_1791796581832.jpg',
  universityId: 'strathmore',
  campusName: 'Madaraka Main Campus',
  seller: {
    name: 'Daniel Maina',
    role: 'hostel_caretaker',
    courseOrBiz: 'Silver Oak Properties',
    phone: '+254722334455',
    whatsapp: '254722334455',
    isVerifiedStudent: false,
    trustScore: 96,
    reviewsCount: 19,
    safeSpot: 'Strathmore Phase 1 Gate',
    tillNumber: 'Paybill 522522'
  },
  details: {
    hostelType: '1 Bedroom',
    distanceToGate: '6 mins walk',
    waterStatus: 'Constant Water Supply',
    electricityType: 'Prepaid Token',
    wifiAvailable: true,
    securityGuard: true,
    roomFeatures: ['Private balcony', 'Kitchen with granite tops', 'High speed fiber']
  },
  isApproved: false, // Default: false
  isFeePaid: true,   // Paid KSh 80
  mpesaRef: 'QK877JJ11',
  listingFeeKsh: 80,
  createdAt: '30 mins ago',
  viewsCount: 0,
```

```
    likesCount: 0
  }
];

export const INITIAL_COMMUNITY_POSTS: CommunityPost[] = [
  {
    id: 'buzz-1',
    type: 'lost_found',
    title: 'LOST: Green Leather Wallet & UoN Student ID (Reg: F17/8241/2023)',
    content: 'Misplaced my wallet yesterday between Chiromo Physical Sciences lecture theatre and th
  e student canteen. Contains student card, national ID (Evans Kiprop), and NHIF card. Cash can be k
  ept, please return the cards! Reward offered.',
    author: 'Evans Kiprop',
    authorRole: 'Chiromo Student',
    universityId: 'uon',
    campusName: 'Chiromo Campus',
    timeAgo: '3 hours ago',
    repliesCount: 8,
    likesCount: 24,
    statusTag: 'URGENT LOST'
  },
  {
    id: 'buzz-2',
    type: 'study_group',
    title: 'Study Buddy: JKUAT Year 2 Software Engineering Discrete Math revision',
    content: 'Forming a study squad for upcoming end-of-sem CATs. Meeting every Tuesday and Thursday
   4-6 PM at Science Complex 3rd Floor. Come with past papers and notebook!',
    author: 'Faith Mwende',
    authorRole: 'SE Class Rep',
    universityId: 'jkuat',
    campusName: 'Juja Main Campus',
    timeAgo: '5 hours ago',
    repliesCount: 14,
    likesCount: 31,
    statusTag: 'STUDY SQUAD'
  },
  {
    id: 'buzz-3',
    type: 'rideshare',
    title: 'Carpool / Shared Uber to Westlands / CBD on Friday 5 PM',
    content: 'Splitting an Uber ride from Strathmore Madaraka to CBD / Westlands after evening lectu
  res. 2 spots open, KES 150 each. Message me if interested.',
    author: 'Ian Karanja',
    authorRole: 'Strathmore Student',
    universityId: 'strathmore',
    campusName: 'Madaraka Main Campus',
    timeAgo: 'Yesterday',
    repliesCount: 6,
    likesCount: 12,
    statusTag: 'CARPOOL'
  },
  {
    id: 'buzz-4',
    type: 'alert',
    title: 'Campus Safety Tip: Late night walking near Gate C Juja',
    content: 'Just a reminder to comrades: avoid unlit paths near the railway line after 9 PM. Alway
  s walk in groups or take the boda-boda from the main tarmac.',
    author: 'Campus Comrades Watch',
    authorRole: 'Student Security Council',
    universityId: 'jkuat',
    campusName: 'Juja Main Campus',
    timeAgo: '1 day ago',
    repliesCount: 29,
    likesCount: 89,
    statusTag: 'SAFETY ALERT'
  }
];

export const SAFE_MEETUP_SPOTS: Record<string, string[]> = {
  uon: ['Main Campus Fountain & Library', 'Chiromo Physical Sciences Foyer', 'Parklands Campus Gate
```

```
  A', 'Gandhi Wing'],
  ku: ['KU Post Office Plaza', 'Nyayo Hostels Gate', 'Student Center Amphitheatre', 'Kahawa Sukari Q
  uickMart Gate'],
  jkuat: ['Juja Gate A Security Post', 'Gate C Main Gate', 'JKUAT Library Entrance', 'Student Centre
   Hall 6'],
  strathmore: ['Phase 1 Security Gate', 'Student Center Courtyard', 'Library Atrium'],
  usiu: ['Main Gate Security Reception', 'Student Center Cafe', 'Auditorium Quad'],
  tuk: ['Main Gate Haile Selassie', 'City Square Security Post', 'Block A Lobby'],
  moi: ['Kesses Main Library', 'Student Center Quad', 'Admin Block Entrance'],
  egerton: ['Njoro Main Gate', 'Kilimo Hall', 'FASS Quad'],
  daystar: ['Athi River Admin Quad', 'Valley Road Campus Lobby'],
  mku: ['Thika Main Campus Gate', 'Parklands Campus Reception', 'Student Center Quad'],

  // KMTC Campuses
  kmtc_nairobi: ['Mbagathi Way Main Gate', 'KNH Administration Block Foyer', 'KMTC Library Entrance'
  , 'Old Hostel Gate'],
  kmtc_mombasa: ['Coast General Hospital Gate', 'Port Reitz KMTC Gate', 'Hospital Administration Lob
  by'],
  kmtc_kisumu: ['JOOTRH Teaching Gate', 'Kondele Road Main Gate', 'Student Canteen Quad'],
  kmtc_nakuru: ['Provincial General Hospital (PGH) Gate', 'Milimani Faculty Lobby', 'Library Lawn'],
  kmtc_eldoret: ['Moi Teaching & Referral (MTRH) Gate', 'Nandi Road Gate', 'KMTC Eldoret Admin Quad'
  ],
  kmtc_nyeri: ['Nyeri PGH Gate', 'Mathari Complex Reception', 'Outspan Road Gate'],
  kmtc_thika: ['Thika Level 5 Gate', 'General Kago Ground Security Post'],
  kmtc_machakos: ['Machakos Level 5 Hospital Main Gate', 'Admin Quad'],
  kmtc_kakamega: ['Kakamega General Hospital Gate', 'KMTC Reception'],
  kmtc_kisii: ['Kisii Teaching & Referral Gate', 'Student Pavilion'],

  // National Polytechnics
  kabete_poly: ['Waiyaki Way Main Gate Security Post', 'Uthiru Lower Gate', 'Administration Block Qu
  ad', 'Library Foyer'],
  kcnp: ['Kisauni Main Gate', 'Mvita Center Security Desk', 'Coast Poly Courtyard'],
  kisumu_poly: ['Nairobi Road Main Gate', 'Polytechnic Grounds Security', 'Admin Block Lobby'],
  eldoret_poly: ['Langas Main Gate', 'Engineering Workshops Entrance', 'Library Steps'],
  nyeri_poly: ['Outspan Road Main Gate', 'Admin Block Entrance'],
  sigalagala_poly: ['Sigalagala Main Gate', 'Student Canteen Steps'],
  meru_poly: ['Nchiru Main Gate', 'Administration Square'],
  kitale_poly: ['Kitale Town Main Gate', 'Engineering Quad'],

  // TVET Colleges & Institutes
  ntti: ['Ngara Ring Road Main Gate', 'Park Road Gate', 'NTTI Administration Foyer', 'Student Center
  '],
  kinyanjui_tech: ['Riruta Main Gate Security Desk', 'Kabiria Wing Gate', 'Admin Quad'],
  rvtti: ['Kapsabet Road Main Gate', 'RVTTI Administration Square', 'Library Steps'],
  kist: ['Kiambu Road Main Gate', 'Engineering Quad Steps', 'KIST Student Center'],
  thika_tvet: ['Hospital Road Main Gate', 'Thika Tech Reception'],
  riat: ['Riat Hills Main Gate', 'RIAT Kisumu Admin Block'],
  kaiboi_tvet: ['Kaiboi Main Gate', 'Admin Foyer']
};
```