SSH Compromise Detection using NetFlow/IPFIX

Rick Hofstede, Luuk Hendriks




"51 percent of respondents admitted that their organizations have already been impacted by an SSH key-related compromise in the last 24 months."


-Ponemon 2014 SSH Security Vulnerability Report

SSH Compromise Detection using NetFlow/IPFIX

Rick Hofstede, Luuk Hendriks







- SSH intrusion detection on end hosts is hardly scalable
- Network-based approaches exist, but only inform security operators about the presence of attacks


We perform compromise detection.




We perform compromise detection.

All flow-based.










- SSHCure 1.0 (June '12):
 - Purely deviation-based compromise detection
- SSHCure 2.0 (May '13):
 - Notifications, database maintenance, performance profiling, ...



- SSHCure 1.0 (June '12):
 - Purely deviation-based compromise detection
- SSHCure 2.0 (May '13):
 - Notifications, database maintenance, performance profiling, ...



- SSHCure 2.4 (July '14):
 - New compromise detection algorithm (CCR paper release), based on 'action upon compromise'
- SSHCure 3.0 (January '14):
 - New frontend, ingress vs. egress attacks




(a) Maintain connection, continue dictionary (1)



(d) Maintain connection, abort dictionary (1)

SSH Compromise Detection using NetFlow/IPFIX.
In: ACM SIGCOMM Computer Communication Review, October 2014



(a) Maintain connection, continue dictionary (1)



(d) Maintain connection, abort dictionary (1)




(c) Instant logout, continue dictionary



(f) Instant logout, abort dictionary


SSH Compromise Detection using NetFlow/IPFIX.
In: ACM SIGCOMM Computer Communication Review, October 2014




(a) Maintain connection, continue dictionary (1)




(d) Maintain connection, abort dictionary (1)



(b) Maintain connection, continue dictionary (2)



(e) Maintain connection, abort dictionary (2)



(c) Instant logout, continue dictionary




(f) Instant logout, abort dictionary


SSH Compromise Detection using NetFlow/IPFIX.
In: ACM SIGCOMM Computer Communication Review, October 2014



- SSHCure 2.4 (July '14):
 - New compromise detection algorithm (CCR paper release), based on 'action upon compromise'
- SSHCure 3.0 (January '14):
 - New frontend, ingress vs. egress attacks

SSHCURE





Incoming attacks					
Phases	Active	Attacker	Date	Targets	
	<i>\$</i>	123.123.123.123	Mon. Jun 30, 2014 19:57	12	
		123.123.123.123	Mon. Jun 30, 2014 19:57	456	
		130.89.148.136	Mon. Jun 30, 2014 19:57	32	
	4	123.123.123.123	Mon. Jun 30, 2014 19:57	7455	
		123.123.123.123	Mon. Jun 30, 2014 19:57	64	

Target	Attacks	Compromise
123.123.123.123	12	2
123.123.123.123	456	3
130.89.148.136	32	5
123.123.123.123	7455	64
123.123.123.123	64	78

Top targets - Compromise

Q	Search
#	Status
(i)	Help
£	Settings

Outgoing attacks					
Phases	Active	Attacker	Date	Targets	
	<i>\$</i>	123.123.123.123	Mon. Jun 30, 2014 19:57	12	
		123.123.123.123	Mon. Jun 30, 2014 19:57	456	
		130.89.148.136	Mon. Jun 30, 2014 19:57	32	
	<i>*</i>	123.123.123.123	Mon. Jun 30, 2014 19:57	7455	
		123.123.123.123	Mon. Jun 30, 2014 19:57	64	

Top targets - Brute Force					
Target Attacks Compromise					
123.123.123.123	12	2			
123.123.123.123	456	3			
130.89.148.136	32	5			
123.123.123.123	7455	64			
123.123.123.123	64	78			

SSHCure

Validation approach

- Ground truth: sshd logs from 93 honeypots, servers and workstations, divided over two datasets:
 - Dataset 1 easy targets
 - Dataset 2 more difficult targets

	Honeypots	Servers	Workstations	Attacks
Dataset 1	13	0	0	636
Dataset 2	0	76	4	10353

SSHCure

Validation results

- Evaluation metrics:
 - TP / FP correct / false identification of incident
 - TN / FN correct / false identification of non-incident
- Detection accuracy close to 100%

	TPR	TNR	FPR	FNR	Acc
Dataset 1	0,692	0,921	0,079	0,308	0,839
Dataset 2		0,997	0,003		0,997

SSHCure

Deployment

- SSHCure is open-source and actively developed
 - Download counter SourceForge (Dec. '14): 3k
 - Recently moved to GitHub (summer '14)
- Tested in several nation-wide backbone networks
- Many successful deployments already:
 - Web hosting companies

- National Research and Education Networks (NRENs)
- Campus networks
- Governmental CSIRTs/CERTs



Ease-of-use is key



- Ease-of-use is key
 - Many potential SSHCure users (e.g., CSIRTs) are lessskilled than we are

- Ease-of-use is key
 - Many potential SSHCure users (e.g., CSIRTs) are lessskilled than we are
 - Installation scripts are important

- Ease-of-use is key
 - Many potential SSHCure users (e.g., CSIRTs) are lessskilled than we are
 - Installation scripts are important
 - Use of NfSen:

- Ease-of-use is key
 - Many potential SSHCure users (e.g., CSIRTs) are lessskilled than we are
 - Installation scripts are important
 - Use of NfSen:
 - Widely used in (European) NREN community

- Ease-of-use is key
 - Many potential SSHCure users (e.g., CSIRTs) are lessskilled than we are
 - Installation scripts are important
 - Use of NfSen:
 - Widely used in (European) NREN community
 - Experience with SURFmap [1]





Ingress vs. egress attacks

- Ingress vs. egress attacks
 - Initial focus mainly on ingress attacks

- Ingress vs. egress attacks
 - Initial focus mainly on ingress attacks
 - CSIRTs are becoming more responsible towards the Internet: Keep it clean!



Integration into workflow is important

- Integration into workflow is important
 - Yet another tool is hard to integrate into CSIRT workflow

- Integration into workflow is important
 - Yet another tool is hard to integrate into CSIRT workflow
 - Integration with existing systems is necessary:
 IODEF, X-ARF, QuarantaineNet, ...



Advertizing is important

- Advertizing is important
 - People don't spot your cool project by themselves

- Advertizing is important
 - People don't spot your cool project by themselves
 - Visit meetings & conferences (FloCon, TERENA TNC, RIPE, etc.)

- Advertizing is important
 - People don't spot your cool project by themselves
 - Visit meetings & conferences (FloCon, TERENA TNC, RIPE, etc.)
 - GitHub vs. SourceForge



• 1:1 sampling is hardly used by non-academia

- 1:1 sampling is hardly used by non-academia
 - Problem for our algorithms

- 1:1 sampling is hardly used by non-academia
 - Problem for our algorithms
 - Admins are 'afraid' of increasing sampling rates



Input data quality is hard to predict



- Input data quality is hard to predict
 - Algorithms should be as resilient to various data sources as possible

- Input data quality is hard to predict
 - Algorithms should be as resilient to various data sources as possible
 - Examples:

- Input data quality is hard to predict
 - Algorithms should be as resilient to various data sources as possible
 - Examples:
 - Availability of TCP flags

- Input data quality is hard to predict
 - Algorithms should be as resilient to various data sources as possible
 - Examples:
 - Availability of TCP flags
 - Assumptions on flow cache entry expiration

Thanks!







https://nl.linkedin.com/in/rhofstede/

WWW

http://rickhofstede.nl

@

r.j.hofstede@utwente.nl, rick.hofstede@redsocks.nl





http://nl.linkedin.com/in/luukhendriks

www

https://luukhendriks.eu

@

luuk.hendriks@utwente.nl

Questions?

https://github.com/sshcure/sshcure

