

STACKUP & IMPEDANCE REPORT


Confidential / Proprietary Information

Planner: SSDC_DILEEPK

Job Name: **992717**
Customer: **Oxide Computer Company**
Part Name: **913-0000114**
Revision:

Customer Required Finished Thickness: **62.00 (+6.20 / -6.20) mils**

Measured: **Over mask on plated copper**
Estimated Finished Thickness: **61.68 mils**

Imp	Lyr	Type	Image	Foil	Plt (Mil)	Thk (Mil)	Er	Generic Name	Name	Starv	
	sm1					0.5			~ ~		
1xΩ	11s	Signal		0.25oz	1.05	1.4	0.00	0.25 oz - Foil	Foil, 0.25 oz /H 18x24		
						3.344	3.59	2113	FR-408HR 2113 18x24 RC57		
	12g	Powe...		1oz	0	5	3.59	0.005 H1xH1	FR-408HR 0.005 H1xH1 CM 24x18		
	13g	Mixed		1oz	0		3.59	2113	FR-408HR 2113 18x24 RC57		
						7.444	3.59	2113	FR-408HR 2113 18x24 RC57		
						21	3.76	0.021 HHxHH	FR-408HR 0.021 HHxHH CM 24x18		
							3.59	2113	FR-408HR 2113 18x24 RC57		
						7.15	3.59	2113	FR-408HR 2113 18x24 RC57		
1xΩ	14g	Signal		1oz	0	5	3.59	0.005 H1xH1	FR-408HR 0.005 H1xH1 CM 24x18		
	15g	Powe...		1oz	0		3.344	3.59	2113	FR-408HR 2113 18x24 RC57	
1xΩ	16s	Signal		0.25oz	1.05	1.4	0.00	0.25 oz - Foil	Foil, 0.25 oz /H 18x24		
	sm6					0.5			~ ~		

Impedance Table *** 0.25 oz on outer layers is the starting copper weight, finish will be 1 oz***

Index	Layer	Required Impedance [ohms]	Tol [ohms] +/-	Type	Ref 1	Ref 2	Orig LW [mil]	Orig Spacing [mil]	Orig CP Spacing [mil]	Finished LW [mil]	Finished Spacing [mil]	Fin. CP Spacing [mil]	Impedance Simulation [ohms]	Impedance before Mask [ohms]	IMG
a	1	85	10.0%	Diff Coated		2	5.50	6.00		5.90	5.60		84.8		
b	6	85	10.0%	Diff Coated		5	5.50	6.00		5.90	5.60		84.8		
c	4	85	10.0%	Diff Stripline	3	5	6.81	5.95		6.81	5.95		84.2		