

## Note:

- 1. Packing requirements: Packing and shipping according to the company's self-made packing requirements.
- 2. All materials are used in accordance with ROHS standards.

|     |                |                      | 8. Measuring the dielectric: Water                |                |
|-----|----------------|----------------------|---|----------------|
|     |                |                      | 7. Working environment humidity: ≤95%             |                |
|     |                |                      | 6. Working medium temperature: 0° C $\sim$ +70° C |                |
|     |                |                      | 5.Storage environment humidity: ≤95%              |                |
| 4   | Wire           | AWM1015 18AWG red 1m | 4. Storage temperature: -40° C∼+70° C             | $\blacksquare$ |
| 3   | Probe          | SUS304               | 3. Power specifications: 24VDC $\pm$ 10%          |                |
| 2   | Ontology       | PP white             | 2. Probe length: 115.5mm                          |                |
| 1   | Hexagon head   | PP black             | 1. Probe diameter: Ø2.5mm                         | $\neg$         |
| NO. | Specifications |                      | Product features                                  |                |

## NINGBO MINGRUI SENSORS CO., LTD. www.mrsensors.com

| <br>$\bigoplus$ | Qual |
|-----------------|------|
| \$              |      |

| Quality | Proportion |
|---------|------------|
|         |            |

MR-G1/4-151 (1841\_715\_104)

ELECTRODE LEVEL SENSOR