



856 Advance Ship Notice (ASN) Guidelines

X12 Version 4010

7/29/2024

EDI Contact Information:

Do it Best Corp.
P.O. Box 868
Fort Wayne, IN 46801-0868
Website: www.doitbestcorp.com
Phone: (260) 748-5619
Email: edivendorsupport@doitbest.com

Introduction

The 856 is used for both Drop Ship (DS) and Warehouse (RSC) orders

The purpose of this document is to present and explain Advance Shipment Notices (ASN's) as they pertain to shipments into a Retail Service Center (warehouse). The primary purpose of an ASN is to provide Do it Best Corp. with advanced and accurate data on shipments into our RSC's so that we can plan workloads and process receipts more efficiently. The key words are "advance" and "accurate". In other words, the ASN must arrive in advance of the merchandise arriving at our dock and the ASN must also be 100% accurate and represent the exact contents of the shipment.

Key Points

- The ASN must contain sku level data and include all other data outlined in this document.
- We recommend a "scan, pack and ship" method of ASN creation. This will ensure that the ASN is 100% accurate and represents the exact contents of the shipment.
- The accuracy and timeliness of the ASN is the responsibility of the vendor.
- SCAC code is required on all ASN's.
- A unique ASN number must be created for each shipment. You may have multiple purchase orders per ASN. If multiple purchase orders are combined, shipped and delivered in a single shipment, then only one ASN should be created. All like items, regardless of Purchase Order, should be packed together on the shipment.
- All backorders should be issued a new and unique ASN number.
- The ASN number(s) must be clearly stated on the Bill of Lading.
- Bills of Lading must be unique for at least 24 months.
- Do it Best Corp recommends Suppliers use the EDI VICS (Voluntary Inter-industry Commerce Standards) standard Bill of Lading form and or the 211 **Motor Carrier Bill of Lading** transaction to communicate Bill of Lading data to carriers.
- All retail cartons must be bar-coded with one of the following retail Level GTINs:
 - ✓ UCC-12 (U.P.C.-A) or (U.P.C.-E)
 - ✓ EAN/UCC-13 or EAN/UCC-8
- All pallets and cartons must be bar-coded with the shipping container code GTIN. The SCC code should be in the standard Interleaved 2 of 5 barcode (1 2 of 5).
 - ✓ EAN/UCC-14 shipping container code (SCC-14 code).
- Failure to comply with these key points or the additional details outlined in this document will result in a vendor chargeback as outlined in the Do it Best Corp. Vendor Compliance Manual.

Depending on the shipment some segments may not be used or may appear at different levels. Segments marked as optional should be sent when available, however the Do it Best Corp. application system can process the ship notice without them.

Minimum Ship Notice Segment Requirements for all shipments

BSN	Shipment Identification
HL*1**S	Shipment Level Information
TD1	Carrier Information (Quantity & Weight)
TD5	Carrier Information (Routing Sequence / Transit Time)
REF*BM	Bill of Lading Number
REF*CN	Carrier's Reference Number
DTM*011	Date Shipped
DTM*067	Delivery Date (actual or Estimated)
N1*ST	Ship To Destination
N1*Sf	Ship From Destination
N3*Sf	Ship From Destination
N4*Sf	Ship From Destination
HL*2*1*O	Order Level Information
PRF	Do it Best Corp. PO number
HL*3*2*I	Item Level Information
LIN	Item Identification
SN1	Item Shipment Quantities
CTT	Segment Totals

Document Layout Key

<u>Data Element</u>	<u>Element Name</u>	<u>X12 Req</u>	<u>Do it Best Req</u>	<u>Data Type</u>	<u>DIB Element Length</u>	<u>Contents</u>
-------------------------	---------------------	--------------------	-------------------------------	----------------------	-----------------------------------	-----------------

Data Element

Position in the segment where the element appears and the corresponding element number

Element Name

Name of the element

X12 Requirement

The Ansi-X12 requirement designator

M = Mandatory
X = Relational
O = Optional
Z = Semantic

Do it Best Requirement

The Do it Best Corp. requirement designator

M = Mandatory
X = Relational
O = Optional
Z = Semantic

Data Type

Nn = Numeric, with number of decimal positions
R = Decimal number
ID = Identifier, must contain an accepted value from the X12 standards
AN = String
DT = Date. Format: ccyymmdd
TM = Time. Format: hhmmss

Element Length

The Minimum and Maximum length according to the X12 standards.

Contents

Notes or other information related to the usage of the element.

Note: If a numeric data element is mandatory, the minimum number of characters must be transmitted, even if the value is zero. See SAC segment for examples.

Header Information Segments

BSN Segment - Required

Beginning Segment for Advance Ship Notice.

Note: The ASN/Shipment ID must be clearly stated on the Bill of Lading.

User Option (Usage): Mandatory

Maximum Occurrence: 1

<u>Data Element</u>	<u>Element Name</u>	<u>X12 Req</u>	<u>Do it Best Req</u>	<u>Data Type</u>	<u>DIB Element Length</u>	<u>Contents</u>
BSN01 353	Transaction Set purpose Code	M	M	ID	2/2	14 = Advance notification 00 = Original
BSN02 396	Shipment ID	M	M	AN	2/30	Unique ID assigned by the original shipper
BSN03 373	Date	M/Z	M/Z	DT	8/8	Date ASN created - CCYYMMDD
BSN04 337	Time	M/Z	M/Z	TM	4/8	Time ASN created - HHMM

Example: BSN*14*999999999*19980626*1418

HL Segment - Hierarchical Level for Shipment Data - Required

User Option (Usage): Mandatory

Maximum Occurrence: 1

<u>Data Element</u>	<u>Element Name</u>	<u>X12 Req</u>	<u>Do it Best Req</u>	<u>Data Type</u>	<u>DIB Element Length</u>	<u>Contents</u>
HL01 628	Hierarchical ID Number	M	M	AN	1/12	Unique number. The value for the first HL segment will be 1, and is incremented by 1 for each subsequent HL in the transaction set.
HL02 734	Hierarchical Parent ID	O	O	AN	1/12	ID# of the next higher HL segment
HL03 735	Hierarchical Level Code	M	M	ID	1/1	S = Shipment

Example: HL*1**S

TD1 Segment - Carrier Information (Quantity & Weight) - Required

Do it Best Corp needs accurate **gross** weight of the entire shipment in the TD107.

User Option (Usage): Mandatory

Maximum Occurrence: 1

<u>Data Element</u>	<u>Element Name</u>	<u>X12 Req</u>	<u>Do it Best Req</u>	<u>Data Type</u>	<u>DIB Element Length</u>	<u>Contents</u>
TD101 103	Packaging Code	O	M	AN	3/5	Part 1 packaging form required, part two packaging material optional
TD102 80	Lading Quantity	X	M	N0	1/7	Number of Packaging Code (TD101) shipped
TD106 187	Weight Qualifier	O	M	ID	1/2	G = Gross Weight
TD107 81	Weight	X	M	R	1/10	Total weight of shipment (If decimal used, total of six decimal places available only; decimal counts as a character in the total length)
TD108 335	Unit or Basis for Measurement Code	X	M	ID	2/2	LB = Pounds

Example: TD1*PLT*10****G*125*LB

TD5 Segment - Carrier Information (Routing Sequence / Transit Time) - Required

The TD5 and the SCAC code are used to monitor freight. The Retail Service Centers require this information in order to expedite the movement of hot freight. The SCAC code is also used in various reports and is key to our Supply Chain processes.

User Option (Usage): Mandatory

Maximum Occurrence: 12

<u>Data Element</u>	<u>Element Name</u>	<u>X12 Req</u>	<u>Do it Best Req</u>	<u>Data Type</u>	<u>DIB Element Length</u>	<u>Contents</u>
TD502 66	Identification Qualifier	O	M	ID	1/1	2 = Standard Carrier Alpha Code
TD503 67	Identification Code	O	M	AN	2/4	SCAC Code
TD504 91	Transport Method	O	M	ID	1/2	L = Contract Carrier M = Motor Carrier U = Private Parcel Service H = Customer Pickup LT = Less than trailer load (LTL) SR = Supplier Truck T = Best Way (Shipper's Option) O = Containerized Ocean
TD505 387	Routing	O	M	AN	1/35	Carrier Name

Example: TD5**2*RRBT*SR*ROARK TRUCKING

REF Segment - Bill of Lading Number - Required

The customer Bill of Lading number will be used to tie the various EDI documents together and track the order through the supply chain. The Bill of Lading number must be unique for a period of 24 months. Do it Best Corp recommends that vendors use the VICS standard Bill of Lading number. The VICS standard Bill of Lading number is based on the UCC global standard identification system. Details can be found in section III of the VISC BOL Guide at <http://www.vics.org/guidelines/bol>. Note- This is Mandatory for RSC and Conditional for DS

User Option (Usage): Mandatory

Maximum Occurrence: 1

<u>Data Element</u>	<u>Element Name</u>	<u>X12 Req</u>	<u>Do it Best Req</u>	<u>Data Type</u>	<u>DIB Element Length</u>	<u>Contents</u>
REF01 128	Reference No. Qualifier	O	M	ID	2/2	'BM'
REF02 127	Reference No.	O	M	AN	1/30	Bill of Lading Number

Example: REF*BM*1234566789

REF Segment - Carrier's Reference Number - Required

The **Carrier's Reference number** is used by the Do it Best Corp Logistics and Merchandising Departments to access carrier shipment status information within our Supply Chain Application and within the Carrier's web portal. This reference number must be unique for 24 months. For LTL carriers, this is the Carrier Pro # - the number assigned by the carrier to a single shipment. For Truckload carriers, this is the carrier assigned reference number. For Parcel carriers, this is the small package tracking number as bar-coded on the package. Note: only 1 small package tracking number provided per System Status Message.

User Option (Usage): Mandatory
Maximum Occurrence: 1

<u>Data Element</u>	<u>Element Name</u>	<u>X12 Req</u>	<u>Do it Best Req</u>	<u>Data Type</u>	<u>DIB Element Length</u>	<u>Contents</u>
REF01 128	Reference No. Qualifier	O	M	ID	2/2	'CN'
REF02 127	Reference No.	O	M	AN	1/30	Carrier's Reference Number (PRO/Invoice)

Example: REF*CN*K0600

DTM - Ship Date & Time - Required

Specifies actual ship date. If the Ship Date is missing, Do it Best Corp. will use the current date for our Supply Chain Visibility software.

User Option (Usage): Mandatory
Maximum Occurrence: 1

<u>Data Element</u>	<u>Element Name</u>	<u>X12 Req</u>	<u>Do it Best Req</u>	<u>Data Type</u>	<u>DIB Element Length</u>	<u>Contents</u>
DTM01 374	Date/Time Qualifier	O	M	ID	3/3	'011'
DTM02 373	Date	O	M	DT	8/8	CCYYMMDD

Example: DTM*011*20050823

DTM - Delivery Date - Conditional

Specifies Estimated or Scheduled delivery date. A second DTM segment containing the expected or scheduled delivery date is required whenever the Shipment method of payment (FOB01) from the original PO is "PP" for Prepaid. When the Shipment method of payment (FOB01) from the original PO is not "PP" for Prepaid, then the Delivery Date is optional. This will be used in our Supply Chain Visibility software to display the arrival data for Do it Best Corp. Purchasing and Receiving departments. If the Delivery date is missing, Do it Best Corp. will calculate using the Ship date plus the transportation time for our Supply Chain Visibility software.

User Option (Usage): Conditional
Maximum Occurrence: 1

<u>Data Element</u>	<u>Element Name</u>	<u>X12 Req</u>	<u>Do it Best Req</u>	<u>Data Type</u>	<u>DIB Element Length</u>	<u>Contents</u>
DTM01 374	Date/Time Qualifier	O	M	ID	3/3	'067' = Scheduled delivery '017' = Estimated delivery
DTM02 373	Date	O	M	DT	8/8	CCYYMMDD

Example: DTM*017*20050825

N1 Segment - Ship To Name and number - Required

Identifies the Retail Service Center or member store. Note: If the product is being shipped to a location other than the RSC or member store, use the Receiving location below to indicate where the product is sent.

User Option (Usage): Mandatory
Maximum Occurrence: 1

<u>Data Element</u>	<u>Element Name</u>	<u>X12 Req</u>	<u>Do it Best Req</u>	<u>Data Type</u>	<u>DIB Element Length</u>	<u>Contents</u>
N101 98	Entity ID Code	O	M	ID	2/2	ST = Ship To
N103 66	ID code qualifier	O	M	ID	2/2	92 = assigned by Do it Best Corp.
N104 67	ID code	O	M	AN	4/5	4 position Retail Service Center Identifier. (Include leading zeros) for RSC, Member number for DS

Example: N1*ST**92*0001

Note: For the complete list of Retail Service Centers, see the list titled "Do it Best Corp. Corporate Office and Retail Service Center Addresses. For the complete list of Import Facilities refer to the list titled "Do it Best Corp. Import Shipping Locations".

N1 Name - Receiving Location - Conditional

Receiving location is needed if the member is shipping to a location other than their store

User Option (Usage): Conditional

Maximum Occurrence: 1

<u>Data Element</u>	<u>Element Name</u>	<u>X12 Req</u>	<u>Do it Best Req</u>	<u>Data Type</u>	<u>DIB Element Length</u>	<u>Contents</u>
N101 98	Entity ID Code	O	M	ID	2/2	RC = Receiving Location
N102 93	Name	O	M	AN	1/30	Receiving location Name

Example: N1*RC*RECEIVING LOCATION NAME

N3 Address - Receiving Location Address - Conditional

User Option (Usage): Conditional

Maximum Occurrence: 1

<u>Data Element</u>	<u>Element Name</u>	<u>X12 Req</u>	<u>Do it Best Req</u>	<u>Data Type</u>	<u>DIB Element Length</u>	<u>Contents</u>
N301 98	Address	O	M	AN	1/35	Address of Receiving location

Example: N3*1234 SOMEWHERE ST

N4 Segment - Receiving Location City, State, & Zip - Conditional

User Option (Usage): Conditional

Maximum Occurrence: 1

<u>Data Element</u>	<u>Element Name</u>	<u>X12 Req</u>	<u>Do it Best Req</u>	<u>Data Type</u>	<u>DIB Element Length</u>	<u>Contents</u>
N401 19	City	O	M	AN	2/19	Origin City
N402 156	State	O	M	AN	2/2	Origin State
N403 116	Zip	O	M	ID	3/9	Origin Zip
N404 26	Country Code	O	M	ID	2/3	Origin Country Code

Example: N4*City Name*ST*468010000*US

N1 Name - Shipped From - Required

Identifies the vendor's origins address for the shipment

User Option (Usage): Mandatory

Maximum Occurrence: 1

<u>Data Element</u>	<u>Element Name</u>	<u>X12 Req</u>	<u>Do it Best Req</u>	<u>Data Type</u>	<u>DIB Element Length</u>	<u>Contents</u>
N101 98	Entity ID Code	O	M	ID	2/2	SF = Ship From
N102 93	Name	O	M	AN	1/30	Ship from Name

Example: N1*Sf*SHIP FROM LOCATION NAME

N3 Address - Shipped From - Required

User Option (Usage): Mandatory

Maximum Occurrence: 1

<u>Data Element</u>	<u>Element Name</u>	<u>X12 Req</u>	<u>Do it Best Req</u>	<u>Data Type</u>	<u>DIB Element Length</u>	<u>Contents</u>
N301 98	Address	O	M	AN	1/35	Address of Shipment Origin

Example: N3*1234 SOMEWHERE ST

N4 Geographic Location - Shipped From - Required

User Option (Usage): Mandatory

Maximum Occurrence: 1

<u>Data Element</u>	<u>Element Name</u>	<u>X12 Req</u>	<u>Do it Best Req</u>	<u>Data Type</u>	<u>DIB Element Length</u>	<u>Contents</u>
N401 19	City	O	M	AN	2/19	Origin City
N402 156	State	O	M	AN	2/2	Origin State
N403 116	Zip	O	M	ID	3/9	Origin Zip
N404 26	Country Code	O	M	ID	2/3	Origin Country Code

Example: N4*City Name*ST*468010000*US

HL Segment - Hierarchical Level for Order Data - Required

User Option (Usage): Mandatory
Maximum Occurrence: 1

<u>Data Element</u>	<u>Element Name</u>	<u>X12 Req</u>	<u>Do it Best Req</u>	<u>Data Type</u>	<u>DIB Element Length</u>	<u>Contents</u>
HL01 628	Hierarchical ID Number	M	M	AN	1/12	Unique number is incremented by 1 for each subsequent HL in the transaction set
HL02 734	Hierarchical Parent ID	O	M	AN	1/12	ID# of the next higher HL segment
HL03 735	Hierarchical Level Code	M	M	ID	1/1	O = Order

Example: HL*2*1*O

PRF Purchase Order Reference - Required

User Option (Usage): Mandatory
Maximum Occurrence: 1

<u>Data Element</u>	<u>Element Name</u>	<u>X12 Req</u>	<u>Do it Best Req</u>	<u>Data Type</u>	<u>DIB Element Length</u>	<u>Contents</u>
PRF01 324	PO Number	O	M	AN	1/11	Do it Best Corp. Assigned PO Number (maximum 11 characters)

Example: PRF*01331M7721

Detail Segments

HL Segment - Hierarchical Level for Item Data - Required

User Option (Usage): Mandatory
Maximum Occurrence: 1

<u>Data Element</u>	<u>Element Name</u>	<u>X12 Req</u>	<u>Do it Best Req</u>	<u>Data Type</u>	<u>DIB Element Length</u>	<u>Contents</u>
HL01 628	Hierarchical ID Number	M	M	AN	1/11	Unique number is incremented by 1 for each subsequent HL in the transaction set
HL02 734	Hierarchical Parent ID	O	M	AN	1/12	ID# of the next higher HL segment
HL03 735	Hierarchical Level Code	M	M	ID	1/1	I = Item

Example: HL*3*2*I

LIN - Item Detail Identification - Required

User Option (Usage): Mandatory
Maximum Occurrence: 1

<u>Data Element</u>	<u>Element Name</u>	<u>X12 Req</u>	<u>Do it Best Req</u>	<u>Data Type</u>	<u>DIB Element Length</u>	<u>Contents</u>
LIN02 235	Product ID Qualifier	M	M	ID	2/2	CB or IN = Buyer's Item #
LIN03 234	Product ID	M	M	R	6/6	SKU (Do it Best Corp.) number. Always 6 positions
LIN04 235	Product ID Qualifier	O	O	ID	2/2	VC or VN = Vendor's Part #
LIN05 234	Product ID	O	O	AN	1/48	Vendor's Part number
LIN06 235	Product ID Qualifier	O	O	ID	2/2	UP, UK, or EN
LIN07 234	Product ID	O	O	AN	1/48	UPC or EAN code

Example: LIN**IN*338516*VN*53168*UP*037516531681

Please be advised that when creating ASNs, it is crucial that all identical SKUs are consolidated onto the same line. We cannot accept ASNs where the same SKU appears on multiple lines. Identical SKUs being shipped must be sent in the same LIN and SN1 loop. This practice ensures accuracy and efficiency in our inventory management and receiving processes.

SN1 - Item Detail Shipment Quantities - Required

User Option (Usage): Mandatory
Maximum Occurrence: 1

<u>Data Element</u>	<u>Element Name</u>	<u>X12 Req</u>	<u>Do it Best Req</u>	<u>Data Type</u>	<u>DIB Element Length</u>	<u>Contents</u>
SN102 382	Number of Units Shipped	M	M	N6	1/10	The Actual quantity shipped on this ASN. Please note that this quantity would not include 0 quantities for items backordered, deleted, or rejected.
SN103 355	Unit of Measure Code	M	M	AN	2/2	Same as the unit from the Purchase Order
SN108 668	Line Item Status Code	O	M	ID	2/2	IA = Accepted

Ship Notice Line Item Status Code (SN108) Usage

The SN1 segment would only reflect the actual items on the ASN/shipment.

Please Note: Any items that are backordered/rejected would be reflected on the 855 Purchase Order Acknowledgement.

- If the item is shipped complete, send the quantity shipped (SN102) and a line item status code of 'IA' (SN108).
Example: SN1**12*EA*****IA
- If making a partial shipment and backordering the remaining quantity, send the quantity shipped (SN102) and a line item status code of 'IA' (SN108). The Do it Best Corp. System will calculate the backordered quantity. For backordered/partial shipments please contact your Merchandise team to discuss and determine how long the backorder will remain open or if they need to be canceled.
Example: SN1**10*EA*****IA
- If the entire order quantity is un-shippable, because the item is rejected or invalid, then there is no need to send a '0' quantity shipped in the ASN. Only the items/quantities that are shipped should be on the ASN.
- Possible reject/cancel reasons include invalid item identification, incorrect order multiple, incorrect pricing, or company backorder policy. **Every effort should be made to resolve rejected items upon receipt of the order, by contacting your Retail Product Manager or an EDI Service Administrator at 260-748-5619.**

DTM - Expiration Date - Conditional

If an item has an expiration date, then the segment is mandatory. If an item does not have an expiration date, then this segment is not required.

User Option (Usage): Conditional

Maximum Occurrence: 1

<u>Data Element</u>	<u>Element Name</u>	<u>X12 Req</u>	<u>Do it Best Req</u>	<u>Data Type</u>	<u>DIB Element Length</u>	<u>Contents</u>
DTM01 374	Date/Time Qualifier	O	M	ID	3/3	'036'
DTM02 373	Date	O	M	DT	8/8	CCYYMMDD

Example: DTM*036*20200823

Summary Segments

CTT Segment - Required

Transaction totals. Contains hash total for line items in transaction set.

User Option (Usage): Mandatory

Maximum Occurrence: 1

<u>Data Element</u>	<u>Element Name</u>	<u>X12 Req</u>	<u>Do it Best Req</u>	<u>Data Type</u>	<u>DIB Element Length</u>	<u>Contents</u>
CTT01 354	Number of Line Items	O	M	N0	1/6	Number of HL Segments

Examples: CTT*3**