

# Module2 - R Markdown Document 1

Daniel Oyama

2024-09-06

## This is a level 1 header

### R Markdown

#### This is a level 3 header

This is an R Markdown document. Markdown is a simple formatting syntax for authoring HTML, PDF, and MS Word documents. For more details on using R Markdown see <http://rmarkdown.rstudio.com>.

Here is a link to [GOOGLE](#)

Here is a word in **bold** and another word in **bold**.

Here is a word in *italics* and another word in *italics*.

When we compile our document, we are using the `rmarkdown` package.

Here are some example R commands:

```
2 + 2
mean(c(1,2,3,4,5))
```

Here is an example of a non-numbered list:

- Breakfast
  - food
    - \* eggs
    - \* toast
    - \* bacon
  - drink
    - \* apple juice
- Lunch
  - taco
- Dinner
  - baked chicken
  - broccoli
  - rice

Here is another list:

1. Breakfast
  - a. food
    - i. eggs
    - ii. toast
    - iii. bacon
  - b. drink i. apple juice
2. Lunch
  - a. taco
3. Dinner
  - a. baked chicken
  - b. broccoli
  - c. rice

Here is a blockquote:

teste teste

1. teste
2. teste

Here is a blockquote:

teste teste

teste

Hre:

```
2 + 2
mean(c(1,2,3,4,5))
```


When you click the **Knit** button a document will be generated that includes both content as well as the output of any embedded R code chunks within the document. You can embed an R code chunk like this:

```
summary(cars)
```

```
##      speed      dist
##  Min.   : 4.0    Min.   :  2.00
## 1st Qu.:12.0    1st Qu.: 26.00
##  Median :15.0    Median : 36.00
##   Mean  :15.4    Mean   : 42.98
## 3rd Qu.:19.0    3rd Qu.: 56.00
##   Max.  :25.0    Max.    :120.00
```

## Including Plots

You can also embed plots, for example:



Note that the `echo = FALSE` parameter was added to the code chunk to prevent printing of the R code that generated the plot.

## Insert Tables

```
knitr::kable(head(cars))
```

speed	dist
4	2
4	10
7	4
7	22
8	16
9	10