



6-MAVZU · I BOB. HTML VA CSS

CSS ulash usullari, selektorlar va sintaksis. Matn va shriftlar

CSS nima, Inline, Internal va External usullar, qoida sintaksisi, teg/class/id va boshqa selektorlar, kaskad va ustuvorlik, ranglar, matn va shrift xossalari, Google Fonts.

Bugun nimani o'rganamiz?

- **CSS** nima va HTML bilan qanday ishlaydi
- CSS'ni ulashning **3 usuli**
- Qoida tuzilishi va **selektorlar**
- **Kaskad:** qaysi qoida "g'olib"?
- **Ranglar, matn va shriftlar**, Google Fonts

CSS nima?

CSS — sahifaning ko'rinishi: rang, shrift, o'lcham, joylashuv

- Cascading **Style Sheets** — kaskadli uslublar jadvali
- HTML — **tuzilma**, CSS — **dizayn**



O'xshatish: HTML — odamning tanasi, CSS — kiyimi va soch turmagi. Bitta odam turli kiyimda butunlay boshqacha ko'rinadi.

CSS qoidasining tuzilishi

```
css
h1 {
  color: blue;
  font-size: 32px;
}
```

- `h1` — **selektor**: QAYSI elementlarga
- `color` — **xossa**: NIMANI o'zgartiramiz
- `blue` — **qiymat**: QANDAY qilib
- `color: blue;` — deklaratsiya



Har deklaratsiya oxirida `;` majburiy!

- Izoh: `/* ... */`

CSS'ni ulashning 3 usuli

1. Inline

```
<p style="color: red; font-size: 20px;">Qizil paragraf</p>
```

2. Internal

```
<style>  
  p { color: green; }  
</style>
```

3. External

```
<link rel="stylesheet" href="css/style.css">
```

Qaysi usul qachon?

Usul	Qayerda	Ta'sir doirasi	Qachon
Inline	<code>style="..."</code>	Bitta element	Tez sinash
Internal	<code><style></code> (head'da)	Bitta sahifa	Kichik loyiha
External	<code>.css</code> fayl + <code><link></code>	Butun sayt	Deyarli har doim

- Bitta `style.css` → barcha sahifalar; o'zgartirish — bitta faylda
- Brauzer faylni xotirada saqlaydi → sayt tezroq

Asosiy selektorlar

CSS

```
p { color: #333; }           /* teg — barcha <p> lar */
.muhim { color: crimson; }   /* class — nuqta bilan */
#sarlavha { color: navy; }    /* id — panjara bilan */
* { font-family: Arial; }     /* universal — hammasi */
h2, h3 { color: teal; }       /* guruh — vergul bilan */
```

- **class** — dizayn uchun deyarli doim; bir nechta: `class="tugma katta qizil"`
- **id** — sahifada **yagona**; havolalar va JavaScript uchun

Kombinatsiyalangan selektorlar

Selektor	Ma'nosi
<code>nav a</code>	<code>nav</code> ichidagi barcha <code>a</code> (bo'sh joy)
<code>.menu > li</code>	Faqat bevosita farzand <code>li</code>
<code>p.eslatma</code>	<code>class="eslatma"</code> bo'lgan <code>p</code>
<code>input[type="email"]</code>	Atribut bo'yicha
<code>h2, h3</code>	Ham <code>h2</code> , ham <code>h3</code> (vergul)

Kaskad: qaysi qoida g'olib?

- 1 **Aniqlik:** inline > id > class > teg
- 2 Aniqlik teng bo'lsa — **keyinroq yozilgani** yutadi

HTML

```
<style>
  p { color: blue; }
  .matn { color: green; }
  #asosiy { color: orange; }
</style>
<p class="matn" id="asosiy">Men to'q sariqman (id yutdi)</p>
```



Ko'rsatmalar: direktor (inline) aytgani sinf rahbari (id) va sardor (class) gapidan ustun; umumiy qoida (teg) eng kuchsiz.

Meros (inheritance)

- Matnga oid xossalar (`color`, `font-family`, `font-size`) ota elementdan **ichkariga meros** o'tadi
- Shuning uchun shriftni bir marta `body` ga berish kifoya

CSS

```
body {  
  font-family: "Segoe UI", Arial, sans-serif;  
  color: #1f2937;  
}
```

Ranglar

CSS

```
.r1 { color: tomato; }           /* nom bilan */
.r2 { color: #4f46e5; }         /* HEX: #RRGGBB */
.r3 { color: #f00; }            /* qisqa HEX */
.r4 { color: rgb(16, 185, 129); } /* RGB: 0-255 */
.r5 { color: rgba(0, 0, 0, 0.4); } /* shaffoflik 0..1 */
.r6 { color: hsl(280, 70%, 50%); } /* tus, to'yinganlik, yorqinlik */
.fon { background-color: #fef3c7; }
```

- `#ff0000` — qizil, `#000000` — qora, `#ffffff` — oq



Matn va fon o'rtasida yetarli **kontrast** bo'lsin!

Matn xossalari

Xossa	Qiymatlar
<code>text-align</code>	<code>left</code> <code>center</code> <code>right</code> <code>justify</code>
<code>text-decoration</code>	<code>none</code> <code>underline</code> <code>line-through</code>
<code>text-transform</code>	<code>uppercase</code> <code>lowercase</code> <code>capitalize</code>
<code>letter-spacing</code> / <code>word-spacing</code>	Harf / so'z oralig'i
<code>line-height</code>	Qator oralig'i (masalan <code>1.6</code>)
<code>text-shadow</code>	<code>2px 2px 4px rgba(0,0,0,.4)</code>

Shriftlar

```
css
body {
  font-family: "Segoe UI", Arial, sans-serif;
  font-size: 16px;
  font-weight: 400;      /* 100..900; 700 = bold */
  font-style: normal;    /* italic */
  line-height: 1.6;
}
```

- **serif** — "oyoqchali" (Georgia): kitob uslubi
- **sans-serif** — oyoqchasiz (Arial): ekran uchun
- **monospace** — bir xil kenglik: kod uchun
- Ro'yxat — **zaxira** shriftlar; oxirida umumiy oila

Google Fonts va o'lcham birliklari

- 1 **fonts.google.com** → shrift tanlang (Latin Extended!)
- 2 "Get embed code" → `<link>` ni `<head>` ga qo'ying
- 3 CSS: `font-family: "Montserrat", sans-serif;`

Birlik	Ma'nosi
px	Aniq piksel
em	Ota element shriftiga nisbatan
rem	Sahifa asosiy shriftiga (16px) nisbatan — shriftlar uchun
%	Ota elementga nisbatan

BO'LIM

Amaliy mashg'ulot

Vizitka saytiga dizayn beramiz

Amaliyot: vizitkaga dizayn

- 1 `css/style.css` yarating
- 2 Har sahifaga: `<link rel="stylesheet" href="css/style.css">` (ichki papkada — `../css/`)
- 3 Google Fonts'dan 2 ta shrift ulang
- 4 `body` , sarlavhalar, havolalar, `.ajratilgan` uchun uslub yozing
- 5 **F12 → Elements → Styles**: qaysi qoida ta'sir qilyapti, qaysi biri "yutqazgan"?

Amaliyot: namuna CSS

CSS

```
body {  
  font-family: "Segoe UI", Arial, sans-serif;  
  font-size: 17px;  
  line-height: 1.7;  
  color: #1f2937;  
  background-color: #f9fafb;  
}  
h1, h2, h3 { font-family: Georgia, serif; color: #4f46e5; }  
h1 { font-size: 2.5rem; text-align: center; }  
nav a { color: #4f46e5; text-decoration: none; font-weight: 600; }  
.ajratilgan { background-color: #fef3c7; padding: 0 4px; }
```

Ko'p uchraydigan xatolar

- ❌ `;` unutilgan: `color: red font-size: 20px;` — ikkalasi ham ishlamaydi
- ❌ CSS'da nuqta unutilgan: `muhim { }` → `.muhim { }`
- ❌ HTML'da nuqta qo'yilgan: `class=".muhim"` → `class="muhim"`
- ❌ CSS fayl yo'li noto'g'ri → Console'da "404 style.css"
- ❌ `colour`, `text-color` → to'g'risi `color`

Savol

`class="karta"` bo'lgan elementlarni tanlovchi selektor qaysi?

A `#karta`

B `.karta`

C `karta`

D `*karta`

Javobni tanlang — to'g'ri variant yashil bo'ladi

Savol

`<p class="a" id="b">` uchun `p{color:red}`, `.a{color:green}`, `#b{color:blue}` yozilgan. Matn qanday rangda?

A Qizil

B Yashil

C Qora

D Ko'k

Javobni tanlang — to'g'ri variant yashil bo'ladi

Savol

nav a selektori nimani tanlaydi?

A nav ichidagi barcha havolalarni

B nav va barcha a larni

C Faqat birinchi havolani

D a ichidagi nav ni

Javobni tanlang — to'g'ri variant yashil bo'ladi

Savol

`font-family: "Roboto", Arial, sans-serif;` — kompyuterda Roboto bo'lmasa?

A Matn ko'rinmaydi

B Arial ishlatiladi

C Xato chiqadi

D Times New Roman ishlatiladi

Javobni tanlang — to'g'ri variant yashil bo'ladi



Uyga vazifa

- 1 **CSS Diner** o'yinida kamida 12-darajagacha o'ting
- 2 **coolors.co** dan 4–5 rangli palitra tanlab, vizitkaga qo'llang
- 3 "Sinfimiz gazetasi"ga gazeta uslubida dizayn: serif shrift, katta sarlavha

✓ Yodda tuting

- Qoida: `selektor { xossa: qiymat; }`
- **External CSS** — asosiy usul
- Selektorlar: `p`, `.class`, `#id`, `*`, `a`, `b`, `a b`, `a > b`
- Ustuvorlik: `inline` > `id` > `class` > `teg`; teng bo'lsa — keyingisi
- Matn: `color`, `text-align`, `line-height`; shrift: `font-family`, `font-size`, `font-weight`



Savollar bormi?

Keyingi mavzu: **7. CSS background va border xossalari**

Batafsil matn, misollar va testlar: **06-css-ulash-selektorlar-matn.html** darsida