



9-MAVZU · I BOB. HTML VA CSS

CSS pseudo-class va pseudo-elementlar. CSS position

:hover, :focus, :active, :nth-child kabi holat selektorlari; ::before, ::after, ::first-letter pseudo-elementlari; static, relative, absolute, fixed, sticky pozitsiyalari va z-index.

Bugun nimani o'rganamiz?

- Holatga qarab uslub: **sichqoncha ustida, bosilganda, tanlanganda**
- Birinchi, oxirgi, juft-toq elementlarni tanlash
- HTML'siz "virtual" elementlar: `::before` , `::after`
- Elementni aniq joyga qo'yish: **position**
- Qatlamlar tartibi: **z-index**

Pseudo-class — element holati

- Bitta ikki nuqta bilan: `a:hover`



Svetofor: svetofor bitta, holati o'zgaradi. Tugma ham bitta: oddiy, ustida (`:hover`), bosilgan (`:active`), tanlangan (`:focus`).

CSS

```
.tugma      { background: #4f46e5; cursor: pointer; }
.tugma:hover { background: #4338ca; }                /* sichqoncha ustida */
.tugma:active { transform: scale(0.95); }             /* bosilgan payt */
.tugma:focus  { outline: 3px solid #fbbf24; }        /* Tab bilan */
input:focus   { border-color: #4f46e5; }
```

Havola holatlari

CSS

```
a:link      { color: #2563eb; } /* bosilmagan */
a:visited   { color: #7c3aed; } /* ilgari bosilgan */
a:hover     { color: #dc2626; } /* ustida */
a:active    { color: #ea580c; } /* bosilgan payt */
```

"LoVe HAte" — L → V → H → A tartibida yozing

- `cursor: pointer` — ko'rsatkich "qo'l"ga aylanadi: bosiladigan narsalarga qo'ying

Tuzilma bo'yicha tanlash

Selektor	Nimani tanlaydi
<code>:first-child</code> / <code>:last-child</code>	Birinchi / oxirgi farzand
<code>:nth-child(3)</code>	3-farzand
<code>:nth-child(even)</code> / <code>(odd)</code>	Juft / toq — "zebra" jadval
<code>:nth-child(3n)</code>	Har uchinchisi: 3, 6, 9...
<code>:not(.x)</code>	<code>.x</code> bo'lmaganlar
<code>:checked</code>	Belgilangan checkbox/radio
<code>:valid</code> / <code>:invalid</code>	To'g'ri / noto'g'ri to'ldirilgan maydon

CSS

```
tr:nth-child(even) { background: #f1f5f9; }
```

Pseudo-element — virtual qism

- Ikki marta ikki nuqta: `::before`, `::after`

CSS

```
.majburiy::after { content: " *"; color: red; }
.tel::before      { content: "☎ "; }

h2.chiziqli::after { /* sarlavha ostida bezak chiziq */
  content: "";
  display: block;
  width: 60px; height: 4px;
  background: #4f46e5;
}

p::first-letter { font-size: 2.5em; float: left; }
input::placeholder { color: #94a3b8; }
```



`content` xossasi **majburiy** (bo'sh bo'lsa ham). Faqat bezak uchun — muhim ma'lumot HTML'da bo'lsin.

BO'LIM

Position

Elementni oqimdan chiqarib, aniq joyga qo'yish

position qiymatlari

Qiymat	Xatti-harakat	Nimaga nisbatan
<code>static</code>	Standart, oddiy oqim	—
<code>relative</code>	Oqimda qoladi	O'z asl joyiga; langar
<code>absolute</code>	Oqimdan chiqadi	Eng yaqin positionli ajdodga
<code>fixed</code>	Scrolllda qimirlamaydi	Ekranga
<code>sticky</code>	Chegaraga yetgach yopishadi	Scroll konteyneriga

- Joy: `top`, `right`, `bottom`, `left`

relative + absolute — eng mashhur juftlik

CSS

```
.karta {  
  position: relative; /* ← langar */  
}  
.chegirma {  
  position: absolute; /* ← kartaga nisbatan */  
  top: 12px;  
  left: 12px;  
  background: #ef4444;  
  color: white;  
}  
.sevimli {  
  position: absolute;  
  top: 12px; right: 12px;  
}
```



Muzlatgich magniti: `relative` karta — muzlatgich eshigi, `absolute` belgi — magnit. Eshik qayerga borsa, magnit ham birga ketadi.



Otada `position: relative` bo'lmasa — "magnit" butun sahifa burchagiga uchib ketadi!

fixed va sticky

CSS

```
.menu {  
  position: sticky;  
  top: 0;           /* tepaga yetganda yopishadi */  
  z-index: 10;  
}  
  
.yuqoriga {  
  position: fixed;  
  bottom: 20px;  
  right: 20px;      /* doim o'ng pastki burchakda */  
  border-radius: 50%;  
}
```

- **sticky** — yopishqoq menyu
- **fixed** — "Yuqoriga" yoki chat tugmasi

z-index — qatlamlar tartibi

- Ustma-ust tushganda **kattasi yuqorida**
- Faqat `position` berilgan (static emas) elementlarda ishlaydi

CSS

```
.a { position: absolute; z-index: 1; }  
.b { position: absolute; z-index: 3; } /* eng yuqorida */  
.c { position: absolute; z-index: 2; }
```

BO'LIM

Amaliy mashg'ulot

3-loyiha: maktab sahifasi

Amaliyot: maktab sahifasi

- 1 **Sticky header:** logo + menyu, havolalarga `:hover`
- 2 **Hero:** fonda maktab rasmi, ustida sarlavha
- 3 **Yangiliklar** kartalari (Grid) — burchakda `absolute` sana belgisi
- 4 **Ustozlar:** doira rasmlar, `:hover` da rangli chegara
- 5 **Dars jadvali:** `nth-child(even)` zebra + `tr:hover`
- 6 **"Yuqoriga"** tugmasi — `fixed`
- 7 Sarlavhalar ostida `::after` chiziq

Amaliyot: yangilik kartasi

CSS

```
.yangilik {  
  position: relative;  
  border-radius: 14px;  
  overflow: hidden;  
  box-shadow: 0 4px 14px rgba(0,0,0,.08);  
  transition: box-shadow .2s;  
}  
.yangilik:hover { box-shadow: 0 12px 30px rgba(0,0,0,.18); }  
.yangilik .sana {  
  position: absolute; top: 12px; left: 12px;  
  background: white; border-radius: 8px;  
  padding: 4px 10px; font-weight: 800; color: #4f46e5;  
}
```

Ko'p uchraydigan xatolar

- ❌ `absolute` element sahifa burchagiga "uchdi" — otada `relative` yo'q
- ❌ `::before` ko'rinmaydi — `content` yozilmagan
- ❌ `sticky` ishlamaydi — `top: 0` yo'q yoki otada `overflow: hidden`
- ❌ `z-index: 9999` ham yordam bermaydi — elementda `position` yo'q
- ❌ `a :hover` (bo'sh joy bilan) — butunlay boshqa selektor

Savol

Sichqoncha element ustiga kelganda ishlaydigan pseudo-class qaysi?

A :active

B :hover

C :focus

D :over

Javobni tanlang — to'g'ri variant yashil bo'ladi

Savol

Jadvalning faqat juft qatorlarini tanlash uchun?

A `tr:even`

B `tr:nth(2)`

C `tr:first-child`

D `tr:nth-child(even)`

Javobni tanlang — to'g'ri variant yashil bo'ladi

Savol

::after ishlashi uchun qaysi xossa majburiy?

A content

B display

C position

D color

Javobni tanlang — to'g'ri variant yashil bo'ladi

Savol

Scrollda ham ekranning bir joyida turadigan tugma uchun qaysi position?

A relative

B absolute

C fixed

D static

Javobni tanlang — to'g'ri variant yashil bo'ladi

Savol

Kartadagi "-20%" belgisi kartaga nisbatan joylashishi uchun **kartaga** nima beriladi?

A `position: absolute`

B `position: relative`

C `position: fixed`

D `z-index: 1`

Javobni tanlang — to'g'ri variant yashil bo'ladi



Uyga vazifa

- 1 Maktab sahifasini yakunlang: barcha `:hover`, `:focus` holatlari
- 2 5 xil tugma: `:hover`, `:active`, `:disabled` holatlari bilan
- 3 Faqat CSS bilan **tooltip**: `position: absolute` + `:hover`

Yodda tuting

- Pseudo-class `:` — holat: `:hover` `:focus` `:active` `:nth-child()` `:not()`
- Pseudo-element `::` — `::before` `::after` (`content` majburiy), `::first-letter`
- `relative` — langar; `absolute` — langarga nisbatan; `fixed` — ekranga; `sticky` — yopishqoq
- `z-index` — qatlamlar tartibi (faqat position berilganlarda)



Savollar bormi?

Keyingi mavzu: **10. Moslashuvchan (responsiv) dizayn va media so'rovlar. Figma bilan ishlash**

Batafsil matn, misollar va testlar: **09-pseudo-class-position.html** darsida