BEFA

Technical Data Sheet

BCMF-3100
Coriolis Mass Flowmeter



Low Flow Precision Measurement	Precision Measurement & Process Control	High Capacity Precision Measurement
Starting at 2kg/hr to330kg/hr Flavoring Vials Chemical injection	Kg/min – tons/hr Truck loading Internal allocation Leak detection Produced fluids with chlorides	Up to 1,200 tons/hr Custody transfer Ship loading Railcar loading Pipeline measurement Marine bunkering Feedstock and fuel blending

CE





General

BCMF Coriolis mass flowmeters are the leading precision flow and density measurement solution offering the most accurate and repeatable mass measurement for liquids, orslurries. BCMF meters offer the most accurate measurement available for virtually any process fluid, while exhibiting exceptionally low pressure drop.

Features

- Unchallengeable BCMF performance on liquid mass flow,volume flow and density measurement
- Unique design delivers unparalleled measurement sensitivity andstability
- Guarantees consistent, reliable performance over the widest flow range
- Designed to minimize process, mounting, and environmental effect

Sensor Details

Accuracy	±0.1~0.5%
Repeatability	±0.1~0.25%
Density measurement range	0.5~2g/cm3, Accuracy: ±0.002 g/cm3
Operating temperature	-50~+200°C, (Min.-200°C, Max.:300°C)
Ambient temperature	-40~+60°C or -20~+60°C
The measuring tube material	SS316L; The housing material: SS304
Nominal pressure	4.0MPa.
Approval	Ex-proof: Exd (ia)IIC T6Gb

Transmitter Details

Principle	Analog signal processing
Ambient temperature	-40~+60°C or -20~+60°C
Display Parameters	Mass flow; Volume flow, Density, Temperature
Power Supply	24VDC/220VAC
Output Signal	Pulse/4-20mA
Communication	Modbus / Hart
Approval	Ex d (ia) ⅡC T6Gb