Technical Data Sheet

BPT10

PressureTransmitter



Features

- Reliable performance, easy application
- Short protection and reverse polarity protection
- Measure gauge, absolute and sealed gauge

Introduction

T10 is high reliable pressure transmitter produced by high stable piezo-resistive pressure sensor and special amplifier circuit.The transmitter is widely used for various pressure measurement application. The media should be compatible with stainless steel and viton.

Specification

- Pressure range:
  -0.1...0 ~ 0.01...60MPa
- Overpressure: 1.5 times FS
- Pressure type: gauge/ absolute / sealed gauge
- Process connection: G1/2 male / G1/4 male/ M20x1.5 male
- Non-linearity: 0.25% FS
- Temperature error:
  Typical: ≤±0.5%FS of span (at 0 ～ 70℃)
  Maximum: ≤±1%FS of span (at 0 ～ 70℃)
  Maximum: ≤±2%FS of span (at -20 ～ 85℃)
- Long term stability: max. ±0.3%FS/year
- Application temp: -20 ～ 85℃
- Storage temp: -40 ～ 100℃
- Power supply: 8 ～ 28VDC
- Output signal: 4 ～ 20mADC, 0.5 ～ 4.5VDC
- Load: ≤（U-8）/0.02Ω（2-wire），≥10k（3-wire）
- Housing protection:IP65

Construction and Outline Dimension

Construction material

- Housing: stainless steel
- Sensor housing: stainless steel
- Diaphragm: stainless steel 316L
- Sensor O-ring: Viton
- Plug housing: plastic

Electric Connection

Pin	2-wire	3-wire
1	+V	+V
2	+OUT	GND
3	Null	+OUT

Order Guide

BPT10	Pressure Transmitter			
	Range	Pressure range: -0.1…0 ～ 0.01…60MPa		
	[0 ～ X]kPa or MPa	X：the actual measured pressure		
		Code	Output signal	
		E	4 ～ 20mADC	
		K	0.5 ～ 4.5VDC	
			Code	Others
			C_2	G1/4
			C_3	G1/2
			C_5	M20×1.5
			C_6	NPT1/4
			G	Gauge
			S	Sealed gauge
			A	Absolute
BPT10	[0 ～ 100]kPa	E	C_2G	the whole spec

Notes

1. Please pay attention that the media should be compatible with the contacting material;
2. If the user has special requirement, please contact our company.