

Hands-on Lab - CRUD operations with Python



Estimated Time Needed: 60 mins

In this lab, you will learn how to create a **Products's list** using a Flask server. Your application should allow you to add a product, retrieve the products, retrieve a specific product with its id, update a specific product with its id, and delete a product with its id. All these operations will be achieved through the REST API endpoints in your Flask server.

You will create an application with API endpoints to perform Create, Retrieve, Update, and Delete operations on the above data using a Flask server.

You will use cURL and POSTMAN to test the implemented endpoints.


Objectives:

After completing this lab you will be able to:

- Create API endpoints to perform Create, Retrieve, Update, and Delete operations on transient data with a Flask server.
- Create REST API endpoints, and use POSTMAN to test your REST APIs.

Set-up : Create application

1. Open a terminal window by using the menu in the editor: **Terminal > New Terminal**.



2. Change to your project folder, if you are not in the project folder already.

```
1. 1
1. cd /home/project
```

Copied!

3. Run the following command to clone the Git repository that contains the starter code needed for this lab, if it doesn't already exist.

```
1. 1
1. [ ! -d 'jmgdo-microservices' ] && git clone https://github.com/ibm-developer-skills-network/jmgdo-microservices.git
```

Copied!

5. Change to the directory **jmgdo-microservices/CRUD** to start working on the lab.

```
1. 1
1. cd jmgdo-microservices/CRUD
```

Copied!

6. List the contents of this directory to see the artifacts for this lab.

```
1. 1
1. ls
```

Copied!

7. Run the following command on the terminal to install the packages that are required.

```
1. 1
1. python3 -m pip install flask flask_cors
```

Copied!

Exercise 1: Understand the server application

1. In the Files Explorer open the **jmgdo-microservices/CRUD** folder and view **products.py**.
2. You first need to import the packages required to create REST APIs with Flask.

```
1. 1
```

```
2.
1. from flask import Flask, jsonify, request
2. import json
```

Copied!

3. You can then create the Flask application, which will service all the REST APIs for adding, retrieving, updating, and deleting products.

```
1. 1
1. app = Flask("Product Server")
```

Copied!

4. The code has precreated products added to the list. These are defined in the following code.

```
1. 1
2. 2
3. 3
4. 4

1. products = [
2.     {'id': 143, 'name': 'Notebook', 'price': 5.49},
3.     {'id': 144, 'name': 'Black Marker', 'price': 1.99}
4. ]
```

Copied!

5. Now that the server is defined, you will create the REST API endpoints and define the routes or paths, one for each of the following operations.

- Retrieve all the products - GET Request Method
- Retrieve a product by its id - GET Request Method
- Add a product - POST Request Method
- Update a product by its id - PUT Request Method
- Delete a product by its id - DELETE Request Method

Add the following code to products.py in the space provided.

```
1. 1
2. 2
3. 3
4. 4
5. 5
6. 6
7. 7
8. 8
9. 9
10. 10
11. 11
12. 12
13. 13
14. 14
15. 15
16. 16
17. 17
18. 18
19. 19
20. 20
21. 21
22. 22
23. 23
24. 24
25. 25
26. 26
27. 27
28. 28
29. 29
30. 30
31. 31
32. 32
33. 33
34. 34
35. 35

1. # Example request - http://localhost:5000/products
2. @app.route('/products', methods=['GET'])
3. def get_products():
4.     return jsonify(products)
5.
6. # Example request - http://localhost:5000/products/144 - with method GET
7. @app.route('/products/<id>', methods=['GET'])
8. def get_product(id):
9.     id = int(id)
10.    product = [x for x in products if x["id"] == id][0]
11.    return jsonify(product)
12.
13. # Example request - http://localhost:5000/products - with method POST
14. @app.route('/products', methods=['POST'])
15. def add_product():
16.     products.append(request.get_json())
17.     return '', 201
18.
19. # Example request - http://localhost:5000/products/144 - with method PUT
20. @app.route('/products/<id>', methods=['PUT'])
21. def update_product(id):
22.     id = int(id)
23.     updated_product = json.loads(request.data)
24.     product = [x for x in products if x["id"] == id][0]
25.     for key, value in updated_product.items():
26.         product[key] = value
27.     return '', 204
28.
29. # Example request - http://localhost:5000/products/144 - with method DELETE
30. @app.route('/products/<id>', methods=['DELETE'])
31. def remove_product(id):
32.     id = int(id)
33.     product = [x for x in products if x["id"] == id][0]
34.     products.remove(product)
35.     return '', 204
```

Copied!

Run and test the server with cURL

1. In the terminal, run the python server using the following command.

```
1. 1
1. python3 products.py
```

Copied!

Executed!

The server starts running and listening at port 5000.

```
* Serving Flask app 'Product Server' (lazy loading)
* Environment: production
  WARNING: This is a development server. Do not use it in a production deployment.
  Use a production WSGI server instead.
* Debug mode: on
* Running on http://127.0.0.1:5000/ (Press CTRL+C to quit)
* Restarting with stat
* Debugger is active!
* Debugger PIN: 145-923-897
```

2. Open another Terminal by clicking the Terminal menu and selecting **New Terminal**.

3. In the new terminal, run the following command to access the <http://localhost:5000/products> API endpoint. curl command stands for Client URL and is used as command line interfacing with the server serving REST API endpoints. It is, by default, a GET request.

- 1. 1
- 1. curl http://localhost:5000/products

Copied! Executed!

This returns a JSON with the products that have been preloaded.

```
theia@theia-lavanyas:/home/project$ curl http://localhost:5000/products
[
  {
    "id": 143,
    "name": "Notebook",
    "price": 5.49
  },
  {
    "id": 144,
    "name": "Black Marker",
    "price": 1.99
  }
]
```

4. In the terminal, run the following command to add a product to the list. This will be a POST request to which you will pass the product parameter as a JSON.

- 1. 1
 - 2. 2
 - 3. 3
- ```
1. curl -X POST -H "Content-Type: application/json" \
2. -d '{"id": 145, "name": "Pen", "price": 2.5}' \
3. http://localhost:5000/products
```

Copied!

This command will not return any output. It will add the product to the list of products.

5. Verify if the product is added by running the following command.

- 1. 1
- 1. curl http://localhost:5000/products/145

Copied!

This should return the details of the product you just added with a POST request.

```
theia@theia-lavanyas:/home/project$ curl http://localhost:5000/products/145
{
 "id": 145,
 "name": "Pen",
 "price": 2.5
}
```

## Using POSTMAN to test the REST API endpoints

While the GET endpoints are easy to test with curl using a command line interface, the POST, PUT and DELETE commands can be cumbersome. To circumvent this problem, you can use Postman, which is a software that is available as a service.

Postman will need remote access to the server as it is an external entity. To get the URL click the following button.

Launch Application

Copy the URL into a notepad or other text editors. Go to <https://www.postman.com/> and sign up before you start using POSTMAN.

► Click here for instructions to sign up for Postman services.

- 1. Click **Create New** to start creating a request to the REST API endpoint.

# Get started with Postman

### Start with something new

Create a new request, collection, or API in a workspace

Create New →

### Import an existing file


Import any API schema file from your local drive or Github

Import file →

2. Choose **HTTP Request** from the options that you are presented with.


Create New

#### Building Blocks




### HTTP Request

Create a basic HTTP request




### WebSocket Request BETA

Test and debug your WebSocket connections




### gRPC Request

Test and debug your gRPC requests




### Collection

Save your requests in a collection for reuse and sharing



### Environment


Save values you frequently use in an environment



### Workspace


Create a workspace independently or share one

#### Advanced




### API Documentation

Create and publish beautiful documentation for your APIs




### Mock Server

Create a mock server for your in-development APIs




### Monitor

Schedule automatic checks to monitor your API performance



### API

Manage all aspects of API design, development, and testing



### Flows BETA

Create API workflows by connecting series of requests through a drag-and-drop UI.

Not sure where to start? [Explore](#) featured APIs, collections, and workspaces published by the Postman community.

3. Paste the URL that you have copied into the address bar. Change the request type to POST. To send input as JSON, choose raw->body->JSON.

POST



https://lavanyas-5000.theia-0-labs-prod-misc-tools-us-east-0.proxy.cognitiveclass.ai/products

Params Authorization Headers (7) Body ● Pre-request Script Tests Settings

☐ none ☐ form-data ☐ x-www-form-urlencoded ☒ raw ☐ binary ☐ GraphQL **JSON** ▼

```
1 {
2 ... "id":146,
3 ... "name":"Laptop Bag",
4 ... "price":45.00
5 }
```

4. Enter the following JSON object and click the Send button. This will add the product to your previous list of products.

```
1. 1
2. 2
3. 3
4. 4
5. 5

1. {
2. "id":146,
3. "name":"Laptop Bag",
4. "price":45.00
5. }
```

Copied!

4. Verify the list of products to ensure that the request has gone through and the product is added. Change the request type to GET and remove the JSON object from the request body. Click Send and observe the output in the response window.

GET

https://lavanyas-5000.theia-0-labs-prod-misc-tools-us-east-0.proxy.cognitiveclass.ai/products

Params Authorization Headers (6) Body Pre-request Script Tests Settings

none form-data x-www-form-urlencoded raw binary GraphQL JSON

1

Body Cookies (1) Headers (10) Test Results

Status: 200 OK

Pretty Raw Preview Visualize JSON

```
7 {
8 "id": 144,
9 "name": "Black Marker",
10 "price": 1.99
11 },
12 {
13 "id": 145,
14 "name": "Pen",
15 "price": 2.5
16 },
17 {
18 "id": 146,
19 "name": "Laptop Bag",
20 "price": 45.0
21 }
22]
```

5. Test the PUT endpoint to update product details by changing the price of the item with id 146 to 42.00. Set the request type to PUT and add the product id to the end of the URL and add the value to be changed as a JSON body and click Send.

```
1. 1
2. 2
3. 3

1. {
2. "price": 42.00
3. }
```

Copied!

PUT

https://lavanyas-5000.theia-0-labs-prod-misc-tools-us-east-0.proxy.cognitiveclass.ai/products/146

ParamsAuthorizationHeaders (8)BodyPre-request ScriptTestsSettings

none

form-data

x-www-form-urlencoded

raw

binary

GraphQL

JSON

1

{

2

"price": 42.00

3

}

6. Verify the product with id 146 to ensure that the request has gone through and the product is updated. Change the request type to GET and remove the JSON object from the request body. Click Send and observe the output in the response window.

GET

https://lavanyas-5000.theia-0-labs-prod-misc-tools-us-east-0.proxy.cognitiveclass.ai/products/146

ParamsAuthorizationHeaders (6)BodyPre-request ScriptTestsSettings

none

form-data

x-www-form-urlencoded

raw

binary

GraphQL

JSON

1

BodyCookies (1)Headers (10)Test Results

Status: 200 OK

PrettyRawPreviewVisualizeJSON

1

{

2

"id": 146,

3

"name": "Laptop Bag",

4

"price": 42.0

5

}

Practice labs

1. Update product details of product with id 144 by changing its price to 2.50.

- Click here for a hint
- Click here for the solution

2. Add the following product using POST method.

```
1. 1
2. 2
3. 3
4. 4
5. 5
1. {
2. "id":142,
3. "name":"Eraser",
4. "price":1.50
5. }
```

Copied!

- Click here for a hint

3. Delete the product with id 142.

- ▶ [Click here for a hint](#)
- ▶ [Click here for the solution](#)

**Congratulations! You have completed the lab for CRUD operations with Python.**

## Summary:

In this lab, you have performed CRUD Operations like GET, POST, PUT, and DELETE on a Python server App and tested the above methods using POSTMAN.

## Author(s)

Lavanya T S

## Changelog

| Date       | Version | Changed by  | Change Description      |
|------------|---------|-------------|-------------------------|
| 01-11-2022 | 1.0     | Lavanya T S | Initial version created |
| 2022-11-25 | 1.1     | Steve Hord  | QA pass edits           |

**(C) IBM Corporation 2022. All rights reserved.**