

SELNIKEL ISITMA SISTEMLERİ A.Ş.

SB-Series Industrial Steam Boiler Technical Datasheet

Document Code: SB-DS-2026 | Revision: REV-02 | Department: Thermal Engineering

1. General Overview & Design Standards

The Selnikel SB-Series is a 3-pass scotch marine industrial fire-tube steam boiler designed in full compliance with EN 12953 and ASME Section I standards. High thermal efficiency is achieved through optimized flame-tube dimensions and integrated flue gas economizers.

2. Technical Operating Parameters & Capacities

Model Code	Steam Cap. (t/h)	Working Press. (bar)	Design Press. (bar)	Steam Temp. (°C)	Thermal Power (kW)
SB-500	0.5 t/h	12.0 bar	16.0 bar	191.6 °C	350 kW
SB-1000	1.0 t/h	16.0 bar	18.0 bar	204.3 °C	700 kW
SB-2000	2.0 t/h	16.0 bar	20.0 bar	204.3 °C	1400 kW
SB-5000	5.0 t/h	16.0 bar	25.0 bar	204.3 °C	3500 kW

3. Safety Relief Valves & Auxiliary Limits

Section 3.1: Safety relief valves must be configured with full discharge capacity at 10% overpressure. Set point for SB-Series safety valve 1 is strictly 16.5 bar, with nominal discharge rate of 1250 kg/h.

Safety Device	Set Pressure (bar)	Connection DN (mm)	Discharge Cap. (kg/h)
Primary Safety Valve	16.5 bar	32 mm	1250 kg/h
Secondary Safety Valve	17.0 bar	32 mm	1300 kg/h
High Pressure Switch	16.2 bar	15 mm	N/A