

IJGTP Class Documentation

Abstract: This guide describes the public interface of `ijgtp.cls`: preparing one manuscript or a collection of papers, setting author and publication metadata, using figures and tables, and compiling bibliographies. It describes the main commands available to authors, selected standard commands whose behavior the class changes, and the additional table column types. Internal commands containing @ are implementation details and are not intended for use in manuscripts.

Keywords: LaTeX; IJGTP; document class; author instructions

Contents

1	Files, packages, and class options	1
2	A minimal manuscript	2
3	Author-facing command reference	2
3.1	Basic information	2
3.2	Abstract, keywords, and metadata	3
3.3	Publication identifiers	3
3.4	Bibliography commands and formatting hooks	4
3.5	Additional table column types	4

1. Files, packages, and class options

Place `ijgtp.cls` and `scilight.bst` in the working directory or in a directory searched by TeX. The title and footer require the image files `header`, `F1`, and `cc-by`; the ORCID command also requires `orcid`. Supply their PDF versions for PDFLaTeX and their EPS versions for the LaTeX–dvips workflow. The sample plot files are examples, not class dependencies.

The class is based on `article`, defaults to 10-point text, and sets A4 journal geometry. Options are passed to `article`: for example, `\documentclass [12pt]{ijgtp}` selects 12-point text.

Load optional packages explicitly. For example:

```
\documentclass[10pt]{ijgtp}
\usepackage{amsmath,amssymb,cmap}
\usepackage[utf8]{inputenc}
\usepackage[T1]{fontenc}
\usepackage[english]{babel}
% \usepackage{float} % only if its facilities are needed
% \usepackage{epstopdf} \epstopdfsetup{suffix=} % convert eps figures in pdf
```

The class already loads `natbib`, `bibunits`, `etoolbox`, `geometry`, `xcolor`, `microtype`, `setspace`, `times`, `titlesec`, `array`, `lineno`, `graphicx`, `caption`, `fancyhdr`, `lastpage`, `catchfile`, and `hyperref`. Their commands remain available.

2. A minimal manuscript

Define the metadata before `\maketitle`. Each `\author` starts a new author record. The following affiliation, email, ORCID, and correspondence commands apply to that author. Avoid verbatim material inside the captured abstract environment.

```
\documentclass{ijgtp}
\begin{document}
\title{Title of the manuscript}
\author{Wednesday Addams}
\affiliation{Department of Physics, Nevermore Academy}
\email{inmemoryofwednesday@gmail.com}
\corresponding
\begin{abstract}
An overview of the question, method, and results.
\end{abstract}
\keywords{gravitation; theoretical physics}
\maketitle
\section{Introduction}\label{sec:intro}
The manuscript starts here.
\section{Conclusions}
See Section~\ref{sec:intro}.
\end{document}
```

`template.tex` provides an extended example that can serve as a starting point for a manuscript.

3. Author-facing command reference

The following list covers the public commands and environments defined or given paper-specific behavior by the class. Arguments in examples are placeholders unless stated otherwise.

3.1. Basic information

`\title {title}` Sets the title for the next `\maketitle`. The title is retained after printing, so it can be reused if no replacement is supplied. Every manuscript is expected to have a title.

`\papertype {type}` Sets the designation above the title, such as `Article` or `Review`. The default is `Article`.

`\author {full name}` Appends an author. Repeat this command for additional authors. Author notes can be supplied with `\thanks {note}` inside the name.

`\authorname {surname}{initials}` Overrides the current author's name parts used in running heads and the suggested citation. It does not alter the displayed full name. For example, use `\authorname {van Beethoven}{L.}` after `\author {Ludwig van Beethoven}`. Without an override, the last space-separated name component is treated as the surname and earlier components supply initials. Use the override for compound surnames, suffixes, or other names that this simple rule cannot represent.

`\affiliation {address}` Adds an affiliation to the current author. Repeat it for multiple affiliations. Identical affiliation text is shared between authors.

`\email {address}` Sets the current author's email address. Only addresses of authors marked as corresponding are printed in the correspondence block. Literal underscores and escaped underscores are supported.

`\orcid {identifier}` Sets the current author's ORCID identifier, without the URL prefix. It produces an icon linking to the ORCID page. An empty argument omits the icon. The identifier is not validated by the class.

`\corresponding` Marks the current author as corresponding. It takes no argument. The class suppresses the distinguishing asterisk when all authors are corresponding. The correspondence block requires a nonempty email address from at least one corresponding author.

The commands `\authorname`, `\affiliation`, `\email`, `\orcid`, and `\corresponding` require a preceding `\author`; otherwise, the class reports an error.

3.2. Abstract, keywords, and metadata

abstract environment Collects the abstract for the next title block. Use `\begin {abstract}` and `\end {abstract}` before `\maketitle`. A later abstract replaces an earlier one.

\keywords {list} Sets the keyword text; use semicolons or another desired separator.

\pacs {list} Sets PACS classification text. It is printed after the keywords.

\arxivnumber {identifier} Sets an arXiv identifier without an `arXiv:` prefix or URL. Examples are 2507.22660, 2603.12466v2, and gr-qc/0307012. The class checks identifier syntax, not whether the record exists. Invalid input produces a warning and preserves any earlier valid identifier. The link appears in the suggested citation.

\maketitle Starts a paper, first finishing the preceding pages and floats.

\appendix Switches the current paper to appendix section numbering.

Keywords, PACS codes, and the arXiv identifier are optional. Empty or space-only keyword and PACS arguments omit their headings.

3.3. Publication identifiers

\ijgtppublished {year}{volume}{issue}{article} Sets journal publication metadata and enables the journal citation suggestion, publication running head, and DOI footer. For example:

```
\ijgtppublished {2026}{2}{1}{5}
```

This constructs 10.53941/ijgtp.2026.100005. The DOI consists of the year, issue, and article number padded to at least five digits; the volume does not enter this identifier. Use actual assigned publication data. Arguments must contain decimal digits only. The year must be at least 2025, and the other values must be positive. Each value must fit TeX's integer range. Leading zeros are accepted and normalized. Invalid input produces a warning and preserves any earlier valid values.

\receiveddate {date} Sets the received-date text.

\reviseddate {date} Sets the revised-date text.

\accepteddate {date} Sets the accepted-date text.

\publisheddate {date} Sets the publication-date text.

Date text is printed as supplied: no date parsing or chronological validation is performed. Without publication metadata, the running head indicates a manuscript prepared for the journal. The copyright year is the supplied publication year, if available; otherwise, it is the current compilation year.

3.4. Bibliography commands and formatting hooks

\bibliography {database} Prints the current bibliography using the named `.bib` database, then closes that bibliography unit. Omit the filename extension; multiple database names may be comma-separated.

\bibliographystyle {style} Selects the current paper's BibTeX style. Place it after `\maketitle` and before `\bibliography`. It may follow citations.

\bibnumfmt {number} The class redefines this `natbib` formatting hook to print a bibliography number followed by a period. Authors normally do not call it.

\bibsection The class redefines this `natbib` hook to create the unnumbered references heading and its table-of-contents entry.

Use the loaded `natbib` commands, such as `\cite {key}`, `\cite {first,second}`, and `\nocite {key}`, in the usual way. The class uses numeric citations with sorting and compression. `\nocite {*}` includes all entries from the selected database.

3.5. Additional table column types

The class defines `L{width}`, `C{width}`, and `R{width}`: fixed-width, vertically centered paragraph columns with left, centered, and right horizontal alignment, respectively. For example:

```
\begin{tabular}{L{4cm}C{2cm}R{2cm}}
Quantity & Symbol & Value \\
Decay time &  $\tau$  & 1.0 \\
\end{tabular}
```

The public helper `\PreserveBackslash {alignment}` applies an alignment command while retaining the meaning of the table row terminator `\\`. The three column types use it internally; ordinary tables do not need to call it directly.