ALPIDE

Threshold Scans and Noise Occupancy

Maurice Donner

21. July 2020

Threshold Scan

Generate digital Pulse in a number of pixels
$\rightarrow$ Then read out hits and repeat

- Up to 32 Pixels per Region simultaneously
- Use only a fraction of the Chip (~1-5%)

Parameters used:

- `PIXPERREGION 1`
- `NMASKSTAGES 164`

} Corresponds to $32 \cdot 164 = 5248$ (1% of the chip)

Threshold Scan

50 Injections per charge point, then plot hit probability. (S-Curve scan)

Example:



$$p_{\text{Hit}}(q_{\text{inj}}) = \frac{1}{2}\left(1 + \text{Erf}\left[\frac{q_{\text{inj}} - \mu}{\sqrt{2}\sigma}\right]\right)$$

Threshold Scan

- Extract mean

Distribution of Thresholds:



Threshold Scan

- Extract mean
- Repeat with different settings and compare the runs

Distribution of Thresholds:





Threshold Scan

- Extract mean
- Repeat with different settings and compare the runs

Distribution of Thresholds:





For cosmic muons at 50 GeV: Energy Deposit ~0.0286 MeV
7900 e-h-pairs

Noiseoccupancy Scan

Gives a selectable number of random triggers and returns the number of hits.

- If Threshold is low enough for electronic noise to produce a hit, measurements taken will be affected by a fake hit rate.

Noiseoccupancy Scan

Gives a selectable number of random triggers and returns the number of hits.

- If Threshold is low enough for electronic noise to produce a hit, measurements taken will be affected by a fake hit rate.



Noiseoccupancy Scan

Gives a selectable number of random triggers and returns the number of hits.

- If Threshold is low enough for electronic noise to produce a hit, measurements taken will be affected by a fake hit rate.