#### Status report - Thursday, April 23nd

Threshold Scans and Data Evaluation

Maurice Donner

23. April 2020

## How things have been done

### General Process - Flow Diagram

Perform a set of measurements in lab  $\rightarrow$  (Python)

## How things have been done

### General Process - Flow Diagram

Perform a set of measurements in lab  $\rightarrow$  Plot results (Python)

## How things have been done

### General Process - Flow Diagram

```
Perform a set of measurements in lab \rightarrow Write results to .csv (done by hand) \rightarrow Plot results (Python)
```

## Problem: Usually quite large set of data

For each measurement we have to

• Extract Parameters used (VCASN, ITHR) from the specific config file

#### Problem: Usually quite large set of data

For each measurement we have to

- Extract Parameters used (VCASN, ITHR) from the specific config file
- Extract and analyze measurement data

4 / 10

### Problem: Usually quite large set of data

For each measurement we have to

- Extract Parameters used (VCASN, ITHR) from the specific config file
- Extract and analyze measurement data
- Write that information into a csv file for further analysis

#### Problem: Usually quite large set of data

For each measurement we have to

- Extract Parameters used (VCASN, ITHR) from the specific config file
- Extract and analyze measurement data
- Write that information into a csv file for further analysis

#### Approach

Simplyfying the process by writing a script that

 Extracts the timestamp for each measurement and properly relates the .cfg to the .dat files

#### Problem: Usually quite large set of data

For each measurement we have to

- Extract Parameters used (VCASN, ITHR) from the specific config file
- Extract and analyze measurement data
- Write that information into a csv file for further analysis

#### Approach

Simplyfying the process by writing a script that

- Extracts the timestamp for each measurement and properly relates the .cfg to the .dat files
- performes analysis on ALL of the measurement data at once

#### Problem: Usually quite large set of data

For each measurement we have to

- Extract Parameters used (VCASN, ITHR) from the specific config file
- Extract and analyze measurement data
- Write that information into a csv file for further analysis

#### Approach

Simplyfying the process by writing a script that

- Extracts the timestamp for each measurement and properly relates the .cfg to the .dat files
- performes analysis on ALL of the measurement data at once
- writes result to a csv file

#### Scripting in Bash

ScanConfig\_200121\_193551.cfg ScanConfig\_200121\_193951.cfg ThresholdScan\_200121\_193551.dat ThresholdScan\_200121\_193951.dat

#### Scripting in Bash

ScanConfig\_200121\_193551.cfg ScanConfig\_200121\_193951.cfg ThresholdScan\_200121\_193551.dat ThresholdScan\_200121\_193951.dat

```
for i in $(ls $PATHTOFILES | grep '.dat'); do
#Extract Timestamp
TIMESTAMP=$(echo $i | tail -c 18 | head -c 13)
CONFIG="ScanConfig_$TIMESTAMP.cfg"

#Then extract Parameters from config file (Later add VBB)
VCASN=$(cat $PATHTOFILES$CONFIG | grep 'VCASN' | awk -F ' ' '{print $2}' | head -1)
ITHR=$(cat $PATHTOFILES$CONFIG | grep 'ITHR' | awk -F ' ' '{print $2}')
TRSH=$(./thresh.py $PATHTOFILES$i)

# Write to csv file
printf '%s\n' "$TIMESTAMP" "$VCASN" "$ITHR" "$TRSH" | paste -sd ',' >> output.csv
done
```

5 / 10

#### Scripting in Bash

ScanConfig\_200121\_193551.cfg ScanConfig\_200121\_193951.cfg ThresholdScan\_200121\_193551.dat ThresholdScan\_200121\_193951.dat

```
for i in $(ls $PATHTOFILES | grep '.dat'); do
#Extract Timestamp
TIMESTAMP=$(echo $i | tail -c 18 | head -c 13)
CONFIG="ScanConfig_$TIMESTAMP.cfg"

#Then extract Parameters from config file (Later add VBB)
VCASN=$(cat $PATHTOFILES$CONFIG | grep 'VCASN' | awk -F ' ' '{print $2}' | head -1)
ITHR=$(cat $PATHTOFILES$CONFIG | grep 'ITHR' | awk -F ' ' '{print $2}')
TRSH=$(./thresh.py $PATHTOFILES$i)

# Write to csv file
printf '%s\n' "$TIMESTAMP" "$VCASN" "$ITHR" "$TRSH" | paste -sd ',' >> output.csv
done
```



```
Timestamp, VCASN, ITHR, Threshold [DAC]
200121_193551,47,51,13.60355155825141
200121_193951,47,60,15.953068558715911
...
```

#### **Plotting**

#### **New Problem**

Data is not ordered, and the csv contains multiple entries for the same values of VCASN and ITHR

6 / 10

### **Plotting**

#### **New Problem**

Data is not ordered, and the csv contains multiple entries for the same values of VCASN and ITHR

 $\rightarrow$  When doing plots, formerly used hardcoding

### **Plotting**

#### **New Problem**

Data is not ordered, and the csv contains multiple entries for the same values of VCASN and ITHR

 $\rightarrow$  When doing plots, formerly used hardcoding

#### Approach

Write a "sorting" algorithm, that automatically identifies the ranges chosen for VCASN and ITHR.


```
Timestamp, VCASN, ITHR, Threshold [DAC]
200323_134855,53,51,6.725833998523066
200323_135218,53,60,8.186236372633545
200323_135541,53,70,9.833234746846962
200323_132837,50,51,9.335578330893117
200323_133200,50,60,11.202496464178642
200323_133523,50,70,13.211766207119839
```


6 / 10

#### plotting

```
VCASN, ITHR, TRSH = np.loadtxt(csv, skiprows=1, usecols=(1,2,3), delimiter=",", unpack=True)
def getValues(array):
   #Create a temporary list
   temp = []
   #Write each unique entry into the temporary list
   for i in array:
       if i in temp: continue
       else: temp.append(i)
   #Since the array of values in this case is quite small, we can use temp.sort
   temp.sort()
   output = np.ndarrav((len(temp)).dtvpe=int)
   for i in range(len(temp)):
       output[i] = int(temp[i])
   return output
VCASN_0 = getValues(VCASN)
ITHR 0 = getValues(ITHR)
##### Implement sorting algorithm #####
Threshold = np.ndarray((len(VCASN_0),len(ITHR_0)))
for i in range(len(VCASN_0)):
   for j in range(len(ITHR_0)):
       Threshold[i,j] = TRSH[(VCASN == VCASN_0[i]) & (ITHR == ITHR_0[j])]
****************
```

#### Results for 0 V Back Bias







#### Notes

- Value for VCASN = 47 and ITHR = 100 is faulty, due to a premature stop of the measurement after about 7% of the injections.
   Threshold calculation fails there.
- The smooth heatmap (on the right) is just for visualization! The colors do NOT represent accurate values

#### Results for 3 V Back Bias





Let the bash script...

Include Errors

Let the bash script...

- Include Errors
- Automatically detect faulty runs

Let the bash script...

- Include Errors
- Automatically detect faulty runs
- Work on different kinds of scans (NOISEOCC etc.)

Let the bash script...

- Include Errors
- Automatically detect faulty runs
- Work on different kinds of scans (NOISEOCC etc.)

# Thank you!