

DS-2CE56C2T-IRM

HD720P Turbo HD Turret Camera




























Key features

- HD720P Video Output
- Adopt HDTVI Technology
- True Day/Night
- DNR, Smart IR
- 20m IR distance
- IP66 weatherproof

Dimensions



DS-2CE56C2T-IRM Camera Image Sensor 1/3" Progressive Scan CMOS Effective Pixels 1280(H)*720(V) Min. Illumination 0.01 Lux @(F1.2,AGC ON), 0 Lux with IR Shutter Time 1/25(1/30) s to 1/50,000 s 3.6mm (2.8mm, 6mm optional) Lens Angle of View: 76.88°(3.6mm), 99.73°(2.8mm), 50.1°(6mm) Lens Mount M12 Angle Adjustment Pan: 0 - 360°, Tilt: 0 - 90°, Rotation: 0 - 360° Day & Night ICR Synchronization Internal synchronization Video Frame Rate 25 fps (PAL) / 30 fps (NTSC) HD Video Output 1 Analog HD output S/N Ratio More than 52dB General Working Temperature/ Humidity -40 °C - 60 °C (-40 °F - 140 °F) Humidity 90% or less (non-condensing) Power Supply 12 VDC Max. 3.5W Power Consumption IP66 Weather Proof Ratings IR Range Up to 20m Dimensions 89.6 × 59.1 mm (3.53" × 2.33") 400 g (0.88 lb) Weight

Accessories





Indoor/outdoor wall mount DS-1272ZJ-110-TRS

Video balun DS-1H18

Available models

DS-2CE56C2T-IRM