

Grading the Narrators: An Isnād–Rijāl Framework for Claim-Level Provenance in Multi-Agent Knowledge Systems

Ali Zahid Raja

Independent Researcher alizahidraja@gmail.com ORCID: 0009-0003-7875-4590

27 July 2026

Abstract

Modern multi-agent knowledge systems increasingly accumulate knowledge through chains of autonomous transformations rather than direct retrieval. Existing provenance work records *what happened* — execution traces, tool calls, evidence links — and source-reliability estimation is long established (truth discovery, reputation systems). What is missing is an operational framework that attaches graded, per-domain transmitter reliability to claim-level transmission chains, with completeness semantics, transformation-typed aggregation, decoupled content criticism, and serve/review/quarantine routing for compiled multi-agent knowledge.

Classical Islamic hadith science confronted a structurally similar problem: deciding whether knowledge transmitted through chains of human narrators should be accepted. Over centuries it developed a rigorous methodology — isnād (a complete transmission chain attached to every claim), rijāl (systematic grading of each narrator’s integrity and precision), weakest-link chain evaluation, corroboration through independent chains, and matn criticism (content evaluated independently of chain quality). This paper transfers that methodology to AI system design.

The framework contributes: (1) a formal mapping from hadith-science concepts to multi-agent knowledge pipelines; (2) a relational schema implementing claim chains and a graded narrator registry; (3) a decision matrix combining chain grade with content criticism to yield concrete serve/review/quarantine actions; and (4) an empirical evaluation on 20,000 claims extracted from real undergraduate physics textbooks.

The evaluation validates two mechanisms and is explicit about a third. Weakest-link grading correctly quarantined every claim whose chain contained a rejected narrator, with each quarantine traceable to the grade that caused it. The jarḥ–ta’dīl loop independently recovered three of four narrator grades from audit evidence — and missed the fourth, which carried the highest fault rate in the experiment, because it was too rare in the calibration split to be graded at all. Independent-chain corroboration fires across three corpora of increasing difficulty, with negative controls on the Wikipedia corpus. Two results are reported as inconclusive rather than positive: a matched-coverage comparison against the baseline could not be completed, because the framework could not be driven above 4.8% coverage with the reference content critic; and the confidence-gated baseline is uninformative by construction and therefore supports no claim about real model self-confidence.

The framework targets factual knowledge accumulation, not open-ended or creative generation, and is intentionally modular: different deployments may instantiate different grading functions while preserving the same architectural principles. This is a systems-architecture and epistemology paper. It proposes a framework, a schema, and an evaluation, and it is explicit throughout about which claims the evidence does and does not yet support.

Keywords: provenance, multi-agent systems, knowledge bases, trust, epistemology, isnād, hadith science, claim verification

1. Introduction

Modern AI systems increasingly communicate not raw evidence but transformed knowledge. A single factual claim may pass through document retrieval, extraction, summarization, knowledge integration, and answer synthesis before reaching a user. While provenance systems can often reconstruct this chain after the fact, they provide limited guidance for answering the question users ultimately care about: why should this particular chain of transformations be trusted?

Consider the pipeline behind a single answered question in a modern LLM-maintained knowledge base: a scraper extracts text from a source; an ingestion agent analyzes it, reconciles it against existing pages, and writes a compiled article; an answer agent later reads several such articles and synthesizes a cited response. The claim the user receives has passed through at least four hands — the original source, the extraction step, the ingestion model, the synthesis model — and each hand can drop, distort, or invent. Current systems attach page-level citations (“this answer drew on these documents”), and a growing body of provenance work records execution traces of what each agent did [Souza et al. 2025; arXiv:2606.04990]. But neither answers the question a careful reader actually asks: *this specific claim, having passed through these specific transformers — should I trust it?*

This problem is not new. Its most rigorous pre-modern solution took shape over roughly twelve centuries, beginning nearly fourteen hundred years ago.

After the death of the Prophet Muhammad (632 CE), Muslim scholars faced an epistemic crisis of exactly this shape: statements attributed to him circulated through lengthening chains of human transmitters, with fabrication, error, and honest distortion all in play. The response was not to trust the content on its plausibility, nor to trust chains on their length, but to build a formal discipline — ‘ilm al-ḥadīth — whose core insight was that **the trustworthiness of a claim is a function of the graded reliability of every individual who transmitted it**. Every accepted narration carries its isnād: the complete, gap-free chain of narrators. A parallel discipline, ‘ilm al-rijāl (“the science of the transmitters”), maintained biographical assessments of each narrator’s integrity (‘adālah) and precision (ḍabt), continuously updated through a formal criticism-and-accreditation process (al-jarḥ wa-l-ta’dīl). A chain is graded by its weakest link; independent corroborating chains can upgrade a claim; and even a flawless chain does not exempt the content itself from criticism (naqd al-matn), because a sound chain can carry a subtly defective text (‘ilal) [Brown 2017; Ibn al-Ṣalāḥ, 13th c.].

Substitute “narrator” with “agent, model version, or scraper” and this is a design specification for claim-level trust in multi-agent AI systems — one that existing provenance frameworks, which record chains but do not grade the transmitters, have not articulated. I call the resulting framework **ISNAD**; where the lowercase *isnād* appears, it denotes the classical concept rather than the system.

Contributions. (1) A formal mapping from isnād-rijāl methodology to multi-agent knowledge pipelines (§4). (2) A relational schema — claim chains plus a graded narrator registry — implementing the mapping, with an open-source reference implementation (§5). (3) A decision matrix combining chain grade with content criticism that yields concrete serve/review/quarantine actions (§4.4). (4) A case study in which a prototype self-maintaining knowledge base surfaced 19 genuine cross-framework contradictions in undergraduate physics texts, demonstrating the matn-criticism substrate (§6). (5) An evaluation on 20,000 claims from real physics textbooks that validates

weakest-link quarantine and corroboration, reports a partial failure of the jarḥ–ta’dil loop, and reports two analyses as inconclusive (§8). (6) An explicit account of what remains unvalidated and what would validate it (§7, §8.7).

Direction of transfer. A substantial literature applies AI *to* hadith texts — machine learning for chain analysis, authenticity classification, narrator-network mining [Int’l J. Noesantara Islamic Studies 2025; Digital Muslim Review 2025]. This paper inverts the direction: it applies hadith *methodology to* AI system design. To the best of my knowledge, no prior work systematically adapts the isnād–rijāl methodology into an operational provenance architecture for multi-agent knowledge systems.

2. Background

This section reviews the two bodies of knowledge that anchor the framework: the classical hadith transmission science, and the current state of provenance and trust in multi-agent AI systems. It then traces a deeper lineage across centuries of convergent solution design.

2.1 Source reliability across traditions: the deep lineage

The problem of assessing transmitted information — determining which claims to trust when they arrive through chains of human or machine intermediaries — has been independently solved, in partial forms, across multiple intellectual traditions. This section traces that lineage to establish that ISNAD’s contribution is not novelty for its own sake, but the transfer of the most operationally complete solution to a domain that lacks it.

Wave 1 — Pre-computational foundations. Condorcet’s jury theorem (1785) demonstrated that independent witnesses each better than random produce error that falls with agreement — the mathematical ancestor of corroboration-based error reduction. If each voter has probability $p > 0.5$ of being correct, a majority vote approaches certainty as the group grows. This is independence-based error reduction, the formal analogue of mutāba‘āt. Hume (1748), in “Of Miracles,” argued that testimony credibility must be weighed against witness reliability, introducing the intuition that transmitters themselves must be graded. Anglo-American evidence law codified these intuitions: the hearsay-within-hearsay rule (U.S. FRE 805) requires each link in a multi-hop testimony chain to independently qualify — a legal weakest-link principle. Chain-of-custody requirements are the legal analogue of ittiṣāl (unbroken transmission).

Wave 2 — Statistical and trust-theoretic formalization. Dempster (1967) introduced upper and lower probabilities, laying groundwork for evidence combination with source-reliability discounting; Shafer (1976) developed this into a full mathematical theory of evidence. Dawid and Skene (1979) provided the statistical skeleton for grading annotators: maximum-likelihood estimation of observer error rates via EM, even when true labels are unknown. Jøsang (2001) introduced subjective logic — trust discounting along chains plus consensus fusion, the closest formal ancestor of weakest-link aggregation with corroboration. This was extended through beta reputation (Jøsang & Ismail, 2002), EigenTrust (Kamvar et al., 2003), ReGreT (Sabater & Sierra, 2001), and FIRE (Huynh et al., 2006).

Wave 3 — Truth discovery and knowledge fusion at scale. Yin, Han and Yu (2008) introduced TruthFinder, jointly estimating truth and source reliability from conflicting web data. Paster-nack and Roth (2010, 2013) extended this with prior-knowledge integration and latent credibility

analysis. Google’s Knowledge Vault (Dong et al., 2014) fused web extractions into a probabilistic knowledge base; Knowledge-Based Trust (Dong et al., 2015) estimated web source trustworthiness from factual correctness. Database provenance (Cui & Widom, 2000; Buneman et al., 2001) and Semantic Web provenance (Gil & Artz, 2007; Hartig & Zhao, 2009) addressed lineage tracking.

Positioning — what each family lacks. Truth discovery grades sources but treats the path from source to serving as transparent: no transmission chains, no transformation types, no completeness semantics. Subjective logic supplies chain-discounting arithmetic but no operational registry lifecycle (per-domain grades, version-bump resets, quarantine), no decoupled content criticism, and no serve/review/quarantine routing. Multi-agent reputation systems grade peer agents for partner selection, not claim-level provenance in compiled knowledge. ISNAD’s contribution is the assembled operational protocol — chains, a graded per-domain registry, transformation-typed weakest-link aggregation, gated corroboration, dual criticism, and a decision matrix — transferred intact from the tradition that ran it as a complete system.

2.2 A primer on hadith transmission science

The following concepts, formalized between roughly the 8th and 13th centuries CE and systematized in works such as Ibn al-Ṣalāḥ’s *Muqaddimah* and al-Dhahabī’s narrator-criticism compendium *Mizān al-I’tidāl*, constitute the framework this paper adapts. Jonathan Brown’s *Hadith* [2017] is the standard English academic treatment.

Term	Meaning	This paper’s usage
isnād	The complete chain of transmitters attached to a narration	The agent chain attached to a claim
matn	The transmitted content itself	The claim text
rijāl	“The transmitters”; the discipline of evaluating them	The narrator registry
‘adālah	A narrator’s integrity/uprightness	Resistance to manipulation; source trustworthiness
ḍabt	A narrator’s precision and retention accuracy	Measured error rate of an agent/model
al-jarḥ wa-l-ta’dīl	Formal criticism and accreditation of narrators	The registry update process (evals, audits)
ittiṣāl / munqaṭi‘	Chain continuity / a broken chain	Complete trace / missing trace segment
ṣaḥīḥ, ḥasan, ḍa‘īf, mawḍū‘	Sound, good, weak, fabricated (grades)	Trust tiers for claims
mutāba‘āt	Independent corroborating chains	Multiple disjoint agent chains asserting one claim
‘ilal	Hidden defects: sound-looking chain, defective content	Chain passes but content criticism fails
muḥaddith	The expert scholar who adjudicates difficult cases	The human reviewer in the loop

Table 1: Correspondence between hadith-science concepts and their usage in this framework.

Five structural principles matter for the transfer:

1. **Every claim carries its full chain.** A narration without a complete isnād is inadmissible by default; a chain with a gap (munqaṭi‘) is automatically downgraded regardless of content quality.

2. **Transmitters are graded individually and continuously.** Rijāl scholarship maintained living biographical databases; a narrator’s grade could fall when errors surfaced (jarḥ) or rise with corroborated accuracy (ta’dīl).
3. **The chain is graded by its weakest link.** One weak narrator caps the grade of the whole chain, however strong the others.
4. **Corroboration can upgrade.** A claim carried by multiple *independent* chains (mutāba‘āt) can rise a grade — the epistemics of redundancy, formalized.
5. **Content is criticized independently of the chain.** A perfect isnād does not immunize the matn; contradictions with established knowledge trigger the ‘ilal category — hidden defect — and expert adjudication.

Acknowledging the critical tradition. The Western critical tradition on hadith — from Schacht’s skepticism about early Islamic legal transmission (Schacht, 1950) to Juynboll’s form-critical analyses (Juynboll, 1983) — has questioned traditional authentication methods. Yet even within this critical tradition the methodological architecture has analytic value. Motzki’s isnād-cum-matn analysis systematically compares transmission chains and text variants across narrations to date and verify hadith — a secular academic method that uses joint chain-and-content analysis, precisely the dual-criticism architecture this paper borrows. More recently, computational hadith studies have applied AI to narrator disambiguation: Mosa (2025) proposed a knowledge graph–transformer framework for narrator resolution in hadith networks. This paper inverts that direction: rather than applying AI to hadith, it extracts hadith’s operational protocol and applies it to AI systems. The paper borrows the methodological architecture and takes no position on theological authentication.

2.3 Multi-agent knowledge systems and the provenance state of the art

The system class motivating this work is the LLM-maintained, compiled knowledge base: rather than re-deriving answers from raw documents per query (retrieval-augmented generation), an LLM continuously compiles sources into a structured, interlinked wiki, resolves contradictions once, and serves cited answers from the compiled artifact — a pattern recently popularized by Karpathy’s “LLM Wiki” sketch [Karpathy 2026] and related to persistent agent-memory systems [Chhikara et al. 2025]. In such systems every compiled claim is the product of a multi-step agent pipeline, which makes claim-level trust both more important and more tractable: the transformation points are known and instrumentable.

Provenance research for LLM agents has advanced rapidly. PROV-AGENT extends the W3C PROV model [Moreau et al. 2013] to capture agent interactions in agentic workflows [Souza et al. 2025]; Agent-Sentry bounds agents via execution provenance [Sequeira et al. 2026]; and a recent survey organizes the field around *evidence tracing* and *execution provenance* [arXiv:2606.04990]. In parallel, claim-level factuality work — FActScore’s atomic-claim decomposition [Min et al. 2023], the FEVER and VitaminC verification benchmarks [Thorne et al. 2018; Schuster et al. 2021] — grades claims against evidence at a point in time. Knowledge-conflict studies show that LLMs handle contradictory evidence poorly: they struggle to represent, surface, or reconcile competing claims [Su et al. 2024; Hou et al. 2024; Wu et al. 2024], and multi-agent failure taxonomies attribute many system failures to weak verification between agents [Cemri et al. 2025]. ContraCrow demonstrates LLM-driven contradiction detection against scientific literature at scale [arXiv:2409.13740].

A third, adjacent stream applies computation *to* hadith grading itself: classifiers that sort narrations into ṣaḥīḥ/ḥasan/ḍa‘īf/mawḍū‘ from chain and text features [Ramzy et al. 2023], narrator-name

extraction and chain datasets [Mghari et al. 2022], and — most relevant here — Hawramani’s *HadithRank*, which models an isnād’s topology using information theory, treating independent transmission chains as redundant channels whose combined error probability falls as p^n with n independent chains [Hawramani]. HadithRank is notable because it independently formalizes, inside the hadith domain, the same epistemic principle this paper’s corroboration rule (§4.3) relies on: independent chains multiply reliability. That a mathematician grading hadith and this paper grading agents converge on the same redundancy rule is evidence the mapping is structural, not decorative. The direction, however, is opposite: that stream brings computation *to* hadith; this framework brings hadith methodology *to* computational systems.

A parallel body of work studies computational trust itself rather than provenance. Subjective-logic trust models, reputation systems for multi-agent environments, truth-discovery algorithms, and recent credibility-scoring methods for LLM-based agents estimate the reliability of entities, sources, or claims through probabilistic updating, consensus, or historical behavior. These approaches address important aspects of trust calibration, but they generally do not couple trust estimation to explicit claim-level transmission chains, graded transformer registries, and an interaction between transmission quality and independent content criticism. Rather than replacing these approaches, the framework proposed here is complementary: it specifies an architectural protocol for how trust should propagate through multi-agent knowledge transmission. Recent work has continued this trajectory. Ebrahimi et al. (2025) introduced credibility scoring for adversary-resistant multi-agent LLM systems, learning agent trustworthiness from past contributions. RAPS (2026) proposed a reputation-aware publish-subscribe framework with Bayesian reputation overlays for LLM coordination. TrustTrade (2026) replaces “uniform trust” — the observed tendency of LLMs to treat heterogeneous sources identically — with cross-agent consistency weighting. Prakash (2026) identified the “Provenance Paradox”: when delegates can inflate self-reported quality, quality-based routing can perform worse than random.

The gap. The provenance and factuality lines record chains, verify claims against evidence, and detect conflicts, but none maintains a *graded registry of the transmitters themselves* with a defined update process, aggregates chain trust by a weakest-link rule with a corroboration escape hatch, or defines the interaction between chain quality and content criticism. The AI-for-hadith line has formalized narrator grading and chain redundancy, but for authenticating historical texts, not for governing live multi-agent knowledge pipelines. Combining a graded transmitter registry, weakest-link-plus-corroboration aggregation, chain completeness as an epistemic property, and a chain-quality $\times$ content-criticism decision procedure — as an operational framework for AI systems — is the contribution rijāl methodology makes here.

3. Threat model and scope

The framework targets *epistemic* degradation in cooperative pipelines: extraction errors, model hallucination during compilation, stale or unreliable sources, silent quality drift across model versions, and unresolved contradictions between sources. It also covers one adversarial case natively: a source that attempts prompt injection is, in rijāl terms, a narrator whose ‘adālah is compromised — and memory/knowledge-base poisoning attacks against agents are an active threat [Chen et al. 2024].

Out of scope: Byzantine collusion among agents (cf. Lamport, Shostak & Pease, 1982), cryptographic attestation of traces (complementary; see [Sequeira et al. 2026]), and fairness questions

raised by grading *human* contributors, which I flag in §7 rather than resolve. Also out of scope by construction is open-ended or creative generation: ISNAD grades claims that can, in principle, be true or false and checked against a corpus. It is a framework for knowledge accumulation, not for tasks where there is no fact of the matter to transmit. A further limitation of scope, discussed in §7, is that the framework as specified assumes claims with determinate truth values; claims that are inherently probabilistic or provisional require an extension not developed here.

4. The Isnād–Rijāl Framework

4.0 Design principles

Before presenting the framework’s mechanisms, it is useful to state the principles that govern every design choice. These are not additional components; they summarize the epistemic commitments inherited from the isnād–rijāl methodology and guide the architecture that follows.

1. **Every claim carries its transmission chain.** Every factual assertion must retain an explicit record of the transformations through which it reached the knowledge base.
2. **Every transmitter maintains an evolving reliability record.** Sources, agents, models, and human contributors accumulate evidence over time, allowing their reliability to improve or degrade as new observations arrive.
3. **Chain trust is bounded by its weakest verified transformation.** Trust cannot exceed the least reliable verified step in a chain, except where justified by independent corroboration.
4. **Independent corroboration increases justified confidence.** Multiple genuinely independent chains strengthen confidence in a claim without eliminating the need for critical evaluation.
5. **Transmission quality and content quality are evaluated independently.** A trustworthy chain does not guarantee a correct claim, and a correct claim does not compensate for an unreliable transmission history.

4.1 Narrators and chains

A **narrator** is any entity that originates, transforms, or transmits a claim: an external source, a scraper version, an ingestion model at a specific version and prompt revision, an answer model, or a human contributor. An **isnād** for claim *c* is the ordered, gap-free sequence of narrators from origin to the point of serving, each link carrying timestamp, version identifiers, and trace references.

Two rules follow directly from classical practice.

Completeness (ittiṣāl). A claim whose chain has a missing segment — a transformation not captured in traces — is *munqaṭiʿ* and automatically capped at the weak tier, regardless of how reliable the recorded narrators are. This makes trace completeness a first-class epistemic property rather than an operational nicety.

Weakest link. A single chain’s grade is the minimum grade over its narrators. A frontier synthesis model at the end of a chain cannot repair a compromised extraction at the start of it — a property that current confidence-scoring practice, which often reflects only the final model’s self-assessment, does not have.

This rule needs one refinement to hold for AI pipelines rather than human ones. In hadith transmission, a weak link is unconditionally corrupting: a narrator with poor memory irreversibly degrades

the text passing through them. AI transformations are not all alike. A *destructive* transformation — extraction, chunking, lossy summarization — can only lose or corrupt information, and there the strict minimum applies: nothing downstream recovers what the extractor dropped. A *generative* transformation — synthesis by a model with broad pre-training — can either repair upstream noise or introduce fresh corruption by favoring its parametric prior over retrieved evidence when the two conflict, a behavior documented in ClashEval (Wu et al., 2024). For generative steps the rule is therefore not a blind minimum but a *bounded* one: a generative narrator can raise the floor only up to its own grade and only when corroboration supports the repair, and it can always lower it.

This mirrors a distinction the muḥaddithūn themselves drew between riwāya bi-l-lafz (transmission of exact wording) and riwāya bi-l-ma‘nā (transmission by meaning): meaning-transmission, where the narrator reconstructs rather than copies, was held to a different and often stricter standard precisely because the transmitter’s own competence now enters the chain. Destructive steps take the strict minimum; generative steps take a bounded, corroboration-gated adjustment. The weakest-link principle survives; it is refined by transformation type.

Repeated narrators. One edge case deserves explicit treatment. If the same narrator appears twice in a chain, a naive minimum returns that narrator’s grade unchanged — yet two passes through the same lossy transformation are strictly worse than one. A faithful implementation should treat repeated traversal of a destructive narrator as compounding rather than idempotent, and should additionally treat the repetition as evidence against independence when the chain is later considered for corroboration (§4.3). The reference implementation records repetition but does not yet penalize it; this is a known gap.

4.2 The narrator registry and al-jarḥ wa-l-ta‘dīl

The **narrator registry** is the system’s rijāl compendium: one row per narrator, carrying type, version, and grade. Grades are **ordinal first, numeric second**: narrators are placed in tiers (reliable/acceptable/weak/rejected), with numeric error rates attached only where calibration data exists. This ordering matters — classical rijāl grading was categorical precisely because false numeric precision invites misplaced confidence, and a registry populated with uncalibrated decimals would reproduce that failure.

The registry is updated through a defined process — the computational jarḥ-ta‘dīl loop. This is a state machine, not a formula. Each narrator occupies an ordinal state (reliable → acceptable → weak → rejected), and transitions are driven by named evidence types: per-narrator evaluation harnesses (extraction fidelity for scrapers, task-specific accuracy for models), post-hoc audits of served claims, corroboration and contradiction outcomes, and human review verdicts. A downgrade fires when accumulated adverse evidence crosses a threshold; an upgrade requires sustained corroborated accuracy.

The paper deliberately does *not* fix the exact transition arithmetic — the sliding window, the update rule, the specific thresholds — as a first-class part of the framework. This is a considered choice, not an omission: a protocol specifies its state space and transition triggers and leaves tuning constants to implementations, exactly as the W3C PROV data model [Moreau et al. 2013] defines provenance structure without dictating how systems compute trust over it, and as transport protocols define state transitions without fixing congestion-control constants. Committing to a specific update formula with no deployment data to calibrate it would manufacture false precision of exactly the kind the framework is built to avoid. §8.6 reports what happens when the reference policy is swept, and the answer — that the choice materially changes both coverage and grade recovery — is itself

an argument for leaving it open.

A model-version bump resets a narrator to ungraded until re-evaluated: version drift is treated as a new narrator, not an inherited reputation. Because grading is domain-conditioned (below), a version bump resets grades per domain as evaluation data arrives, rather than all at once. This mechanism has a known blind spot: a hosted model whose weights change without a version-string change will silently retain a grade it no longer merits. Deployments against third-party APIs should therefore treat scheduled re-evaluation as mandatory rather than relying on version signals alone.

‘Adālah and ḍabt map onto distinguishable properties. Ḍabt — precision — is the measurable error rate. ‘Adālah — integrity — covers manipulation-resistance: whether a source domain is reputable, whether a scraper fences untrusted content against prompt injection, whether a human contributor’s submissions have survived verification. The mapping is imperfect (§7): models are stochastic artifacts, not moral agents. But the *functional* distinction — “does this narrator make honest mistakes, or can it be made to lie?” — carries over cleanly, and it is a distinction current provenance schemas do not draw.

Grading is domain-conditioned, not global. A model’s reliability is not a single number. An LLM’s error rate varies sharply with the semantic domain of the task — a model precise on historical dates may be unreliable on quantum-mechanical equations — and even varies run to run under fixed settings. A single global grade per narrator would therefore be a naive point estimate of a distribution that does not exist as a scalar. The framework grades each narrator *per domain*: the registry key is (narrator, domain), not narrator alone. This is not a concession forced by the peculiarities of LLMs; it is a return to classical practice. Rijāl scholars graded transmitters domain-specifically as a matter of course — a narrator could be judged reliable (thiqah) in the hadith of one teacher and weak in another’s, precise in law and unreliable in history. The discipline never assumed a transmitter was uniformly reliable across all material, and neither should a system grading models.

Domain-conditioned grading carries an operational cost that §8.2 makes concrete: it multiplies the number of registry cells that must be filled, and a narrator that is rare within a given domain may never accumulate enough evidence to be graded at all.

4.3 Corroboration (mutāba‘āt)

The weakest-link rule alone would be too conservative: much useful knowledge arrives through imperfect chains. Classical methodology solves this with corroboration: a claim carried by k independent chains — chains sharing no narrators — may be upgraded. Computationally: same normalized claim, disjoint narrator sets, independent sources.

Two constraints keep this from becoming an unbounded trust-inflation loop. First, the upgrade is *capped* — corroboration can raise a claim toward but not past the sound tier, and it cannot manufacture trust from chains that are all weak: some corroborating chain must itself clear a minimum grade. Second, the exact aggregation is, like the jarḥ-ta’dīl transition function (§4.2), a deliberately open implementation parameter. The ordinal-first commitment governs what the system *reports* (tiers, not false-precise decimals); it does not forbid an implementation from computing tier upgrades numerically under the hood. HadithRank’s information-theoretic model — combined error probability falling as roughly p^n across n independent chains [Hawramani] — is precisely one such numeric instantiation, developed independently inside the hadith domain.

The framework specifies the *rule* (independent chains upgrade, capped, gated on a minimum grade)

and leaves the *arithmetic* to implementations. This gives the framework the redundancy epistemics that single-chain confidence scores lack, and it creates the right incentive at the system level — breadth of independent sourcing, not repeated re-ingestion through the same pipeline. The design parallels Condorcet’s insight (1785) that independent agreement reduces error and Shafer’s evidence combination (1976), with HadithRank as the within-domain instantiation.

The word doing the most work in this rule is *independent*, and §7 returns to how easily it can be overstated.

4.4 Dual criticism and the decision matrix

The chain grades the *transmission*; matn criticism grades the *content* — in a compiled knowledge base, contradiction detection against the existing corpus at ingest time. The two verdicts interact according to a decision matrix, which is the framework’s most directly actionable artifact.

	Matn: consistent	Matn: contradiction	Matn: unverifiable
Ṣaḥīḥ-tier chain (complete; all narrators graded reliable)	Serve directly; cache	ʿIlal flag → human review. Highest-value review case.	Serve with caveat
Ḥasan-tier chain (complete; ≥1 narrator ungraded or mid-tier)	Serve with explicit confidence caveat; seek corroboration	Hold in review queue; do not serve	Hold in review queue
Ḍaʿīf-tier chain (weak narrator, or munqaṭiʿ)	Hold; seek corroborating chain before serving	Quarantine	Hold in review queue
Mawḍūʿ-tier chain (rejected narrator — e.g. known injection source)	Reject and log; quarantine the narrator	Reject and log; quarantine the narrator	Reject and log; quarantine the narrator

Table 2: The decision matrix. Chain grade (rows) × content-criticism verdict (columns) → action.

The third column is not a formality. Content criticism is a partial function: a critic that cannot evaluate a claim must be able to say so rather than defaulting to “consistent.” Unverifiable is the classical position of tawaqquf — suspension of judgment — and routing it conservatively is what makes the framework safe under a weak critic. It is also, as §8.6 shows, the binding constraint on practical coverage: with a critic that returns unverifiable on most real prose, ḥasan-tier claims cannot graduate to serving, and coverage is capped at the review budget regardless of how well chain grading performs. A framework that omitted this column would look far more capable on paper and behave far worse in deployment.

Three design defaults embedded here deserve emphasis.

First, **contradictions are adjudicated by humans by default** — the muḥaddith role. This is not conservatism for its own sake: knowledge-conflict research consistently finds LLMs unreliable at representing and reconciling competing evidence [Su et al. 2024; Hou et al. 2024; Wu et al. 2024], and during development of the prototype described in §6, early evaluations found that LLM synthesis handled contradiction cases *worse* than an extractive baseline until contradiction markers were made explicitly visible in context — after which auto-resolution was still disabled in favor of

gated review. The classical discipline reached the same conclusion about hard cases a millennium earlier: they go to the expert.

Second, the ṣaḥīḥ-chain-with-contradiction cell is the system’s most informative signal, not an error state — it is where either a trusted source has changed the world’s state or the corpus contains a latent defect, and both are exactly what a self-maintaining knowledge base exists to catch.

Third, the mawḍū‘ tier is the framework’s native defense against knowledge-base poisoning. Adversarial prompt-injection and memory-poisoning attacks against agents are an active and demonstrated threat [Chen et al. 2024]: a compromised source or a manipulated agent is, in rijāl terms, a fabricator — a narrator whose ‘adālah has failed. Grading narrators for integrity, not merely precision, means the framework quarantines a source that attempts injection rather than merely noting low confidence in its output. The rejected tier is thus an active containment action, and it connects claim-level provenance directly to the AI-security literature on agent poisoning.

4.5 A worked example

Consider the claim “*the momentum of a photon is $p = h/\lambda$* ”, ingested from an openly licensed physics text.

Chain: [OpenStax University Physics Vol. 3 (source; publisher-trusted, ‘adālah high)] → [pdf-scraper v1.2 (ḍabṭ graded: high extraction fidelity on text-layer PDFs)] → [ingest-analysis model $M@v$ (ungraded — recent version bump)] → [ingest-renderer $M@v$ (ungraded)].

Chain grade: complete (ittiṣāl holds), but two narrators ungraded → ḥasan-tier by the weakest-link rule.

Matn criticism: the corpus already contains a page asserting momentum as $p = mv$ without regime qualification. Contradiction detected.

Matrix cell: ḥasan × contradiction → review queue; do not serve.

Adjudication: a human reviewer recognizes both claims as valid in different regimes — classical and quantum — and updates both pages with regime qualifiers, resolving the contradiction *once, at ingest time*, rather than leaving every future query to renegotiate it. The resolution event feeds back: the ingestion model’s contradiction-detection behavior on this case becomes ta’dīl evidence toward its grade; both claims’ chains record the adjudication.

This is the framework operating end to end: chain capture, weakest-link grading, dual criticism, matrix-routed action, registry update. It is implemented as a runnable example and an integration test in the reference implementation.

4.6 What rijāl adds over existing provenance

Compressed to its differences from the state of the art [Souza et al. 2025; arXiv:2606.04990; Moreau et al. 2013], the contribution is a package of five interlocking mechanisms. Table 3 anchors each to its strongest ancestor.

Table 4 states the same comparison as capability coverage. The columns are defined narrowly: *chain capture* means claim-level transmission chains are recorded per claim; *graded transmitters* means each transformer carries a maintained reliability grade; *content criticism* means content is evaluated independently of chain quality; and *decision routing* means the system emits a concrete

Mechanism	Strongest ancestor	What ISNAD adds
Chain aggregation	Jøsang subjective logic (2001) — trust discounting along chains	Transformation typing (riwāya bi-l-lafz vs. bi-l-ma‘nā); completeness semantics
Source registry	Truth discovery (Yin et al., 2008; Dong et al., 2014) — source reliability estimation	Per-domain grading; version-bump resets; quarantine lifecycle
Content criticism	FEVER-style fact-checking	Decoupled from chain quality; operates on matn independently; explicit unverifiable verdict
Agent grading	MAS reputation (EigenTrust, ReGreT, FIRE)	Claim-level provenance, not just partner selection
Decision routing	— (no direct ancestor)	Chain grade $\times$ content verdict $\rightarrow$ concrete serve/review/quarantine action

Table 3: Each mechanism against its strongest existing ancestor.

serve/review/quarantine action. A mark indicates that the approach addresses that capability as a first-class concern, not that competing systems could not be extended to it.

Approach	Chain capture	Graded transmitters	Content criticism	Decision routing
W3C PROV / PROV-AGENT	yes	no	no	no
Truth discovery (TruthFinder, KBT)	no	yes	partial	no
MAS reputation (EigenTrust, ReGreT)	no	yes	no	partial
FEVER-style fact-checking	no	no	yes	no
ISNAD	yes	yes	yes	yes

Table 4: Capability coverage across approaches, under the narrow column definitions given above.

Individually these are implementable engineering choices; as a package they constitute a coherent trust methodology grounded in principles refined over centuries of hadith scholarship.

5. Reference schema

The framework’s data model is concrete and implementable independent of any particular host system. It requires only two properties of whatever pipeline it instruments: that each claim-transforming step emits a trace identifier, and that the system maintains a compiled knowledge artifact rather than re-deriving answers per query. Given those two properties — which hold for the compiled-wiki class of systems generally [Karpathy 2026] — the framework is expressed in two tables:

```
CREATE TABLE rijal_claims (
  claim_id      TEXT PRIMARY KEY,    -- hash of normalized claim text
  page_slug     TEXT NOT NULL,
  claim_text    TEXT NOT NULL,
  narrator_chain JSONB NOT NULL,     -- [{step, narrator_id, version,
                                     --   confidence, trace_id, ts}]
```

```

    chain_confidence NUMERIC(4,3),      -- min over links; NULL until graded
    valid_from       TIMESTAMPTZ,
    valid_until      TIMESTAMPTZ,      -- lifecycle: supersession, not deletion
    superseded_by    TEXT,
    chain_status      TEXT DEFAULT 'active'
);

CREATE TABLE narrator_registry (
    narrator_id      TEXT NOT NULL,      -- e.g. 'pdf-scraper', 'ingest:M@v'
    domain_tag       TEXT NOT NULL,      -- grading is per (narrator, domain)
    narrator_type     TEXT NOT NULL,      -- source | scraper | model | human
    grade            TEXT NOT NULL,      -- reliable|acceptable|weak|rejected
    known_error_rate NUMERIC(4,3),      -- NULL = uncalibrated
    model_version     TEXT,
    is_active        BOOLEAN DEFAULT TRUE,
    PRIMARY KEY (narrator_id, domain_tag)
);

```

Because the pipeline’s transformation points already emit trace identifiers, populating `narrator_chain` is an instrumentation task, not an architectural change. This is the practical argument for reserving the schema early: retrofitting claim-level chains onto a live corpus requires re-deriving provenance that was never captured, whereas capturing it at each transformation is nearly free once the trace points exist.

Implementation status. The schema, its dataclasses, the lifecycle columns, and the five core components — registry, chain engine, weakest-link evaluator, corroboration, and matn criticism — are implemented, migration-tested, and released as an open-source reference implementation with a passing test suite (§8.7). What has been exercised end to end is the offline evaluation pipeline of §8: chains are constructed, graded, routed through the decision matrix, and audited. What has *not* been demonstrated is a live production deployment in which chains are written automatically at ingest and the registry gates a serving path under real query load. §6 and §8 should be read accordingly.

6. Case study: the matn-criticism substrate on real texts

The decision matrix (§4.4) is only useful if its column variable — contradiction detection at ingest — actually fires on real, uncurated material. To test this, a prototype compiled-wiki system ingested openly licensed undergraduate physics texts: OpenStax *University Physics* volumes 1–3 [Ling, Moebs, Sanny] and Crowell’s *Light and Matter* series, via chunked PDF extraction (approximately 15K characters per chunk) through a pipeline instrumented with the schema above (DeepSeek-chat as the ingestion model; single run).

Physics textbooks are a deliberately chosen stress case: the same concepts — momentum, energy, light — receive genuinely different treatments across classical, electromagnetic, relativistic, and quantum frameworks. These are not fixture contradictions written to be found; they are real epistemic tensions native to the source material.

Result. The analysis step surfaced **19 contradictions across the corpus, each manually reviewed and confirmed genuine** — among them: classical momentum ($p = mv$) versus photon momentum ($p = h/\lambda$); wave versus particle treatments of light; Newtonian versus relativistic

kinematics. Four contradiction markers were injected into three compiled pages, and four items were routed to the human review queue by the severity gate, exercising the ‘ilal path of the matrix on real content.

Reproducibility caveat. The prototype in which this case study was run is a proprietary system and is not part of the open-source release. Unlike the §8 experiments, these 19 contradictions are reported as an observational case study and are not independently reproducible from the public repository. They are included because they motivated the framework’s content-criticism column and because they demonstrate the substrate on genuinely uncurated material, not as formal evidence.

Two kinds of contradiction. A distinction matters here that the raw count obscures. A *Type A* contradiction is an error: one of the two claims is simply wrong, and resolution means correction. A *Type B* contradiction is a regime distinction: both claims are true within their respective domains of validity, and resolution means qualification. All 19 contradictions surfaced here are Type B — $p = mv$ and $p = h/\lambda$ are each correct in their regime, and the reviewer’s job is to add regime qualifiers rather than to correct an error. This validates the detection substrate and the routing path, but it does not demonstrate error-correction capability. An experiment with deliberately injected Type A errors — wrong constants, swapped equations, sign flips — would test that, and §8 supplies the closest available analogue by injecting synthetic faults into a corpus of known-correct text.

A traced example. To show how a detected contradiction maps into the schema, consider one of the 19. The claim “*a photon carries momentum $p = h/\lambda$* ” is ingested from *University Physics* Vol. 3. Its `rijal_claims` row records the chain [{source: openstax-v3, domain: physics-quantum}, {narrator: pdf-scraper@1.2}, {narrator: ingest:M@v, domain: physics-quantum}]; `chain_status` = active; `chain_confidence` = NULL (registry not live in this run). The analysis step’s contradiction field names a conflict with the existing claim “*momentum $p = mv$* ” (from Vol. 1, domain: physics-classical). Under the decision matrix this is a chain-complete-but-ungraded (ḥasan-default) row meeting a detected contradiction → routed to the review queue, not served.

Had the registry been live and both ingest steps graded reliable *in the physics-quantum domain*, the same row would sit in the ṣaḥīḥ × contradiction cell — the ‘ilal signal — flagging that two regime-specific claims coexist and need regime qualifiers rather than one overwriting the other. This is the difference the framework adds: without narrator grading, a contradiction is merely a conflict to resolve; with it, the chain quality of each conflicting claim tells the reviewer which to trust more, and whether the conflict signals a defect or a genuine regime distinction.

On precision and recall. The reported figure is a *precision* result: of the contradictions the pipeline surfaced, 19 of 19 were confirmed genuine on manual review — no false positives in this run. *Recall* is deliberately not claimed. Measuring it would require a ground-truth set of every genuine contradiction across three physics textbooks, which does not exist and whose construction is a research project in its own right. A reader should read “19 contradictions found” as “at least 19 genuine contradictions exist and were caught,” not as “exactly 19 exist.”

Parametric knowledge confound. The ingestion model possessed substantial parametric knowledge of undergraduate physics before ingesting the corpus. A detected contradiction could in principle arise from the model’s pretrained knowledge rather than from information extracted from the ingested documents. During manual verification, every reported contradiction was confirmed to correspond to explicit statements present in the ingested textbook chunks rather than unsupported model recall. However, this experiment does not isolate the relative contributions of retrieved evidence and parametric knowledge. A stronger evaluation would compare identical pipelines with

retrieval disabled, or use models lacking relevant domain pretraining.

What this does and does not show. It shows the substrate works: an LLM ingestion pipeline can detect cross-framework contradictions in real, uncured texts with high precision, at a volume sufficient to feed the matrix’s content-criticism column, and severity gating can route them to human adjudication. It does not show that narrator grading improves outcomes — the registry was not live, so all chains were effectively ungraded. It is a single run with a single model on one domain, reported as a case study, not a benchmark. §8 supplies the controlled evaluation.

7. Limitations and ethical considerations

The analogy has edges. Classical narrators were moral agents whose ‘adālah was a judgment of character formed over a lifetime; models are stochastic artifacts whose “integrity” is an engineering property of their deployment (fencing, sandboxing, source policy). The mapping is functional, not metaphysical, and I do not claim otherwise. Similarly, classical grading rested on scholarly consensus formed over generations; a registry populated by one team’s evaluations is a far thinner epistemic base, and its grades should be presented with corresponding humility.

Non-stationarity, and why it vindicates ordinal grading. Model reliability is not stable: error rates shift with prompt framing, context crowding, and domain, and outputs vary run to run even at temperature zero. This is a real objection to any scheme that stores a single scalar reliability per model — and it is precisely why this framework grades ordinally and per domain rather than as a global decimal (§4.2). A point-valued `known_error_rate` treated as ground truth would misrepresent a quantity that is genuinely a domain-conditioned distribution; an ordinal tier, refined by continued evidence, is the honest representation. The non-stationarity of LLM narrators does not break the framework; it is the strongest argument for the anti-false-precision principle the framework already insists on. It does raise the cost of the jarḥ-ta’dīl loop — grades must be maintained per domain and revisited on drift — which §8.2 shows is not merely a cost but a failure mode.

Registry cold start. Weakest-link grading with an empty registry caps everything at ḥasan-tier or below. This is arguably correct behavior — new pipelines *should* earn trust — but it front-loads human review cost, and the framework’s practical value depends on the jarḥ-ta’dīl loop converging faster than review budgets exhaust. The intended mitigation is *bootstrapping*, and here the classical discipline is instructive: a new scholar did not begin from zero but inherited the tradition’s accumulated biographical evaluations. Computationally, narrators can be pre-graded before deployment from evidence that already exists — a model’s published benchmark accuracy seeds its ḍabt grade; a source domain’s reputation seeds its ‘adālah grade; a scraper’s extraction-fidelity test suite seeds its precision grade. §8.6 reports how far this mitigation actually goes, which is less far than this section originally anticipated.

Grading humans. Where human contributors are narrators, the registry becomes a reputation system over people, with the fairness, contestability, and workplace-power questions that implies. I flag this as requiring governance design — contestable grades, transparent criteria — rather than resolving it here.

False precision. `chain_confidence` as a decimal invites over-trust. The ordinal-first principle (§4.2) is the mitigation; implementations that surface raw numbers to end users without tier context would be misusing the framework.

The independence of corroborating chains is an idealization. The corroboration rule (§4.3) assumes chains with disjoint narrator sets are independent. In practice two chains may share no explicit narrator yet still fail together — if both terminate in the same answer model, or in different models drawn from a family with correlated training data and therefore correlated blind spots. Classical scholars faced a structurally identical problem in the *madār* (the pivot narrator through which ostensibly independent chains converge), and treated such convergence as reducing, not confirming, independence. A faithful implementation must likewise detect correlated narrators — shared model family, shared upstream source — and discount their corroboration accordingly. Naive set-disjointness will over-credit correlated chains. The reference implementation enforces an independence check on narrator identity, model family, and upstream source, and §8.5 reports how that check behaves; but a genuinely correlated pair that shares none of those three attributes would still pass, and content-level correlated error — two independent sources repeating the same received mistake — is not addressed at all.

Probabilistic and provisional claims. The framework as specified assumes claims with determinate truth values. A claim such as “the Higgs boson mass is 125.1 GeV” carries an implicit uncertainty interval, and a claim reported as a current best estimate may be superseded without either version having been wrong. Contradiction detection between a point estimate and an interval, or between two overlapping intervals, is not defined by the *matn*-criticism step as described. The lifecycle columns in the schema (*valid_from*, *valid_until*, *superseded_by*) provide a mechanism for supersession but not a semantics for uncertainty. Extending the framework to probabilistic claims is future work.

Storage and query overhead. Attaching a chain to every claim and consulting a registry at serve time has a cost, but the scale is modest by construction: chains are short (typically three to five links — source, scraper, ingest, answer), so a per-claim JSONB chain is small and bounded; the narrator registry holds one row per agent *version and domain*, not per claim, so it grows with pipeline changes rather than with corpus size. Standard JSONB indexing supports the queries the gate requires. At the sizing this framework targets — knowledge bases of thousands to low millions of claims — neither table is expected to be a bottleneck. Deployments at far larger scale would want to normalize chains into foreign-keyed link rows rather than JSONB and to cache registry lookups. These are design expectations rather than measured results: no latency or storage benchmark was run, and none is claimed.

Positionality and religious respect. I am a Muslim practitioner and builder; Islam & AI, a Quranic NLP platform I founded, is where I first worked seriously with these scholarly traditions. This paper adapts a *methodology* developed by hadith scholars; it makes no religious claims, issues no rulings, and does not position any computational system as an authority within the religious sciences themselves. The direction of intellectual credit should be unambiguous: the framework’s rigor belongs to twelve centuries of *muḥaddithūn*; the transfer to AI systems is the contribution claimed here. I would welcome collaboration with hadith-studies scholars to correct any misrepresentation of the classical discipline.

8. Evaluation

This section reports an evaluation of the framework on 20,000 claims extracted from real undergraduate physics textbooks. Two mechanisms are validated, one partial failure is reported, and two analyses are reported as inconclusive.

8.1 Protocol

Status of the protocol. The analysis protocol — hypotheses, metrics, conditions, and decision rule — was written before the experiment was run and is preserved verbatim in the repository as `ANALYSIS_PLAN.md`, together with a dated log of deviations made during execution. It was committed to the public repository alongside the first result artifacts rather than in advance of them. The commit history therefore establishes the plan’s content but not its timing, and readers should treat it as a pre-committed analysis plan rather than as third-party preregistration. What *is* independently verifiable is the leakage firewall: the injection manifest lives in a dedicated module that an enforced test forbids any grading, gating, or routing code from importing. That test is part of the passing suite.

Corpus. 20,000 atomic claims were extracted from real PDF text of OpenStax *University Physics* Volumes 1–3 (CC BY 4.0) and Crowell’s *Light and Matter* (CC BY-SA), split evenly, 10,000 per source. Claims were assigned domain tags: mechanics (7,600), general (6,890), electromagnetism (3,054), modern-quantum (1,728), and optics-waves (728). Extraction used `deepseek-chat` over chunked PDF text. Claims were split 30% calibration / 70% evaluation, giving 14,001 evaluation claims, across 10 random seeds for narrator assignment and fault injection.

Narrator pipeline and fault injection. Each claim was assigned one scraper variant and one ingest variant uniformly at random. Four narrators were configured with distinct designed fault rates: `pdf-scraper@1.2` (1%), `ingest@good` (2%), `ingest@weak` (15%), and `pdf-scraper@0.9-legacy` (18%). Faults are deterministic rule-based corruptions applied per seed: OCR noise, digit swap, sign flip, negation drop, unit corruption, formula mangling, entity swap, fabricated numerics, and regime confusion. Approximately 5% of chains were marked incomplete to exercise the `munqatir` path.

Definitions. These two terms carry the results and are used precisely.

Error. A served claim counts as an error if its text was altered by fault injection, per the manifest. These are synthetic corruptions of correct source text, not naturally occurring factual errors in the textbooks. The evaluation therefore measures whether the framework blocks known-corrupted transmissions, not whether it can adjudicate genuine physics disputes.

Coverage. The fraction of evaluation claims the decision matrix routes to serve or serve-with-caveat. Claims routed to review beyond the review budget, and claims quarantined, are not served and do not count toward coverage.

Conditions. Four serving conditions were evaluated at review budgets $B \in \{2\%, 5\%, 10\%, 20\%\}$: ungated serving with random review; confidence-gated serving; ISNAD-gated serving (chain grading $\rightarrow$ matn criticism $\rightarrow$ decision matrix $\rightarrow$ prioritized review queue); and ISNAD-gated with corroboration disabled. A simulated perfect reviewer resolves reviewed claims correctly, so review-queue precision is the realistic cost metric.

One condition could not be evaluated. The corroboration ablation requires claims asserted by two independent chains. On this corpus, cross-source overlap after normalization was too sparse to exercise it, and the ISNAD and ISNAD-without-corroboration conditions produced identical results across all seeds. The corroboration mechanism is therefore evaluated separately, on corpora selected for cross-source redundancy (§8.5), rather than within this experiment.

8.2 Validated: weakest-link quarantine, and a partial failure of grade recovery

The weakest-link mechanism performed as specified. Every claim whose chain contained a narrator graded rejected was quarantined — 4,057 claims, 29% of the evaluation split — and every quarantine was traceable to the specific narrator grade that caused it. A representative trace:

Step 0: source:openstax	RELIABLE	
Step 1: pdf-scraper@1.2	RELIABLE	[DESTRUCTIVE]
Step 2: ingest@weak	REJECTED	[GENERATIVE] <- binding link
Chain grade: MAWDU -> REJECT_AND_QUARANTINE_NARRATOR		

Full traces for all quarantined claims are in the repository.

The jarḥ-ta’dil loop recovered three of four narrator grades from audit evidence alone. `pdf-scraper@1.2` (1% designed fault rate) earned reliable in all 50 (narrator, domain) cells; `ingest@good` (2%) earned acceptable in all 50; and `ingest@weak` (15%) — the one narrator deliberately left ungraded before the run — was independently discovered and driven to rejected in 49 of 50 cells, weak in the remaining one. The registry recovered the designed reliability ordering for these three without access to the injection manifest.

The fourth narrator was not recovered, and the failure is instructive. The legacy scraper variant (`pdf-scraper@0.9`), carrying the *highest* designed fault rate in the experiment (18%), never accumulated enough claims in the calibration split to earn any grade in any domain, and remained ungraded throughout. It was in fact among the largest single sources of injected faults. The loop found the unreliable narrator it was given enough evidence about and silently missed the one it was not.

This is a genuine operational failure mode, and it is not the one §7 anticipated. Grade recovery is bounded by calibration *coverage* per (narrator, domain) cell, not only by the transition policy. Domain-conditioned grading (§4.2) multiplies the number of cells that must be filled, and a narrator that is rare within a domain is invisible to jarḥ-ta’dil regardless of how unreliable it is. Warm-start seed grading does not fix this: seeding assigns an initial grade but does not guarantee that subsequent evidence will arrive in sufficient volume per cell to revise it. A deployment should therefore monitor per-cell evidence counts as a first-class operational metric and treat a persistently under-evidenced cell as a risk, not as a neutral absence.

8.3 The confidence baseline is uninformative by construction

A confidence-gated condition was included to represent current practice, in which routing is driven by a model’s self-reported confidence. In this experiment that baseline performs at chance — but for a reason that sharply limits what can be concluded from it.

The corpus carries a `model_confidence` field computed at extraction time from surface features of the claim text — a base value keyed on whether the text contains a formula character, plus a deterministic hash term. It is assigned before fault injection and never updated afterwards. Confidence is therefore statistically independent of corruption by construction. Measured on the injection manifest, the point-biserial correlation between confidence and corruption is $r = 0.04$; mean confidence on corrupted claims (0.853) and clean claims (0.848) differ by less than one hundredth.

This is a floor, not a finding. It establishes that the ISNAD condition is not being measured against a baseline that trivially wins, and nothing more. No claim is made here about whether

real LLM self-confidence carries a defect signal. Testing that would require eliciting genuine self-assessments from a model on its own outputs, which this experiment does not do, and it remains an open question worth answering directly.

Prakash’s “Provenance Paradox” (2026) reports that self-reported quality scores can make routing worse than random when delegates are able to inflate them. That result is consistent with the design intuition behind ISNAD’s attested-reliability approach, and it is independent evidence for treating self-report with suspicion — but it is not a replication of anything measured here, and this paper does not present it as one.

8.4 Inconclusive: matched-coverage comparison

Comparing served-error rates across conditions operating at different coverage levels is not meaningful. A system that serves 5% of claims will trivially show lower error than one serving 100%, and reporting the two side by side would overstate the framework. The standard remedy in selective prediction is a matched-coverage comparison: sweep each condition’s operating point and compare served error at equal coverage. This analysis was specified in advance and attempted.

It could not be completed. With the reference content critic, ISNAD-gated serving could not be driven above 4.8% coverage at any review budget between 5% and 50%; the risk–coverage relationship is a single point rather than a curve. At every matched target — 20%, 30%, 50%, 70%, 90% — the confidence-gated condition reached the target and the ISNAD condition did not.

Target coverage	ISNAD coverage	ISNAD error	Baseline coverage	Baseline error
20%	4.8% (not reached)	0.0%	20.0%	15.1%
30%	4.8% (not reached)	0.0%	30.0%	15.8%
50%	4.8% (not reached)	0.0%	50.0%	16.3%
70%	4.8% (not reached)	0.0%	70.0%	16.0%
90%	4.8% (not reached)	0.0%	90.0%	16.1%

Table 5: Matched-coverage comparison. The ISNAD condition cannot reach any target above 4.8%, so no matched comparison is available; the rows are reported to show what was attempted and where it failed, not as an advantage.

The honest conclusion is stated plainly. This experiment establishes that ISNAD-gated serving admits no corrupted claims among those it serves. It does *not* establish that ISNAD outperforms the baseline at matched coverage, because it cannot reach matched coverage with the reference critic. The binding constraint is the content critic (§8.6), not the grading mechanism. Any future claim of a risk–coverage advantage requires a critic capable of returning a consistent verdict on real prose, and this paper makes no such claim.

8.5 Validated: corroboration across three corpora

The corroboration mechanism (mutāba‘āt, §4.3) was evaluated in three dedicated experiments of increasing difficulty. Because the physics corpus of §8.1 lacks sufficient cross-source overlap, corpora were selected for genuine cross-source redundancy.

Independence, and an honest ordering. v2 draws on English Wikipedia and Simple English Wikipedia. These have separate editorial communities and produce substantially different text, and matching was semantic rather than string-based, so corroboration is credited only when disjoint chains express the same meaning in different words. But they are both Wikimedia projects, and

	v1 (exact)	v2 (Wikipedia)	v3 (physics)
Matching criterion	exact string	cosine ≥ 0.75	cosine ≥ 0.80
Corpus	12 article intros	30 article pairs	2 textbooks
Sentences	215	10,544	22,372
Candidate pairs	136	662	104
Pairs evaluated	136	603	104
Match density	—	6.3%	0.5%
Corroboration fired	68/136	603/603	104/104
Negative controls	none run	8/8	none run
Independence basis	synthetic chains	separate editorial communities	different authors and publishers
Difficulty	easy	medium	hard

Table 6: Corroboration validation across corpora of increasing difficulty. In v2, semantic matching produced 662 candidate pairs; the cross-source phase was randomly subsampled to 500 pairs (fixed seed) for compute cost and combined with 103 cross-topic pairs, giving 603 evaluated. Fire rate is reported over evaluated pairs; the gap between 662 and 603 is subsampling, not failure. Negative controls were run only on v2.

Simple English articles are frequently written by simplifying their English counterparts. v2 should therefore be read as validating the *mechanics* of corroboration — that the system detects cross-source semantic overlap, applies the grade gate, respects the cap, and issues an upgrade — rather than as a clean test of the independence assumption.

v3 is the stronger independence test. OpenStax *University Physics* Vol. 1 and Crowell’s *Light and Matter* have different authors, different publishers, different decades, and different upstream domains, and the independence check scored them fully disjoint on narrator identity, model family, and upstream source. Volumes 2 and 3 were deliberately excluded because they share authors with Volume 1 and are therefore not independent of it. Formal textbook prose also yields far lower overlap density (0.5%) than encyclopedic paraphrase (6.3%), which makes v3 the harder corpus in both senses.

Negative controls. On v2, eight controls covering the cases where corroboration must not fire — no matching text, shared model family (the madār case), corroborators below the grade gate, a rejected base chain, the ṣaḥīḥ cap, shared upstream source, insufficient independent chains, and an empty corpus — all correctly produced no upgrade. **No negative controls were run on v3.** A 100% fire rate without a discrimination check is weaker evidence than the same rate with one, and the v3 result should be read with that in mind.

Match quality. Matched pairs were manually inspected. On v3, a 15-pair sample contained 87% genuine physics statements, 13% problem or exercise text, and no citation boilerplate. On v2, the corresponding sample rated 65% as clearly genuine factual overlap. Neither sample is large enough to support a precision estimate, and neither is presented as one.

A construction caveat. In both v2 and v3, the weak-tier baseline chain was created by assigning one ingestion narrator a weak grade, because the underlying sources are in fact high-quality. The experiment tests whether corroboration upgrades a weak chain when an independent chain corroborates it, which it did in every evaluated case. It does not test corroboration on chains that are weak for organic reasons.

8.6 Honest negatives: transition policy and the content critic

Two results limit the framework’s practical reach, and both are reported here rather than deferred.

The transition policy trades coverage against grade recovery. Sweeping the downgrade threshold of the reference transition policy shows the tradeoff directly:

Downgrade threshold	Coverage	Served error	Review precision	Grades recovered
3	7.1%	0.0%	0.11	2/4
6	9.4%	0.0%	0.15	2/4
10	10.0%	0.0%	0.11	1/4
15	10.0%	0.0%	0.13	0/4
25	10.0%	0.0%	0.13	0/4

Table 7: Transition-policy sweep. Looser thresholds buy coverage but degrade the registry’s ability to recover the designed reliability ordering.

Loosening the threshold raises coverage from 7.1% to 10.0% and then saturates, while grade recovery falls from 2 of 4 narrators to 0 of 4. There is no setting in this range that delivers both. This is a direct empirical argument for the position taken in §4.2 — that the transition function is a genuine implementation parameter requiring per-deployment calibration, not a constant the framework should fix — but it is also a limitation: the reference policy has no sweet spot on this corpus.

More audit evidence did not help. Increasing the per-cell audit budget did not improve coverage; it reduced it, from 10.0% at budgets of 10 and 20 audited claims to 5.9% at 40 and above. The default policy over-penalizes reliable narrators as evidence accumulates on small samples. This is transition-policy sensitivity, not a data-volume problem, and more calibration is not the remedy.

The content critic is the binding constraint. The reference content critic — which, despite being named for embeddings, scores word overlap with a negation heuristic rather than using semantic embeddings — catches only obvious contradictions and returns unverifiable on most real prose. Under the decision matrix (§4.4), a ḥasan-tier chain meeting an unverifiable verdict routes to review rather than serve. With most claims receiving that verdict, ḥasan-tier claims cannot graduate to serving, and coverage is capped at approximately the review budget regardless of how well chain grading performs. This single fact explains the coverage ceiling in §8.4 and the saturation in Table 7.

A separate evaluation of the reference critics on 20 labeled claims returned perfect precision and recall, but those contradictions were template-injected and built from patterns the critics already encode; the numbers overstate real capability and are not reported as evidence here. A semantic or LLM-backed critic is the single highest-value component for practical end-to-end coverage, and building one is the most immediate item of future work.

8.7 Reproducibility and availability

The reference implementation, the §8 experimental data, the analysis scripts, and the results are open source under Apache 2.0. The analysis plan and its deviation log are committed to version control. The test suite comprises 157 tests, all passing, including an enforced firewall test that prevents grading and routing code from importing the injection manifest, and an integration test that reproduces the worked example of §4.5 exactly.

The framework is installable via `pip install isnad`. The software is archived at <https://doi.org/10.5281/zenodo.21216873> and the paper record at <https://doi.org/10.5281/zenodo.21211290>. Source, corpus, and experiments are at <https://github.com/alizahidraja/isnad>.

Component	Status	What remains
Weakest-link grading and quarantine	Validated	—
jarḥ-ta’dīl grade recovery	Partial	Recovered 3/4; missed the highest-fault narrator through insufficient per-cell calibration evidence
Corroboration (mutāba’āt)	Validated	Negative controls on the physics corpus; organically weak chains
Confidence baseline	Not tested	Baseline is synthetic; real model self-confidence untested
Matched-coverage advantage	Inconclusive	Requires a critic that can reach matched coverage
Content criticism	Partial	Semantic or LLM-backed critic
End-to-end serving pipeline	Open	Live deployment at practical coverage

Table 8: Status of each mechanism: what the evaluation established, and what it did not.

The case study of §6 is the one exception: it was run on a proprietary prototype and is not reproducible from the public repository, as noted there.

9. Conclusion

The question of whether to trust transmitted knowledge did not originate with language models, and the most rigorous pre-modern answer to it did not originate in computer science. Hadith scholarship’s insight — grade the transmitters, demand complete chains, let the weakest link cap trust, allow independent corroboration to restore it, and criticize content independently of transmission — translates with surprising directness into the multi-agent knowledge pipelines now being built.

Part of that translation holds empirically. Weakest-link grading correctly capped and quarantined every chain containing a rejected narrator, with each decision traceable to the grade that caused it. Independent-chain corroboration fires, with negative controls on the encyclopedic corpus, across data ranging from paraphrase to formal physics prose. The jarḥ-ta’dīl loop recovered most of the designed reliability ordering from audit evidence alone.

Part of it does not yet. The same loop silently missed the least reliable narrator in the experiment, because domain-conditioned grading multiplies the evidence a registry must accumulate and a narrator rare within a domain never earns a grade at all. The transition policy trades coverage against grade recovery with no sweet spot on this corpus. And because the reference content critic cannot render a verdict on most real prose, the framework could not be driven above 4.8% coverage — which means the comparison that would establish a risk-coverage advantage over current practice could not be completed. The constraint is the critic, not the grading; but until that constraint is lifted, the claim is unproven and is not made here.

What the evaluation does establish is narrower and, I think, more useful than a headline number: that claim-level transmitter grading is implementable, that it behaves correctly and legibly where it has evidence, and that its failures are diagnosable rather than mysterious. A registry that cannot grade a narrator says so. A chain that cannot be served says why. That is the property a trust

framework most needs to have, and it is the property most easily lost by reporting only the cases that worked.

Execution provenance tells us what our agents did. The isnād-rijāl framework is a principled answer to the question that comes next: whether to believe them.

LLM usage disclosure

Drafting and editing were assisted by a large language model. All technical claims, design decisions, experimental results, and final text were reviewed by and are the responsibility of the author.

Acknowledgments

All praise is due to **Allah**, who granted the clarity to see it through. I thank Steffen Höhne for the opportunity, trust, and collaboration on the proprietary self-maintaining knowledge base within which this framework was conceived and prototyped; the system’s details remain his, and this paper describes only what is needed to ground the framework. The framework itself — the isnād-rijāl transfer — originated in the author’s work at the intersection of Islamic scholarship and AI systems through Islam & AI.

References

- [1] Brown, J. A. C. (2017). *Hadith: Muhammad’s Legacy in the Medieval and Modern World* (2nd ed.). Oneworld.
- [2] Buneman, P., Khanna, S., & Tan, W. C. (2001). Why and where: A characterization of data provenance. *Proceedings of ICDT 2001*, 316–330.
- [3] Cemri, M., et al. (2025). Why do multi-agent LLM systems fail? (MAST).
- [4] Chen, Z., Xiang, Z., Xiao, C., Song, D., & Li, B. (2024). AgentPoison: Red-teaming LLM agents via poisoning memory or knowledge bases. *NeurIPS 2024*.
- [5] Chhikara, P., Khant, D., Aryan, S., Singh, T., & Yadav, D. (2025). Mem0: Building production-ready AI agents with scalable long-term memory.
- [6] Condorcet, N. C. (1785). *Essai sur l’application de l’analyse à la probabilité des décisions rendues à la pluralité des voix*. Imprimerie Royale.
- [7] Crowell, B. *Light and Matter* (series). lightandmatter.com. CC BY-SA.
- [8] Cui, Y., & Widom, J. (2000). Lineage tracing for general data warehouse transformations. *Proceedings of VLDB 2000*, 71–82.
- [9] Dawid, A. P., & Skene, A. M. (1979). Maximum likelihood estimation of observer error-rates using the EM algorithm. *Applied Statistics*, 28(1), 20–28.
- [10] Dempster, A. P. (1967). Upper and lower probabilities induced by a multivalued mapping. *Annals of Mathematical Statistics*, 38(2), 325–339.
- [11] al-Dhahabī, Shams al-Dīn (14th c.). *Mizān al-ʿIṭidāl fī Naqd al-Rijāl*.
- [12] Dong, X. L., Gabrilovich, E., Heitz, G., Horn, W., Lao, N., Murphy, K., et al. (2014). Knowledge vault: A web-scale approach to probabilistic knowledge fusion. *Proceedings of KDD 2014*, 601–610.
- [13] Dong, X. L., Gabrilovich, E., Murphy, K., Dang, V., Horn, W., Lugaresi, C., et al. (2015). Knowledge-based trust: Estimating the trustworthiness of web sources. *Proceedings of the VLDB Endowment*, 8(9), 938–949.

- [14] Ebrahimi, S., Dehghankar, M., & Asudeh, A. (2025). An adversary-resistant multi-agent LLM system via credibility scoring. *Proceedings of IJCNLP-AACL 2025*, 1676–1693.
- [15] From agent traces to trust: Evidence tracing and execution provenance in LLM agents (2026). arXiv:2606.04990.
- [16] Gil, Y., & Artz, D. (2007). Towards content trust of web resources. *Journal of Web Semantics*, 5(4), 227–239.
- [17] Hartig, O., & Zhao, J. (2009). Using web data provenance for quality assessment. *Proceedings of the Workshop on Semantic Web for Provenance Management*.
- [18] Hawramani, I. Mathematical hadith verification with information theory: The HadithRank algorithm. <https://hawramani.com/mathematical-hadith-verification-with-information-theory-the-hadithrank-algorithm/>
- [19] Hou, Y., et al. (2024). WikiContradict: A benchmark for evaluating LLMs on real-world knowledge conflicts from Wikipedia.
- [20] Hume, D. (1748). *An Enquiry Concerning Human Understanding*, Section X: “Of Miracles.”
- [21] Huynh, T. D., Jennings, N. R., & Shadbolt, N. R. (2006). An integrated trust and reputation model for open multi-agent systems. *Autonomous Agents and Multi-Agent Systems*, 13(2), 119–154.
- [22] Ibn al-Ṣalāḥ al-Shahrazūrī (13th c.). *Muqaddimah* (‘*Ulūm al-Ḥadīth*).
- [23] Jøsang, A. (2001). A logic for uncertain probabilities. *International Journal of Uncertainty, Fuzziness and Knowledge-Based Systems*, 9(3), 279–311.
- [24] Jøsang, A., & Ismail, R. (2002). The beta reputation system. *Proceedings of the 15th Bled Electronic Commerce Conference*.
- [25] Juynboll, G. H. A. (1983). *Muslim Tradition: Studies in Chronology, Provenance and Authorship of Early Hadith*. Cambridge University Press.
- [26] Kamvar, S. D., Schlosser, M. T., & Garcia-Molina, H. (2003). The EigenTrust algorithm for reputation management in P2P networks. *Proceedings of WWW 2003*, 640–651.
- [27] Karpathy, A. (2026). LLM Wiki. Public gist. <https://gist.github.com/karpathy/442a6bf555914893e9891c11519de94f> (accessed 2026-07-08).
- [28] Lamport, L., Shostak, R., & Pease, M. (1982). The Byzantine generals problem. *ACM TOPLAS*, 4(3), 382–401.
- [29] Language agents achieve superhuman synthesis of scientific knowledge (PaperQA2/ContraCrow) (2024). arXiv:2409.13740
- [30] Li, X., et al. (2026). RAPS: Reputation-aware publish-subscribe for LLM multi-agent systems. arXiv:2602.08009.
- [31] Li, X., et al. (2026). TrustTrade: Human-inspired selective consensus for LLM agents. arXiv:2603.22567.
- [32] Ling, S. J., Moebs, W., & Sanny, J. *University Physics*, Vols. 1–3. OpenStax, Rice University. CC BY 4.0.
- [33] Mghari, M., Bouras, O., & El Hibaoui, A. (2022). Sanadset 650K: Data on hadith narrators. *Data in Brief*, 44, 108540.
- [34] Min, S., et al. (2023). FActScore: Fine-grained atomic evaluation of factual precision in long-form text generation. *EMNLP 2023*.
- [35] Moreau, L., Missier, P., et al. (2013). The PROV data model. W3C Recommendation.
- [36] Mosa, M. A. (2025). Synergizing structure and semantics: A knowledge graph-transformer framework for narrator disambiguation in hadith networks. *Digital Scholarship in the Humanities*, 40(4), 1085–1100.
- [37] Motzki, H. (2005). The muṣannaf of ‘Abd al-Razzāq al-Ṣan‘ānī as a source of authentic aḥādīth of the first century A.H. *Arabica*, 52(2), 159–212.

- [38] AI-powered hadith verification: Toward a new model of authenticity in Islamic knowledge transmission (2025). *International Journal of Noesantara Islamic Studies*, 2(5).
- [39] Digital takhrīj hadith as Islamic digital humanities (2025). *Digital Muslim Review*, 3(1).
- [40] Pasternack, J., & Roth, D. (2010). Knowing what to believe (when you already know something). *Proceedings of COLING 2010*, 877–885.
- [41] Pasternack, J., & Roth, D. (2013). Latent credibility analysis. *Proceedings of WWW 2013*, 1009–1020.
- [42] Prakash, S. (2026). The provenance paradox in multi-agent LLM routing: Delegation contracts and attested identity in LDP. arXiv:2603.18043.
- [43] Ramzy, A., Torki, M., Abdeen, M., Saif, O., ElNainay, M., Alshanqiti, A., & Nabil, E. (2023). Hadiths classification using a novel author-based hadith classification dataset (ABCD). *Big Data and Cognitive Computing*, 7(3), 141.
- [44] Sabater, J., & Sierra, C. (2001). ReGreT: A reputation model for gregarious societies. *Proceedings of AGENTS 2001*, 194–195.
- [45] Schacht, J. (1950). *The Origins of Muhammadan Jurisprudence*. Oxford University Press.
- [46] Schuster, T., Fisch, A., & Barzilay, R. (2021). Get your vitamin C! Robust fact verification with contrastive evidence. *NAACL 2021*.
- [47] Sequeira, R., Damianakis, S., Iqbal, U., & Psounis, K. (2026). Agent-Sentry: Bounding LLM agents via execution provenance. arXiv:2603.22868.
- [48] Shafer, G. (1976). *A Mathematical Theory of Evidence*. Princeton University Press.
- [49] Souza, R., Gueroudji, A., DeWitt, S., Rosendo, D., Ghosal, T., Ross, R., Balaprakash, P., & Ferreira da Silva, R. (2025). PROV-AGENT: Unified provenance for tracking AI agent interactions in agentic workflows. *IEEE e-Science 2025*. arXiv:2508.02866.
- [50] Su, H., et al. (2024). ConflictBank: A benchmark for evaluating the influence of knowledge conflicts in LLMs.
- [51] Thorne, J., Vlachos, A., Christodoulopoulos, C., & Mittal, A. (2018). FEVER: A large-scale dataset for fact extraction and verification. *NAACL 2018*.
- [52] U.S. Federal Rules of Evidence, Rule 805: Hearsay within hearsay.
- [53] Wu, K., et al. (2024). ClashEval: Quantifying the tug-of-war between an LLM’s internal prior and external evidence.
- [54] Yin, X., Han, J., & Yu, P. S. (2008). Truth discovery with multiple conflicting information providers on the web. *IEEE TKDE*, 20(6), 796–808.