

LiveMem: Maintaining Memory State Continuity in Long-Running LLM Inference

Zhichen Liu^{1,2*} Ruihan Sun^{1*} Hengjie Yang¹ Zipeng Wu^{1,3}
Zhaohan Chen¹ Xiaofan Zhang¹ Yang Xu²

¹NatureSelect.AI

²Southern University of Science and Technology

³Xidian University

Abstract

Long-running assistants and agents consume interaction streams that eventually outgrow the context. Existing context retention, summarization, and retrieval preserve access to selected history, but do not provide a persistent state over the full lifecycle when working context changes. We formulate this missing inference capability as *state continuity under context turnover*: carrying computation forward through a fixed-capacity memory state whose lifetime is independent of the active context. We introduce an intrinsic memory method, **LiveMem**, which augments a pretrained full-attention LLM with a memory state that preserves the historical information over the whole lifecycle while the main attention path retains a bounded KV window. Context turnover and memory state maintaining, memory-oriented post-training, and state-aware serving jointly make this memory state load bearing after its originating tokens are released. Our experiments show that LiveMem achieves leading overall performance among evaluated systems and other intrinsic memory methods. Experiments on LongMemEval show that LiveMem is able to answer the question based on the memory state, even when the supporting evidence has been removed from the current context, and evidence-distance analysis shows that useful information persists beyond the active window. LiveMem thus establishes state continuity as a distinct and complementary abstraction for continual LLM inference.




Figure 1: LiveMem enables stateful continual inference under context turnover. A bounded working context provides precise short-term access, while a fixed-capacity recurrent memory state preserves information across the model lifecycle.

*Corresponding authors: liuzc2024@mail.sustech.edu.cn; sunruihan2019@163.com

1 Introduction

Language models are evolving from isolated question-answering systems into continuously active assistants and agents over long-term interactions [OpenClaw Foundation, 2026, Nous Research, 2026]. Such systems no longer receive a single instruction to complete one task; instead, they continuously interact with the environment and accomplish various tasks in a scenario with no termination signal. As a result, the total history is determined by the lifecycle of the interaction, and has no theoretical ending. As history grows, the model’s working context must inevitably be replaced through some means. This raises a fundamental question: *how can language models maintain continuity across different working contexts within the same lifecycle?*

Existing widely used RAG-like systems do not truly solve the problem of continuity. Instead, they rely on engineering-based memory management strategies as patches (e.g., high-dimensional summaries) to maintain a certain level of awareness of the entire lifecycle [Chhikara et al., 2025, Li et al., 2025, Xu et al., 2025, Latimer et al., 2025]. These systems provide effective “historical access” mechanisms that determine how past content is supplied to the model, we regard them as persistent memory storage like notepads. Since the working context can be viewed as a precise short-term memory mechanism, this distinction reveals a scale missing from existing directions: a continuous memory state throughout the lifecycle—updated online, with fixed capacity, and persisting independently of the working context.

We term this requirement, which exists at the lifecycle scale and is independent of the working context, *state continuity*. Engineered memory systems are effective at persistent storage and on-demand retrieval, but difficult to provide this seamless continuity. The latter is precisely what recurrent memory states excel at, which can transmit information from multiple working contexts through model space in a high-dimensional form continuously. Therefore, memory systems that provide “historical access” and recurrent memory states that provide “state continuity” are not competing definitions of memory; they are orthogonal and potentially complementary in temporal scale and information representation.

Recent research has explored the continuity of memory states at this scale, ranging from neural long-term memory in Titans to the continuous memory perspective in Nested Learning [Behrouz et al., 2025b,a]. However, merely having a nominal recurrent memory state does not answer this question. If only a recurrent state is used as the model backbone, the model struggles to maintain precision when handling short-term tasks. Some works introduce a memory state branch on top of the transformer backbone, which provides certain cross-context representation capabilities [Yang et al., 2026], but if key history remains visible to attention at all times, the model may learn to bypass the memory state rather than maintaining continuity through it. Therefore, establishing a functional continuous memory state requires more than a state tensor labeled as memory: the model must undergo context turnover, learn to effectively write to and read from the memory state, and maintain predictive capability through the memory state even after historical contexts are no longer accessible. Thus, our goal is not merely to add a recurrent mechanism, but to ensure that the memory state genuinely carries effective information. Unlike methods that primarily introduce a memory representation, we explicitly study the lifecycle transition where information leaves attention and must remain usable through a persistent state.

We introduce **LiveMem**, an attention-LLM augmented with a recurrent memory state maintained by a parallel memory branch using Gated DeltaNet-2 (GDN2) [Hatamizadeh et al., 2026] as backbone. The branch continuously read and update a fixed-size memory state, while the original attention path supplies exact access to a bounded working context. KV turnover releases chunks from the attention path when the context reaches its limit, while the information remaining stays in the memory state. We apply memory-oriented post-training task to train the model to write, preserve, and read the memory state. LiveMem is a more complete structure of stateful continual inference: architecture, post-training, context turnover, and serving jointly make the memory state behaviorally effective after its originating context has disappeared.

Our experiments demonstrate the effectiveness of LiveMem. LiveMem achieves leading overall performance across evaluated tasks. Meanwhile, our experiments on LongMemEval show that even when evidence has been completely phased out of the current context window, LiveMem still maintains an accuracy above the baseline; this accuracy varies with the distance from the evidence to the window, but remains measurable. Our experiments indicate that LiveMem is not universally

optimal across all tasks—retrieval memory and parametric memory also have their own strengths—but the results sufficiently show that memory states can carry historical information beyond the working context. In summary, our contributions include:

- Defining memory state continuity, modeling this continuity with LiveMem architecture, providing an end-to-end design from formulation to implementation.
- Proposing memory-oriented post-training tasks to enable memory states to genuinely carry effective information.
- Demonstrating the usefulness of LiveMem through comprehensive evaluations and exploring the boundaries of its capabilities.

2 Preliminaries: Inference with Memory State under Context Turnover

For continuously running language models, the total token consumption can far exceed their context capacity. Therefore, the issue is not merely how past information is accessed, but rather how to maintain computational continuity when context turnover occurs. This chapter formalizes this problem and defines how latent states can function as memory.

2.1 Bounded Context and Reconstructive Inference

Let $H_t = (x_1, \dots, x_t)$ denote the interaction history available by time t , and let C_t denote the representation of tokens within the context window under the attention mechanism. An attention-only decoder with fixed parameters can be abstracted as

$$y_t \sim p_\theta(y_t | C_t). \quad (1)$$

Thus, C_t can be viewed as the inference state of the transformer. This state, composed of key-value pairs, grows with the history and, once it exceeds the context window, the information it carries also disappears [Kwon et al., 2023, Zhang et al., 2023]. Therefore, when C_t leaves the context, historical information can only be reused to influence subsequent predictions by building a system that retrieves C_t or some representation derived from it in some form [Lewis et al., 2020, Packer et al., 2023]. This paradigm, in which the model reconstructs its working state by reading explicit representations of relevant past information, is referred to as reconstructive inference.

2.2 Memory State Continuity

Let M_t be the memory state after the model has processed up to time t . We model the update of the memory state as follows:

$$M_{t+1} = U_\phi(M_t, X_{t+1}), \quad (2)$$

$$y_t \sim p_{\theta, \phi}(y_t | C_t, M_t), \quad (3)$$

where U_ϕ is a learned state transition function, and ϕ denotes parameters introduced by the memory module. The working context C_t provides fine-grained access to recent information, and M_t carries compressed historical memory information whose size is fixed. We do not require that M_t be able to reconstruct every token exactly. We refer to this setup as continual inference with an accompanying memory state, where inference is viewed as an ever-evolving state transition process that persists throughout the entire lifespan. This mechanism is complementary to external retrieval systems. A standalone memory retrieval system, when the model has no knowledge of the past, can only recall based on the model’s understanding of the current query. If the model is equipped with an accompanying memory state, it allows the model to have a rough awareness of the past.

Recurrent memory tokens, compressed attention states, and fixed latent memory pools implement similar memory states [Bulatov et al., 2022, Munkhdalai et al., 2024, Wang et al., 2024], but these states rely on independent context-turnover operations. In contrast, we integrate U_ϕ into the model itself and train it as part of the model backbone – namely, the GDN2 side-path architecture that we adopt.

The mere presence of a recurrent module does not prove that it carries memory. We refer to a recurrent state that satisfies these requirements as a living memory state. (i) it is updated online with incoming inputs, (ii) it persists after context switches, and (iii) the critical information contained within it




Figure 2: Overview of LiveMem. A full-attention main path maintains a bounded working context, while a recurrent side path updates the recurrent memory state from the same hidden representations. Their outputs are combined at every decoder layer. Context turnover evicts old KV entries from the main path, keeps only the system instruction as attention sink, and the current context in KV cache. The information carried by the evicted context is kept in the recurrent memory state.

influences the model’s subsequent behavior. Therefore, we consider a model to truly carry memory only when it can rely on the memory state to make decisions after the evidence has been completely removed from the context.

3 LiveMem

LiveMem adds a recurrent memory path to the attention module of a pretrained decoder transformer, which operates in parallel with the attention computation. These two paths serve different timescales: the attention mechanism provides precise access to the working context, while the recurrent memory path carries memory information across the entire lifetime. In this chapter, we will introduce the overall paradigm and how to train it.

3.1 Recurrent Memory State and Side Attention

The memory module of LiveMem is attached as a side branch to each attention layer. It reads and maintains the memory state via Gated DeltaNet-2 (GDN2) [Hatamizadeh et al., 2026], and its output is directly added back to the original attention output. Let h_t^ℓ be the normalized hidden representation at layer ℓ , S_t^ℓ be the memory state. The block computes

$$a_t^\ell = \text{Attn}_\ell(h_{\leq t}^\ell; C_t), \quad (4)$$

$$(r_t^\ell, S_t^\ell) = \text{GDN2}_\ell(h_t^\ell, S_{t-1}^\ell), \quad (5)$$

$$o_t^\ell = a_t^\ell + r_t^\ell, \quad (6)$$

after which the o_t^ℓ returns to the original model. In this way, historical memory information is injected into the model through the side branch of the attention module.

For one recurrent head, let $S_t \in \mathbb{R}^{d_k \times d_v}$ denote its state (omitting layer and head indices). GDN2 produces a log-decay $g_t \leq 0$, an erase gate $b_t \in [0, 1]^{d_k}$, and a write gate $w_t \in [0, 1]^{d_v}$. Its update

can be written as

$$\bar{S}_t = \text{Diag}(\exp(g_t)) S_{t-1}, \quad \text{forget,} \quad (7)$$

$$\rho_t = w_t \odot v_t - \bar{S}_t^\top (b_t \odot k_t), \quad \text{erase and prepare,} \quad (8)$$

$$S_t = \bar{S}_t + k_t \rho_t^\top, \quad r_t = S_t^\top q_t, \quad \text{write and read.} \quad (9)$$

The decay operation selectively forgets the current memory state along the key dimension, and the erase operation selectively removes old information to reduce interference when writing new information; these behaviors are learned during training. The read and update operations are performed per token to ensure real-time memory utilization and updating, so when context turnover occurs, no additional write operations are performed.

The q , k and v parameters of the side branch are initialized from those of the attention backbone, while other parameters are newly initialized. The output projection is initialized with zeros, so that the introduction of the entire side branch is initially equivalent to the original model itself, and the model gradually opens the side branch through learning. See Section C.1 for details.

3.2 Live Memory under Context Turnover

LiveMem processes the input as an ordered sequence of chunks $X_0, X_1, \dots$. We retain the system prompt, which structurally serves as an attention sink [Xiao et al., 2024b] and semantically preserves the most important system instructions, ensuring that they are always precisely visible to the model. All other chunks processed through a bounded attention window, which is actually a first-in-first-out queue. When a new chunk enters the window, if the total number of chunks in the window or the total number of tokens contained in all chunks exceeds a threshold, old chunks are evicted until it satisfies the threshold. This behavior can be expressed by the following formula:

$$\text{visible}(i, j) = \mathbf{1}[i \leq j] \mathbf{1}[\text{in_mem}(\text{chunk}(i), j)]. \quad (10)$$

where j is the position of the current query token, i denotes the position of another token, $c(i)$ represents the chunk containing token i , and $\text{in_window}(c(i), j)$ indicates whether chunk i is within the window when the query is at position j . This behavior ensures that the activation boundary changes only at chunk boundaries, and guarantees that no out-of-bounds situations occur. eq. (10) applies only to the main attention path, whereas eqs. (7) to (9) scan over the entire sequence. When an old chunk leaves C_t , its KV becomes invisible in the main attention, but its information has already been preserved in the memory state.

We apply this constraint during both training and inference to ensure training-inference consistency. During training, we implement it via dynamic attention masks. During inference, we directly release the evicted KV pages to make them inaccessible. Detailed explanations of the infrastructure are provided in Section C

3.3 Memory-Oriented Post-Training

Adding recurrent states does not guarantee that the model will actually utilize it to carry memory. Therefore, we design memory-oriented post-training tasks. In these tasks, each example consists of a segment of historical memory and one or more corresponding queries. We leverage the context turnover mechanism described in Section 3.2 to ensure that most of the history is removed from attention during training, thereby forcing the model to learn how to utilize the information in the memory state to produce answers, and also how to better preserve information into the memory state. We train the full memory branch while keeping the backbone parameters frozen. Meanwhile, we also explore training the memory branch with LoRA [Hu et al., 2022], and examine the effects of partially introducing the backbone parameters into training (Section 4.4). We design two training paradigms: supervised fine-tuning (SFT) and reinforcement learning (RL).

Answer-based Supervised Learning In SFT, each example concatenates the history, queries, and reference answers into a single causal stream. The loss is applied only to the answer positions $\mathcal{A}$:

$$\mathcal{L}_{\text{SFT}} = -\frac{1}{|\mathcal{A}|} \sum_{t \in \mathcal{A}} \log p_{\theta, \phi}(x_t | C_t, S_t). \quad (11)$$

We first use long-document question-answering data to establish stable memory-utilization behavior, and help activate the memory side branch. We then train on a broader mixture of data including QA, classification, and multiple-query tasks. Through SFT, the model learns how to use the side branch to carry memory information.

Exploration with Memory In RL, we optimize using the GRPO algorithm [Shao et al., 2024], incorporating practices from DAPO [Yu et al., 2025b]: clip-higher, token-level loss, dynamic sampling, and removal of KL. Given a prompt q containing memory, we sample $G = 8$ responses o_i and compute their advantages with group normalization:

$$\hat{A}_i = \frac{R_i - \mu_R}{\sigma_R}, \quad \mu_R = \frac{1}{G} \sum_{j=1}^G R_j, \quad \sigma_R = \text{Std}_j(R_j). \quad (12)$$

For response token $o_{i,t}$, let $\rho_{i,t} = \pi_\theta(o_{i,t} \mid q, o_{i,<t}) / \pi_{\theta_{\text{old}}}(o_{i,t} \mid q, o_{i,<t})$ and $\bar{\rho}_{i,t} = \text{clip}(\rho_{i,t}, 1 - \epsilon_{\text{low}}, 1 + \epsilon_{\text{high}})$. Our maximization objective is

$$J_{\text{RL}}(\theta) = \mathbb{E} \left[\frac{1}{\sum_i T_i} \sum_{i=1}^G \sum_{t=1}^{T_i} \Phi(\rho_{i,t}, \hat{A}_i) \right], \quad (13)$$

$$\Phi(\rho, A) = \begin{cases} \min(\rho A, \bar{\rho} A), & A \geq 0, \\ \max(\gamma A, \min(\rho A, \bar{\rho} A)), & A < 0, \end{cases}$$

where $\epsilon_{\text{low}} = 0.20$, $\epsilon_{\text{high}} = 0.28$, and $\gamma = 3$. We perform token-level normalization based on the number of tokens in the generated responses. For dynamic sampling, we retain only groups with $\text{Std}_i(a_i) > 0$, where a_i is the accuracy of the i -th response. Each q may contain one or more questions. We compute accuracy as $a_i = k_i / n_i$, where n_i is the number of questions and k_i is the number of correctly answered questions. When $n_i > 1$, we additionally give a bonus of 0.5 if all questions are answered correctly. If there is a formatting issue ($F_i = 0$), we apply a penalty of -0.5. Thus, the reward is formulated as:

$$R_i = a_i + 0.5 \cdot \mathbf{1}[k_i = n_i] - 0.5 \cdot \mathbf{1}[F_i = 0] \quad (14)$$

We first compute accuracy using exact match, and for negative cases, we fall back to an LM judge for equivalence judgment to ensure the unbiasedness of the reward signal as much as possible. Through this process, the model learns to better utilize the side branch for carrying memory.

4 Experiments

Our experiments primarily address three research questions:

1. How does LiveMem perform compared to other text-based memory and intrinsic memory approaches? (Section 4.2)
2. To what extent can LiveMem retain memories outside the window, and how well can these memories be maintained as the lifecycle evolves? (Section 4.3)
3. How can one effectively train a LiveMem module? (Section 4.4)

4.1 Experimental Setup

Tasks and metrics. We evaluated our approach on Wiki QA, Conversation QA, Test-Time Learning (TTL), and Long Document QA (Long QA). For the Wiki QA suite, we used 2WikiMultiHopQA, HotpotQA, and MuSiQue as evaluation sets [Ho et al., 2020, Yang et al., 2018, Trivedi et al., 2022], and additionally packed multiple samples together to form a multi-question (MQ) task. For the Conversation suite, we employed LoCoMo, LongMemEval, and the FactConsolidation dialogue data from MemoryAgentBench (MAB) for evaluation [Maharana et al., 2024, Wu et al., 2025, Hu et al., 2026]. For the TTL suite, we used the six TTL subsets from MAB, namely Banking77, CLINC150, NLU, TREC-coarse/fine, and ReDial [Casanueva et al., 2020, Larson et al., 2019, Liu et al., 2019, Li and Roth, 2002, Li et al., 2018]. For Long QA, we adopted the English QA task from ∞ Bench [Zhang et al., 2024], EventQA from MAB, and NarrativeQA [Kočíský et al., 2018]. We report per-question accuracy, using LLM-Judge to determine whether open-ended answers are consistent with the reference answers, using exact match to judge whether the answers to classification tasks are correct, and using recall@5 for ReDial. Detailed introductions to the evaluation tasks can be found in section D.

Table 1: Results under bounded-context configurations. The best results on each line are bolded, the second results are underlined.

	Qwen3-4B	RAG	Recurrent	Context2LoRA	δ -Mem	LiveMem-SFT	LiveMem-RL
Wiki QA							
2Wiki	<u>0.817</u>	0.117	0.775	0.213	0.824	0.768	0.784
2Wiki-MQ	0.336	-	0.204	0.009	0.232	<u>0.551</u>	0.587
Hotpot	<u>0.846</u>	0.399	0.819	0.234	0.853	<u>0.755</u>	0.772
Hotpot-MQ	0.329	-	0.256	0.008	0.226	<u>0.477</u>	0.487
MuSiQue	<u>0.461</u>	0.117	0.483	0.095	0.483	<u>0.369</u>	0.383
MuSiQue-MQ	0.200	-	0.165	0.003	0.151	<u>0.327</u>	0.347
All	0.498	0.211	0.450	0.094	0.462	<u>0.541</u>	0.560
Conversation							
LoCoMo	0.255	0.405	0.175	0.140	0.256	0.295	<u>0.314</u>
LME-s	0.224	0.548	<u>0.386</u>	0.168	0.230	0.286	0.302
FactCons	0.177	0.090	0.100	0.081	0.171	<u>0.175</u>	<u>0.175</u>
All	0.219	0.348	0.220	0.130	0.219	0.252	<u>0.264</u>
TTL							
Banking	0.770	0.740	0.000	0.860	0.770	<u>0.920</u>	0.940
CLINC	0.870	0.660	0.000	0.830	0.890	0.930	<u>0.920</u>
NLU	0.760	0.600	0.010	0.860	0.770	<u>0.820</u>	<u>0.820</u>
TREC-C	0.730	0.720	0.340	0.940	0.740	<u>0.780</u>	0.770
TREC-F	0.460	0.290	0.220	0.860	<u>0.510</u>	0.480	0.470
Redial	0.141	0.069	0.081	0.081	<u>0.146</u>	0.131	0.149
All	0.622	0.513	0.109	0.739	0.638	0.677	<u>0.678</u>
Long QA							
∞ Bench-QA	0.117	0.228	0.316	0.083	0.114	0.234	<u>0.251</u>
EventQA	0.445	0.612	0.447	0.269	0.433	0.463	<u>0.506</u>
NarrQA	0.313	0.233	0.282	0.150	0.326	<u>0.332</u>	0.371
All	0.282	<u>0.358</u>	0.348	0.167	0.291	0.343	0.376
Overall							
Overall	0.458	0.389	0.281	0.327	0.451	<u>0.505</u>	0.519

Evaluation protocol. All systems are compared using Qwen3-4B-Instruct-2507² (hereinafter referred to as Qwen3-4B) [Yang et al., 2025a]. To fully test the performance of each approach under limited context, we restrict the context window to 32k tokens; for shorter datasets (Wiki QA suite, LoCoMo), we further restrict it to 8k tokens. This means that if the compared method does not have a corresponding memory mechanism, the part of the input memory document that exceeds the window limit will be truncated from the head. For all generation, we uniformly adopt the sampling parameters officially recommended by Qwen: temperature 0.7, top-p 0.8, and top-k 20².

Systems. We use Qwen3-4B as the direct baseline for comparison, while δ -mem [Lei et al., 2026] adds a side-path state to it. We also compare against Context2LoRA, for which we construct the LoRA parameter memory module following the official behavior in our experiments Back et al. [2026]. RAG uses Qwen3-Embedding-0.6B [Zhang et al., 2025] as the retrieval model and retrieves relevant evidence via vector recall for generation. In addition, we design a Recurrent baseline, which behaviorally references MemAgent [Yu et al., 2025a]: it maintains a memory context, updates the memories within it upon each context turnover, outputs the entire memory after each round of processing, and feeds it into the prompt in the next round of memory processing. For LiveMem, we compare the models obtained from the two training steps described in Section 3.3, namely LiveMem-SFT and LiveMem-RL. More implementation details can be found in Section D.

4.2 Main Results

Table 1 reports the experimental results under the limited context window setting. On the Wiki QA suite, Qwen3-4B and δ -mem both achieve strong performance on the single-question tasks, closely

²<https://huggingface.co/Qwen/Qwen3-4B-Instruct-2507>

Table 2: The results of LiveMem performance w./w.o. historical information stored in memory state. “State” processes the complete history and stores them in memory state, whereas “Trunc.” sees only the truncated suffix and begins from zero state. Δ is State minus Trunc.

Dataset	LiveMem-SFT			LiveMem-RL		
	Trunc.	State	Δ	Trunc.	State	Δ
2Wiki-MQ	0.512	0.551	+0.039	0.545	0.587	+0.042
LoCoMo	0.277	0.295	+0.019	0.299	0.314	+0.015
LME-S	0.296	0.286	-0.010	0.294	0.302	+0.008
Banking	0.900	0.920	+0.020	0.930	0.940	+0.010
∞ Bench-QA	0.228	0.234	+0.006	0.222	0.251	+0.028
NarrQA	0.332	0.332	+0.000	0.357	0.371	+0.014

followed by LiveMem and Recurrent. However, on the MQ tasks, the performance of these methods drops dramatically, with only LiveMem maintaining its lead. This indicates that existing baselines are good at handling only a single multi-hop logic chain, but struggle when faced with multiple logic chains simultaneously. As a result, LiveMem outperforms the other methods overall on Wiki QA.

We also observe that RAG and Context2LoRA achieve SOTA results on Conversation and TTL suites, respectively. However, they are too specialized on their suites. They show little performance on tasks other than their respective SOTA ones. On Long QA, although RAG and Recurrent each excel on particular tasks, LiveMem maintains an overall lead in this group by achieving balanced and strong scores across all three tasks.

In summary, LiveMem is a well-rounded method that performs consistently across all tasks. The result shows that LiveMem achieves SOTA results on Wiki QA and Long QA, and while it does not rank first on Conversation and TTL, its performance is second only to the SOTA baselines on these tasks. Meanwhile, other baselines each have their own strengths and weaknesses. Once they encounter tasks they are not good at, their performance almost completely collapses. Therefore, overall, LiveMem substantially outperforms the other baselines.

4.3 Does the Recurrent State Carry Evicted Evidence?

We compare the performance of LiveMem under two settings: one with historical memory incorporated, and the other with historical information directly truncated. For models that include historical memory in their memory state, they can refer to the history to a certain extent when answering questions; for the truncation setting, without historical information, the model can only rely on the information within the current window to answer questions. Table 2 reports representative experimental results. It can be observed that for LiveMem-SFT, except for a performance drop on LongMemEval, incorporating historical information leads to improvements on all other datasets. For LiveMem-RL, on the reported datasets, performance consistently improves after incorporating historical information. This may be attributed to the fact that the model after RL is better at maintaining and leveraging historical memories.




Figure 3: LongMemEval-s accuracy grouped by whether the supporting evidence is fully or partially displaced from the active context. This analysis tests whether the memory state truly benefits performance when the evidence leaves the working context.




Figure 4: LongMemEval-S accuracy as supporting evidence is placed progressively farther from the active-context window. Accuracy remains measurable after multiple turnover intervals rather than collapsing at the eviction boundary.

We further filter the results on LongMemEval and select instances where all key evidence lies outside the window, as well as those where key evidence is partially outside the window, and report the accuracy on these subsets. Figure 3 presents the accuracy comparison results. It can be seen that, regardless of whether the evidence is entirely or partially removed, leveraging historical information from LiveMem’s memory state can achieve higher accuracy than other methods. Notably, under the full-eviction setting, while Qwen3-4B and δ -mem, which have no access to historical information, achieve extremely low accuracy, LiveMem outperforms them by more than ten percentage points. This demonstrates the necessity of the memory state in carrying historical memories.

We also manually control the distance from evidence to the current window in the LongMemEval subset in Figure 3 A to investigate whether the retention duration of evidence in the memory state affects LiveMem’s utilization of memories. Figure 4 shows the results as the evicted evidence moves progressively farther away from the active window. The model’s accuracy exhibits a slight downward trend as the distance increases, but overall remains at a stable level. This indicates that the memory update and forgetting mechanism based on GDN2 does affect the usability of key evidence in the memory state to some extent, yet it is still capable of keeping such evidence retainable within the memory state.

4.4 Architecture and Training Ablations

Trainable capacity. We compare the performance of LiveMem under different training capacity settings, including side-path LoRA, side-path full-parameter, and side-path full-parameter + main-path LoRA. We present the comparison results of the SFT checkpoints, which are shown in Table 3 (a). The results indicate that using full-parameter training for the side-path yields more stable performance, likely because the distribution gap between Attention and GDN2 is relatively large, and LoRA—which optimizes within a small subspace—struggles to adapt to the behavior of GDN2.

Table 3: SFT ablations under bounded active context. Panel (a) varies which parameters are trainable; Panel (b) varies the proportion and order of long-context data.

	2Wiki-MQ	LoCoMo	LME-S	Banking	TREC-F	∞ Bench-QA	EventQA
<i>(a) Trainable capacity</i>							
LoRA side	0.479	0.256	0.362	0.880	0.440	0.214	0.490
Full side	0.551	0.234	0.286	0.920	0.480	0.234	0.463
Full side + main-path LoRA	0.520	0.220	0.280	0.910	0.540	0.236	0.412
<i>(b) Training curriculum</i>							
Direct mixture	0.439	0.261	0.298	0.740	0.420	0.222	0.448
Rebalanced mixture	0.452	0.263	0.326	0.770	0.260	0.208	0.412
Long warmup + rebalanced	0.479	0.256	0.362	0.880	0.440	0.214	0.490

Adding LoRA to the main path does not bring significant improvements; we suspect that the main-path LoRA training may absorb some of the memory that should have been directed to the side-path.

Data Mixture and Training curriculum. We also compare the effects of data mixing ratios and curriculum training in Table 3 (b). Specifically, we compare three settings: (1) using all data directly, (2) using rebalanced data, where we removed the majority of the long-text QA data, which had originally constituted a large proportion of the overall dataset, and (3) using long-text QA data for cold-start to open the side-path, followed by formal training with the rebalanced data. The results show that simply mixing all data together does not perform well, because the long-text data imposes low recall requirements, leaving the model with little incentive to learn how to maintain the memory state. After we reduced the long-text data, the model’s performance on recall tasks improved, but its performance on Long QA declined. We attribute that the rebalanced data is too small to sufficiently activate the side-path, which prevents the main path from fully leveraging the information in memory state. Therefore, we first use long-text data for warm-up to activate the side-path, and then use the rebalanced data to train the model to maintain the memory state. This curriculum yields the greatest overall performance improvement.

5 Conclusion

What long-context language models truly require goes beyond merely accessing stored historical records; it also entails maintaining coherence of memory when their own working context changes. We formulate this requirement as state continuity under context turnover, thereby distinguishing the model’s intrinsic memory state mechanism from external retrieval-based mechanisms. This distinction reveals an inference-time scale that has been overlooked between retrieval systems and attention contexts with limited capacity—the scale over the lifecycle.

LiveMem realizes this mechanism by augmenting a pretrained full-attention model with a parallel GDN2 memory branch to manage the memory state. The memory state is updated online, and when old attention KV is evicted, its information is preserved in the memory state. We propose a standardized scheduling paradigm and training scheme that maintains training-inference consistency under this paradigm while fully training the memory state to bear the burden of memory over the lifecycle.

Across various evaluation tasks, LiveMem demonstrates strong overall performance, and it is particularly effective when multiple questions share the same historical background and the supporting evidence has been entirely moved out of the active window. Ablation studies show that the displaced history still continuously influences predictions through the memory state.

More broadly, retrieval and state continuity address different aspects of long-term reasoning: retrieval determines which past information the model reads, while the recurrent memory state determines how the model maintains information coherence over the lifecycle after reading that information. Therefore, for ultra-long-context scenarios, LiveMem’s approach of internally maintaining a memory state to sustain information continuity throughout the entire lifecycle plays an important role in moving toward practical infinite-context inference.

References

- Seungju Back, Dongwoo Lee, Naun Kang, Taehee Lee, S. K. Hong, Youngjune Gwon, and Sungjin Ahn. Understanding LoRA as knowledge memory: An empirical analysis. In *Proceedings of the 43rd International Conference on Machine Learning*, 2026. URL <https://openreview.net/forum?id=0MVEJk4dhE>.
- Yushi Bai, Xin Lv, Jiajie Zhang, Yuze He, Ji Qi, Lei Hou, Jie Tang, Yuxiao Dong, and Juanzi Li. LongAlign: A recipe for long context alignment of large language models. In *Findings of the Association for Computational Linguistics: EMNLP 2024*, pages 1376–1395, Miami, Florida, USA, November 2024. Association for Computational Linguistics. doi: 10.18653/v1/2024.findings-emnlp.74. URL <https://aclanthology.org/2024.findings-emnlp.74/>.
- Ali Behrouz, Meisam Razaviyayn, Peilin Zhong, and Vahab Mirrokni. Nested learning: The illusion of deep learning architectures. In *Advances in Neural Information Processing Sys-*

- tems, 2025a. URL https://proceedings.neurips.cc/paper_files/paper/2025/hash/4309616aaed8e848009bc4a7ef73b493-Abstract-Conference.html.
- Ali Behrouz, Peilin Zhong, and Vahab Mirrokni. Titans: Learning to memorize at test time. *arXiv preprint arXiv:2501.00663*, 2025b. URL <https://arxiv.org/abs/2501.00663>.
- Aydar Bulatov, Yuri Kuratov, and Mikhail S. Burtsev. Recurrent memory transformer. *arXiv preprint arXiv:2207.06881*, 2022. URL <https://arxiv.org/abs/2207.06881>.
- Iñigo Casanueva, Tadas Temčinas, Daniela Gerz, Matthew Henderson, and Ivan Vulić. Efficient intent detection with dual sentence encoders. In *Proceedings of the 2nd Workshop on Natural Language Processing for Conversational AI*, pages 38–45, Online, July 2020. Association for Computational Linguistics. doi: 10.18653/v1/2020.nlp4convai-1.5. URL <https://aclanthology.org/2020.nlp4convai-1.5/>.
- Yukang Chen, Shengju Qian, Haotian Tang, Xin Lai, Zhijian Liu, Song Han, and Jiaya Jia. LongLoRA: Efficient fine-tuning of long-context large language models. In *The Twelfth International Conference on Learning Representations*, 2024. URL <https://openreview.net/forum?id=6PmJoRfdaK>. Introduces the LongAlpaca long-context instruction-following dataset.
- Zhi Chen, Qiguang Chen, Libo Qin, Qipeng Guo, Haijun Lv, Yicheng Zou, Hang Yan, Kai Chen, and Dahua Lin. What are the essential factors in crafting effective long context multi-hop instruction datasets? insights and best practices. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 27129–27151, Vienna, Austria, July 2025. Association for Computational Linguistics. doi: 10.18653/v1/2025.acl-long.1316. URL <https://aclanthology.org/2025.acl-long.1316/>.
- Prateek Chhikara, Dev Khant, Saket Aryan, Taranjeet Singh, and Deshraj Yadav. Mem0: Building production-ready AI agents with scalable long-term memory. In *ECAI 2025 – 28th European Conference on Artificial Intelligence*, Frontiers in Artificial Intelligence and Applications, pages 2993–3000. IOS Press, 2025. doi: 10.3233/FAIA251160. URL <https://doi.org/10.3233/FAIA251160>.
- Zihang Dai, Zhilin Yang, Yiming Yang, Jaime Carbonell, Quoc Le, and Ruslan Salakhutdinov. Transformer-XL: Attentive language models beyond a fixed-length context. In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, 2019. URL <https://aclanthology.org/P19-1285/>.
- Payel Das, Subhajit Chaudhury, Elliot Nelson, Igor Melnyk, Sarathkrishna Swaminathan, Sihui Dai, et al. Larimar: Large language models with episodic memory control. In *Proceedings of the 41st International Conference on Machine Learning*, 2024. URL <https://proceedings.mlr.press/v235/das24a.html>.
- Pradeep Dasigi, Kyle Lo, Iz Beltagy, Arman Cohan, Noah A. Smith, and Matt Gardner. A dataset of information-seeking questions and answers anchored in research papers. In *Proceedings of the 2021 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, 2021. URL <https://aclanthology.org/2021.naacl-main.365/>.
- Juechu Dong, Boyuan Feng, Driss Guessous, Yanbo Liang, and Horace He. Flex attention: A programming model for generating optimized attention kernels. *arXiv preprint arXiv:2412.05496*, 2024. URL <https://arxiv.org/abs/2412.05496>.
- Albert Gu and Tri Dao. Mamba: Linear-time sequence modeling with selective state spaces. *arXiv preprint arXiv:2312.00752*, 2023. URL <https://arxiv.org/abs/2312.00752>.
- Ali Hatamizadeh, Yejin Choi, and Jan Kautz. Gated DeltaNet-2: Decoupling erase and write in linear attention. *arXiv preprint arXiv:2605.22791*, 2026. URL <https://arxiv.org/abs/2605.22791>.
- Xanh Ho, Anh-Khoa Duong Nguyen, Saku Sugawara, and Akiko Aizawa. Constructing a multi-hop QA dataset for comprehensive evaluation of reasoning steps. In *Proceedings of the 28th International Conference on Computational Linguistics*, 2020. URL <https://aclanthology.org/2020.coling-main.580/>.

- Cheng-Ping Hsieh, Simeng Sun, Samuel Krizan, Shantanu Acharya, Dima Rekesh, Fei Jia, Yang Zhang, and Boris Ginsburg. RULER: What’s the real context size of your long-context language models? *arXiv preprint arXiv:2404.06654*, 2024. URL <https://arxiv.org/abs/2404.06654>.
- Edward J. Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen. LoRA: Low-rank adaptation of large language models. In *International Conference on Learning Representations*, 2022. URL <https://openreview.net/forum?id=nZeVKeeFYf9>.
- Yuanzhe Hu, Yu Wang, and Julian McAuley. Evaluating memory in LLM agents via incremental multi-turn interactions. In *International Conference on Learning Representations*, 2026. URL <https://openreview.net/forum?id=ZgQ0t3zYTQ>.
- Vladimir Karpukhin, Barlas Oguz, Sewon Min, Patrick Lewis, Ledell Wu, Sergey Edunov, Danqi Chen, and Wen-tau Yih. Dense passage retrieval for open-domain question answering. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 6769–6781, Online, November 2020. Association for Computational Linguistics. doi: 10.18653/v1/2020.emnlp-main.550. URL <https://aclanthology.org/2020.emnlp-main.550/>.
- Kimi Team. Kimi linear: An expressive, efficient attention architecture. *arXiv preprint arXiv:2510.26692*, 2025. URL <https://arxiv.org/abs/2510.26692>.
- Tomáš Kočiský, Jonathan Schwarz, Phil Blunsom, Chris Dyer, Karl Moritz Hermann, Gábor Melis, and Edward Grefenstette. The NarrativeQA reading comprehension challenge. *Transactions of the Association for Computational Linguistics*, 2018. URL <https://aclanthology.org/Q18-1023/>.
- Woosuk Kwon, Zhuohan Li, Siyuan Zhuang, Ying Sheng, Lianmin Zheng, Cody Hao Yu, Joseph E. Gonzalez, Hao Zhang, and Ion Stoica. Efficient memory management for large language model serving with PagedAttention. In *Proceedings of the 29th Symposium on Operating Systems Principles*, 2023. URL <https://arxiv.org/abs/2309.06180>.
- Stefan Larson, Anish Mahendran, Joseph J. Peper, Christopher Clarke, Andrew Lee, Parker Hill, Jonathan K. Kummerfeld, Kevin Leach, Michael A. Laurenzano, Lingjia Tang, and Jason Mars. An evaluation dataset for intent classification and out-of-scope prediction. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pages 1311–1316, Hong Kong, China, November 2019. Association for Computational Linguistics. doi: 10.18653/v1/D19-1131. URL <https://aclanthology.org/D19-1131/>.
- Chris Latimer, Nicoló Boschi, Andrew Neeser, Chris Bartholomew, Gaurav Srivastava, Xuan Wang, and Naren Ramakrishnan. Hindsight is 20/20: Building agent memory that retains, recalls, and reflects. *arXiv preprint arXiv:2512.12818*, 2025. doi: 10.48550/arXiv.2512.12818. URL <https://arxiv.org/abs/2512.12818>.
- Jingdi Lei, Di Zhang, Junxian Li, Weida Wang, Kaixuan Fan, Xiang Liu, Qihan Liu, Xiaoteng Ma, Baian Chen, and Soujanya Poria. δ -mem: Efficient online memory for large language models. *arXiv preprint arXiv:2605.12357*, 2026. URL <https://arxiv.org/abs/2605.12357>.
- Patrick Lewis, Ethan Perez, Aleksandra Piktus, Fabio Petroni, Vladimir Karpukhin, Naman Goyal, Heinrich Küttler, Mike Lewis, Wen-tau Yih, Tim Rocktäschel, Sebastian Riedel, and Douwe Kiela. Retrieval-augmented generation for knowledge-intensive NLP tasks. In *Advances in Neural Information Processing Systems*, 2020. URL https://proceedings.neurips.cc/paper_files/paper/2020/hash/6b493230205f780e1bc26945df7481e5-Abstract.html.
- Raymond Li, Samira Ebrahimi Kahou, Hannes Schulz, Vincent Michalski, Laurent Charlin, and Chris Pal. Towards deep conversational recommendations. In *Advances in Neural Information Processing Systems*, volume 31, 2018. URL <https://papers.nips.cc/paper/8180-towards-deep-conversational-recommendations>.
- Xin Li and Dan Roth. Learning question classifiers. In *COLING 2002: The 19th International Conference on Computational Linguistics*, 2002. URL <https://aclanthology.org/C02-1150/>.

- Yuhong Li, Yingbing Huang, Bowen Yang, Bharat Venkitesh, Acyr Locatelli, Hanchen Ye, Tianle Cai, Patrick Lewis, and Deming Chen. SnapKV: LLM knows what you are looking for before generation. In *Advances in Neural Information Processing Systems*, 2024. URL https://proceedings.neurips.cc/paper_files/paper/2024/hash/28ab418242603e0f7323e54185d19bde-Abstract-Conference.html.
- Zhiyu Li, Chenyang Xi, Chunyu Li, Ding Chen, Boyu Chen, Shichao Song, Simin Niu, Hanyu Wang, Jiawei Yang, Chen Tang, Qingchen Yu, Jihao Zhao, Yezhaohui Wang, Peng Liu, Zehao Lin, Pengyuan Wang, Jiahao Huo, Tianyi Chen, Kai Chen, Kehang Li, Zhen Tao, Huayi Lai, Hao Wu, Bo Tang, Zhengren Wang, Zhaoxin Fan, Ningyu Zhang, Linfeng Zhang, Junchi Yan, Mingchuan Yang, Tong Xu, Wei Xu, Huajun Chen, Haofen Wang, Hongkang Yang, Wentao Zhang, Zhi-Qin John Xu, Siheng Chen, and Feiyu Xiong. MemOS: A memory OS for AI system. *arXiv preprint arXiv:2507.03724*, 2025. doi: 10.48550/arXiv.2507.03724. URL <https://arxiv.org/abs/2507.03724>.
- Opher Lieber, Barak Lenz, Hofit Bata, Gal Cohen, Jhonathan Osin, et al. Jamba: A hybrid transformer-mamba language model. *arXiv preprint arXiv:2403.19887*, 2024. URL <https://arxiv.org/abs/2403.19887>.
- Xingkun Liu, Arash Eshghi, Pawel Swietojanski, and Verena Rieser. Benchmarking natural language understanding services for building conversational agents. *arXiv preprint arXiv:1903.05566*, 2019. doi: 10.48550/arXiv.1903.05566. URL <https://arxiv.org/abs/1903.05566>.
- Adyasha Maharana, Dong-Ho Lee, Sergey Tulyakov, Mohit Bansal, Francesco Barbieri, and Yuwei Fang. Evaluating very long-term conversational memory of LLM agents. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics*, 2024. URL <https://aclanthology.org/2024.acl-long.747/>.
- Moonshot AI. Kimi K3: Open frontier intelligence. Technical blog, 2026. URL <https://www.kimi.com/blog/kimi-k3>.
- Tsendsuren Munkhdalai, Manaal Faruqui, and Siddharth Gopal. Leave no context behind: Efficient infinite context transformers with infini-attention. *arXiv preprint arXiv:2404.07143*, 2024. URL <https://arxiv.org/abs/2404.07143>.
- Nous Research. Hermes Agent: The self-improving ai agent. <https://github.com/NousResearch/hermes-agent>, July 2026. Version 0.19.0 (release tag v2026.7.20), accessed July 27, 2026.
- OpenClaw Foundation. OpenClaw: A personal, open-source ai assistant. <https://github.com/openclaw/openclaw>, July 2026. Version 2026.7.1, accessed July 27, 2026.
- Charles Packer, Sarah Wooders, Kevin Lin, Vivian Fang, Shishir G. Patil, Ion Stoica, and Joseph E. Gonzalez. MemGPT: Towards LLMs as operating systems. *arXiv preprint arXiv:2310.08560*, 2023. URL <https://arxiv.org/abs/2310.08560>.
- Imanol Schlag, Kazuki Irie, and Jürgen Schmidhuber. Linear transformers are secretly fast weight programmers. In *Proceedings of the 38th International Conference on Machine Learning*, 2021. URL <https://proceedings.mlr.press/v139/schlag21a.html>.
- Zhihong Shao, Peiyi Wang, Qihao Zhu, Runxin Xu, Junxiao Song, et al. DeepSeekMath: Pushing the limits of mathematical reasoning in open language models. *arXiv preprint arXiv:2402.03300*, 2024. URL <https://arxiv.org/abs/2402.03300>.
- Jianlin Su, Yu Lu, Shengfeng Pan, Ahmed Murtadha, Bo Wen, and Yunfeng Liu. Roformer: Enhanced transformer with rotary position embedding, 2023. URL <https://arxiv.org/abs/2104.09864>.
- Yu Sun, Xinhao Li, Karan Dalal, Jiarui Xu, Arjun Vikram, Genghan Zhang, et al. Learning to (Learn at test time): RNNs with expressive hidden states. In *Proceedings of the 42nd International Conference on Machine Learning*, 2025. URL <https://proceedings.mlr.press/v267/sun25h.html>.

- Together AI. Long-Data-Collections. Hugging Face dataset, 2023. URL <https://huggingface.co/datasets/togethercomputer/Long-Data-Collections>. A collection of long-context pretraining and instruction-finetuning datasets.
- Harsh Trivedi, Niranjan Balasubramanian, Tushar Khot, and Ashish Sabharwal. MuSiQue: Multihop questions via single-hop question composition. *Transactions of the Association for Computational Linguistics*, 2022. URL <https://aclanthology.org/2022.tacl-1.31/>.
- Weizhi Wang, Li Dong, Hao Cheng, Xiaodong Liu, Xifeng Yan, Jianfeng Gao, and Furu Wei. Augmenting language models with long-term memory. In *Advances in Neural Information Processing Systems*, 2023. URL https://proceedings.neurips.cc/paper_files/paper/2023/hash/ebd82705f44793b6f9ade5a669d0f0bf-Abstract-Conference.html.
- Yu Wang, Yifan Gao, Xiusi Chen, Haoming Jiang, Shiyang Li, Jingfeng Yang, et al. MEMORYLLM: Towards self-updatable large language models. In *Proceedings of the 41st International Conference on Machine Learning*, 2024. URL <https://proceedings.mlr.press/v235/wang24s.html>.
- Yu Wang, Dmitry Krotov, Yuanzhe Hu, Yifan Gao, Wangchunshu Zhou, Julian McAuley, Dan Gutfreund, Rogerio Feris, and Zexue He. M+: Extending MemoryLLM with scalable long-term memory. In *Proceedings of the 42nd International Conference on Machine Learning*, 2025. URL <https://proceedings.mlr.press/v267/wang25au.html>.
- Rubin Wei, Jiaqi Cao, Jiarui Wang, Jushi Kai, Qipeng Guo, Bowen Zhou, and Zhouhan Lin. MLP Memory: A retriever-pretrained memory for large language models. In *The Fourteenth International Conference on Learning Representations*, 2026. URL <https://openreview.net/forum?id=1SMdxRtLBp>.
- Di Wu, Hongwei Wang, Wenhao Yu, Yuwei Zhang, Kai-Wei Chang, and Dong Yu. LongMemEval: Benchmarking chat assistants on long-term interactive memory. In *International Conference on Learning Representations*, 2025. URL <https://openreview.net/forum?id=UBvm2bIyxz>.
- Yuhuai Wu, Markus N. Rabe, DeLesley Hutchins, and Christian Szegedy. Memorizing transformers. In *International Conference on Learning Representations*, 2022. URL <https://openreview.net/forum?id=TrjbxzRcnf->.
- Chaojun Xiao, Pengl Zhang, Xu Han, Guangxuan Xiao, Yankai Lin, Zhengyan Zhang, Zhiyuan Liu, and Maosong Sun. InfLLM: Training-free long-context extrapolation for LLMs with an efficient context memory. In *Advances in Neural Information Processing Systems*, 2024a. URL https://proceedings.neurips.cc/paper_files/paper/2024/hash/d842425e4bf79ba039352da0f658a906-Abstract-Conference.html.
- Guangxuan Xiao, Yuandong Tian, Beidi Chen, Song Han, and Mike Lewis. Efficient streaming language models with attention sinks. In *International Conference on Learning Representations*, 2024b. URL <https://arxiv.org/abs/2309.17453>.
- Wujiang Xu, Zujie Liang, Kai Mei, Hang Gao, Juntao Tan, and Yongfeng Zhang. A-MEM: Agentic memory for LLM agents. In *Advances in Neural Information Processing Systems*, volume 38, 2025. URL https://proceedings.neurips.cc/paper_files/paper/2025/hash/19909c36f51abc4856b4560aff3d36d6-Abstract-Conference.html.
- An Yang et al. Qwen3 technical report. *arXiv preprint arXiv:2505.09388*, 2025a. URL <https://arxiv.org/abs/2505.09388>.
- Songlin Yang, Bailin Wang, Yu Zhang, Yikang Shen, and Yoon Kim. Parallelizing linear transformers with the delta rule over sequence length. In *Advances in Neural Information Processing Systems*, 2024. URL https://proceedings.neurips.cc/paper_files/paper/2024/hash/d13a3eae72366e61dfdc7eea82eeb685-Abstract-Conference.html.
- Songlin Yang, Jan Kautz, and Ali Hatamizadeh. Gated delta networks: Improving Mamba2 with delta rule. In *International Conference on Learning Representations*, 2025b. URL <https://arxiv.org/abs/2412.06464>.

- Xintong Yang, Hao Gu, Binxing Xu, Lujun Li, Bei Liu, Jiacheng Liu, Qiyuan Zhu, Yike Guo, and Sirui Han. IndexMem: Learned KV-cache eviction with latent memory for long-context LLM inference. *arXiv preprint arXiv:2605.25475*, 2026. URL <https://arxiv.org/abs/2605.25475>.
- Zhilin Yang, Peng Qi, Saizheng Zhang, Yoshua Bengio, William W. Cohen, Ruslan Salakhutdinov, and Christopher D. Manning. HotpotQA: A dataset for diverse, explainable multi-hop question answering. In *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing*, 2018. URL <https://aclanthology.org/D18-1259/>.
- Hongli Yu, Tinghong Chen, Jiangtao Feng, Jiangjie Chen, Weinan Dai, Qiyang Yu, et al. MemAgent: Reshaping long-context LLM with multi-conv RL-based memory agent. *arXiv preprint arXiv:2507.02259*, 2025a. URL <https://arxiv.org/abs/2507.02259>.
- Qiyang Yu, Zheng Zhang, Ruofei Zhu, Yufeng Yuan, Xiaochen Zuo, et al. DAPO: An open-source LLM reinforcement learning system at scale. *arXiv preprint arXiv:2503.14476*, 2025b. URL <https://arxiv.org/abs/2503.14476>.
- Xiang Zhang, Junbo Zhao, and Yann LeCun. Character-level convolutional networks for text classification. In *Advances in Neural Information Processing Systems*, 2015. URL <https://proceedings.neurips.cc/paper/2015/hash/250cf8b51c773f3f8dc8b4be867a9a02-Abstract.html>.
- Xinrong Zhang, Yingfa Chen, Shengding Hu, Zihang Xu, Junhao Chen, Moo Hao, et al. ∞ Bench: Extending long context evaluation beyond 100K tokens. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics*, 2024. URL <https://aclanthology.org/2024.acl-long.814/>.
- Yanzhao Zhang, Mingxin Li, Dingkun Long, Xin Zhang, Huan Lin, Baosong Yang, Pengjun Xie, An Yang, Dayiheng Liu, Junyang Lin, Fei Huang, and Jingren Zhou. Qwen3 embedding: Advancing text embedding and reranking through foundation models. *arXiv preprint arXiv:2506.05176*, 2025.
- Zhenyu Zhang, Ying Sheng, Tianyi Zhou, Tianlong Chen, Lianmin Zheng, Ruisi Cai, et al. H2O: Heavy-hitter oracle for efficient generative inference of large language models. In *Advances in Neural Information Processing Systems*, 2023. URL https://proceedings.neurips.cc/paper_files/paper/2023/hash/6ceefa7b15572587b78ecfceb2827f8-Abstract-Conference.html.
- Wanjun Zhong, Lianghong Guo, Qiqi Gao, He Ye, and Yanlin Wang. MemoryBank: Enhancing large language models with long-term memory. *arXiv preprint arXiv:2305.10250*, 2023. URL <https://arxiv.org/abs/2305.10250>.

A Related Work

A.1 Textual Memory and RAG-like System

Retrieval-augmented generation conditions a parametric generator on passages selected from an external corpus [Lewis et al., 2020]. Related systems retrieve model-side representations rather than raw corpus passages. Memorizing Transformers performs approximate nearest-neighbor lookup over cached internal key-value pairs [Wu et al., 2022]; LongMem uses a frozen language model as a memory encoder and trains a residual side network to retrieve and read from a cached memory bank [Wang et al., 2023]; and InfLLM stores distant context blocks in external memory units that are selected for attention without fine-tuning [Xiao et al., 2024a]. These methods differ substantially in what they index and retrieve, but all expand *history access* by selecting an explicit record or representation to reintroduce into the current computation.

Agent systems additionally manage editable textual records over time. MemoryBank retrieves, updates, and selectively forgets conversational memories [Zhong et al., 2023], while MemGPT moves information among context and external storage tiers [Packer et al., 2023]. Mem0 [Chhikara et al., 2025] introduces a scalable long-term memory framework for production-grade agents. By dynamically extracting, consolidating, and retrieving salient facts from historical interactions, it enables agents to maintain consistent user models across multi-turn and cross-session interactions. Its extended version further incorporates graph structures to explicitly capture relationships among memory entries. A-Mem [Xu et al., 2025] represents memories as structured notes containing contextual descriptions, keywords, and tags. When new memories are added, it autonomously establishes associations and updates existing memories, thereby forming a continuously evolving memory network. In contrast, MemOS [Li et al., 2025] treats memory as a manageable first-class resource at the system level. Through MemCube, it provides a unified abstraction for textual, activation-based, and parametric memories, while supporting the scheduling, migration, composition, and evolution of different memory forms, thus offering a unified memory infrastructure for continual learning and personalized agents. These external memory systems rely on heuristic rules and system designs to determine how memories are stored and retrieved, representing a distinct approach from intrinsic memory.

A.2 Intrinsic Memory

Past information can also be internalized in model parameters. Context2LoRA studies history-specific low-rank adapters as modular knowledge memory [Back et al., 2026], following the low-rank adaptation mechanism of Hu et al. [2022]. This offers a persistent parametric representation but requires an optimization procedure to create or update each adapter. MLP Memory [Wei et al., 2026] decouples knowledge storage from the language model decoder by introducing a lightweight, differentiable external MLP module. By imitating a retriever’s behavior over large-scale pretraining corpora, it internalizes non-parametric retrieval patterns into a parametric memory.

Several architectures maintain an explicit latent memory. MemoryLLM adds a fixed-size latent memory pool that self-updates from text [Wang et al., 2024]; M+ augments that design with a co-trained retriever and longer-term store [Wang et al., 2025]; and Larimar supports one-shot knowledge updates through a distributed episodic memory [Das et al., 2024]. Test-Time Training layers make the recurrent hidden state itself a learned model and update it with a self-supervised objective [Sun et al., 2025]. Titans learns a test-time neural memory, and Nested Learning generalizes this view to interacting learning processes at multiple update frequencies [Behrouz et al., 2025b,a]. δ -Mem augments a frozen full-attention backbone with a compact associative state whose readout produces low-rank attention corrections [Lei et al., 2026]. In our evaluation protocol, its released evaluation path is nevertheless context limited: history that exceeds the configured input budget is truncated before inference, rather than processed through a lifecycle in which old KV leaves attention while the auxiliary state persists.³

LiveMem uses the state matrix of an RNN as the memory substrate and maintains the memory state online during inference. It can therefore be viewed as either a parametric method or a form of latent memory. We do not distinguish between these two perspectives here and refer to it simply as intrinsic memory.

³<https://github.com/declare-lab/delta-Mem>.

A.3 Recurrent and Hybrid Sequence Models

Segment recurrence has a long history in Transformer language models. Transformer-XL reuses hidden states from preceding segments as extended context [Dai et al., 2019], whereas Recurrent Memory Transformer passes learned memory tokens between segments and trains the model to control their contents [Bulatov et al., 2022]. Modern subquadratic models provide fixed-size recurrent computation through selective state-space models such as Mamba [Gu and Dao, 2023]. Hybrid architectures combine recurrent and softmax-attention mechanisms: Infini-attention places local masked attention and compressive linear memory in one block [Munkhdalai et al., 2024], while Jamba interleaves Transformer and Mamba layers [Lieber et al., 2024].

Linear attention supplies another direct connection between recurrence and memory. It can be interpreted as a fast-weight programmer with a finite associative matrix, motivating delta-rule updates that overwrite an existing key-value association [Schlag et al., 2021]. DeltaNet provides a parallel training algorithm for this update and studies hybrids with softmax-attention layers [Yang et al., 2024]; Gated DeltaNet combines the delta rule with a decay gate for rapid forgetting [Yang et al., 2025b]; and Kimi Delta Attention adopts finer-grained gating within a layerwise hybrid [Kimi Team, 2025]. GDN2 further separates erase and write controls [Hatamizadeh et al., 2026]. LiveMem uses GDN2 as a parallel *memory branch* in every decoder layer rather than replacing the pretrained attention backbone or pretraining a recurrent-attention hybrid from scratch. Its focus is also post-training: the recurrent capacity is exposed to turnover so that its memory state becomes behaviorally useful after source tokens leave attention.

A.4 Bounded Attention and KV Turnover

KV-cache methods bound active attention without necessarily introducing a carried latent state. StreamingLLM retains recent tokens together with initial attention sinks [Xiao et al., 2024b]; H₂O balances recent entries with attention heavy hitters [Zhang et al., 2023]; and SnapKV uses a prompt observation window to select head-specific KV positions [Li et al., 2024]. InfLLM moves distant blocks to an external context store for relevance-based lookup [Xiao et al., 2024a].

IndexMem is principally a learned KV-cache eviction method: an importance indexer retains selected KV entries exactly, while evicted entries update a state whose residual readout is trained to compensate for attention removed by compression [Yang et al., 2026]. IndexMem employs an indexer to perform query-aware token selection. Similar to the query-conditioned mechanism in MemAgent [Yu et al., 2025a], it uses the given question to determine which tokens are important. However, applying such a mechanism to general-purpose memory introduces additional uncertainty, because future queries are not yet known when information must be committed to memory. IndexMem primarily focuses on query-aware KV compression rather than maintaining a query-independent memory state throughout a lifecycle. Therefore, it addresses a different problem from state continuity.

LiveMem instead targets this setting by maintaining a query-independent memory state during context turnover: its memory state explicitly carries critical information and remains functional during context turnover.

B Reference Results: Under 256K Context Limit

We additionally evaluate a context-limited protocol in which up to 256K tokens remain materialized in the attention context and no pages are released during the request. Inputs that exceed the model budget lose the oldest memory tokens while preserving the recent suffix, query, and generation reserve. This protocol mirrors the operational behavior of the released δ -Mem code, which fills a configured context budget and keeps the recent tail on overflow.

As demonstrated in Table 4, increasing the context limit does not fundamentally alter the overall trend. The conclusions are similar to those in Section 4.2: RAG and Context2LoRA continue to perform well on the tasks to which they are best suited, but remain highly task-specific. The key difference is that LiveMem achieves comprehensive improvements over the baselines on LoCoMo and Long QA tasks, indicating that a larger context limit is particularly beneficial to LiveMem. Overall, LiveMem continues to maintain the leading position with strong and well-rounded performance across tasks.

Table 4: Performance with a 256K materialized-context cap. Overflow is tail-preserving: the oldest memory tokens are removed before inference. This is a context-limited reference rather than a state-continuity test.

	Qwen3-4B	RAG	Recurrent	Context2LoRA	δ -Mem	LiveMem-SFT	LiveMem-RL
Wiki QA							
2Wiki	0.683	0.117	<u>0.775</u>	0.218	0.637	0.771	0.787
2Wiki-MQ	0.511	-	0.204	0.009	0.187	<u>0.625</u>	0.653
Hotpot	0.632	0.399	0.819	0.237	0.590	<u>0.756</u>	<u>0.772</u>
Hotpot-MQ	0.361	-	0.256	0.025	0.144	<u>0.706</u>	0.718
MuSiQue	<u>0.400</u>	0.117	0.483	0.096	0.365	<u>0.362</u>	0.379
MuSiQue-MQ	0.305	-	0.165	0.002	0.201	<u>0.381</u>	0.417
Conversation							
LoCoMo	0.575	0.405	0.175	0.210	<u>0.585</u>	0.554	0.599
LME-s	0.384	0.548	0.386	0.156	0.360	0.422	<u>0.438</u>
FactCons	0.175	0.090	0.100	0.096	0.165	0.168	<u>0.170</u>
TTL							
Banking	0.830	0.740	0.000	0.910	0.860	0.950	<u>0.940</u>
CLINC	0.860	0.660	0.000	0.920	0.850	0.950	0.950
NLU	0.800	0.600	0.010	<u>0.820</u>	0.790	<u>0.820</u>	0.830
TREC-C	0.680	0.720	0.340	0.940	0.690	<u>0.800</u>	0.660
TREC-F	0.460	0.290	0.220	0.870	0.460	<u>0.570</u>	0.510
Redial	<u>0.169</u>	0.069	0.081	0.142	0.172	0.093	<u>0.169</u>
Long QA							
∞ Bench-QA	0.291	0.228	0.316	0.131	0.302	<u>0.407</u>	0.419
EventQA	<u>0.624</u>	0.612	0.447	0.252	0.608	0.515	0.654
NarrQA	0.410	0.233	0.282	0.181	<u>0.411</u>	0.383	0.412

C Infrastructure and State Lifecycle Details

C.1 GDN2 Parameterization and State Geometry

The implementation uses a short causal convolution of width four before the GDN2 query, key, and value projections. For completeness, the single-head state update in eqs. (7) to (9) is equivalent to

$$S_t = (I - k_t(b_t \odot k_t)^\top) \text{Diag}(\exp(g_t)) S_{t-1} + k_t(w_t \odot v_t)^\top. \quad (15)$$

Queries and keys are ℓ_2 -normalized inside the recurrent kernel. The readout $S_t^\top q_t$ passes through a gated RMS normalization and an output projection before it is added to the softmax-attention output.

The Qwen3-4B backbone has 36 layers, 32 query heads, 8 KV heads, and head dimension 128. The memory path uses 32 query/key/value heads of dimension 128 in every layer. Backbone KV projections are repeated across the corresponding query-head groups for initialization and can diverge during post-training. Consequently, each layer and request has a recurrent tensor of shape $32 \times 128 \times 128$ in addition to the short-convolution state. The state using FP32.

The query, key, and value projections of the memory branch are initialized from the matching backbone projections. The decay, erase, write, output-gate, and short-convolution parameters are initialized independently, and the final memory projection is initialized to zero.

C.2 Chunk-Turnover Training with FlexAttention

Given chunk spans $[u_i, v_i)$, the canonical policy appends each non-sink chunk to a live queue and removes the oldest entries while either the chunk count or token budget is exceeded. The newest chunk is never removed at its arrival step. The policy returns an eviction step for every chunk, which is expanded into the per-token $c(i)$ and $e(i)$ fields used by eq. (10). SFT examples use dataset-defined semantic or fixed-token chunks; serving and RL recomputation use deterministic fixed-stride chunks. Both instantiate the same oldest-first state transition.

During SFT, FlexAttention [Dong et al., 2024] combines the turnover predicate with causality and, for packed data, a sequence-identity predicate. The GDN2 chunk kernel receives cumulative sequence

boundaries and starts a zero state at each packed-example boundary. Thus a 64K-token packed row can be evaluated in one differentiable forward pass without allowing either attention or recurrent state to cross between constituent examples. Only answer tokens contribute to eq. (11).

RL rollouts use a length-dependent fixed-stride policy. The trainer derives the same per-token chunk and eviction fields from the rollout tokens when it recomputes log probabilities, so the policy update sees the attention visibility used to generate the response. Chunk boundaries are multiples of the 32-token serving page size, which makes token-level mask changes and page release agree exactly.

Let L_p denote the length of the fully templated prompt and let M be the generation allowance in a rule-table row. The rollout server and training recomputation select the first row of Table 5 satisfying $L_p + M$ in the indicated half-open interval. The system-instruction prefix is rounded up to a 32-token page boundary and retained as a sink; all subsequent chunks follow the selected stride, including during generation. For determinism, even a partially filled frontier chunk is charged at its full chunk size when enforcing the live-token budget.

Table 5: Fixed-stride turnover parameters used for RL rollout serving and policy recomputation. All quantities are tokens.

Range of $L_p + M$	Chunk size	Live-token budget	M
[1K, 2K)	64	512	256
[2K, 8K)	256	1,024	512
[8K, 16K)	512	2,048	1,024
[16K, 32K)	512	4,096	2,048
[32K, 64K)	512	8,192	4,096

Benchmark inference uses the same oldest-first transition and page-alignment rules, while overriding the chunk size to 1,024 and the live-token budget to 8K or 32K to realize the fixed evaluation conditions in Section 4.1. Samples outside the RL table are filtered during training; serving clamps an out-of-range request to the nearest row rather than changing the lifecycle semantics.

C.3 Serving

The serving implementation follows paged KV management [Kwon et al., 2023] and maintains two pieces of per-request state. The ordinary attention manager holds KV pages for the instruction sink and recent live chunks. A separate paged slot holds the convolution state and GDN2 matrix state for every memory-augmented layer. At each turnover boundary, complete middle KV pages are returned to the allocator and omitted from the attention read set; the memory slot is unaffected. Prefill slices are clamped to the next chunk boundary so a scheduler batch cannot apply a future turnover state to earlier tokens in the same slice.

For a prefill or decode step, the engine gathers the request’s recurrent state, runs the same GDN2 update as training, and scatters the final state back to its slot. Requests without an initial slot read a zero state. When generation finishes, the scheduler removes the request’s turnover record and the state manager releases its recurrent slot. This explicit lifecycle implements continuity within a stream while preventing accidental state leakage between requests. Learned decay and erasure in eq. (15) operate within that lifecycle; whole-state reset is a separate systems operation.

C.4 Post-Training Recipe

SFT uses fixed 64K-token packs in two stages. The first stage runs for 100 steps on long-form instruction and document data using LongAlign, LongAlpaca, LongMIT, and Long-Data-Collection [Bai et al., 2024, Chen et al., 2024, 2025, Together AI, 2023], with a 50-step learning-rate warmup followed by a constant rate. The second runs for 500 steps on a mixture of MuSiQue, 2WikiMultihopQA, NarrativeQA, Qasper, long-form instruction data, AG News, and DBpedia [Dasigi et al., 2021, Zhang et al., 2015]. We use an answer-token cross-entropy objective, AdamW with weight decay 0.01, gradient clipping at 1.0, and a peak learning rate of 5×10^{-5} . In the second stage, the rate remains constant for 50 steps and then follows a cosine schedule. LoRA dropout is zero.

SFT is run in BF16 on two nodes with eight A800-80GB GPUs each. Each device processes one 64K pack per step, giving a global batch of 16 packs, or approximately one million tokens per optimizer

step. We use gradient checkpointing, distributed data parallelism, and ZeRO-1 optimizer-state sharding. The GDN2 recurrent state remains FP32.

The RL stage uses groups of eight responses and the reward described in Section 3.3. We use group-relative advantages, no KL penalty, lower and upper clipping ratios of 0.20 and 0.28, token-mean loss aggregation, an actor learning rate of 10^{-5} , and dynamic sampling that discards groups with zero accuracy variance. Training uses FSDP2 actors, asynchronous vLLM rollouts, two eight-GPU trainer nodes, one eight-GPU rollout node, and a separate two-GPU tensor-parallel judge service. Per-request generation limits are coupled to the turnover bucket so generated tokens cannot silently exceed the context policy used for their prompt.

D Additional Experimental Details

D.1 Evaluation Dataset Construction

2WikiMultiHopQA, HotpotQA, and MuSiQue are knowledge-based question-answering datasets constructed from Wikipedia-derived documents [Karpukhin et al., 2020], and they are all multi-hop QA datasets. These datasets evaluate the performance of memory mechanisms in multi-hop knowledge QA scenarios. Each instance in HotpotQA and 2WikiMultiHopQA consists of 10 documents, which include both relevant and irrelevant documents, with the evidence required to answer the question distributed across the relevant documents. MuSiQue is similar, except that it consists of 20 documents per instance. For the MQ setting, each instance is formed by packing together 5 randomly sampled instances from the corresponding dataset (10 for 2WikiMultiHopQA), meaning that the model must answer all questions simultaneously based solely on a memory summary it has condensed from the packed data. For each of 2WikiMultiHopQA, HotpotQA, and MuSiQue, we evaluate a fixed seed-0 sample of 2,000 single-question instances and 400 multi-question instances. For the MQ setting, all questions are answered at once after the memory is processed.

LoCoMo, LongMemEval, and FactConsolidation are all dialogue-based QA datasets that evaluate the capability of memory mechanisms in realistic dialogue scenarios. We use all 500 questions in LongMemEval-S, all questions associated with the ten released LoCoMo conversations, and all questions in MAB FactConsolidation.

The TTL suite is based on existing text-label pairs and requires labeling the input text-label pairs. It demands that the memory mechanism generalize patterns and distill experience from past text-label pairs, rather than simply memorizing the text verbatim. We directly use the MAB’s TTL episodes, and follow its evaluation settings.

The LongQA suite focuses on completing question-answering tasks over long input texts, where the information required to answer the questions is scattered throughout the lengthy text. It requires the memory mechanism to possess the ability to gather such distributed information and answer questions when faced with extremely long texts. NarrativeQA is sampled by document: we select 120 test documents with seed 0 and evaluate every retained question for those documents.

Open-ended QA and conversation answers are evaluated by a Qwen3.6-35B-A3B judge prompted with the question, reference answers, and prediction and asked for a binary correctness decision. The judge uses greedy decoding with thinking disabled. EventQA and the five TTL classification sources use normalized exact match. ReDial uses recall@5 after resolving the released entity identifiers to movie names.

D.2 Context Accounting and Generation

Every method receives the same system instruction, task template, and answer format. When an input exceeds a direct-context cap, the instruction and query are retained and the memory portion is truncated from the oldest end. The 256K condition additionally reserves the task-specific generation allowance and 1,024 tokens for chat-template overhead before allocating the remaining budget to memory. The bounded direct-context controls expose the corresponding recent 8K or 32K suffix; LiveMem instead scans up to 256K input tokens while maintaining only the stated live KV budget.

Except for separately identified official-protocol checks, decoding uses temperature 0.7, top- p 0.8, and top- k 20. Single-question requests permit up to 1,024 generated tokens and multi-question requests

up to 8,192. Prompts that contain multiple questions are never shortened by dropping questions; the memory prefix is the only truncation target.

D.3 Baseline Implementation Details

For the evaluation of all approaches, we construct inputs in the format of [system prompt, user prompt (memory documents, question), assistant answer]. For Qwen3-4B, when the context exceeds the window limit, we retain the system prompt and perform head truncation only on the memory documents. For δ -Mem, we adopt its TSW setting. Although its paper contains claims that are inconsistent with its code behavior, we choose to strictly follow its code behavior, i.e., directly discarding the portion that exceeds the context window limit. For Context2LoRA, for each input memory instance, it pre-constructs multiple QA pairs and then uses these QA pairs to train a LoRA module (rank=4, alpha=8, lr= 5×10^{-4}). During evaluation, it leverages the memories stored in the LoRA parameters to answer questions. We apply a separate LoRA module for each dataset. For TTL, since it inherently consists of text-label pairs and is not suitable for constructing QA pairs, we choose to follow Context2LoRA’s original assumption about memory, and directly fine-tune LoRA using these text-label pairs. This may be the reason why Context2LoRA performs particularly well on TTL. For the RAG method, we use Qwen3-Embedding-0.6B as the vector model and build a vector retrieval environment over the memory documents for retrieval and recall. For datasets with fewer than 20 memory documents, we use top-1; for others, we use top-3. If the input does not have a strict partitioning into memory documents (e.g., Long QA), we split it into chunks of 512 tokens each. Since RAG’s top-k fundamentally cannot meet the evidence requirements of the MQ task, we omit RAG’s performance on MQ. For Recurrent, we draw on MemAgent’s setting of maintaining a memory context through recurrent cycles. We set the upper limit of the memory context to 8k tokens, so the maximum length of memory text it can process at one time is 16k tokens. The model is required to extract important information from the memory documents and, after processing is complete, answer questions based on the memory context.

E Limitations

E.1 A Lossy State Is Not an Exact Archive

The task variants in this section follow the RULER long-context evaluation suite [Hsieh et al., 2024].

Table 6: Needle-in-a-haystack accuracy with full and bounded active contexts. The bounded-context result shows that the current LiveMem model does not reliably recover arbitrary fine-grained needles from its recurrent state.

	S-NIAH-2	S-NIAH-3	MK-NIAH-1	MQ-NIAH
<i>256k</i>				
Qwen3-4B	1.00	1.00	0.97	0.97
δ -Mem	1.00	1.00	0.97	0.97
LiveMem	1.00	0.86	0.99	0.97
<i>32k</i>				
Qwen3-4B	0.19	0.18	0.21	0.23
δ -Mem	0.19	0.18	0.21	0.23
LiveMem	0.19	0.18	0.21	0.23

The results are shown in table 6. With the 256K materialized context, where the needles remain directly addressable through attention, all systems are near ceiling on most variants; LiveMem adds no systematic benefit. Under the 32K bounded context, all three systems obtain the same low scores. The current LiveMem memory state therefore does not reliably reconstruct arbitrary token-level needles after their KV entries have been released.

This is consistent with the intended role of the memory state, but it remains a real limitation. NIAH asks for lossless archival recall of sparse strings whose later relevance is not predictable from their content. LiveMem instead compresses an indefinitely growing stream into a fixed-size, lossy

memory state and trains that state to preserve features useful for subsequent behavior. The evidence-conditioned LongMemEval analyses in figs. 3 and 4 show that this state can carry task-relevant influence across turnover; they do not imply that it stores every past token verbatim.

The distinction from query-aware KV retention is important here. IndexMem’s long-prefill indexer can score the prompt after a terminal query is present and keep the query-relevant needle exactly in attention [Yang et al., 2026]. That is a natural advantage on NIAH, but it does not require a latent state to carry information whose future relevance was unknown at eviction time. In a continuing stream, no fixed KV budget can retain every token that might become a future needle. Applications requiring exact archival recall should therefore combine LiveMem with retrieval or an external store; these mechanisms provide addressable history access while LiveMem provides state continuity.

E.2 Finite Positional Horizon

LiveMem’s recurrent memory state and active KV budget are independent of the number of previously processed tokens, but the current system is not literally unbounded. Its Qwen3 backbone uses rotary position encodings [Su et al., 2023] with a configured maximum position of 262,144 tokens [Yang et al., 2025a]. KV eviction preserves the original absolute position indices of retained tokens, so continuing past the trained and configured range requires positional extrapolation whose quality is not guaranteed. The experiments therefore process at most 256K input tokens even though the memory state itself could continue updating.

Position-free attention offers a plausible route around this architectural ceiling. Kimi Linear applies NoPE to its full-attention layers and delegates positional and recency information to recurrent KDA layers, demonstrating the design at 48B total parameters and a 1M-token context [Kimi Team, 2025]. Kimi K3 adopts a KDA-based hybrid architecture into a publicly deployed 2.8T-parameter model with a 1M-token context [Moonshot AI, 2026]. This provides deployment-scale evidence that the direction is practical. Adapting LiveMem to a NoPE or otherwise length-generalizing backbone remains as future work.