

Arbitrage-Aware Multi-Step Forecasting of Implied Volatility Surfaces

Modelling Surface Trajectories Using Latent Diffusion

Dominik Manuel Buchegger[✉]

University of St.Gallen
St.Gallen, Switzerland

Lukas Gonon

University of St.Gallen
St.Gallen, Switzerland

Abstract

Implied volatility surfaces summarise the option market and are central to many financial applications. Forecasting their future evolution requires modelling two-dimensional geometry, temporal dependence, and predictive uncertainty while preserving economic admissibility. We propose a conditional latent diffusion framework for generating joint 30-step trajectories of implied volatility surfaces and underlying returns. An arbitrage-aware autoencoder learns a low-dimensional surface representation, while the diffusion model captures the conditional joint evolution. Evaluated on SPX surfaces, the framework generates realistic probabilistic multi-step scenarios while also outperforming the persistence benchmark in point forecasting.

Keywords

Implied volatility surfaces, probabilistic forecasting, latent diffusion models, trajectory generation, static arbitrage, option markets

1 Introduction

The *implied volatility surface (IVS)* summarises option-implied uncertainty across moneyness and maturity and is a core input to pricing, hedging, and risk management. Although the shape of the IVS varies across assets and over time, three properties frame the modelling problem. First, an admissible IVS must satisfy shape restrictions that rule out *static arbitrage*. Second, a forecast of the *IVS trajectory*, the surface’s evolution over multiple days, must reproduce the realised dependence structure. Third, the IVS is generally *persistent*, so its current state already provides a strong prediction of its future evolution. A useful model must demonstrate value beyond carrying the most recent surface forward.

Together, these properties make point-forecast accuracy insufficient as the sole modelling target. A model that merely copies the current IVS can achieve low errors, especially at short horizons, while learning little about the conditional law of future surface movements. A useful forecasting model must instead respect the economic structure of option markets, generate informative trajectories with realistic uncertainty, and demonstrate predictive value relative to persistence rather than merely visual plausibility or realistic unconditional sampling.

Existing work does not jointly address these requirements. In particular, probabilistic forecasting of complete IVS trajectories has received almost no attention. We address this gap with a two-stage *latent diffusion* model. An *autoencoder* compresses daily surfaces into latent codes, while its decoder is regularised towards no-static-arbitrage consistency, making admissibility a property of the reconstruction map rather than of a parametric family or a

post-processing step. On these latent codes, a conditional *diffusion* model generates the next 30 days of surfaces jointly with daily equity returns in a single non-autoregressive pass, conditional on the recent surface history. This separation assigns representation learning and economic regularisation to the autoencoder, and the conditional law over future paths to the diffusion model.

Our contribution is twofold. First, we provide a transparent, reproducible protocol for constructing IVS forecasting datasets from *OptionMetrics* data on *WRDS*, allowing licensed users to recreate a common evaluation setting. Second, we develop a latent diffusion model for conditional, multi-step generation of joint IVS–return trajectories and evaluate it systematically against persistence. Code is available on [GitHub](https://github.com/DomBBB/implicit-volatility-trajectories-using-latent-diffusion)¹. Together, the data protocol, our model, and the persistence baseline constitute a first step towards a reproducible benchmark for a forecasting problem that currently lacks one.

The results support the model primarily as a probabilistic scenario generator and multi-step trajectory model, rather than as a one-day point forecaster. Generated surfaces preserve the dominant smile and term-structure geometry, recover the realised level, skew, and curvature factors of surface movements, and reproduce the negative return–volatility dependence particularly closely at weekly-to-monthly horizons. These trajectories improve substantially upon persistence, while the generated surfaces remain essentially free of static arbitrage. The principal limitation is underdispersion: predictive intervals widen with the horizon but remain too narrow, indicating that the model captures the directions and dependence of future movements more accurately than their amplitude. Beyond this distributional performance, the predictive mean also contains information not available from persistence. Persistence remains superior at the one-day horizon, but the model overtakes it from approximately weekly horizons onward. Gains are strongest at short maturities and in the wings, whereas the stable long-maturity centre remains difficult to improve upon.

2 Related Work

Representation and admissibility. Implied volatility surfaces are empirically low-dimensional, with level, skew, and curvature explaining most daily variation [13]. Useful representations must also respect (static) no-arbitrage restrictions [31]. Learnt models address this either by operating within an admissible parametric family [27] or by combining a flexible representation with soft arbitrage penalties [1, 37]. SANOS provides a recent nonparametric alternative that is arbitrage-free by construction [6].

¹<https://github.com/DomBBB/implicit-volatility-trajectories-using-latent-diffusion>

Dynamic surface forecasting. Most prior machine-learning approaches produce deterministic single-step forecasts. Zhang et al. [39] compress the surface, forecast its low-dimensional features, and reconstruct. Cao et al. [7] regress expected IVS changes on returns, moneyness, maturity, and VIX. Neither yields predictive uncertainty. Generative work began without dynamics. VAEs learn latent spaces from which realistic surfaces can be decoded [2] or learn the parameter space of an SDE family to obtain admissibility by design [27], an approach extended to dynamic neural-SDE market models [12]. Dynamics also appear in one-step generative approaches: Vuletić and Cont [35] generate surfaces jointly with the underlying (controlling arbitrage through a smoothness penalty and reweighting) and Chen et al. [9] generate surfaces from historical sequences using CVAE-LSTMs to condition on any set of historical data.

Existing multi-step methods remain mostly deterministic, e.g., ConvLSTMs applied to discretised IV values without arbitrage constraints [25], SVI coefficient dynamics with admissibility resting on the parametric family [4], and functional autoregression on surface time series [10]. Our closest comparator is Choudhary et al. [11], who combine functional PCA with neural SDEs to generate surfaces jointly with price paths and assess admissibility empirically.

DYSANOS by Buehler et al. [5] (currently available only as a conference presentation) takes a complementary route to dynamic generation by encoding arbitrage-free surfaces in a low-dimensional state (SANOS) and modelling this state. Its objective is generative market simulation rather than conditional forecasting, but it provides a related alternative for combining low-dimensional representations with learnt dynamics.

Latent diffusion. Existing diffusion applications to IVSs are surface completion and static generation of synthetic surfaces [21, 24], exogenous-shock learning [33], and, closest to us, one-day-ahead forecasting with an SNR-weighted arbitrage penalty [22]. However, these applications always operate directly on surfaces and are always static or single-step.

Persistence rarely confronted. A rarely confronted difficulty runs through the forecasting literature: daily IVSs are highly persistent. Consequently, low errors and visually plausible forecasts may reflect little more than copying the latest surface. This risk is especially acute for models conditioned primarily on the current surface. Yet few forecasting studies thoroughly evaluate against a persistence baseline, and fewer beat it convincingly.

3 Theoretical Background

Options and the Implied Volatility Surface. Options grant their holder the right, but not the obligation, to buy (a *call*) or sell (a *put*) an underlying in the future on fixed terms, notably the transaction price (*strike* K) and the contract’s remaining lifetime in years (*time to maturity* τ). Options are traded for different reasons, including speculation and hedging against future uncertainty. Consequently, there needs to be a way to determine option values, which requires a model for how uncertainty in the underlying’s price process up to maturity propagates into value. The *Black–Scholes–Merton (BSM)* model [3, 26] supplies one under a stylised set of assumptions. Of the inputs to these call (C_t^{BSM}) and put (P_t^{BSM}) formulas, all are

contractual, observed, or estimated – except volatility σ . Volatility governs the uncertainty of the underlying over the option’s remaining life and is unobservable *ex ante*. However, with prices C_t, P_t observed on the market, the (*BSM*) *implied volatility (IV)* $\hat{\sigma}$ is defined as the volatility value that reproduces the observed market price, e.g., $C_t^{BSM}(\hat{\sigma}) = C_t$.

Under BSM, σ is constant across all options on a given underlying, so each option should imply the same IV – the market’s assessment of future uncertainty over the option’s life. Empirically, however, IV varies with both strike and maturity. The resulting function, $\Sigma : (K, \tau) \mapsto \hat{\sigma}(K, \tau)$, is the *implied volatility surface (IVS)*. Its non-flatness reflects the failure of BSM’s constant-volatility assumption to explain the complete option-price cross-section. Nevertheless, BSM IV remains the standard convention in which option prices are quoted and compared across strikes, maturities, and dates.[16]

Surface construction and static arbitrage. The IVS is continuous, whereas markets provide only a finite irregular collection of quotes. These quotes are additionally affected by bid–ask spreads, non-synchronous recording, and occasional errors. Constructing a surface therefore requires interpolation, smoothing, and extrapolation across unobserved strike–maturity combinations.[15]

A central requirement is the absence of *static arbitrage*. Unlike dynamic arbitrage, static arbitrage can be identified from the contemporaneous option-price cross-section without specifying a stochastic model for the underlying [8]. It therefore provides a model-independent notion of internal consistency for a fitted or generated surface, and translates into shape constraints on the IVS, specifically on the *time-scaled IVS (t-IVS)* in *log–forward–moneyness* reparametrisation, $\Xi(m, \tau) = \Sigma(m, \tau) \sqrt{\tau}$. The six model-independent no-static-arbitrage conditions² are

- | | |
|----------------------------|---|
| C1) Smoothness | $\forall \tau > 0 : \Xi_t(\cdot, \tau)$ twice differentiable |
| C2) Positivity | $\forall \tau > 0, \forall m : \Xi > 0$ |
| C3) Durrleman’s condition | $\forall \tau > 0, \forall m : \left(1 - \frac{m \partial_m \Xi}{\Xi}\right)^2 - \frac{1}{4} \Xi^2 (\partial_m \Xi)^2 + \Xi \partial_{mm}^2 \Xi \geq 0$ |
| C4) Monotonicity in τ | $\forall m : \Xi(m, \cdot)$ non-decreasing |
| C5) Large moneyness | $\forall \tau > 0 : \lim_{m \rightarrow \infty} d_+(m, \Xi) = -\infty$ |
| C6) Value at maturity | $\forall m : \Xi(m, 0) = 0$ |

Condition C3 excludes *butterfly arbitrage*, condition C4 excludes *calendar–spread arbitrage*, and condition C5 concerns the asymptotic large-moneyness behaviour [31]. In the bounded empirical domain studied in our work, only C1–C4 apply, since C5 and C6 concern behaviour outside its bounds.

4 Methodology

4.1 Data

We construct daily IVSs from OptionMetrics *IvyDB US* end-of-day SPX option quotes obtained through WRDS [28, 36]. The sample

²Stated for zero rates and dividends; the functional forms are unchanged for non-zero parameters in log–forward–moneyness [1].

covers January 2000 to August 2025. We apply *operator deep smoothing* [37] for each date: a *pretrained*³ *graph neural operator* (GNO) maps the irregular (BSM) IV quote set to a smooth, essentially static–arbitrage-free surface on prescribed coordinates. Our initial coordinate grid is $\mathcal{G}_{\text{orig}} = \mathcal{M} \times \mathcal{T}$, $\mathcal{M} = \{-1.5, -1.4, \dots, 0.5\}$, $\mathcal{T} = \{1/12, \dots, 12/12\}$. We retain 170 coordinates that lie within the domain supported by the pretrained operator ($(\sqrt{\tau} \in [0.01, 1], m/\sqrt{\tau} \in [-1.5, 0.5])$), yielding identical grid availability on every date,

$$\mathcal{G}_{\text{obs}} = \{(m, \tau) \in \mathcal{G}_{\text{orig}} \mid \omega(m, \tau) = 1\} \subseteq \mathcal{G}_{\text{orig}},$$

where $\omega(m, \tau) \in \{0, 1\}$ denotes the observation indicator on $\mathcal{G}_{\text{orig}}$.

To provide the diffusion model with information about recent underlying dynamics, the time-scaled surface (t–IVS) history is augmented with SPX log returns and rolling summaries of return levels and return volatility. The complete surface-construction pipeline is provided in the accompanying code repository.

The resulting dataset contains 6429 daily t–IVSs and associated conditioning variables. We split it chronologically into 5511 *training* observations through 2021, 251 *validation* observations from 2022, and 667 *test* observations from 2023 onward.

4.2 Latent Surface Representation

First, we transform each daily t–IVS as $y_i := \log \Xi_i$ and standardise it. Modelling y_i^{norm} would require the diffusion model to learn dynamics in a high-dimensional and strongly constrained space. We therefore compress each y_i^{norm} into an eight-dimensional latent state using a deterministic, RAE-inspired [17] autoencoder. Recent work on the role of traditionally used variational autoencoders in latent diffusion suggests that diffusion may benefit from different autoencoder designs, including deterministic variants with additional architectural constraints and regularisations.

Architectural choices for the autoencoder matter because they affect reconstruction accuracy and the latent space. For our task, the autoencoder must construct a latent that preserves enough information to reconstruct IVSs while being sufficiently regularised so that changes in latent space are decoded into admissible surfaces. We use an *RAE-inspired* architecture that is deterministic and shapes the latent space through explicit and implicit regularisation.

Encoder. The encoder is a residual convolutional network [19] illustrated in Figure 1. It receives the normalised log surface y_i^{norm} and the common observation mask as two input channels and outputs an eight-dimensional latent code z_i .




Figure 1: Encoder: mapping the IVS to a latent state.

³https://github.com/DomBBB/implied-volatility-trajectories-using-latent-diffusion/blob/main/operator-deep-smoothing/volatility_smoothing/train/store/9448705/checkpoints/checkpoint_final.pt

Decoder. The decoder is a coordinate-based neural field [38], illustrated in Figure 2. It reconstructs the normalised log–t–IVS $\hat{y}_i^{\text{norm}}$ continuously for each queried coordinate $c = (m, \tau)$.




Figure 2: Decoder: mapping m– τ coordinates to IV values.

Training objective. We write the terms for a minibatch $\mathcal{B}$. The *reconstruction term* is the masked mean squared error,

$$\mathcal{L}_{\text{rec}} = \frac{\sum_{i \in \mathcal{B}} \sum_{(m, \tau) \in \mathcal{G}_{\text{orig}}} \omega(m, \tau) (\hat{y}_i^{\text{norm}}(m, \tau) - y_i^{\text{norm}}(m, \tau))^2}{\sum_{i \in \mathcal{B}} \sum_{(m, \tau) \in \mathcal{G}_{\text{orig}}} \omega(m, \tau)}.$$

The *latent regularisation term* regularises the representation directly,

$$\mathcal{L}_{\ell_2} = \frac{1}{|\mathcal{B}| \dim(z_i)} \sum_{i \in \mathcal{B}} \|z_i\|_2^2.$$

The two *no-static–arbitrage terms* guide the model. Smooth operations in the architecture make the decoder twice differentiable (C1); the logarithmic surface parametrisation guarantees positivity (C2). Butterfly (C3) and calendar–spread (C4) conditions are evaluated on $\mathcal{G}_{\text{dense}}$, a denser set that is useful because the decoder represents a continuous coordinate-based surface.⁴ In log t–IV parametrisation, we have $0 \leq (1 - my_m)^2 - \frac{1}{4}e^{4y}y_m^2 + e^{2y}(y_m^2 + y_{mm}) =: l_{\text{but}}$ and $0 \leq y_\tau =: l_{\text{cal}}$. Negative values of l_{but} and l_{cal} correspond to violations and are therefore penalised as follows, for $\text{cond} \in \{\text{but}, \text{cal}\}$:

$$\mathcal{L}_{\text{cond}} = \frac{1}{|\mathcal{B}| |\mathcal{G}_{\text{dense}}|} \sum_{i \in \mathcal{B}} \sum_{(m, \tau) \in \mathcal{G}_{\text{dense}}} [\max\{0, -l_{\text{cond}, i}(m, \tau)\}]^2.$$

Optimisation. The autoencoder is trained by minimising $\mathcal{L} = \mathcal{L}_{\text{rec}} + \lambda_{\ell_2} \mathcal{L}_{\ell_2} + \lambda_{\text{but}} \mathcal{L}_{\text{but}} + \lambda_{\text{cal}} \mathcal{L}_{\text{cal}}$, with $\lambda_{\ell_2} = 10^{-4}$, $\lambda_{\text{but}} = 10^{-3}$, $\lambda_{\text{cal}} = 10^{-4}$. Architectural choices are selected on the validation set. The final autoencoder is trained on the combined training and validation sample for 300 epochs. Weight decay acts as parameter-space regularisation, providing an explicit regularisation mechanism of the RAE [17] framework, complemented by implicit regularisation associated with CNNs and gradient-based optimisation.

4.3 Conditional Latent Trajectory Diffusion

The autoencoder converts the daily surfaces into latent states z_i that are then used to construct trajectories. We model their future evolution with a conditional latent diffusion model, avoiding direct generation in the high-dimensional surface space [20, 30].

At forecast origin t , the diffusion model observes $S = 21$ trading days and jointly generates the next $H = 30$ latent surface states and daily returns. The time-series diffusion literature provides different strategies for achieving temporal and conditional coherence, e.g., [14, 23, 29, 32]. We formulate our task as a one-sided inpainting problem, asking the model to plausibly extend observed trajectories.

⁴ $\mathcal{G}_{\text{obs}} \subseteq \mathcal{G}_{\text{dense}} = \{(m, \tau) \in [-1.5, 0.5]_{0.02} \times [\frac{1}{12}, 1]_{0.02}\}; [\cdot]_{0.02}$ denotes the discretised interval with step size 0.02; $\times$ indicates restriction to observation bounds.




Figure 3: Transformer denoiser for joint latent surface and return continuation.

Trajectory representation. We represent each latent by *anchored displacements*, $\Delta^{\text{anc}} z_s = z_s - z_{t_0}$, with $t_0 = t - S + 1$. Using a common anchor places observed and future trajectories in the same coordinate system while separating evolution from absolute latent levels. Persistence of the latest observed state corresponds to future anchored displacements remaining at their value at the forecast origin. This aligns the training target with the object of interest: conditional departures from persisting the latest observed state.

The clean diffusion target $x_0 = [\Delta^{\text{anc}} z_{t+1:t+30}^{\text{norm}}, \text{LogR}_{t+1:t+30}^{\text{norm}}]$ is generated conditional on $C_t = (\Delta^{\text{anc}} z_{t-20:t}^{\text{norm}}, z_t^{\text{norm}}, \text{LogR}_t^{\text{norm}}, c_t^{\text{norm}})$, where c_t contains 27 contemporaneous surface and return-state variables. All targets and conditioning variables have been standardised (and some transformed) using training statistics only.

Forecast origins are retained only when their full H -day target is within the data split. This yields 5461 *training*, 221 *validation*, and 637 *test* trajectories. After model selection, the final diffusion model is refitted on 5712 trajectories constructed from the combined *training and validation* period.

Continuation denoiser. The denoiser is a Transformer-style [34] sequence model, illustrated in Figure 3. The historical path is embedded as anchored-displacement history tokens, while the future target is embedded as future tokens containing anchored displacement and returns; positional embeddings place both on a common continuation timeline. The sequence is processed by self-attention blocks to jointly predict the denoising targets for all 30 future steps.

Diffusion training. The forward process gradually corrupts the sequence over 500 diffusion steps using a linear variance schedule ($\beta_1 = 10^{-4}, \beta_2 = 10^{-2}$). Rather than predicting x_0 or ϵ directly, we use v -parameterisation and minimise the mean squared error $\mathcal{L}_{\text{diff}} = \mathbb{E} [\|\hat{v}(x_k, k, C_t) - v_k\|_2^2]$ between the denoiser output and the v -target. The final model is trained for 100 epochs.

Mean-scaling gate. The predictive mean of the diffusion distribution tended to overstate movement on the validation set. This may reflect the difficulty of learning a single rule over a long

historical sample with changing market regimes and an increasingly efficient option market. We therefore freeze the trained diffusion model and subsequently fit a small horizon-specific scaling gate on the same data. For horizon h , let $\hat{z}_h^{\text{mean}}$ denote the mean of generated forecast samples. The gated mean is $\hat{z}_h^{\text{scaled}} = \hat{z}^{\text{persistence}} + \hat{\lambda}_h (\hat{z}_h^{\text{mean}} - \hat{z}^{\text{persistence}})$. The gate is trained for 15 epochs by minimising the mean squared error between the scaled latent forecast and the realised latent code. Its average fitted value is approximately 0.80. Instead of applying the gate to each path, we preserve the sampled variability by only shifting the predictive mean and adding back the original residuals. The gate therefore acts as a market-dependent correction to the forecast magnitude.

Trajectory generation. At inference, the complete 30-day continuation is generated from Gaussian noise conditional on C_t . For each test origin, we generate joint latent–return trajectories, $\hat{\Delta}^{\text{anc}} z_{t+1:t+30}^{\text{norm}}$ and $\hat{\text{LogR}}_{t+1:t+30}^{\text{norm}}$. The generated variables are de-standardised to $\hat{\Delta}^{\text{anc}} z_{t+1:t+30}$ and $\hat{\text{LogR}}_{t+1:t+30}$, and the anchored displacements are converted back to latent levels according to $\hat{z}_{t+1:t+30} = \hat{\Delta}^{\text{anc}} z_{t+1:t+30} + z_{t_0}$. After applying the gate, each latent trajectory is passed through the decoder to obtain a corresponding 30-day t-IVS trajectory.

5 Results

The final pipeline is trained on the combined training and validation data and evaluated once on the held-out test set. For each forecast origin, we generate 1000 30-day trajectories and corresponding returns using DDPM [20] sampling.

5.1 Generative Realism and Economic Admissibility

Surface geometry. Figure 4 compares realised and model-mean t-IVSs averaged over all test origins and horizons. The model closely reproduces the dominant smile and term-structure geometry. Residuals are small but structured: the forecast mildly attenuates parts of the left wing and elevates the central region, particularly at

longer maturities. The same pattern is stronger in autoencoder-only reconstructions, indicating that much of the bias originates in the representation rather than the diffusion dynamics. However, a more expressive autoencoder introduces additional difficulty for the diffusion model and does not necessarily improve the full pipeline.




Figure 4: Average realised t-IVS, model-mean forecast, and signed residual over all test origins and forecast horizons.

Quantitative descriptors support these visual results. The global IV level is reproduced closely, while the remaining discrepancies concern local shape. Moreover, these biases are small relative to variation across forecast origins, suggesting that the model captures the dominant surface geometry while smoothing some local movements. **Figure 5** shows an illustrative distribution. Generated paths fluctuate coherently around the predictive centre, remain within economically plausible ranges, and produce widening intervals for level, skew, term structure, and returns.




Figure 5: Illustrative generated surface/return trajectories.

Low-dimensional surface dynamics. We fit a principal-component basis to realised log t-IVS increments in the test set and project generated increments onto that basis.⁵

⁵Using a common basis avoids comparing unstable principal components estimated from separate samples.

Table 1 shows that surface movements are low-dimensional: the first three components explain 91.76% of realised increment variance. Generated loading directions align⁶ closely with the realised directions. The lower PC3 alignment is unsurprising given PC3's substantially smaller variance contribution.

Table 1: Principal components of realised log t-IVS increments and generated-loading alignment.

PC	Variance share	Cum. share	Alignment	Interpretation
PC1	83.95%	83.95%	0.996	Level factor
PC2	5.41%	89.35%	0.962	Skew factor
PC3	2.41%	91.76%	0.831	Curvature factor

Table 2: Correlations between realised-PCA scores and surface descriptors. Entries report realised/generated correlations, with generated values averaged across sample paths.

PC	Average IV	3M skew	3M curvature	Interpretation
PC1	+0.977/+0.963	-0.129/-0.238	-0.734/-0.680	Level
PC2	-0.117/+0.034	-0.748/-0.712	-0.446/-0.543	Skew/tilt
PC3	+0.086/-0.031	+0.363/+0.546	+0.384/+0.615	Curvature/bend

The loading surfaces in **Figure 6** provide clear economic interpretations. PC1 is broadly same-signed and captures level movements. PC2 changes sign across moneyness. PC3 bends around the central region. The model therefore reproduces both the concentration of variance in a few factors and the principal directions of surface deformation. Descriptor correlations at $h = 21$, reported in **Table 2**, strengthen these interpretations. PC1 is strongly associated with average-IV changes, PC2 with skew, and PC3 with curvature.




Figure 6: Loadings of the first three principal components of realised log t-IVS increments.

The main discrepancy concerns amplitude. Generated factor dispersion is close to realised dispersion at $h = 1$, but becomes increasingly understated at longer horizons. For PC1, generated and realised standard deviations are 0.669 and 0.923 at $h = 21$, and 0.769 and 1.021 at $h = 30$. Thus, the model captures the dominant modes of movement more accurately than their longer-horizon magnitude.

Joint dependence and return-surface dynamics. **Figure 7** compares realised and generated dependence among economically interpretable state variables at $h = 21$. The difference matrix is relatively muted from $h = 5$ onwards, indicating that the broader dependence structure is captured well.

⁶As a robustness check, separate PCA bases are fitted to generated paths and aligned with the realised loadings using the absolute inner product.




Figure 7: Realised correlations, mean generated correlations, and their difference at forecast horizon ($h=21$).

The largest discrepancies concern the magnitude of return-surface dependence. Table 3 shows that the model reproduces its negative sign throughout, but understates the immediate leverage relation. At $h = 1$, the realised and generated correlations differ substantially, but agreement improves at multi-day horizons. The model therefore captures the main negative return-surface dependence at weekly to monthly horizons, but its first-day magnitude remains too weak. Correlations between returns and PC2/PC3 are small and are therefore not interpreted as robust leverage factors.

Table 3: Realised/generated correlations between daily returns and selected surface changes.

Horizon h	Δ Average IV	Δ ATM 3M IV	Δ Term-spread	PC1 score
(1)	-0.791/-0.464	-0.860/-0.553	-0.800/-0.440	-0.854/-0.538
(5)	-0.326/-0.290	-0.349/-0.346	-0.324/-0.303	-0.351/-0.326
(10)	-0.276/-0.219	-0.297/-0.263	-0.301/-0.239	-0.296/-0.248
(21)	-0.208/-0.186	-0.217/-0.216	-0.235/-0.202	-0.215/-0.211
(30)	-0.173/-0.156	-0.179/-0.175	-0.194/-0.172	-0.183/-0.172

Economic admissibility. We evaluate arbitrage restrictions using finite differences on the grid. Since a surface is classified as non-arbitrage-free if it contains any local violation, the free-surface share is interpreted jointly with violation frequency and magnitude.

Table 4: No-arbitrage diagnostics. “Cal.”/“Bfly.” report violated checks; “Repair” reports the correction at each surface’s worst grid point relative to the median half bid-ask spread.

Surface	Free	Cal.	Bfly.	Mean repair	Max repair
DDPM samples	88.1%	0.00%	0.13%	15%	605%
Ensemble mean	98.4%	0.00%	0.01%	5%	25%
Ensemble median	97.7%	0.00%	0.02%	5%	28%

Table 4 shows virtually no calendar violations and only sparse butterfly violations. Detected violations are economically small: the required IV repair averages only 15% of the median half bid-ask spread for individual samples and 5% for the ensemble surfaces.⁷ In absolute terms, the typical repair of 1.4 IV bps remains below local half-spreads across the grid, which range from about 3.5 bps at the money to 45 bps in the deep wings. Only rare tail violations in

⁷The repair is a local proxy: for each violated finite-difference constraint, we approximate the minimum IV correction required to reach the no-arbitrage boundary using the constraint’s first-order gradient.

individual samples exceed the half-spread at their worst grid point. These results suggest that detected arbitrage largely reflects quote noise, non-synchronous observations, or smoothing/interpolation artefacts rather than economically material arbitrage.

Disabling the no-arbitrage mechanism ($\lambda_{\text{but}} = 0, \lambda_{\text{cal}} = 0$) cuts the arbitrage-free share to about 24% while corrections increase two- to fivefold (mostly still within the half-spread). This is most likely because the training surfaces themselves contain arbitrage only at small magnitudes, so the mechanism primarily ensures admissibility rather than preventing exploitable arbitrage.

5.2 Distributional Forecast Quality

Proper scoring rule. We evaluate whether the conditional samples assign probability mass effectively to the realised future, using the continuous ranked probability score (CRPS) [18]. Persistence corresponds to a degenerate distribution, so we construct a probabilistic persistence benchmark by sampling 1000 30-day surface-change trajectories from the training and validation period and anchoring them at each forecast origin. For returns, the benchmark is zero.

Table 5 shows that the large gains relative to deterministic persistence partly reflect distributional asymmetry. At $h = 1$, diffusion only modestly improves on bootstrap persistence for average and ATM levels and is worse for skew, curvature, and term spread. The comparison becomes favourable at longer horizons: by $h = 10$, diffusion outperforms bootstrap persistence in eight (of nine) surface descriptors and in seven (of nine) grid buckets; by $h = 30$, it outperforms bootstrap persistence in eight descriptors and eight grid buckets, with the only disadvantage in the central long-maturity region. Thus, deterministic persistence overstates the apparent short-horizon probabilistic gain, whereas diffusion retains broad distributional improvements at medium and longer horizons.

Table 5: CRPS gains relative to deterministic and bootstrap persistence benchmarks. Positive gains indicate lower CRPS.

Quantity	$h=1$	$h=10$	$h=30$
Average IV level	+25.5/+4.4%	+31.7/+10.7%	+33.2/+11.0%
ATM IV level	+22.7/+0.9%	+30.5/+8.1%	+29.6/+4.2%
3M skew	+10.4/-20.9%	+34.9/+8.4%	+32.0/+4.8%
3M curvature	+5.7/-26.8%	+32.5/+5.8%	+26.7/-1.5%
Short-long spread	-26.6/-61.0%	+21.7/-0.8%	+31.3/+9.4%
Daily return	+26.5/-	+25.7/-	+26.0/-

The multivariate energy score [18] shows the same pattern: persistence dominates at one day, whereas the diffusion model provides better trajectory distributions from weekly horizons onward. The same results also hold when returns are included jointly.

Calibration. We construct pointwise predictive intervals from the generated paths and average coverage over grid points and test origins. Figure 8 shows systematic surface undercoverage across horizons and interval levels. Coverage falls from 0.400 to 0.340 for nominal 50% intervals and from 0.856 to 0.811 for nominal 95% intervals between $h = 1$ and $h = 30$, despite monotonically increasing interval widths. The model therefore expands uncertainty over time, but not sufficiently. The gap narrows for the highest confidence levels. Moreover, calibration errors are heterogeneous. At $h = 1$, the largest undercoverage occurs in the short-maturity right wing; at

longer horizons, it shifts towards the central region at medium and long maturities. These results are consistent with the factor diagnostics: the model captures the relevant directions and dependence structure but understates the amplitude of future movements. Its samples are therefore informative but underdispersed.




Figure 8: Predictive-interval reliability for pointwise surface values and daily returns.

Daily-return intervals lie closer to the diagonal, although their widest intervals also show slight undercoverage.

5.3 Predictive Content Beyond Persistence

Finally, we ask whether the predictive mean also improves upon persistence as a point forecast. Because (SPX) options trade in a highly efficient market, persistence is a particularly demanding baseline: most available information is already reflected in the surface, so improvements of even a few percentage points can represent meaningful predictive gains. Conversely, not confronting persistence can flatter a model more than it informs the reader.

Surface improvement. Table 6 shows a clear horizon transition. Aggregated over all horizons, the model reduces RMSE and MAE. Its signed bias remains small, indicating that gains arise from horizon-dependent shape adjustments rather than uniform level shifts. At $h = 1$, persistence is substantially better: the model introduces too much movement. One possible explanation is that the model observes a 21-day evolution and uses it to infer a continuation. Such recent dynamics may contain information about more persistent medium-horizon movements, while the next-day innovation itself remains noisy and difficult to predict. Part of the short-horizon difficulty also arises from the latent representation: AE-only reconstruction RMSE is 0.0039, which constitutes a comparatively larger share of total error at short horizons. Estimated gains turn positive from approximately $h = 4$ for RMSE and $h = 6$ for MAE.

Table 6: Accuracy of the model mean relative to persistence.

Scope	RMSE	Persistence RMSE	RMSE gain	MAE gain	Bias
All 30	0.01262	0.01343	+6.09%	+3.45%	+0.00022
$h = 1$	0.00619	0.00535	-15.72%	-34.49%	+0.00002
$h = 5$	0.01017	0.01043	+2.52%	-0.75%	+0.00018
$h = 10$	0.01223	0.01305	+6.28%	+4.46%	-0.00007
$h = 21$	0.01367	0.01459	+6.29%	+4.30%	+0.00022
$h = 30$	0.01460	0.01567	+6.83%	+4.95%	+0.00084

Figure 9 shows that the gains are not driven by a few origins. Model and persistence errors co-move strongly and spike during

the same difficult market episodes. The model therefore does not eliminate inherently difficult episodes but produces recurrent incremental gains once persistence becomes less dominant.




Figure 9: Surface RMSE of the model mean and persistence across test origins at selected horizons.

Performance is heterogeneous across the surface. Aggregated over all horizons, RMSE improves by 11.69% at short maturities, 6.46% at medium maturities, and 4.99% at long maturities. Both wings improve by approximately 6%–7%, whereas the central region improves by only 2.45% in RMSE. From $h = 10$ onwards, all maturity–moneyness buckets except the long-maturity central region improve upon persistence. Gains are therefore strongest where the surface moves most and weakest in the stable central region with little movement for the model to exploit.

The example point forecast in Figure 10 illustrates this trade-off. Small departures from persistence are costly when the future surface barely moves, particularly at short horizons. At longer horizons, the predictive mean makes smooth, locally plausible adjustments while the generated paths remain coherent. The model's gains therefore arise from modest departures from persistence rather than unstable point predictions.




Figure 10: Realised future t -IV, model predictive mean, persistence, predictive intervals, and sampled forecast paths.

Return channel. The return channel matches the zero-return baseline and is best interpreted as part of the joint trajectory generator: it produces informative distributions and realistic return–surface dependence without implying return predictability.

6 Conclusion

We introduced a conditional latent diffusion framework for generating 30-day joint trajectories of implied volatility surfaces and returns. The model produces realistic, coherent, low-dimensional, and essentially arbitrage-free scenarios, frequently outperforming functional persistence in point forecasting. Its main limitations are underdispersion and weak one-day-ahead performance, reinforcing that the framework is best viewed as a probabilistic trajectory model rather than a one-step point forecaster.

This work provides a foundation for a reproducible IVS-forecasting benchmark. Establishing such a benchmark requires direct comparison under common data construction and a thorough evaluation protocol. A first priority is to evaluate DYSANOS and a SANOS-based diffusion model within our framework. More fundamentally, future work should identify which metrics are most appropriate for evaluating functional trajectories. Applications to hedging, risk measurement, and stress testing should then assess whether statistical gains translate into practical value.

References

- [1] Damien Ackerer, Natasa Tagasovska, and Thibault Vatter. 2020. Deep Smoothing of the Implied Volatility Surface. In *Advances in Neural Information Processing Systems*. 11552–11563. https://proceedings.neurips.cc/paper_files/paper/2020/hash/858e47701162578e5e627cd93ab0938a-Abstract.html
- [2] Maxime Bergeron, Nicholas Fung, John Hull, Zissis Poulos, and Andreas Veneris. 2022. Variational Autoencoders: A Hands-Off Approach to Volatility. *The Journal of Financial Data Science* 4, 2 (2022), 125–138. doi:10.3905/jfds.2022.1.093
- [3] Fischer Black and Myron Scholes. 1973. The Pricing of Options and Corporate Liabilities. *Journal of Political Economy* 81, 3 (1973), 637–654. doi:10.1086/260062
- [4] Daniel A. Bloch and Arthur Böök. 2021. Deep Learning Based Dynamic Implied Volatility Surface. SSRN preprint. doi:10.2139/ssrn.3952842
- [5] Hans Buehler, Blanka Horvath, and Anastasis Kratsios. 2026. DYSANOS - Generative Dynamic Smooth Arbitrage-Free Non-Parametric Option Surfaces. Presentation at XIII Bachelier World Congress. doi:10.2139/ssrn.7047878
- [6] Hans Buehler, Blanka Horvath, Anastasis Kratsios, Yannick Limmer, and Raed Saqr. 2026. SANOS Smooth Strictly Arbitrage-Free Non-Parametric Option Surfaces. arXiv preprint. doi:10.48550/arXiv.2601.11209
- [7] Jay Cao, Jacky Chen, and John Hull. 2020. A Neural Network Approach to Understanding Implied Volatility Movements. *Quantitative Finance* 20, 9 (2020), 1405–1413. doi:10.1080/14697688.2020.1750679
- [8] Peter Carr and Dilip B. Madan. 2005. A Note on Sufficient Conditions for No Arbitrage. *Finance Research Letters* 2, 3 (2005), 125–130. doi:10.1016/j.frl.2005.04.005
- [9] Jacky Chen, John Hull, Zissis Poulos, Haris Rasul, Andreas Veneris, and Yuntao Wu. 2025. A Variational Autoencoder Approach to Conditional Generation of Possible Future Volatility Surfaces. *The Journal of Financial Data Science* 7, 3 (2025), 86–114. doi:10.3905/jfds.2025.1.196
- [10] Ying Chen, Maria Grith, and Hannah L. H. Lai. 2026. Neural Tangent Kernel in Implied Volatility Forecasting: A Nonlinear Functional Autoregression Approach. *Journal of Business & Economic Statistics* 44, 1 (2026), 24–38. doi:10.1080/07350015.2025.2489087
- [11] Vedant Choudhary, Sebastian Jaimungal, and Maxime Bergeron. 2024. FuN-Vol: Multi-asset Implied Volatility Market Simulator using Functional Principal Components and Neural SDEs. *Quantitative Finance* 24, 8 (2024), 1077–1103. doi:10.1080/14697688.2024.2396977
- [12] Samuel N. Cohen, Christoph Reisinger, and Sheng Wang. 2023. Estimating Risks of European Option Books Using Neural-SDE Market Models. *Journal of Computational Finance* 26, 3 (2023), 33–72. doi:10.21314/JCF.2022.028
- [13] Rama Cont and José da Fonseca. 2002. Dynamics of Implied Volatility Surfaces. *Quantitative Finance* 2, 1 (2002), 45–60. doi:10.1088/1469-7688/2/1/304
- [14] Shibo Feng, Chunyan Miao, Zhong Zhang, and Peilin Zhao. 2024. Latent Diffusion Transformer for Probabilistic Time Series Forecasting. In *Proceedings of the AAAI Conference on Artificial Intelligence*. 11979–11987. doi:10.1609/aaai.v38i11.29085
- [15] Matthias R. Fengler. 2012. Option Data and Modeling BSM Implied Volatility. In *Handbook of Computational Finance*, Jin-Chuan Duan, Wolfgang K. Härdle, and James E. Gentle (Eds.). Springer, Berlin, Heidelberg, 117–142.
- [16] Jim Gatheral. 2006. *The Volatility Surface*. John Wiley & Sons, Hoboken, NJ.
- [17] Partha Ghosh, Mehdi S. M. Sajjadi, Antonio Vergari, Michael Black, and Bernhard Schölkopf. 2020. From Variational to Deterministic Autoencoders. In *International Conference on Learning Representations*. <https://openreview.net/forum?id=S1g7tpEYDS>
- [18] Tilmann Gneiting and Adrian E. Raftery. 2007. Strictly Proper Scoring Rules, Prediction, and Estimation. *J. Amer. Statist. Assoc.* 102, 477 (2007), 359–378. doi:10.1198/016214506000001437
- [19] Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. 2016. Deep Residual Learning for Image Recognition. In *2016 IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*. 770–778. doi:10.1109/CVPR.2016.90
- [20] Jonathan Ho, Ajay N. Jain, and Pieter Abbeel. 2020. Denoising Diffusion Probabilistic Models. In *Advances in Neural Information Processing Systems*. 6840–6851. <https://proceedings.neurips.cc/paper/2020/hash/4c5bcfec8584af0d967f1ab10179ca4b-Abstract.html>
- [21] Ying Kit Hui. 2023. *Volatility Surface Completion Using Score-Based Generative Models*. Master’s thesis. University of Waterloo. https://uwaterloo.ca/computational-mathematics/sites/default/files/uploads/documents/ying_kit_hui_research_paper.pdf
- [22] Chen Jin and Ankush Agarwal. 2025. Forecasting Implied Volatility Surface with Generative Diffusion Models. arXiv preprint. doi:10.48550/arXiv.2511.07571
- [23] Marcel Kollovich, Abdul F. Ansari, Michael Bohlke-Schneider, Jasper Zschiegner, Hao Wang, and Yuyang Wang. 2023. Predict, Refine, Synthesize: Self-Guiding Diffusion Models for Probabilistic Time Series Forecasting. In *Advances in Neural Information Processing Systems*. 28341–28364. https://proceedings.neurips.cc/paper_files/paper/2023/hash/5a1a10c2c2c9b9af1514687bc24b8f3d-Abstract-Conference.html
- [24] Xiaochan Ma. 2023. *Diffusion Probabilistic Model for Implied Volatility Surface Generation and Completion*. Master’s thesis. Delft University of Technology. https://diamhomes.ewi.tudelft.nl/~kviuk/numanal/ma_afst.pdf
- [25] Nikita Medvedev and Zhiguang Wang. 2022. Multistep Forecast of the Implied Volatility Surface using Deep Learning. *Journal of Futures Markets* 42, 4 (2022), 645–667. doi:10.1002/fut.22302
- [26] Robert C. Merton. 1973. Theory of Rational Option Pricing. *The Bell Journal of Economics and Management Science* 4, 1 (1973), 141–183. doi:10.2307/3003143
- [27] Brian Ning, Sebastian Jaimungal, Xiaorong Zhang, and Maxime Bergeron. 2023. Arbitrage-Free Implied Volatility Surface Generation with Variational Autoencoders. *SIAM Journal on Financial Mathematics* 14, 4 (2023), 1004–1027. doi:10.1137/21M1443546
- [28] OptionMetrics. 2024. *IvyDB US*. Retrieved 2026-08-02 from https://wrds-www.wharton.upenn.edu/documents/1995/IvyDB_US_v6.0_Reference_Manual.pdf
- [29] Kashif Rasul, Calvin Seward, Ingmar Schuster, and Roland Vollgraf. 2021. Autoregressive Denoising Diffusion Models for Multivariate Probabilistic Time Series Forecasting. In *Proceedings of the 38th International Conference on Machine Learning*. 8857–8868. <https://proceedings.mlr.press/v139/rasul21a.html>
- [30] Robin Rombach, Andreas Blattmann, Dominik Lorenz, Patrick Esser, and Björn Ommer. 2022. High-Resolution Image Synthesis with Latent Diffusion Models. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*. 10684–10695. https://openaccess.thecvf.com/content/CVPR2022/html/Rombach_High-Resolution_Image_Synthesis_With_Latent_Diffusion_Models_CVPR_2022_paper.html
- [31] Michael Roper. 2010. Arbitrage Free Implied Volatility Surfaces. Preprint. <https://talus.maths.usyd.edu.au/u/pubs/publist/preprints/2010/roper-9.pdf>
- [32] Lifeng Shen and James Kwok. 2023. Non-Autoregressive Conditional Diffusion Models for Time Series Prediction. In *Proceedings of the 40th International Conference on Machine Learning*. 31016–31029. <https://proceedings.mlr.press/v202/shen23d.html>
- [33] John Skelton. 2024. *Generative Implied Volatility Modelling in the Era of ODTE Options*. Master’s thesis. ETH Zürich. <https://github.com/JPNotleKs/VolaDiff/blob/main/VolaDiff%20Thesis.pdf>
- [34] Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N. Gomez, Lukasz Kaiser, and Illia Polosukhin. 2017. Attention Is All You Need. In *Advances in Neural Information Processing Systems*. 5998–6008. <https://papers.neurips.cc/paper/7181-attention-is-all-you-need>
- [35] Milena Vuletić and Rama Cont. 2024. VolGAN: A Generative Model for Arbitrage-Free Implied Volatility Surfaces. *Applied Mathematical Finance* 31, 4 (2024), 203–238. doi:10.1080/1350486X.2025.2471317
- [36] Wharton Research Data Services. 2026. *IvyDB US by OptionMetrics*. Retrieved 2026-08-02 from <https://wrds-www.wharton.upenn.edu/pages/about/data-vendors/optionmetrics/>
- [37] Ruben Wiedemann, Antoine Jacquier, and Lukas Gonon. 2025. Operator Deep Smoothing for Implied Volatility. In *International Conference on Learning Representations*. 96833–96872. https://proceedings.iclr.cc/paper_files/paper/2025/hash/f115f619b62833aad5ac6b058975b0e6-Abstract-Conference.html
- [38] Yiheng Xie, Towaki Takikawa, Shunsuke Saito, Or Litany, Shiqin Yan, Numair Khan, Federico Tomba, James Tompkin, Vincent Sitzmann, and Srinath Sridhar. 2022. Neural Fields in Visual Computing and Beyond. *Computer Graphics Forum* 41, 2 (2022), 641–676. doi:10.1111/cgf.14505
- [39] Wenyong Zhang, Lingfei Li, and Gongguo Zhang. 2023. A Two-step Framework for Arbitrage-free Prediction of the Implied Volatility Surface. *Quantitative Finance* 23, 1 (2023), 21–34. doi:10.1080/14697688.2022.2135454