
TAVIS: A Benchmark for Egocentric Active Vision and Anticipatory Gaze in Imitation Learning

Giacomo Spigler

Department of Intelligent Systems
Tilburg University
Netherlands
g.spigler@tilburguniversity.edu

Abstract

Active vision – where a policy controls its own gaze during manipulation – has emerged as a key capability for imitation learning, with multiple independent systems demonstrating its benefits in the past year. Yet there is no shared benchmark to compare approaches or quantify what active vision contributes, on which task types, and under what conditions. We introduce TAVIS, evaluation infrastructure for active-vision imitation learning, with two complementary task suites – TAVIS-Head (5 tasks, global search via pan/tilt necks) and TAVIS-Hands (3 tasks, local occlusion via wrist cameras) – on two humanoid torso embodiments (GR1T2, Reachy2), built on IsaacLab. TAVIS provides three evaluation primitives: a paired headcam-vs-fixedcam protocol on identical demonstrations; GALT (Gaze-Action Lead Time), a novel metric grounded in cognitive science and HRI that quantifies anticipatory gaze in learned policies; and procedural ID/OOD splits. Baseline experiments with Diffusion Policy and π_0 reveal that (i) active-vision generally helps, but benefits are task-conditional rather than uniform; (ii) multi-task policies degrade sharply under controlled distribution shifts on both suites; and (iii) imitation alone yields anticipatory gaze, with median lead times comparable to the human teleoperator reference. Code, evaluation scripts, demonstrations (LeRobot v3.0; ~ 2200 episodes) and trained baselines are released at <https://github.com/spiglerg/tavis> and <https://huggingface.co/tavis-benchmark>.

1 Introduction

Imitation learning (IL) has progressed rapidly on visuomotor manipulation, yet most existing benchmarks and methods assume a fixed third-person or wide-angle camera. Over the past year, at least eight independent systems have shown that letting the policy control its own gaze can improve manipulation performance: ranging from high-DoF active necks Chuang et al. [2025a], Xiong et al. [2025], Yu et al. [2025] to low-DoF stereo or eyeball heads Cheng et al. [2025], Kerr et al. [2025], foveated and viewpoint-optimised vision Chuang et al. [2025b], Liu et al. [2025], and bimanual wrist-driven eyes He et al. [2026]. These systems converge on the same finding: active gaze provides information that fixed cameras cannot, and policies that exploit it perform better.

Despite this convergence, no shared evaluation infrastructure exists for active-vision IL. Standard manipulation benchmarks – LIBERO Liu et al. [2023], RL Bench James et al. [2020], CALVIN Mees et al. [2022], etc – all assume fixed cameras and cannot isolate active vision as a controlled variable. Even EFM-10 He et al. [2026], the closest existing artifact, is hardware-locked to a specific bimanual real-robot setup that other groups cannot easily reproduce. The eight systems above therefore cannot be meaningfully compared: each defines its own tasks, hardware, and metrics. Benchmarks have




Figure 1: **The TAVIS Benchmark.** TAVIS comprises two task suites that isolate distinct roles of active vision in manipulation. *TAVIS-Head* targets *global* active vision – head reorientation for search and to handle clutter – while *TAVIS-Hands* targets *local* active vision via wrist cameras peering past occlusions. Demonstrations are collected via first-person Meta Quest 3 teleoperation with gaze control through head movements, and released on Hugging Face. The evaluation protocol pairs three controlled axes – fixed vs. head-mounted camera, in- vs. out-of-distribution splits, and single- vs. multi-task training – along with the GALT (Gaze-Action Lead Time) metric for action legibility, enabling a thorough comparison of active-vision policies.

repeatedly catalyzed progress in machine learning by enabling fair comparison and identifying open problems; the absence of one for active-vision IL is a concrete bottleneck on the community’s ability to assess what active vision contributes, on which task types, and under what conditions.

Indeed, active vision is a coupled perception-action problem: the policy must learn to control gaze in coordination with manipulation, and gaze itself serves multiple roles – visual search, clutter disambiguation, temporal monitoring, and the communication of intent to human collaborators. This last role has deep precedent in cognitive science, where human gaze proactively leads the hand by hundreds of milliseconds at each contact landmark Johansson et al. [2001], and in HRI, where this same temporal coupling makes a robot’s behaviour *legible* to bystanders Dragan et al. [2013]. A policy that simply lifts the correct object scores identically to one that also uses anticipatory gaze to communicate intention. Evaluating active vision therefore requires new metrics designed to measure the temporal and communicative dimensions of gaze behaviour, not just task completion.

To close both gaps, we introduce the TAVIS benchmark (Figure 1) with two complementary task suites, *TAVIS-Head* (global search and intent signalling through head gaze) and *TAVIS-Hands* (local occlusion via wrist cameras), based on two humanoid torso embodiments (GR1T2, Reachy2).

TAVIS is positioned as *evaluation infrastructure* centered on three evaluations: a *paired headcam-vs-fixedcam protocol* that isolates active vision as a controlled variable on identical demonstrations; *GALT (Gaze-Action Lead Time)*, a novel metric that quantifies anticipatory gaze in successful episodes; and *ID and OOD distribution splits* that distinguish in-distribution interpolation from extrapolation under controlled perturbations.

Overall, our novel contributions are:

- The TAVIS benchmark¹: 2 task suites (TAVIS-Head, TAVIS-Hands), 2 humanoid torsos (GR1T2, Reachy2), and a paired headcam/fixedcam evaluation protocol enabled by simultaneously-recorded demonstrations (LeRobot v3.0; ~2200 episodes).

¹<https://github.com/spiglerg/tavis>

- Two evaluation primitives beyond task success: *GALT*, a kinematic metric grounded in cognitive science and HRI for anticipatory gaze; and *ID/OOD distribution splits* extending the LIBERO-Pro Zhou et al. [2025] paradigm to active vision.
- Baseline analyses with Diffusion Policy Chi et al. [2023] and π_0 Black et al. [2024] showing (i) active-vision benefits (+8 to +26pp head-vs-fixed on TAVIS-Head; 70–77% success on TAVIS-Hands), (ii) sharp degradation under controlled OOD shifts on both suites, and (iii) anticipatory gaze acquired from imitation alone, with median lead times comparable to the human teleoperator.

2 Related Work

We organize related work along the three threads TAVIS draws on: imitation-learning benchmarks, active vision in manipulation, and gaze-coordination in cognitive science and HRI.

Imitation Learning Benchmarks. Benchmarks have been instrumental to progress in machine learning by providing shared platforms for fair comparison; in robotics, where research ultimately targets hardware and sim-to-real gaps remain a real concern, simulation-based benchmark adoption has been more uneven. Nonetheless, some benchmarks have achieved significant impact in the field, including for example RL Bench James et al. [2020], CALVIN Mees et al. [2022], RoboCasa Nasiriany et al. [2024], RoboCerebra Han et al. [2025], and LIBERO Liu et al. [2023]. However, almost all of these benchmarks rely on fixed workspace cameras. The few exceptions that target active vision are EFM-10 He et al. [2026], a real-robot benchmark for bimanual active perception, and AV-ALOHA Chuang et al. [2025a], which provides teleoperation datasets and simulated environments. Outside of the visual domain, Tactile-MNIST Schneider et al. [2025] provides a benchmark for active tactile perception. Beyond camera placement, most IL benchmarks are tied to a single robot platform, limiting cross-embodiment evaluation. TAVIS addresses both gaps in a single benchmark.

Active Vision in Robot Manipulation. Active perception in robotics is a long-standing idea – that an agent which controls its sensors can acquire information unavailable to a passive observer – with foundational work by, e.g., Bajcsy [1988], Aloimonos et al. [1988], and Ballard [1991]. Recently, the idea has been revisited from the perspective of imitation learning, whereby policies are trained to learn gaze directly from human teleoperation. The resulting systems vary mainly in how they organize the sensor’s degrees of freedom. Low-DoF pan/tilt cameras – whether mounted on a humanoid neck (Open-Television Cheng et al. [2025], and our TAVIS-Head setup) or on a mechanical eye gimbal (Eye Robot Kerr et al. [2025]) – provide the simplest configuration; higher-DoF active cameras can be realized either as a 6–7-DoF neck, as in AV-ALOHA Chuang et al. [2025a], ViA Xiong et al. [2025], and EgoMI Yu et al. [2025], or by using one arm as a movable eye, as in EFM-10 He et al. [2026] – functionally similar despite the different embodiment. A complementary axis is image-space attention rather than camera motion: GIAVA Chuang et al. [2025b] extends AV-ALOHA with foveated processing driven by human eye-tracking, and AVR Liu et al. [2025] jointly optimizes viewpoint and focal length for precision tasks. Within this landscape, TAVIS-Head focuses on commodity pan/tilt necks, to capture most of the search and legibility benefits without the cost of a high-DoF neck, while TAVIS-Hands explores wrist-driven AV with *both* arms used *jointly* for perception and manipulation, in contrast to EFM-10’s explicit one-arm-sees / one-arm-acts decomposition.

Gaze Coordination and Legibility in Humans and Robots. Two fields converge on the claim that gaze should precede action: cognitive-science studies of natural manipulation, and HRI work on legible motion. In natural object manipulation, gaze proactively marks upcoming contact landmarks rather than tracking the hand, leading the fingertips to each grasp or release site Johansson et al. [2001]. Reported lead times are ~ 560 ms in everyday tea-making Land et al. [1999] and ~ 400 ms in speed stacking Foerster et al. [2011]. This temporal coupling is sometimes formalized as the *eye-hand arrival span* Kim et al. [2018], equivalent to the GALT metric we introduce in Section 4.1.

In parallel, HRI work argues that *how* a robot moves – not only whether it succeeds – shapes how readily humans interpret and accept its behaviour Dragan et al. [2013]. Concretely, deliberately timed handovers let observers read the robot’s gaze Admoni et al. [2014], legible articulated pointing communicates intent Holladay et al. [2014], and human-imitated head and gaze patterns improve naturalness on humanoid platforms Ding et al. [2024]. Conversely, observers spontaneously generate

anticipatory gaze toward robot goals Sciutti et al. [2013], and recent learned models reproduce this gaze-primed reaching motion Hatano et al. [2025].

Despite this convergent evidence, no IL benchmark has measured whether learned manipulation policies acquire anticipatory gaze; TAVIS introduces GALT (Section 4.1) to close that gap, and validates it both on trained policies and on the human teleoperation reference.

3 The TAVIS Benchmark

TAVIS is a composable evaluation platform for egocentric active vision: two robot embodiments $\times$ two task suites $\times$ two camera modes (head-mounted vs. fixed) $\times$ multiple distribution splits, all evaluable head-to-head. The two suites cover complementary regimes: *TAVIS-Head* (global search via pan/tilt necks) and *TAVIS-Hands* (local occlusion via wrist cameras). High-DoF necks are deliberately out of scope (Section 2).

We implemented TAVIS purely in simulation on top of IsaacLab Mittal et al. [2025] and IsaacLab-Arena NVIDIA Isaac Lab Arena Contributors [2025], to take advantage of ray-traced rendering.

3.1 Task Suites

Task design follows two conventions used throughout: unless otherwise specified, scenes draw from a fixed set of five distinct YCB objects, and language conditioning is task-dependent. Per-task scenes, prompts, randomization ranges, and success criteria are listed in Appendix A.

TAVIS-Head. The suite contains five tasks targeting roles where active head movement is expected to help: clutter disambiguation, conditional information gathering, temporal monitoring, and vertical workspace search. The suite is composed of the following tasks:

- *conditional-pick*: Two objects are placed left and right; a colored card indicates the target (red = left, green = right). The robot must look at the card, then look at and lift the correct object.
- *wait-then-act*: The robot waits for a status light to turn from red to green after a randomized delay; only then it grasps and lifts the object.
- *clutter-pick-cube*: A red cube and four distractor YCB objects are placed at randomized positions. The robot must visually locate the cube among the distractors and lift it.
- *clutter-pick-lift*: A language prompt names a target among five objects. The robot must visually locate the object, grasp it, and lift it. For each object, 3 distinct prompts are used on different trials.
- *multi-shelf-scan*: A three-shelf unit holds the target, which is named in a language prompt. The robot must scan the shelves vertically to locate it, then retrieve it. Like *clutter-pick-lift*, each episode randomizes the instruction across 3 distinct prompts per object.

TAVIS-Hands. This suite targets local occlusion where head movement alone cannot reveal the target; the policy relies on wrist cameras for both perception and manipulation, using both arms jointly since the reachable hand is not known in advance.

- *peeking-box*: A box with one side opening (left or right, randomized per episode) is placed on the table with a target object inside. The head camera cannot see the sides; the wrist cameras must determine which side is open. The robot reaches in with the corresponding hand and lifts the object.
- *occluded-reach*: A vertical screen sits on the table between the robot’s head and the workspace, blocking the head’s view of a single target object placed behind it. Wrist cameras provide the only useful view. The robot reaches around the screen and lifts the object.
- *blocked-clutter-pick-cube*: Identical to *clutter-pick-cube*, except the robot’s head camera is masked. The robot can only rely on the wrist cameras to locate and grasp the red cube.

3.2 Robots

TAVIS supports two fixed-base humanoid torsos, both with two 7-DoF arms and a 3-DoF neck: *Reachy2* (Pollen Robotics) and *GRIT2* (Fourier Intelligence, with Robotiq 2F-85 grippers replacing its native dexterous hands to match Reachy2).

Tasks operate on a unified 19-D canonical action space (per-arm IK target, 3-DoF neck, per-hand gripper) defined in a hip-centred frame; full layout and the canonical-frame wrapper are in Appendix B.

3.3 Demonstration Collection and Datasets

Demonstrations are collected via a Quest 3 first-person-view teleoperation interface (Appendix C). The operator views the head-camera feed (with optional side-by-side wrist-camera overlays), while controller pose drives the robot’s bimanual end-effectors and headset orientation drives the neck. A central fixation marker keeps the operator’s eye gaze stable, so head motion captures gaze.

A second *fixed workspace camera* records the same episode in parallel, yielding paired headcam/fixedcam streams over identical trajectories – the basis for the head-vs-fixed comparison in Section 4. Camera specs and control rates are in Appendix B; teleop protocol and the LeRobot v3.0 release format with per-task and per-prompt fields are in Appendices C, F.

Datasets are released as four Hugging Face repositories², one per (suite $\times$ robot) combination, totalling 2200 episodes. All demonstrations were collected by a single teleoperator, providing consistency across robots and tasks but limiting evaluator variability; we revisit this in Section 6.

4 Evaluation Protocol

TAVIS provides three controlled evaluation axes: the *camera mode* used by the policy (head-mounted vs. fixed workspace camera, recorded simultaneously on identical demonstrations); the *distribution split* (in-distribution and out-of-distribution variants); and the *Gaze-Action Lead Time* (GALT), a kinematic metric that quantifies whether a policy’s gaze anticipates its action. Throughout, we report success rate (SR) over 96 evaluation episodes, with Wilson 95% confidence intervals in Appendix E; GALT is reported for successful TAVIS-Head episodes only.

Paired Headcam vs Fixedcam Comparison The central evaluation primitive of TAVIS is a *paired* comparison between an agent-controlled head-mounted camera and a static workspace camera. Both image streams are recorded simultaneously from the same teleoperation episode (Section 3.3); any policy can therefore be trained and evaluated under either camera mode while every other variable – demonstration, scene layout, robot trajectory, language prompt – is held constant. TAVIS-Hands tasks omit the fixedcam condition by design: the head camera is structurally uninformative there, and a fixed camera adds no information the wrists do not already provide.

A subtle confound is intrinsic to this paired setup: shared demonstrations cause fixedcam policies to inherit a brief ‘look-then-reach’ pause from head-driven teleoperation. We treat this as ecologically valid (humans look before reaching) and quantify its magnitude (Section 5).

ID and OOD Distribution Splits TAVIS includes randomized OOD splits to stress-test extrapolation, mitigating the memorization-not-generalization concern for fixed-configuration IL benchmarks raised by LIBERO-Pro Zhou et al. [2025] and LIBERO-Plus Fei et al. [2025].

We define three cases. The *in-distribution* (id) split samples within the same range used during demonstration collection, testing whether a policy interpolates over the variation it has already seen. *ood-spatial* expands the distribution of initial positions of all objects to a larger region than in the training dataset. *ood-init-pose* perturbs the robot reset pose (Gaussian noise $\sigma = 10\text{cm}$ on the Cartesian end-effector positions, $\sigma = 10^\circ$ on the neck’s yaw and pitch). These ranges are intentionally aggressive: the same perturbation is applied uniformly across all checkpoints, so absolute success rates are biased downward but cross-method comparisons remain valid.

4.1 GALT: Gaze-Action Lead Time

Cognitive science has long established that gaze precedes manual action: humans initiate eye fixations on a target $\sim 400\text{--}600\text{ ms}$ before the corresponding hand movement Johansson et al. [2001], Land et al. [1999], Foerster et al. [2011], Kim et al. [2018]. HRI work further shows that this temporal gap carries communicative value, allowing observers to read intent before action completion Dragan et al.

²<https://huggingface.co/tavis-benchmark>

[2013], Admoni et al. [2014]. Despite the importance of this pattern, no robot-learning benchmark currently quantifies whether learned policies acquire it. We introduce GALT to fill this gap.

Note that TAVIS robots fixate via head and neck movements only, so absolute GALT values differ from the saccade literature and other AV platforms; we use the cog-sci range qualitatively to ground the anticipatory-gaze framing, not as a numerical target.

Definition. For a successful episode, let t_{head} be the time at which the head-mounted camera reaches its final pre-grasp fixation, and t_{hand} the time of grasp completion (gripper closure). We define

$$\text{GALT} = t_{\text{hand}} - t_{\text{head}}, \quad (1)$$

with $\text{GALT} > 0$ indicating anticipatory gaze. Using both events as *arrivals* (rather than onsets) aligns with Kim et al.’s “eye-hand arrival span” Kim et al. [2018] and captures the legibility-relevant interval during which an observer can read intent and, in principle, intervene before contact.

GALT generalises to any action anchor (grasp, place, hand-off) and to multiple anchors per episode; here, each TAVIS task has a single grasp, so we report one value per successful episode.

Detection. Both events are inferred from proprioception alone, making GALT portable to real-robot evaluation. The hand event t_{hand} is the latest gripper-command transition (per-arm, with mutual-exclusion); t_{head} is the arrival of the lowest-velocity neck fixation within a lookback window from t_{hand} . Sim-state-aware variants (e.g. gaze-ray verification) are possible but unnecessary on TAVIS. Full thresholds, exclusion codes, pseudocode, and detection-rate validation appear in Appendix G.

5 Experiments and Analysis

We use TAVIS to investigate four questions about active-vision IL:

- **Q1:** How much does active vision help, and on which task types?
- **Q2:** To what extent does multi-task training help versus single-task training?
- **Q3:** What is the impact of distribution shift during evaluation?
- **Q4:** Do policies acquire anticipatory gaze from imitation alone?

Baselines and Training Details. We train two baselines via LeRobot Cadene et al. [2024] on each (suite, robot, camera-mode): π_0 Black et al. [2024] at single-task and suite-multi-task scopes (fine-tuned from `lerobot/pi0_base`), and Diffusion Policy Chi et al. [2023] single-task on non-language-prompted tasks only. Each policy is evaluated for 96 episodes per condition; hyperparameters in Appendix D. Multi-task π_0 checkpoints are released on Hugging Face³.

Full per-task results are reported in Table 1 (multi-task π_0); single-task results for both Diffusion Policy and π_0 are in Appendix E, along with per-cell Wilson 95% confidence intervals. Aggregated visualisations for Q1-Q3 appear in Figure 2 (panels a-d), and GALT histograms for Q4 in Figure 3.

Q1: How much does active vision help, and on which task types? On TAVIS-Head, headcam outperforms fixedcam at the suite-mean level on both robots (paired protocol, Section 4; GR1T2: 47.1% vs 38.8%; Reachy2: 38.8% vs 13.3%; Table 1, Figure 2a), but the gap is conditional. The largest active-vision benefit appears on *conditional-pick* (+28pp GR1T2, +45pp Reachy2), where gaze toward the cue card precedes the reach; conversely, *wait-then-act* regresses on GR1T2 (−23pp), where head motion adds nuisance variance over an already-fully-observable workspace. Reachy2’s fixedcam baseline is uniformly weak (suite mean 13.3%), inflating the apparent gap on that robot, so per-task structure is cleaner on GR1T2.

On TAVIS-Hands, both head and fixed cameras are structurally uninformative by design, so we report only head + wrist success rates and probe per-modality contributions through a paired ablation on the *clutter-pick-cube* task family (Figure 2d): *no AV* (TAVIS-Head fixedcam checkpoint), *full AV* (TAVIS-Head headcam, head + wrist), and *wrist only* (TAVIS-Hands’ *blocked-clutter-pick-cube*

³<https://huggingface.co/tavis-benchmark>

Table 1: **Multi-task π_0 success rates (%) on TAVIS.** One policy per (suite, robot, camera-mode); each cell averages 96 evaluation episodes. Columns group by robot and split (*id* / *ood-spatial* / *ood-init-pose*; defined in Section 4). For TAVIS-Head, separate head-cam and fixed-cam multi-task policies. For TAVIS-Hands, only the native head+wrst setup is reported (head and fixed cameras are both uninformative by design; Section 4). *Suite mean* is the task average within each suite. Per-cell 95% Wilson CIs and single-task training for π_0 and Diffusion Policy are in Appendix E.

multi-task (π_0)	GRIT2						Reachy2					
	id		ood-spatial		ood-init-pose		id		ood-spatial		ood-init-pose	
	head	fixed	head	fixed	head	fixed	head	fixed	head	fixed	head	fixed
TAVIS-Head												
conditional-pick	87.5	59.4	49.0	32.3	2.1	12.5	52.1	7.3	27.1	10.4	12.5	9.4
wait-then-act	65.6	88.5	44.8	61.5	3.1	15.6	55.2	13.5	32.3	5.2	14.6	10.4
clutter-pick-cube	41.7	32.3	26.0	27.1	0.0	12.5	50.0	20.8	26.0	12.5	16.7	8.3
clutter-pick-lift	22.9	13.5	9.4	11.5	0.0	4.2	18.8	10.4	9.4	9.4	5.2	4.2
multi-shelf-scan	17.7	0.0	10.4	4.2	4.2	5.2	17.7	14.6	15.6	7.3	7.3	9.4
<i>suite mean</i>	47.1	38.8	27.9	27.3	1.9	10.0	38.8	13.3	22.1	9.0	11.2	8.3
TAVIS-Hands												
peeking-box		64.6		51.0		15.6		84.4		68.8		39.6
occluded-reach		87.5		60.4		24.0		78.1		43.8		43.8
blocked-clutter-pick-cube		58.3		35.4		4.2		67.7		40.6		31.2
<i>suite mean</i>		70.1		49.0		14.6		76.7		51.0		38.2

checkpoint, head masked). Going from no-AV (fixed-cam) to full-AV (head+wrst) gives +19pp (45.9% vs 26.6%), while wrist-only reaches 63.0% – exceeding full-AV due to demonstration design: TAVIS-Hands trains on explicitly exploratory wrist trajectories under occlusion. Across the suite, the multi-task policies reach 70–77% id success, where the fixed/head views would fail by design.

Q2: To what extent does multi-task training help versus single-task training? We compare single-task π_0 checkpoints against the suite-multi-task π_0 checkpoint on the headcam id split (Figure 2b; full per-task numbers in Appendix E). We find that multi-task training improves on the per-task baselines on both suites, consistent with prior IL scaling findings: suite-mean SR rises from 32.7% to 43.0% on TAVIS-Head and from 53.5% to 73.4% on TAVIS-Hands, with larger gains on the smaller-data Hands suite.

Q3: What is the impact of distribution shift during evaluation? In the spirit of LIBERO-Pro Zhou et al. [2025] and LIBERO-Plus Fei et al. [2025] but on new tasks, robots, and with ray-traced rendering, we evaluate the multi-task π_0 headcam policies on the three TAVIS splits (Section 4; results in Figure 2c and Table 1). Performance degrades substantially under both controlled OOD shifts: TAVIS-Head suite-mean SR drops from 43.0% (id) to 25.0% (ood-spatial) and 6.6% (ood-init-pose), and TAVIS-Hands from 73.4% to 50.0% and 26.4% respectively. The ood-init-pose collapse on TAVIS-Head headcam exceeds that of TAVIS-Head fixedcam and TAVIS-Hands, consistent with head-pose perturbation only surfacing visually for cameras that track the head.

Q4: Do policies acquire anticipatory gaze from imitation alone? For each (task, robot), we compare the policy’s GALT distribution on TAVIS-Head id-split successful episodes against the dataset reference (Figure 3), and find that multi-task π_0 headcam policies acquire anticipatory gaze comparable to the human teleoperator reference. Policy GALT leads the grasp by $\sim 2\text{--}3$ s; pooled medians agree with the dataset reference within ~ 180 ms on a $\sim 2.1\text{--}2.7$ s scale, and per-task $|\Delta\text{median}|/\text{median}_{\text{dataset}}$ stays within $\sim 7\text{--}10\%$ on four of five tasks. The remaining outlier, *multi-shelf-scan* ($|\Delta\text{median}| \approx 450$ ms, $\sim 20\%$ of the dataset median), likely reflects per-shelf fixation variability rather than absent GALT structure. Crucially, the temporal coupling between gaze and action – not just the spatial trajectory – is acquired through imitation.

Headcam teleoperation bias. Fixedcam policies in Section 5 are trained on fixed-camera observations from *head*-teleoperated demonstrations, which could bias the head-vs-fixed comparison if




Figure 2: **TAVIS results overview.** Aggregated multi-task π_0 success rates across the four main evaluation cuts of Section 5. Bars: suite-mean SR (per-task averaged over robots); coloured dots: per-task points; thin lines: paired conditions per task. **(A) Q1, active vision:** head-vs-fixed on TAVIS-Head, and head + wrist SR on TAVIS-Hands (no fixed-cam variant by design). **(B) Q2, multi-task scaling:** single-task checkpoints vs. suite-multi-task π_0 . **(C) Q3, distribution shift:** id, ood-spatial (*ood-sp*), ood-init-pose (*ood-ip*). **(D) Paired ablation on clutter-pick-cube:** no AV (TAVIS-Head fixed-cam), full AV (TAVIS-Head head + wrist), wrist only (TAVIS-Hands blocked-clutter-pick-cube). Per-cell numbers in Table 1.

head-teleop trajectories encode active-vision structure. To test this, we collect a matched fixedcam-only teleoperation dataset on *wait-then-act* (GR1T2) and train a *single-task* π_0 checkpoint. The fixedcam-only ablation reaches 39.6% id success, against 52.1% for the standard fixedcam policy (head-teleop trajectories) and 63.5% for headcam. The 24pp head-vs-fixedcam-only gap thus decomposes into ~ 11 pp from observation-time headcam access (63.5% vs 52.1%) and ~ 13 pp from trajectory-time head-teleop bias (52.1% vs 39.6%) – head-teleop trajectories slightly *aid* fixedcam learning, making the comparison in Q1 a conservative estimate of the headcam advantage.

6 Assumptions and Limitations

Simulation only. TAVIS is implemented purely in simulation on top of IsaacLab Mittal et al. [2025]. Simulation is deliberate: it eliminates per-lab setup variability and lets any researcher reproduce the results, but comes at the price of a sim-to-real gap.

Teleoperation setup. All demonstrations were collected by a single operator. This guarantees consistency across robots and tasks, but introduces operator-specific gaze and pacing patterns. Further, we adopt by design specific and consistent fixation patterns (i.e., forcing fixations through head movement, Section 3.3). Alternative collection strategies (naive head-tracks-hands, GALT-relabelled trajectories, decoupled head/hand action lag) are interesting open directions. Lastly, the same trajectories serve both headcam and fixedcam policies, so fixedcam inherits head-teleop look-then-reach pauses; the bias investigation in Section 5 bounds this confound and finds it actually *aids* fixedcam learning, making our head-vs-fixed comparison conservative.

Restricted active-vision configurations. TAVIS focuses on commodity 2–3-DoF pan/tilt necks (TAVIS-Head) and bimanual wrist cameras (TAVIS-Hands). The 6–7-DoF active necks explored in




Figure 3: **GALT (Gaze-Action Lead Time) distributions per TAVIS-Head task: multi-task π_0 policy vs human-teleoperator reference.** Solid curves are the multi-task π_0 headcam-policy GALT distribution per robot (GR1T2 blue, Reachy2 orange); dashed curves are the human teleoperation reference at the dataset’s native 60 Hz. Light shaded histograms behind each curve use 20 equal-width bins on $[-0.5, 3.5]$ s. Filled triangles at the x -axis mark policy medians, hollow triangles mark dataset medians. Only successful evaluation episodes with valid GALT detections contribute, with values outside $[-0.5, 3.0]$ s discarded at detection time – the same window for policy and dataset.

prior work Chuang et al. [2025a], Xiong et al. [2025] and the eye-gimbal configurations Kerr et al. [2025] are not directly supported, although TAVIS’s compositional design admits their addition.

GALT scope. GALT is a *post-hoc* metric on successful episodes with correct fixation. Indeed, its direct optimization (e.g., RL fine-tuning) may reward any jerky pre-grasp head motions; meaningful use requires the underlying policy to already exhibit coherent fixation. GALT also uses head orientation as a proxy for gaze direction (TAVIS robots have no independent eye DoFs), so absolute values are not directly comparable to eye-tracking literature. Variants combining timing with fixation-location verification (e.g., gaze-ray intersection with the target) are possible but not used here.

OOD splits. OOD-spatial and OOD-init-pose target only two pre-defined axes, but real-world distribution shift is richer (e.g. visual textures, lighting, object semantics). Notably, most tasks use a common scene template (the same metal table in an open arena). Scene-level distribution shift is not evaluated, but is a useful OOD scenario to explore. Extending TAVIS to support more OOD cases is relatively straightforward, and will be useful future work.

Single-seed evaluation. All cells use a single seed per configuration, as in standard IL benchmarks Liu et al. [2023]. Aggregate trends are more reliable than individual cells.

7 Conclusion

TAVIS provides reproducible evaluation infrastructure for egocentric active-vision imitation learning: two complementary task suites (TAVIS-Head, TAVIS-Hands), two humanoid torso embodiments under a unified canonical action space, simultaneous head/fixed-camera recording on identical demonstrations, ID/OOD distribution splits, and GALT – a kinematic metric that quantifies anticipatory gaze in learned policies. Our baselines show that active-vision benefits are task-conditional rather than uniform, that policies degrade sharply under controlled distribution shifts, and that imitation alone yields anticipatory gaze with median lead times matching the human teleoperator reference.

The benchmark is designed to grow. Adding a new humanoid torso requires only its USD, joint indices, gripper interface, and a hip-frame offset; new tasks fit into the suite-builder interface; and the

existing OOD framework extends naturally to additional perturbation axes – visual textures, semantic substitutions, scene-level changes, and language-prompt variations are all straightforward to add given TAVIS’s procedural environments. Beyond these axes, several directions are particularly promising: post-hoc gaze relabeling that retrofits anticipatory fixations onto the majority of existing IL datasets which lack head tracking; sim-to-real bridges for the established TAVIS tasks; foveated-vision variants leveraging eye-tracking, in the spirit of GIAVA Chuang et al. [2025b].

Acknowledgments and Disclosure of Funding

This work used the Dutch national e-infrastructure with the support of the SURF Cooperative using grant no. EINF-17183. The author thanks Murat Kirtay and Bosong Ding (AIR-Lab, Tilburg University) for valuable feedback on TAVIS.

References

- Henny Admoni, Anca Dragan, Siddhartha S Srinivasa, and Brian Scassellati. Deliberate delays during robot-to-human handovers improve compliance with gaze communication. In *Proceedings of the 2014 ACM/IEEE international conference on Human-robot interaction*, pages 49–56, 2014.
- John Aloimonos, Isaac Weiss, and Amit Bandyopadhyay. Active vision. *International journal of computer vision*, 1(4):333–356, 1988.
- Ruzena Bajcsy. Active perception. *Proceedings of the IEEE*, 76(8):966–1005, 1988.
- Dana H Ballard. Animate vision. *Artificial intelligence*, 48(1):57–86, 1991.
- Kevin Black, Noah Brown, Danny Driess, Adnan Esmail, Michael Equi, Chelsea Finn, Niccolo Fusai, Lachy Groom, Karol Hausman, Brian Ichter, Szymon Jakubczak, Tim Jones, Liyiming Ke, Sergey Levine, Adrian Li-Bell, Mohith Mothukuri, Suraj Nair, Karl Pertsch, Lucy Xiaoyang Shi, James Tanner, Quan Vuong, Anna Walling, Haohuan Wang, and Ury Zhilinsky. π_0 : A vision-language-action flow model for general robot control. *arXiv preprint arXiv:2410.24164*, 2024.
- Remi Cadene, Simon Alibert, Alexander Soare, Quentin Gallouedec, Adil Zouitine, Steven Palma, Pepijn Kooijmans, Michel Aractingi, Mustafa Shukor, Dana Aubakirova, Martino Russi, Francesco Capuano, Caroline Pascal, Jade Choghari, Jess Moss, and Thomas Wolf. Lerobot: State-of-the-art machine learning for real-world robotics in pytorch. <https://github.com/huggingface/lerobot>, 2024.
- Xuxin Cheng, Jialong Li, Shiqi Yang, Ge Yang, and Xiaolong Wang. Open-TeleVision: Teleoperation with immersive active visual feedback. In *Conference on Robot Learning*, pages 2729–2749. PMLR, 2025.
- Cheng Chi, Siyuan Feng, Yilun Du, Zhenjia Xu, Eric Cousineau, Benjamin Burchfiel, and Shuran Song. Diffusion policy: Visuomotor policy learning via action diffusion. In *Proceedings of Robotics: Science and Systems (RSS)*, 2023.
- Ian Chuang, Andrew Lee, Dechen Gao, M-Mahdi Naddaf-Sh, and Iman Soltani. Active vision might be all you need: Exploring active vision in bimanual robotic manipulation. In *2025 IEEE International Conference on Robotics and Automation (ICRA)*, pages 7952–7959. IEEE, 2025a.
- Ian Chuang, Andrew Lee, Dechen Gao, Jinyu Zou, and Iman Soltani. Look, focus, act: Efficient and robust robot learning via human gaze and foveated vision transformers. *arXiv e-prints*, pages arXiv–2507, 2025b.
- Bosong Ding, Murat Kirtay, and Giacomo Spigler. Imitation of human motion achieves natural head movements for humanoid robots in an active-speaker detection task. In *2024 IEEE-RAS 23rd International Conference on Humanoid Robots (Humanoids)*, pages 645–652. IEEE, 2024.
- Anca D Dragan, Kenton CT Lee, and Siddhartha S Srinivasa. Legibility and predictability of robot motion. In *2013 8th ACM/IEEE International Conference on Human-Robot Interaction (HRI)*, pages 301–308. IEEE, 2013.

- Senyu Fei, Siyin Wang, Junhao Shi, Zihao Dai, Jikun Cai, Pengfang Qian, Li Ji, Xinzhe He, Shiduo Zhang, Zhaoye Fei, et al. LIBERO-Plus: In-depth robustness analysis of Vision-Language-Action models. *arXiv preprint arXiv:2510.13626*, 2025.
- Rebecca M Foerster, Elena Carbone, Hendrik Koesling, and Werner X Schneider. Saccadic eye movements in a high-speed bimanual stacking task: Changes of attentional control during learning and automatization. *Journal of vision*, 11(7):9–9, 2011.
- Songhao Han, Boxiang Qiu, Yue Liao, Siyuan Huang, Chen Gao, Shuicheng Yan, and Si Liu. Robocerebra: A large-scale benchmark for long-horizon robotic manipulation evaluation. In *The Thirty-ninth Annual Conference on Neural Information Processing Systems Datasets and Benchmarks Track*, 2025.
- Masashi Hatano, Saptarshi Sinha, Jacob Chalk, Wei-Hong Li, Hideo Saito, and Dima Damen. Prime and reach: Synthesising body motion for gaze-primed object reach. *arXiv e-prints*, pages arXiv–2512, 2025.
- Yuxin He, Ruihao Zhang, Tianao Shen, Cheng Liu, and Qiang Nie. Towards exploratory and focused manipulation with bimanual active perception: A new problem, benchmark and strategy. *arXiv preprint arXiv:2602.01939*, 2026.
- Rachel M Holladay, Anca D Dragan, and Siddhartha S Srinivasa. Legible robot pointing. In *The 23rd IEEE International Symposium on robot and human interactive communication*, pages 217–223. IEEE, 2014.
- Stephen James, Zicong Ma, David Rovick Arrojo, and Andrew J Davison. RL Bench: The robot learning benchmark & learning environment. *IEEE Robotics and Automation Letters*, 5(2):3019–3026, 2020.
- Roland S Johansson, Göran Westling, Anders Bäckström, and J Randall Flanagan. Eye–hand coordination in object manipulation. *Journal of neuroscience*, 21(17):6917–6932, 2001.
- Justin Kerr, Kush Hari, Ethan Weber, Chung Min Kim, Brent Yi, Tyler Bonnen, Ken Goldberg, and Angjoo Kanazawa. Eye, robot: Learning to look to act with a BC-RL perception-action loop. In *Conference on Robot Learning*, pages 3647–3664. PMLR, 2025.
- Hye Jin Kim, Cho Hee Lee, and Eun Young Kim. Temporal differences in eye–hand coordination between children and adults during manual action on objects. *Hong Kong Journal of Occupational Therapy*, 31(2):106–114, 2018.
- Michael Land, Neil Mennie, and Jennifer Rusted. The roles of vision and eye movements in the control of activities of daily living. *Perception*, 28(11):1311–1328, 1999.
- Bo Liu, Yifeng Zhu, Chongkai Gao, Yihao Feng, Qiang Liu, Yuke Zhu, and Peter Stone. LIBERO: Benchmarking knowledge transfer for lifelong robot learning. *Advances in Neural Information Processing Systems*, 36:44776–44791, 2023.
- Yushan Liu, Shilong Mu, Xintao Chao, Zizhen Li, Yao Mu, Tianxing Chen, Shoujie Li, Chuqiao Lyu, Xiao-ping Zhang, and Wenbo Ding. AVR: Active vision-driven robotic precision manipulation with viewpoint and focal length optimization. *arXiv e-prints*, pages arXiv–2503, 2025.
- Oier Mees, Lukas Hermann, Erick Rosete-Beas, and Wolfram Burgard. CALVIN: A benchmark for language-conditioned policy learning for long-horizon robot manipulation tasks. *IEEE Robotics and Automation Letters*, 7(3):7327–7334, 2022.
- Mayank Mittal, Pascal Roth, James Tigue, Antoine Richard, Octi Zhang, Peter Du, Antonio Serrano-Muñoz, Xinjie Yao, René Zurbrügg, Nikita Rudin, Lukasz Wawrzyniak, Milad Rakhsha, Alain Denzler, Eric Heiden, Ales Borovicka, Ossama Ahmed, Iretiayo Akinola, Abrar Anwar, Mark T. Carlson, Ji Yuan Feng, Animesh Garg, Renato Gasoto, Lionel Gulich, Yijie Guo, M. Gussert, Alex Hansen, Mihir Kulkarni, Chenran Li, Wei Liu, Viktor Makovychuk, Grzegorz Malczyk, Hammad Mazhar, Masoud Moghani, Adithyavairavan Murali, Michael Noseworthy, Alexander Poddubny, Nathan Ratliff, Welf Rehberg, Clemens Schwarke, Ritvik Singh, James Latham Smith, Bingjie Tang, Ruchik Thaker, Matthew Trepte, Karl Van Wyk, Fangzhou Yu, Alex Millane,

- Vikram Ramasamy, Remo Steiner, Sangeeta Subramanian, Clemens Volk, CY Chen, Neel Jawale, Ashwin Varghese Kuruttukulam, Michael A. Lin, Ajay Mandlekar, Karsten Patzwaldt, John Welsh, Huihua Zhao, Fatima Anes, Jean-Francois Laffleche, Nicolas Moënné-Loccoz, Soowan Park, Rob Stepinski, Dirk Van Gelder, Chris Amever, Jan Carius, Jumyung Chang, Anka He Chen, Pablo de Heras Ciechowski, Gilles Daviet, Mohammad Mohajerani, Julia von Muralt, Viktor Reutsky, Michael Sauter, Simon Schirm, Eric L. Shi, Pierre Terdiman, Kenny Vilella, Tobias Widmer, Gordon Yeoman, Tiffany Chen, Sergey Grizan, Cathy Li, Lotus Li, Connor Smith, Rafael Wiltz, Kostas Alexis, Yan Chang, David Chu, Linxi "Jim" Fan, Farbod Farshidian, Ankur Handa, Spencer Huang, Marco Hutter, Yashraj Narang, Soha Pouya, Shiwei Sheng, Yuke Zhu, Miles Macklin, Adam Moravanszky, Philipp Reist, Yunrong Guo, David Hoeller, and Gavriel State. Isaac lab: A gpu-accelerated simulation framework for multi-modal robot learning. *arXiv preprint arXiv:2511.04831*, 2025. URL <https://arxiv.org/abs/2511.04831>.
- Soroush Nasiriany, Abhiram Maddukuri, Lance Zhang, Adeet Parikh, Aaron Lo, Abhishek Joshi, Ajay Mandlekar, and Yuke Zhu. RoboCasa: Large-scale simulation of household tasks for generalist robots. In *Robotics: Science and Systems Foundation*, 2024.
- NVIDIA Isaac Lab Arena Contributors. Isaac lab arena: Composable environment creation and policy evaluation for robotics, 2025. URL <https://github.com/isaac-sim/IsaacLab-Arena>.
- Tim Schneider, Guillaume Duret, Cristiana de Farias, Roberto Calandra, Liming Chen, and Jan Peters. Tactile mnist: Benchmarking active tactile perception. *arXiv preprint arXiv:2506.06361*, 2025.
- Alessandra Sciutti, Ambra Bisio, Francesco Nori, Giorgio Metta, Luciano Fadiga, and Giulio Sandini. Robots can be perceived as goal-oriented agents. *Interaction Studies*, 14(3):329–350, 2013.
- Haoyu Xiong, Xiaomeng Xu, Jimmy Wu, Yifan Hou, Jeannette Bohg, and Shuran Song. Vision in action: Learning active perception from human demonstrations. In *Conference on Robot Learning*, pages 5450–5463. PMLR, 2025.
- Justin Yu, Yide Shentu, Di Wu, Pieter Abbeel, Ken Goldberg, and Philipp Wu. EgoMI: Learning active vision and whole-body manipulation from egocentric human demonstrations. *arXiv e-prints*, pages arXiv–2511, 2025.
- Xueyang Zhou, Yangming Xu, Guiyao Tie, Yongchao Chen, Guowen Zhang, Duanfeng Chu, Pan Zhou, and Lichao Sun. LIBERO-PRO: Towards robust and fair evaluation of Vision-Language-Action models beyond memorization. *arXiv e-prints*, pages arXiv–2510, 2025.

Supplementary Material

A Task Specifications

Shared configuration. TAVIS-Head tasks use a fixed pool of 5 YCB objects (*soup can*, *meat can*, *tuna can*, *gelatin box*, *pudding box*; uniformly scaled $0.75\times$) on a 1.0m-high table. The fixed camera is positioned at (0.2, 0, 1.43) m (thus above the workspace, slightly in front of the robot), and angled $\sim 45^\circ$ downward to provide a 120° wide-angle coverage of the manipulation area, recording 640×480 RGB. Scene lighting is held constant (800 lux dome + 2000 lux distant). Episodes are capped at 20 s; teleoperation episodes are operator-terminated (no enforced cap).

Per-episode variance at evaluation arises entirely from task-scene randomization; the deterministic post-reset state lies mostly inside the training start-state distribution on the axes we measured (Appendix C), ruling out first-frame OOD as a confound.

Prompts.

- *conditional-pick*: "Look at the card. If it is red, pick the object on the left. If it is green, pick the object on the right."
- *wait-then-act*: "Watch the red light. When it turns green, pick up the object."
- *clutter-pick-cube & blocked-clutter-pick-cube*: "Find the red cube and pick it up."
- *clutter-pick-lift*: object-conditional (3 phrasings $\times$ 5 objects = 15 prompts; e.g., "Pick up the tomato soup can and lift it.>").
- *multi-shelf-scan*: object-conditional (15 prompts; e.g., "Find the tomato soup can on the shelf and bring it to me.>").
- *peeking-box*: "Retrieve the object from inside the box."
- *occluded-reach*: "Reach around the screen and pick up the object behind it."

Object-conditional prompts. *clutter-pick-lift* and *multi-shelf-scan* each use 3 phrasings per object across the 5 TAVIS-Head YCB objects (15 prompts per task):

- *clutter-pick-lift*:
 - *soup can*: "Pick up the tomato soup can and lift it." / "Grasp the soup can and hold it up." / "Lift the red soup can off the table."
 - *meat can*: "Pick up the potted meat can and lift it." / "Grasp the can of spam and hold it up." / "Lift the meat can off the table."
 - *tuna fish can*: "Pick up the tuna fish can and lift it." / "Grasp the tuna can and hold it up." / "Lift the tuna fish can off the table."
 - *gelatin box*: "Pick up the gelatin box and lift it." / "Grasp the gelatin box and hold it up." / "Lift the gelatin box off the table."
 - *pudding box*: "Pick up the pudding box and lift it." / "Grasp the pudding box and hold it up." / "Lift the pudding box off the table."
- *multi-shelf-scan*:
 - *soup can*: "Find the tomato soup can on the shelf and bring it to me." / "Retrieve the soup can from the shelves." / "Look through the shelves, find the red soup can, and take it."
 - *meat can*: "Find the potted meat can on the shelf and bring it to me." / "Retrieve the spam can from the shelves." / "Look through the shelves, find the meat can, and take it."
 - *tuna fish can*: "Find the tuna fish can on the shelf and bring it to me." / "Retrieve the tuna can from the shelves." / "Look through the shelves, find the tuna can, and take it."
 - *gelatin box*: "Find the gelatin box on the shelf and bring it to me." / "Retrieve the gelatin box from the shelves." / "Look through the shelves, find the gelatin box, and take it."
 - *pudding box*: "Find the pudding box on the shelf and bring it to me." / "Retrieve the pudding box from the shelves." / "Look through the shelves, find the pudding box, and take it."

Per-task scenes, randomization, and success criteria. Table 2 summarises the per-task scene composition, in-distribution (*id*) spatial ranges, the wider *ood-spatial* ranges, and the success criterion. The *ood-init-pose* split applies a global Gaussian perturbation to the robot’s reset pose (Section 4) and is not task-specific.

Table 2: **Per-task specifications.** Scene composition and randomization ranges for the 8 TAVIS tasks. Position ranges are in metres; rotations in degrees. Success requires the listed object position threshold and end-effector velocity < 1 m/s (held briefly to avoid mid-flight detection).

Task	Scene	ID area	OOD area	Success
<i>TAVIS-Head</i>				
conditional-pick	2 YCB + cue card	objs: 10×10 cm strips at $ y = 20$ cm; card: 10×10 cm centred	objs: 20×25 cm strips at $ y \approx 22$ cm; card: 20×16 cm centred	target $z > 1.2$ m
wait-then-act	1 YCB + signal light	obj: 10×24 cm; light: 10×20 cm at $x = 0.65$ m; cue delay $\in [2, 5]$ s	obj: 20×40 cm; light: 20×30 cm; delay $\in [2, 8]$ s	light green AND target $z > 1.2$ m
clutter-pick-cube	4 YCB distractors + red cube (5.5 cm)	10×50 cm; min separation 10 cm	20×70 cm; min separation 5 cm	cube $z > 1.2$ m
clutter-pick-lift	5 YCB; one is target	same as clutter-pick-cube	same as clutter-pick-cube	target $z > 1.2$ m
multi-shelf-scan	5 YCB on 3- shelf unit (heights 0.97/1.10/1.27 m)	per-slot jitter $\Delta x, \Delta y \leq 3$ cm	$\Delta y \leq 10$ cm, $\Delta x \leq 3$ cm	target $x < 0.46$ m
<i>TAVIS-Hands</i>				
peeking-box	1 YCB inside open-side box ($20 \times 14 \times 20$ cm)	box $\pm(2, 4)$ cm, yaw $\pm 5^\circ$; obj inside $\pm(4, 2)$ cm	box $\pm(4, 4)$ cm, yaw $\pm 10^\circ$; obj inside $\pm(4, 4)$ cm	target $z > 1.25$ m
occluded-reach	1 YCB behind screen (16×40 cm panel at $x = 0.27$ m)	obj 10×40 cm	obj 17×60 cm	target $z > 1.25$ m
blocked-clutter-pick-cube	inherits clutter-pick-cube; head-camera blacked out	inherited from clutter-pick-cube	inherited from clutter-pick-cube	cube $z > 1.2$ m

B Robot Specifications

Both TAVIS robots share a unified 19-dimensional canonical action space, abstracting away the underlying models to enable cross-embodiment evaluation:

- **Indices 0–6:** left-arm IK target, $(x, y, z, q_w, q_x, q_y, q_z)$ in canonical frame.
- **Indices 7–13:** right-arm IK target, same parameterisation.
- **Indices 14–16:** head roll, pitch, yaw (radians, absolute).
- **Indices 17–18:** left, right gripper, normalised $[-1, 1]$ scalar.

A canonical-frame wrapper translates EEF targets between the canonical hip-centric frame and each robot’s root frame using a fixed offset; orientation, head, and gripper actions pass through unchanged. Arm IK uses damped least-squares null-space solving. Per-robot models include additional locked DoFs (waist, legs, mobile base, antennas) clamped via high stiffness (10^7); the canonical action space exposes only the controlled joints. Grippers differ in hardware (GR1T2: Robotiq 2F-85 parallel; Reachy2: custom Pollen with mimic fingers) but expose the same scalar action. Neck roll is implemented in the library and Quest 3 teleoperation app, but disabled in our experiments.

Because of the canonical action space and composable nature of the TAVIS codebase, it is possible to extend the benchmark with new robots, only requiring the new robot’s USD, joint indices, gripper interface, and the hip-frame offset.

Cameras. All on-board cameras (head, left wrist, right wrist) record 640×480 RGB. Head camera FOV $\approx 70^\circ$ (focal length 15 mm); wrist cameras $\approx 53^\circ$ (21 mm). Camera link mounts vary slightly across robots due to head/hand-link geometry differences; the canonical role – on-board observation streams synchronised to the agent’s gaze and hand motion – is identical.

Control frequency. Teleoperation is recorded at 60 Hz. Policies are queried at 20 Hz during training and evaluation (downsampled by a factor of 3, matching common practice in the field).

C Demonstration Collection Protocol

Hardware. All demonstrations were collected by a single operator using a Meta Quest 3 VR headset over a wired link, with the simulated head-camera view streamed to the HMD and bimanual controllers driving the robot’s arms.

Per-episode protocol. On reset, the robot’s pose snaps to track the operator’s current controller pose; the operator scans the scene briefly via head movement, returns to a near-default gaze, and then begins the recorded segment. Recording therefore starts from an operator-driven, near-canonical pose rather than the deterministic post-reset state, producing realistic mildly varied starting conditions and motivating the *ood-init-pose* evaluation axis (Section 4).

Initial-state distributions. Figure 4 compares the teleop dataset’s frame-0 distribution (green), the *id* eval reset (black dashed), and the *ood-init-pose* eval distribution (red) per robot. The *ood-init-pose* perturbation extends well beyond dataset support on every dimension, especially on neck pitch and yaw where the dataset starts each episode at a near-fixed pose. Some sampled poses are physically awkward (e.g., EEF intersecting task geometry); since the same perturbation is applied uniformly across all checkpoints (Section 4), absolute success rates may be biased downward but cross-method comparisons remain valid.

D Supplementary Methods

Baseline training setup. Both Diffusion Policy Chi et al. [2023] and π_0 Black et al. [2024] are trained via their LeRobot Cadene et al. [2024] implementations. π_0 checkpoints fine-tune from the official LeRobot pretrained baseline (lerobot/pi0_base) at two scopes: *single-task* (one checkpoint per (suite, robot, camera, task) tuple) and *multi-task* (one checkpoint per (suite, robot, camera) trained jointly over all suite tasks). Diffusion Policy is trained single-task only and only on tasks without language conditioning (*clutter-pick-lift* and *multi-shelf-scan* are excluded). Each setting trains two separate checkpoints – one for headcam observations and one for fixedcam.




Figure 4: **Initial-state distributions: teleop dataset, *id* eval reset, and *ood-init-pose* perturbation.** Rows: robot (GR1T2 top, Reachy2 bottom). Columns: end-effector position x , $|y|$, z (metres), and neck pitch, yaw (degrees). Histograms and KDEs compare the frame-0 distribution in the teleoperation dataset (green) with the *ood-init-pose* eval distribution (red, $\sigma_{\text{pos}} = 0.1$ m and $\sigma_{\text{head}} = 0.175$ rad $\approx 10^\circ$); the deterministic *id* eval reset, a single value per dimension, is shown as a black dashed line. End-effector y is reported in absolute value because demonstrations are bilaterally symmetric.

Training duration. π_0 multi-task checkpoints were trained for 120k steps initially. For GR1T2 this produced strong results across all TAVIS-Head tasks. For Reachy2, the 120k checkpoint underperformed the corresponding single-task baselines on several tasks (notably *wait-then-act* fixedcam at $\sim 5\%$ SR), suggesting overfitting on its smaller effective dataset. A second Reachy2 multi-task checkpoint was trained for 60k steps with identical hyperparameters and seed; this checkpoint recovered SR on the previously-collapsed cells (e.g., *wait-then-act* fixedcam: $5\% \rightarrow 13\%$ id; headcam: $49\% \rightarrow 55\%$) without regressing elsewhere. We report the 60k checkpoint as canonical for Reachy2 multi-task and the 120k checkpoint for GR1T2 multi-task; the choice of 60k was guided by training-loss curves (still decreasing at 60k for GR1T2, plateaued for Reachy2) rather than eval SR. A more careful sweep over training duration is left to future work.

Constant-dimension normalization. A subtle failure mode arises in sim-based IL when observation dimensions have near-zero variance in the training data (e.g., locked joints, passive DoFs left to settle under gravity): standard mean/std normalization produces large coefficients that amplify tiny eval-time deviations into catastrophic apparent OOD signals. We implement a preprocessing step (`fix_constant_dims`) that detects these dimensions and applies identity normalization to them. This affected Reachy2 (where settle dynamics on its mobile base differ from GR1T2’s grounded torso) and was not necessary for GR1T2.

Confidence intervals. All success-rate confidence intervals reported in this paper use the Wilson score interval at $\alpha = 0.05$, computed via `statsmodels.stats.proportion.proportion_confint` with `method='wilson'`.

Hyperparameters and compute. Training hyperparameters and wall-clock estimates are listed in Table 3. Individual training runs used single NVIDIA H100 GPUs, while evaluation was run on a single NVIDIA GeForce RTX 4090, since raytracing is required.

E Supplementary Results

We report per-cell results that complement the main-text Table 1. Three tables follow, all using the same 96-episode-per-cell evaluation protocol and 95% Wilson confidence intervals: multi-task π_0 with explicit CIs (Table 4, mirroring Table 1), single-task π_0 checkpoints across all (suite, robot,

Table 3: **Training hyperparameters.** Both baselines use LeRobot defaults except where noted.

	Diffusion Policy	π_0
Parameters	272.5 M	3.5 B
Optimizer	AdamW	AdamW
Learning rate	1×10^{-4}	2.5×10^{-5}
Weight decay	1×10^{-6}	1×10^{-2}
Batch size (per device)	16	16
Mixed precision	bfloat16	bfloat16
Observation horizon	2 frames	1 frame
Prediction horizon	16 frames (0.8s)	16 frames (0.8s)
Action chunk size	8 frames (0.4s)	8 frames (0.4s)
Image resolution	320×240	224×224 (PaLiGemma)
Noise schedule	DDPM, sq.cos.cap.v2 (100 steps)	—
Training steps (single-task)	200k	15k
Training steps (multi-task)	—	60k (Reachy2) / 120k (GRIT2)

camera, task) tuples (Table 5), and single-task Diffusion Policy checkpoints (Table 6). Single-task DP entries for the two language-conditioned TAVIS-Head tasks (*clutter-pick-lift*, *multi-shelf-scan*) are absent by design.

Diffusion Policy vs π_0 (single-task). The two methods produce qualitatively similar findings on TAVIS: head-vs-fixed gaps on TAVIS-Head, OOD degradation patterns, and per-task ordering are largely consistent. In absolute single-task ID success, Diffusion Policy is competitive with – and on several TAVIS-Head tasks, outperforms – π_0 at the same scope (e.g., GRIT2 headcam suite mean: 54.2% vs 25.8%). This is not an apples-to-apples comparison: π_0 single-task fine-tunes a strong pretrained checkpoint for 15k steps, while Diffusion Policy trains from scratch for 200k steps. π_0 ’s relative advantage materialises in the multi-task scope (Table 4), which Diffusion Policy cannot access in its standard form due to the absence of language conditioning.

Implicit language-prompting comparison. Two of the five TAVIS-Head tasks – *clutter-pick-lift* and *multi-shelf-scan* – include natural-language conditioning across three prompt variants for each object in the task (i.e., 15 different prompts per task), while the other three use a single fixed objective. Despite 250 vs. 100 demonstrations, the language-prompted tasks reach only $\sim 19\%$ multi-task π_0 id headcam SR (averaged across robots) against $\sim 59\%$ for the non-prompted ones. We do not read this as a clean language-vs.-no-language ablation: the language tasks are also our most complex in absolute terms, and per (object, prompt) tuple they actually receive fewer demonstrations than the non-prompted counterparts (~ 17 vs. 20). Disentangling language conditioning from task complexity at matched data budgets is left to future work; we report the gap here as an implicit observation built into the existing benchmark design.

Table 4: **Multi-task π_0 success rates (%) on TAVIS, with 95% Wilson confidence intervals.** Same checkpoints, evaluation episodes (96 per cell), column structure, and split definitions as Table 1; intervals are computed per cell using the Wilson score method.

multi-task (π_0 , 95% CI)	GRIT2						Reachy2					
	id		ood-spatial		ood-init-pose		id		ood-spatial		ood-init-pose	
	head	fixed	head	fixed	head	fixed	head	fixed	head	fixed	head	fixed
TAVIS-Head												
conditional-pick	87.5 [79.4,92.7]	59.4 [49.4,68.7]	49.0 [39.2,58.8]	32.3 [23.8,42.2]	2.1 [0.6,7.3]	12.5 [7.3,20.6]	52.1 [42.2,61.8]	7.3 [3.6,14.3]	27.1 [19.2,36.7]	10.4 [5.8,18.1]	12.5 [7.3,20.6]	9.4 [5.0,16.9]
wait-then-act	65.6 [55.7,74.4]	88.5 [80.6,93.5]	44.8 [35.2,54.7]	61.5 [51.5,70.6]	3.1 [1.1,8.8]	15.6 [9.7,24.2]	55.2 [45.3,64.8]	13.5 [8.1,21.8]	32.3 [23.8,42.2]	5.2 [2.2,11.6]	14.6 [8.9,23.0]	10.4 [5.8,18.1]
clutter-pick-cube	41.7 [32.3,51.7]	32.3 [23.8,42.2]	26.0 [18.3,35.6]	27.1 [19.2,36.7]	0.0 [0.0,3.8]	12.5 [7.3,20.6]	50.0 [40.2,59.8]	20.8 [13.9,30.0]	26.0 [18.3,35.6]	12.5 [7.3,20.6]	16.7 [10.5,25.4]	8.3 [4.3,15.6]
clutter-pick-lift	22.9 [15.6,32.3]	13.5 [8.1,21.8]	9.4 [5.0,16.9]	11.5 [6.5,19.4]	0.0 [0.0,3.8]	4.2 [1.6,10.2]	18.8 [12.2,27.7]	10.4 [5.8,18.1]	9.4 [5.0,16.9]	9.4 [5.0,16.9]	5.2 [2.2,11.6]	4.2 [1.6,10.2]
multi-shelf-scan	17.7 [11.4,26.5]	0.0 [0.0,3.8]	10.4 [5.8,18.1]	4.2 [1.6,10.2]	4.2 [1.6,10.2]	5.2 [2.2,11.6]	17.7 [11.4,26.5]	14.6 [8.9,23.0]	15.6 [9.7,24.2]	7.3 [3.6,14.3]	7.3 [3.6,14.3]	9.4 [5.0,16.9]
<i>suite mean</i>	47.1 [42.7,51.6]	38.8 [34.5,43.2]	27.9 [24.1,32.1]	27.3 [23.5,31.4]	1.9 [1.0,3.5]	10.0 [7.6,13.0]	38.8 [34.5,43.2]	13.3 [10.6,16.7]	22.1 [18.6,26.0]	9.0 [6.7,11.8]	11.2 [8.7,14.4]	8.3 [6.2,11.1]
TAVIS-Hands												
peeking-box	64.6 [54.6,73.4]		51.0 [41.2,60.8]		15.6 [9.7,24.2]		84.4 [75.8,90.3]		68.8 [58.9,77.1]		39.6 [30.4,49.6]	
occluded-reach	87.5 [79.4,92.7]		60.4 [50.4,69.6]		24.0 [16.5,33.4]		78.1 [68.9,85.2]		43.8 [34.3,53.7]		43.8 [34.3,53.7]	
blocked-clutter-pick-cube	58.3 [48.3,67.7]		35.4 [26.6,45.4]		4.2 [1.6,10.2]		67.7 [57.8,76.2]		40.6 [31.3,50.6]		31.2 [22.9,41.1]	
<i>suite mean</i>	70.1 [64.6,75.1]		49.0 [43.2,54.7]		14.6 [11.0,19.1]		76.7 [71.5,81.2]		51.0 [45.3,56.8]		38.2 [32.8,43.9]	

Table 5: **Single-task π_0 success rates (%) on TAVIS, with 95% Wilson confidence intervals.** Each cell corresponds to an independent π_0 checkpoint trained on a single (suite, robot, camera-mode, task) tuple and evaluated for 96 episodes. Column structure and split definitions are identical to Table 1.

single-task (π_0 , 95% CI)	GRIT2						Reachy2					
	id		ood-spatial		ood-init-pose		id		ood-spatial		ood-init-pose	
	head	fixed	head	fixed	head	fixed	head	fixed	head	fixed	head	fixed
TAVIS-Head												
conditional-pick	42.7 [33.3,52.7]	59.4 [49.4,68.7]	12.5 [7.3,20.6]	19.8 [13.1,28.9]	1.0 [0.2,5.7]	10.4 [5.8,18.1]	46.9 [37.2,56.8]	43.8 [34.3,53.7]	22.9 [15.6,32.3]	11.5 [6.5,19.4]	37.5 [28.5,47.5]	37.5 [28.5,47.5]
wait-then-act	63.5 [53.6,72.5]	52.1 [42.2,61.8]	17.7 [11.4,26.5]	29.2 [21.0,38.9]	31.2 [22.9,41.1]	22.9 [15.6,32.3]	61.5 [51.5,70.6]	60.4 [50.4,69.6]	42.7 [33.3,52.7]	26.0 [18.3,35.6]	43.8 [34.3,53.7]	37.5 [28.5,47.5]
clutter-pick-cube	17.7 [11.4,26.5]	27.1 [19.2,36.7]	16.7 [10.5,25.4]	14.6 [8.9,23.0]	5.2 [2.2,11.6]	12.5 [7.3,20.6]	62.5 [52.5,71.5]	14.6 [8.9,23.0]	38.5 [29.4,48.5]	3.1 [1.1,8.8]	18.8 [12.2,27.7]	7.3 [3.6,14.3]
clutter-pick-lift	0.0 [0.0,3.8]	10.4 [5.8,18.1]	0.0 [0.0,3.8]	1.0 [0.2,5.7]	0.0 [0.0,3.8]	4.2 [1.6,10.2]	13.5 [8.1,21.8]	14.6 [8.9,23.0]	7.3 [3.6,14.3]	5.2 [2.2,11.6]	6.2 [2.9,13.0]	15.6 [9.7,24.2]
multi-shelf-scan	5.2 [2.2,11.6]	0.0 [0.0,3.8]	1.0 [0.2,5.7]	1.0 [0.2,5.7]	6.2 [2.9,13.0]	6.2 [2.9,13.0]	13.5 [8.1,21.8]	5.2 [2.2,11.6]	9.4 [5.0,16.9]	6.2 [2.9,13.0]	8.3 [4.3,15.6]	2.1 [0.6,7.3]
<i>suite mean</i>	25.8 [22.1,29.9]	29.8 [25.9,34.0]	9.6 [7.3,12.5]	13.1 [10.4,16.4]	8.8 [6.5,11.6]	11.2 [8.7,14.4]	39.6 [35.3,44.0]	27.7 [23.9,31.9]	24.2 [20.6,28.2]	10.4 [8.0,13.5]	22.9 [19.4,26.9]	20.0 [16.7,23.8]
TAVIS-Hands												
peeking-box	47.9 [38.2,57.8]		38.5 [29.4,48.5]		21.9 [14.8,31.1]		72.9 [63.3,80.8]		46.9 [37.2,56.8]		56.2 [46.3,65.7]	
occluded-reach	68.8 [58.9,77.1]		36.5 [27.5,46.4]		11.5 [6.5,19.4]		53.1 [43.2,62.8]		29.2 [21.0,38.9]		40.6 [31.3,50.6]	
blocked-clutter-pick-cube	44.8 [35.2,54.7]		21.9 [14.8,31.1]		10.4 [5.8,18.1]		33.3 [24.7,43.2]		32.3 [23.8,42.2]		25.0 [17.4,34.5]	
<i>suite mean</i>	53.8 [48.0,59.5]		32.3 [27.2,37.9]		14.6 [11.0,19.1]		53.1 [47.4,58.8]		36.1 [30.8,41.8]		40.6 [35.1,46.4]	

Table 6: **Single-task Diffusion Policy success rates (%) on TAVIS, with 95% Wilson confidence intervals.** Each cell corresponds to an independent Diffusion Policy Chi et al. [2023] checkpoint trained on a single (suite, robot, camera-mode, task) tuple and evaluated for 96 episodes. Diffusion Policy is trained only on tasks without language conditioning, so *clutter-pick-lift* and *multi-shelf-scan* are excluded (marked ‘-’). Column structure and split definitions are identical to Table 1.

single-task (diffusion, 95% CI)	GRIT2						Reachy2					
	id		ood-spatial		ood-init-pose		id		ood-spatial		ood-init-pose	
	head	fixed	head	fixed	head	fixed	head	fixed	head	fixed	head	fixed
TAVIS-Head												
conditional-pick	47.9 [38.2,57.8]	33.3 [24.7,43.2]	21.9 [14.8,31.1]	9.4 [5.0,16.9]	12.5 [7.3,20.6]	19.8 [13.1,28.9]	40.6 [31.3,50.6]	40.6 [31.3,50.6]	21.9 [14.8,31.1]	7.3 [3.6,14.3]	21.9 [14.8,31.1]	20.8 [13.9,30.0]
wait-then-act	71.9 [62.2,79.9]	43.8 [34.3,53.7]	36.5 [27.5,46.4]	12.5 [7.3,20.6]	40.6 [31.3,50.6]	16.7 [10.5,25.4]	68.8 [58.9,77.1]	25.0 [17.4,34.5]	30.2 [21.9,40.0]	10.4 [5.8,18.1]	20.8 [13.9,30.0]	28.1 [20.1,37.8]
clutter-pick-cube	42.7 [33.3,52.7]	30.2 [21.9,40.0]	41.7 [32.3,51.7]	20.8 [13.9,30.0]	18.8 [12.2,27.7]	13.5 [8.1,21.8]	31.2 [22.9,41.1]	14.6 [8.9,23.0]	27.1 [19.2,36.7]	14.6 [8.9,23.0]	24.0 [16.5,33.4]	9.4 [5.0,16.9]
clutter-pick-lift	-	-	-	-	-	-	-	-	-	-	-	-
multi-shelf-scan	-	-	-	-	-	-	-	-	-	-	-	-
<i>suite mean</i>	54.2 [48.4,59.8]	35.8 [30.4,41.5]	33.3 [28.1,39.0]	14.2 [10.7,18.7]	24.0 [19.4,29.2]	16.7 [12.8,21.4]	46.9 [41.2,52.6]	26.7 [22.0,32.1]	26.4 [21.6,31.8]	10.8 [7.7,14.9]	22.2 [17.8,27.4]	19.4 [15.3,24.4]
TAVIS-Hands												
peeking-box	69.8 [60.0,78.1]		54.2 [44.2,63.8]		43.8 [34.3,53.7]		56.2 [46.3,65.7]		47.9 [38.2,57.8]		43.8 [34.3,53.7]	
occluded-reach	83.3 [74.6,89.5]		52.1 [42.2,61.8]		27.1 [19.2,36.7]		39.6 [30.4,49.6]		31.2 [22.9,41.1]		46.9 [37.2,56.8]	
blocked-clutter-pick-cube	37.5 [28.5,47.5]		28.1 [20.1,37.8]		17.7 [11.4,26.5]		28.1 [20.1,37.8]		22.9 [15.6,32.3]		15.6 [9.7,24.2]	
<i>suite mean</i>	63.5 [57.8,68.9]		44.8 [39.2,50.6]		29.5 [24.5,35.0]		41.3 [35.8,47.1]		34.0 [28.8,39.7]		35.4 [30.1,41.1]	

F Dataset Documentation

Format and hosting. The four TAVIS datasets (one per suite $\times$ robot combination, totalling ~ 2200 episodes and $\sim 3\text{h}$ of teleoperation, 800 episodes per robot in the head suite, 300 per robot in the hands one) are released as LeRobotDataset v3.0 repositories on the project Hugging Face organisation⁴, under a CC-BY-4.0 license. Each dataset includes synchronised head, fixed, left-wrist, and right-wrist RGB streams (640×480 , MP4-encoded), full proprioceptive state, 19-dimensional canonical actions, and per-episode language instructions where applicable. Episodes are further labelled with the Python class name (task field) for the corresponding task, so that single-task training is possible by filtering episodes from the published multi-task datasets.

Structured metadata (Croissant). Each dataset has an automatically generated MLCommons Croissant file at `huggingface.co/api/datasets/<repo>/croissant`, augmented with the Croissant-RAI extension fields (intended use, biases, limitations, sensitive-information disclosure, social impact); the augmented files are submitted as supplementary material on OpenReview.

Maintenance. The benchmark is maintained by the authors via the project code repository (`https://github.com/spiglerg/tavis`) and the Hugging Face organisation. The authors commit to issue triage and PR review for at least two years post-publication. Future versions (additional tasks, robots, scene variations) will be released as new tagged versions in the repository.

Reproducibility. All training and evaluation scripts are publicly released alongside the datasets; pretrained π_0 multi-task checkpoints are hosted as separate model repositories on the same Hugging Face organisation.

G GALT (Gaze-Action Lead Time): Algorithm, Hyperparameters, and Validation

Algorithm overview. We implement a single, sim-free GALT detector that consumes only the episode’s commanded-action trajectory (Algorithm 1). The action stream exposes neck joint targets, end-effector Cartesian targets, and gripper commands, which together are sufficient to identify the two events that define GALT: the latest gripper state change in the episode (anchor, t^{hand}) and the matching head fixation (t^{head}) found within a backward search window from the anchor. GALT is then $t^{\text{hand}} - t^{\text{head}}$, in seconds. A positive GALT indicates the head arrived at the task-relevant fixation before the gripper event, consistent with the active-vision pattern observed in teleoperation. The detector additionally validates that the gripper event was preceded by a real end-effector reach (i.e., a stable-to-motion transition before the anchor); episodes lacking such a reach are rejected as spurious. Because the detector relies on commanded actions rather than simulator state or external sensing, the metric transfers unchanged to real-robot deployments. For tasks with multiple grasp/release events per episode, the algorithm generalises trivially by iterating over all anchors and returning a list of per-event GALTs; the released implementation returns a single value anchored on the last gripper event, sufficient for the task suite reported here.

Extensibility to other robots. GALT is intentionally a *family* of metrics rather than a single fixed algorithm, parameterised by which channels of the action vector represent arm end-effector positions, head joints, and gripper states. Our released implementation expresses this via a small `ActionLayout` specification mapping these channels to indices in the canonical 19-dimensional action vector. Any robot whose policy outputs include or can compute arm-EE-position, head-joint, and gripper-scalar streams can plug into the same code. Users with their own datasets only need to construct the corresponding action trajectory to apply the detector as-is.

Hyperparameter calibration. All GALT hyperparameters (Table 8) were calibrated once on teleoperation reference episodes and applied *unchanged* to all policy rollouts reported in this paper. Differences between teleop and policy GALT distributions therefore reflect behavioural differences, not detector differences.

Parameter rationale. The two speed thresholds (v_h, v_n) distinguish “moving” from “holding” phases in the commanded trajectory; their values reflect typical teleoperation noise floors on EE pose (a few cm/s) and neck joints (a few deg/s). The persistence windows (K_f, τ_s) suppress brief

⁴<https://huggingface.co/tavis-benchmark>

Input : Action trajectory $A \in \mathbb{R}^{T \times 19}$, sampling rate f Hz, hyperparameters (Table 8).

Output : GALT $g \in \mathbb{R}$ in seconds, or stop with reason code.

$\dot{q}_n \leftarrow$ per-step neck angular speed

foreach arm $a \in \{L, R\}$ **do**

$\dot{p}_a \leftarrow$ per-step end-effector linear speed; $E_a \leftarrow$ gripper-command sign changes

$t_a^{\text{hand}} \leftarrow \max E_a$ // gripper anchor

$t_a^{\text{onset}} \leftarrow$ end of latest $\geq \tau_s f$ -step run with $\dot{p}_a < v_h$, before t_a^{hand}

if none then skip (no_hand_onset)

$t_a^{\text{head}} \leftarrow$ start of nearest $\geq K_f f$ -step run with $\dot{q}_n < v_n$ within $[t_a^{\text{hand}} - Lf, t_a^{\text{hand}} + Sf]$, refined back in joint-position space within margin r

if none then skip (no_fixation)

$g_a \leftarrow (t_a^{\text{hand}} - t_a^{\text{head}})/f$

if $g_a \notin [\gamma_{\min}, \gamma_{\max}]$ **then skip** (outlier)

 arm a valid with value g_a

end

if both arms valid then return ambiguous_arms

if no arm valid then return most informative skip reason

return GALT = g_{a^*} for the unique valid arm a^*

Algorithm 1: GALT (Gaze-Action Lead Time) detector. Operates on the canonical 19-D action trajectory only; anchor is the last gripper-command sign change, and a valid result requires unique-arm validation.

oscillations near the thresholds: K_f requires a fixation to last at least ~ 80 ms before counting, and τ_s requires ~ 300 ms of prior stillness before a hand onset is declared, ensuring we pick up genuine stable-to-motion transitions rather than mid-reach micro-pauses. The search windows (L, S) are generous enough to cover multi-second gaze-ahead patterns while cutting off at 3 s pre-anchor to avoid picking up fixations from earlier task phases. The refinement margin r ($\sim 3^\circ$) handles the smooth-deceleration case where the head reaches its fixation direction well before the velocity threshold is crossed; walking back in joint-position space recovers the true onset of fixation. Finally, $[\gamma_{\min}, \gamma_{\max}]$ discards pathological detections (e.g., gripper events unrelated to the task grasp) without changing the success-rate denominator: an outlier-flagged episode contributes to SR but not to the GALT distribution.

Detection-rate validation. On the teleoperation reference episodes (TAVIS-Head, $n = 800$ per robot), the detector produces a valid GALT reading for 98.8% of GR1T2 and 98.9% of Reachy2 demonstrations at the native 60 Hz dataset rate (Table 7), confirming that the heuristic reliably captures the gaze-manipulation structure embedded in expert behaviour. At the 20 Hz policy-evaluation stride, detection rate drops to 85.6% (GR1T2) and 93.0% (Reachy2) – entirely due to a tighter τ_s stability budget (only 6 frames at 20 Hz vs 18 at 60 Hz). Critically, the pooled median GALT itself is stable to within ± 20 ms across sampling rates, confirming that the metric is robust to evaluation stride and that the policy-rollout GALT distributions reported in the main text are not biased by the rate change.

Table 7: **GALT detection-rate validation on teleoperation reference episodes.** Pooled across the 5 TAVIS-Head tasks, $n = 800$ episodes per robot. Mean and median GALT shown only for valid (non-rejected) episodes.

	Detection rate	Pooled mean GALT (s)	Pooled median GALT (s)
GR1T2 @ 60 Hz (native)	790/800 (98.8%)	2.57	2.57
GR1T2 @ 20 Hz (eval stride)	685/800 (85.6%)	2.55	2.55
Reachy2 @ 60 Hz (native)	791/800 (98.9%)	2.10	2.10
Reachy2 @ 20 Hz (eval stride)	744/800 (93.0%)	2.11	2.10

Table 8: **GALT detector hyperparameters.** Calibrated once on the teleoperation reference episodes and applied unchanged to all policy rollouts. Code-side variable names: v_h =v_hand_thresh, v_n =v_sac_thresh, K_f =K_fix_s, τ_s =min_stable_for_onset_s, L =lookback_s, S =forward_slack_s, r =arrival_margin_rad, $\gamma_{\min, \max}$ =outlier_min/max_s.

Symbol	Value	Unit	Description
<i>Speed thresholds (moving phase vs. stationary phase)</i>			
v_h	0.05	m/s	End-effector commanded linear-speed floor.
v_n	0.10	rad/s	Neck commanded angular-speed floor.
<i>Persistence / stability windows</i>			
K_f	0.080	s	Minimum duration below v_n to qualify as a fixation.
τ_s	0.300	s	Minimum stable (below- v_h) duration preceding a hand onset.
<i>Search windows around the gripper anchor</i>			
L	3.0	s	Backward lookback horizon for head-arrival candidates.
S	0.5	s	Post-anchor slack for head-arrival candidates.
<i>Arrival refinement</i>			
r	0.05	rad ($\approx 2.9^\circ$)	L_∞ neck-joint margin defining “at final fixation”.
<i>Outlier bounds on the final GALT value</i>			
$\gamma_{\min}$	-0.5	s	Below this $\Rightarrow$ outlier_low.
$\gamma_{\max}$	4.0	s	Above this $\Rightarrow$ outlier_high.