

From Multi-Fisheye Sensing to Panoramic Perception: A Parallax-Aware Onboard Platform for Ultra-Low-Altitude UAVs

Dun Dai*, Ze Lu*, Cheng He, Yaowen Wang, and Quan Quan†

Abstract—Ultra-low-altitude unmanned aerial vehicles (UAVs) require surround vision near buildings, vegetation, and other obstacles. We present a parallax-aware onboard platform that converts four synchronized fisheye streams into an open 1280×640 equirectangular panorama (ERP) interface. A purpose-built carbon-fiber airframe integrates the cameras, NVIDIA Jetson Orin NX, a flight controller, and a global navigation satellite system (GNSS) receiver. The formation pipeline selects projection depth per overlap and combines controlled seams and photometric fusion. Its accuracy profile adds content-adaptive seam search and a validation-gated residual mesh, whereas its deployed profile retains margin-gated Per-seam updates for sensor-rate operation. Evaluation uses more than 50,000 four-view groups from 18 field sequences. Relative to Fixed Depth, the accuracy profile reduces far-field P90 feature misalignment by 41.6%; the deployed Per-seam profile achieves the lowest aggregate geometric errors across held-out sites. Under a paced 20 Hz replay, the deployed profile sustains 19.99 frames/s at 13.29 W mean module-input power. Eight-sector ERP sampling reaches 90.8% mean daytime visual-place-recognition Recall@5. Together, these results validate an integrated onboard panoramic-perception architecture that unifies parallax-aware formation, sensor-rate embedded execution, and reusable downstream vision interfaces for ultra-low-altitude UAVs. The project has been open-sourced at <https://github.com/DUNDAI1998/parallax-aware-uav-panorama>.

I. INTRODUCTION

Ultra-low-altitude unmanned aerial vehicles (UAVs) move between open views and cluttered areas near buildings, vegetation, and people. A forward camera can lose landmarks or objects during turns, whereas panoramic vision preserves surround-view context. In dynamic flight, limited visual coverage can couple sensing direction to avoidance decisions [1]. Raw fisheye views preserve calibration access and support specialized fisheye processing, but their separate optical centres, circular distortion, camera ordering, and overlap boundaries must otherwise be handled by every downstream module. We retain the raw views while forming an equirectangular panorama (ERP) as a continuous angular coordinate frame from which task-specific rectilinear sectors can be sampled consistently. This interface decouples multi-camera formation from reusable




Fig. 1. Concept of the parallax-aware onboard panoramic perception platform. Four synchronized fisheye streams are formed onboard into a continuous ERP stream that provides a common interface for object detection and localization.

vision models and makes angular coverage an explicit operating choice. The experiments in this paper validate the effectiveness of real-time onboard panorama formation as a reusable interface for downstream perception and localization. This advantage matters in practice only when a complete multi-camera system can form a geometrically useful panorama at the sensor rate within the onboard compute and power budgets.

Angular coverage is the first requirement. Four cameras have different optical centres, so near and far content require different projection depths. A mount or camera-order change can invalidate calibration, while independent exposure control produces visible colour layers. Closed consumer panoramic cameras hide the raw views and calibration. Open rigs expose them, but transfer synchronization, calibration, panorama formation, and runtime control to the robot. Existing aerial panoramic systems demonstrate segmentation or visual-inertial Simultaneous Localization and Mapping (SLAM) [2], [3]. The remaining systems gap is the combination of synchronized raw-view access, parallax-aware ERP formation, and measured embedded sensor-rate execution. Mechanical integration is also coupled to formation because camera placement determines overlap, baseline, and calibration.

We address this gap with a purpose-built lightweight airframe that embeds four hardware-synchronized global-shutter camera heads and integrates a Jetson Orin NX, a flight controller, and GNSS sensing. RflyPano introduced this multi-fisheye sensing arrangement in simulation [4]; the present work carries it into a physical platform for real-field panoramic perception. The platform exposes real-data interfaces and an embedded

Dun Dai, Ze Lu, and Yaowen Wang are with the School of Automation Science and Electrical Engineering, Beihang University, Beijing 100191, China (e-mail: d_dai_3@buaa.edu.cn; luze@buaa.edu.cn; 22375266@buaa.edu.cn). Cheng He is with the Tianmushan Laboratory, Hangzhou 311115, China (e-mail: bht0130@tmslab.cn).

Quan Quan is with the School of Automation Science and Electrical Engineering, Beihang University, Beijing 100191, China, and also with the Tianmushan Laboratory, Hangzhou 311115, China (e-mail: qq_bua@buaa.edu.cn).

* Dun Dai and Ze Lu contributed equally to this work. † Corresponding author: Quan Quan.

panorama formation pipeline. A calibration model binds camera order and geometry. The pipeline selects projection depth independently for each adjacent-camera overlap, then applies a dynamic seam, photometric correction, and two-band blending. Cached projection maps and multi-rate state updates reduce the per-frame embedded workload.

We evaluate the system along three axes. Field sequences from multiple sites test panorama geometry and colour; the proposed method is compared with fixed-feather, fixed-depth, and globally adaptive alternatives under a matched pipeline. Strict wall-clock Jetson measurements test whether the implementation sustains the 20 Hz camera stream within its compute and power budgets. Frozen object detection and visual place recognition models measure output-interface utility, while direct geometry and colour metrics independently assess local stitching quality.

The main contributions of this work are as follows:

- An open onboard multi-fisheye sensing platform that combines a purpose-built lightweight carbon-fiber airframe with four embedded camera heads, onboard computing, flight and navigation sensing, and open raw-view, panorama, calibration-metadata, and pose interfaces.
- A parallax-aware panorama formation pipeline that couples overlap-wise projection-depth adaptation, margin-gated temporal selection, and controlled photometric fusion with cached maps and multi-rate state updates for embedded execution, obtaining the lowest far-field median/P90 and two-site held-out cross-site geometric errors among the four matched pipelines.
- A system-level evaluation of geometric and photometric panorama quality, complete-path Jetson Orin NX performance, and frozen downstream perception and localization on real UAV data. The final profile sustains a strict 20 Hz input at 19.99 frames/s with 0.026% timed drops, 71.0% 50 ms timely outputs, and 13.29 W mean module-input power.

II. RELATED WORK

A. Aerial panoramic sensing and formation

Multi-sensor aerial datasets commonly use perspective cameras with inertial, GNSS, or LiDAR sensing [5], [6]. Aerial-PASS uses a panoramic annular lens for aerial segmentation, while PAIR360 provides six fisheye views and navigation sensors on a ground platform [2], [7]. Outside aerial robotics, FishEye8K shows the value and remaining distortion and calibration challenges of accessible multi-fisheye sensing [8]. Kim and Ueda combined real-time panoramic generation with dynamics-based motion deblurring for robotic vision [9]. PanoAir couples a consumer dual-fisheye camera with embedded panoramic visual-inertial SLAM [3]. OmniNxt is a closely related open compact multi-fisheye aerial platform that uses calibrated virtual views for onboard visual-inertial odometry and real-time dense mapping [10], but does not report a continuous sensor-rate ERP output. Our system instead exposes raw views and calibration while measuring real-time ERP formation, output quality, runtime cost, and downstream interfaces as parts of the integrated system design. Table I

TABLE I
PUBLIC AVAILABILITY AND OUTPUT INTERFACES OF RESEARCH AERIAL SYSTEMS AND COMMERCIAL 360 CAMERAS. ✓: PUBLICLY RELEASED; −: NOT RELEASED OR NOT STATED IN THE CITED SOURCE.

System/product	Hardware open	Software open	Data open	ERP out.	Fisheye out.
PanoAir [3]	−	✓	✓	✓	✓
RflyPano [4]	−	✓	✓	✓	✓
OmniNxt [10]	✓	✓	−	−	✓
Omni-Swarm [11]	−	✓	✓	−	✓
Insta360 X5/DJI Osmo 360 [12], [13]	−	−	−	✓	−
Ours	✓	✓	✓	✓	✓

summarizes these interface-level differences and reported validation scopes.

Parallax-aware stitching has progressed from spatially varying projective warps to structure-preserving, learned, and pixel-wise alignment [14]–[18]. Patch-wise alignment and gravity priors constrain seams and global orientation, while efficient learned matching improves pairwise correspondences [19]–[21]. These methods are mainly evaluated on image pairs. Airborne use also adds rig changes, exposure variation, temporal seam constraints, and bounded computation. To meet these constraints, our pipeline selects from a discrete projection-radius bank independently in each overlap and stabilizes continuous four-camera input with margin-gated temporal hysteresis and a coverage-constrained photometric fallback.

B. Embedded panoramic perception and localization

Panoramic segmentation methods address ERP distortion through domain adaptation, spherical geometry, or spherical attention [22]–[25]; panoramic depth estimation likewise requires explicit projection and cross-view consistency [26], [27]. For localization, modern place-recognition descriptors provide strong perspective-image baselines [28], [29], while 360Loc evaluates cross-device panoramic retrieval [30]. Recent aerial systems further connect onboard sensing with vehicle-level localization and vision-based interaction [31], [32]. RflyPano and AirSim360 provide aerial panoramic simulation resources [4], [33], whereas physical deployment introduces calibration changes, sensor-rate deadlines, and compute constraints. The cited perception and localization methods motivate our downstream tests. We keep these models frozen to measure field utility, while direct embedded tests evaluate camera-rate four-fisheye panorama formation.

III. SYSTEM DESIGN AND FIELD DATASET

The system integrates synchronized imaging, onboard panorama formation, flight and navigation sensing, and open data interfaces (Fig. 2). It exposes the four raw fisheye views, an ERP panorama, and timestamped navigation records. Raw views preserve access to calibration and alternative processing, while the ERP supplies a regular interface to downstream algorithms.

A. Integrated sensing, computing, and interfaces

The lightweight carbon-fiber frame was fabricated around the four-fisheye module. Its embedded camera heads face the




Fig. 2. Integrated four-fisheye UAV system and panorama formation. (a) Carbon-fiber airframe, camera heads, GNSS receiver, and Jetson Orin NX. (b) Integrated UAV. (c) Synchronized inputs are formed onboard into ERP; navigation is exported as timestamped metadata, and frozen downstream models evaluate the panorama offline.

front-left, front-right, rear-right, and rear-left instead of forming a separate panoramic payload. The platform measures $28 \times 28 \times 13.3$ cm and has a measured mass of 1002.3 g with a 4000 mAh battery and 693.2 g without it. It supports up to 500 g auxiliary payload and has a 4.2:1 thrust-to-weight ratio. With no auxiliary payload and the Jetson configured in 25 W mode, the measured endurance is 9 min. The Seeker Omni-4P provides four hardware-synchronized global-shutter streams at 1088×1280 , 20 Hz, and nominal 206° FOV through USB 3.0 [34].

An NVIDIA Jetson Orin NX Developer Kit with 16 GB memory receives each synchronized four-view group and forms a 1280×640 ERP target in a configured 25 W power mode. The system target is one published panorama per 20 Hz input group without unbounded queue growth. A MicoAir743v2-AIO-45A flight controller and MG-F10-A dual-band GNSS receiver provide navigation metadata when available [35], [36]. Table II lists the configuration relevant to sensing, onboard computation, and navigation interfaces.

B. Synchronization and calibration


The camera module hardware-synchronizes the four visual streams [34]. Each recorded visual group is stored as one

TABLE II
INTEGRATED PLATFORM CONFIGURATION.


Component	Configuration
UAV platform	Purpose-built lightweight carbon-fiber quadrotor frame with four embedded camera heads; $28 \times 28 \times 13.3$ cm; 1002.3 g with battery; 693.2 g without battery
Payload/propulsion	Up to 500 g auxiliary payload; thrust-to-weight ratio 4.2:1
Unloaded endurance	9 min with no auxiliary payload and the Jetson configured in 25 W mode
Panoramic camera	Four hardware-synchronized global-shutter fisheye views
Visual input	$4 \times 1088 \times 1280$ at 20 Hz; nominal 206° FOV; USB 3.0
Onboard computer	NVIDIA Jetson Orin NX Developer Kit; 16 GB memory; configured 25 W power mode
Flight/navigation	MicoAir H743 flight controller and MG-F10-A GNSS receiver
Panorama output	1280×640 at 20 Hz target
Runtime environment	Ubuntu 20.04 (L4T 35.5); CUDA 11.4; TensorRT 8.5.2.2

synchronized four-view data unit. Navigation records are associated with visual groups by host timestamps. Flight-controller and GNSS records retain their native timestamps

(a) Field coverage and acquisition conditions



(b) Traceable four-view data unit



(c) Paired teach-repeat flights




Fig. 3. Real-world dataset overview. (a) Representative panoramas from the seven-site field record, covering natural and built scenes and daytime and night-time flights; Section III-C enumerates the complete site set. The record contains 18 complete sequences and more than 50,000 valid four-view groups. (b) One representative synchronized data unit with four hardware-synchronized fisheye images and its panorama. The fisheye images are rotated by 180° only for display. (c) General teach-repeat protocol, in which the repeat flight revisits the teach route. The route is schematic and not metric.

and provide navigation metadata when present. The reported ERP warp and quantitative benchmarks follow the calibrated image path, with navigation records exported independently.

The camera model and extrinsics are obtained with Kalibr [37]. The fixed visual calibration binds topic order, camera intrinsics, inter-camera extrinsics, and image-space refinement; these parameters remain unchanged during evaluation. We use the left-front camera C_0 as reference and express all camera transforms in a common rig frame.

C. Field data for evaluation

The collection spans natural and built sites, teach-repeat flights, and daytime and night-time revisits recorded as synchronized four-view data (Fig. 3). The curated field record contains 18 complete sequences and more than 50,000 valid four-view groups across seven field sites: Court, Farmland, Lake, North Playground, North Square, South Playground, and South Square. South Playground and South Square include both daytime and night-time revisits. An additional near-field sequence provides a close-structure stress test.

Panorama evaluation uses sequence- and site-disjoint samples from the complete four-view recordings. Timestamp-associated

navigation records are used when available for downstream analyses. The organized data record contains synchronized fisheye views, corrected panoramas, calibration metadata, and navigation records when available. Splits are made by sequence or site to avoid adjacent-frame leakage.

IV. ADAPTIVE MULTI-FISHEYE PANORAMA FORMATION

The panorama formation pipeline is the visual core of the onboard system. Its design separates a per-frame CUDA data path from slower geometry, seam, and exposure state updates so that image quality can adapt without repeating every optimization for every frame. This section describes the geometric and photometric formulation. Section IV-D maps the formulation to the embedded schedule and defines the complete-path runtime protocol.

Let I_i^t denote the synchronized image from camera C_i at time t , where $i \in \{0, 1, 2, 3\}$. We attach a base-camera frame $\mathcal{B}$ to C_0 , with its optical centre as the origin, and express every calibrated camera pose in this common frame. The output is an equirectangular panorama $P^t \in \mathbb{R}^{H \times W \times 3}$. A fixed projection-sphere radius is stable for distant content but produces parallax when an overlap contains a nearby object. We therefore select




Fig. 4. Adaptive panorama formation. A projection-radius bank selects one radius per adjacent-camera overlap; a large score margin enables a fast update and weaker evidence retains temporal confirmation. The resulting local warp uses a dynamic seam and two-band blend. Inputs and ERP are from one airborne capture; the rig and radius bank are schematic.

a projection-sphere radius independently for each adjacent-camera overlap and restrict the resulting geometry change to a narrow band around that overlap. The far projection is retained elsewhere.

Figure 4 summarizes the method. The calibrated geometry binds recording topics to physical cameras and stores the intrinsic and extrinsic calibration. At each update, mutually consistent feature correspondences are tested against a projection-radius bank. When features are insufficient, a coverage-constrained photometric score provides a fallback. Temporal hysteresis stabilizes the selected depth. Each frame is then processed in a fixed order: cached lookup-table remapping, seam-local warp composition, dynamic seam estimation, exposure correction, and two-band blending. All reported panorama experiments use $H = 640$, $W = 1280$, and a 130° vertical field of view. The same ERP dimensions are used for the embedded timing tests in Section V-C.

A. Rig-aware projection and adaptive radius

For ERP pixel (u, v) , longitude and elevation are $\theta = 2\pi u/W - \pi$ and $\phi = \Phi(v/(H-1) - 1/2)$. The corresponding unit ray in the reference frame $\mathcal{B}$ is

$$\mathbf{d}(u, v) = [\cos \phi \sin \theta \quad \sin \phi \quad \cos \phi \cos \theta]^T. \quad (1)$$

Here, r denotes the projection-sphere radius and serves as a discrete proxy for scene depth. For camera C_i , calibrated transform $\mathbf{T}_{C_i \leftarrow \mathcal{B}} = [\mathbf{R}_i, \mathbf{t}_i]$ and its equidistant model map the point $r\mathbf{d}$ to the fisheye image. We cache a remapping table and validity mask for every camera and candidate radius $\mathcal{R} = \{1, 2, 4, 12, 30\}$ m. The system stores this map bank together with camera order, intrinsics, extrinsics, and image-space refinement.

For each adjacent-camera overlap p , bidirectional SIFT matches [38] are undistorted into rays. A ray $\mathbf{d}_{i,n}$ from camera centre $\mathbf{c}_i$ intersects the sphere of radius r at

$$\begin{aligned} \mathbf{x}_{i,n}(r) &= \mathbf{c}_i + \tau_{i,n}(r) \mathbf{d}_{i,n}, \\ \tau_{i,n}(r) &= -\mathbf{c}_i^T \mathbf{d}_{i,n} + \sqrt{(\mathbf{c}_i^T \mathbf{d}_{i,n})^2 + r^2 - \|\mathbf{c}_i\|_2^2}. \end{aligned} \quad (2)$$

After ERP projection $\pi(\cdot)$, $e_{p,n}(r)$ is the Euclidean displacement with horizontal wrap. The overlap selects

$$S_p(r) = Q_{0.65}\{e_{p,n}(r)\}, \quad \hat{r}_p = \arg \min_{r \in \mathcal{R}} S_p(r). \quad (3)$$

Here, $Q_{0.65}$ denotes the empirical 65th percentile of the valid displacement set $E_p(r) = \{e_{p,n}(r)\}_{n=1}^{N_p}$ in overlap p : 65% of its valid match displacements are no greater than $Q_{0.65}$. Consequently, $S_p(r)$ is measured in ERP pixels. This upper-tail statistic penalizes residual local misalignment while limiting the influence of isolated mismatches. Matches inconsistent with every layer are rejected. A candidate needs at least eight valid matches and a 0.18-pixel improvement. Let $\Delta S_p = S_p(r_p^{t-1}) - S_p(\hat{r}_p)$. A feature-supported candidate is accepted after one update when $\Delta S_p \geq 0.5$ pixels and otherwise after two consecutive selections. This margin-gated rule removes stale states during clear depth transitions without applying one-frame switching to ambiguous candidates. Radius updates run every five frames. When features are insufficient, a coverage-constrained photometric score over the same layer bank provides the fallback, which always retains two-update confirmation. The 0.5-pixel gate was selected on a farmland diagnostic subset. Farmland is therefore treated as a development site and excluded from the held-out transfer table. All thresholds were frozen before evaluation on lake and south-square data. Section V isolates this temporal rule against unconditional two-confirmation and immediate-update endpoints.

B. Seam-controlled photometric fusion

The 30 m layer supplies the base panorama. Within a $B_r = 72$ -pixel half-band around overlap p , the selected layer replaces the base warp through a 12-pixel raised-cosine transition. Seam search is controlled separately by B_s . Let $\delta_W(a, b)$ denote signed circular column displacement from b to a on ERP width W , and define $d_{c,y} = \delta_W(s_y^t, c_p)/B_s$ and $d_{t,y} = \delta_W(s_y^t, s_{y-1}^{t-1})/(2B_s)$. A dynamic-programming seam minimizes

$$\hat{s}^t = \arg \min_{s^t} \sum_y [C_p^t(y, s_y^t) + \lambda_c d_{c,y}^2 + \lambda_t d_{t,y}^2], \quad (4)$$

where $s^t = \{s_y^t\}_y$ is the seam path, c_p is the nominal overlap centre, and B_s is the seam-search half-band width. For the two exposure-corrected overlap bands, let D_c be mean absolute RGB difference divided by 255, $D_s = G_4 * D_c$, $D_f = \mathcal{D}_{18,6}(D_c)$, and let D_g and E be the normalized gradient discrepancy and edge strength. The image cost is

$$C_p^t(y, x) = D_c + 0.75D_s + 0.35D_f + 0.30D_g + 0.35E. \quad (5)$$

Here G_4 has $\sigma = 4$ pixels, $\mathcal{D}_{18,6}$ has 18- and 6-pixel horizontal/vertical radii, and $\lambda_c = 0.10$, $\lambda_t = 0.20$. The Per-seam deployment ablation fixes $B_s = 72$ pixels. Adaptive Seam evaluates 72- and 120-pixel half-bands and accepts the wider path only when its mean robust path cost improves by at least 0.01. The dynamic program constrains $|\delta_W(s_y^t, s_{y-1}^{t-1})| \leq 2$ pixels, and a temporal limiter bounds circular displacement from the previous path to 16 pixels.

The full accuracy profile, denoted Ours, adds a residual-triggered local mesh before the adaptive seam selection. A mesh is considered only when overlap residual exceeds 8 pixels and at least 15 mutual controls are available. Two thirds of spatially distributed controls fit an APAP-style affine mesh and one third validate it. The mesh is retained only when validation median error improves by at least 1 pixel and 12%, validation P90 rises by no more than 2%, and the selected seam-path score rises by no more than 0.005; otherwise the frame falls back to Adaptive Seam. Displacement is capped at 36 pixels. Mutual AKAZE features used for final evaluation do not fit or accept the mesh.

Cross-camera exposure is estimated from robust log-intensity differences in valid overlaps. Solving the overlap graph gives per-camera gains; only the dynamic scalar exposure component is retained and combined with static colour calibration. Updates run every ten frames with exponential smoothing. To avoid the double edges of a wide feather, corrected warp I_i is decomposed into $L_i = G_\sigma * (M_i I_i) / (G_\sigma * M_i)$ and $H_i = I_i - L_i$, where $*$ denotes spatial convolution, G_σ is a Gaussian kernel with standard deviation σ , and $M_i \in \{0, 1\}$ is the valid-pixel mask of warp i . Products and division are pointwise, with the ratio evaluated only where the convolved mask is nonzero. The output is

$$P^t = \sum_i w_i^{\text{wide}} L_i + \sum_i w_i^{\text{narrow}} H_i, \quad (6)$$

using 16- and 3-pixel wrapped feathers for low and high frequencies, respectively. Both weight fields are zero outside valid camera masks and are normalized across cameras at

every covered pixel. Thus, low-frequency colour changes are smoothed without broadly averaging displaced foreground edges.

C. Panorama and navigation interfaces

Each synchronized group exports the four raw fisheye views and the completed ERP with a shared image timestamp. Flight-controller and GNSS records are retained independently as timestamped navigation metadata, while the reported image-quality and embedded-runtime paths remain image-only. This separation keeps the panorama interface reusable by downstream algorithms without coupling the formation benchmark to a particular state estimator.

D. Embedded implementation

The CUDA implementation caches maps, masks, and buffers for the selected rig. Each four-view group is uploaded and remapped as an FP16 batch. The embedded variants reuse cached geometry and multi-rate state. Adaptive variants reuse the five-layer projection bank and SIFT-based radius evidence; Per-seam uses the Fast-margin state rule. Global Radius and Per-seam submit feature selection asynchronously every five frames. Per-seam remaps the far layer over the full ERP and replaces the currently selected local overlap bands. The Jetson evaluation uses this Per-seam deployment profile without the residual mesh; local-mesh timing is not attributed to the onboard benchmark.

The system publishes the ERP with its synchronized source timestamps and retains the raw views and recorded navigation state. The input queue holds two synchronized groups. When it is full, the oldest queued group is discarded before the newest group is inserted. Drop rate is defined as $(N_{\text{input}} - N_{\text{published}})/N_{\text{input}}$.

We define sensor-rate operation at the stream level: effective output remains within 0.1 Hz of the offered 20 Hz rate, the queue does not grow without bound, and timed drops remain negligible. Latency is measured from four-view availability to ERP publication; camera exposure and data transfer precede this boundary. Section V-C reports latency, throughput, drop rate, power, memory, and temperature for this complete embedded path.

V. SYSTEM AND EXPERIMENTAL EVALUATION

The evaluation follows the system claim from output quality to embedded cost and downstream use. We first compare panorama geometry and colour under far-field and near-field scene conditions, then isolate the adaptive state behaviour. We next measure complete-path execution on the Jetson Orin NX and finally test the output interface using frozen perception and localization models.

A. Panorama quality and downstream continuity

We compared Fixed Feather, fixed 30 m projection with dynamic seams (Fixed Depth), one panorama-wide adaptive radius (Global Radius), Per-seam with a fixed 72-pixel seam search, Adaptive Seam, and Residual Mesh + Adaptive Seam

TABLE III

PANORAMA QUALITY ON 60 FRAMES PER CONDITION AND FROZEN-YOLOv10-N 8V RESPONSE. MED./P90: FEATURE MISALIGNMENT/MEDIAN FRAME P90; S. MAE: SEAM RGB ERROR; COV./CONF.: PERSON-RESPONSE COVERAGE/MEAN CONFIDENCE ON THE MATCHED 181-FRAME FAR-FIELD SEQUENCE. AP/PREC./REC.@10°: PANO8 ANGULAR TARGET MATCHING ON 33 MATCHED OUTDOOR FRAMES UNDER FIXED CALIBRATION AND 10-DEGREE CROSS-CAMERA ASSOCIATION; THESE ARE NOT BOUNDING-BOX IOU METRICS. PER-SEAM (ABL.) FIXES A 72-PIXEL SEARCH AND OMITTS ADAPTIVE SEAM AND THE MESH; ADAPTIVE SEAM (ABL.) SELECTS 72 OR 120 PIXELS BUT OMITTS THE MESH; OURS ADDS THE VALIDATION-GATED RESIDUAL MESH. BOLD/UNDERLINED VALUES MARK BEST/SECOND-BEST DISTINCT RESULTS; TIES SHARE STYLING.

Method	Far-field quality			Near-field quality			YOLO 8V response				
	Med. ↓	P90 ↓	S. MAE ↓	Med. ↓	P90 ↓	S. MAE ↓	Cov. ↑	Conf. ↑	AP@10° (%) ↑	Prec.@10° (%) ↑	Rec.@10° (%) ↑
Fixed Feather	5.82	9.92	10.50	35.56	36.74	22.83	47.0	.790	67.1	88.1	67.3
Fixed Depth	5.66	9.97	5.00	35.76	36.96	10.00	45.9	.790	73.4	91.1	74.5
Global Radius	4.94	9.43	5.00	36.12	37.90	10.00	45.9	.787	71.2	87.0	72.7
Per-seam (abl.)	3.99	6.10	5.00	35.84	37.81	9.83	45.9	.801	79.6	93.8	81.8
Adaptive Seam (abl.)	<u>3.99</u>	6.02	5.00	35.77	37.84	7.50	49.7	<u>.807</u>	87.7	96.1	89.1
Ours	3.81	5.82	5.00	9.25	37.18	<u>7.67</u>	49.7	.809	88.0	96.1	89.1

(Ours). All share calibration, exposure correction, ERP sampling, and two-band fusion. Final geometry is evaluated with independent AKAZE features. The frozen YOLO interface test in Table III uses the same Pano8 detector interface across all methods. The near-field structure experiment additionally retains the original two-confirmation Per-seam policy as an accuracy-oriented temporal control. Generic OpenCV affine and homography stitching were also tested in transfer trials. These cases document departures from the 2:1 ERP coverage contract; matched numeric comparisons use the contract-compliant pipelines.

Matched frames were sampled uniformly from far-field and near-field sequences. Radius selection used SIFT, whereas evaluation used independent mutual AKAZE matches in unblended overlaps. For both conditions, we report median and per-frame P90 misalignment together with seam colour MAE; CIEDE2000 [39] is additionally reported in the continuous cross-site test below. This sampled comparison evaluates each group independently to isolate spatial depth and seam adaptation; the continuous clips below evaluate the temporal switching policy. All methods produced complete panoramas on the matched quality inputs; AKAZE geometry was evaluated on shared valid frames. Structural continuity was then evaluated on a separate continuous near-field sequence at all four physical overlap seams. OpenCV line-segment detection was applied inside fixed 170-pixel seam bands after excluding the top and bottom 10% of the ERP. A structure was counted as preserved when a segment crossed the seam or compatible fragments terminated on its two sides. Pooled continuity is the number of preserved structures divided by all detected seam-local structures.

Ours reduces far-field median and P90 misalignment by 32.7% and 41.6%, respectively, relative to Fixed Depth. Relative to Adaptive Seam, the residual mesh reduces these errors by 4.5% and 3.3%. In the near-field sample, Ours reduces median misalignment from 35.77 to 9.25 pixels, whereas Adaptive Seam retains the lowest seam MAE (7.50 versus 7.67). In the frozen-detector sensitivity, Ours gives the highest mean confidence and AP@10°, while Ours and Adaptive Seam tie on coverage, precision, and recall. The angular target metrics are downstream interface proxies, not bounding-box IoU accuracy.

Figure 5(a) summarizes the near-field structure test. Fast-margin preserved 50.8% of seam-local structures, well above Fixed Feather (27.4%) but below Fixed Depth (55.8%) and

Global Radius (56.1%). The paired median frame-level line-break difference relative to Fixed Feather was -0.245 (95% block-bootstrap CI, -0.271 to -0.167); differences relative to Fixed Depth and Global Radius were 0.027 and 0.002, with intervals touching zero. In the temporal-policy comparison, Two-confirmation, Fast-margin, and Immediate preserved 51.8%, 50.8%, and 50.6%, respectively. The principal benefit of margin gating is state responsiveness, with structural continuity remaining close to both temporal endpoints.

a) *Object-detection interface validation.*: Using frozen YOLOv10-N, Fig. 5(b) evaluates the exported ERP representations of the Per-seam deployment profile on matched post-takeoff far-field panoramas. Eight sectors increased response coverage from 6.9% for the forward sector to 55.1%, compared with 39.4% for direct ERP inference and 46.4% for four sectors. The bootstrap intervals quantify frame-level sampling uncertainty; they do not measure detector retraining or ground-truth detection accuracy.

To assess continuous low-altitude transfer, we evaluated synchronized groups from held-out lake and south-square teach/repeat clips anchored near minimum recorded GNSS altitude. All parameters were frozen. Farmland clips were reserved for development; Table IV uses the held-out lake and south-square clips. Every pipeline produced a complete ERP.

Per-seam achieved the lowest three geometric errors and tied the best seam MAE in Table IV. Relative to Global Radius, it reduced median, P90, and worst-overlap P90 errors by 3.5%, 3.7%, and 2.2%, while retaining comparable CIEDE2000 colour consistency (2.403 versus 2.406). Because frames within each clip are correlated, we report the clip aggregates descriptively.

B. Temporal-policy ablation

We varied only temporal acceptance; synchronized inputs, calibration, geometry, feature selection, seams, exposure, and fusion were fixed. Two-confirmation accepts a reliable feature candidate after two observations, Immediate after one, and Fast-margin after one only when improvement is at least 0.5 pixels. Photometric fallback always retains two observations. Table V reports transition counts and decomposes each accepted Fast-margin transition. An accelerated transition is one whose new Fast-margin state agrees with Immediate while Two-confirmation is still different; a confirmed transition agrees with Two-confirmation. Each retained sample is one update

TABLE IV

CONTINUOUS QUALITY ON CALIBRATED GROUPS FROM HELD-OUT LAKE AND SOUTH-SQUARE TEACH/REPEAT CLIPS. MED./P90: INDEPENDENT-AKAZE MISALIGNMENT; WORST P90: LARGEST ADJACENT-OVERLAP P90; S. MAE: MEDIAN SEAM RGB ERROR; CIEDE2000: MEDIAN PERCEPTUAL SEAM DIFFERENCE [39]. VALUES ARE PER-FRAME MEDIANS. ALL GROUPS COMPLETED; LOWER IS BETTER. BOLD/UNDERLINED VALUES MARK THE BEST/SECOND-BEST DISTINCT RESULTS.

Method	Med.	P90	Worst P90	Seam MAE	CIEDE2000
Fixed Feather	5.705	9.869	11.253	<u>9.333</u>	4.073
Fixed Depth	5.712	9.758	11.122	3.333	2.409
Global Radius	<u>5.415</u>	<u>9.291</u>	<u>10.201</u>	3.333	<u>2.406</u>
Per-seam	5.227	8.945	9.976	3.333	2.403

TABLE V

SINGLE-VARIABLE TEMPORAL-POLICY ABILATION AT 1280×640 . TWO/IMM./FAST SW.: TOTAL RADIUS-STATE TRANSITIONS; SUPP.: FAST-MARGIN REDUCTION RELATIVE TO IMMEDIATE; ACC./CONF.: ACCELERATED/CONFIRMED EVENTS; ACC.: ACCELERATED FRACTION; Δ LINE I/T: CONTINUITY DIFFERENCE FROM IMMEDIATE/TWO-CONFIRMATION (PERCENTAGE POINTS).

Condition	Endpoint switches		Fast-margin mechanism				Δ Line I/T
	Two sw.	Imm. sw.	Fast sw.	Supp. (%)	Acc./Conf.	Acc. (%)	
Near-field	6	49	15	69.4	10/5	66.7	+0.25/ - 0.99
Far-field	7	19	6	68.4	5/1	83.3	+0.12/ - 0.20

opportunity, while embedded scheduling is evaluated separately in Section V-C.

Relative to Immediate, Fast-margin reduced state changes by 69.4%/68.4% in near-field/far-field tests, from 49/19 switches to 15/6. Of the accepted Fast-margin transitions, 10/15 and 5/6 followed the acceleration-consistent branch; all remaining transitions followed confirmation, with no unclassified Fast-margin switch. Pooled structure continuity was 0.25/0.12 percentage points above Immediate and 0.99/0.20 points below Two-confirmation. Fast-margin therefore combines one-step adaptation under strong evidence with confirmation under ambiguous evidence while maintaining the endpoint-level structure quality. Layers at or below 4 m occurred in 45.6%/31.9% of near-field/far-field overlap-frame assignments.

TABLE VI

JETSON ORIN NX REPLAY AT 1280×640 UNDER STRICT 20 Hz FOUR-FISHEYE INPUT. P50/P95 USE THE SLOWER CONDITION; FPS/TIMELY USE THE LOWER CONDITION; DROP/POWER/RAM USE THE HIGHER CONDITION. EACH CONDITION AVERAGES THREE WARM-UP-EXCLUDED REPETITIONS. TIMELY IS OUTPUT WITHIN 50 ms; DROP IS MISSED TIMED OUTPUT; POWER IS MEAN VDD_IN.

Configuration	P50/P95 (ms)	FPS	Timely (%)	Drop (%)	Power (W)	RAM (GiB)
Fixed Feather	20.55/24.74	20.00	100.0	0.000	10.90	9.18
Fixed Depth	20.54/24.73	20.00	100.0	0.000	10.92	9.21
Global Radius	21.67/29.40	19.99	99.92	0.026	12.31	9.78
Per-seam	42.32/71.88	19.99	71.04	0.026	13.29	9.91

C. Sensor-rate performance on Jetson Orin NX

The benchmark device is an NVIDIA Jetson Orin NX Developer Kit with 16 GiB memory, CUDA 11.4, TensorRT 8.5.2.2, and OpenCV 4.8.0 in a configured 25 W mode. Per-run INA3221 VDD_IN logging records module-input power, while tegrastats records memory and temperature. The full far-field and near-field sequences are replayed without subsampling. A prefetched producer releases group n at $t_0 + n/20$ s, independent of source-file timestamps, and a run is accepted only when the actual input rate is 20.0 ± 0.1 Hz, the P95 absolute arrival error is at most 5 ms, and no decode failure occurs. All 36 profile and method runs passed this input gate; the largest observed P95 arrival error was 0.235 ms.

Fixed Feather, Fixed Depth, Global Radius, and Fast-margin Per-seam use the matched Onboard-fast profile in Section IV-D. Each method is evaluated three times per condition for 3–5 minutes with rotated run order. Statistics exclude the first 10 s. Timing covers four-view availability to ERP publication. The configured 25 W mode is reported separately from measured module consumption. We call the summary aggregation conservative because P50/P95 use the slower condition, FPS and timely-output rate use the lower condition, and drop, power, and RAM use the higher condition.

All four methods sustain the offered stream. Fixed Feather and Fixed Depth have the lowest latency and power, while Global Radius adds modest cost for a single adaptive depth. The local quality tests show a clear Per-seam geometry gain in the far-field scene and across held-out sites; Fixed Depth slightly




Fig. 5. Task-level validation. (a) Pooled line-structure continuity on a separate near-field sequence; labels give preserved structures/frame. Two-confirmation is the accuracy control; Fast-margin is the deployed policy. (b) Frozen-YOLOv10-N object-detection interface validation on matched post-takeoff far-field panoramas generated by the Per-seam deployment profile; error bars are 95% bootstrap confidence intervals over frames.

TABLE VII

FROZEN-CosPLACE CROSS-FLIGHT VPR FOR LOCALIZATION (%). DAY VALUES AVERAGE ACROSS DAYTIME SITES; ERR. IS MEAN MEDIAN TOP-1 GNSS ERROR. SQUARE D→N AND PLAYGROUND N→N DENOTE THE CROSS-ILLUMINATION AND SAME-ILLUMINATION PROTOCOLS. CALLS: DESCRIPTOR EVALUATIONS PER GROUP. RAW FISHEYE 4V IS THE WIDER-FOV REFERENCE; RECTIFIED 4V AND ERP 4V ARE EQUAL-FOV CONTROLS. BOLD/UNDERLINED VALUES MARK THE BEST/SECOND-BEST DISTINCT RESULTS.

Representation	Calls	Day R@1	Day R@5	Err. (m) ↓	Square D→N	Play. N→N
Raw fisheye 4V	4	<u>69.3</u>	85.8	18.1	9.5	70.4
Rectified multi-view 4V	4	61.8	<u>87.2</u>	19.8	<u>19.0</u>	70.4
ERP 4V	4	66.7	83.6	20.1	<u>19.0</u>	77.8
ERP 8V	8	74.9	90.8	17.2	23.8	63.0

leads the near-field feature-misalignment sample. Relative to Global Radius, Per-seam increases mean module-input power from 12.31 to 13.29 W and P95 latency from 29.40 to 71.88 ms. Both retain 19.99 frames/s with 0.026% cross-condition timed drops, but their 50 ms timely-output rates are 99.92% and 71.04%, respectively. A separate Quality-full diagnostic operates at 5.37 frames/s, while Onboard-fast supplies the sensor-rate results. The maximum measured junction temperature is 59.3°C. Together, output rate and the separate 50 ms timely-output metric define the verified quality–efficiency operating point.

D. Visual place recognition for localization

VPR compares raw fisheye, rectified 4V, ERP 4V, and ERP 8V representations with a frozen ResNet-18 CosPlace model [40]; direct geometry metrics remain the local stitching-quality evidence. Raw fisheye 4V is the wide-FOV reference, whereas rectified 4V and ERP 4V are equal-FOV controls. CosPlace uses fixed 320×320 preprocessing and cosine retrieval without temporal smoothing; 4V uses four descriptor calls and ERP 8V uses eight. Teach–repeat queries are sampled every two seconds under a 10 m GNSS radius across daytime, day-to-night, and night-to-night protocols.

ERP 8V gives the strongest daytime result (74.9% Recall@1, 90.8% Recall@5, and 17.2 m error), but doubles descriptor calls relative to ERP 4V. ERP 8V gives the highest South-Square day-to-night Recall@5 (23.8%), whereas ERP 4V gives the highest South-Playground night-to-night Recall@5 (77.8%); the preferred sector density is therefore condition- and budget-dependent.

VI. CONCLUSION

We presented an open sensing-to-perception platform that combines synchronized raw fisheye views, calibrated ERP formation, navigation metadata, and onboard computation in a reusable interface for panoramic robotics. Ours improves the accuracy-oriented panorama profile while retaining a sensor-rate deployment configuration. Direct geometry and photometry provide the primary stitching evidence; frozen detection and VPR provide complementary interface evidence, not detector accuracy or a universal representation ranking. The results also expose a quality–efficiency trade-off: sector density, temporal adaptation, and embedded cost should be selected for the task and compute budget.




Fig. 6. CosPlace retrieval at nearby day and night query locations. Rows show the query, forward-sector retrieval, and final ERP panorama retrieval. Green results satisfy the 10 m GNSS threshold; each column shares a query timestamp across representations.

The present formulation models one dominant depth per overlap and remains limited by mixed-depth content and real-time resource constraints. These boundaries motivate richer local scene models that preserve the open raw-view and calibration interfaces while extending downstream aerial perception and localization.

REFERENCES

- [1] G. Chen, W. Dong, X. Sheng, X. Zhu, and H. Ding, “An active sense and avoid system for flying robots in dynamic environments,” *IEEE/ASME Transactions on Mechatronics*, vol. 26, no. 2, pp. 668–678, 2021.
- [2] J. Wang, K. Yang, S. Gao, L. Sun, C. Zhu, K. Wang, and J. Bai, “High-performance panoramic annular lens design for real-time semantic segmentation on aerial imagery,” *Optical Engineering*, vol. 61, no. 3, p. 035101, 2022.
- [3] Y. Wu, X. Zhang, Y. Du, T. Zhang, C. Li, S. Chen, G. Zhang, and X. Xu, “PanoAir: A panoramic visual-inertial SLAM with cross-time real-world UAV dataset,” 2026. [Online]. Available: <https://arxiv.org/abs/2604.00852>
- [4] D. Dai, Z. Lu, X. Dai, and Q. Quan, “RflyPano: A panoramic benchmark for ultra-low altitude UAV localization powered by RflySim,” *Proceedings of the AAAI Conference on Artificial Intelligence*, vol. 40, no. 22, pp. 18 216–18 224, 2026.
- [5] H. Li, Y. Zou, N. Chen, J. Lin, X. Liu, W. Xu, C. Zheng, R. Li, D. He, F. Kong, Y. Cai, Z. Liu, S. Zhou, K. Xue, and F. Zhang, “MARS-LVIG dataset: A multi-sensor aerial robots SLAM dataset for LiDAR-visual-inertial-GNSS fusion,” *The International Journal of Robotics Research*, vol. 43, no. 8, pp. 1114–1127, 2024.
- [6] S. Wang, S. Li, Y. Zhang, S. Yu, S. Yuan, R. She, Q. Guo, J. Zheng, O. K. Howe, L. Chandra, S. Srijevan, A. Sivasdas, T. Aggarwal, H. Liu, H. Zhang, C. Chen, J. Jiang, L. Xie, and W. P. Tay, “UAVScenes: A multi-modal dataset for UAVs,” in *Proceedings of the IEEE/CVF International Conference on Computer Vision*, 2025, pp. 28 946–28 958.
- [7] G. Kim, D. Kim, J. Jang, and H. Hwang, “PAIR360: A paired dataset of high-resolution 360° panoramic images and LiDAR scans,” *IEEE Robotics and Automation Letters*, vol. 9, no. 11, pp. 9550–9557, 2024.
- [8] M. Gochoo, M.-E. Otgonbold, E. Ganbold, J.-W. Hsieh, M.-C. Chang, P.-Y. Chen, B. Dorj, H. Al Jassmi, G. Batnasan, F. Alnajjar, M. Abduljabbar, and F.-P. Lin, “FishEye8K: A benchmark and dataset for fisheye camera

- object detection,” in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition Workshops*, 2023, pp. 5305–5313.
- [9] M. D. Kim and J. Ueda, “Real-time panoramic image generation and motion deblurring by using dynamics-based robotic vision,” *IEEE/ASME Transactions on Mechatronics*, vol. 21, no. 3, pp. 1376–1387, 2016.
- [10] P. Liu, C. Feng, Y. Xu, Y. Ning, H. Xu, and S. Shen, “OmniNxt: A fully open-source and compact aerial robot with omnidirectional visual perception,” in *2024 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, 2024, pp. 10 605–10 612.
- [11] H. Xu, Y. Zhang, B. Zhou, L. Wang, X. Yao, G. Meng, and S. Shen, “Omni-Swarm: A decentralized omnidirectional visual–inertial–UWB state estimation system for aerial swarms,” *IEEE Transactions on Robotics*, vol. 38, no. 6, pp. 3374–3394, 2022.
- [12] Insta360, “X5 flagship 360 action camera,” 2025, accessed 1 September 2026. [Online]. Available: <https://store.insta360.com/product/x5>
- [13] DJI, “Osmo 360 specifications,” 2025, accessed 1 September 2026. [Online]. Available: <https://www.dji.com/360/specs>
- [14] J. Zaragoza, T.-J. Chin, M. S. Brown, and D. Suter, “As-projective-as-possible image stitching with moving DLT,” in *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, 2013, pp. 2339–2346.
- [15] C.-C. Lin, S. U. Pankanti, K. Natesan Ramamurthy, and A. Y. Aravkin, “Adaptive as-natural-as-possible image stitching,” in *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, 2015, pp. 1155–1163.
- [16] P. Du, J. Ning, J. Cui, S. Huang, X. Wang, and J. Wang, “Geometric structure preserving warp for natural image stitching,” in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2022, pp. 3688–3696.
- [17] L. Nie, C. Lin, K. Liao, S. Liu, and Y. Zhao, “Parallax-tolerant unsupervised deep image stitching,” in *Proceedings of the IEEE/CVF International Conference on Computer Vision*, 2023, pp. 7399–7408.
- [18] H. Kwon, H. Kim, Y. Kang, Y. Yoon, W. Jeong, and K.-J. Yoon, “Pixel-wise warping for deep image stitching,” in *Proceedings of the AAAI Conference on Artificial Intelligence*, vol. 37, no. 1, 2023, pp. 1196–1204.
- [19] T. Liao, C. Zhao, L. Li, and H. Cao, “Leveraging local patch alignment to seam-cutting for large parallax image stitching,” in *Proceedings of the IEEE/CVF International Conference on Computer Vision*, 2025, pp. 27 262–27 271.
- [20] Y. Ding, D. Barath, and Z. Kukelova, “Minimal solutions for panoramic stitching given gravity prior,” in *Proceedings of the IEEE/CVF International Conference on Computer Vision*, 2021, pp. 5579–5588.
- [21] P. Lindenberger, P.-E. Sarlin, and M. Pollefeys, “LightGlue: Local feature matching at light speed,” in *Proceedings of the IEEE/CVF International Conference on Computer Vision*, 2023, pp. 17 627–17 638.
- [22] J. Zhang, K. Yang, C. Ma, S. Reiß, K. Peng, and R. Stiefelhagen, “Bending reality: Distortion-aware transformers for adapting to panoramic semantic segmentation,” in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2022, pp. 16 917–16 927.
- [23] X. Li, T. Wu, Z. Qi, G. Wang, Y. Shan, and X. Li, “SGAT4PASS: Spherical geometry-aware transformer for panoramic semantic segmentation,” in *Proceedings of the Thirty-Second International Joint Conference on Artificial Intelligence*, 2023, pp. 1125–1133.
- [24] W. Zhang, Y. Liu, X. Zheng, and L. Wang, “GoodSAM: Bridging domain and capacity gaps via segment anything model for distortion-aware panoramic semantic segmentation,” in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2024, pp. 28 264–28 273.
- [25] Y. Benny and L. Wolf, “SphereUformer: A u-shaped transformer for spherical 360° perception,” in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2025, pp. 940–950.
- [26] M. Rey-Area, M. Yuan, and C. Richardt, “360MonoDepth: High-resolution 360° monocular depth estimation,” in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2022, pp. 3762–3772.
- [27] Z. Cao, J. Zhu, W. Zhang, H. Ai, H. Bai, H. Zhao, and L. Wang, “PanDA: Towards panoramic depth anything with unlabeled panoramas and möbius spatial augmentation,” in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2025, pp. 982–992.
- [28] A. Ali-bey, B. Chaib-draa, and P. Giguère, “MixVPR: Feature mixing for visual place recognition,” in *Proceedings of the IEEE/CVF Winter Conference on Applications of Computer Vision*, 2023, pp. 2998–3007.
- [29] N. Keetha, A. Mishra, J. Karhade, K. M. Jatavallabhula, S. Scherer, M. Krishna, and S. Garg, “AnyLoc: Towards universal visual place recognition,” *IEEE Robotics and Automation Letters*, vol. 9, no. 2, pp. 1286–1293, 2024.
- [30] H. Huang, C. Liu, Y. Zhu, H. Cheng, T. Braud, and S.-K. Yeung, “360Loc: A dataset and benchmark for omnidirectional visual localization with cross-device queries,” in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2024, pp. 22 314–22 324.
- [31] Y. Li, P. Zhang, Z. Mei, and W. Dong, “Efficiently range-coupled position estimation for an aerial swarm with the confidence evaluation of onboard sensing,” *IEEE/ASME Transactions on Mechatronics*, vol. 28, no. 4, pp. 2178–2188, 2023.
- [32] G. Roggi, G. Gozzini, D. Invernizzi, and M. Lovera, “Vision-based air-to-air autonomous landing of underactuated vtol uavs,” *IEEE/ASME Transactions on Mechatronics*, vol. 29, no. 3, pp. 2338–2349, 2024.
- [33] X. Ge, Y. Pan, Y. Zhang, X. Li, W. Zhang, D. Zhang, Z. Wan, X. Lin, X. Zhang, J. Liang, X. Li, W. Jiang, B. Du, M.-H. Yang, and L. Qi, “AirSim360: A panoramic simulation platform within drone view,” in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2026, pp. 26 931–26 940.
- [34] Shenzhen Shiyuan Intelligent Technology Co., Ltd., “Seeker Omni Depth camera user manual and ROS SDK,” Gitee repository, 2025, version 1.0; accessed 26 July 2026. [Online]. Available: <https://gitee.com/nochain/seeker1>
- [35] MicoAir Technology, “MicoAir743v2-AIO-45A user manual,” 2026, accessed 26 July 2026. [Online]. Available: <https://micoair.cn/zh/docs/flight-controller/micoair743-aio-series/micoair743v2-aio-45a-manual>
- [36] —, “MG-F10-A dual-frequency GNSS module user manual,” 2026, accessed 26 July 2026.
- [37] P. Furgale, J. Rehder, and R. Siegwart, “Unified temporal and spatial calibration for multi-sensor systems,” in *2013 IEEE/RSJ International Conference on Intelligent Robots and Systems*, 2013, pp. 1280–1286.
- [38] D. G. Lowe, “Distinctive image features from scale-invariant keypoints,” *International Journal of Computer Vision*, vol. 60, no. 2, pp. 91–110, 2004.
- [39] G. Sharma, W. Wu, and E. N. Dalal, “The CIEDE2000 color-difference formula: Implementation notes, supplementary test data, and mathematical observations,” *Color Research & Application*, vol. 30, no. 1, pp. 21–30, 2005.
- [40] G. Berton, C. Masone, and B. Caputo, “Rethinking visual geo-localization for large-scale applications,” in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2022, pp. 4878–4888.