

Choosing the Lens: Strategic Perspective Activation in Context-Dependent Argumentation

Albert Sadowski¹, Jarosław A. Chudziak¹

¹Warsaw University of Technology
{albert.sadowski.stud, jaroslaw.chudziak}@pw.edu.pl

Abstract

The same arguments often need to be evaluated under different external regimes. An agent with influence over the regime has a strategic lever that standard formalisms do not directly capture. We introduce context-dependent argumentation frameworks (CDAFs), an extension of Dung’s theory in which a defeat function determines, per context, which attacks succeed. A perspective-labeled specialisation derives the defeat function from a relevance set ρ and a priority π . The relevance set is the agent’s action space. In a small worked example, the agent’s target argument is rejected under every full-relevance injective priority, yet accepted under partial activations, one of which no VAF audience can mirror. We define the corresponding decision problem, ACTIVATION-MANIPULATION, and record baseline complexity bounds. Tight bounds and multi-agent variants are left open.

1 Introduction

Consider a team proposing an architectural change to a production service. The proposal accumulates arguments about latency, operational complexity, deployment cost, and regression risk. These claims are not in dispute as facts; what is in dispute is how they bear on the decision. To a performance reviewer, latency dominates and complexity is secondary. A reliability reviewer reads the same arguments through incident risk, and is unmoved by latency improvements without stability evidence. The finance reviewer cares about deployment and headcount cost. The arguments and their conflicts are fixed across reviewers. Which attacks succeed depends on which lens governs the review.

The proposal sponsor has some influence over which lens applies. They choose which review tracks to pursue, who is included in early design discussions, and which forums hear the proposal first. They cannot change how each reviewer ranks considerations within a lens (the reliability reviewer always prioritises stability), but they can decide which lenses are foregrounded at all. Influence over the regime is a strategic lever. Standard argumentation (Dung 1995) has no parameter for the regime. Value-based argumentation (Bench-Capon 2003) comes close, since each audience produces a different defeat pattern. But a VAF audience is a strict total order on the value set; it can rerank values, not deactivate them. So the question of whether the

agent can choose a regime that accepts their target argument is inconvenient to pose in existing formalisms.

We propose an extension of Dung’s framework, context-dependent argumentation frameworks (CDAFs), and use it to study a strategic question. We work through an example in which the target argument is reachable only via partial-relevance activation, an action that does not correspond to any audience choice in a value-based framework. We define the corresponding decision problem, ACTIVATION-MANIPULATION, and record baseline complexity bounds. A fuller study of the framework is beyond this paper’s scope; here we focus on the strategic angle.

2 Context-Dependent Argumentation Frameworks

General definition. A *context-dependent argumentation framework* is a tuple $\text{CDAF} = \langle \mathcal{A}, R, \mathcal{C}, \delta \rangle$ where $\mathcal{A}$ is a finite set of arguments, $R \subseteq \mathcal{A} \times \mathcal{A}$ is the attack relation, $\mathcal{C}$ is a finite set of contexts, and $\delta: \mathcal{C} \times R \rightarrow \{0, 1\}$ is the *defeat function*. For each context $c \in \mathcal{C}$, the *induced framework* is $\text{AF}_c = \langle \mathcal{A}, R_c \rangle$ with $R_c = \{(a, b) \in R : \delta(c, (a, b)) = 1\}$. Since each AF_c is a standard Dung framework, the classical semantics carry over per context: a σ -extension in c is just a σ -extension of AF_c (Baroni, Caminada, and Giacomin 2018), for any of $\sigma \in \{\text{gr}, \text{pref}, \text{stb}, \text{comp}\}$. We write $\sigma(c)$ for the set of σ -extensions of AF_c .

Perspective-labeled CDAFs. In the specialisation we use throughout the paper, the defeat function is derived rather than given. Every argument carries a source perspective. A context activates some subset of perspectives and ranks them by priority. Defeat then follows from these assignments.

Definition 1 (Perspective-labeled CDAF). A perspective-labeled CDAF is a tuple $\langle \mathcal{A}, R, \mathcal{C}, \Pi, \text{src}, \rho, \pi \rangle$ with Π a finite set of perspectives, $\text{src}: \mathcal{A} \rightarrow \Pi$ assigning each argument to its source, $\rho: \mathcal{C} \rightarrow 2^\Pi$ giving the active perspectives in each context, and $\pi: \mathcal{C} \times \Pi \rightarrow \mathbb{N}$ a priority function. The defeat function is

$$\delta_\pi(c, (a, b)) = 1 \text{ iff } \text{src}(a) \in \rho(c) \\ \wedge \pi(c, \text{src}(a)) \geq \pi(c, \text{src}(b)).$$

The condition gates only the attacker: $\text{src}(a) \in \rho(c)$ is required, while $\text{src}(b)$ is not. Deactivating a perspective there-

fore removes the attacks its arguments *mount*, but their priority is still counted when they are *targeted*, and the arguments themselves remain present and eligible for acceptance. This asymmetry is what lets a perspective be silenced as an attacker while its arguments are still defended and accepted; see Table 2, where (b, t) stays active even though t 's perspective α is inactive.

Comparison to VAFs and the action space. Perspectives are loosely analogous to values, and (ρ, π) to a VAF audience. The differences are that π may rerank perspectives across contexts, and that ρ may deactivate them outright. The second is what drives the strategic story of this paper. We read ρ as the agent's action space: the lens through which they choose to have arguments evaluated. The priority π is institutional structure that the agent cannot directly change, the ranking each lens imposes once selected. We take the action space to be the *nonempty* subsets of Π : an empty ρ activates no attack and would accept every argument vacuously, which we read as the absence of any evaluative regime rather than a lens the agent could select. The example of Section 3 shows that, for a fixed π , varying ρ alone can be the only way for the agent to have their target argument accepted. Throughout Sections 3 and 4 we work with a single context c , and accordingly write ρ for $\rho(c) \subseteq \Pi$ and $\pi(\cdot)$ for $\pi(c, \cdot)$.

3 A Worked Example

Setup. Let $\mathcal{A} = \{a, b, t, d\}$, $\Pi = \{\alpha, \beta, \gamma\}$, $\text{src}(a) = \text{src}(t) = \alpha$, $\text{src}(b) = \beta$, $\text{src}(d) = \gamma$, and $R = \{(a, t), (b, t), (a, b), (b, a), (d, b)\}$. Table 1 summarises the structure.

Argument	Perspective	Attacked by	Attacks
a	α	b	t, b
b	β	a, d	t, a
t	α	a, b	—
d	γ	—	b

Table 1: Argument structure of the worked example.

The point of the construction is that a and t share a perspective, so the attack (a, t) is intra-perspective. The agent's goal is to have t accepted under the preferred semantics.

Result 1: t is rejected under full relevance. For every injective $\pi: \Pi \rightarrow \mathbb{N}$, t is not credulously preferred-accepted in the framework induced by $\rho = \Pi$.

Proof. With $\rho = \Pi$, (a, t) is active under every injective π , since $\pi(\alpha) \geq \pi(\alpha)$ holds trivially. Suppose E is admissible and contains t . Then E must defend t against a , and the only attacker of a is b , so $b \in E$ and (b, a) must be active. Injectivity forces $\pi(\beta) > \pi(\alpha)$, but this also activates (b, t) , so b defeats t and $\{b, t\} \subseteq E$ violates conflict-freeness. Conversely, if $\pi(\alpha) > \pi(\beta)$, then (b, a) is inactive and t cannot be defended against a . Either way, no admissible set contains t . The priority of γ is irrelevant: d attacks only b , not a . $\square$

Result 2: t is accepted under $\rho = \{\beta, \gamma\}$. With $\pi(\alpha) = 1$, $\pi(\beta) = 2$, $\pi(\gamma) = 3$, and $\rho = \{\beta, \gamma\}$, the set $\{a, d, t\}$ is a preferred extension of the induced framework, so t is credulously preferred-accepted.

Proof. Computing δ_π under $\rho = \{\beta, \gamma\}$ gives the activations in Table 2. The active defeats are $\{(b, t), (b, a), (d, b)\}$.

Attack	$\text{src} \in \rho?$	Priority	Active?
(a, t)	$\alpha \notin \rho$	—	no
(b, t)	$\beta \in \rho$	$2 \geq 1$	yes
(a, b)	$\alpha \notin \rho$	—	no
(b, a)	$\beta \in \rho$	$2 \geq 1$	yes
(d, b)	$\gamma \in \rho$	$3 \geq 2$	yes

Table 2: Active defeats under $\rho = \{\beta, \gamma\}$.

The argument d has no active attacker and defeats b , so it defends both a and t against the only active attacker either has. Since (a, t) is no longer active, a and t are not in conflict. The set $\{a, d, t\}$ is conflict-free, every member is defended by d , and adding b creates a conflict with all three. Hence $\{a, d, t\}$ is preferred and t is accepted. $\square$

Under any full-relevance evaluation, t is caught in a structural trap. Its same-perspective neighbour a attacks it, and the only argument that can defend t against a is b , which itself attacks t . Whenever b is strong enough to defeat a , it is also strong enough to defeat t . The defender doubles as an attacker, and the trap holds for every injective priority. The agent's way out is to deactivate α . Setting $\rho = \{\beta, \gamma\}$ silences every attack from an α -perspective argument, including the friendly-fire attack (a, t) . The price is that a loses its offensive capability against b , but the trap is now broken: d , unaffected by the move since $\gamma \in \rho$, defeats b and clears the only remaining threat to t . This is the strategically interesting case, since t is still under the active attack (b, t) and is accepted only because d defends it; deactivating α does not simply remove t 's attackers. The following proposition states the existence claim in general form.

Proposition 1. *There exists a perspective-labeled CDFAF $\langle \mathcal{A}, R, \Pi, \text{src} \rangle$ and a target argument $t \in \mathcal{A}$ such that*

- (i) *for every injective priority $\pi: \Pi \rightarrow \mathbb{N}$, t is not credulously preferred-accepted under full relevance $\rho = \Pi$;*
- (ii) *for some priority π and some nonempty $\rho \subsetneq \Pi$, t is credulously preferred-accepted.*

Proof. Take $\mathcal{A}, R, \Pi, \text{src}$ as in the setup. Clause (i) is Result 1; clause (ii) is Result 2 with $\pi(\alpha) = 1$, $\pi(\beta) = 2$, $\pi(\gamma) = 3$, and $\rho = \{\beta, \gamma\}$. $\square$

The same example also rules out a VAF rendering of one of the agent's winning moves. Consider the activation $\rho = \{\gamma\}$, with the same priority. Now (a, t) , (b, t) , (a, b) , and (b, a) are all inactive, since neither α nor β lies in ρ . Only (d, b) remains active, so $\{a, d, t\}$ is again the preferred extension and t is accepted. Both directions of the mutual attack between a and b fail to be active under $\rho = \{\gamma\}$, and that is what no VAF audience can do.

Observation 1. *The defeat pattern induced by $\rho = \{\gamma\}$ in the framework above is not realisable as any audience of any VAF over $\mathcal{A}$.*

Proof. Let V be a value set and $val: \mathcal{A} \rightarrow V$ any value assignment, and consider any audience, that is, any strict total order on V . If $val(a) = val(b)$, then both (a, b) and (b, a) are intra-value attacks and succeed in every audience (Bench-Capon 2003). If $val(a) \neq val(b)$, the strict total order satisfies exactly one of $val(a) \succ val(b)$ or $val(b) \succ val(a)$, so exactly one of the two directions succeeds. In neither case do both directions fail. So the defeat pattern under $\rho = \{\gamma\}$ is not realisable as a VAF audience, regardless of the value assignment. $\square$

In the perspective-labeled formalism, the agent picks ρ , not the source assignment. So even if some other choice of values were to recover the strategically natural move $\rho = \{\beta, \gamma\}$ within VAF expressiveness, the move $\rho = \{\gamma\}$ remains available to the agent and falls outside what any VAF audience can do.

4 Activation Manipulation

The strategic question of the previous section generalises to a decision problem. Given a perspective-labeled framework, a fixed priority, and a target argument, does the agent have any choice of ρ that accepts the target?

ACTIVATION-MANIPULATION $_{\sigma}$.

Input. A finite tuple $\langle \mathcal{A}, R, \Pi, src \rangle$, a priority $\pi: \Pi \rightarrow \mathbb{N}$, and a target argument $t \in \mathcal{A}$.

Question. Does there exist a nonempty $\rho \subseteq \Pi$ such that t is credulously σ -accepted in the framework induced by (ρ, π) ?

For the upper bound we use a standard guess-and-check. Nondeterministically choose a nonempty $\rho \subseteq \Pi$, then verify σ -acceptance in the induced framework. The verification cost depends on σ : polynomial for grounded, and in NP for stable (guess a stable extension containing t).

The preferred case looks harder at first. Verifying that a set is a preferred extension requires checking maximality, that no admissible superset exists, which is co-NP, suggesting an overall Σ_2^P bound. The escape is a standard fact: credulous preferred-acceptance coincides with credulous admissibility, since every admissible set extends to some preferred extension. So it suffices to find an admissible set containing t , and we can guess ρ and the admissible witness together in a single NP computation.

Together with the existential guess of ρ , this keeps ACTIVATION-MANIPULATION $_{\text{pref}}$ in NP. So ρ and a witness extension can be guessed jointly and verified in polynomial time, placing ACTIVATION-MANIPULATION $_{\sigma}$ in NP for $\sigma \in \{\text{gr}, \text{stb}, \text{pref}\}$. For lower bounds, set $\Pi = \{\pi_0\}$ with all arguments mapped to the single perspective and π trivially fixed. Since ρ must be nonempty and Π is a singleton, the only admissible activation is $\rho = \{\pi_0\}$, under which every attack is active, so the induced framework is exactly the input Dung framework and the problem reduces to credulous σ -acceptance in standard Dung. This yields NP-hardness for $\sigma \in \{\text{stb}, \text{pref}\}$ (Baroni, Caminada, and Giacomin 2018; Dung 1995), so ACTIVATION-MANIPULATION $_{\sigma}$ is NP-complete in those cases. Credulous grounded acceptance is in P, so the same reduction gives only P-hardness for grounded. Whether the freedom

to choose ρ raises the grounded variant to NP-completeness is open.

The restriction to nonempty ρ is essential to these bounds. An empty activation deactivates every attack, so the induced framework has $\mathcal{A}$ as its unique extension under each $\sigma \in \{\text{gr}, \text{stb}, \text{pref}\}$ and accepts every argument; allowing it would make the problem trivially positive and break the reduction, since the constructed instance would answer “yes” regardless of whether t is credulously accepted in the input. Even among nonempty activations many instances stay easy: if some perspective is the source of no attacker of t , then for $\sigma \in \{\text{gr}, \text{pref}\}$ activating only that perspective leaves t unattacked, hence accepted. The hardness above therefore comes from instances in which t cannot be isolated in this way, as in the single-perspective reduction, where the sole nonempty activation reinstates every attack.

Several variants of the problem are not addressed here. The activation ρ may be further constrained, for instance by requiring some perspectives to remain active or by attaching a cost to each activation; such constraints are also what block the cheap isolation move above and make the general problem robustly nontrivial. The priority π may itself be a choice variable, which enlarges the action space. In a multi-agent version, several agents pick disjoint or overlapping subsets of Π , with the realised ρ formed by union or intersection; this yields natural game-theoretic refinements with cooperative and adversarial variants, including the existence of strategic equilibria in which no agent can unilaterally redirect the outcome by altering its share of ρ . The skeptical version, asking whether some ρ accepts t in every σ -extension, is also open.

5 Discussion

The strategic action we study here, varying which attacks constitute defeats while keeping the argument structure fixed, has three close neighbours. Control argumentation frameworks (Dimopoulos, Mailly, and Moraitis 2018) let an agent choose between alternative argument and attack sets so that a target is accepted under uncertainty about the framework’s structure; here, the structure is fixed and only the defeat function varies. Manipulation in incomplete argumentation (Baumeister et al. 2021) is the closest of the three, since both ask whether an agent can drive a target to acceptance via a structural choice, and a careful comparison is left for future work. Value-based argumentation (Bench-Capon 2003) is the closest formal kin, and the example of Section 3 sharpens the difference: a VAF audience can rerank values but cannot deactivate one, so the strategic options it offers are strictly fewer than those of perspective activation. Other extensions of Dung’s theory modulate defeat through meta-level argumentation (Modgil 2009) or per-node acceptance conditions (Brewka and Woltran 2010), but in each case the modulation is endogenous or fixed at definition time, and none treats activation as an action available to the agent. Beyond these formal neighbours, applied multi-agent and LLM-based systems operationalise argumentation as explicit debate among agents, for instance, dialectical refinement for argument-component classification (Bąba and Chudziak 2026). Such systems fix neither an attack relation

nor a defeat function explicitly, working at a different level of abstraction from the framework here, and the strategic question we raise is orthogonal to their design.

Several questions remain open. Tight complexity bounds for ACTIVATION-MANIPULATION, especially for the grounded variant, are unsettled. There are mechanism-design questions when the agent’s choice of ρ is institutionally constrained, for instance when certain perspectives are mandatory or when activations carry cost. The multi-agent setting, where several agents jointly determine ρ under cooperative or adversarial dynamics, is the most direct extension of the present work and, we think, the most productive direction for further study; the existence of strategic equilibria under such dynamics is a natural question there. Whether the phenomenon arises in larger or applied frameworks is also open - multi-perspective agent memory, where the same experience receives goal-conditioned encodings reconciled by argumentation at retrieval (Sadowski and Chudziak 2026), is one such setting.

References

- Baroni, P.; Caminada, M. W. A.; and Giacomin, M. 2018. Abstract argumentation frameworks and their semantics. In van der Torre, L.; Villata, S.; and Gabbay, D. M., eds., *Handbook of Formal Argumentation*. London, UK: College Publications. 159–236.
- Baumeister, D.; Järvisalo, M.; Neugebauer, D.; Niskanen, A.; and Rothe, J. 2021. Acceptance in incomplete argumentation frameworks. *Artificial Intelligence* 295:103470.
- Bench-Capon, T. J. M. 2003. Persuasion in practical argument using value-based argumentation frameworks. *Journal of Logic and Computation* 13(3):429–448.
- Baba, J., and Chudziak, J. A. 2026. Multi-agent dialectical refinement for enhanced argument classification. doi:10.48550/arXiv.2603.27451.
- Brewka, G., and Woltran, S. 2010. Abstract dialectical frameworks. KR’10, 102–111. AAAI Press.
- Dimopoulos, Y.; Maily, J.-G.; and Moraitis, P. 2018. Control argumentation frameworks. AAAI’18/IAAI’18/EAAI’18. AAAI Press.
- Dung, P. M. 1995. On the acceptability of arguments and its fundamental role in nonmonotonic reasoning, logic programming and n-person games. *Artificial Intelligence* 77(2):321–357.
- Modgil, S. 2009. Reasoning about preferences in argumentation frameworks. *Artificial Intelligence* 173(9):901–934.
- Sadowski, A., and Chudziak, J. A. 2026. Rashomon memory: Towards argumentation-driven retrieval for multi-perspective agent memory. doi:10.48550/arXiv.2604.03588.