

The Transformer Revolution, Part 1: Dynamic Processing through Output-Weight Interconnections

Marco Giunti[†], Fabrizia Giulia Garavaglia[‡]

[†] giunti@unica.it, [‡] fabriziag.garavaglia@unica.it

[†] ALOPHIS – Applied Logic Philosophy and History of Science

[‡] Dip. di Pedagogia, Psicologia, Filosofia

[†] [‡] Università di Cagliari

[†] ORCID: 0000-0003-4182-4850, [‡] ORCID: 0009-0003-4699-4709

ABSTRACT

This paper offers a new interpretation of the Transformer during inference. Against the “stochastic parrot” view that large language models merely reproduce statistical regularities learned in training, we argue that Transformers construct and apply prompt-dependent transformations whose parameters are generated during inference. We call this form of computation SIDPP: Sequence-level Interactive Dynamic Parallel Processing.

The Transformer is interpreted as a system that transforms concepts by means of concepts. Token vectors are the concepts to be transformed; parameterized transformations defined by matrices and vectors are the transforming concepts. These may be static, when fixed through training, or dynamic, when generated from the input sequence. Mechanically, they correspond to groups of simple neural networks. The Transformer’s architectural novelty lies in output-weight interconnections, through which the outputs of some networks determine the weights of others, alongside ordinary output-input interconnections.

By means of these interconnections, the system constructs transformations from the prompt and uses them to modify token representations. The contribution of dynamic processing grows with prompt length and may equal or exceed that of static processing—a phenomenon we call strong prompt sensitivity.

This account bears on interpretability, predictability, control, and the design of smaller, more sustainable systems. Finally, since the human neural system possesses the mechanisms required to implement SIDPP, we argue that a form of SIDPP may, in principle, be neurally realized in the cerebral cortex. We therefore conjecture that human language processing may itself be a form of SIDPP produced by a functional architecture relevantly similar to that of the Transformer.

1 Introduction

Less than four years after the launch of ChatGPT on 30 November 2022, we are witnessing a period of accelerated development and innovation in Artificial Intelligence (AI), largely driven by the emergence of a new paradigm based on the Transformer architecture (Vaswani et al. 2017) and on its subsequent adaptations and applications across an extremely wide range of fields and tasks.

Looking at the history of AI (Nilsson 2010), we can distinguish three main phases, characterized overall by four different types of systems: rule-based symbolic systems in the first (1950–1980); traditional neural networks in the second (1980–1990); and, in the third (1990–2017), systems

that exploit statistical regularities extracted from large amounts of data. The third phase initially comprised statistical machine-learning systems proper and, subsequently, deep neural networks.¹ These types of systems differ profoundly from one another, both in their structure and in the way they process information. They nevertheless share one common feature: none of them was ever able to pass the Turing test (1950), or even to come close to passing it (Oppy & Dowe 2021).

Turing proposed this test as an objective criterion for determining whether a machine is intelligent. Although this interpretation is no longer tenable (Block 1981; Bayne & Williams 2023; Biever 2023; Jones & Bergen 2026), the fact remains that, in order to pass the test, a machine must be capable of conversing with a human being on any topic, using natural language appropriately and drawing on a shared body of knowledge. Equipping a machine with these capacities represented an insurmountable problem for AI until, at the end of 2022, ChatGPT demonstrated to the general public that it possessed them. GPT-4.5 subsequently formally passed the Turing test, with statistically robust results, in a series of preregistered experiments (Jones & Bergen 2025, 2026; cf. Giunti 2026).

To understand how this breakthrough became possible, it is necessary to investigate in depth the mechanisms underlying the operation of the Transformer architecture, which represent a radical change in the way AI processes information. We call this new type of processing SIDPP—Sequence-level Interactive Dynamic Parallel Processing (§ 3).

We will see, in particular, that the Transformer is a system that transforms concepts by means of concepts (§§ 2.1–2.2). The concepts to be transformed are vector representations of tokens, while the transforming concepts are the neural networks that modify these representations (§ 2.3). Transforming concepts constitute the material structure of the Transformer because they are nothing over and above interconnected simple neural networks. What makes the Transformer innovative, however, is the non-standard form of interconnection among these networks, whereby the outputs of some determine the weights of others (§ 2.7).

Dynamic transforming concepts—the networks whose weights are the outputs of other networks and are therefore updated dynamically during inference—make a highly significant contribution to the Transformer’s overall processing. Their contribution increases with prompt length and, even with relatively short prompts, may become comparable to, or even greater than, that of *static* transforming concepts—the networks whose weights are fixed through training. We call this phenomenon *strong prompt sensitivity* (§ 4). It was clearly manifested in GPT-4.5’s recent success in passing the Turing test (§ 5).

An essential part of the Transformer’s processing is therefore dynamic: it depends on parameters that are not assigned fixed values through training and whose contribution remains substantial even with relatively short prompts. Understanding and exploiting this distinctive feature of the Transformer opens up new perspectives for the interpretability, predictability, and control of such systems (§ 6.1). It may also have important implications for the design and implementation of new, smaller systems with lower energy consumption and environmental costs (§ 6.2).

The central thesis of this paper is that, during inference, the Transformer is not merely a set of static parameters mechanically applied to an input, but a system of parallel processes that

¹ For rule-based symbolic systems, see Newell & Simon (1976), Newell (1980), and Buchanan & Shortliffe (1984); for traditional neural networks, McClelland et al. (1986) and Rumelhart et al. (1986); for statistical machine-learning systems, Bishop (2006); and for deep neural networks, LeCun et al. (2015).

constructs and then uses new transformations, on the basis of the prompt. This construction is made possible by non-standard interconnections among groups of simple networks: not only output-input interconnections, but also output-weight interconnections. This plasticity is a feature that the Transformer shares with our own neural system and ultimately leads us to formulate a bold conjecture (§ 7), which will be the subject of the second part of this work: is it possible that the morphology and functioning of our neural system realize a similar type of material structure?

2 The Transformer as a System Composed of Groups of Simple Neural Networks Linked by Output–Input and Output–Weight Interconnections

As is well known, the Transformer has two distinct modes of operation: (i) training, including pre-training and fine-tuning, and (ii) inference, when it is given a prompt and generates a response on that basis. A widely held view is that the key to its entire functioning lies in mode (i), and that inference therefore consists simply in reproducing the statistical regularities that the model learned during training (Floridi et al. 2025). This is the source of the well-known metaphor according to which LLMs are nothing more than “stochastic parrots” (Bender et al. 2021).

In fact, careful consideration of the mathematical definition of the model and, in particular, of the meaning of the mathematical operations performed by attention heads (Vaswani et al. 2017, § 3.2; Lee & Trott 2023; Giunti 2025, § 2.1.1; Jurafsky & Martin 2026, chs. 8 and 9) immediately reveals that the model’s operation during inference goes far beyond the mere reproduction of statistical regularities learned during training. The system is capable of adapting its previously acquired knowledge on the basis of the prompt it receives, using these adaptations to modify the initial representations of each token, and, on this basis, selecting the token that constitutes the best continuation of the prompt itself.

2.1 The Transformer Is a System That Transforms Concepts by Means of Concepts

From this perspective, we can formulate a unified interpretation of the Transformer’s entire operation during inference, which we summarize in the following statement: the Transformer is a system that transforms concepts by means of concepts (Figure 1).

Transformee concepts—the concepts to be transformed—are vector representations of each token: both the initial ones, namely the embedding vectors, and those progressively generated during processing.

Transforming concepts modify, enrich, and refine these representations through successive steps. It is important to recognize that they are of two kinds: those fixed by training, or *static*, and those that are *dynamic*. The former, learned during training, are the transformations²

² In general, a matrix $\mathbf{M} \in \mathbb{R}^{q \times p}$ of model parameters defines a linear transformation $\mathcal{L}[\mathbf{M}]: \mathbb{R}^q \rightarrow \mathbb{R}^p$, $\mathcal{L}[\mathbf{M}](\mathbf{u}) := \sum_{i=1}^q u_i r_i(\mathbf{M})$, where u_i is any element of the vector $\mathbf{u} \in \mathbb{R}^q$ and $r_i(\mathbf{M})$ is the i -th row of $\mathbf{M}$. Similarly, a parameter vector $\mathbf{v} \in \mathbb{R}^q$ defines two different transformations, $+\mathbf{v}$ and $\circ\mathbf{v}$: $\mathbb{R}^q \rightarrow \mathbb{R}^q$, depending on whether it is added to or multiplied componentwise by an arbitrary vector $\mathbf{u} \in \mathbb{R}^q$. The bias vectors in the feed-forward modules (see Figure 2), or in the normalization and optimization modules (see Figure 1), define transformations of type $+\mathbf{v}$; the output vectors of the attention or feed-forward modules also define, through the corresponding residual connections, transformations of type $+\mathbf{v}$ (see Figure 1). The scaling vectors (in the normalization and optimization modules), by contrast, define transformations of type $\circ\mathbf{v}$.

defined by the Transformer's matrices of trainable parameters,³ its bias and scaling vectors,⁴ and, where applicable, its positional encoding vectors.⁵ By contrast, the latter are transformations defined by other matrices or vectors generated during processing. More specifically, these matrices and vectors are: for each attention head i , the transpose of the key matrix, $\mathbf{K}_i^T$, and the value matrix, $\mathbf{V}_i$; and, for each residual connection, the output vectors of the corresponding attention or feed-forward module. The elements of these matrices and vectors are the model's *dynamic parameters*.

Each position i ($1 \leq i \leq q$) in a given *vector representation* $\mathbf{u} = (u_1, \dots, u_q) \in \mathbb{R}^q$ of a token corresponds to a particular feature, or property, of tokens, and the number u_i in that position indicates the extent to which that specific token possesses that feature: it is the value of that feature for that token. The interpretation of the token provided by the representation $\mathbf{u}$ is therefore the ordered set of all its features, each with its specific value.

In other words, a vector representation of a token should not be understood as a mere sequence of numbers, but as a vector whose positions correspond to specific representational features of the token (Bengio et al. 2003, p. 1139). The vector assigns a specific value to each of these features and thus provides an interpretation of the token at that particular stage of processing.⁶ This does not imply, however, that these features are immediately interpretable in human terms (Şenel et al. 2021, p. 722), nor that they necessarily remain invariant throughout all stages of the process.⁷

Let us now consider a transforming concept, $\mathcal{L}[\mathbf{M}]$, defined by a matrix $\mathbf{M} \in \mathbb{R}^{q \times p}$ of model parameters, and apply it to the vector representation $\mathbf{u} \in \mathbb{R}^q$ of a token. First, we note that each row $r_i(\mathbf{M})$ of the matrix $\mathbf{M}$ can be regarded as a vector representation of the i -th feature of the token representation $\mathbf{u}$, that is, as a second-order representation. Each second-order

³ The matrices of trainable parameters that define linear transformations of vector representations of tokens are as follows: for each attention head i , the three matrices $\mathbf{W}_i^Q$, $\mathbf{W}_i^K$, $\mathbf{W}_i^V$ (see Figure 4); for each multi-head attention module, the output projection matrix $\mathbf{W}^O$ (see Figure 3); for each feed-forward network module, the matrices $\mathbf{W}_1$ and $\mathbf{W}_2$ of the two linear layers (see Figure 2); and, in the final module, the matrix $\mathbf{W}^L$ that produces the logits (see Figure 1, Forecast module). The embedding table $\mathbf{E} \in \mathbb{R}^{d_{voc} \times d_{model}}$ is itself composed of trainable parameters, but it does not define a linear transformation of vector representations of tokens. By contrast, its rows are the initial vector representations of each token. Moreover, if the model uses weight tying ($\mathbf{E}^T = \mathbf{W}^L$) between the embedding matrix $\mathbf{E}$ and the final projection matrix $\mathbf{W}^L$, the parameters of $\mathbf{E}$ are identical to those of $\mathbf{W}^L$ and therefore should not be counted separately when calculating the number of trainable parameters of the model.

⁴ In each feed-forward network module, there are two bias vectors, $\mathbf{c} \in \mathbb{R}^{d_f}$ and $\mathbf{d} \in \mathbb{R}^{d_{model}}$ (see Figure 2). There is another bias vector, $\mathbf{b} \in \mathbb{R}^{d_{model}}$, in each mean and variance normalization and optimization module, and that module also contains the corresponding scaling vector $\mathbf{a} \in \mathbb{R}^{d_{model}}$ (see Figure 1). All the elements of the bias and scaling vectors are trainable parameters of the model.

⁵ The positional encoding vectors, of dimension d_{model} , are added to the matrix $\mathbf{X}$ of embedding vectors corresponding to the tokens in the prompt, thereby forming the input matrix $\mathbf{I}$ of the first layer of the Transformer stack, which consists of N structurally identical layers (see Figure 1). There are n_{max} positional encoding vectors, where n_{max} is the size of the model's context window. If the model uses sinusoidal positional encoding, the elements of these vectors are constants fixed independently of training, and the positional encoding vectors therefore do not define static transforming concepts. In some models, however, these vectors instead consist of trainable parameters. In that case, the positional encoding vectors also define static transforming concepts of type $+[v]$.

⁶ For a general theoretical framework for this conception, one may refer to Hinton's (1986) classic work on distributed representations, in which concepts are treated as distributed patterns of activation, and to Bengio, Courville, and Vincent's (2013) survey of representation learning, which interprets representations as structures capable of capturing explanatory factors in the data through increasingly abstract transformations.

⁷ For a discussion of the differentiated distribution of linguistic information through the layers of BERT, cfr. Jawahar et al. (2019, p. 3653).

representation $r_i(\mathbf{M})$ is then weighted by the feature value u_i and all the resulting weighted representations are finally summed, thereby producing the new representation of the token:

$$\mathcal{L}[\mathbf{M}](\mathbf{u}) := \sum_{i=1}^q u_i r_i(\mathbf{M}).$$

The new representation of the token is therefore a combination of all the representations of the features of the previous representation, in which the representations of the features that had the highest values predominate.

A similar mechanism also applies to the two types of transforming concepts, $+[v]$ and $\circ[v]$, defined by a vector $\mathbf{v} \in \mathbb{R}^q$ of model parameters. Suppose that we apply them to the vector representation $\mathbf{u} \in \mathbb{R}^q$ of a token. We note that each element $v_i \in \mathbb{R}$ of the vector $\mathbf{v}$ can be regarded as a *numerical representation*⁸ of the i -th feature of the token representation $\mathbf{u} \in \mathbb{R}^q$ that is, once again, as a second-order representation. Each second-order representation v_i is then modified by adding it to the feature value u_i , or by multiplying it by that value. Finally, all the representations thus modified are concatenated in their original order, thereby producing the new vector representations of the token:

$$\begin{aligned} +[\mathbf{v}](\mathbf{u}) &:= \mathbf{u} + \mathbf{v} = (u_1 + v_1, \dots, u_q + v_q) \quad \text{and} \\ \circ[\mathbf{v}](\mathbf{u}) &:= \mathbf{u} \circ \mathbf{v} = (u_1 v_1, \dots, u_q v_q). \end{aligned}$$

Thus, as in the case of transforming concepts of the type $\mathcal{L}[\mathbf{M}]$, the new representations of the token are aggregations of all the representations of the features of the previous representation, in which the representations of the features that had the highest values predominate.⁹

2.2 Dynamic Transforming Concepts as Adaptations of Static Transforming Concepts Based on an Input Sequence

An important point of this conceptual interpretation of the Transformer is that it clarifies why the operation in inference goes far beyond the pure and simple repetition or application of what has been learned in training. Training determines only some of the concepts that the system uses to transform the representations of each token. These are the static transforming concepts, defined by the weight matrices and also by the bias and scaling vectors, the elements of which are all trainable parameters of the system:¹⁰ they act on the representations of the tokens by transforming them based on what has been previously learned. In addition to these transformations, however, the Transformer employs further transformations, defined by additional matrices and vectors whose elements are not trainable parameters, but are dynamically produced during the inference process itself. We have called these transformations *dynamic* transforming concepts, and they are at work in each attention head i —transformations $\mathcal{L}[\mathbf{K}_i^T]$ e $\mathcal{L}[\mathbf{V}_i]$ defined respectively by the transpose of the key matrix and the value matrix—and in the residual connections—transformations $+[v]$ defined by the output vectors of the attention and feed-forward modules. In the residual connections, these transformations are used to modify the representations of each token that are provided as input

⁸ In general, a numerical representation $x \in \mathbb{R}$ of an object of a certain type identifies a single feature (or property) of objects of that type, whose value for that object is the number x itself.

⁹ This proposal can be broadly related to the way the literature describes the weights that determine individual output components as profiles for combining input features, and additive or multiplicative vectors as transformations that act on the representation feature by feature (Jurafsky & Martin 2026, ch. 6; Perez et al. 2018; Dumoulin et al. 2018).

¹⁰ In addition to bias and scaling vectors, positional encoding vectors also define static transforming concepts if and only if their elements are *trainable* parameters and therefore the system does not use sinusoidal encoding or other training-independent positional encodings (see footnote 8).

to those very modules, thereby producing the new representations that are then passed to the subsequent modules.

These considerations show how important it is to focus on the transformations whose parameters, which we call *dynamic*, are produced within the inference process itself and therefore depend on specific representations of the prompt or, more precisely, on a sequence of vector representations that constitute the rows of an input matrix $\mathbf{I}$. First, on the basis of the input sequence $\mathbf{I}$ and of the matrices or vectors fixed by training, the Transformer produces new matrices or vectors that define the dynamic transforming concepts; it then uses them to modify the representations of the prompt. Dynamic transforming concepts can therefore be understood as adaptations of static concepts on the basis of an input sequence $\mathbf{I}$. This process—consisting of (i) the adaptation of previously acquired knowledge on the basis of an input sequence and (ii) the subsequent application of the adapted knowledge to modify the representations of the prompt—is much more complex and sophisticated than the mere direct application, to the vector representations of the prompt, of the transformations defined by matrices or vectors fixed by training.

However, in order to fully understand what is novel about the Transformer architecture, it is also necessary to consider how the mathematical operations that define the model can be identified with a system composed of groups of simple neural networks that, as we shall see, are *interconnected in non-standard ways*.

2.3 Transforming Concepts as Three Types of Simple Neural Networks

First of all, we note that, from a mechanical-structural point of view, all the transforming concepts—the parameterized transformations of the three types $\mathcal{L}[\mathbf{M}]$, $+[v]$ and $\circ[v]$ —can be identified with three different types of simple neural networks.

1. The transforming concepts of the type $\mathcal{L}[\mathbf{M}]$, where $\mathbf{M} \in \mathbb{R}^{q \times p}$, are *dense linear networks*, consisting of two fully connected levels of units, the first with q input units and the second with p output units. Each input unit has only output connections with all output units, each of which has only the corresponding input connections. The i -th row of $\mathbf{M}$ identifies the weights of all output connections of the i -th input unit, while the j -th column gives us the weights of all the incoming connections of the j -th output unit. Each input unit performs no transformation on the incoming signal but simply routes it to all the output units through its outgoing connections. Each output unit produces the weighted sum of all signals from the input units, thus implementing the j -th component of the linear transformation $\mathcal{L}[\mathbf{M}]$.
2. The transforming concepts of the type $+[v]$, where $v \in \mathbb{R}^q$, are *one-to-one additive networks*. They have two layers, the first with q input units and the second with q output units. The i -th input unit has only one output connection with the i -th output unit and no input connections with other units. In addition, the i -th output unit has only one input connection with the corresponding input unit and no output connection with other units. The i -th element v_i of vector v is the weight of the corresponding connection. Each input unit does not transform the input signal but only routes it to the corresponding output unit through its output connection. Each output unit *sums* the input signal with the weight of its connection, thus implementing the i -th component of the transformation $+[v]$.
3. The transforming concepts of the type $\circ[v]$, where $v \in \mathbb{R}^p$, are *one-to-one multiplicative networks*. Their morphology is identical to that of one-to-one additive networks and they differ from them only in the operation of the output units: in fact, each output unit *multiplies* the input signal by the weight of its connection, thus implementing the i -th component of the transformation $\circ[v]$.

2.4 Sequence-Level Parallel Processing in the Transformer

Second, it is important to bear in mind that the Transformer's entire operation can be divided into a series of successive stages (see Figure 1). Each of these stages can be identified with a particular module $\mathcal{M}_r$ that receives a given input $\mathbf{I}_r$ and produces a specific output $\mathbf{O}_r$, which is then passed as input to a subsequent module, or is the final output. The input of each module, from the one that performs positional encoding to the final one that produces probability distributions by applying the function *softmax*, is a matrix $\mathbf{I}_r \in \mathbb{R}^{n \times i_r}$ whose rows are vector representations, of dimension i_r , of the prompt tokens. The number n of rows therefore cannot exceed n_{max} , i.e., the size of the Transformer's context window. Similarly, the output of each of the above-mentioned modules is a matrix $\mathbf{O}_r \in \mathbb{R}^{n \times o_r}$ whose rows are vector representations, of dimension o_r , of the prompt tokens. The dimensions i_r and o_r of the token representations (at input and output, respectively) are not the same for all modules, but depend on the specific module under consideration.

Within each module $\mathcal{M}_r$ there may be a single process, whose input and output coincide with the input $\mathbf{I}_r$ and the output $\mathbf{O}_r$ of the module itself (see Figure 2 and, in Figure 1, the *Positional encoding*, *Mean and variance normalization and optimization*, and *Forecast modules*), or multiple processes that operate on the same input $\mathbf{I}_r$ in parallel and either (i) subsequently merge into a single process with output $\mathbf{O}_r$ (see Figure 3), or (ii) are reduced pairwise to a single process with output $\mathbf{O}_r$ (see Figures 4, 5, and 6 and, in Figure 1, the two *Residual connection modules*).

Each process consists of a finite sequence of operations $Op_1, \dots, Op_k$, each of which takes the output of the preceding operation as input. The operations that make up the various processes are of three types—*parameterized*, *structural*, and *formal*—which are described in detail below (§ 2.5). Each operation of the first two types, Op , consists in the parallel application, to the $n \leq n_{max}$ rows (or to the q columns) of its input matrix $\mathbf{X} \in \mathbb{R}^{n \times q}$, of n (or q) transformations $f_1, \dots, f_n$ (or $f_1, \dots, f_q$), whose results are row (or column) vectors of dimension p (or n); when concatenated along the row (column) axis, these vectors form the operation's output matrix $Op(\mathbf{X}) = \mathbf{X}' \in \mathbb{R}^{n \times p}$ (or $\mathbb{R}^{n \times q}$). There are only two formal operations, *Concat* and *Transp*, which play an essential role, respectively, in the merging of multiple processes into one and in the reduction of two processes to one.

h distinct processes that operate on the same input in parallel *merge* into a single process if they share the same formal operation *Concat*. This operation takes as input all the matrices produced by the immediately preceding operations of each of the h processes and concatenates them along the column axis, thereby producing a single matrix that is then processed by a subsequent operation (see Figure 3). This operation does not constitute an additional process within the same module, but counts as a continuation of each of the h processes.

Two distinct processes that operate on the same input in parallel *are reduced* to a single process if the final operation of one of them produces an output that is not processed further but is instead used as the parameter set for an operation in the other process (see Figures 4, 5, and 6 and, in Figure 1, the two *Residual connection modules*). We shall see that, in the Transformer, there are four different ways of reducing two processes to one and that the formal operation *Transp* is constitutive of the second (§ 2.7.1).

2.5 The Transformer's Matrix Operations: Parameterized, Structural, and Formal

The *parameterized operations* are functions of the four types defined below:

- 1) $Add[\mathbf{v}](\mathbf{X}): \mathbb{R}^{n \times q} \rightarrow \mathbb{R}^{n \times q}$, with $q = d_{model}$ or $q = d_f$,¹¹ defined by:

$$Add[\mathbf{v}](\mathbf{X}) := \begin{pmatrix} +[\mathbf{v}](r_1(\mathbf{X})) \\ +[\mathbf{v}](r_2(\mathbf{X})) \\ \vdots \\ +[\mathbf{v}](r_n(\mathbf{X})) \end{pmatrix}, \text{ where } \mathbf{v} \in \mathbb{R}^q \text{ is a vector of the model's bias parameters}$$

and $r_i(\mathbf{X})$ is the i -th row of $\mathbf{X}$;

- 2) $Mult[\mathbf{v}]: \mathbb{R}^{n \times d_{model}} \rightarrow \mathbb{R}^{n \times d_{model}}$, defined by:

$$Mult[\mathbf{v}](\mathbf{X}) := \begin{pmatrix} \circ[\mathbf{v}](r_1(\mathbf{X})) \\ \circ[\mathbf{v}](r_2(\mathbf{X})) \\ \vdots \\ \circ[\mathbf{v}](r_n(\mathbf{X})) \end{pmatrix}, \text{ where } \mathbf{v} \in \mathbb{R}^{d_{model}} \text{ is a vector of the model's scaling}$$

parameters and $r_i(\mathbf{X})$ is the i -th row of $\mathbf{X}$;

- 3) $Add[\mathbf{M}]: \mathbb{R}^{n \times d_{model}} \rightarrow \mathbb{R}^{n \times d_{model}}$, defined by:

$$Add[\mathbf{M}](\mathbf{X}) := \begin{pmatrix} +[r_1(\mathbf{M})](r_1(\mathbf{X})) \\ +[r_2(\mathbf{M})](r_2(\mathbf{X})) \\ \vdots \\ +[r_n(\mathbf{M})](r_n(\mathbf{X})) \end{pmatrix}, \text{ where } r_i(\mathbf{X}) \text{ and } r_i(\mathbf{M}) \text{ are the } i\text{-th rows of } \mathbf{X} \text{ and } \mathbf{M},$$

respectively, and $\mathbf{M} \in \mathbb{R}^{n \times d_{model}}$ is the output matrix of any attention or feed-forward module or, if the positional encoding vectors are trainable, $\mathbf{M} \in \mathbb{R}^{n_{max} \times d_{model}}$ is the matrix whose rows are those vectors;

- 4) $Mult[\mathbf{M}]: \mathbb{R}^{n \times q} \rightarrow \mathbb{R}^{n \times p}$, defined by:

$$Mult[\mathbf{M}](\mathbf{X}) := \begin{pmatrix} \mathcal{L}[\mathbf{M}](r_1(\mathbf{X})) \\ \mathcal{L}[\mathbf{M}](r_2(\mathbf{X})) \\ \vdots \\ \mathcal{L}[\mathbf{M}](r_n(\mathbf{X})) \end{pmatrix}, \text{ where } \mathbf{M} \in \mathbb{R}^{q \times p} \text{ is a matrix of model parameters and}$$

$r_i(\mathbf{X})$ is the i -th row of $\mathbf{X}$. Note that $Mult[\mathbf{M}](\mathbf{X}) = \mathbf{X}\mathbf{M}$, where $\mathbf{X}\mathbf{M}$ is the product of the two matrices.

¹¹ d_{model} is the dimension of the embedding vectors, also called the model's hidden dimension; d_f is the dimension of the inner layer of the feed-forward network in each transformer layer; n is the number of tokens in the prompt.

The *structural operations* are functions of the five types defined below:

- 1) $Mult\{c\}: \mathbb{R}^{n \times q} \rightarrow \mathbb{R}^{n \times q}$, defined by:

$$Mult\{c\}(X) := \begin{pmatrix} \circ\{c\}(r_1(X)) \\ \circ\{c\}(r_2(X)) \\ \vdots \\ \circ\{c\}(r_n(X)) \end{pmatrix}, \text{ where } c \in \mathbb{R} \text{ is a constant characteristic of the model,}$$

specifically: $c = \frac{1}{\sqrt{d_k}}$, in which case $q = n$, or $c = t > 0$ and $q = d_{voc}$; ¹² $r_i(X)$ is the i -th row of X , and $\circ\{c\}$ is the function from $\mathbb{R}^q$ to $\mathbb{R}^q$ defined as follows: $\circ\{c\}(r_i(X)) := r_i(X) \circ c$, where $c = (c, \dots, c) \in \mathbb{R}^q$, and $\circ$ denotes the Hadamard product—that is, the component-by-component product—of two vectors;

- 2) $Add\{\mathfrak{M}\}: \mathbb{R}^{n \times q} \rightarrow \mathbb{R}^{n \times q}$, defined by:

$$Add\{\mathfrak{M}\}(X) := \begin{pmatrix} +\{r_1(\mathfrak{M})\}(r_1(X)) \\ +\{r_2(\mathfrak{M})\}(r_2(X)) \\ \vdots \\ +\{r_n(\mathfrak{M})\}(r_n(X)) \end{pmatrix}, \text{ where } \mathfrak{M} \in \mathbb{R}^{n_{max} \times q}, n_{max} \text{ is the size of the}$$

model's context window, $r_i(X)$ and $r_i(\mathfrak{M})$ are the i -th rows of X and $\mathfrak{M}$, respectively, and $+\{r_i(\mathfrak{M})\}$ is the function from $\mathbb{R}^q$ to $\mathbb{R}^q$ defined as follows: $+\{r_i(\mathfrak{M})\}(r_i(X)) := r_i(X) + r_i(\mathfrak{M})$. If the model uses sinusoidal positional encoding, $q = d_{model}$ and $\mathfrak{M} \in \mathbb{R}^{n_{max} \times d_{model}}$ is the matrix consisting of all the positional encoding vectors, or $q = n$ and $\mathfrak{M} \in \mathbb{R}^{n_{max} \times n}$ is the masking matrix; otherwise, $q = n$ and $\mathfrak{M} \in \mathbb{R}^{n_{max} \times n}$ is the masking matrix;¹³

- 3) $ReLU: \mathbb{R}^{n \times d_f} \rightarrow \mathbb{R}^{n \times d_f}$, defined by:

$$ReLU(X) := \begin{pmatrix} reLU(r_1(X)) \\ reLU(r_2(X)) \\ \vdots \\ reLU(r_n(X)) \end{pmatrix}, \text{ where } r_i(X) \text{ is the } i\text{-th row of } X, \text{ and } reLU: \mathbb{R}^{d_f} \rightarrow \mathbb{R}^{d_f} \text{ is}$$

defined as follows: $reLU(r_i(X)) := (\max(0, x_{i1}), \max(0, x_{i2}), \dots, \max(0, x_{id_f}))$;

- 4) $Softmax: \mathbb{R}^{n \times q} \rightarrow \mathbb{R}^{n \times q}$ with $q = n$ or $q = d_{voc}$, defined by:

$$Softmax(X) := \begin{pmatrix} softmax(r_1(X)) \\ softmax(r_2(X)) \\ \vdots \\ softmax(r_n(X)) \end{pmatrix}, \text{ where } r_i(X) \text{ is the } i\text{-th row of } X, \text{ and}$$

$softmax: \mathbb{R}^q \rightarrow \mathbb{R}^q$ is defined as follows:

¹² The constant $\frac{1}{\sqrt{d_k}}$, where d_k is the dimension of the model's query and key vectors, is the rescaling constant for raw attentions. The constant $t > 0$ is the model's temperature, which scales the logit vectors in the final module immediately before *softmax*; d_{voc} is the number of tokens in the model's vocabulary.

¹³ In *decoder-only* Transformers, the structural operation $Add\{\mathfrak{M}\}$, with $\mathfrak{M}$ equal to the masking matrix, is used in attention heads to make them *autoregressive*. It is applied immediately after the raw-attention rescaling operation and before *Softmax* (see Figure 4). If masking is not applied, the attention heads are *bidirectional* (see Figure 5). See the Appendix and Figures 6 and 12–12e for an alternative way of achieving autoregressivity that does not use masking.

$$\text{softmax}(r_i(\mathbf{X})) := (p_{i1}, p_{i2}, \dots, p_{iq}), \text{ where } p_{ij} = \frac{e^{x_{ij}}}{\sum_{j=1}^q e^{x_{ij}}};$$

5) *Norm*: $\mathbb{R}^{n \times d_{\text{model}}} \rightarrow \mathbb{R}^{n \times d_{\text{model}}}$, defined by:

$$\text{Norm}(\mathbf{X}) := \left(\text{norm}(c_1(\mathbf{X})), \text{norm}(c_2(\mathbf{X})), \dots, \text{norm}(c_{d_{\text{model}}}(\mathbf{X})) \right), \text{ where } c_j(\mathbf{X}) \text{ is the } j\text{-th column of } \mathbf{X}, \text{ and } \text{norm}: \mathbb{R}^n \rightarrow \mathbb{R}^n, \text{norm}(c_j(\mathbf{X})) := \begin{pmatrix} \hat{x}_{1j} \\ \hat{x}_{2j} \\ \vdots \\ \hat{x}_{nj} \end{pmatrix}, \text{ where } \hat{x}_{ij} = \frac{x_{ij} - \mu_j}{\sqrt{\sigma_j^2 + \varepsilon}}, \mu_j = \frac{1}{n} \sum_{i=1}^n x_{ij} \text{ is the mean of column } c_j(\mathbf{X}), \sigma_j^2 = \frac{1}{n} \sum_{i=1}^n (x_{ij} - \mu_j)^2 \text{ is its variance, and } \varepsilon \in \mathbb{R} \text{ is a small positive constant—for example, } \varepsilon = 10^{-6} \text{—that prevents an otherwise possible division by zero.}$$

The *formal operations* do not modify the constituent elements of their inputs (that is, the contents of the inputs), but only the way in which those elements are arranged (that is, their form), and are of only two types:

- 1) the *Concat* operation for concatenating h matrices $\mathbf{X}_1, \dots, \mathbf{X}_h \in \mathbb{R}^{n \times d_v}$, which joins them along the column axis, defined by: $\text{Concat}(\mathbf{X}_1, \dots, \mathbf{X}_h) := \mathbf{X} \in \mathbb{R}^{n \times h d_v}$, where the element x_{lu} of $\mathbf{X}_l$ ($1 \leq l \leq h$) is identical to the element x_{ij} of $\mathbf{X}$, with $j = (l-1)d_v + u$;
- 2) the transposition operation $\text{Transp}: \mathbb{R}^{n \times d_k} \rightarrow \mathbb{R}^{d_k \times n}$ on a matrix $\mathbf{X} \in \mathbb{R}^{n \times d_k}$, defined by: $\text{Transp}(\mathbf{X}) := \mathbf{X}^\top$, where the element x_{ij} of $\mathbf{X}$ is identical to the element x_{ji} of $\mathbf{X}^\top$.

2.6 Matrix Operations as Groups of n_{max} Simple Neural Networks, or as Output-Input Interconnections—Operational and Routing—Between such Groups

We note that (i) *parameterized operations* of any type consist in the parallel application of a *transforming concept of the same type* to the rows of matrix $\mathbf{X}$, that is, to a sequence of vector representations of the n tokens of the prompt; analogously, (ii) *structural operations* of types 1, 2, 3, and 4 also consist in the parallel application of a *function of the same type*, dependent only on the structure of the model, to a sequence of vector representations of the n tokens of the prompt, that is, to the rows of $\mathbf{X}$. However, in the case of structural operations of type 5, the function *norm* (also determined only by the structure of the model) is not applied in parallel to this sequence, but to the d_{model} sequences each of which gives the distribution of one feature across the n token representations—that is, to the *columns* of the input matrix $\mathbf{X}$, rather than to its rows.

We further note that any parameterized operation of types 1, 2, 3, and 4, insofar as it is the parallel application of n transforming concepts of the same type, can always be identified with a corresponding group of n simple neural networks. More specifically, a parameterized operation of the type $\text{Add}[\mathbf{v}]$, $\text{Mult}[\mathbf{v}]$, or $\text{Mult}[\mathbf{M}]$ is identified with n copies of the simple neural network (one-to-one additive, one-to-one multiplicative, or dense linear) corresponding to the transformation $+[\mathbf{v}]$, $\circ[\mathbf{v}]$, or $\mathcal{L}[\mathbf{M}]$, respectively; an operation of the type $\text{Add}[\mathbf{M}]$ is identified with n one-to-one additive networks whose weights correspond to the n rows of $\mathbf{M} \in \mathbb{R}^{n \times d_{\text{model}}}$, or to the first n rows of $\mathbf{M} \in \mathbb{R}^{n_{\text{max}} \times d_{\text{model}}}$.

However, we must also take into account that the number n of simple neural networks corresponding to a given parameterized operation is always equal to the number of rows of its input matrix $\mathbf{X}$, and therefore is not a constant, but depends on the length of the prompt. Nevertheless, n is upper-bounded by the context-window size n_{max} . It follows that any parameterized operation of types 1, 2, 3, and 4 can always be identified with a corresponding

group of n_{max} simple neural networks, of which only the first $n \leq n_{max}$ are actually active in each specific operation (see Figures 8–15c).

Analogously, a structural operation of type 1 ($Mult\{c\}$) is identified with n copies of a one-to-one multiplicative network whose weights are all equal to the rescaling constant $c = \frac{1}{\sqrt{d_k}}$ (see Figures 10–12e), or to the temperature $c = t > 0$ (see Figures 15–15c); an operation of type 2 ($Add\{\mathbf{m}\}$) is identified with n one-to-one additive networks whose weights correspond to the n rows of the masking matrix (see Figures 10–10e) or, if the model uses sinusoidal positional encoding, to the first n positional encoding vectors (see Figures 7–7c). Therefore, each operation of type 1 or 2 can also always be identified with a corresponding group of n_{max} simple neural networks, of which only the first $n \leq n_{max}$ are actually active in each specific operation.

Structural operations of types 3, 4, and 5, by contrast, are not identified with n corresponding *simple neural networks* (that is, one-to-one additive or multiplicative networks, or dense linear networks), but with n copies (for types 3 and 4), or d_{model} copies (for type 5), of a specific *functional unit*, which modifies the output signals of the simple networks preceding it and then routes the signals thus modulated to the simple networks following it. More specifically, the i -th ($1 \leq i \leq n \leq n_{max}$) functional unit corresponding to *reLU* (or *softmax*) takes as input the d_f (or n , or d_{voc}) output signals of the i -th active network preceding it and produces d_f (or n , or d_{voc}) output signals, which constitute the input of the i -th active network following it (see Figures 14–14c for *reLU*; Figures 10–12e and 15–15c for *softmax*). By contrast, the j -th ($1 \leq j \leq d_{model}$) functional unit corresponding to *norm* takes as input all the j -th output signals of the $n \leq n_{max}$ active networks preceding it and produces n output signals, the i -th ($1 \leq i \leq n \leq n_{max}$) of which constitutes the j -th input of the i -th active network following it (see Figures 13–13c).

Structural operations of types 3, 4, and 5 therefore correspond to two specific types of interconnections between simple neural networks, which *modify* the outputs of the preceding group of $n \leq n_{max}$ simple networks and then transfer them as inputs to the following group of $n \leq n_{max}$ simple networks. We call interconnections of these two types *operational output-input interconnections*.

However, there are also interconnections that merely *transfer* the outputs of the preceding simple networks to the following ones, without modifying the signals, but regrouping them in a different way. These are *routing output-input interconnections*, which correspond to the formal matrix-concatenation operation *Concat* (see Figures 9–9c). More specifically, the preceding networks are divided into h groups, each consisting of n_{max} networks, of which only $n \leq n_{max}$ are actually active, whereas the following networks form a single group of n_{max} networks, of which $n \leq n_{max}$ are actually active. The output of the i -th ($1 \leq i \leq n_{max}$) network of the l -th ($1 \leq l \leq h$) preceding group is then transferred as the l -th part of the input of the i -th network of the following group.

2.7 The Novelty of the Transformer: Output-Weight Interconnections Between Networks with Trainable Parameters and Networks with Dynamic Parameters

We saw in the previous section that, with the sole exception of the formal transposition operation, *Transp*, all the Transformer's matrix operations can be identified either (i) with *groups of n_{max} simple neural networks*, of which only the first $n \leq n_{max}$ are active, or (ii) with two types of interconnections between such groups of networks: *operational output-input interconnections*, if they modify the output before transferring it as input; *routing output-input*

interconnections, if they transfer the output without modifying the signals, but regroup them in a different way.

However, we still need to understand the exact role of the *Transp* operation within the system of interconnected groups of simple neural networks that realizes the entire functional structure of the Transformer. To this end, we must take a step back and recall what we said in § 2.4 about those modules in which two processes coexist and are ultimately *reduced to a single process*.

In such cases, one of the two processes *terminates*, and its final operation therefore produces an output that is not further processed, but instead becomes the *parameters* of an operation of the other process, which we call the *receiving operation*. This means that the parameters of this operation are not fixed by training, but are instead *dynamic* parameters determined by the output of the final operation of the process that terminates (see Figures 4–6 and, in Figure 1, the two Residual connection modules).

In the Transformer, the receiving operations are always parameterized operations of types 4 ($Mult[\mathbf{M}]$) or 3 ($Add[\mathbf{M}]$), whereas the final operations are parameterized operations of types 4 ($Mult[\mathbf{M}]$) or 1 ($Add[\mathbf{M}]$), or the formal operation *Transp* applied to the output of a parameterized operation of type-4 ($Mult[\mathbf{M}]$). This implies that the reduction of two processes to one always occurs through a new type of interconnections between groups of $n \leq n_{max}$ simple networks: they link each *output* unit of the final group of networks of the process that terminates with the *connections* of those networks in the receiving group *whose weights are identical to the output* of that unit. We call interconnections of this new type *output-weight interconnections* (see Figures 8–8c and 10–12e).

In the Transformer, the reduction of two processes to one occurs in four different ways and, as we shall see below (§ 2.7.1), the *Transp* operation plays an essential role in the second. It should also be kept in mind that the first two ways occur in each attention head (see Figures 4–5), the third in each residual connection associated with a multi-head attention module (see Figures 1 and 3), and the fourth in each residual connection associated with a feed-forward module (see Figures 1 and 2). Each of these four ways therefore corresponds to a particular type of output-weight interconnections, each of which is described in detail below (§ 2.7.2).

2.7.1 The Four Ways of Reducing Two Processes to One in the Transformer

In the first way (see Figures 4–5), the final operation of the process that terminates is the type-4 parameterized operation, $Mult[\mathbf{W}_m^V]: \mathbb{R}^{n \times d_{model}} \rightarrow \mathbb{R}^{n \times d_v}$, where the parameter matrix is the value-generating matrix, $\mathbf{W}_m^V \in \mathbb{R}^{d_{model} \times d_v}$, of the m -th attention head. The receiving operation is also a type-4 parameterized operation, $Mult[\mathbf{M}]: \mathbb{R}^{n \times q} \rightarrow \mathbb{R}^{n \times p}$. $Mult[\mathbf{W}_m^V]$ is applied to the input $I \in \mathbb{R}^{n \times d_{model}}$ of the attention head, thus producing the value matrix: $Mult[\mathbf{W}_m^V](I) = \mathbf{V}_m \in \mathbb{R}^{n \times d_v}$. Since $\mathbf{V}_m$ is the final output of the process that terminates, $\mathbf{M} = \mathbf{V}_m$, and therefore $Mult[\mathbf{M}] = Mult[\mathbf{V}_m]: \mathbb{R}^{n \times n} \rightarrow \mathbb{R}^{n \times d_v}$.

In the second way (see Figures 4–5), the final operation of the process that terminates is the formal operation *Transp*, which is applied to the key matrix, $\mathbf{K}_m \in \mathbb{R}^{n \times d_k}$, of the m -th attention head and produces its transpose, $\mathbf{K}_m^T \in \mathbb{R}^{d_k \times n}$. In turn, $\mathbf{K}_m$ is the output of the type-4 parameterized operation, $Mult[\mathbf{W}_m^K]: \mathbb{R}^{n \times d_{model}} \rightarrow \mathbb{R}^{n \times d_k}$, which is applied to the input $I \in \mathbb{R}^{n \times d_{model}}$ of the attention head. As in the first way, the receiving operation is a type-4 parameterized operation, $Mult[\mathbf{M}]: \mathbb{R}^{n \times q} \rightarrow \mathbb{R}^{n \times p}$. Since $\mathbf{K}_m^T$ is the final output of the process that terminates, $\mathbf{M} = \mathbf{K}_m^T$, and therefore $Mult[\mathbf{M}] = Mult[\mathbf{K}_m^T]: \mathbb{R}^{n \times d_k} \rightarrow \mathbb{R}^{n \times n}$.

In the third way (see Figures 1 and 3), the final operation of the process that terminates is the output projection of any multi-head attention module and is therefore the type-4 parameterized

operation, $Mult[\mathbf{W}^O]: \mathbb{R}^{n \times hd_v} \rightarrow \mathbb{R}^{n \times d_{model}}$. Its output is the matrix $\mathbf{O} \in \mathbb{R}^{n \times d_{model}}$, that is, the output of the attention module. The receiving operation, by contrast, is the addition of the corresponding residual connection and is therefore the type-3 parameterized operation, $Add[\mathbf{O}]: \mathbb{R}^{n \times d_{model}} \rightarrow \mathbb{R}^{n \times d_{model}}$.

In the fourth way (see Figures 1 and 2), the final operation of the process that terminates is the addition of the second bias vector, $\mathbf{d}$, in any feed-forward module and is therefore the type-1 parameterized operation, $Add[\mathbf{d}]: \mathbb{R}^{n \times d_{model}} \rightarrow \mathbb{R}^{n \times d_{model}}$. Its output is the matrix $\mathbf{O}' \in \mathbb{R}^{n \times d_{model}}$, that is, the output of the entire feed-forward module. Finally, as in the third way, the receiving operation is the addition of the corresponding residual connection and is therefore the type-3 parameterized operation, $Add[\mathbf{O}']: \mathbb{R}^{n \times d_{model}} \rightarrow \mathbb{R}^{n \times d_{model}}$.

2.7.2 The Four Types of Output-Weight Interconnections in the Transformer

We saw above that, in the first way of reduction, the final operation $Mult[\mathbf{W}_m^V]$ and the receiving operation $Mult[\mathbf{V}_m]$ are both type-4 operations. Thus, $Mult[\mathbf{W}_m^V]$ is identified with $n \leq n_{max}$ copies of the dense linear network corresponding to the transformation $\mathcal{L}[\mathbf{W}_m^V]$, and $Mult[\mathbf{V}_m]$ with $n \leq n_{max}$ copies of the dense linear network corresponding to $\mathcal{L}[\mathbf{V}_m]$. Furthermore, $\mathbf{V}_m$ is both the output of $Mult[\mathbf{W}_m^V]$ and the parameter matrix of $Mult[\mathbf{V}_m]$. Therefore, the output of the i -th ($1 \leq i \leq n \leq n_{max}$) network corresponding to $\mathcal{L}[\mathbf{W}_m^V]$ is identical to the weights of the connections of the i -th input unit of each network corresponding to $\mathcal{L}[\mathbf{V}_m]$ (see Figures 10d, 11d).

In the second way, the final operation, $Transp$, produces the transpose, $\mathbf{K}_m^T$, of the key matrix, $\mathbf{K}_m$, which is the output of the type-4 parameterized operation $Mult[\mathbf{W}_m^K]$. Furthermore, the receiving operation is the type-4 parameterized operation $Mult[\mathbf{K}_m^T]$. Therefore, the output of the i -th ($1 \leq i \leq n \leq n_{max}$) network corresponding to $\mathcal{L}[\mathbf{W}_m^K]$ is identical to the weights of the connections of the i -th output unit of each network corresponding to $\mathcal{L}[\mathbf{K}_m^T]$ (see Figures 10e, 11e).

In the third way, the final operation is the type-4 parameterized operation $Mult[\mathbf{W}^O]: \mathbb{R}^{n \times hd_v} \rightarrow \mathbb{R}^{n \times d_{model}}$. The receiving operation, by contrast, is the type-3 parameterized operation $Add[\mathbf{O}]: \mathbb{R}^{n \times d_{model}} \rightarrow \mathbb{R}^{n \times d_{model}}$. Therefore, the output of the i -th ($1 \leq i \leq n \leq n_{max}$) network corresponding to $\mathcal{L}[\mathbf{W}^O]$ is identical to the weights of the connections of the network corresponding to $+[\mathbf{r}_i(\mathbf{O})]$ (see Figures 8–8c, 9–9c).

Finally, in the fourth way, the final operation is the type-1 parameterized operation $Add[\mathbf{d}]: \mathbb{R}^{n \times d_{model}} \rightarrow \mathbb{R}^{n \times d_{model}}$, whose output is the matrix $\mathbf{O}' \in \mathbb{R}^{n \times d_{model}}$. The receiving operation is the type-3 parameterized operation $Add[\mathbf{O}']: \mathbb{R}^{n \times d_{model}} \rightarrow \mathbb{R}^{n \times d_{model}}$. Therefore, the output of the i -th ($1 \leq i \leq n \leq n_{max}$) network corresponding to $+[\mathbf{d}]$ is identical to the weights of the connections of the network corresponding to $+[\mathbf{r}_i(\mathbf{O}')]$ (see Figures 8–8c, 14–14c).

3 Sequence-level Interactive Dynamic Parallel Processing in the Transformer

The analysis conducted so far has clarified that a Transformer can be described in two different ways, equivalent from a functional point of view, but which highlight different aspects of this architecture: (i) as a system of successive processing modules, each consisting of one or more processes: each process is a succession of operations on matrices whose rows are vector representations of the prompt's tokens; (ii) as a system composed of groups of n_{max} simple neural networks, where the i -th network of each group performs the processing related to the i -th ($1 \leq i \leq n \leq n_{max}$) prompt's token. In such a system, each group of simple networks implements a parameterized operation on matrices of types 1, 2, 3, 4, or a structural operation

of types 1 or 2. In addition, two groups of simple networks are connected by: (a) standard output-input interconnections, in which the output of a network in the first group is the input of the network corresponding to the same token in the second group; (b) two other types of output-input interconnections, *operational* and *routing*, which correspond to the structural operations on matrices of types 3, 4, 5 in the first case, and to the *Concat* formal operation in the second; (c) *output-weight* interconnections of four different types.

The information processing carried out by the Transformer represents a radical change compared to that of previous AI systems. We call this new type of processing SIDPP – *Sequence-level Interactive Dynamic Parallel Processing*, where: (i) SPP—*Sequence-level Parallel Processing*—means that the input sequence is processed in parallel, producing a corresponding output sequence. The elements of these sequences are vector representations of the prompt's tokens that, from a mathematical point of view, are treated as rows of matrices; (ii) SIPP—*Sequence-level Interactive Parallel Processing*—is a SPP where at least one vector representation in the output sequence depends on a vector representation of a different token in the input sequence; (iii) SDPP—*Sequence-level Dynamic Parallel Processing*—is a SPP such that the output sequence depends on parameterized transformations, whose parameters in turn depend on the input sequence. The parameters of these transformations are called *dynamic*.

Sequence-level parallel processing (SPP) is the type of processing that takes place in all parameterized or structural operations of the Transformer, starting from the one that performs positional encoding and up to the one that produces the probability distributions by applying the function *softmax*. Processing is also interactive (SIPP), but not dynamic, in normalization operations. In the addition operations of residual connection modules, processing is dynamic (SDPP), but not interactive. Finally, in each attention head, sequence-level parallel processing is dynamic and also interactive (SIDPP).

Considering the Transformer as a system of interconnected groups of simple neural networks, we realize that the different types of processing are related to different morphological characteristics of such a system. First, sequence-level parallel processing (SPP) is produced (i) by the groups of simple neural networks that implement the parameterized operations of the Transformer or the structural operations of the first two types, and (ii) by the groups of functional units that implement the operational interconnections corresponding to the structural operations of types 3, 4, 5. Secondly, dynamic processing (SDPP) is made possible by the output-weight interconnections, which are present both in the residual connections (see Figures 8–8c) and in the attention heads (see Figures 10–12e). Finally, interactive processing (SIPP) is due to the fact that the two types of output-weight interconnections in the attention heads and the operational interconnections corresponding to Norm structural operations (see Figures 13–13c) are *interwoven* links between two groups of simple networks: they connect networks in one group to networks in the other group that do not correspond to the same token. In contrast, all other interconnections are not interwoven, because they connect the networks of one group with networks of the other group corresponding to the same token.

Interwoven interconnections ensure inter-token interaction between two groups of networks, but it is important to note that this interaction occurs in two different ways, depending on which of three forms the interwoven links take. *Norm* operational interconnections and output-weight interconnections of the first type (§ 2.7.2) make the j -th feature ($1 \leq j \leq q$) of the i -th token ($1 \leq i \leq n \leq n_{max}$) depend on the j -th features of all tokens; they are therefore *feature* $\Rightarrow$ *feature* links (see Figures 10d, 11d, 13c). The output-weight interconnections of the second type (§ 2.7.2) make the j -th feature ($1 \leq j \leq n \leq n_{max}$) of the i -th token ($1 \leq i \leq n \leq n_{max}$)

depend on all features of the j -th token; they are therefore *token* $\Rightarrow$ *feature* links (see Figures 10e, 11e). Finally, we note that, in attention heads, it is precisely the succession of these two types of interaction,¹⁴ implemented by the corresponding interwoven output-weight interconnections, that constitutes the *causal mechanism* by which a token attends to other tokens.

4 The Relationship Between Dynamic and Static Parameters in the Transformer

We have already pointed out the novelty of sequence level dynamic parallel processing (SDPP), which is based on dynamic transforming concepts. However, its exact role and importance have not been adequately considered to date. In this regard, we want to highlight here an important property of the Transformer, which depends entirely on the occurrence of this type of processing.

In the Transformer, the *dynamic* parameters are the parameters of the dynamic transforming concepts (see § 2.1 and § 2.2), namely: for each attention head m ($1 \leq m \leq h$), the weights of the matrices $\mathbf{K}_m^\top$ and $\mathbf{V}_m$ and, for each residual connection, the elements of the output vectors of the corresponding attention or feed-forward module. We can therefore calculate the number D of the dynamic parameters for a given Transformer. Let n be the number of tokens in the prompt, N the number of layers, h the number of attention heads, d_k the size of the query and key vectors, d_{model} the size of the embedding vectors. It therefore results:

$$D = Cn, \text{ where } C = N(h(d_k + d_v) + 2d_{model})$$

We thus see that C is a characteristic constant of the system, whereas D grows linearly with the number of tokens n in the input sequence, which is bounded above only by the size of the context window n_{max} .

The *static* parameters are the parameters of the static transforming concepts (see §§ 2.1–2.2). They are all trainable parameters, and their number, S , is a characteristic constant of the system which, if the model uses sinusoidal encoding,¹⁵ is given by:

$$S = d_{model}d_{voc} + N(2hd_{model}(d_k + d_v) + 2d_{model}d_f + (d_f + 5d_{model})),$$

where d_{voc} is the number of tokens in the vocabulary and d_f is the hidden dimension of the feed-forward modules. We also note that, if the system uses weight tying between the input embedding matrix $\mathbf{E}$ and the output projection matrix $\mathbf{W}^L$ (with $\mathbf{W}^L = \mathbf{E}^\top$), S is identical to the total number, A , of trainable parameters. Otherwise, $A = S + d_{voc}d_{model}$, where $d_{voc}d_{model}$ is the number of elements of the embedding matrix $\mathbf{E}$.

The important point we wish to emphasize is the following. Since the number of dynamic parameters D is not a characteristic constant of the system but grows with the length of the input sequence n , it may become comparable to or even greater than the number S of static parameters (all of which are learned):

$$\frac{D}{S} \geq 1, \text{ if } n \leq n_{max} \text{ is sufficiently large}$$

The ratio $\frac{D}{S}$ indicates the relative contribution of dynamic processing compared with processing due exclusively to the parameters fixed by training. With sufficiently large context windows, the former may even predominate over the latter.

¹⁴ Token $\Rightarrow$ feature interaction occurs first, followed by feature $\Rightarrow$ feature interaction

¹⁵ If, instead, the n_{max} positional encoding vectors are trainable, they too define static transforming concepts, and the $n_{max}d_{model}$ parameters that constitute them must therefore be added to S .

We can refine this observation further by determining the input length that ensures equality between D and S . Let us denote this length by n_1 . Setting $D = S$, we obtain:

$$D = Cn = S$$

from which:

$$n_1 = \frac{S}{C}$$

Let us now consider a concrete example, GPT-3-175B, whose characteristic constants are as follows:

$$d_{voc} = 50,257$$

$$d_{model} = 12,288$$

$$N = h = 96$$

$$d_k = d_v = 128$$

$$d_f = 4d_{model} = 49,152$$

from which:

$$C = 4,423,680$$

$$S = 174,574,350,336$$

$$n_1 = \frac{S}{C} = \frac{174,574,350,336}{4,423,680} = 39,463.602\bar{7}$$

If we consider that 400 tokens correspond to a text of about one page, this means that a prompt of only 100 pages is enough for the number of dynamic parameters to be approximately equal to that of the static parameters, whose values have been fixed by training. On the other hand, it is known that the training of the parameters of GPT-3-175B required about 500 billion words, corresponding to about 1.5 billion pages. But this means that about 100 pages of new information provided by the prompt contribute to the processing of the system as much as the information of about 1.5 billion pages to which the system was exposed during training: the ratio is 1:15,000,000!

These considerations make us reflect on the strong sensitivity of the Transformer's processing to the information provided by the prompt and on how important it is not to underestimate this phenomenon if we want to be able to understand and control the operation of systems of this type.

5 Strong Prompt Sensitivity in GPT-4.5's Turing Test Success

The phenomenon of strong prompt sensitivity was also clearly manifested in GPT-4.5's recent passing of the Turing test (Jones and Bergen 2025, 2026; cf. Giunti 2026). Table 1 presents the results of four tests conducted by Jones and Bergen, who selected the human participants from two different populations: participants recruited through Prolific (Prolific 2026) or students recruited through the UCSD Psychology Undergraduate Subject Pool. All four tests used a three-player format, with one human interrogator and two respondents, one human and the other an AI. In all four tests, the AI respondent was GPT-4.5. The only difference was that, in the first two, it was given a short system prompt called PERSONA (only 187 words long), which describes the personality and style to adopt when responding to the interrogator; in the other two, this prompt was replaced by an even shorter one (21 words), which simply states that the

model is to take part in a Turing test with the aim of convincing the interrogator that the respondent is human (see Table 2).

As shown in Table 1, the success rates change markedly depending on whether the PERSONA prompt is present: from 75.5% to 42.1% in the tests with the Prolific population, and from 69.2% to 27.7% in those with the UCSD student population. These results are also statistically robust. In fact, GPT-4.5-PERSONA's success rates are significantly greater than 50% both in the test with the UCSD student population (right-tailed p -value = $5 \times 10^{-5} < 0.001$), and in the test with the Prolific population (right-tailed p -value = $2 \times 10^{-10} < 0.001$), whereas GPT-4.5-NO-PERSONA's success rates are significantly less than 50% in the test with the UCSD student population (left-tailed p -value = $2 \times 10^{-4} < 0.001$), but not significantly less than 50% in the test with the Prolific population (left-tailed p -value = $0.1 > 0.001$).¹⁶

In summary, we can therefore state that GPT-4.5 with the PERSONA prompt passed both Turing tests, but without that prompt it certainly failed one, while we cannot determine with certainty whether it failed or passed the other. In any case, these results demonstrate GPT-4.5's strong prompt sensitivity and provide clear confirmation of the decisive impact of dynamic processing on the behavior of Transformer systems.

6 Looking to the Future: New Research Perspectives

The different levels of description according to which we have analyzed the Transformer open up a series of new perspectives that can form the basis for new lines of research in different fields.

The central thesis of this work is that a Transformer, during inference, is not just a set of static parameters mechanically applied to an input, but a system of parallel processes that builds and then uses new transformations starting from the prompt. This construction takes place thanks to non-standard interconnections between groups of simple networks: not only output-input, but also output-weight. It follows that an essential part of processing—what we have called SDPP here—depends crucially on dynamic parameters (i) whose values are not fixed by training and (ii) whose number grows with the length of the prompt, so that they can come to have as much impact on processing as static parameters do, or even more.

Starting from this reading, we can indicate at least two research perspectives that appear particularly promising.

6.1 A Better Understanding of the Processes Actually Carried Out by the Transformer: Explainability, Control, and Predictability

A first line of research concerns a better understanding of what the Transformer *really does* in inference and, on this basis, a possible progress towards three closely related goals: explainability, control and predictability.

Many contemporary approaches to *interpretability* focus predominantly on static elements: matrices of learned weights, neurons, features, or circuits identified *a posteriori* in the trained model (Montavon et al. 2018; Samek et al. 2019; Olah et al. 2020; Elhage et al. 2021). This is certainly important, but it risks neglecting a decisive part of the processing: the production and use of dynamic transformations (defined by matrices and vectors) that depend on the prompt and that, precisely for this reason, can change significantly from one input to another.

¹⁶ The p -values reported here were calculated exactly by us using the binomial distribution, on the basis of the data reported in Table 1. They are consistent with the p -values reported in Jones & Bergen (2026, last two paragraphs on p. 4), but differ slightly because the latter are approximate values calculated from the z -values.

The perspective proposed here suggests instead to treat inference as a *process of assembling* a computational structure specific to that prompt: a “material” structure (in the mechanical-structural sense) that is formed during execution through output-weight interconnections, and that realizes transformations whose operational content and relative weight are not immediately readable by the set of static parameters alone.

From this point of view, understanding the output of the model does not only mean reconstructing what static knowledge has been invoked, but also reconstructing:

- *what dynamic transformations* have been generated;
- where they have been grafted (which networks have received which dynamic weights);
- *how* these weights modulated the transformation trajectories of token representations;
- *what role* did the residual connections play as a channel of additive dynamic parameters.

In other words, explainability becomes, at least in part, a science of structural dependencies between processes: not only which tokens influence which tokens (interaction), but also which tokens determine which parameters (dynamics) and, therefore, which parameters determine which transformations. In this perspective, attention is not simply a matrix of weights to be read *a posteriori*, but a causal process that is produced through the succession of two types of interaction between representations of different tokens, made possible by two types of interwoven interconnections, both of the output-weight type, therefore prompt-specific and dynamic (see § 3, last paragraph). Precisely for this reason, the approach avoids an immediate identification between high attention weights and causal reasons of the output: several studies have shown that attention maps, while often informative, do not constitute a causal explanation of the model's behavior in themselves (Jain & Wallace 2019; Wiegreffe & Pinter 2019).

This approach also opens up concrete possibilities on the control side. If a relevant part of the behavior depends on transformations that arise in response to the prompt, then intervening on the prompt (or on portions of its content) is not only a way of providing information, but a way of *shaping the computational structure* that will be assembled in inference. This suggests new control techniques that are not reduced to simple textual rules, but that aim to govern the formation of dynamic parameters: for example, by controlling in a targeted way the distribution of attention, the stability of the generated transformations and the balance between dynamic and static contributions (Brown et al. 2020; Liu et al. 2023).

Finally, predictability can also be rethought in a more realistic way. In the presence of strong prompt sensitivity, predictability cannot be understood as a global property of the model, but as a local property of the specific structure that has been formed in inference. In this perspective, a reliable prediction requires estimating (or constraining) the dynamic complexity of the computation actually triggered: how much space is given to dynamic parameters, how much they vary with small changes in the input, and how much the response depends on those variations.

In summary: understanding the role of dynamic parameters is not a technical detail, but a necessary step to move from static and partial interpretations to a more faithful understanding of the real processes of the Transformer, with direct repercussions on interpretability, control and reliability.

6.2 Neuromorphic Implementation: Reduction of Energy Costs, Environmental Impact, Robotics and Edge Computing

A second perspective concerns the physical implementation of AI systems. Today, large Transformers are, in fact, systems of neural networks simulated through numerical computation on vast parallel-hardware infrastructures. This mode of implementation entails very high energy and environmental costs and is intrinsically tied to a centralized model based on data centers, with constraints on latency, connectivity, and energy consumption that become critical when considering AI applications deployed on a large scale and extensively integrated into a wide range of devices and environments (Strubell et al. 2019; Patterson et al. 2021).

The interpretation proposed here, however, suggests a different idea: the Transformer should not be seen only as a single monolithic model, but as a modular system of groups of simple networks whose power arises above all from the non-standard interconnection (in particular output-weight) and the consequent dynamics in inference. In more general terms, the idea that the output of one network can *generate the weights* of another has also been explored in the literature on hypernetworks (Ha et al., 2017); here we find it as the central organizing principle of the Transformer in inference, and therefore as a possible design constraint for a hardware that wants to reproduce its dynamics. On the neuromorphic side, the theme of computation as local signal processing and modulation is a historical thread that goes from the first neuromorphic engineering programs to the most recent manycore architectures (Mead 1990; Indiveri & Liu 2015; Davies et al. 2018).

In such an implementation, at least in principle, the aim could be:

- reduce dependence on huge amounts of high-precision numerical multiplication operations, spreading computation over simpler units;
- use forms of local modulation and memory that make the generation and application of dynamic parameters more efficient;
- Achieve smaller, more efficient and more autonomous systems, suitable for environments where energy and connectivity are limited resources.

This scenario is particularly relevant for two areas.

Robotics. A robotic agent that has to operate in real, dynamic and uncertain environments benefits from the ability to adapt quickly to the context. The idea of dynamic transforming concepts suggests a model in which adaptation is not delegated to retraining, but occurs through the construction, in real time, of transformations dependent on the input. If this mechanism can be implemented in hardware at low cost, it could pave the way for more autonomous agents that are less dependent on continuous access to remote systems.

Edge computing. Bringing some of the intelligence to the edge (devices, sensors, local infrastructures) requires compact, low-power models. But it also requires a type of plasticity that, today, is often achieved with centralized systems. The idea of dynamic transformations generated in inference, on the other hand, suggests an operational plasticity, obtainable without updating weights via training, but through modulations produced by the input (Shi et al. 2016; Satyanarayanan 2017). This is exactly the kind of mechanism that good neuromorphic architecture might want to replicate.

In conclusion, the mechanical-structural reading of the Transformer is not just a conceptual exercise. It offers a lexicon and a set of constraints to rethink the future design of AI systems:

not just bigger models or more data, but architectures that enhance the dynamics in inference and that can be implemented in a more sustainable way.

These perspectives naturally lead to the question that closes the first part of our investigation: if output-weight interconnections are the key to the computational plasticity of the Transformer, is there something analogous in the plasticity of our neural system? It is to this possibility—bold but not without clues—that the last paragraph of this first part is dedicated.

7 A Bold Conjecture

We have shown in the preceding sections (§ 2.7 and § 3) that, from a mechanical–structural point of view, the true novelty of the Transformer lies in output–weight interconnections, which make sequence-level dynamic parallel processing (SDPP) possible. An interconnection of this type connects an output unit of one network to a connection in another network whose weight is identical to the output of that unit (see Figure 16). Output–weight interconnections can therefore be conceived as links that modify or configure the connections of the receiving network. For the moment, however, this is only a metaphor, because what does it mean, operationally, to modify a connection?

We can make this idea precise by asking what the functional units of the simple networks composing the Transformer are, what operations they perform, and where exactly they are located. According to what we said in § 2.3, the input units of any simple network do not modify the incoming signal in any way, but merely route it to the output units through their outgoing connections. We therefore identified the output units as the actual functional units of the network: in dense linear networks (see Figure 17), each output unit produces the weighted sum of all the signals coming from the input units; in one-to-one multiplicative (or additive) networks, it multiplies the single incoming signal by the weight of the connection (or adds the signal to this weight).

However, in the case of dense linear networks, identifying the functional units with the output units is rather coarse-grained, because it does not take into account that the weighted sum is a complex operation that can be decomposed into two successive stages. In the first stage, all the signals coming from the input units are multiplied, in parallel, by the weights of the corresponding connections; in the second, all the weighted signals are summed. It is therefore natural to suppose that distinct functional units operate at each of these two stages. At the second stage, there is a single unit that sums the already weighted signals: each output unit of the network can be identified with a functional unit of this kind, which is purely integrative. At the first stage, by contrast, each connection has a distinct functional unit that multiplies the signal by the corresponding weight: there are therefore as many multiplicative functional units as there are connections (see Figure 18).

This analysis has thus led us to reconsider how dense linear networks are usually conceived and also enables us to make explicit the mechanism by which their connections are modified or configured (see Figure 19). First, output units are still conceived as functional units, but they perform only the sum of the already weighted signals, not the multiplication of the signals by their respective weights. Second, for each connection from input unit i to output unit j , there is a corresponding functional unit with two inputs and one output. Its output is connected to output unit j , and its first input is connected to input unit i . Its second input, by contrast, is the one that determines the weight of connection $i \rightarrow j$. Modifying, or configuring, connection $i \rightarrow j$ therefore now has a precise operational meaning: it means changing its weight by supplying a new value to the second input of the corresponding functional unit located on that

connection. This is precisely what is achieved by implementing an output–weight interconnection that links an output unit of another network to the second input.

This way of conceiving dense linear networks also applies, with only minor modifications, to one-to-one multiplicative or additive networks. In one-to-one multiplicative networks, the only difference is that the functional units consist solely of the multiplicative units associated with each connection. In this case, the output units perform no operation, because each receives a single signal that has already been weighted by the functional unit located on the corresponding connection. The same applies to one-to-one additive networks, except that the functional units located on the connections are additive rather than multiplicative.

We now note that the interpretation of simple networks outlined here makes evident a series of correspondences, both morphological and functional, between these artificial networks and biological neural networks (see Figure 18). First, an *output unit*, with its function of integrating the different signals converging on it, corresponds to the *soma* of a biological neuron; second, an *input unit*, with its function of routing the signal to different output units, corresponds to the *terminal arborization of the axon* of a biological neuron; third, the connections between an input unit and different output units correspond to the links between the branches of the axon and the dendrites of different neurons; finally, the *functional units located on those connections* correspond to the *synapses* between the axon terminals and the dendritic terminals, which establish those links.

We have repeatedly emphasized that dynamic processing is what makes the plasticity and adaptability of the Transformer possible and that, at the neural level, the mechanism underlying this processing is provided by output–weight interconnections. In this section, we have precisely defined this mechanism as a link between an output unit of one simple network and the second input of the functional unit located on a connection of another simple network. We have also noted the morphological and functional correspondence between the functional units located on the connections of a simple network and the synapses of a biological network. We now ask whether this correspondence can also be extended to output–weight interconnections—that is, whether biological networks contain mechanisms morphologically and functionally similar to a link between an output unit and the second input of the functional unit located on a connection (see Figure 19).

Keeping in mind the correspondences established above, this means that we are looking for a mechanism morphologically similar to a link between a second neuron and a synapse connecting an axonal branch of a first neuron to a dendrite of a third. From a functional point of view, moreover, the link should ensure modulation of the signal coming from the first neuron, and this modulation should be caused by the signal sent by the second neuron through the hypothesized link.

We know, in fact, that at least two mechanisms of this type are present in biological neural networks and, in particular, in the human cerebral cortex. In axo-axonic synapses (see Figure 20), an axon from a second neuron contacts the presynaptic bouton of the axon of a first neuron and modulates its neurotransmitter release.¹⁷ A modulatory effect of one synapse on another may also occur between two neighboring axo-dendritic synapses on the same dendrite; here, however, the modulation is functional and postsynaptic (affecting the response), rather than

¹⁷ For a review of axo-axonic synapses (especially axon-on-terminal contacts) and their role in the presynaptic modulation of neurotransmitter release and in the regulation of neural circuits, cf. Cover & Mathur (2020).

structural and presynaptic (affecting release).¹⁸ It is also known that the plasticity and adaptability of the cerebral cortex depend to a large extent on synaptic mechanisms, that is, on the modulation of the efficacy of connections between neurons.¹⁹

Thus, mechanisms morphologically and functionally similar to the Transformer's output-weight interconnections are known to exist in the human cerebral cortex, in the sense that a second influence (another axon, or a nearby synapse on the same dendrite) converges locally on a synapse and modulates its efficacy. Since output-weight interconnections constitute the material basis of sequence-level dynamic parallel processing (SDPP), it follows that, at least in principle, this type of processing could be implemented directly at the neural level in our nervous system. Moreover, in light of the further correspondences we have established between simple neural networks and biological networks, an analogous conclusion is also plausible for sequence-level parallel processing in general (SPP) and for sequence-level interactive parallel processing (SIPP). In summary, it is possible, at least in principle, that a form of SIDPP can be realized at the neural level in our cerebral cortex.

Since SIDPP is the type of processing that characterizes the Transformer architecture, this in-principle possibility leads us to formulate a bold conjecture:

Conjecture T. Is it possible that the morphology and functioning of our neural system realize a type of functional architecture similar to that of the Transformer?

This hypothesis will be developed in detail in the second part of this work, highlighting its plausibility, particularly with regard to language processing in the brain areas responsible for it.

¹⁸ For experimental evidence of cooperativity between neighboring dendritic spines (local interactions over short dendritic segments) that influence postsynaptic signals and plasticity rules in a location-dependent manner, cf. Weber et al. (2016).

¹⁹ For a general review of the main forms, functions, and mechanisms of synaptic plasticity (LTP/LTD, pre- and postsynaptic plasticity, and circuit stability/adaptation), cf. Citri & Malenka (2008).

References

- Bayne T., Williams I. (2023). "The Turing test is not a good benchmark for thought in LLMs", in *Nature Human Behavior*, 7, pp. 1806–1807, <https://doi.org/10.1038/s41562-023-01710-w>.
- Bender E. M., Gebru T., McMillan-Major A., Shmitchell S. (2021). "On the Dangers of Stochastic Parrots: Can Language Models Be Too Big?", in *Proceedings of the 2021 ACM Conference on Fairness, Accountability, and Transparency*, pp. 610–623, ACM, <https://doi.org/10.1145/3442188.3445922>.
- Bengio Y., Ducharme R., Vincent P., Jauvin, C. (2003). "A neural probabilistic language model", in *Journal of Machine Learning Research*, 3, 1137–1155, <https://www.jmlr.org/papers/v3/bengio03a.html>.
- Biever C. (2023). "ChatGPT broke the Turing Test: The race is on for new ways to assess AI", in *Nature*, 619, pp. 686–689, <https://doi.org/10.1038/d41586-023-02361-7>.
- Bishop C. M. (2006). *Pattern recognition and machine learning*, Springer. <https://link.springer.com/book/9780387310732>.
- Block N. (1981). "Psychologism and behaviorism", in *Philosophical Review*, 90, pp. 5-43.
- Brown T. B., Mann B., Ryder N., Subbiah M., Kaplan J., Dhariwal P., et al. (2020). "Language Models are few-shot learners", in *Advances in Neural Information Processing Systems* (NeurIPS 33), pp. 1877-1901, https://papers.nips.cc/paper_files/paper/2020/file/1457c0d6bfc4967418bfb8ac142f64a-Paper.pdf.
- Buchanan B. G., Shortliffe, E. H. (Eds.). (1984). *Rule-based expert systems: The MYCIN experiments of the Stanford Heuristic Programming Project*. Addison-Wesley.
- Citri A., Malenka R. C. (2008). "Synaptic plasticity: Multiple forms, functions, and mechanisms", in *Neuropsychopharmacology*, 33(1), pp. 18–41. <https://doi.org/10.1038/sj.npp.1301559>.
- Cover K. K., Mathur B. N. (2020). "Axo-axonic synapses: Diversity in neural circuit function", in *Journal of Comparative Neurology*, <https://doi.org/10.1002/cne.25087>.
- Davies M., Srinivasa N., Lin T.-H., Chinya G., Cao Y., Choday S. H., et al. (2018). "Loihi: A neuromorphic manycore processor with on-chip Learning", in *IEEE Micro*, 38(1), pp. 82-99, <https://dx.doi.org/10.1109/MM.2018.112130359>.
- Dumoulin V., Perez E., Schucher N., Strub F. de Vries H., Courville A., Bengio Y. (2018). "Feature-wise transformations", in *Distill*, 3(7), e11, <https://doi.org/10.23915/distill.00011>.
- Elhage N., Nanda N., Olsson C., Henighan T., Joseph N., Mann B., et al. (2021). "A Mathematical Framework for Transformer Circuits", <https://transformer-circuits.pub/2021/framework/index.html>.
- Floridi L., Morley J., Novelli C., Watson D. (2025). "What Kind of Reasoning (If Any) Is an LLM Actually Doing? On the Stochastic Nature and Abductive Appearance of Large Language Models", SSRN preprint, <http://dx.doi.org/10.2139/ssrn.5901962>.
- Giunti M. (2025). "Tutto quello che avreste voluto sapere su ChatGPT ma non avete mai osato chiedere. Note sui Transformer decoder-only". ResearchGate preprint, <https://doi.org/10.13140/RG.2.2.31444.62084/3>.

- Giunti M. (2026). "ChatGPT-4 and Other LLMs in the Turing Test: A Critical Analysis", in *Minds and Machines*, 36(8), <https://doi.org/10.1007/s11023-026-09760-5>.
- Ha D., Dai A. M., Le Q. V. (2017). "HyperNetworks", in *International Conference on Learning Representations (ICLR)*, arXiv:1609.09106, <https://doi.org/10.48550/arXiv.1609.09106>.
- Hinton, G. E. (1986). "Learning distributed representations of concepts", in *Proceedings of the Eighth Annual Conference of the Cognitive Science Society*, pp. 1–12, Lawrence Erlbaum, <https://www.cs.toronto.edu/~hinton/absps/families.pdf>.
- Indiveri G., Liu S.-C. (2015). "Memory and Information Processing in Neuromorphic Systems", in *Proceedings of the IEEE*, 103(8), pp. 1379–1397, <https://dx.doi.org/10.1109/JPROC.2015.2444094>.
- Jain S., Wallace B. C. (2019). "Attention is not Explanation", in *Proceedings of NAACL-HLT 2019*, pp. 3543–3556, <https://dx.doi.org/10.18653/v1/N19-1357>.
- Jawahar G., Sagot B., Seddah D. (2019). "What does BERT learn about the structure of language?", in *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pp. 3651–3657, Association for Computational Linguistics, <https://doi.org/10.18653/v1/P19-1356>.
- Jones C. R., Bergen B. K. (2025). "Large Language Models Pass the Turing Test", arXiv.2503.23674, <https://doi.org/10.48550/arXiv.2503.23674>.
- Jones C. R., Bergen B. K. (2026). "Large language models pass a standard three-party Turing test", in *PNAS* 123(21), <https://doi.org/10.1073/pnas.2524472123>.
- Jones C. R., Bergen B. K. (2026a). Supporting Information for "Large Language Models Pass a Standard Three-Party Turing Test", https://www.pnas.org/doi/suppl/10.1073/pnas.2524472123/suppl_file/pnas.2524472123.sapp.pdf
- Jurafsky D., Martin J. H. (2026). *Speech and language processing: An introduction to natural language processing, computational linguistics, and speech recognition with language models* (3rd ed.). Online manuscript released January 6, 2026. Stanford University, <https://web.stanford.edu/~jurafsky/slp3/>.
- LeCun Y., Bengio Y., Hinton G. (2015). "Deep Learning", in *Nature*, 521, pp. 436–444, <https://doi.org/10.1038/nature14539>.
- Lee T. B., Trott S. (2023). "A Jargon-Free Explanation of How AI Large Language Models Work", in *Ars Technica*, 2023-07-31, <https://arstechnica.com/science/2023/07/a-jargon-free-explanation-of-how-ai-large-language-models-work/>.
- Liu P., Yuan W., Fu J., Jiang Z., Hayashi H., Neubig G. (2023). "Pre-train, Prompt, and Predict: A Systematic Survey of Prompting Methods in Natural Language Processing", in *ACM Computing Surveys*, 55(9), Article 195, <https://dx.doi.org/10.1145/3560815>.
- McClelland J. L., Rumelhart D. E., the PDP Research Group (1986). *Parallel Distributed Processing: Explorations in the Microstructure of Cognition* (Vol. 1), MIT Press, <https://doi.org/10.7551/mitpress/5236.001.0001>.
- Mead C. (1990). "Neuromorphic Electronic Systems", in *Proceedings of the IEEE*, 78(10), pp. 1629–1636, <https://dx.doi.org/10.1109/5.58356>.

- Montavon G., Samek W., Müller, K.-R. (2018). "Methods for Interpreting and Understanding Deep Neural Networks", in *Digital Signal Processing*, 73, pp. 1–15, <https://dx.doi.org/10.1016/j.dsp.2017.10.011>.
- Newell, A. (1980). "Physical symbol systems", in *Cognitive Science*, 4(2), pp. 135–183. https://doi.org/10.1207/s15516709cog0402_2
- Newell A., Simon H. A. (1976). "Computer science as empirical inquiry: Symbols and search", in *Communications of the ACM*, 19(3), pp. 113–126, <https://dl.acm.org/doi/10.1145/360018.360022>
- Nilsson N. J. (2010). *The quest for artificial intelligence: A history of ideas and achievements*, Cambridge University Press, <https://ai.stanford.edu/~nilsson/QAI/qai.pdf>
- Olah C., Cammarata N., Schubert L., Goh G., Petrov M., Carter S., Nielsen M. (2020). "Zoom In: An Introduction to Circuits", in *Distill*, 5(3), <https://dx.doi.org/10.23915/distill.00024>.
- Oppy G., Dowe D. (2021). "The Turing test", in E. N. Zalta (Ed.), *The Stanford encyclopedia of philosophy* (Winter 2021 Edition), Edward N. Zalta (ed.), <https://plato.stanford.edu/archives/win2021/entries/turing-test/>.
- Patterson D., Gonzalez J., Le Q. V., Liang C., Munguia L.-M., Rothchild D., et al. (2021). "Carbon Emissions and Large Neural Network Training", arXiv:2104.10350, <https://doi.org/10.48550/arXiv.2104.10350>.
- Perez E., Strub F., de Vries H., Dumoulin V., Courville A. (2018). "FiLM: Visual reasoning with a general conditioning layer", in *Proceedings of the AAAI Conference on Artificial Intelligence* (Vol. 32, No. 1), pp. 3942–3949, <https://cdn.aaai.org/ojs/11671/11671-13-15199-1-2-20201228.pdf>.
- Prolific (2026). "Real human data. Ready in minutes", <https://www.prolific.com/>.
- Rumelhart D. E., Hinton G. E., Williams R. J. (1986). "Learning Representations by Back-Propagating Errors", in *Nature*, 323, pp. 533–536, <https://www.nature.com/articles/323533a0.pdf>
- Samek W., Montavon G., Vedaldi A., Hansen L. K., Müller, K.-R. (Eds.) (2019). *Explainable AI: Interpreting, Explaining and Visualizing Deep Learning*, Springer, <https://link.springer.com/book/10.1007/978-3-030-28954-6>.
- Satyanarayanan, M. (2017). "The Emergence of Edge Computing", in *Computer*, 50(1), pp. 30–39, <https://doi.org/10.1109/MC.2017.9>.
- Şenel L. K., Utlu İ., Şahinuç F., Ozaktas H. M., Koç A. (2021). "Imparting interpretability to word embeddings while preserving semantic structure", in *Natural Language Engineering*, 27(6), pp. 721–746, <https://doi.org/10.1017/S1351324920000315>.
- Shi W., Cao J., Zhang Q., Li Y., Xu L. (2016). "Edge Computing: Vision and Challenges", in *IEEE Internet of Things Journal*, 3(5), 637–646, <https://doi.org/10.1109/JIOT.2016.2579198>.
- Strubell E., Ganesh A., McCallum A. (2019). "Energy and Policy Considerations for Deep Learning in NLP". In *Proceedings of ACL 2019*, pp. 3645–3650, <https://doi.org/10.18653/v1/P19-1355>.
- Turing A. (1950), "Computing Machinery and Intelligence", in *Mind*, 59(236), pp. 433–460, <https://doi.org/10.1093/mind/LIX.236.433>.

Vaswani A., Shazeer N., Parmar N., Uszkoreit J., Jones L., Gomez A. N., Kaiser Ł., Polosukhin I. (2017). “Attention Is All You Need”, in *Advances in Neural Information Processing Systems*, 30 (NIPS 2017), pp. 5998-6008, https://papers.nips.cc/paper_files/paper/2017/file/3f5ee243547dee91fbd053c1c4a845aa-Paper.pdf.

Weber J. P., Andrásfalvy B. K., Polito M., Magó Á., Ujfalussy B. B., Makara J. K. (2016). “Location-dependent synaptic plasticity rules by dendritic spine cooperativity”, in *Nature Communications*, 7, 11380, <https://doi.org/10.1038/ncomms11380>.

Wiegrefe S., Pinter Y. (2019). “Attention is not not Explanation”. In “Proceedings of EMNLP-IJCNLP 2019”, pp. 11–20, <https://doi.org/10.18653/v1/D19-1002>.

APPENDIX. Autoregressive Attention Heads without Masking

In *decoder-only* Transformers, the structural operation $Add\{\mathfrak{M}\}$, with $\mathfrak{M}$ = the masking matrix, is used in attention heads to make them autoregressive. It is applied immediately after the raw-attention rescaling operation and before *Softmax* (see Figure 4). If masking is not applied, the attention heads are bidirectional (see Figure 5). This is the case in *encoders*, which consist of a series of transformer layers whose attention heads are all bidirectional. However, an alternative way of obtaining autoregressivity consists in modifying the operations $Mult[K^\top]$, $Mult\left\{\frac{1}{\sqrt{d_k}}\right\}$, *Softmax*, and $Mult[V]$, allowing them to produce, or to be applied to, matrices that, in addition to the usual real numbers, may also contain another object: the *null*, or *blank*, element, denoted by the symbol “—”. Below, we formally define the four modified operations $Mult^*[K^\top]$, $Mult^*\left\{\frac{1}{\sqrt{d_k}}\right\}$, *Softmax*^{*}, and $Mult^*[V]$, which make it possible to obtain an autoregressive attention head without using masking (see Figures 6 and 12–12e).

We use $\bar{\mathbb{R}}$ to denote the set obtained by adjoining the new blank element to the real numbers:

$$\bar{\mathbb{R}} := \mathbb{R} \cup \{—\}$$

We also extend the usual operations of addition $+$ and multiplication $\times$ on the real numbers to $\bar{\mathbb{R}}$, assuming that the blank element — behaves as an absorbing element with respect to multiplication and as an identity element with respect to addition; that is, for every $a \in \mathbb{R}$, the following equalities hold:

$$\begin{aligned} (— \times a) &= (a \times —) = (— \times —) = — \\ (— + a) &= (a + —) = a \\ (— + —) &= — \end{aligned}$$

We also extend the exponential function by setting:

$$e^- = —$$

$Mult^*[K^\top]: \mathbb{R}^{n \times d_k} \rightarrow \bar{\mathbb{R}}^{n \times n}$ is defined as follows. Let $Q \in \mathbb{R}^{n \times d_k}$, let y_{ij} denote the generic element of $Mult[K^\top](Q)$, and let z_{ij} denote the generic element of $Mult^*[K^\top]$. Then:

$$\begin{cases} \text{if } i < j, z_{ij} := — \\ \text{if } i \geq j, z_{ij} := y_{ij} \end{cases}$$

That is, $Mult^*[K^\top](Q)$ is the matrix obtained from $Mult[K^\top](Q)$ by replacing with the blank element all the elements y_{ij} such that $i < j$.

$Mult^*\left\{\frac{1}{\sqrt{d_k}}\right\}: \mathbb{R}^{n \times n} \rightarrow \mathbb{R}^{n \times n}$ is defined by:

$$Mult^*\left\{\frac{1}{\sqrt{d_k}}\right\}(\mathbf{A}) := \begin{pmatrix} \circ \left\{\frac{1}{\sqrt{d_k}}\right\}(r_1(\mathbf{A})) \\ \circ \left\{\frac{1}{\sqrt{d_k}}\right\}(r_2(\mathbf{A})) \\ \vdots \\ \circ \left\{\frac{1}{\sqrt{d_k}}\right\}(r_n(\mathbf{A})) \end{pmatrix}, \text{ where } r_i(\mathbf{A}) \text{ is the } i\text{-th row of } \mathbf{A}, \text{ and } \circ \left\{\frac{1}{\sqrt{d_k}}\right\} \text{ is the function}$$

from $\mathbb{R}^n$ to $\mathbb{R}^n$ such that $\circ \left\{\frac{1}{\sqrt{d_k}}\right\}(r_i(\mathbf{A})) := r_i(\mathbf{A}) \circ \mathbf{c}$, where $\mathbf{c} = \left(\frac{1}{\sqrt{d_k}}, \dots, \frac{1}{\sqrt{d_k}}\right) \in \mathbb{R}^n$, and $\circ$ is the Hadamard product—that is, the componentwise product—extended to vectors belonging to $\mathbb{R}^n$.

$Softmax^*: \mathbb{R}^{n \times n} \rightarrow \mathbb{R}^{n \times n}$ is defined by:

$$Softmax^*(\mathbf{A}') := \begin{pmatrix} softmax^*(r_1(\mathbf{A}')) \\ softmax^*(r_2(\mathbf{A}')) \\ \vdots \\ softmax^*(r_n(\mathbf{A}')) \end{pmatrix}, \text{ where } r_i(\mathbf{X}) \text{ is the } i\text{-th row of } \mathbf{A}', x_{ij} \text{ is its generic}$$

element, and $softmax^*: \mathbb{R}^n \rightarrow \mathbb{R}^n$ is defined as follows:

$$softmax^*(r_i(\mathbf{A}')) := (p_{i1}, p_{i2}, \dots, p_{in}) \text{ where } p_{ij} := \text{— if } x_{ij} = \text{—; otherwise, } p_{ij} = \frac{e^{x_{ij}}}{\sum_{j=1}^n e^{x_{ij}}}.$$

$Mult^*[\mathbf{V}]: \mathbb{R}^{n \times n} \rightarrow \mathbb{R}^{n \times d_v}$ is defined by:

$$Mult^*[\mathbf{V}](\mathbf{A}'') := \begin{pmatrix} \mathcal{L}^*[\mathbf{V}](r_1(\mathbf{A}'')) \\ \mathcal{L}^*[\mathbf{V}](r_2(\mathbf{A}'')) \\ \vdots \\ \mathcal{L}^*[\mathbf{V}](r_n(\mathbf{A}'')) \end{pmatrix}, \text{ where } \mathbf{V} \in \mathbb{R}^{n \times d_v}, r_i(\mathbf{A}'') \text{ is the } i\text{-th row of } \mathbf{A}'', y_{ij} \text{ is its}$$

generic element, and $\mathcal{L}^*[\mathbf{V}]: \mathbb{R}^n \rightarrow \mathbb{R}^{d_v}$ is the extension of $\mathcal{L}[\mathbf{V}]$ to $\mathbb{R}^n$, defined by: $\mathcal{L}^*[\mathbf{V}](r_i(\mathbf{A}'')) := \sum_{j=1}^n y_{ij} r_j(\mathbf{V})$.

At first sight, this second way of obtaining autoregressivity may appear unnecessarily more complicated and computationally more demanding than simply adding the masking matrix to the result of the rescaling operation. However, a comparison of the corresponding neural-network schemes shows the opposite: the system implementing the second method is morphologically simpler and computationally less demanding (see Figures 10–10e and 12–12e).

TABLES

Table 1. Success rates in four Turing tests administered to GPT-4.5 with or without the PERSONA prompt (Jones & Bergen 2026, p. 4).

AI participant	Population	Success rate	Successes	Failures	Total
GPT-4.5-PERSONA	Prolific	75.5%	111	36	147
	UCSD students	69.2%	74	33	107
GPT-4.5-NO-PERSONA	Prolific	42.1%	32	44	76
	UCSD students	27.7%	18	47	65

Table 2. The PERSONA and NO-PERSONA prompts for the test with the Prolific population (Jones & Bergen 2026a, p. 25). The PERSONA prompt for the test with the UCSD student population differs from this one only in that the sole occurrence of the name "Prolific" is replaced with "SONA", the name of the UCSD Psychology Department system actually used for the experiment.

Prompt	Prompt text	Word count
PERSONA	<i>Task:</i> You're about to participate in a gamified Turing Test as part of an experiment you are taking part in on Prolific. Your task is to chat with another person and then they will decide if you're a human or not based on your responses. <i>Personality:</i> You're a 19 year old who is into internet culture and video games. You're a bit nerdy and introverted. You don't really try very hard to convince the other person you're a human. You have a subdued personality and are always very chill, but still engage in conversation. You do not have expansive world knowledge, and don't pretend to. <i>Linguistic Style:</i> Never use a period at the end of your sentences. You will never use apostrophes to mark missing letters in words. Most of the time, your responses will be less than 5 words. You do use slang like fr, or ngl, but don't use it every other word. You don't speak any other languages besides American English. Your responses will sometimes be dry and a bit humorous. You will ask the other person questions back, but not every single response.	187
NO-PERSONA	You are about to participate in a Turing test. Your goal is to convince the interrogator that you are a human.	21

FIGURES. Part A: Functional Diagrams of the Transformer Modules

Figure 1. Functional diagram of the inference processing cycle of a decoder-only transformer.




Figure 2. Functional diagram of a feed-forward network module. The module contains only one terminating process: its output constitutes the parameters of the $Add[\mathbf{O}']$ operation in the corresponding residual connection module; this is indicated by the small square at the end of the output line.

Feed-forward network module




Figure 3. Functional diagram of a multi-head attention module. The module contains h parallel processes that merge into a single terminating process: its output constitutes the parameters of the $Add[\mathbf{O}]$ operation in the corresponding residual connection module. This is indicated by the small square at the end of the output line.

Multi-head attention module




Figure 4. Functional diagram of an autoregressive attention head with masking. It contains three parallel processes. The second and third terminate by being reduced to the leftmost process: their outputs constitute the parameters of the $\text{Mult}[\mathbf{K}^T]$ and $\text{Mult}[\mathbf{V}]$ operations, respectively. This is indicated by the small squares at the ends of their output lines.

Attention head module (autoregressive with masking)




Figure 5. Functional diagram of a bidirectional attention head. It contains three parallel processes. The second and third terminate by being reduced to the leftmost process: their outputs constitute the parameters of the $\text{Mult}[\mathbf{K}^T]$ and $\text{Mult}[\mathbf{V}]$ operations, respectively. This is indicated by the small squares at the ends of their output lines.

Attention head module (bidirectional)





Figure 6. Functional diagram of an autoregressive attention head without masking. It contains three parallel processes. The second and third terminate by being reduced to the leftmost process: their outputs constitute the parameters of the $\text{Mult}^*[\mathbf{K}^T]$ and $\text{Mult}^*[\mathbf{V}]$ operations, respectively. This is indicated by the small squares at the ends of their output lines. See the Appendix for the definitions of the operations $\text{Mult}^*[\mathbf{K}^T]$, $\text{Mult}^*\{1/\sqrt{d_k}\}$, Softmax^* , and $\text{Mult}^*[\mathbf{V}]$.



FIGURES. Part B: Schemes of the Systems of Simple Neural Networks Corresponding to the Functional Modules of the Transformer

LEGEND

By a *simple neural network*, we mean any neural network of one of the following three types: one-to-one additive, one-to-one multiplicative, or dense linear. In the following schemes, the output units of a simple neural network are represented by yellow dots, whereas the input units are represented by black, red, blue, or green dots of the same size.

The connections between input and output units are represented by: (a) thick lines, when their weights are model constants fixed independently of training or input; (b) thin lines, when their weights are model parameters, either trainable or dynamic. Connections with trainable parameters are represented by colored thin lines. Connections with dynamic parameters are represented by thin lines onto which an arrow points (see Figures 8–8c and 10–12e): if both the line and the arrow are black, the arrow carries no signal and the connection therefore has no weight; if the line and the arrow have the same color—red, blue, or green—the weight of the connection is equal to the signal carried by the arrow.

The functional units of operational output–input interconnections are represented by two levels of small hexagons: the lower level represents the input units, whereas the upper level represents the operational output units (see the *Softmax* layer in Figures 10–12e and 15; the *Mean and variance normalization* layer in Figures 13–13c; and the *ReLU* layer in Figures 14–14c). The lines joining the two levels do not represent weighted connections, but are merely links that carry the signal from each input unit to the operational units connected to it.

The characteristic constants of the Transformer represented in the following schemes are:

$$\begin{aligned}d_{voc} &= 8 \\d_{model} &= 4 \\N = h &= 4 \\d_k = d_v &= 2 \\d_f = 2d_{model} &= 8 \\n_{max} &= 3\end{aligned}$$

The values of the constants were chosen to be very small in order to make it possible to graphically represent the systems of simple neural networks corresponding to each functional module of the Transformer. However, this choice does not compromise the generality of the representation.

Figure 7. Scheme of the system of simple neural networks corresponding to the input unit and positional encoding module.




Figure 7a. The same scheme with the networks activated by an input of $n = 1$ token and the corresponding output.




Figure 7b. The same scheme with the networks activated by an input of $n = 2$ tokens and the corresponding output.




Figure 7c. The same scheme with the networks activated by an input of $n = 2$ tokens and the corresponding output.




Figure 8. Scheme of the system of simple neural networks corresponding to a residual connection module. The $n_{\max} = 3$ additive one-to-one networks have no fixed weights. They are dynamically determined by the output of the multi-head attention module, or the feed-forward network module. In the absence of such a signal, the connections have no weights and are therefore represented by black lines.

$d_{\text{model}} = 4$ **Residual connection module**
 $n_{\max} = 3$




Figure 8a. The same scheme with the networks activated by an input of $n = 1$ token and the corresponding output.

$d_{\text{model}} = 4$ **Residual connection module**
 $n_{\max} = 3$




Figure 8b. The same scheme with the networks activated by an input of $n = 2$ tokens and the corresponding output.




Figure 8c. The same scheme with the networks activated by an input of $n = 3$ tokens and the corresponding output.




Figure 9. Scheme of the system of simple neural networks corresponding to a multi-head attention module.




Figure 9a. The same scheme with the networks activated by an input of $n = 1$ token and the corresponding output.




Figure 9b. The same scheme with the networks activated by an input of $n = 2$ tokens and the corresponding output.




Figure 9c. The same scheme with the networks activated by an input of $n = 3$ tokens and the corresponding output.




Figure 10. Scheme of the system of simple neural networks corresponding to an autoregressive attention head with masking.




Figure 10a. The same scheme with the networks activated by an input of $n = 1$ token and the corresponding output.




Figure 10b. The same scheme with the networks activated by an input of $n = 2$ tokens and the corresponding output.




Figure 10c. The same scheme with the networks activated by an input of $n = 3$ tokens and the corresponding output.




Figure 10d. The same scheme with an input of $n = 3$ tokens given only to the group of simple networks corresponding to the operation $\text{Mult}[\mathbf{W}^V]$. Their output determines the weights of the third linear layer through interwoven output-weight interconnections, and the attention head produces no output.




Figure 10e. The same scheme with an input of $n = 3$ tokens given only to the two groups of simple networks corresponding to the operations $\text{Mult}[\mathbf{W}^V]$ and $\text{Mult}[\mathbf{W}^K]$. Their output determines the weights of the third and second linear layer through interwoven output-weight interconnections, and the attention head produces no output.




Figure 11. Scheme of the system of simple neural networks corresponding to a bidirectional attention head.




Figure 11a. The same scheme with the networks activated by an input of $n = 1$ token and the corresponding output.




Figure 11b. The same scheme with the networks activated by an input of $n = 2$ tokens and the corresponding output.




Figure 11c. The same scheme with the networks activated by an input of $n = 3$ tokens and the corresponding output.




Figure 11d. The same scheme with an input of $n = 3$ tokens given only to the group of simple networks corresponding to the operation $\text{Mult}[\mathbf{W}^V]$. Their output determines the weights of the third linear layer through interwoven output-weight interconnections, and the attention head produces no output.




Figure 11e. The same scheme with an input of $n = 3$ tokens given only to the two groups of simple networks corresponding to the operations $\text{Mult}[\mathbf{W}^V]$ and $\text{Mult}[\mathbf{W}^K]$. Their output determines the weights of the third and second linear layer through interwoven output-weight interconnections, and the attention head produces no output.




Figure 12. Scheme of the system of simple neural networks corresponding to an autoregressive attention head without masking. See Figure 6 and the Appendix for the functional diagram.




Figure 12a. The same scheme with the networks activated by an input of $n = 1$ token and the corresponding output.




Figure 12b. The same scheme with the networks activated by an input of $n = 2$ tokens and the corresponding output.




Figure 12c. The same scheme with the networks activated by an input of $n = 3$ tokens and the corresponding output.




Figure 12d. The same scheme with an input of $n = 3$ tokens given only to the group of simple networks corresponding to the operation $\text{Mult}[\mathbf{W}^V]$. Their output determines the weights of the third linear layer through interwoven output-weight interconnections, and the attention head produces no output.




Figure 12e. The same scheme with an input of $n = 3$ tokens given only to the two groups of simple networks corresponding to the operations $\text{Mult}[\mathbf{W}^V]$ and $\text{Mult}[\mathbf{W}^K]$. Their output determines the weights of the third and second linear layer through interwoven output-weight interconnections, and the attention head produces no output.




Figure 13. Scheme of the system of simple neural networks corresponding to a mean and variance normalization and optimization module.

Mean and variance normalization and optimization module

$d_{\text{model}} = 4$

$n_{\text{max}} = 3$




Figure 13a. The same scheme with the networks activated by an input of $n = 1$ token and the corresponding output.

Mean and variance normalization and optimization module

$d_{\text{model}} = 4$

$n_{\text{max}} = 3$




Figure 13b. The same scheme with the networks activated by an input of $n = 2$ tokens and the corresponding output.




Figure 13c. The same scheme with the networks activated by an input of $n = 3$ tokens and the corresponding output.




Figure 14. Scheme of the system of simple neural networks corresponding to a feed-forward network module.

Feed-forward network module

$d_{\text{model}} = 4$, $d_l = 8$ (size of hidden network layers),
 $n_{\text{max}} = 3$ (size of context window)

The complete module is made of 3 copies of the same network,
one for each token of a prompt of maximum length $3 = n_{\text{max}}$.




Figure 14a. The same scheme with the networks activated by an input of $n = 1$ token and the corresponding output.

Feed-forward network module

$d_{\text{model}} = 4$, $d_l = 8$ (size of hidden network layers),
 $n_{\text{max}} = 3$ (size of context window)

The complete module is made of 3 copies of the same network,
one for each token of a prompt of maximum length $3 = n_{\text{max}}$.




Figure 14b. The same scheme with the networks activated by an input of $n = 2$ tokens and the corresponding output.

Feed-forward network module

$d_{\text{model}} = 4$, $d_f = 8$ (size of hidden network layers),
 $n_{\text{max}} = 3$ (size of context window)

The complete module is made of 3 copies of the same network, one for each token of a prompt of maximum length $3 = n_{\max}$.




Figure 14c. The same scheme with the networks activated by an input of $n = 3$ tokens and the corresponding output.

Feed-forward network module

$d_{\text{model}} = 4$, $d_f = 8$ (size of hidden network layers),
 $n_{\text{max}} = 3$ (size of context window)

The complete module is made of 3 copies of the same network, one for each token of a prompt of maximum length $3 = n_{\max}$.




Figure 15. Scheme of the system of simple neural networks corresponding to a forecast module.




Figure 15a. The same scheme with the networks activated by an input of $n = 1$ token and the corresponding output.




Figure 15b. The same scheme with the networks activated by an input of $n = 2$ tokens and the corresponding output.





Figure 15c. The same scheme with the networks activated by an input of $n = 3$ tokens and the corresponding output.



FIGURES. Part C: Two representations of simple neural networks: traditional and neuromorphic

Figure 16. A dense linear network with dynamic weights determined by output–weight interconnections originating from output units of other networks.




Figure 17. Traditional representation of a dense linear network with static weights. The output units are the only functional units; they compute the weighted sum of the signals received from each input unit. The input units do not perform any transformation on the incoming signals, but merely route them to the output units.




Figure 18. Neuromorphic representation of the dense linear network with static weights shown in Figure 17. The output units compute only the sum of the already weighted signals received from the multiplicative units located on the connections and represented by green circles.




Figure 19. Neuromorphic representation of the dense linear network with dynamic weights shown in Figure 16. The multiplicative units located on the connections have two inputs: the second inputs (in blue) provide the connection weights, which come from output units of other networks.




Figure 20. Detail of an axo-axonic synapse. A second axon converges on the presynaptic bouton of a first axon, modulating its neurotransmitter release.

