

SMART: SMPLest-X Mesh Adaptation and RAFT Tracking for Soccer Pose Estimation

Parthsarathi Rawat
GameChanger by Dick’s Sporting Goods
sarathi.rawat@gc.com

Abstract

We present our approach to the FIFA Skeletal Tracking Challenge 2026, which requires estimating 3D world-space poses of soccer players from broadcast video. Our method fine-tunes **SMPLest-X** (ViT-H, 687 M parameters) via a stratified clip split, multi-task depth supervision, and broadcast augmentation, paired with a **RAFT** dense optical flow camera tracker, foot-plane anchoring, and two-pass temporal smoothing. Against the FIFA baseline score of 1.053 on the validation set, SMART achieves **0.647**, a **38.6%** improvement; on the held-out test set, SMART scores **0.593** (Global MPJPE: 0.324 m, Local MPJPE: 0.054 m).

1. Task Definition

Given a broadcast soccer video clip with T frames and N tracked players, the goal is to predict per-frame, per-player 3D joint positions in a shared world coordinate system. Each player is represented by a **FIFA-15 skeleton**: 15 joints comprising Nose, right/left Shoulder, Elbow, Wrist, Hip, Knee, Ankle, and Big Toe (indices 0–14). The **root joint** is the mid-hip: $\mathbf{r}_t = \frac{1}{2}(\mathbf{j}_{t,7} + \mathbf{j}_{t,8})$.

Performance is measured by two metrics (in metres): **Global MPJPE** measures mean per-joint error in absolute world coordinates, and **Local MPJPE** measures mean per-joint error after subtracting the root. The competition score is $\mathcal{L} = \text{Global MPJPE} + 5 \times \text{Local MPJPE}$, reflecting the $5\times$ higher leverage of local pose quality.

2. Data

Competition data. The benchmark provides 20 sequences from FIFA World Cup 2022 broadcast video at 50 fps and 1920×1080 resolution (6 validation, 14 test). Per-frame player bounding boxes, camera intrinsics K_t , radial distortion coefficients k_t , and an initial camera pose (R_0, t_0) are all provided by the competition; K_t varies per frame to account for continuous zoom changes in broadcast production. The baseline propagates subsequent per-frame poses (R_t, t_t)

via Lucas-Kanade sparse optical flow on 714 pre-annotated 3D pitch landmarks.

WorldPose fine-tuning data. We fine-tune on **WorldPose** [1], which pairs broadcast soccer clips with pseudo-ground-truth 3D body poses. We partition 89 clips at clip boundaries into a *stratified* split: 70 training and 19 validation clips with zero frame overlap and matched camera-height and viewing-angle distributions. No competition frames are used during training.

3. Methodology

Our pipeline has four stages: (1) SMPLest-X recovers each player’s camera-space root-relative skeleton and absolute pelvis depth from their image crop; (2) RAFT-small propagates per-frame camera rotation R_t and translation t_t from the provided (R_0, t_0) ; (3) the skeleton and pelvis depth are combined with (R_t, t_t) to place each player in the shared world coordinate system and anchor them to the pitch plane; and (4) world trajectories and root-relative joints are independently smoothed to remove detection jitter.

3.1. 3D Body Mesh Recovery

We use **SMPLest-X** [2], a regression-based expressive body mesh recovery model (ViT-H backbone, 687 M parameters) built on the **SMPL-X** body representation — a parametric model that encodes human shape and pose as low-dimensional coefficients. Each player’s bounding box is first expanded by $1.2\times$ to include contextual background, then resized to 512×384 pixels via affine transform. Given the player crop, SMPLest-X regresses SMPL-X parameters (shape β , pose θ , global orientation) and produces a full body mesh ($V=10,475$ vertices). FIFA-15 joints are read off this mesh via a fixed per-joint vertex lookup: each of the 15 competition joints maps to a designated SMPL-X surface vertex, requiring no additional learned module.

Domain-adaptive fine-tuning. Pre-trained SMPLest-X suffers a domain gap on broadcast soccer: small player size,

wide viewing angles, and partial occlusions degrade accuracy. We address this via a *stratified* clip-boundary split and a multi-task loss $\mathcal{L}_{\text{train}} = \lambda_1 \mathcal{L}_{3D} + \lambda_2 \mathcal{L}_{2D} + \lambda_3 \mathcal{L}_{\text{depth}}$, where $\mathcal{L}_{3D}$ is weighted MPJPE (extremities at $3\times$ weight), $\mathcal{L}_{2D}$ is L2 on projected keypoints, and $\mathcal{L}_{\text{depth}}$ is L1 on camera-space pelvis depth, the single most important factor for world-space grounding (see Table 2). Broadcast augmentation completes the training recipe: random resized cropping (scale $\in [0.75, 1.0]$, 80% probability), horizontal flipping (50%, with symmetric joint permutation), and colour jitter (± 0.4 brightness/contrast/saturation, ± 0.1 hue).

3.2. Camera Pose Estimation

With per-frame intrinsics K_t and distortion k_t provided, we need only propagate camera rotation $R_t \in SO(3)$ and translation $t_t \in \mathbb{R}^3$ from the initial (R_0, t_0) . We replace the competition baseline’s Lucas-Kanade sparse tracker with **RAFT-small** [3], which provides substantially more reliable correspondences on broadcast grass textures, particularly during panning and zoom. Per frame, we compute dense flow from I_{t-1} to I_t and sample it inside the convex hull of the 714 projected pitch landmarks at stride 4, yielding $\sim 50\times$ more correspondences than landmark tracking alone. Flow vectors contaminated by player motion are removed via MAD outlier rejection (3σ threshold) [4] before fitting an inter-frame homography via RANSAC and decomposing to (R_t, t_t) ; updates with $|\Delta R| > 60^\circ$ are rejected to guard against tracking failures. When field line intersections are detected via Hough transform, an EPnP (Efficient Perspective- n -Point) [5] solve further corrects absolute camera position on the first frame.

3.3. World-Space Skeleton Placement

With per-frame camera poses established, we lift each player’s camera-space skeleton into the shared world coordinate system in three steps.

(1) Rotation and initial placement. The root-relative skeleton is rotated to world frame as $\hat{\mathbf{S}}_t = R_t \mathbf{S}_t^{(\text{cam})}$. The camera-space pelvis translation $\mathbf{p}_t^{(\text{cam})}$ predicted by SMPLest-X is projected to world space as $\mathbf{p}_t = R_t \mathbf{p}_t^{(\text{cam})} + t_t$, establishing the player’s initial absolute position.

(2) Foot-plane anchoring. The lowest foot pixel in the bounding box is back-projected to a camera ray using K_t and intersected with the known pitch-plane equation, yielding ground contact point $\mathbf{f}_t$; all joints are then translated so the lower ankle aligns with $\mathbf{f}_t$:

$$\mathbf{J}_{t,j} = \hat{\mathbf{S}}_{t,j} - \hat{\mathbf{S}}_{t,\text{ankle}} + \mathbf{f}_t. \quad (1)$$

(3) Reprojection refinement. A two-stage L-BFGS optimisation (50 steps translating the skeleton centroid onto the bounding-box centre, then 50 steps aligning projected joints with 2D keypoints) refines the absolute placement.

3.4. Temporal Smoothing

Raw per-frame predictions exhibit jitter from detection noise and occasional misassociated crops under occlusion; we apply a two-pass smoothing strategy to produce clean trajectories. In the first pass, global root trajectories are cleaned: MAD outlier detection flags teleporting jumps, which are replaced by linear interpolation before a Gaussian filter removes residual high-frequency noise. In the second pass, root-relative joint offsets are smoothed independently with a narrower Gaussian to remove single-frame jitter while preserving rapid limb movements such as kicks; the world centroid is frozen during this step so the two passes do not interfere.

4. Implementation Details

Fine-tuning. Only the SMPLest-X decoder and prediction heads are trainable; the ViT-H backbone is frozen. Training: 15 epochs, batch size 16, Adam, LR 2×10^{-6} , AMP mixed precision, 1×24 GB A10G GPU. Loss weights: $\lambda_1=1.0$, $\lambda_2=0.1$, $\lambda_3=0.5$; per-joint weights 3.0 for wrists (5,6), ankles (11,12), big toes (13,14), and 1.0 otherwise.

Camera tracking. RAFT-small (default pretrained weights); stride-4 dense flow inside the 714-landmark convex hull; MAD 3σ outlier rejection; RANSAC homography (2000 iter, 1 px threshold); $|\Delta R| > 60^\circ$ rejection.

Smoothing. Global: MAD ($5\times$) + linear interp + Gaussian ($\sigma=3$ fr), clamp at 0.35 m/fr. Local joints: independent Gaussian ($\sigma=1.5$ fr).

5. Results

Main results. Table 1 compares our method against the FIFA competition baseline. Against the FIFA baseline on the validation set, our method reduces the competition score by **38.6%** ($1.053 \rightarrow 0.647$). On the held-out test set, SMART achieves **0.593**, demonstrating strong generalisation beyond the validation distribution.

Table 1. Results vs. the FIFA baseline.

Method	Global↓	Local↓	Score↓
FIFA Baseline (val)	0.602	0.090	1.053
Ours (val)	0.370	0.055	0.647
Ours (test)	0.324	0.054	0.593

5.1. Ablation: Fine-tuning Strategy

We ablate each fine-tuning design choice incrementally on the validation split. Results are shown in Table 2.

Table 2. Incremental fine-tuning ablation on the validation split. From *SMPLest-X pretrained* onward, rows use the RAFT camera tracker and foot-ray placement.

Configuration	G (m)	L (m)	Score
FIFA Baseline (SAM-3D)	0.602	0.090	1.053
SAM-3D + MLP	0.470	0.079	0.864
SMPLest-X pretrained	0.522	0.065	0.846
+ naïve fine-tune	0.425	0.079	0.820
+ foot-plane anchoring	0.381	0.067	0.714
+ improved training (ours)	0.370	0.055	0.647

FIFA Baseline (SAM-3D). The competition baseline uses SAM-3D-Body [6] as the 3D lifter, scoring 1.053 on the validation split.

SAM-3D + MLP. We augmented the baseline with a learned Placement MLP predicting absolute hip position from camera geometry and foot-ray features (the ray cast from the camera through the player’s lowest visible foot pixel to the pitch plane), reducing the score to 0.864 (global: 0.470 m, local: 0.079 m). The MLP generalises poorly across the range of camera heights in the competition sequences, motivating a switch to SMPLest-X.

SMPLest-X pretrained. Off-the-shelf SMPLest-X ViT-H (no domain adaptation) achieves score 0.846 (global: 0.522 m, local: 0.065 m). The domain gap with broadcast soccer video limits out-of-the-box effectiveness, motivating domain-specific fine-tuning.

+ Naïve fine-tuning. A chronological split with standard 3D MPJPE loss improves global MPJPE to 0.425 m (score: 0.820), but local MPJPE *worsens* from 0.065 to 0.079 m: adjacent clips share nearly identical camera angles, so the model overfits training-set viewpoints at the cost of held-out local accuracy.

+ Foot-plane anchoring. Without explicit pitch-plane constraints, skeletons float at arbitrary height, inflating both global and local error. Ray-casting the lowest foot pixel to the pitch plane reduces global MPJPE by 44 mm and local MPJPE by 12 mm (score: 0.820→0.714), confirming that grounding improves both absolute placement and root-relative scale.

+ Improved training (ours). Our full strategy adds (i) stratified clip-boundary split, (ii) depth supervision $\mathcal{L}_{\text{depth}}$, and (iii) broadcast augmentation, yielding local 0.055 m and global 0.370 m for a final score of 0.647. Depth supervision is the dominant factor: without it, local MPJPE stagnates at 0.067 m regardless of augmentation.

5.2. Ablation: Camera Tracker

We compared optical flow methods for camera pose propagation, measuring rotation error against ground-truth camera poses on our WorldPose validation split (19 clips; Table 3). ECC homography (0.107°) performs worst: soccer frames

Table 3. Camera tracker ablation. Rotation error (°) vs. GT camera poses on our WorldPose validation split (19 clips).

Tracker	Rot. Err (°)↓	ms/frame
ECC homography	0.107	—
Lucas-Kanade (baseline)	0.043	—
RAFT-small, no filter	0.043	55
RAFT-small + MAD (ours)	0.041	55
RAFT-large + MAD	0.041	110

contain many moving players that occupy a large fraction of the image, and ECC has no mechanism to ignore them, so their motion corrupts the background homography estimate causing systematic drift. Lucas-Kanade sparse tracking (0.043°) handles this via RANSAC inlier rejection of player-located feature points. RAFT-small without filtering ties Lucas-Kanade, as dense flow over player silhouettes introduces noise that cancels the correspondence benefit; adding MAD outlier filtering removes contaminated pixels and reduces error to 0.041°. RAFT-large provides no further gain at double the compute, so we adopt RAFT-small with MAD outlier filtering.

5.3. Ablation: Temporal Refiner

We trained a sliding-window temporal refinement network (27-frame window, hidden dim 128) on WorldPose to suppress per-frame jitter. While it reduces local MPJPE by 22% on our WorldPose validation split, competition performance degrades (score 0.680 vs. 0.647) as the refiner over-smooths fast actions not well-represented in its training distribution. We therefore use only Gaussian smoothing in our final submission.

6. Discussion

Global vs. local error. Global MPJPE contributes ~55% of our total competition score, making camera tracking the primary bottleneck. Sequences with aggressive zoom cause apparent pitch-plane deformation that confounds the homography model, raising global error by up to 2× compared to stable wide-angle shots. In contrast, local MPJPE is largely camera-independent once the fine-tuned lifter is in place.

Limitations. (i) Diving poses are underrepresented in WorldPose; SMPLest-X struggles with extreme configurations, and foot-plane anchoring breaks when the player is airborne. (ii) SMPLest-X is per-frame only, making it fragile under occlusion; a temporally-aware lifter would handle occluded frames more robustly. (iii) The 687 M ViT-H backbone dominates inference cost; ViT-S could yield a 4× speedup with modest accuracy loss.

References

- [1] Tianjian Jiang, Johsan Billingham, Sebastian Müksch, Juan Zarate, Nicolas Evans, Martin Oswald, Marc Pollefeys, Otmar Hilliges, Manuel Kaufmann, and Jie Song. WorldPose: A world cup dataset for global 3D human pose estimation. In *ECCV*, 2024. [1](#)
- [2] Wanqi Yin, Zhongang Cai, Ruisi Wang, Ailing Zeng, Chen Wei, Qingping Sun, Haiyi Mei, Yanjun Wang, Hui En Pang, Mingyuan Zhang, Lei Zhang, Chen Change Loy, Atsushi Yamashita, Lei Yang, and Ziwei Liu. SMPLeSt-X: Ultimate scaling for expressive human pose and shape estimation. *IEEE TPAMI*, 48(2):1778–1794, 2026. [1](#)
- [3] Zachary Teed and Jia Deng. RAFT: Recurrent all-pairs field transforms for optical flow, 2020. [2](#)
- [4] Christophe Leys, Christophe Ley, Olivier Klein, Philippe Bernard, and Laurent Licata. Detecting outliers: Do not use standard deviation around the mean, use absolute deviation around the median. *Journal of Experimental Social Psychology*, 49(4):764–766, 2013. [2](#)
- [5] Vincent Lepetit, Francesc Moreno-Noguer, and Pascal Fua. EPnP: An accurate $O(n)$ solution to the PnP problem. *IJCV*, 81(2):155–166, 2009. [2](#)
- [6] Xitong Yang, Devansh Kukreja, Don Pinkus, Anushka Sagar, Taosha Fan, Jinhyung Park, Soyong Shin, Jinkun Cao, Jiawei Liu, Nicolas Ugrinovic, Matt Feiszli, Jitendra Malik, Piotr Dollar, and Kris Kitani. SAM 3D body: Robust full-body human mesh recovery. *arXiv preprint arXiv:2602.15989*, 2026. [3](#)